

# Safety Data Sheet

## SO-SURE General Purpose Enamel

SDS Revision Date:

08/23/2018



### 1. Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

<b>Product Identity</b>	SO-SURE General Purpose Enamel
<b>Alternate Names</b>	Red 11136 LHB Part Number: 01D4-110 National Stock Number: 8010-01-505-1971 CAGE Code: 0FTT5 Contract Number: SPE8EG-16-D-0015

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

<b>Intended use</b>	See product label.
<b>Application Method</b>	See product label.

#### 1.3. Details of the supplier of the safety data sheet

<b>Company Name</b>	LHB Industries 8833 Fleischer Place Berkeley, MO 63134
---------------------	--

#### Emergency

<b>24 hour Emergency Telephone No.</b>	(800) 633-8253 (PERS)
<b>Customer Service: LHB Industries</b>	(314) 423-4333

### 2. Hazard identification of the product

#### 2.1. Classification of the substance or mixture

Flam. Aerosol 1;H222	Extremely flammable aerosol.
Press. Gas;H280	Contains gas under pressure; may explode if heated.
Acute Tox. 5;H303	May be harmful if swallowed. (Not adopted by US OSHA)
Acute Tox. 5;H313	May be harmful in contact with skin. (Not adopted by US OSHA)
Acute Tox. 4;H332	Harmful if inhaled.
Skin Irrit. 3;H316	Causes mild skin irritation. (Not adopted by US OSHA)
Eye Irrit. 2;H319	Causes serious eye irritation.
STOT SE 3;H336	May cause drowsiness or dizziness.

# Safety Data Sheet

## SO-SURE General Purpose Enamel

SDS Revision Date:

08/23/2018



### 2.2. Label elements

Using the Toxicity Data listed in section 11 and 12 the product is labeled as follows.



**Danger**

- H222 Extremely flammable aerosol.
- H280 Contains gas under pressure; may explode if heated.
- H303 May be harmful if swallowed.
- H313 May be harmful in contact with skin.
- H316 Causes mild skin irritation.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.

#### **[Prevention]:**

- P210 Keep away from heat / sparks / open flames / hot surfaces - No smoking.
- P261 Avoid breathing dust / fume / gas / mist / vapors / spray.
- P264 Wash thoroughly after handling.
- P271 Use only outdoors or in a well-ventilated area.
- P280 Wear protective gloves / eye protection / face protection.

#### **[Response]:**

- P304+312 IF INHALED: Call a POISON CENTER or doctor / physician if you feel unwell.
- P305+351+338 IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing.
- P332+313 If skin irritation occurs: Get medical advice / attention.
- P337+313 If eye irritation persists: Get medical advice / attention.
- P340 Remove victim to fresh air and keep at rest in a position comfortable for breathing.
- P377 Leaking gas fire - do not extinguish unless leak can be stopped safely.
- P381 Eliminate all ignition sources if safe to do so.

#### **[Storage]:**

- P410+403 Protect from sunlight. Store in a well ventilated place.

# Safety Data Sheet

## SO-SURE General Purpose Enamel

SDS Revision Date:

08/23/2018



**[Disposal]:**

No GHS disposal statements

### 3. Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of the relevant State and Federal Hazardous Substances regulations.

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
Petroleum gases, liquefied, sweetened CAS Number: 0068476-86-8	25 - 50	Press. Gas;H280 Flam. Gas 1;H220	[1]
Acetone CAS Number: 0000067-64-1	10 - 25	Flam. Liq. 2;H225 Eye Irrit. 2;H319 STOT SE 3;H336	[1][2]
N-Butyl Acetate CAS Number: 0000123-86-4	10 - 25	Flam. Liq. 3;H226 STOT SE 3;H336	[1][2]
Methyl Isoamyl Ketone CAS Number: 0000110-12-3	1.0 - 10	Flam. Liq. 3;H226 Acute Tox. 4;H332	[1][2]
Butan-1-ol CAS Number: 0000071-36-3	1.0 - 10	Flam. Liq. 3;H226 Acute Tox. 4;H302 STOT SE 3;H335 Skin Irrit. 2;H315 Eye Dam. 1;H318 STOT SE 3;H336	[1][2]
Methyl Propyl Ketone CAS Number: 0000107-87-9	1.0 - 10	Flam. Liq. 2;H225 Acute Tox. 4;H302 Eye Irrit. 2;H319 STOT SE 3;H335 Skin Irrit. 2;H315	[1][2]
iso-Butyl acetate CAS Number: 0000110-19-0	1.0 - 10	Flam. Liq. 2;H225	[1][2]
Methyl Amyl Ketone CAS Number: 0000110-43-0	1.0 - 10	Flam. Liq. 3;H226 Acute Tox. 4;H332 Acute Tox. 4;H302	[1][2]
Diacetone Alcohol CAS Number: 0000123-42-2	1.0 - 10	Eye Irrit. 2;H319	[1][2]

[1] Substance classified with a health or environmental hazard.

[2] Substance with a workplace exposure limit.

[3] PBT-substance or vPvB-substance.

\*The full texts of the phrases are shown in Section 16.

### 4. First aid measures

# Safety Data Sheet

## SO-SURE General Purpose Enamel

SDS Revision Date:

08/23/2018



### 4.1. Description of first aid measures

<b>General</b>	Move victim to fresh air. Call 911 or emergency medical service if deemed necessary. Give artificial respiration if victim is not breathing. Administer oxygen if breathing is difficult. Remove and isolate contaminated clothing and shoes. In case of contact with liquefied gas, thaw frosted parts with lukewarm water. Keep victim warm and quiet. Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves.
<b>Inhalation</b>	Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, give artificial respiration. If unconscious place in the recovery position and obtain immediate medical attention. Give nothing by mouth.
<b>Eyes</b>	Irrigate copiously with clean water for at least 15 minutes, holding the eyelids apart and seek medical attention.
<b>Skin</b>	Remove and isolate contaminated clothing and shoes. Clothing frozen to the skin should be thawed before being removed. In case of contact with liquefied gas, thaw frosted parts with lukewarm water.
<b>Ingestion</b>	If swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

### 4.2. Most important symptoms and effects, both acute and delayed

<b>Overview</b>	No specific symptom data available. Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.  Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage. See section 2 for further details.
<b>Inhalation</b>	Harmful if inhaled. May cause drowsiness or dizziness.
<b>Eyes</b>	Causes serious eye irritation.
<b>Skin</b>	May be harmful in contact with skin. (Not adopted by US OSHA) Causes mild skin irritation. (Not adopted by US OSHA)
<b>Ingestion</b>	May be harmful if swallowed. (Not adopted by US OSHA)

## 5. Fire-fighting measures

### 5.1. Extinguishing media

# Safety Data Sheet

## SO-SURE General Purpose Enamel

SDS Revision Date:

08/23/2018



Carbon Dioxide, Dry Chemical, Foam

### 5.2. Special hazards arising from the substance or mixture

Hazardous decomposition: No hazardous decomposition data available.

Keep away from heat / sparks / open flames / hot surfaces - No smoking.

Avoid breathing dust / fume / gas / mist / vapors / spray.

### 5.3. Advice for fire-fighters

Wear positive pressure self-contained breathing apparatus (SCBA).

Wear chemical protective clothing that is specifically recommended by the manufacturer. It may provide little or no thermal protection.

Structural firefighters' protective clothing will only provide limited protection.

Some may burn but none ignite readily.

Containers may explode when heated.

Ruptured cylinders may rocket.

Vapors may cause dizziness or asphyxiation without warning.

Vapors from liquefied gas are initially heavier than air and spread along ground.

Contact with gas or liquefied gas may cause burns, severe injury and/or frostbite.

Fire may produce irritating, corrosive and/or toxic gases.

**ERG Guide No.** 126

## 6. Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Do not touch or walk through spilled material.

Stop leak if you can do it without risk.

Do not direct water at spill or source of leak.

Use water spray to reduce vapors or divert vapor cloud drift. Avoid allowing water runoff to contact spilled material.

If possible, turn leaking containers so that gas escapes rather than liquid.

Prevent entry into waterways, sewers, basements or confined areas.

Allow substance to evaporate.

Ventilate the area.

### 6.2. Environmental precautions

Do not allow spills to enter drains or waterways.

Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

### 6.3. Methods and material for containment and cleaning up

Stay upwind.

Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks).

**Safety Data Sheet**  
**SO-SURE General Purpose Enamel**

SDS Revision Date:

08/23/2018



Keep out of low areas.  
Ventilate closed spaces before entering.

# Safety Data Sheet

## SO-SURE General Purpose Enamel

SDS Revision Date:

08/23/2018



### 7. Handling and storage

#### 7.1. Precautions for safe handling

Store in accordance with the National Fire Protection Association's publication NFPA 30, Flammable and Combustible Liquids Code. 29 CFR 1910.106 applies to the handling, storage, and use of flammable and combustible liquids.

See section 2 for further details. - [Prevention]:

#### 7.2. Conditions for safe storage, including any incompatibilities

Handle containers carefully to prevent damage and spillage.

Store this product below 120°F, in a cool, dry, well ventilated area away from heat, sparks, flame, oxidizers and out of direct sunlight.

Incompatible materials: Strong Oxidizing Agents, Strong Acids and Alkalis.

See section 2 for further details. - [Storage]:

#### 7.3. Specific end use(s)

No data available.

### 8. Exposure controls and personal protection

#### 8.1. Control parameters

CAS No.	Ingredient	Exposure	
		Source	Value
0000067-64-1	Acetone	OSHA	TWA 1000 ppm (2400 mg/m <sup>3</sup> ) STEL 2400 mg/m <sup>3</sup>
		ACGIH	TWA: 250 ppm STEL: 500 ppm Skin
		NIOSH	250 ppm (590 mg/m <sup>3</sup> ) TWA
		Supplier	No Established Limit
0000071-36-3	Butan-1-ol	OSHA	TWA 100 ppm (300 mg/m <sup>3</sup> )
		ACGIH	TWA: 15 ppm Ceiling: 30 ppm
		NIOSH	C 50 ppm (150 mg/m <sup>3</sup> ) [skin]
		Supplier	No Established Limit
0000107-87-9	Methyl Propyl Ketone	OSHA	TWA 200 ppm (700 mg/m <sup>3</sup> )
		ACGIH	TWA: 150 ppm STEL: 250 ppm
		NIOSH	TWA 150 ppm (530 mg/m <sup>3</sup> )
		Supplier	No Established Limit
0000110-12-3	Methyl Isoamyl Ketone	OSHA	TWA 100 ppm (475 mg/m <sup>3</sup> )
		ACGIH	TWA: 50 ppm
		NIOSH	TWA 50 ppm (240 mg/m <sup>3</sup> )

# Safety Data Sheet

## SO-SURE General Purpose Enamel

SDS Revision Date:

08/23/2018



CAS No.	Ingredient	Source	Value
0000110-19-0	iso-Butyl acetate	Supplier	No Established Limit
		OSHA	TWA 150 ppm (700 mg/m <sup>3</sup> )
		ACGIH	TWA: 150 ppm
		NIOSH	TWA 150 ppm (700 mg/m <sup>3</sup> )
0000110-43-0	Methyl Amyl Ketone	Supplier	No Established Limit
		OSHA	TWA 100 ppm (465 mg/m <sup>3</sup> )
		ACGIH	TWA: 50 ppm
		NIOSH	TWA 100 ppm (465 mg/m <sup>3</sup> )
0000123-42-2	Diacetone Alcohol	Supplier	No Established Limit
		OSHA	TWA 50 ppm (240 mg/m <sup>3</sup> )
		ACGIH	TWA: 50 ppm
		NIOSH	TWA 50 ppm (240 mg/m <sup>3</sup> )
0000123-86-4	N-Butyl Acetate	Supplier	No Established Limit
		OSHA	TWA 150 ppm (710 mg/m <sup>3</sup> )
		ACGIH	TWA: 20 ppmS
		NIOSH	TWA 150 ppm (710 mg/m <sup>3</sup> ) ST 200 ppm (950 mg/m <sup>3</sup> )
0068476-86-8	Petroleum gases, liquefied, sweetened	Supplier	No Established Limit
		OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit

### Carcinogen Data

CAS No.	Ingredient	Source	Value
0000067-64-1	Acetone	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0000071-36-3	Butan-1-ol	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0000107-87-9	Methyl Propyl Ketone	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0000110-12-3	Methyl Isoamyl Ketone	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0000110-19-0	iso-Butyl acetate	OSHA	Select Carcinogen: No



# Safety Data Sheet

## SO-SURE General Purpose Enamel

SDS Revision Date:

08/23/2018



		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0000110-43-0	Methyl Amyl Ketone	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0000123-42-2	Diacetone Alcohol	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0000123-86-4	N-Butyl Acetate	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0068476-86-8	Petroleum gases, liquefied, sweetened	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;

### 8.2. Exposure controls

#### Respiratory

If workers are exposed to concentrations above the exposure limit they must use the appropriate, certified respirators.

#### Eyes

Wear safety eyewear, e.g. safety spectacles, goggles or visors to protect against the splash of liquids.

#### Skin

Overalls which cover the body, arms and legs should be worn. Skin should not be exposed. All parts of the body should be washed after contact.

#### Engineering Controls

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and any vapor below occupational exposure limits suitable respiratory protection must be worn.

#### Other Work Practices

Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

See section 2 for further details. - [Prevention]:

## 9. Physical and chemical properties

**Appearance**

Red Liquid/Gas

**Odor**

Solvent

**Odor threshold**

Not Measured

**pH**

Not Measured

# Safety Data Sheet

## SO-SURE General Purpose Enamel

SDS Revision Date:

08/23/2018



Melting point / freezing point	Not Measured
Initial boiling point and boiling range	Not Measured
Flash Point	Propellant < 0 F
Evaporation rate (Ether = 1)	Slower than ether
Flammability (solid, gas)	Flam. Aerosol 1;H222 Extremely flammable aerosol.
Upper/lower flammability or explosive limits	<b>Lower Explosive Limit:</b> 1.1 <b>Upper Explosive Limit:</b> 12.8
Vapor pressure (Pa)	Not Measured
Vapor Density	Heavier than Air
Specific Gravity	0.762 (6.35 lb/gal)
Solubility in Water	Insoluble
Partition coefficient n-octanol/water (Log Kow)	Not Measured
Auto-ignition temperature	Not Measured
Decomposition temperature	Not Measured
Viscosity (cSt)	Not Measured
VOC	56.5% by wt., (4.59 lb/gal), (549 g/l), less water and exempt solvents
Maximum Incremental Reactivity	0.62
HAPS (lbs/gal)	0.0
HAPS (lbs/gal of Solids)	0.0
HAPS (lbs/lb of Solids)	0.0
% Volatile (by volume)	89.4% (by volume)
<b>9.2. Other information</b>	
No other relevant information.	

## 10. Stability and reactivity

### 10.1. Reactivity

Hazardous Polymerization will not occur.

### 10.2. Chemical stability

Stable under normal circumstances.

### 10.3. Possibility of hazardous reactions

No data available.

### 10.4. Conditions to avoid

Avoid contact with open flame, sparks or hot surfaces.

### 10.5. Incompatible materials

Strong Oxidizing Agents, Strong Acids and Alkalis.

# Safety Data Sheet

## SO-SURE General Purpose Enamel

SDS Revision Date:

08/23/2018



### 10.6. Hazardous decomposition products

No hazardous decomposition data available.

## 11. Toxicological information

### Acute toxicity

Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage.

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LD50, mg/L/4hr	Inhalation Dust/Mist LD50, mg/L/4hr	Inhalation Gas LD50, ppm
Petroleum gases, liquefied, sweetened - (68476-86-8)	No data available	No data available	No data available	No data available	No data available
Acetone - (67-64-1)	2,000.00, Rat - Category: 4	2,000.00, Rabbit - Category: 4	76.00, Rat - Category: NA	No data available	No data available
N-Butyl Acetate - (123-86-4)	10,700.00, Rat - Category: NA	17,600.00, Rabbit - Category: NA	No data available	No data available	No data available
Methyl Isoamyl Ketone - (110-12-3)	3,200.00, Rat - Category: 5	8,110.00, Rabbit - Category: NA	No data available	No data available	No data available
Butan-1-ol - (71-36-3)	2,292.00, Rat - Category: 5	3,430.00, Rabbit - Category: 5	No data available	No data available	8,000.00, Rat - Category: 4
Methyl Propyl Ketone - (107-87-9)	1,600.00, Rat - Category: 4	6,500.00, Rabbit - Category: NA	No data available	No data available	No data available
iso-Butyl acetate - (110-19-0)	13,400.00, Rat - Category: NA	17,400.00, Rabbit - Category: NA	No data available	No data available	No data available
Methyl Amyl Ketone - (110-43-0)	1,670.00, Rat - Category: 4	12,600.00, Rabbit - Category: NA	No data available	No data available	No data available
Diacetone Alcohol - (123-42-2)	2,520.00, Rat - Category: 5	13,500.00, Rabbit - Category: NA	No data available	No data available	1,500.00, Rat - Category: NA

# Safety Data Sheet

## SO-SURE General Purpose Enamel

SDS Revision Date:

08/23/2018



Note: When no route specific LD50 data is available for an acute toxin, the converted acute toxicity point estimate was used in the calculation of the product's ATE (Acute Toxicity Estimate).

Classification	Category	Hazard Description
Acute toxicity (oral)	5	May be harmful if swallowed. (Not adopted by US OSHA)
Acute toxicity (dermal)	5	May be harmful in contact with skin. (Not adopted by US OSHA)
Acute toxicity (inhalation)	4	Harmful if inhaled.
Skin corrosion/irritation	3	Causes mild skin irritation. (Not adopted by US OSHA)
Serious eye damage/irritation	2	Causes serious eye irritation.
Respiratory sensitization	---	Not Applicable
Skin sensitization	---	Not Applicable
Germ cell mutagenicity	---	Not Applicable
Carcinogenicity	---	Not Applicable
Reproductive toxicity	---	Not Applicable
STOT-single exposure	3	May cause drowsiness or dizziness.
STOT-repeated exposure	---	Not Applicable
Aspiration hazard	---	Not Applicable

## 12. Ecological information

### 12.1. Toxicity

#### Aquatic Ecotoxicity

Ingredient	96 hr LC50 fish, mg/l	48 hr EC50 crustacea, mg/l	ErC50 algae, mg/l
Petroleum gases, liquefied, sweetened - (68476-86-8)	Not Available	Not Available	Not Available
Acetone - (67-64-1)	100.00, Pimephales promelas	10.00, Daphnia magna	20.565 (72 hr), Ulva pertusa
N-Butyl Acetate - (123-86-4)	18.00, Pimephales promelas	32.00, Artemia salina	674.70 (72 hr), Scenedesmus subspicatus
Methyl Isoamyl Ketone - (110-12-3)	159.00, Pimephales promelas	560.00, Daphnia magna	920.00 (72 hr), Chlorococcales

# Safety Data Sheet

## SO-SURE General Purpose Enamel

SDS Revision Date:

08/23/2018



Butan-1-ol - (71-36-3)	1,376.00, Pimephales promelas	1,328.00, Daphnia magna	500.00 (96 hr), Scenedesmus subspicatus
Methyl Propyl Ketone - (107-87-9)	1,240.00, Pimephales promelas	Not Available	0.00 (96 hr),
iso-Butyl acetate - (110-19-0)	101.00, Leuciscus idus	250.00, Daphnia magna	600.00 (24 hr), Chlorococcales
Methyl Amyl Ketone - (110-43-0)	131.00, Pimephales promelas	Not Available	Not Available
Diacetone Alcohol - (123-42-2)	420.00, Lepomis macrochirus	9,000.00, Daphnia magna	Not Available

### 12.2. Persistence and degradability

There is no data available on the preparation itself.

### 12.3. Bioaccumulative potential

Not Measured

### 12.4. Mobility in soil

No data available.

### 12.5. Results of PBT and vPvB assessment

This product contains no PBT/vPvB chemicals.

### 12.6. Other adverse effects

No data available.

## 13. Disposal considerations

### 13.1. Waste treatment methods

Do not allow into drains or water courses. Wastes and emptied containers should be disposed of in accordance with regulations made under the Control of Pollution Act and the Environmental Protection Act.

Using information provided in this data sheet advice should be obtained from the Waste Regulation Authority, whether the special waste regulations apply.

## 14. Transport information

	<b>DOT (Domestic Surface Transportation)</b>	<b>IMO / IMDG (Ocean Transportation)</b>	<b>ICAO/IATA</b>
<b>14.1. UN number</b>	UN1950	UN1950	UN1950
<b>14.2. UN proper shipping name</b>	UN1950, Aerosols, Limited Quantity, 2.1,	Aerosols, Limited Quantity	Aerosols, Limited Quantity

# Safety Data Sheet

## SO-SURE General Purpose Enamel

SDS Revision Date:

08/23/2018



<b>14.3. Transport hazard class(es)</b>	<b>DOT Hazard Class:</b> 2.1	<b>IMDG:</b> 2.1	<b>Air Class:</b> 2.1
<b>14.4. Packing group</b>	Not Applicable	Not Applicable	Not Applicable
<b>14.5. Environmental hazards</b>			
<b>IMDG</b>	Marine Pollutant: No		
<b>14.6. Special precautions for user</b>			
No further information			

### 15. Regulatory information

<b>Regulatory Overview</b>	The regulatory data in Section 15 is not intended to be all-inclusive, only selected regulations are represented.
<b>Toxic Substance Control Act (TSCA)</b>	All components of this material are either listed or exempt from listing on the TSCA Inventory.
<b>WHMIS Classification</b>	A B1 D2B
<b>US EPA Tier II Hazards</b>	<b>Fire:</b> Yes <b>Sudden Release of Pressure:</b> Yes <b>Reactive:</b> No <b>Immediate (Acute):</b> Yes <b>Delayed (Chronic):</b> No

#### EPCRA 311/312 Chemicals and RQs (lbs):

Acetone ( 5,000.00)  
Butan-1-ol ( 5,000.00)  
iso-Butyl acetate ( 5,000.00)  
N-Butyl Acetate ( 5,000.00)

**EPCRA 302 Extremely Hazardous :**  
(No Product Ingredients Listed)

#### EPCRA 313 Toxic Chemicals:

Butan-1-ol

**Proposition 65 - Carcinogens (>0.0%):**  
(No Product Ingredients Listed)

**Proposition 65 - Developmental Toxins (>0.0%):**  
(No Product Ingredients Listed)

**Proposition 65 - Female Repro Toxins (>0.0%):**  
(No Product Ingredients Listed)

**Proposition 65 - Male Repro Toxins (>0.0%):**  
(No Product Ingredients Listed)

# Safety Data Sheet

## SO-SURE General Purpose Enamel

SDS Revision Date:

08/23/2018



### N.J. RTK Substances (>1%):

Diacetone Alcohol  
Methyl Isoamyl Ketone  
Acetone  
Butan-1-ol  
Methyl Amyl Ketone  
iso-Butyl acetate  
N-Butyl Acetate  
Methyl Propyl Ketone

### Penn RTK Substances (>1%):

Diacetone Alcohol  
Methyl Isoamyl Ketone  
Acetone  
Butan-1-ol  
Methyl Amyl Ketone  
iso-Butyl acetate  
N-Butyl Acetate  
Methyl Propyl Ketone

## 16. Other information

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapor.

H226 Flammable liquid and vapor.

H280 Contains gas under pressure; may explode if heated.

H302 Harmful if swallowed.

H315 Causes skin irritation.

**Safety Data Sheet**  
**SO-SURE General Purpose Enamel**

SDS Revision Date:

08/23/2018



- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness and dizziness.

IMPORTANT NOTE: This information is furnished without warranty, expressed or implied, as to accuracy or completeness. The information is obtained from various sources including the manufacturer and other third party sources. The information may not be valid under all conditions nor if this material is used in combination with other materials or any process. Final determination of suitability of any material is the sole responsibility of the user.

End of Document