

# Safety Data Sheet

## ECO-SURE Industrial Enamel Aerosol Paint

SDS Revision Date:

07/05/2018



### 1. Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

**Product Identity**

ECO-SURE Industrial Enamel Aerosol Paint

**Alternate Names**

Specification: A-A-2787 Type I, Gloss Red 11136  
LHB Part Number: 0674-111  
National Stock Number: 8010-01-331-6109  
CAGE Code: 0FTT5  
Contract Number: SPE8EG-16-D-0015

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Intended use**

See product label.

**Application Method**

See product label.

#### 1.3. Details of the supplier of the safety data sheet

**Company Name**

LHB Industries  
8833 Fleischer Place  
Berkeley, MO 63134

**Emergency**

**24 hour Emergency Telephone No.**

(800) 633-8253 (PERS)

**Customer Service: LHB Industries**

(314) 423-4333

### 2. Hazard identification of the product

#### 2.1. Classification of the substance or mixture

Flam. Aerosol 1;H222

Extremely flammable aerosol.

Press. Gas;H280

Contains gas under pressure; may explode if heated.

Acute Tox. 5;H303

May be harmful if swallowed. (Not adopted by US OSHA)

Skin Irrit. 3;H316

Causes mild skin irritation. (Not adopted by US OSHA)

Eye Dam. 1;H318

Causes serious eye damage.

STOT SE 3;H336

May cause drowsiness or dizziness.

# Safety Data Sheet

## ECO-SURE Industrial Enamel Aerosol Paint

SDS Revision Date:

07/05/2018



### 2.2. Label elements

Using the Toxicity Data listed in section 11 and 12 the product is labeled as follows.



**Danger**

H222 Extremely flammable aerosol.

H280 Contains gas under pressure; may explode if heated.

H303 May be harmful if swallowed.

H316 Causes mild skin irritation.

H318 Causes serious eye damage.

H336 May cause drowsiness and dizziness.

#### **[Prevention]:**

P210 Keep away from heat / sparks / open flames / hot surfaces - No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Pressurized container: Do not pierce or burn, even after use.

P261 Avoid breathing dust / fume / gas / mist / vapors / spray.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves / eye protection / face protection.

#### **[Response]:**

P304+312 IF INHALED: Call a POISON CENTER or doctor / physician if you feel unwell.

P305+351+338 IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing.

P310 Immediately call a POISON CENTER or doctor / physician.

P332+313 If skin irritation occurs: Get medical advice / attention.

P340 Remove victim to fresh air and keep at rest in a position comfortable for breathing.

#### **[Storage]:**

P403+233 Store in a well ventilated place. Keep container tightly closed.

P405 Store locked up.

P410+412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C / 122 °F.

#### **[Disposal]:**

P501 Dispose of contents / container in accordance with local / national regulations.

# Safety Data Sheet

## ECO-SURE Industrial Enamel Aerosol Paint

SDS Revision Date:

07/05/2018



### 3. Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of the relevant State and Federal Hazardous Substances regulations.

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
2-Propanone CAS Number: 0000067-64-1	10 - 25	Flam. Liq. 2;H225 Eye Irrit. 2;H319 STOT SE 3;H336	[1][2]
Propane CAS Number: 0000074-98-6	10 - 25	Flam. Gas 1;H220 Press. Gas;H280	[1][2]
N-Butyl Acetate CAS Number: 0000123-86-4	10 - 25	Flam. Liq. 3;H226 STOT SE 3;H336	[1][2]
Butane CAS Number: 0000106-97-8	1.0 - 10	Flam. Gas 1;H220 Press. Gas;H280	[1][2]
Propane, 2-methyl- CAS Number: 0000075-28-5	1.0 - 10	Flam. Gas 1;H220 Press. Gas;H280	[1][2]
5-Methyl-2-hexanone CAS Number: 0000110-12-3	1.0 - 10	Flam. Liq. 3;H226 Acute Tox. 4;H332	[1][2]
Butan-1-ol CAS Number: 0000071-36-3	1.0 - 10	Flam. Liq. 3;H226 Acute Tox. 4;H302 STOT SE 3;H335 Skin Irrit. 2;H315 Eye Dam. 1;H318 STOT SE 3;H336	[1][2]
Pentan-2-one CAS Number: 0000107-87-9	1.0 - 10	Flam. Liq. 2;H225 Acute Tox. 4;H302 Eye Irrit. 2;H319 STOT SE 3;H335 Skin Irrit. 2;H315	[1][2]
iso-Butyl acetate. CAS Number: 0000110-19-0	1.0 - 10	Flam. Liq. 2;H225	[1][2]
4-Hydroxy-4-Methylpentan-2-one CAS Number: 0000123-42-2	1.0 - 10	Eye Irrit. 2;H319	[1][2]

[1] Substance classified with a health or environmental hazard.

[2] Substance with a workplace exposure limit.

[3] PBT-substance or vPvB-substance.

\*The full texts of the phrases are shown in Section 16.

# Safety Data Sheet

## ECO-SURE Industrial Enamel Aerosol Paint

SDS Revision Date:

07/05/2018



### 4. First aid measures

#### 4.1. Description of first aid measures

##### General

Move victim to fresh air.  
Call 911 or emergency medical service if deemed necessary.  
Give artificial respiration if victim is not breathing.  
Administer oxygen if breathing is difficult.  
Remove and isolate contaminated clothing and shoes.  
In case of contact with liquefied gas, thaw frosted parts with lukewarm water.  
Keep victim warm and quiet.  
Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves.

##### Inhalation

Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, give artificial respiration. If unconscious place in the recovery position and obtain immediate medical attention. Give nothing by mouth.

##### Eyes

Irrigate copiously with clean fresh water for at least 15 minutes, holding the eyelids apart and seek medical attention.

##### Skin

Remove and isolate contaminated clothing and shoes. Clothing frozen to the skin should be thawed before being removed. In case of contact with liquefied gas, thaw frosted parts with lukewarm water.

##### Ingestion

If accidentally swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

#### 4.2. Most important symptoms and effects, both acute and delayed

##### Overview

Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage. See section 2 for further details.

##### Inhalation

May cause drowsiness or dizziness.

##### Eyes

Causes serious eye damage.

##### Skin

Causes mild skin irritation. (Not adopted by US OSHA)

##### Ingestion

May be harmful if swallowed. (Not adopted by US OSHA)

# Safety Data Sheet

## ECO-SURE Industrial Enamel Aerosol Paint

SDS Revision Date:

07/05/2018



### 5. Fire-fighting measures

#### 5.1. Extinguishing media

**Fire involving Tanks:** Some of these materials, if spilled, may evaporate leaving a flammable residue. Some of these materials, if spilled, may evaporate leaving a flammable residue.

#### 5.2. Special hazards arising from the substance or mixture

Carbon Monoxide and Carbon Dioxide

Keep away from heat / sparks / open flames / hot surfaces - No smoking.

Do not spray on an open flame or other ignition source.

Pressurized container: Do not pierce or burn, even after use.

Avoid breathing dust / fume / gas / mist / vapors / spray.

#### 5.3. Advice for fire-fighters

Wear positive pressure self-contained breathing apparatus (SCBA).

Wear chemical protective clothing that is specifically recommended by the manufacturer. It may provide little or no thermal protection.

Structural firefighters' protective clothing will only provide limited protection.

Some may burn but none ignite readily.

Containers may explode when heated.

Ruptured cylinders may rocket.

Vapors may cause dizziness or asphyxiation without warning.

Vapors from liquefied gas are initially heavier than air and spread along ground.

Contact with gas or liquefied gas may cause burns, severe injury and/or frostbite.

Fire may produce irritating, corrosive and/or toxic gases.

**ERG Guide No.** 126

### 6. Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

Do not touch or walk through spilled material.

Stop leak if you can do it without risk.

Do not direct water at spill or source of leak.

Use water spray to reduce vapors or divert vapor cloud drift. Avoid allowing water runoff to contact spilled material.

If possible, turn leaking containers so that gas escapes rather than liquid.

Prevent entry into waterways, sewers, basements or confined areas.

Allow substance to evaporate.

Ventilate the area.

#### 6.2. Environmental precautions

Do not allow spills to enter drains or watercourses.

Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove

# Safety Data Sheet

## ECO-SURE Industrial Enamel Aerosol Paint

SDS Revision Date:

07/05/2018



soiled clothing and wash thoroughly before reuse.

### 6.3. Methods and material for containment and cleaning up

As an immediate precautionary measure, isolate spill or leak area for at least 100 meters (330 feet) in all directions.

Keep unauthorized personnel away.

Stay upwind.

Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks).

Keep out of low areas.

Ventilate closed spaces before entering.

## 7. Handling and storage

### 7.1. Precautions for safe handling

Store in accordance with the National Fire Protection Association's publication NFPA 30, Flammable and Combustible Liquids Code. 29 CFR 1910.106 applies to the handling, storage, and use of flammable and combustible liquids.

See section 2 for further details. - [Prevention]:

### 7.2. Conditions for safe storage, including any incompatibilities

Handle containers carefully to prevent damage and spillage.

Incompatible materials: Strong oxidizing agents

See section 2 for further details. - [Storage]:

### 7.3. Specific end use(s)

No data available.

## 8. Exposure controls and personal protection

### 8.1. Control parameters

#### Exposure

CAS No.	Ingredient	Source	Value
0000067-64-1	2-Propanone	OSHA	TWA 1000 ppm (2400 mg/m <sup>3</sup> ) STEL 2400 mg/m <sup>3</sup>
		ACGIH	TWA: 250 ppm STEL: 500 ppm Skin
		NIOSH	250 ppm (590 mg/m <sup>3</sup> ) TWA
		Supplier	No Established Limit

# Safety Data Sheet

## ECO-SURE Industrial Enamel Aerosol Paint

SDS Revision Date:

07/05/2018



0000071-36-3	Butan-1-ol	OSHA	TWA 100 ppm (300 mg/m3)
		ACGIH	TWA: 15 ppm Ceiling: 30 ppm
		NIOSH	C 50 ppm (150 mg/m3) [skin]
		Supplier	No Established Limit
0000074-98-6	Propane	OSHA	TWA 1000 ppm (1800 mg/m3)
		ACGIH	No Established Limit
		NIOSH	TWA 1000 ppm (1800 mg/m3)
		Supplier	No Established Limit
0000075-28-5	Propane, 2-methyl-	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	TWA 800 ppm (1900 mg/m3)
		Supplier	No Established Limit
0000106-97-8	Butane	OSHA	No Established Limit
		ACGIH	TWA: 600 ppm STEL: 750 ppm
		NIOSH	TWA 800 ppm (1900 mg/m3)
		Supplier	No Established Limit
0000107-87-9	Pentan-2-one	OSHA	TWA 200 ppm (700 mg/m3)
		ACGIH	TWA: 150 ppm STEL: 250 ppm
		NIOSH	TWA 150 ppm (530 mg/m3)
		Supplier	No Established Limit
0000110-12-3	5-Methyl-2-hexanone	OSHA	TWA 100 ppm (475 mg/m3)
		ACGIH	TWA: 50 ppm
		NIOSH	TWA 50 ppm (240 mg/m3)
		Supplier	No Established Limit
0000110-19-0	iso-Butyl acetate.	OSHA	TWA 150 ppm (700 mg/m3)
		ACGIH	TWA: 150 ppm
		NIOSH	TWA 150 ppm (700 mg/m3)
		Supplier	No Established Limit
0000123-42-2	4-Hydroxy-4-Methylpentan-2-one	OSHA	TWA 50 ppm (240 mg/m3)
		ACGIH	TWA: 50 ppm
		NIOSH	TWA 50 ppm (240 mg/m3)
		Supplier	No Established Limit
0000123-86-4	N-Butyl Acetate	OSHA	TWA 150 ppm (710 mg/m3)
		ACGIH	TWA: 20 ppmS
		NIOSH	TWA 150 ppm (710 mg/m3) ST 200 ppm (950 mg/m3)
		Supplier	No Established Limit

# Safety Data Sheet

## ECO-SURE Industrial Enamel Aerosol Paint

SDS Revision Date:

07/05/2018



### Carcinogen Data

CAS No.	Ingredient	Source	Value
0000067-64-1	2-Propanone	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0000071-36-3	Butan-1-ol	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0000074-98-6	Propane	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0000075-28-5	Propane, 2-methyl-	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0000106-97-8	Butane	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0000107-87-9	Pentan-2-one	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0000110-12-3	5-Methyl-2-hexanone	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0000110-19-0	iso-Butyl acetate.	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0000123-42-2	4-Hydroxy-4-Methylpentan-2-one	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0000123-86-4	N-Butyl Acetate	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;

## 8.2. Exposure controls

### Respiratory

If workers are exposed to concentrations above the exposure limit they must use the appropriate, certified respirators.

### Eyes

Wear safety eyewear, e.g. safety spectacles, goggles or visors to protect against the splash of liquids.



# Safety Data Sheet

## ECO-SURE Industrial Enamel Aerosol Paint

SDS Revision Date:

07/05/2018



<b>Skin</b>	Overalls which cover the body, arms and legs should be worn. Skin should not be exposed. All parts of the body should be washed after contact.
<b>Engineering Controls</b>	Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and any vapor below occupational exposure limits suitable respiratory protection must be worn.
<b>Other Work Practices</b>	Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

See section 2 for further details. - [Prevention]:

### 9. Physical and chemical properties

<b>Appearance</b>	Red Liquid/Gas
<b>Odor</b>	Paint
<b>Odor threshold</b>	Not Measured
<b>pH</b>	Not Measured
<b>Melting point / freezing point</b>	Not Measured
<b>Initial boiling point and boiling range</b>	Not Measured
<b>Flash Point</b>	Not Measured
<b>Evaporation rate (Ether = 1)</b>	Slower than ether
<b>Flammability (solid, gas)</b>	Flam. Aerosol 1; H222 Extremely flammable aerosol.
<b>Upper/lower flammability or explosive limits</b>	<b>Lower Explosive Limit:</b> 1.1% <b>Upper Explosive Limit:</b> 12.8%
<b>Vapor pressure (Pa)</b>	Not Measured
<b>Vapor Density</b>	>1 (Heavier than Air)
<b>Specific Gravity</b>	0.746 (6.56 lb/gal)
<b>Solubility in Water</b>	Insoluble
<b>Partition coefficient n-octanol/water (Log Kow)</b>	Not Measured
<b>Auto-ignition temperature</b>	Not Measured
<b>Decomposition temperature</b>	Not Measured
<b>Viscosity (cSt)</b>	Not Measured
<b>VOC %</b>	54.8% by wt, 4.51 lb/gal
<b>Maximum Incremental Reactivity</b>	0.67
<b>HAPS (lbs/gal)</b>	0.00 lbs/gal
<b>HAPS (lbs/gal of Solids)</b>	0.00 lbs/gal
<b>HAPS (lbs/lb of Solids)</b>	0.00 lbs/lb

# Safety Data Sheet

## ECO-SURE Industrial Enamel Aerosol Paint

SDS Revision Date:

07/05/2018



### 9.2. Other information

No other relevant information.

## 10. Stability and reactivity

### 10.1. Reactivity

Hazardous Polymerization will not occur.

### 10.2. Chemical stability

Stable under normal circumstances.

### 10.3. Possibility of hazardous reactions

No data available.

### 10.4. Conditions to avoid

Avoid contact with open flame, sparks or hot surfaces.

### 10.5. Incompatible materials

Strong oxidizing agents

### 10.6. Hazardous decomposition products

Carbon Monoxide and Carbon Dioxide

## 11. Toxicological information

### Acute toxicity

Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage.

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LD50, mg/L/4hr	Inhalation Dust/Mist LD50, mg/L/4hr	Inhalation Gas LD50, ppm
2-Propanone - (67-64-1)	2,000.00, Rat - Category: 4	2,000.00, Rabbit - Category: 4	76.00, Rat - Category: NA	No data available	No data available
Propane - (74-98-6)	No data available	No data available	658.00, Rat - Category: NA	No data available	No data available
N-Butyl Acetate - (123-86-4)	10,700.00, Rat - Category: NA	17,600.00, Rabbit - Category: NA	No data available	No data available	No data available

# Safety Data Sheet

## ECO-SURE Industrial Enamel Aerosol Paint

SDS Revision Date:

07/05/2018



Butane - (106-97-8)	No data available	No data available	658.00, Rat - Category: NA	No data available	No data available
Propane, 2-methyl- - (75-28-5)	No data available	No data available	658.00, Rat - Category: NA	No data available	No data available
5-Methyl-2-hexanone - (110-12-3)	3,200.00, Rat - Category: 5	8,110.00, Rabbit - Category: NA	No data available	No data available	No data available
Butan-1-ol - (71-36-3)	2,292.00, Rat - Category: 5	3,430.00, Rabbit - Category: 5	No data available	No data available	8,000.00, Rat - Category: 4
Pentan-2-one - (107-87-9)	1,600.00, Rat - Category: 4	6,500.00, Rabbit - Category: NA	No data available	No data available	No data available
iso-Butyl acetate. - (110-19-0)	13,400.00, Rat - Category: NA	17,400.00, Rabbit - Category: NA	No data available	No data available	No data available
4-Hydroxy-4-Methylpentan-2-one - (123-42-2)	2,520.00, Rat - Category: 5	13,500.00, Rabbit - Category: NA	No data available	No data available	1,500.00, Rat - Category: NA

Note: When no route specific LD50 data is available for an acute toxin, the converted acute toxicity point estimate was used in the calculation of the product's ATE (Acute Toxicity Estimate).

Classification	Category	Hazard Description
Acute toxicity (oral)	5	May be harmful if swallowed. (Not adopted by US OSHA)
Acute toxicity (dermal)	---	Not Applicable
Acute toxicity (inhalation)	---	Not Applicable
Skin corrosion/irritation	3	Causes mild skin irritation. (Not adopted by US OSHA)
Serious eye damage/irritation	1	Causes serious eye damage.
Respiratory sensitization	---	Not Applicable
Skin sensitization	---	Not Applicable
Germ cell mutagenicity	---	Not Applicable
Carcinogenicity	---	Not Applicable
Reproductive toxicity	---	Not Applicable
STOT-single exposure	3	May cause drowsiness or dizziness.
STOT-repeated exposure	---	Not Applicable
Aspiration hazard	---	Not Applicable

# Safety Data Sheet

## ECO-SURE Industrial Enamel Aerosol Paint

SDS Revision Date:

07/05/2018



### 12. Ecological information

#### 12.1. Toxicity

##### Aquatic Ecotoxicity

Ingredient	96 hr LC50 fish, mg/l	48 hr EC50 crustacea, mg/l	ErC50 algae, mg/l
2-Propanone - (67-64-1)	100.00, Pimephales promelas	10.00, Daphnia magna	20.565 (72 hr), Ulva pertusa
Propane - (74-98-6)	Not Available	Not Available	Not Available
N-Butyl Acetate - (123-86-4)	18.00, Pimephales promelas	32.00, Artemia salina	674.70 (72 hr), Scenedesmus subspicatus
Butane - (106-97-8)	6.00, Fish (Piscis)	Not Available	Not Available
Propane, 2-methyl- - (75-28-5)	Not Available	Not Available	Not Available
5-Methyl-2-hexanone - (110-12-3)	159.00, Pimephales promelas	560.00, Daphnia magna	920.00 (72 hr), Chlorococcales
Butan-1-ol - (71-36-3)	1,376.00, Pimephales promelas	1,328.00, Daphnia magna	500.00 (96 hr), Scenedesmus subspicatus
Pentan-2-one - (107-87-9)	1,240.00, Pimephales promelas	Not Available	0.00 (96 hr),
iso-Butyl acetate. - (110-19-0)	101.00, Leuciscus idus	250.00, Daphnia magna	600.00 (24 hr), Chlorococcales
4-Hydroxy-4-Methylpentan-2-one - (123-42-2)	420.00, Lepomis macrochirus	9,000.00, Daphnia magna	Not Available

#### 12.2. Persistence and degradability

There is no data available on the preparation itself.

#### 12.3. Bioaccumulative potential

Not Measured

#### 12.4. Mobility in soil

No data available.

#### 12.5. Results of PBT and vPvB assessment

This product contains no PBT/vPvB chemicals.

#### 12.6. Other adverse effects

# Safety Data Sheet

## ECO-SURE Industrial Enamel Aerosol Paint

SDS Revision Date:

07/05/2018



No data available.

### 13. Disposal considerations

#### 13.1. Waste treatment methods

Do not allow into drains or water courses. Wastes and emptied containers should be disposed of in accordance with regulations made under the Control of Pollution Act and the Environmental Protection Act.

Using information provided in this data sheet advice should be obtained from the Waste Regulation Authority, whether the special waste regulations apply.

### 14. Transport information

	<b>DOT (Domestic Surface Transportation)</b>	<b>IMO / IMDG (Ocean Transportation)</b>	<b>ICAO/IATA</b>
<b>14.1. UN number</b>	UN1950	UN1950	UN1950
<b>14.2. UN proper shipping name</b>	UN1950, Aerosols, Limited Quantity, 2.1,	Aerosols, Limited Quantity	Aerosols, Limited Quantity
<b>14.3. Transport hazard class(es)</b>	<b>DOT Hazard Class: 2.1</b>	<b>IMDG: 2.1</b>	<b>Air Class: 2.1</b>
<b>14.4. Packing group</b>	Not Applicable	Not Applicable	Not Applicable
<b>14.5. Environmental hazards</b>			

**IMDG** Marine Pollutant: No

#### 14.6. Special precautions for user

No further information

#### 14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not Applicable

### 15. Regulatory information

**Regulatory Overview** The regulatory data in Section 15 is not intended to be all-inclusive, only selected regulations are represented. All ingredients of this product are listed on the TSCA (Toxic Substance Control Act) Inventory or are not required to be listed on the TSCA Inventory.

# Safety Data Sheet

## ECO-SURE Industrial Enamel Aerosol Paint

SDS Revision Date:

07/05/2018



**WHMIS Classification** D2B E

**US EPA Tier II Hazards**

**Fire:** No

**Sudden Release of Pressure:** Yes

**Reactive:** No

**Immediate (Acute):** Yes

**Delayed (Chronic):** No

### EPCRA 311/312 Chemicals and RQs (lbs):

2-Propanone ( 5,000.00)

Butan-1-ol ( 5,000.00)

iso-Butyl acetate. ( 5,000.00)

N-Butyl Acetate ( 5,000.00)

### EPCRA 302 Extremely Hazardous :

(No Product Ingredients Listed)

### EPCRA 313 Toxic Chemicals:

Butan-1-ol

### Proposition 65 - Carcinogens (>0.0%):

(No Product Ingredients Listed)

### Proposition 65 - Developmental Toxins (>0.0%):

(No Product Ingredients Listed)

### Proposition 65 - Female Repro Toxins (>0.0%):

(No Product Ingredients Listed)

### Proposition 65 - Male Repro Toxins (>0.0%):

(No Product Ingredients Listed)

### N.J. RTK Substances (>1%) :

4-Hydroxy-4-Methylpentan-2-one

5-Methyl-2-hexanone

2-Propanone

Butan-1-ol

Butane

iso-Butyl acetate.

N-Butyl Acetate

Pentan-2-one

Propane

Propane, 2-methyl-

# Safety Data Sheet

## ECO-SURE Industrial Enamel Aerosol Paint

SDS Revision Date:

07/05/2018



### Penn RTK Substances (>1%) :

4-Hydroxy-4-Methylpentan-2-one  
5-Methyl-2-hexanone  
2-Propanone  
Butan-1-ol  
Butane  
iso-Butyl acetate.  
N-Butyl Acetate  
Pentan-2-one  
Propane  
Propane, 2-methyl-

## 16. Other information

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

H220 Extremely flammable gas.  
H225 Highly flammable liquid and vapor.  
H226 Flammable liquid and vapor.  
H302 Harmful if swallowed.  
H315 Causes skin irritation.  
H318 Causes serious eye damage.  
H319 Causes serious eye irritation.  
H332 Harmful if inhaled.  
H335 May cause respiratory irritation.  
H336 May cause drowsiness and dizziness.

**This is the first version in the GHS SDS format. Listings of changes from previous versions in other formats are not applicable.**

**Safety Data Sheet**  
**ECO-SURE Industrial Enamel Aerosol Paint**

SDS Revision Date:

**07/05/2018**



IMPORTANT NOTE: This information is furnished without warranty, expressed or implied, as to accuracy or completeness. The information is obtained from various sources including the manufacturer and other third party sources. The information may not be valid under all conditions nor if this material is used in combination with other materials or any process. Final determination of suitability of any material is the sole responsibility of the user.

End of Document