

# Safety Data Sheet

## ECO-SURE Industrial Enamel Aerosol Paint

SDS Revision Date:

08/23/2018



### 1. Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

**Product Identity**

ECO-SURE Industrial Enamel Aerosol Paint

**Alternate Names**

Specification: A-A-2787 Type I, Gloss Blue 15102  
LHB Part Number: 0674-152  
National Stock Number: 8010-01-331-6119  
CAGE Code: 0FTT5  
Contract Number: SPE8EG-16-D-0015

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Intended use**

See product label.

**Application Method**

See product label.

#### 1.3. Details of the supplier of the safety data sheet

**Company Name**

LHB Industries  
8833 Fleischer Place  
Berkeley, MO 63134

**Emergency**

**24 hour Emergency Telephone No.**

(800) 633-8253 (PERS)

**Customer Service: LHB Industries**

(314) 423-4333

### 2. Hazard identification of the product

#### 2.1. Classification of the substance or mixture

Flam. Aerosol 1;H222

Extremely flammable aerosol.

Press. Gas;H280

Contains gas under pressure; may explode if heated.

Eye Irrit. 2;H319

Causes serious eye irritation.

STOT RE 1;H372

Causes damage to organs through prolonged or repeated exposure. Specific Target Organs: (central nervous system )

Simple Asphyxiant

May displace oxygen and cause rapid suffocation.

# Safety Data Sheet

## ECO-SURE Industrial Enamel Aerosol Paint

SDS Revision Date:

08/23/2018



### 2.2. Label elements

Using the Toxicity Data listed in section 11 and 12 the product is labeled as follows.



### Danger

H222 Extremely flammable aerosol.

H280 Contains gas under pressure; may explode if heated.

H319 Causes serious eye irritation.

H372 Causes damage to organs through prolonged or repeated exposure.

May displace oxygen and cause rapid suffocation.

#### [Prevention]:

P210 Keep away from heat / sparks / open flames / hot surfaces - No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Pressurized container: Do not pierce or burn, even after use.

P260 Do not breathe mist / vapors / spray.

P262 Do not get in eyes, on skin, or on clothing.

P264 Wash thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P280 Wear protective gloves / eye protection / face protection.

#### [Response]:

P301+310 IF SWALLOWED: Immediately call a POISON CENTER or doctor / physician.

P305+351+338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing.

P314 Get Medical advice / attention if you feel unwell.

P331 Do NOT induce vomiting.

P337+313 If eye irritation persists: Get medical advice / attention.

#### [Storage]:

P410+412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C / 122 °F.

#### [Disposal]:

P501 Dispose of contents / container in accordance with local / national regulations.

# Safety Data Sheet

## ECO-SURE Industrial Enamel Aerosol Paint

SDS Revision Date:

08/23/2018



### 3. Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of the relevant State and Federal Hazardous Substances regulations.

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
Acetone CAS Number: Proprietary	10 - 25	Flam. Liq. 2;H225 Eye Irrit. 2;H319 STOT SE 3;H336	[1][2]
Propane CAS Number: 0000074-98-6	10 - 25	Flam. Gas 1;H220 Press. Gas;H280	[1][2]
N-Butyl Acetate CAS Number: 0000123-86-4	10 - 25	Flam. Liq. 3;H226 STOT SE 3;H336	[1][2]
Solvent naphtha (petroleum), light aliphatic CAS Number: 0064742-89-8	10 - 25	Asp. Tox. 1;H304	[1]
Butane CAS Number: 0000106-97-8	1.0 - 10	Flam. Gas 1;H220 Press. Gas;H280 Simple Asphyxiant	[1][2]
Propane, 2-methyl- CAS Number: 0000075-28-5	1.0 - 10	Flam. Gas 1;H220 Press. Gas;H280	[1][2]
Propylene glycol monomethyl ether acetate CAS Number: 0000108-65-6	1.0 - 10	Flam. Liq. 3;H226	[1]
Stoddard solvent CAS Number: 0008052-41-3	1.0 - 10	STOT RE 1;H372 Asp. Tox. 1;H304	[1][2]
Solvent naphtha (petroleum), light aromatic CAS Number: 0064742-95-6	1.0 - 10	Asp. Tox. 1;H304	[1]

In accordance with paragraph (i) of §1910.1200, the specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

[1] Substance classified with a health or environmental hazard.

[2] Substance with a workplace exposure limit.

[3] PBT-substance or vPvB-substance.

\*The full texts of the phrases are shown in Section 16.

### 4. First aid measures

#### 4.1. Description of first aid measures

##### General

Move victim to fresh air.  
 Call 911 or emergency medical service if deemed necessary.  
 Give artificial respiration if victim is not breathing.  
 Administer oxygen if breathing is difficult.  
 Remove and isolate contaminated clothing and shoes.  
 In case of contact with liquefied gas, thaw frosted parts with lukewarm water.  
 Keep victim warm and quiet.

# Safety Data Sheet

## ECO-SURE Industrial Enamel Aerosol Paint

SDS Revision Date:

08/23/2018



	Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves.
<b>Inhalation</b>	Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, give artificial respiration. If unconscious place in the recovery position and obtain immediate medical attention. Give nothing by mouth.
<b>Eyes</b>	Irrigate copiously with clean fresh water for at least 15 minutes, holding the eyelids apart and seek medical attention.
<b>Skin</b>	Remove and isolate contaminated clothing and shoes. Clothing frozen to the skin should be thawed before being removed. In case of contact with liquefied gas, thaw frosted parts with lukewarm water.
<b>Ingestion</b>	If accidentally swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

#### 4.2. Most important symptoms and effects, both acute and delayed

**Overview** Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage. See section 2 for further details.

**Eyes** Causes serious eye irritation.

## 5. Fire-fighting measures

### 5.1. Extinguishing media

**Fire involving Tanks:** Some of these materials, if spilled, may evaporate leaving a flammable residue. Some of these materials, if spilled, may evaporate leaving a flammable residue.

### 5.2. Special hazards arising from the substance or mixture

Carbon Monoxide and Carbon Dioxide

Keep away from heat / sparks / open flames / hot surfaces - No smoking.

Do not spray on an open flame or other ignition source.

Pressurized container: Do not pierce or burn, even after use.

Do not breathe mist / vapors / spray.

Do not get in eyes, on skin, or on clothing.

### 5.3. Advice for fire-fighters

Wear positive pressure self-contained breathing apparatus (SCBA).

# Safety Data Sheet

## ECO-SURE Industrial Enamel Aerosol Paint

SDS Revision Date:

08/23/2018



Wear chemical protective clothing that is specifically recommended by the manufacturer. It may provide little or no thermal protection.

Structural firefighters' protective clothing will only provide limited protection.

Some may burn but none ignite readily.

Containers may explode when heated.

Ruptured cylinders may rocket.

Vapors may cause dizziness or asphyxiation without warning.

Vapors from liquefied gas are initially heavier than air and spread along ground.

Contact with gas or liquefied gas may cause burns, severe injury and/or frostbite.

Fire may produce irritating, corrosive and/or toxic gases.

**ERG Guide No.** 126

## 6. Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Do not touch or walk through spilled material.

Stop leak if you can do it without risk.

Do not direct water at spill or source of leak.

Use water spray to reduce vapors or divert vapor cloud drift. Avoid allowing water runoff to contact spilled material.

If possible, turn leaking containers so that gas escapes rather than liquid.

Prevent entry into waterways, sewers, basements or confined areas.

Allow substance to evaporate.

Ventilate the area.

### 6.2. Environmental precautions

Do not allow spills to enter drains or watercourses.

Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

### 6.3. Methods and material for containment and cleaning up

As an immediate precautionary measure, isolate spill or leak area for at least 100 meters (330 feet) in all directions.

Keep unauthorized personnel away.

Stay upwind.

Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks).

Keep out of low areas.

Ventilate closed spaces before entering.

# Safety Data Sheet

## ECO-SURE Industrial Enamel Aerosol Paint

SDS Revision Date:

08/23/2018



### 7. Handling and storage

#### 7.1. Precautions for safe handling

Store in accordance with the National Fire Protection Association's publication NFPA 30, Flammable and Combustible Liquids Code. 29 CFR 1910.106 applies to the handling, storage, and use of flammable and combustible liquids.

See section 2 for further details. - [Prevention]:

#### 7.2. Conditions for safe storage, including any incompatibilities

Handle containers carefully to prevent damage and spillage.

Incompatible materials: Strong oxidizing agents

See section 2 for further details. - [Storage]:

#### 7.3. Specific end use(s)

No data available.

### 8. Exposure controls and personal protection

#### 8.1. Control parameters

##### Exposure

CAS No.	Ingredient	Source	Value
000067-64-1	2-Propanone	OSHA	TWA 1000 ppm (2400 mg/m <sup>3</sup> ) STEL 2400 mg/m <sup>3</sup>
		ACGIH	TWA: 250 ppm STEL: 500 ppm Skin
		NIOSH	250 ppm (590 mg/m <sup>3</sup> ) TWA
		Supplier	No Established Limit
000074-98-6	Propane	OSHA	TWA 1000 ppm (1800 mg/m <sup>3</sup> )
		ACGIH	No Established Limit
		NIOSH	TWA 1000 ppm (1800 mg/m <sup>3</sup> )
		Supplier	No Established Limit
000075-28-5	Propane, 2-methyl-	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	TWA 800 ppm (1900 mg/m <sup>3</sup> )
		Supplier	No Established Limit
0000106-97-8	Butane	OSHA	No Established Limit
		ACGIH	TWA: 600 ppm STEL: 750 ppm
		NIOSH	TWA 800 ppm (1900 mg/m <sup>3</sup> )
		Supplier	No Established Limit

# Safety Data Sheet

## ECO-SURE Industrial Enamel Aerosol Paint

SDS Revision Date:

08/23/2018



0000108-65-6	2-Methoxy-1-Methylethyl Acetate	OSHA	No Established Limit
		ACGIH	TWA: 50 ppm STEL: 75 ppm
		NIOSH	No Established Limit
		Supplier	No Established Limit
0000123-86-4	N-Butyl Acetate	OSHA	TWA 150 ppm (710 mg/m3)
		ACGIH	TWA: 20 ppmS
		NIOSH	TWA 150 ppm (710 mg/m3) ST 200 ppm (950 mg/m3)
		Supplier	No Established Limit
0008052-41-3	Stoddard solvent	OSHA	TWA 500 ppm (2900 mg/m3)
		ACGIH	TWA: 290 mg/m3 STEL: 580 mg/m3
		NIOSH	TWA 350 mg/m3 C 1800 mg/m3 [15-minute]
		Supplier	No Established Limit
0064742-89-8	Solvent naphtha (petroleum), light aliphatic	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
0064742-95-6	Solvent naphtha (petroleum), light aromatic	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit

### Carcinogen Data

CAS No.	Ingredient	Source	Value
0000067-64-1	2-Propanone	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0000074-98-6	Propane	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0000075-28-5	Propane, 2-methyl-	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0000106-97-8	Butane	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0000108-65-6	2-Methoxy-1-Methylethyl Acetate	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;

# Safety Data Sheet

## ECO-SURE Industrial Enamel Aerosol Paint

SDS Revision Date:

08/23/2018



0000123-86-4	N-Butyl Acetate	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0008052-41-3	Stoddard solvent	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0064742-89-8	Solvent naphtha (petroleum), light aliphatic	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0064742-95-6	Solvent naphtha (petroleum), light aromatic	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;

### 8.2. Exposure controls

#### Respiratory

If workers are exposed to concentrations above the exposure limit they must use the appropriate, certified respirators.

#### Eyes

Wear safety eyewear, e.g. safety spectacles, goggles or visors to protect against the splash of liquids.

#### Skin

Overalls which cover the body, arms and legs should be worn. Skin should not be exposed. All parts of the body should be washed after contact.

#### Engineering Controls

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and any vapor below occupational exposure limits suitable respiratory protection must be worn.

#### Other Work Practices

Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

See section 2 for further details. - [Prevention]:

## 9. Physical and chemical properties

**Appearance**

Blue Liquid/Gas

**Odor**

Paint

**Odor threshold**

Not Measured

**pH**

Not Measured

**Melting point / freezing point**

Not Measured

**Initial boiling point and boiling range**

Not Measured

**Flash Point**

Not Measured



# Safety Data Sheet

## ECO-SURE Industrial Enamel Aerosol Paint

SDS Revision Date:

08/23/2018



<b>Evaporation rate (Ether = 1)</b>	Slower than ether
<b>Flammability (solid, gas)</b>	Flam. Aerosol 1; H222 Extremely flammable aerosol.
<b>Upper/lower flammability or explosive limits</b>	<b>Lower Explosive Limit:</b> 1.1% <b>Upper Explosive Limit:</b> 12.8%
<b>Vapor pressure (Pa)</b>	Not Measured
<b>Vapor Density</b>	>1 (Heavier than Air)
<b>Specific Gravity</b>	0.746 (6.22 lb/gal)
<b>Solubility in Water</b>	Insoluble
<b>Partition coefficient n-octanol/water (Log Kow)</b>	Not Measured
<b>Auto-ignition temperature</b>	Not Measured
<b>Decomposition temperature</b>	Not Measured
<b>Viscosity (cSt)</b>	Not Measured
<b>VOC (minus water and exempt solvents)</b>	4.74 lb/gal, 567 g/L
<b>Maximum Incremental Reactivity</b>	0.78
<b>HAPS (lbs/gal)</b>	0.00 lbs/gal
<b>HAPS (lbs/gal of Solids)</b>	0.00 lbs/gal
<b>HAPS (lbs/lb of Solids)</b>	0.00 lbs/lb

### 9.2. Other information

No other relevant information.

## 10. Stability and reactivity

### 10.1. Reactivity

Hazardous Polymerization will not occur.

### 10.2. Chemical stability

Stable under normal circumstances.

### 10.3. Possibility of hazardous reactions

No data available.

### 10.4. Conditions to avoid

Avoid contact with open flame, sparks or hot surfaces.

### 10.5. Incompatible materials

Strong oxidizing agents

### 10.6. Hazardous decomposition products

Carbon Monoxide and Carbon Dioxide

# Safety Data Sheet

## ECO-SURE Industrial Enamel Aerosol Paint

SDS Revision Date:

08/23/2018



### 11. Toxicological information

#### Acute toxicity

Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage.

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LD50, mg/L/4hr	Inhalation Dust/Mist LD50, mg/L/4hr	Inhalation Gas LD50, ppm
2-Propanone - (67-64-1)	2,000.00, Rat - Category: 4	2,000.00, Rabbit - Category: 4	76.00, Rat - Category: NA	No data available	No data available
Propane - (74-98-6)	No data available	No data available	658.00, Rat - Category: NA	No data available	No data available
N-Butyl Acetate - (123-86-4)	10,700.00, Rat - Category: NA	17,600.00, Rabbit - Category: NA	No data available	No data available	No data available
Solvent naphtha (petroleum), light aliphatic - (64742-89-8)	5,000.00, Mouse - Category: 5	3,000.00, Rabbit - Category: 5	No data available	No data available	No data available
Butane - (106-97-8)	No data available	No data available	658.00, Rat - Category: NA	No data available	No data available
Propane, 2-methyl- - (75-28-5)	No data available	No data available	658.00, Rat - Category: NA	No data available	No data available
2-Methoxy-1-Methylethyl Acetate - (108-65-6)	8,532.00, Rat - Category: NA	5,000.00, Rabbit - Category: 5	No data available	No data available	4,345.00, Rat - Category: NA
Stoddard solvent - (8052-41-3)	No data available	No data available	No data available	No data available	No data available
Solvent naphtha (petroleum), light aromatic - (64742-95-6)	6,800.00, Rat - Category: NA	3,400.00, Rabbit - Category: 5	No data available	No data available	No data available

Note: When no route specific LD50 data is available for an acute toxin, the converted acute toxicity point estimate was used in the calculation of the product's ATE (Acute Toxicity Estimate).

# Safety Data Sheet

## ECO-SURE Industrial Enamel Aerosol Paint

SDS Revision Date:

08/23/2018



Classification	Category	Hazard Description
Acute toxicity (oral)	---	Not Applicable
Acute toxicity (dermal)	---	Not Applicable
Acute toxicity (inhalation)	---	Not Applicable
Skin corrosion/irritation	---	Not Applicable
Serious eye damage/irritation	2	Causes serious eye irritation.
Respiratory sensitization	---	Not Applicable
Skin sensitization	---	Not Applicable
Germ cell mutagenicity	---	Not Applicable
Carcinogenicity	---	Not Applicable
Reproductive toxicity	---	Not Applicable
STOT-single exposure	---	Not Applicable
STOT-repeated exposure	2	May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard	---	Not Applicable

## 12. Ecological information

### 12.1. Toxicity

No additional information provided for this product. See Section 3 for chemical specific data.

### Aquatic Ecotoxicity

Ingredient	96 hr LC50 fish, mg/l	48 hr EC50 crustacea, mg/l	ErC50 algae, mg/l
2-Propanone - (67-64-1)	100.00, Pimephales promelas	10.00, Daphnia magna	20.565 (72 hr), Ulva pertusa
Propane - (74-98-6)	Not Available	Not Available	Not Available
N-Butyl Acetate - (123-86-4)	18.00, Pimephales promelas	32.00, Artemia salina	674.70 (72 hr), Scenedesmus subspicatus
Solvent naphtha (petroleum), light aliphatic - (64742-89-8)	Not Available	Not Available	4,700.00 (72 hr), Selenastrum capricornutum
Butane - (106-97-8)	6.00, Fish (Piscis)	Not Available	Not Available
Propane, 2-methyl- - (75-28-5)	Not Available	Not Available	Not Available
2-Methoxy-1-Methylethyl Acetate - (108-65-6)	100.00, Salmo gairdneri	500.00, Daphnia magna	Not Available
Stoddard solvent - (8052-41-3)	Not Available	Not Available	Not Available
Solvent naphtha (petroleum), light aromatic - (64742-95-6)	9.22, Oncorhynchus mykiss	6.14, Daphnia magna	19.00 (72 hr), Selenastrum capricornutum

# Safety Data Sheet

## ECO-SURE Industrial Enamel Aerosol Paint

SDS Revision Date:

08/23/2018



### 12.2. Persistence and degradability

There is no data available on the preparation itself.

### 12.3. Bioaccumulative potential

Not Measured

### 12.4. Mobility in soil

No data available.

### 12.5. Results of PBT and vPvB assessment

This product contains no PBT/vPvB chemicals.

### 12.6. Other adverse effects

No data available.

## 13. Disposal considerations

### 13.1. Waste treatment methods

Do not allow into drains or water courses. Wastes and emptied containers should be disposed of in accordance with regulations made under the Control of Pollution Act and the Environmental Protection Act.

Using information provided in this data sheet advice should be obtained from the Waste Regulation Authority, whether the special waste regulations apply.

## 14. Transport information

	<b>DOT (Domestic Surface Transportation)</b>	<b>IMO / IMDG (Ocean Transportation)</b>	<b>ICAO/IATA</b>
<b>14.1. UN number</b>	UN1950	UN1950	UN1950
<b>14.2. UN proper shipping name</b>	UN1950, Aerosols, Limited Quantity, 2.1,	Aerosols, Limited Quantity	Aerosols, Limited Quantity
<b>14.3. Transport hazard class(es)</b>	<b>DOT Hazard Class: 2.1</b>	<b>IMDG: 2.1</b>	<b>Air Class: 2.1</b>
<b>14.4. Packing group</b>	Not Applicable	Not Applicable	Not Applicable
<b>14.5. Environmental hazards</b>			
<b>IMDG</b>	Marine Pollutant: No		
<b>14.6. Special precautions for user</b>	No further information		
<b>14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code</b>	Not Applicable		

# Safety Data Sheet

## ECO-SURE Industrial Enamel Aerosol Paint

SDS Revision Date:

08/23/2018



### 15. Regulatory information

**Regulatory Overview** The regulatory data in Section 15 is not intended to be all-inclusive, only selected regulations are represented. All ingredients of this product are listed on the TSCA (Toxic Substance Control Act) Inventory or are not required to be listed on the TSCA Inventory.

**WHMIS Classification** A B5 D2A

**US EPA Tier II Hazards**

**Fire:** No

**Sudden Release of Pressure:** Yes

**Reactive:** No

**Immediate (Acute):** Yes

**Delayed (Chronic):** Yes

**EPCRA 311/312 Chemicals and RQs (lbs):**

2-Propanone ( 5,000.00)

N-Butyl Acetate ( 5,000.00)

**EPCRA 302 Extremely Hazardous :**

(No Product Ingredients Listed)

**EPCRA 313 Toxic Chemicals:**

(No Product Ingredients Listed)

**Proposition 65 - Carcinogens (>0.0%):**

(No Product Ingredients Listed)

**Proposition 65 - Developmental Toxins (>0.0%):**

(No Product Ingredients Listed)

**Proposition 65 - Female Repro Toxins (>0.0%):**

(No Product Ingredients Listed)

**Proposition 65 - Male Repro Toxins (>0.0%):**

(No Product Ingredients Listed)

**N.J. RTK Substances (>1%) :**

2-Propanone

Butane

N-Butyl Acetate

Propane

Propane, 2-methyl-

Stoddard solvent

# Safety Data Sheet

## ECO-SURE Industrial Enamel Aerosol Paint

SDS Revision Date:

08/23/2018



### Penn RTK Substances (>1%) :

2-Propanone

Butane

N-Butyl Acetate

Propane

Propane, 2-methyl-

Stoddard solvent

## 16. Other information

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

# Safety Data Sheet

## ECO-SURE Industrial Enamel Aerosol Paint

SDS Revision Date:

08/23/2018



The full text of the phrases appearing in section 3 is:

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapor.

H226 Flammable liquid and vapor.

H304 May be fatal if swallowed and enters airways.

H319 Causes serious eye irritation.

H336 May cause drowsiness and dizziness.

H340 May cause genetic defects.

H350 May cause cancer.

H372 Causes damage to organs through prolonged or repeated exposure.

**This is the first version in the GHS SDS format. Listings of changes from previous versions in other formats are not applicable.**

IMPORTANT NOTE: This information is furnished without warranty, expressed or implied, as to accuracy or completeness. The information is obtained from various sources including the manufacturer and other third party sources. The information may not be valid under all conditions nor if this material is used in combination with other materials or any process. Final determination of suitability of any material is the sole responsibility of the user.

End of Document