LPS.

SAFETY DATA SHEET

1. Identification

Product identifier LPS® Precision Clean (Ready-to-use)

Other means of identification

Part Number 02728, 02765

Recommended use An industrial cleaner designed to remove grime, oils and light grease from metal, concrete and

other durable surfaces.

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Manufacturer

Company name ITW Pro Brands

Address 4647 Hugh Howell Rd.

Tucker, GA 30084

Country (U.S.A.)

Tel: +1 770-243-8800

In Case of Emergency 1-800-424-9300 (inside U.S.)

+001 703-527-3887 (outside U.S.)

Website www.lpslabs.com

E-mail lpssds@itwprobrands.com

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Skin corrosion/irritation Category 2

Serious eye damage/eye irritation Category 2B

Environmental hazards Not classified.

OSHA defined hazards Not classified.

Label elements



Signal word Warning

Hazard statement Causes skin irritation. Causes eye irritation.

Precautionary statement

Prevention Wash thoroughly after handling. Wear protective gloves.

Response If on skin: Wash with plenty of water. If in eyes: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off

contaminated clothing and wash before reuse.

Storage Store away from incompatible materials.

Disposal Dispose of waste and residues in accordance with local authority requirements.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Ethoxylated alcohols		68002-97-1	0.5 - 1
Silicic acid, Disodium salt		6834-92-0	0.5 - 1
Tetrapotassium pyrophosphate		7320-34-5	0.5 - 1
Sodium dodecyl sulphate		151-21-3	0.1 - 0.5
Diethanolamine		111-42-2	< 0.1

4. First-aid measures

Move to fresh air. Call a physician if symptoms develop or persist. Inhalation

Wash off with soap and water. Get medical attention if irritation develops and persists. Skin contact

Rinse with water. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical **Eve contact**

attention if irritation develops and persists.

redness, swelling, and blurred vision.

Ingestion Rinse mouth. Get medical attention if symptoms occur.

Most important symptoms/effects, acute and

delayed

Indication of immediate medical attention and special treatment needed

Treat symptomatically.

General information Ensure that medical personnel are aware of the material(s) involved, and take precautions to

During fire, gases hazardous to health may be formed.

Move containers from fire area if you can do so without risk.

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

protect themselves.

None known.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

media

Specific hazards arising from the chemical

Special protective equipment

and precautions for firefighters

Fire fighting equipment/instructions

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials.

General fire hazards No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions. protective equipment and emergency procedures

Methods and materials for containment and cleaning up Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Use personal protection recommended in Section 8 of the SDS.

Firefighters should wear full protective clothing including self contained breathing apparatus.

Direct contact with eves may cause temporary irritation. Symptoms may include stinging, tearing.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid discharge into drains, water courses or onto the ground. Prevent further leakage or spillage if safe to do so. Contact local authorities in case of spillage to drain/aquatic environment.

7. Handling and storage

Environmental precautions

Precautions for safe handling

Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. When using, do not eat, drink or smoke. Use only outdoors or in a well-ventilated area. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities Store in original tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

Components	Туре	Value	Form
Dipropylene Glycol Monomethyl Ether (CAS 34590-94-8)	PEL	600 mg/m3	
		100 ppm	
Glycerin (CAS 56-81-5)	PEL	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
US. ACGIH Threshold Limit Values			
Components	Туре	Value	Form
Diethanolamine (CAS 111-42-2)	TWA	1 mg/m3	Inhalable fraction and vapor.
Dipropylene Glycol Monomethyl Ether (CAS 34590-94-8)	STEL	150 ppm	
,	TWA	100 ppm	
US. NIOSH: Pocket Guide to Chemi	cal Hazards		
Components	Туре	Value	
Diethanolamine (CAS 111-42-2)	TWA	15 mg/m3	
		3 ppm	
Dipropylene Glycol Monomethyl Ether (CAS 34590-94-8)	STEL	900 mg/m3	
		150 ppm	
	TWA	600 mg/m3	
		-	

Biological limit valuesNo biological exposure limits noted for the ingredient(s).

Exposure guidelines

US - California OELs: Skin designation

Diethanolamine (CAS 111-42-2)

Can be absorbed through the skin.

Dipropylene Glycol Monomethyl Ether (CAS 34590-94-8)

Can be absorbed through the skin.

US - Tennessee OELs: Skin designation

Dipropylene Glycol Monomethyl Ether (CAS 34590-94-8) Can be absorbed through the skin.

US ACGIH Threshold Limit Values: Skin designation

Diethanolamine (CAS 111-42-2)

Can be absorbed through the skin.

Dipropylene Glycol Monomethyl Ether (CAS 34590-94-8)

Can be absorbed through the skin.

US NIOSH Pocket Guide to Chemical Hazards: Skin designation

Dipropylene Glycol Monomethyl Ether (CAS 34590-94-8) Can be absorbed through the skin.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Dipropylene Glycol Monomethyl Ether (CAS 34590-94-8) Can be absorbed through the skin.

Appropriate engineering

controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection Wear appropriate chemical resistant gloves.

Other Wear suitable protective clothing.

Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment.

Thermal hazards None known.

Material name: LPS® Precision Clean (Ready-to-use)

SDS US

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance Clear.

Physical state Liquid.

Form Liquid.

Color Green.

Odor Mild. Citrus.

Odor threshold Not available. pH 12.5

Melting point/freezing point Not available.

Initial boiling point and boiling ~100°C (212°F)

range

Flash point None
Evaporation rate 1 BuAc
Flammability (solid, gas) Not available.
Upper/lower flammability or explosive limits

iei/iowei iiaiiiiiabiiity oi explosive iiiiit

Flammability limit - lower

1.1 % estimated

(%)

Flammability limit - upper

14 % estimated

(%)

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure 17.5 mm Hg @ 20°C est.

Vapor density > 1

Relative density Not available.

Solubility(ies)

Solubility (water) 100 %

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperature Not available.

Decomposition temperature Not available.

Viscosity Low viscosity comparable to water (water = 1 cST. @ 20°C)

Other information

Density8.44 lb/galPercent volatile96 %Specific gravity1.01

VOC 0.38 % per State and Federal Consumer Product Regulations

10. Stability and reactivity

Reactivity Reacts violently with strong acids. This product may react with oxidizing agents.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

Reacts violently with strong acids. This product may react with oxidizing agents. Hazardous

polymerization does not occur.

Conditions to avoidDo not mix with other chemicals. Contact with incompatible materials.

Incompatible materials Acids. Strong oxidizing agents. Oxidizing agents.

Hazardous decomposition

products

reactions

Carbon oxides. Nitrogen oxides (NOx).

Material name: LPS® Precision Clean (Ready-to-use)

SDS US

11. Toxicological information

Information on likely routes of exposure

Prolonged inhalation may be harmful. Inhalation

Causes skin irritation. Skin contact Eye contact Causes eye irritation.

Expected to be a low ingestion hazard. May cause discomfort if swallowed. Ingestion

Symptoms related to the physical, chemical and toxicological

Causes eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. Exposure may cause temporary irritation, redness, or discomfort.

characteristics

Information on toxicological effects

Acute toxicity Not expected to be acutely toxic.

Acute toxicity	Not expected to be acutely toxic.		
Components	Species	Test Results	
Diethanolamine (CAS 111-42-	2)		
<u>Acute</u>			
Dermal			
LD50	Rabbit	11.9 ml/kg	
Oral			
LD50	Rat	1100 mg/kg	
		710 mg/kg	
Dipropylene Glycol Monometh	yl Ether (CAS 34590-94-8)		
<u>Acute</u>			
Dermal			
LD50	Rabbit	> 19020 mg/kg, 24 Hours	
Oral			
LD50	Rat	> 5000 mg/kg	
Glycerin (CAS 56-81-5)			
<u>Acute</u>			
Dermal			
LD50	Guinea pig	45 ml/kg, Days	
Inhalation			
Vapor	Б.,	1055	
LC50	Rat	4655 mg.min/l, 7 Hours	
Oral	В.	10000 //	
LD50	Rat	18300 mg/kg	
Tetrapotassium pyrophosphat	e (CAS 7320-34-5)		
Acute			
Dermal LD50	Rabbit	> 2000 mg/kg, 24 Hours	
LD30			
	Rat	> 2000 mg/kg, 24 Hours	
Inhalation			
<i>Dust</i> LC50	Rat	> 0.58 mg/l, 4 Hours	
	Tiat	> 0.50 mg/i, 4 mours	
Oral LD100	Rat	<= 5000 mg/kg	
LD50	Rat	300 - 2000 mg/kg	
		300 - 2000 mg/ng	
Skin corrosion/irritation	Causes skin irritation.		
Serious eye damage/eye irritation	Causes eye irritation.		

Respiratory sensitization

Respiratory or skin sensitization

Not a respiratory sensitizer.

02728, 02765 Version #: 02 Revision date: 07-20-2016 Issue date: 01-07-2016

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicityNo data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

ACGIH Carcinogens

Diethanolamine (CAS 111-42-2)

A3 Confirmed animal carcinogen with unknown relevance to

humans

IARC Monographs. Overall Evaluation of Carcinogenicity

Diethanolamine (CAS 111-42-2) 2B Possibly carcinogenic to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

Reproductive toxicityThis product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity - single exposure

Not classified.

Specific target organ toxicity - repeated

Not classified.

exposure

Not classified.

Aspiration hazard Chronic effects

Prolonged or repeated contact may cause drying, cracking, or irritation.

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components Species Test Results

Diethanolamine (CAS 111-42-2)

Aquatic

Crustacea EC50 Water flea (Ceriodaphnia dubia) 61.8 - 86.04 mg/l, 48 hours

Fish LC50 Fathead minnow (Pimephales promelas) 100 mg/l, 96 hours

Glycerin (CAS 56-81-5)

Aquatic

Fish LC50 Rainbow trout, donaldson trout 51000 - 57000 mg/l, 96 hours

(Oncorhynchus mykiss)

Persistence and degradability Expected to biodegrade.

Bioaccumulative potential No data available.

Partition coefficient n-octanol / water (log Kow)

Diethanolamine -1.43 Glycerin -1.76

Mobility in soil This product is completely water soluble and will disperse in soil.

Other adverse effects

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructionsCollect and reclaim or dispose in sealed containers at licensed waste disposal site.

Local disposal regulationsDispose in accordance with all applicable regulations.

Hazardous waste code D002: Waste Corrosive material [pH <=2 or =>12.5, or corrosive to steel]

Waste from residues / unused

products

Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions). Dispose of in accordance with local

regulations.

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal.

Since emptied containers may retain product residue, follow label warnings even after container is

emptied.

Material name: LPS® Precision Clean (Ready-to-use)

02728, 02765 Version #: 02 Revision date: 07-20-2016 Issue date: 01-07-2016 6 /

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Not available.

Annex II of MARPOL 73/78 and

the IBC Code

15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Diethanolamine (CAS 111-42-2)

Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes

Delayed Hazard - No Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

chemical

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Yes

Diethanolamine (CAS 111-42-2)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

FEMA Priority Substances Respiratory Health and Safety in the Flavor Manufacturing Workplace

Glycerin (CAS 56-81-5)

Other Flavoring Substances with OSHA PEL's

US state regulations

US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

Not listed.

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd.

(a))

Diethanolamine (CAS 111-42-2)

US. Massachusetts RTK - Substance List

Diethanolamine (CAS 111-42-2)

Dipropylene Glycol Monomethyl Ether (CAS 34590-94-8)

Glycerin (CAS 56-81-5)

US. New Jersey Worker and Community Right-to-Know Act

Diethanolamine (CAS 111-42-2)

Dipropylene Glycol Monomethyl Ether (CAS 34590-94-8)

02728, 02765 Version #: 02 Revision date: 07-20-2016 Issue date: 01-07-2016

Material name: LPS® Precision Clean (Ready-to-use)

andy to year

Glycerin (CAS 56-81-5)

US. Pennsylvania Worker and Community Right-to-Know Law

Diethanolamine (CAS 111-42-2)

Dipropylene Glycol Monomethyl Ether (CAS 34590-94-8)

Glycerin (CAS 56-81-5)

US. Rhode Island RTK

Diethanolamine (CAS 111-42-2)

US. California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

Diethanolamine (CAS 111-42-2) Listed: June 22, 2012

16. Other information, including date of preparation or last revision

 Issue date
 01-07-2016

 Revision date
 07-20-2016

Version # 02

Disclaimer Not available.

Revision information Product and Company Identification: Product and Company Identification

Hazard(s) identification: Disposal Hazard(s) identification: Prevention Hazard(s) identification: Response

Hazard(s) identification: Hazard(s) not otherwise classified (HNOC)

Hazard(s) identification: Supplemental information

Composition / Information on Ingredients: Disclosure Overrides Composition/information on ingredients: Composition comments

Material name: LPS® Precision Clean (Ready-to-use)

02728, 02765 Version #: 02 Revision date: 07-20-2016 Issue date: 01-07-2016 8 / 8