

## Eastman(TM) MPK

Version            Revision Date:            SDS Number:            Date of last issue: 11/12/2018  
2.3                05/13/2020                150000001116            Date of first issue: 09/06/2016  
PRD

---

**SECTION 1. IDENTIFICATION**

Product name                                : Eastman(TM) MPK  
Product code                                : 06548-00, P0654801, P0654806, P0654807, P0654808,  
P0654809, P0654800, E0654801

**Manufacturer or supplier's details**

Company name of supplier                : Eastman Chemical Company  
Address                                        : 200 South Wilcox Drive  
Kingsport TN 37660-5280  
Telephone                                    : (423) 229-2000  
Emergency telephone                      : CHEMTREC: +1-800-424-9300, +1-703-527-3887 CCN7321

**Recommended use of the chemical and restrictions on use**


Recommended use                          : Solvent  
Restrictions on use                        : None known.

---

**SECTION 2. HAZARDS IDENTIFICATION****GHS classification in accordance with 29 CFR 1910.1200**

Flammable liquids                         : Category 2  
Acute toxicity (Oral)                      : Category 4  
Eye irritation                                : Category 2A

**GHS label elements**

Hazard pictograms                        : 

Signal Word                                 : Danger  
Hazard Statements                         : H225 Highly flammable liquid and vapor.  
H302 Harmful if swallowed.  
H319 Causes serious eye irritation.

Precautionary Statements                : **Prevention:**  
P210 Keep away from heat/ sparks/ open flames/ hot surfaces.  
No smoking.  
P233 Keep container tightly closed.

## Eastman(TM)MPK

Version	Revision Date:	SDS Number:	Date of last issue: 11/12/2018
2.3	05/13/2020	15000001116	Date of first issue: 09/06/2016
PRD		SDSUS / Z8 / 0001	

P240 Ground/bond container and receiving equipment.  
 P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.  
 P242 Use only non-sparking tools.  
 P243 Take precautionary measures against static discharge.  
 P264 Wash skin thoroughly after handling.  
 P270 Do not eat, drink or smoke when using this product.  
 P280 Wear protective gloves/ eye protection/ face protection.

**Response:**

P301 + P312 + P330 IF SWALLOWED: Call a POISON CENTER/ doctor if you feel unwell. Rinse mouth.  
 P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.  
 P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 P337 + P313 If eye irritation persists: Get medical advice/ attention.  
 P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

**Storage:**

P403 + P235 Store in a well-ventilated place. Keep cool.

**Disposal:**

P501 Dispose of contents/ container to an approved waste disposal plant.

**Other hazards**

None known.

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS****Components**

Chemical name	CAS-No.	Concentration (% w/w)
methyl propyl ketone	107-87-9	> 90
methyl isobutyl ketone	108-10-1	< 10

**SECTION 4. FIRST AID MEASURES**

If inhaled	:	Move to fresh air. Treat symptomatically. If symptoms persist, call a physician.
In case of skin contact	:	Wash off with soap and water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur.
In case of eye contact	:	Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/ attention.

## Eastman(TM)MPK

Version	Revision Date:	SDS Number:	Date of last issue: 11/12/2018
2.3	05/13/2020	15000001116	Date of first issue: 09/06/2016
PRD		SDSUS / Z8 / 0001	

---

If swallowed : Seek medical advice.

Most important symptoms and effects, both acute and delayed : Harmful if swallowed.  
Causes serious eye irritation.  
Harmful if swallowed.  
Causes serious eye irritation.

Notes to physician : Treat symptomatically.

---

**SECTION 5. FIRE-FIGHTING MEASURES**

Suitable extinguishing media : Carbon dioxide (CO2)  
Dry chemical  
Water spray

Unsuitable extinguishing media : Water spray jet

Specific hazards during fire fighting : Water may be ineffective.  
The product will float on water and can be reignited on surface water.

Hazardous combustion products : No hazardous combustion products are known

Further information : Use water spray to cool unopened containers.

Special protective equipment for fire-fighters : Wear an approved positive pressure self-contained breathing apparatus in addition to standard fire fighting gear.

---

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protective equipment and emergency procedures : Wear appropriate personal protective equipment.  
Local authorities should be advised if significant spillages cannot be contained.

Environmental precautions : Avoid release to the environment.

Methods and materials for containment and cleaning up : Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).  
After cleaning, flush away traces with water.  
Eliminate all ignition sources if safe to do so.

---

**SECTION 7. HANDLING AND STORAGE**

Advice on protection against fire and explosion : None known.

Advice on safe handling : Avoid inhalation of vapor or mist.

---

## Eastman(TM)MPK

Version	Revision Date:	SDS Number:	Date of last issue: 11/12/2018
2.3	05/13/2020	15000001116	Date of first issue: 09/06/2016
PRD		SDSUS / Z8 / 0001	

Do not get in eyes.  
 Avoid contact with skin, eyes and clothing.  
 Do not swallow.  
 Ensure adequate ventilation.  
 Wash thoroughly after handling.  
 Keep away from fire (No Smoking).  
 Keep away from fire, sparks and heated surfaces.  
 Do not use sparking tools.

Conditions for safe storage : Keep container closed when not in use.

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

## Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
methyl propyl ketone	107-87-9	STEL	150 ppm	ACGIH
		TWA	150 ppm 530 mg/m3	NIOSH REL
		TWA	200 ppm 700 mg/m3	OSHA Z-1
		TWA	200 ppm 700 mg/m3	OSHA P0
		STEL	250 ppm 875 mg/m3	OSHA P0
methyl isobutyl ketone	108-10-1	TWA	20 ppm	ACGIH
		STEL	75 ppm	ACGIH
		ST	75 ppm 300 mg/m3	NIOSH REL
		TWA	50 ppm 205 mg/m3	NIOSH REL
		TWA	100 ppm 410 mg/m3	OSHA Z-1
		TWA	50 ppm 205 mg/m3	OSHA P0
		STEL	75 ppm 300 mg/m3	OSHA P0

Engineering measures : Ensure adequate ventilation.

## Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Hand protection

Remarks : Wear suitable gloves.

Eye protection : Wear safety glasses with side shields (or goggles).

## Eastman(TM)MPK

Version	Revision Date:	SDS Number:	Date of last issue: 11/12/2018
2.3	05/13/2020	15000001116	Date of first issue: 09/06/2016
PRD		SDSUS / Z8 / 0001	

---

Face-shield  
Always wear eye protection when the potential for inadvertent eye contact with the product cannot be excluded.

Protective measures : Remove respiratory and skin/eye protection only after vapors have been cleared from the area.  
Ensure that eye flushing systems and safety showers are located close to the working place.  
Use personal protective equipment as required.

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice.

---

## SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Color : colorless

Odor : alcohol-like

Odor Threshold : 11 ppm

pH : not determined

Melting point/range : -108 °F / -78 °C

Boiling point/boiling range : 214 °F / 101 °C

Flash point : 46.0 °F / 7.8 °C

Method: Tag closed cup

Evaporation rate : 2.3

Self-ignition : 842 °F / 450 °C  
1,013 hPa

Upper explosion limit / Upper flammability limit : 8.7 %(V)

Lower explosion limit / Lower flammability limit : 1.56 %(V)

Vapor pressure : 37 mbar (68 °F / 20 °C)

Relative vapor density : 2.9

Relative density : 0.81 (68 °F / 20 °C)

## Eastman(TM)MPK

Version	Revision Date:	SDS Number:	Date of last issue: 11/12/2018
2.3	05/13/2020	15000001116	Date of first issue: 09/06/2016
PRD		SDSUS / Z8 / 0001	

---

Solubility(ies)	
Water solubility	: Moderate
Partition coefficient: n-octanol/water	: log Pow: 0.857 (68 °F / 20 °C)
Autoignition temperature	: 840 °F / 449 °C Method: ASTM D2155
Decomposition temperature	: Method: DTA No exotherm to boiling
Viscosity	
Viscosity, dynamic	: 0.607 mPa.s (68 °F / 20 °C)
Viscosity, kinematic	: not determined
Explosive properties	: No data available
Oxidizing properties	: No data available

---

**SECTION 10. STABILITY AND REACTIVITY**

Reactivity	: Stable
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: Hazardous decomposition products formed under fire conditions.
Conditions to avoid	: Heat, flames and sparks.
Incompatible materials	: Oxidizing agents
Hazardous decomposition products	: Carbon dioxide (CO <sub>2</sub> ) Carbon monoxide

---

**SECTION 11. TOXICOLOGICAL INFORMATION****Acute toxicity**

Harmful if swallowed.

**Product:**

Acute oral toxicity	: Remarks: Harmful if swallowed.
Acute inhalation toxicity	: Remarks: No data available
Acute dermal toxicity	: Remarks: No data available

**Components:****methyl propyl ketone:**

## Eastman(TM) MPK

Version	Revision Date:	SDS Number:	Date of last issue: 11/12/2018
2.3	05/13/2020	15000001116	Date of first issue: 09/06/2016
PRD		SDSUS / Z8 / 0001	

---

Acute oral toxicity : LD50 Oral (Rat): 1,600 mg/kg

Acute inhalation toxicity : LC50 (Rat): 25.5 mg/l  
Exposure time: 4 h

**methyl isobutyl ketone:**

Acute oral toxicity : LD50 Oral (Rat): 2,080 mg/kg

Acute inhalation toxicity : LC50 (Rat): 16.4 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor

**Skin corrosion/irritation**

Not classified based on available information.

**Product:**

Remarks : No data available

**Components:****methyl propyl ketone:**

Species : Guinea pig  
Exposure time : 24 h  
Result : slight

**methyl isobutyl ketone:**

Species : Rabbit  
Exposure time : 72 h  
Result : none

**Serious eye damage/eye irritation**

Causes serious eye irritation.

**Product:**

Remarks : No data available

**Components:****methyl isobutyl ketone:**

Species : Rabbit  
Result : Eye irritation

**Respiratory or skin sensitization****Skin sensitization**

Not classified based on available information.

**Respiratory sensitization**

Not classified based on available information.

## Eastman(TM)MPK

Version	Revision Date:	SDS Number:	Date of last issue: 11/12/2018
2.3	05/13/2020	15000001116	Date of first issue: 09/06/2016
PRD		SDSUS / Z8 / 0001	

---

**Product:**

Remarks : No data available

**Germ cell mutagenicity**

Not classified based on available information.

**Components:****methyl propyl ketone:**

Genotoxicity in vitro : Test Type: Salmonella typhimurium assay (Ames test)  
Metabolic activation: +/- activation  
Method: Bacterial Reverse Mutation Assay  
Result: negative

Test Type: Mutagenicity - Mammalian  
Metabolic activation: +/- activation  
Method: In vitro Mammalian Cell Gene Mutation Test  
Result: negative

Test Type: Mutagenicity - Mammalian  
Metabolic activation: +/- activation  
Method: In vitro Mammalian Chromosome Aberration Test  
Result: negative

**Carcinogenicity**

Not classified based on available information.

**Product:**

Remarks : This information is not available.

**IARC** Group 2B: Possibly carcinogenic to humans  
methyl isobutyl ketone 108-10-1

**OSHA** No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

**NTP** No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

**Reproductive toxicity**

Not classified based on available information.

**Product:**

Effects on fertility : Remarks: No data available

**STOT-single exposure**

Not classified based on available information.

**Product:**

Remarks : No data available



## Eastman(TM) MPK

Version          Revision Date:          SDS Number:          Date of last issue: 11/12/2018  
2.3                05/13/2020                150000001116        Date of first issue: 09/06/2016  
PRD                                SDSUS / Z8 / 0001

---

**STOT-repeated exposure**

Not classified based on available information.

**Product:**

Remarks                                : No data available

**Repeated dose toxicity****Product:**

Remarks                                : No data available

**Aspiration toxicity**

Not classified based on available information.

**Product:**

No aspiration toxicity classification

**Components:****methyl propyl ketone:**

May be harmful if swallowed and enters airways.

**methyl isobutyl ketone:**

May be harmful if swallowed and enters airways.

**Information on likely routes of exposure****Product:**

Inhalation                                : Remarks: None known.

Skin contact                                : Remarks: None known.

Eye contact                                : Remarks: Causes serious eye irritation.

Ingestion                                : Remarks: Harmful if swallowed.

**Further information****Product:**

Remarks                                : None known.

---

**SECTION 12. ECOLOGICAL INFORMATION****Ecotoxicity****Components:****methyl propyl ketone:**

Toxicity to fish                                : LC50 (Pimephales promelas (fathead minnow)): 1,240 mg/l

---

## Eastman(TM)MPK

Version	Revision Date:	SDS Number:	Date of last issue: 11/12/2018
2.3	05/13/2020	15000001116	Date of first issue: 09/06/2016
PRD		SDSUS / Z8 / 0001	

Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 110 mg/l  
Exposure time: 48 h

Toxicity to algae/aquatic plants : NOEC: (Chlorella pyrenoidosa): 74 mg/l  
Exposure time: 72 h

EC50 (Chlorella pyrenoidosa): 150 mg/l  
Exposure time: 72 h

**methyl isobutyl ketone:**

Toxicity to fish : LC50 (goldfish): 460 mg/l  
Exposure time: 24 h

LC50 (golden orfe): 675 - 750 mg/l  
Exposure time: 48 h

Toxicity to daphnia and other aquatic invertebrates : LC50 (Daphnia magna (Water flea)): 4,300 mg/l  
Exposure time: 24 h

LC50 (Crangon crangon (shrimp)): 1,250 mg/l  
Exposure time: 24 h

**Persistence and degradability****Components:****methyl propyl ketone:**

Biodegradability : Result: Readily biodegradable

Biochemical Oxygen Demand (BOD) : BOD-5:  
1,380 mg/g

BOD-20:  
1,800 mg/g

Chemical Oxygen Demand (COD) : 1,800 mg/g

**methyl isobutyl ketone:**

Biodegradability : Result: Readily biodegradable

Biochemical Oxygen Demand (BOD) : BOD-5:  
1,940 - 2,060 mg/g

Chemical Oxygen Demand (COD) : 2,160 - 2,460 mg/g

ThOD : 2,720 mg/g

## Eastman(TM)MPK

Version	Revision Date:	SDS Number:	Date of last issue: 11/12/2018
2.3	05/13/2020	15000001116	Date of first issue: 09/06/2016
PRD		SDSUS / Z8 / 0001	

**Bioaccumulative potential****Components:****methyl propyl ketone:**

Partition coefficient: n-octanol/water : Pow: 0.857 (68 °F / 20 °C)

**methyl isobutyl ketone:**

Partition coefficient: n-octanol/water : Pow: 24  
log Pow: 1.38

**Mobility in soil**

No data available

**Other adverse effects**

No data available

**SECTION 13. DISPOSAL CONSIDERATIONS****Disposal methods**

Waste from residues : Dispose of in accordance with local regulations.

**SECTION 14. TRANSPORT INFORMATION****International Regulations****IATA-DGR**

UN/ID No. : UN 1224  
 Proper shipping name : Ketones, liquid, n.o.s.  
 (methyl propyl ketone, methyl isobutyl ketone)  
 Class : 3  
 Packing group : II  
 Labels : Flammable Liquids  
 Packing instruction (cargo aircraft) : 364  
 Packing instruction (passenger aircraft) : 353

**IMDG-Code**

UN number : UN 1224  
 Proper shipping name : KETONES, LIQUID, N.O.S.  
 (methyl propyl ketone, methyl isobutyl ketone)  
 Class : 3  
 Packing group : II  
 Labels : 3  
 EmS Code : F-E, S-D  
 Marine pollutant : no

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

Not applicable for product as supplied.

## Eastman(TM)MPK

Version	Revision Date:	SDS Number:	Date of last issue: 11/12/2018
2.3	05/13/2020	15000001116	Date of first issue: 09/06/2016
PRD		SDSUS / Z8 / 0001	

**Domestic regulation****49 CFR**

UN/ID/NA number	: UN 1224
Proper shipping name	: Ketones, liquid, n.o.s. (methyl propyl ketone, methyl isobutyl ketone)
Class	: 3
Packing group	: II
Labels	: FLAMMABLE LIQUID
ERG Code	: 127
Marine pollutant	: no

**Special precautions for user**

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

**SECTION 15. REGULATORY INFORMATION****EPCRA - Emergency Planning and Community Right-to-Know****CERCLA Reportable Quantity**

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
methyl isobutyl ketone	108-10-1	5000	*

\*: Calculated RQ exceeds reasonably attainable upper limit.

**SARA 304 Extremely Hazardous Substances Reportable Quantity**

This material does not contain any components with a section 304 EHS RQ.

**SARA 302 Extremely Hazardous Substances Threshold Planning Quantity**

This material does not contain any components with a section 302 EHS TPQ.

**SARA 311/312 Hazards** : Flammable (gases, aerosols, liquids, or solids)  
Acute toxicity (any route of exposure)  
Serious eye damage or eye irritation

**SARA 313** : The following components are subject to reporting levels established by SARA Title III, Section 313:

methyl isobutyl 108-10-1  
ketone

**California Prop. 65**

WARNING: This product can expose you to chemicals including methyl isobutyl ketone, which is/are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

**The ingredients of this product are reported in the following inventories:**

TSCA : All substances listed as active on the TSCA inventory

DSL : All components of this product are on the Canadian DSL

**Eastman(TM) MPK**

Version	Revision Date:	SDS Number:	Date of last issue: 11/12/2018
2.3	05/13/2020	15000001116	Date of first issue: 09/06/2016
PRD		SDSUS / Z8 / 0001	

- AICS : On the inventory, or in compliance with the inventory
- ENCS : On the inventory, or in compliance with the inventory
- ISHL : On the inventory, or in compliance with the inventory
- KECI : On the inventory, or in compliance with the inventory
- PICCS : On the inventory, or in compliance with the inventory
- IECSC : On the inventory, or in compliance with the inventory
- TCSI : On the inventory, or in compliance with the inventory

**TSCA list**


No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

**SECTION 16. OTHER INFORMATION**

**Further information**

**NFPA 704:**



**HMIS® IV:**

<b>HEALTH</b>	/	<b>2</b>
<b>FLAMMABILITY</b>		<b>3</b>
<b>PHYSICAL HAZARD</b>		<b>0</b>

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "\*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

**Full text of other abbreviations**

- ACGIH : USA. ACGIH Threshold Limit Values (TLV)
- NIOSH REL : USA. NIOSH Recommended Exposure Limits
- OSHA P0 : USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000
- OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
- ACGIH / TWA : 8-hour, time-weighted average

## Eastman(TM)MPK

Version	Revision Date:	SDS Number:	Date of last issue: 11/12/2018
2.3	05/13/2020	15000001116	Date of first issue: 09/06/2016
PRD		SDSUS / Z8 / 0001	

ACGIH / STEL	:	Short-term exposure limit
NIOSH REL / TWA	:	Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
NIOSH REL / ST	:	STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday
OSHA P0 / TWA	:	8-hour time weighted average
OSHA P0 / STEL	:	Short-term exposure limit
OSHA Z-1 / TWA	:	8-hour time weighted average

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 05/13/2020

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / Z8