## **Section 1: IDENTIFICATION**

#### 1.1 PRODUCT IDENTIFIER

Product Name: SKL-SP2 Aerosol
Product Code: Not available.

#### 1.2 RECOMMENDED USE OF CHEMICAL AND RESTRICTIONS ON USE

**Use:** Non-Destructive Testing.

#### 1.3 DETAILS OF THE SUPPLIER OF THE SAFETY DATA SHEET

Name/Address: Magnaflux

155 Harlem Avenue Glenview, Illinois

60025

**Telephone Number:** 847-657-5300

## 1.4 EMERGENCY TELEPHONE NUMBER

**Emergency Telephone Number:** CHEMTREC 800-424-9300

Date of Preparation: November 25, 2013 Version #: 1.0

## Section 2: HAZARD(S) IDENTIFICATION

## 2.1 CLASSIFICATION OF THE CHEMICAL ACCORDING TO OSHA HAZCOM 2012

# **Hazard class**

Flammable Aerosol 2 Gases Under Pressure - Compressed Gas Reproductive toxicity 2 Aspiration hazard 1

## 2.2 LABEL ELEMENTS ACCORDING TO OSHA HAZCOM 2012

#### **Hazard Pictogram:**







Signal Word: Danger

Hazard Statement: Flammable aerosol. Contains gas under pressure; may explode if

heated. Suspected of damaging fertility or the unborn child. May be

fatal if swallowed and enters airways.


**Prevention:** Keep away from heat/sparks/open flames/hot surfaces. -No

smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Obtain special instructions before use. Do not handle until all safety

precautions have been read and understood. Wear protective gloves/protective clothing/eye protection/face protection.

**Response:** If exposed or concerned: Get medical advice/attention. If swallowed:

Immediately call a poison center/doctor. Do NOT induce vomiting.



Storage: Protect from sunlight. Do not expose to temperatures exceeding

50 °C/122 °F. Store in a well-ventilated place. Store locked up.

**Disposal:** Dispose of contents and container in accordance with all local,

regional, national and international regulations.

#### 2.3 ADDITIONAL INFORMATION

Hazards not otherwise classified: Not applicable.

2 % of the mixture consists of ingredient(s) of unknown acute toxicity.

This product is a hazardous chemical as defined by NOM-018-STPS-2000.

## **Mexico Classification:**



Blue = Health Red = Flammability Yellow = Reactivity White = Special

Hazard Rating: 0 = minimal, 1 = slight, 2 = moderate, 3 = severe, 4 = extreme

# WHMIS Classification(s):

Class A - Compressed Gas Class B5 - Flammable Aerosol Class D2A - Reproductive Toxicity

## **WHMIS Hazard Symbols:**







**WHMIS Signal Word:** 


**DANGER** 

## Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

## 3.1 MIXTURES

Ingredient	UN#	H / F/ R / *	CAS No	Wt. %
			00.4=0.00.0	10 =0
Petroleum gases, liquefied, sweetened	UN1075	Not available	68476-86-8	40 - 70
White mineral oil, petroleum	Not available	Not available	8042-47-5	15 - 40
Distillates (petroleum), hydrotreated light				
naphthenic	Not available	Not available	64742-53-6	1 - 5
2-Naphthalenol, 1-[[4-				
(phenylazo)phenyl]azo]-, ar-heptyl ar',ar"-Me				
derivs.	Not available	Not available	92257-31-3	1 - 5
Ethylbenzene	UN1175	2/3/0	100-41-4	< 0.1

The exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200.



<sup>\*</sup> Per NOM-018-STPS-2000

## **Section 4: FIRST- AID MEASURES**

#### 4.1 DESCRIPTION OF THE FIRST AID MEASURE

Eye: In case of contact, immediately flush eyes with plenty of water for at

least 15 minutes, including under lids. If easy to do, remove contact

lenses, if worn, Get medical attention immediately.

Skin: In case of contact, immediately flush skin with plenty of water. Call a

physician if irritation develops and persists.

**Inhalation:** If breathing is difficult, remove to fresh air and keep at rest in a position

comfortable for breathing. Get medical advice/attention if you feel unwell.

**Ingestion:** If swallowed, do NOT induce vomiting unless directed to do so by

medical personnel. Never give anything by mouth to an unconscious

person. Get immediate medical advice/attention.

# 4.2 MOST IMPORTANT SYMPTOMS AND EFFECTS, BOTH ACUTE AND DELAYED

**Eye:** May cause eye irritation. Symptoms may include discomfort or pain,

excess blinking and tear production, with marked redness and

swelling of the conjunctiva.

**Skin:** May cause skin irritation. Symptoms may include redness, drying,

defatting and cracking of the skin.

**Inhalation:** May cause respiratory tract irritation. May cause drowsiness or dizziness.

**Ingestion:** May be fatal if swallowed and enters airways. May cause stomach

distress, nausea or vomiting. This product may be aspirated into the

lungs and cause chemical pneumonitis.

# 4.3 INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENTS NEEDED

**Note to Physicians:** Symptoms may not appear immediately.

Specific Treatments: In case of accident or if you feel unwell, seek medical advice

immediately (show the label or SDS where possible).

## **Section 5: FIRE-FIGHTING MEASURES**

## **5.1 FLAMMABILITY**

Flammability: Flammable by WHMIS/OSHA/NOM-018-STPS-2000 criteria.

## **5.2 EXTINGUISHING MEDIA**

Suitable Extinguishing Media: Foam, carbon dioxide.

Unsuitable Extinguishing Media: Water.


#### 5.3 SPECIAL HAZARDS ARISING FROM THE CHEMICAL

**Products of Combustion:** May include, and are not limited to: oxides of carbon, oxides of nitrogen.

**Explosion Data:** 

Sensitivity to Mechanical Impact: Not available.

Sensitivity to Static Discharge: Not available.



## 5.4 SPECIAL PROTECTIVE EQUIPMENT AND PRECAUTIONS FOR FIRE FIGHTERS

Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA). Use water spray to keep fire-exposed containers cool. Avoid water in straight hose stream; will scatter and spread fire. Containers may explode when heated.

#### Section 6: ACCIDENTAL RELEASE MEASURES

## 6.1 PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES

Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Eliminate sources of ignition.

## 6.2 METHODS AND MATERIALS FOR CONTAINMENT AND CLEANING - UP

**Methods for Containment:** Contain and/or absorb spill with inert material (e.g. sand, vermiculite),

then place in a suitable container. Do not flush to sewer or allow to enter waterways. Use appropriate Personal Protective Equipment (PPE).

**Methods for Cleaning-Up:** Scoop up material and place in a disposal container. Provide ventilation.

## **Section 7: HANDLING AND STORAGE**

#### 7.1 PRECAUTIONS FOR SAFE HANDLING

**Handling:** Keep away from sources of ignition. - No smoking. Do not spray on

an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Container may explode if heated. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapors/spray. Do not swallow. Use only outdoors or in a well-ventilated area. When using do not eat, drink or smoke. Use non-

sparking tools. (See section 8)

General Hygiene Advice: Launder contaminated clothing before reuse. Wash hands before

eating, drinking, or smoking.

## 7.2 CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES

Storage: Keep out of the reach of children. Store locked up. Protect from

sunlight. Do not store at temperatures above 50 °C / 122 °F. Store in


a well-ventilated place. (See section 10)

# Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

## **8.1 CONTROL PARAMETERS**

# **Exposure Guidelines**

Occupational Exposure Limits				
Ingredient	OSHA-PEL	ACGIH-TLV		
Petroleum gases, liquefied, sweetened	1000 ppm	1000 ppm		
White mineral oil, petroleum	Not available.	Not available.		
Distillates (petroleum), hydrotreated light naphthenic	5 mg/m³ (mist)	5 mg/m³ (mist)		
2-Naphthalenol, 1-[[4-(phenylazo)phenyl]azo]-, ar-heptyl				
ar',ar"-Me derivs.	Not available.	Not available.		
Ethylbenzene	100 ppm	20 ppm		



# **8.2 EXPOSURE CONTROLS**

Engineering Controls: Use ventilation adequate to keep exposures (airborne levels of dust,

fume, vapor, etc.) below recommended exposure limits.

#### **8.3 INDIVIDUAL PROTECTIVE MEASURES**

**Personal Protective Equipment:** 

**Eye/Face Protection:** Safety glasses or goggles are recommended when using product.

**Skin Protection:** 

Hand Protection: Chemical-resistant gloves.

Body Protection: Wear suitable protective clothing.

**Respiratory Protection:** In case of insufficient ventilation, wear suitable respiratory equipment.

Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the

selected respirator.

**General Health and Safety** 

Measures:

Do not eat, smoke or drink where material is handled, processed or stored. Wash hands carefully before eating or smoking. Handle according to established industrial hygiene and safety practices.

#### **Section 9: PHYSICAL AND CHEMICAL PROPERTIES**

#### 9.1 INFORMATION ON BASIC PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Oily.

Color: Dark red.

Odor: Mild oily odor.

Odor Threshold: Not available.

Physical State: Gas/Pressurized Liquid.

pH: Neutral.

Melting Point/Freezing Point: Not available.

Initial Boiling Point and Boiling Range: ~ 235 °C (~ 455 °F)

Flash Point: Not applicable.

**Evaporation Rate:** Negligible. Flammability: Flammable.

Lower Flammability/Explosive Limit: 1%
Upper Flammability/Explosive Limit: 6%

Vapor Pressure: 60 psi @ 24°C (75 °F)

Vapor Density: >1 (Air= 1)

Relative Density/Specific Gravity: 0.89


Solubility: Insoluble

Partition coefficient: n-octanol/water: Not available.

Auto-ignition Temperature: Not available.

Decomposition Temperature: Not available.

Trade Name: SKL-SP2 Aerosol Print date: 2013-11-25



Viscosity: 4 cSt

Oxidizing Properties: Not available.

Explosive Properties: Not available.

#### Section 10: STABILITY AND REACTIVITY

#### **10.1 REACTIVITY**

No dangerous reaction known under conditions of normal use.

#### **10.2 CHEMICAL STABILITY**

Stable under normal storage conditions. Contents under pressure. Container may explode if heated. Do not pierce or burn, even after use.

## 10.3 POSSIBILITY OF HAZARDOUS REACTIONS

No dangerous reaction known under conditions of normal use.

# **10.4 CONDITIONS TO AVOID**

Heat. Incompatible materials. Sources of ignition.

## 10.5 INCOMPATIBLE MATERIALS

Strong oxidizing agents.

#### 10.6 HAZARDOUS DECOMPOSITION PRODUCTS

May include, and are not limited to: oxides of carbon, oxides of nitrogen.

# **Section 11: TOXICOLOGICAL INFORMATION**

# 11.1 INFORMATION ON TOXICOLOGICAL EFFECTS

**Likely Routes of Exposure:** Skin contact, eye contact, inhalation, and ingestion.

# Symptoms related to physical/chemical/toxicological characteristics:

**Eye:** May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva.

**Skin:** May cause skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin.

Ingestion: May be fatal if swallowed and enters airways. May cause stomach

distress, nausea or vomiting. This product may be aspirated into the lungs

and cause chemical pneumonitis.

**Inhalation:** May cause respiratory tract irritation. May cause drowsiness or dizziness.

## **Acute Toxicity:**

Ingredient	IDLH	LC50	LD50
Petroleum gases, liquefied,		Inhalation 658 mg/L	
sweetened	Not available.	4h, rat	Not available.
		Inhalation >5 mg/L	Oral >5000 mg/kg, rat
White mineral oil, petroleum	Not available.	4h, rat	Dermal >2000 mg/kg, rabbit
Distillates (petroleum),		Inhalation <5.7	Oral >5000 mg/kg, rat
hydrotreated light naphthenic	Not available.	mg/L 4h, rat	Dermal >2000 mg/kg, rabbit

2-Naphthalenol, 1-[[4- (phenylazo)phenyl]azo]-, ar-			
heptyl ar',ar''-Me derivs.	Not available.	Not available.	Not available.
		Inhalation 17.2	Oral 3500 mg/kg, rat
Ethylbenzene	800 ppm	mg/L 4h, rat	Dermal 15354 mg/kg, rabbit

Calculated overall Chemical Acute Toxicity Values					
LC50 (inhalation) LD50 (oral) LD50 (dermal)					
> 5 mg/L 4h, rat > 2000 mg/kg, rat > 2000 mg/kg, rabbit					

Ingredient	Chemical Listed as Carcinogen or Potential Carcinogen (NTP, IARC, OSHA, ACGIH, CP65)*
Petroleum gases, liquefied, sweetened	Not listed.
White mineral oil, petroleum	Not listed.
Distillates (petroleum), hydrotreated light naphthenic	Not listed.
2-Naphthalenol, 1-[[4-(phenylazo)phenyl]azo]-, ar-	
heptyl ar',ar''-Me derivs.	Not listed.
Ethylbenzene	O, G-A3, I-2B, CP65

<sup>\*</sup> See Section 15 for more information.

# 11.2 DELAYED, IMMEDIATE, AND CHRONIC EFFECTS OF SHORT- AND LONG-TERM EXPOSURE

Skin Corrosion/Irritation:Based on available data, the classification criteria are not met.Serious Eye Damage/Irritation:Based on available data, the classification criteria are not met.Respiratory Sensitization:Based on available data, the classification criteria are not met.Skin Sensitization:Based on available data, the classification criteria are not met.STOT-Single Exposure:Based on available data, the classification criteria are not met.

**Chronic Health Effects:** 

Carcinogenicity: Based on available data, the classification criteria are not met.

Germ Cell Mutagenicity: Based on available data, the classification criteria are not met.

Reproductive Toxicity:

**Developmental:** Suspected of damaging the unborn child.

**Teratogenicity:** Based on available data, the classification criteria are not met. **Embryotoxicity:** Based on available data, the classification criteria are not met.


Fertility: Suspected of damaging fertility.

STOT-Repeated Exposure: Based on available data, the classification criteria are not met.

**Aspiration Hazard:** May be fatal if swallowed and enters airways.

**Toxicologically Synergistic** 

Materials:Not available.Other Information:Not available.



# **Section 12: ECOLOGICAL INFORMATION**

#### 12.1 ECOTOXICITY

Acute/Chronic Toxicity: May cause long-term adverse effects in the aquatic environment.

# 12.2 PERSISTENCE AND DEGRADABILITY

Not available.

## 12.3 BIOACCUMULATIVE POTENTIAL

Bioaccumulation: Not available.

#### **12.4 MOBILITY IN SOIL**

Not available.

#### 12.5 OTHER ADVERSE EFFECTS

Floats on water.

#### Section 13: DISPOSAL CONSIDERATIONS

#### 13.1 WASTE TREATMENT METHODS

**Disposal Method:** This material must be disposed of in accordance with all

local, state, provincial, and federal regulations.

Other disposal recommendations: Not available.

## **Section 14: TRANSPORT INFORMATION**

# **14.1 UN NUMBER**

DOT TDG NOM-004-SCT2-1994

UN1950 UN1950 UN1950

**14.2 UN PROPER SHIPPING NAME** 

DOT TDG NOM-004-SCT2-1994

Aerosols, flammable Aerosols, flammable Aerosols, flammable

14.3 TRANSPORT HAZARD CLASS (ES)

DOT TDG NOM-004-SCT2-1994

2.1 2.1

14.4 PACKING GROUP

DOT TDG NOM-004-SCT2-1994

Not applicable. Not applicable. Not applicable.

#### 14.5 ENVIRONMENTAL HAZARDS

Not available.

#### 14.6 TRANSPORT IN BULK ACCORDING TO ANNEX II OF MARPOL 73/78 AND THE IBC CODE

Not available.

## 14.7 SPECIAL PRECAUTIONS FOR USER

Do not handle until all safety precautions have been read and understood.



# **Section 15: REGULATORY INFORMATION**

# 15.1 SAFETY, HEALTH AND ENVIRONMENTAL REGULATIONS/ LEGISLATIONS SPECIFIC FOR THE CHEMICAL

**Canada:** This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

**US:** MSDS prepared pursuant to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

Mexico: MSDS prepared pursuant to NOM-018-STPS-2000.

SARA Title III				
Ingredient	Section 313			
Petroleum gases, liquefied,				
sweetened	Not listed.	Not listed.	Not listed.	Not listed.
White mineral oil, petroleum	Not listed.	Not listed.	Not listed.	Not listed.
Distillates (petroleum),				
hydrotreated light naphthenic	Not listed.	Not listed.	Not listed.	Not listed.
2-Naphthalenol, 1-[[4-				
(phenylazo)phenyl]azo]-, ar-				
heptyl ar',ar"-Me derivs.	Not listed.	Not listed.	Not listed.	Not listed.
Ethylbenzene	Not listed.	Not listed.	1,000	313

# **State Regulations**

# California Proposition 65:

This product contains a chemical known to the State of California to cause cancer.

#### **Global Inventories:**


Ingredient	Canada DSL/NDSL	USA TSCA
Petroleum gases, liquefied, sweetened	DSL	Yes.
White mineral oil, petroleum	DSL	Yes.
Distillates (petroleum), hydrotreated light naphthenic	DSL	Yes.
2-Naphthalenol, 1-[[4-(phenylazo)phenyl]azo]-, ar-heptyl ar',ar"-Me derivs.	DSL	Yes.
Ethylbenzene	DSL	Yes.

NFPA-National Fire Protection Association:				
Health: 1				
Fire: 4				
Reactivity:				

HMIS-Hazardous Materials Identification System:			
Health: 1*			
Fire: 4			
Physical Hazard: 0			

**Hazard Rating:** 0 = minimal, 1 = slight, 2 = moderate, 3 = severe, 4 = extreme

Trade Name: SKL-SP2 Aerosol Print date: 2013-11-25



## SOURCE AGENCY CARCINOGEN CLASSIFICATIONS:

CP65 California Proposition 65

OSHA (O) Occupational Safety and Health Administration.

ACGIH (G) American Conference of Governmental Industrial Hygienists.

A1 - Confirmed human carcinogen.

A2 - Suspected human carcinogen.

A3 - Animal carcinogen.

A4 - Not classifiable as a human carcinogen.

A5 - Not suspected as a human carcinogen.

# IARC (I) International Agency for Research on Cancer.

1 - The agent (mixture) is carcinogenic to humans.

2A - The agent (mixture) is probably carcinogenic to humans; there is limited evidence of carcinogenicity in humans and sufficient evidence of carcinogenicity in experimental animals.

2B - The agent (mixture) is possibly carcinogenic to humans; there is limited evidence of carcinogenicity in humans in the absence of sufficient evidence of carcinogenicity in experimental animals.

3 - The agent (mixture, exposure circumstance) is not classifiable as to its carcinogenicity to humans.

4 - The agent (mixture, exposure circumstance) is probably not carcinogenic to humans.

# NTP (N) National Toxicology Program.

1 - Known to be carcinogens.

2 - Reasonably anticipated to be carcinogens.

#### **Section 16: OTHER INFORMATION**

**Date of Preparation:** November 25, 2013 **Expiry Date:** November 25, 2016

Version: 1.0

Revision Date: November 25, 2013

**Disclaimer:** We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.

Prepared by: Nexreg Compliance Inc.

Phone: (519) 488-5126

www.nexreg.com

Prepared for: Magnaflux

**End of Safety Data Sheet** 

## **Section 1: IDENTIFICATION**

#### 1.1 PRODUCT IDENTIFIER

Product Name: SKC-S Aerosol
Product Code: Not available.

# 1.2 RECOMMENDED USE OF CHEMICAL AND RESTRICTIONS ON USE

**Use:** Non-Destructive Testing.

#### 1.3 DETAILS OF THE SUPPLIER OF THE SAFETY DATA SHEET

Name/Address: Magnaflux

155 Harlem Avenue Glenview, Illinois

60025

**Telephone Number:** 847-657-5300

## 1.4 EMERGENCY TELEPHONE NUMBER

**Emergency Telephone Number:** CHEMTREC 800-424-9300

Date of Preparation: January 16, 2015 Version #: 2.0

## Section 2: HAZARD(S) IDENTIFICATION

## 2.1 CLASSIFICATION OF THE CHEMICAL ACCORDING TO OSHA HAZCOM 2012

## **Hazard class**

Flammable aerosol 1
Gases under pressure - Compressed gas
Acute toxicity 4 – Inhalation
Skin irritant 2
Specific target organ toxicity - Single exposure 3
Aspiration hazard 1

#### 2.2 LABEL ELEMENTS ACCORDING TO OSHA HAZCOM 2012

# **Hazard Pictogram:**









Signal Word: Danger

Hazard Statement: Extremely flammable aerosol. Contains gas under pressure; may

explode if heated. Harmful if inhaled. Causes skin irritation. May cause drowsiness or dizziness. May be fatal if swallowed and enters airways.

**Prevention:** Keep away from heat/sparks/open flames/hot surfaces. -No

smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid breathing dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area. Wash hands thoroughly after handling. Wear

protective gloves.

**Response:** If inhaled: Remove person to fresh air and keep comfortable for

breathing. Call a poison center/doctor if you feel unwell. If on skin: Wash with plenty of water. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention. If swallowed: Immediately call a poison

center/doctor. Do NOT induce vomiting.

Storage: Protect from sunlight. Do not expose to temperatures exceeding

50 °C/122 °F. Store in a well-ventilated place. Store locked up.

**Disposal:** Dispose of contents and container in accordance with all local,

regional, national and international regulations.

#### 2.3 ADDITIONAL INFORMATION

Hazards not otherwise classified: Not applicable.

4 % of the mixture consists of ingredient(s) of unknown acute toxicity.

This product is a hazardous chemical as defined by NOM-018-STPS-2000.

#### **Mexico Classification:**



Blue = Health Red = Flammability Yellow = Reactivity White = Special

Hazard Rating: 0 = minimal, 1 = slight, 2 = moderate, 3 = severe, 4 = extreme

# WHMIS Classification(s):

Class A - Compressed Gas Class B5 - Flammable Aerosol Class D1B - Toxic Material Class D2B - Skin Irritant

## **WHMIS Hazard Symbols:**









WHMIS Signal Word:

DANGER

## Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

# 3.1 MIXTURES

Trade Name: SKC-S Aerosol

Ingredient	UN#	H/F/R/*	CAS No	Wt. %
Distillates (petroleum), light distillate				
hydrotreating process, low-boiling	Not available	Not available	68410-97-9	60 - 100
Carbon dioxide	UN1013	1/0/0	124-38-9	1 - 5

The exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200.

## \* Per NOM-018-STPS-2000

## **Section 4: FIRST- AID MEASURES**

# 4.1 DESCRIPTION OF THE FIRST AID MEASURE

Eye: In case of contact, immediately flush eyes with plenty of water. Remove

contact lenses, if worn. If irritation persists, get medical attention.

**Skin:** In case of contact, immediately flush skin with plenty of water.

Remove contaminated clothing and shoes. Wash clothing before

reuse. Call a physician if irritation develops and persists.

**Inhalation:** If inhaled, remove to fresh air. If not breathing, give artificial

respiration. If breathing is difficult, give oxygen. Get medical advice/

attention if you feel unwell.

**Ingestion:** Do NOT induce vomiting. Never give anything by mouth to an

unconscious person. Get immediate medical advice/attention.

## 4.2 MOST IMPORTANT SYMPTOMS AND EFFECTS, BOTH ACUTE AND DELAYED

**Eye:** May cause eye irritation. Symptoms may include discomfort or pain,

excess blinking and tear production, with marked redness and

swelling of the conjunctiva.

**Skin:** Causes skin irritation. Symptoms may include redness, edema,

drying, defatting and cracking of the skin.

Inhalation: Harmful if inhaled. May cause respiratory tract irritation. May cause

drowsiness or dizziness.

**Ingestion:** May be fatal if swallowed and enters airways. May cause stomach

distress, nausea or vomiting. This product may be aspirated into the

lungs and cause chemical pneumonitis.

# 4.3 INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENTS NEEDED

**Note to Physicians:** Symptoms may not appear immediately.

Specific Treatments: In case of accident or if you feel unwell, seek medical advice

immediately (show the label or SDS where possible).

#### Section 5: FIRE-FIGHTING MEASURES

#### 5.1 FLAMMABILITY

Flammability: Flammable by WHMIS/OSHA/NOM-018-STPS-2000 criteria.

**5.2 EXTINGUISHING MEDIA** 

Suitable Extinguishing Media: Foam, carbon dioxide.

Unsuitable Extinguishing Media: Water.

# 5.3 SPECIAL HAZARDS ARISING FROM THE CHEMICAL

**Products of Combustion:** May include, and are not limited to: oxides of carbon.

**Explosion Data:** 

Sensitivity to Mechanical Impact: Not available.

Sensitivity to Static Discharge: Not available.



## 5.4 SPECIAL PROTECTIVE EQUIPMENT AND PRECAUTIONS FOR FIRE FIGHTERS

Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA). Use water spray to keep fire-exposed containers cool. Avoid water in straight hose stream; will scatter and spread fire. Containers may explode when heated. Spills of this material are a slipping hazard.

#### Section 6: ACCIDENTAL RELEASE MEASURES

## 6.1 PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES

Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Eliminate sources of ignition.

#### 6.2 METHODS AND MATERIALS FOR CONTAINMENT AND CLEANING - UP

**Methods for Containment:** Contain and/or absorb spill with inert material (e.g. sand, vermiculite),

then place in a suitable container. Do not flush to sewer or allow to enter waterways. Use appropriate Personal Protective Equipment (PPE).

**Methods for Cleaning-Up:** Scoop up material and place in a disposal container. Provide ventilation.

## **Section 7: HANDLING AND STORAGE**

## 7.1 PRECAUTIONS FOR SAFE HANDLING

**Handling:** Keep away from sources of ignition. - No smoking. Do not spray on

an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Container may explode if heated. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapors/spray. Do not swallow. Use only outdoors or in a well-ventilated area. When using do not eat, drink or smoke. Use non-

sparking tools. (See section 8)

General Hygiene Advice: Launder contaminated clothing before reuse. Wash hands before

eating, drinking, or smoking.

## 7.2 CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES

Storage: Keep out of the reach of children. Store locked up. Protect from

sunlight. Do not store at temperatures above 50 °C / 122 °F. Store in

a well-ventilated place. (See section 10)

# Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

## **8.1 CONTROL PARAMETERS**


## **Exposure Guidelines**

Occupational Exposure Limits		
Ingredient	OSHA-PEL	ACGIH-TLV
Distillates (petroleum), light distillate hydrotreating process, low-boiling	Not available.	Not available.
Carbon dioxide	5000 ppm	5000 ppm

# **8.2 EXPOSURE CONTROLS**

**Engineering Controls:** Use ventilation adequate to keep exposures (airborne levels of dust,

fume, vapor, etc.) below recommended exposure limits.



## **8.3 INDIVIDUAL PROTECTIVE MEASURES**

**Personal Protective Equipment:** 

Eye/Face Protection: Safety glasses or goggles are recommended when using product.

**Skin Protection:** 

Hand Protection: Chemical-resistant gloves.

**Body Protection:** Wear suitable protective clothing.

Respiratory Protection: In case of insufficient ventilation, wear suitable respiratory equipment.

Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the

selected respirator.

General Health and Safety

Measures:

Do not eat, smoke or drink where material is handled, processed or stored. Wash hands carefully before eating or smoking. Handle according to established industrial hygiene and safety practices.

# **Section 9: PHYSICAL AND CHEMICAL PROPERTIES**

# 9.1 INFORMATION ON BASIC PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Clear.

**Color:** Colorless to pale straw.

Odor: Hydrocarbon.
Odor Threshold: Not available.

Physical State: Gas/pressurized liquid.

pH: Not available.Melting Point/Freezing Point: Not available.

Initial Boiling Point and Boiling Range: > 118 °C (> 245 °F)

Flash Point: Not applicable.

**Evaporation Rate:** 0.987 ASTM D1901

Flammability: Flammable.

Lower Flammability/Explosive Limit: Not available.

Upper Flammability/Explosive Limit: Not available.

Vapor Pressure: 10 torr @ 20 °C (68 °F) ASTM D2879

Vapor Density: Not available.

Relative Density/Specific Gravity: 0.727


Solubility: Negligible.

Partition coefficient: n-octanol/water: Not available.

Auto-ignition Temperature: Not available.

Decomposition Temperature: Not available.

Viscosity: 7.8 cSt



Oxidizing Properties:

Not available.

Explosive Properties:

Not available.

## Section 10: STABILITY AND REACTIVITY

#### **10.1 REACTIVITY**

No dangerous reaction known under conditions of normal use.

#### 10.2 CHEMICAL STABILITY

Stable under normal storage conditions. Contents under pressure. Container may explode if heated. Do not pierce or burn, even after use.

#### 10.3 POSSIBILITY OF HAZARDOUS REACTIONS

No dangerous reaction known under conditions of normal use.

#### **10.4 CONDITIONS TO AVOID**

Heat. Incompatible materials. Sources of ignition.

# **10.5 INCOMPATIBLE MATERIALS**

Strong oxidizing agents.

# **10.6 HAZARDOUS DECOMPOSITION PRODUCTS**

May include, and are not limited to: oxides of carbon.

#### Section 11: TOXICOLOGICAL INFORMATION

#### 11.1 INFORMATION ON TOXICOLOGICAL EFFECTS

**Likely Routes of Exposure:** Skin contact, eye contact, inhalation, and ingestion.

## Symptoms related to physical/chemical/toxicological characteristics:

Eye: May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva.

**Skin:** Causes skin irritation. Symptoms may include redness, edema, drying, defatting and cracking of the skin.

Ingestion: May be fatal if swallowed and enters airways. May cause stomach

distress, nausea or vomiting. This product may be aspirated into the lungs

and cause chemical pneumonitis.

**Inhalation:** Harmful if inhaled. May cause respiratory tract irritation. May cause

drowsiness or dizziness.

## **Acute Toxicity:**

Ingredient	IDLH	LC50	LD50
Distillates (petroleum), light distillate hydrotreating process, low-boiling	Not available.	Inhalation 2.18 mg/l/4h, rat	Oral >5000 mg/kg, rat Dermal >2000 mg/kg, rabbit
Carbon dioxide	40,000 ppm	Not available.	Not available.

Calculated overall Chemical Acute Toxicity Values				
LC50 (inhalation) LD50 (oral) LD50 (dermal)				
>1.0 but ≤5.0 mg/l/4h, rat > 2000 mg/kg, rat > 2000 mg/kg, rabbit				



Ingredient	Chemical Listed as Carcinogen or Potential Carcinogen (NTP, IARC, OSHA, ACGIH, CP65)*
Distillates (petroleum), light distillate hydrotreating process,	
low-boiling	Not listed.
Carbon dioxide	Not listed.

<sup>\*</sup> See Section 15 for more information.

## 11.2 DELAYED, IMMEDIATE, AND CHRONIC EFFECTS OF SHORT- AND LONG-TERM EXPOSURE

**Skin Corrosion/Irritation:** Causes skin irritation.

Serious Eye Damage/Irritation:

Respiratory Sensitization:

Based on available data, the classification criteria are not met.

Based on available data, the classification criteria are not met.

Based on available data, the classification criteria are not met.

Based on available data, the classification criteria are not met.

**STOT-Single Exposure:** May cause drowsiness or dizziness.

**Chronic Health Effects:** 

Carcinogenicity: Based on available data, the classification criteria are not met.

Germ Cell Mutagenicity: Based on available data, the classification criteria are not met.

**Reproductive Toxicity:** 

Developmental: Based on available data, the classification criteria are not met.
 Teratogenicity: Based on available data, the classification criteria are not met.
 Embryotoxicity: Based on available data, the classification criteria are not met.
 Fertility: Based on available data, the classification criteria are not met.

STOT-Repeated Exposure: Based on available data, the classification criteria are not met.

**Aspiration Hazard:** May be fatal if swallowed and enters airways.

**Toxicologically Synergistic Materials:** Not available. **Other Information:** Not available.

## **Section 12: ECOLOGICAL INFORMATION**

# **12.1 ECOTOXICITY**

Acute/Chronic Toxicity: May cause long-term adverse effects in the aquatic environment.

## 12.2 PERSISTENCE AND DEGRADABILITY

Not available.

# 12.3 BIOACCUMULATIVE POTENTIAL


Bioaccumulation: Not available.

**12.4 MOBILITY IN SOIL** 

Not available.

# 12.5 OTHER ADVERSE EFFECTS

Not available.



# **Section 13: DISPOSAL CONSIDERATIONS**

#### 13.1 WASTE TREATMENT METHODS

**Disposal Method:** This material must be disposed of in accordance with all

local, state, provincial, and federal regulations.

Other disposal recommendations: Not available.

## **Section 14: TRANSPORT INFORMATION**

#### **14.1 UN NUMBER**

DOT TDG NOM-004-SCT2-1994

UN1950 UN1950 UN1950

14.2 UN PROPER SHIPPING NAME

DOT TDG NOM-004-SCT2-1994

Aerosols, flammable Aerosols, flammable Aerosols, flammable

14.3 TRANSPORT HAZARD CLASS (ES)

DOT TDG NOM-004-SCT2-1994

2.1 2.1

**14.4 PACKING GROUP** 

DOT TDG NOM-004-SCT2-1994

Not applicable. Not applicable. Not applicable.

# 14.5 ENVIRONMENTAL HAZARDS

Not available.

## 14.6 TRANSPORT IN BULK ACCORDING TO ANNEX II OF MARPOL 73/78 AND THE IBC CODE

Not available.

# 14.7 SPECIAL PRECAUTIONS FOR USER

Do not handle until all safety precautions have been read and understood.


#### **Section 15: REGULATORY INFORMATION**

# 15.1 SAFETY, HEALTH AND ENVIRONMENTAL REGULATIONS/ LEGISLATIONS SPECIFIC FOR THE CHEMICAL

**Canada:** This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

**US:** MSDS prepared pursuant to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

Mexico: MSDS prepared pursuant to NOM-018-STPS-2000.



SARA Title III					
Ingredient Section 302 Section 304 CERCLA Section (EHS) TPQ (Ibs.) EHS RQ (Ibs.) RQ (Ibs.) 313					
Distillates (petroleum), light distillate hydrotreating process, low-boiling Not listed. Not listed. Not listed. Not listed.					
Carbon dioxide	Not listed.	Not listed.	Not listed.	Not listed.	

## **State Regulations**

## **California Proposition 65:**

This product does not contain a chemical known to the State of California to cause cancer, birth defects or other reproductive harm.

#### **Global Inventories:**

Ingredient	Canada DSL/NDSL	USA TSCA
Distillates (petroleum), light distillate hydrotreating process, low-boiling	DSL	Yes.
Carbon dioxide	DSL	Yes.

NFPA-National Fire Protection Association:			
Health: 2			
Fire: 3			
Reactivity: 0			

HMIS-Hazardous Materials Identification System:			
Health: 2			
Fire: 3			
Physical Hazard: 0			

**Hazard Rating:** 0 = minimal, 1 = slight, 2 = moderate, 3 = severe, 4 = extreme

# SOURCE AGENCY CARCINOGEN CLASSIFICATIONS:

CP65 California Proposition 65

OSHA (O) Occupational Safety and Health Administration.

ACGIH (G) American Conference of Governmental Industrial Hygienists.

A1 - Confirmed human carcinogen.

A2 - Suspected human carcinogen.

A3 - Animal carcinogen.

A4 - Not classifiable as a human carcinogen.

A5 - Not suspected as a human carcinogen.

## IARC (I) International Agency for Research on Cancer.

1 - The agent (mixture) is carcinogenic to humans.

2A - The agent (mixture) is probably carcinogenic to humans; there is limited evidence of carcinogenicity in humans and sufficient evidence of carcinogenicity in experimental animals.

2B - The agent (mixture) is possibly carcinogenic to humans; there is limited evidence of carcinogenicity in humans in the absence of sufficient evidence of carcinogenicity in experimental animals.

3 - The agent (mixture, exposure circumstance) is not classifiable as to its carcinogenicity to humans.


4 - The agent (mixture, exposure circumstance) is probably not carcinogenic to humans.

# NTP (N) National Toxicology Program.

1 - Known to be carcinogens.

2 - Reasonably anticipated to be carcinogens.

Trade Name: SKC-S Aerosol Print date: 2015-01-16



# **Section 16: OTHER INFORMATION**

Date of Preparation: January 16, 2015

Expiry Date: January 16, 2018

Version: 2.0

Revision Date: January 16, 2015

**Disclaimer:** We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.

Prepared by: Nexreg Compliance Inc.

Phone: (519) 488-5126

www.nexreg.com

Prepared for: Magnaflux

**End of Safety Data Sheet** 

## **Section 1: IDENTIFICATION**

#### 1.1 PRODUCT IDENTIFIER

Product Name: SKD-S2 Aerosol
Product Code: Not available.

# 1.2 RECOMMENDED USE OF CHEMICAL AND RESTRICTIONS ON USE

**Use:** Non-Destructive Testing.

#### 1.3 DETAILS OF THE SUPPLIER OF THE SAFETY DATA SHEET

Name/Address: Magnaflux

155 Harlem Avenue Glenview, Illinois

60025

**Telephone Number:** 847-657-5300

## 1.4 EMERGENCY TELEPHONE NUMBER

**Emergency Telephone Number:** CHEMTREC 800-424-9300

Date of Preparation: November 25, 2013 Version #: 1.0

## Section 2: HAZARD(S) IDENTIFICATION

## 2.1 CLASSIFICATION OF THE CHEMICAL ACCORDING TO OSHA HAZCOM 2012

## **Hazard class**

Flammable Aerosol 1

Gases Under Pressure - Compressed Gas

Eye irritation 2A

Specific target organ toxicity - Single exposure 3 Specific target organ toxicity - Repeated exposure 1

# 2.2 LABEL ELEMENTS ACCORDING TO OSHA HAZCOM 2012

# **Hazard Pictogram:**









Signal Word: Danger

Hazard Statement: Extremely flammable aerosol. Contains gas under pressure; may

explode if heated. Causes serious eye irritation. May cause drowsiness or dizziness. Causes damage to lungs through

prolonged or repeated exposure.

**Prevention:** Keep away from heat/sparks/open flames/hot surfaces. -No

smoking. Do not spray on an open flame or other ignition source.

Pressurized container: Do not pierce or burn, even after use. Wash

hands thoroughly after handling. Wear eye protection/face protection. Use only outdoors or in a well-ventilated area. Do not breathe dust/fume/gas/mist/vapors/spray. Do not eat, drink or

smoke when using this product.

**Response:** If in eyes: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a

poison center/doctor if you feel unwell.

Storage: Protect from sunlight. Do not expose to temperatures exceeding

50 °C/122 °F. Store in a well-ventilated place. Store locked up.

**Disposal:** Dispose of contents and container in accordance with all local,

regional, national and international regulations.

# 2.3 ADDITIONAL INFORMATION

Hazards not otherwise classified: Not applicable.

2 % of the mixture consists of ingredient(s) of unknown acute toxicity.

This product is a hazardous chemical as defined by NOM-018-STPS-2000.

## **Mexico Classification:**



Blue = Health Red = Flammability Yellow = Reactivity White = Special

Hazard Rating: 0 = minimal, 1 = slight, 2 = moderate, 3 = severe, 4 = extreme

# WHMIS Classification(s):

Class A - Compressed Gas Class B5 - Flammable Aerosol Class D2A - Chronic Toxic Effects

Class D2B - Eye Irritant

## **WHMIS Hazard Symbols:**







**WHMIS Signal Word:** 

DANGER

## Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

## 3.1 MIXTURES

Ingredient	UN#	H / F/ R / *	CAS No	Wt. %
Isopropanol	UN1219	1/3/0	67-63-0	30 - 60
Petroleum gases, liquefied, sweetened	UN1075	Not available.	68476-86-8	15 - 40
Acetone	UN1090	1/3/0	67-64-1	10 - 30
Ceramic materials and wares, chemicals	Not available.	Not available.	66402-68-4	3 - 7
Talc	Not available.	Not available.	14807-96-6	1 - 5

Trade Name: SKD-S2 Aerosol Print date: 2013-11-25



Silica, crystalline, quartz Not a	ailable. Not available. 14808-60-7	< 0.1
-----------------------------------	------------------------------------	-------

The exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200.

#### **Section 4: FIRST- AID MEASURES**

## 4.1 DESCRIPTION OF THE FIRST AID MEASURE

**Eye:** In case of contact, immediately flush eyes with plenty of water for at

least 15 minutes, including under lids. If easy to do, remove contact

lenses, if worn. Get medical attention immediately.

Skin: In case of contact, immediately flush skin with plenty of water. Call a

physician if irritation develops and persists.

**Inhalation:** If breathing is difficult, remove to fresh air and keep at rest in a position

comfortable for breathing. Get medical advice/attention if you feel unwell.

**Ingestion:** If swallowed, do NOT induce vomiting unless directed to do so by

medical personnel. Never give anything by mouth to an unconscious

person. Get immediate medical advice/attention.

#### 4.2 MOST IMPORTANT SYMPTOMS AND EFFECTS. BOTH ACUTE AND DELAYED

Eye: Causes serious eye irritation. Symptoms may include discomfort or

pain, excess blinking and tear production, with marked redness and

swelling of the conjunctiva.

**Skin:** May cause skin irritation. Symptoms may include redness, drying,

defatting and cracking of the skin.

**Inhalation:** May cause respiratory tract irritation. May cause drowsiness or dizziness.

Ingestion: May be harmful if swallowed. May cause stomach distress, nausea

or vomiting.

## 4.3 INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENTS NEEDED

**Note to Physicians:** Symptoms may not appear immediately.

Specific Treatments: In case of accident or if you feel unwell, seek medical advice

immediately (show the label or SDS where possible).

#### **Section 5: FIRE-FIGHTING MEASURES**

#### **5.1 FLAMMABILITY**

Flammability: Flammable by WHMIS/OSHA/NOM-018-STPS-2000 criteria.

**5.2 EXTINGUISHING MEDIA** 

Suitable Extinguishing Media: Water, foam, carbon dioxide.

Unsuitable Extinguishing Media: Not available.

5.3 SPECIAL HAZARDS ARISING FROM THE CHEMICAL

**Products of Combustion:** May include, and are not limited to: oxides of carbon.

**Explosion Data:** 

Sensitivity to Mechanical Impact: Not available.

<sup>\*</sup> Per NOM-018-STPS-2000

Sensitivity to Static Discharge: Not available.

# 5.4 SPECIAL PROTECTIVE EQUIPMENT AND PRECAUTIONS FOR FIRE FIGHTERS

Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA). Use water spray to keep fire-exposed containers cool. Containers may explode when heated.

## **Section 6: ACCIDENTAL RELEASE MEASURES**

#### 6.1 PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES

Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Eliminate sources of ignition.

# 6.2 METHODS AND MATERIALS FOR CONTAINMENT AND CLEANING - UP

**Methods for Containment:** Contain and/or absorb spill with inert material (e.g. sand, vermiculite),

then place in a suitable container. Do not flush to sewer or allow to enter waterways. Use appropriate Personal Protective Equipment (PPE).

**Methods for Cleaning-Up:** Scoop up material and place in a disposal container. Provide ventilation.

## **Section 7: HANDLING AND STORAGE**

#### 7.1 PRECAUTIONS FOR SAFE HANDLING

**Handling:** Keep away from sources of ignition. - No smoking. Do not spray on

an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Container may explode if heated. Avoid contact with skin and eyes. Do not breathe dust/fume/gas/mist/vapors/spray. Do not swallow. Use only outdoors or in a well-ventilated area. When using do not eat, drink or smoke. Use non-

sparking tools. (See section 8)

General Hygiene Advice: Launder contaminated clothing before reuse. Wash hands before

eating, drinking, or smoking.

# 7.2 CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES

Storage: Keep out of the reach of children. Store locked up. Protect from

sunlight. Do not store at temperatures above 50 °C / 122 °F. Store in

a well-ventilated place. (See section 10)

#### Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### **8.1 CONTROL PARAMETERS**

# **Exposure Guidelines**

Occupational Exposure Limits				
Ingredient	OSHA-PEL	ACGIH-TLV		
Isopropanol	400 ppm	200 ppm		
Petroleum gases, liquefied, sweetened	1000 ppm	1000 ppm		
Acetone	1000 ppm TWA; 2400 mg/m <sup>3</sup> TWA	500 ppm		
Ceramic materials and wares, chemicals	5 mg/m <sup>3</sup>	Not available.		
Talc	20 mppcf	2 mg/m <sup>3</sup> (resp)		
	$((10 \text{ mg/m}^3)/(\% \text{SiO}_2 + 2) \text{ TWA (resp)})$ $((30 \text{ mg/m}^3)/(\% \text{SiO}_2 + 2) \text{ TWA (total)})$			
Silica, crystalline, quartz	((250)/(%SiO <sub>2</sub> +5) mppcf TWA (resp))	0.025 mg/m <sup>3</sup>		

## **8.2 EXPOSURE CONTROLS**

Engineering Controls: Use ventilation adequate to keep exposures (airborne levels of dust,

fume, vapor, etc.) below recommended exposure limits.

#### **8.3 INDIVIDUAL PROTECTIVE MEASURES**

**Personal Protective Equipment:** 

**Eye/Face Protection:** Safety glasses or goggles are recommended when using product.

**Skin Protection:** 

Hand Protection: Chemical-resistant gloves.

**Body Protection:** Wear suitable protective clothing.

**Respiratory Protection:** In case of insufficient ventilation, wear suitable respiratory equipment.

Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the

selected respirator.

**General Health and Safety** 

Measures:

Do not eat, smoke or drink where material is handled, processed or stored. Wash hands carefully before eating or smoking. Handle according to established industrial hygiene and safety practices.

#### **Section 9: PHYSICAL AND CHEMICAL PROPERTIES**

#### 9.1 INFORMATION ON BASIC PHYSICAL AND CHEMICAL PROPERTIES

Appearance: White liquid.

Color: White.
Odor: Alcohol.

Odor Threshold: Not available.

Physical State: Gas/Pressurized Liquid.

pH: Neutral.

Melting Point/Freezing Point: Not available.

Initial Boiling Point and Boiling Range: ~ 55 °C (~ 132 °F)

Flash Point:

Evaporation Rate:

0.4 (Ether = 1)

Flammability: Flammable.

Lower Flammability/Explosive Limit: 2 %
Upper Flammability/Explosive Limit: 15 %

**Vapor Pressure:** 65 psi @ 24 °C (75 °F)

Vapor Density: 3

Relative Density/Specific Gravity: 0.87

Solubility: Partial.

Partition coefficient: n-octanol/water: Not available.

Auto-ignition Temperature: Not available.

Decomposition Temperature: Not available.

Viscosity: Not available.

Oxidizing Properties: Not available.

Explosive Properties: Not available.

#### Section 10: STABILITY AND REACTIVITY

#### **10.1 REACTIVITY**

No dangerous reaction known under conditions of normal use.

## **10.2 CHEMICAL STABILITY**

Stable under normal storage conditions. Contents under pressure. Container may explode if heated. Do not pierce or burn, even after use.

## 10.3 POSSIBILITY OF HAZARDOUS REACTIONS

No dangerous reaction known under conditions of normal use.

# **10.4 CONDITIONS TO AVOID**

Heat. Incompatible materials. Sources of ignition.

## 10.5 INCOMPATIBLE MATERIALS

Strong oxidizing agents.

#### 10.6 HAZARDOUS DECOMPOSITION PRODUCTS

May include, and are not limited to: oxides of carbon.

# **Section 11: TOXICOLOGICAL INFORMATION**

## 11.1 INFORMATION ON TOXICOLOGICAL EFFECTS

**Likely Routes of Exposure:** Skin contact, eye contact, inhalation, and ingestion.

# Symptoms related to physical/chemical/toxicological characteristics:

vomiting.

**Eye:** Causes serious eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva.

**Skin:** May cause skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin.

Ingestion: May be harmful if swallowed. May cause stomach distress, nausea or

Inhalation: May cause respiratory tract irritation. May cause drowsiness or dizziness.

#### **Acute Toxicity:**

Ingredient	IDLH	LC50	LD50
	Г		0 1 1000 //
			Oral 4396 mg/kg, rat
		Inhalation 72.6	Dermal 12800 mg/kg, rat
Isopropanol	2,000 ppm	mg/L 4h, rat	Dermal 12870 mg/kg, rabbit
Petroleum gases,		Inhalation 658	
liquefied, sweetened	Not available.	mg/L 4h, rat	Not available.
		Inhalation 50100	
Acetone	2,500 ppm	mg/m <sup>3</sup> 8h, rat	Oral 5800 mg/kg, rat

Ceramic materials			Oral > 2000 mg/kg, rat
and wares, chemicals	Not available.	Not available.	Dermal > 2500 mg/kg, rabbit
Talc	1,000 mg/m <sup>3</sup>	Not available.	Not available.
	25 mg/m <sup>3</sup> (Cristobalite &		
Silica, crystalline,	Tridymite)		
quartz	50 mg/m <sup>3</sup> (Quartz & Tripoli)	Not available.	Oral 500 mg/kg, rat

Calculated overall Chemical Acute Toxicity Values		
LC50 (inhalation)	LD50 (oral)	LD50 (dermal)
> 5 mg/L 4h, rat	> 2000 mg/kg, rat	> 2000 mg/kg, rabbit

Ingredient	Chemical Listed as Carcinogen or Potential Carcinogen (NTP, IARC, OSHA, ACGIH, CP65)*
Isopropanol	G-A4, I-3
Petroleum gases, liquefied, sweetened	Not listed.
Acetone	G-A4
Ceramic materials and wares, chemicals	Not listed.
Talc	G-A4, I-3
Silica, crystalline, quartz	G-A2, I-1, N-1, O, CP65

<sup>\*</sup> See Section 15 for more information.

## 11.2 DELAYED, IMMEDIATE, AND CHRONIC EFFECTS OF SHORT- AND LONG-TERM EXPOSURE

**Skin Corrosion/Irritation:** Based on available data, the classification criteria are not met.

**Serious Eye Damage/Irritation:** Causes serious eye irritation.

**Respiratory Sensitization:**Based on available data, the classification criteria are not met. **Skin Sensitization:**Based on available data, the classification criteria are not met.

**STOT-Single Exposure:** May cause drowsiness or dizziness.

**Chronic Health Effects:** 

Carcinogenicity: Based on available data, the classification criteria are not met.Germ Cell Mutagenicity: Based on available data, the classification criteria are not met.

**Reproductive Toxicity:** 

Developmental: Based on available data, the classification criteria are not met.Teratogenicity: Based on available data, the classification criteria are not met.Embryotoxicity: Based on available data, the classification criteria are not met.


Fertility: Based on available data, the classification criteria are not met.

STOT-Repeated Exposure: Causes damage to lungs through prolonged or repeated exposure.

Aspiration Hazard: Based on available data, the classification criteria are not met.

**Toxicologically Synergistic** 

Materials:Not available.Other Information:Not available.



# **Section 12: ECOLOGICAL INFORMATION**

#### 12.1 ECOTOXICITY

Acute/Chronic Toxicity: May cause long-term adverse effects in the aquatic environment.

# 12.2 PERSISTENCE AND DEGRADABILITY

Not available.

#### 12.3 BIOACCUMULATIVE POTENTIAL

Bioaccumulation: Not available.

#### **12.4 MOBILITY IN SOIL**

Not available.

#### 12.5 OTHER ADVERSE EFFECTS

Not available.

#### Section 13: DISPOSAL CONSIDERATIONS

#### 13.1 WASTE TREATMENT METHODS

**Disposal Method:** This material must be disposed of in accordance with all

local, state, provincial, and federal regulations.

Other disposal recommendations: Not available.

## **Section 14: TRANSPORT INFORMATION**

# **14.1 UN NUMBER**

DOT TDG NOM-004-SCT2-1994

UN1950 UN1950 UN1950

**14.2 UN PROPER SHIPPING NAME** 

DOT TDG NOM-004-SCT2-1994

Aerosols, flammable Aerosols, flammable Aerosols, flammable

14.3 TRANSPORT HAZARD CLASS (ES)

DOT TDG NOM-004-SCT2-1994

2.1 2.1

14.4 PACKING GROUP

DOT TDG NOM-004-SCT2-1994

Not applicable. Not applicable. Not applicable.

#### 14.5 ENVIRONMENTAL HAZARDS

Not available.

#### 14.6 TRANSPORT IN BULK ACCORDING TO ANNEX II OF MARPOL 73/78 AND THE IBC CODE

Not available.

## 14.7 SPECIAL PRECAUTIONS FOR USER

Do not handle until all safety precautions have been read and understood.

# **Section 15: REGULATORY INFORMATION**

# 15.1 SAFETY, HEALTH AND ENVIRONMENTAL REGULATIONS/ LEGISLATIONS SPECIFIC FOR THE CHEMICAL

**Canada:** This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

**US:** MSDS prepared pursuant to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

Mexico: MSDS prepared pursuant to NOM-018-STPS-2000.

SARA Title III				
Ingredient	Section 302 (EHS) TPQ (lbs.)	Section 304 EHS RQ (lbs.)	CERCLA RQ (lbs.)	Section 313
Isopropanol	Not listed.	Not listed.	Not listed.	313
Petroleum gases, liquefied,				
sweetened	Not listed.	Not listed.	Not listed.	Not listed.
Acetone	Not listed.	Not listed.	5,000	Not listed.
Ceramic materials and				
wares, chemicals	Not listed.	Not listed.	Not listed.	Not listed.
Talc	Not listed.	Not listed.	Not listed.	Not listed.
Silica, crystalline, quartz	Not listed.	Not listed.	Not listed.	Not listed.

## **State Regulations**

# California Proposition 65:

This product contains a chemical known to the State of California to cause cancer.

# **Global Inventories:**


Ingredient	Canada DSL/NDSL	USA TSCA
Isopropanol	DSL	Yes.
Petroleum gases, liquefied, sweetened	DSL	Yes.
Acetone	DSL	Yes.
Ceramic materials and wares, chemicals	DSL	Yes.
Talc	DSL	Yes.
Silica, crystalline, quartz	DSL	Yes.

NFPA-National Fire Protection Association:		
Health:	2	
Fire:	4	
Reactivity:	0	

HMIS-Hazardous Materials Identification System:		
Health:	2*	
Fire:	4	
Physical Hazard:	0	

**Hazard Rating:** 0 = minimal, 1 = slight, 2 = moderate, 3 = severe, 4 = extreme

Trade Name: SKD-S2 Aerosol Print date: 2013-11-25



## SOURCE AGENCY CARCINOGEN CLASSIFICATIONS:

CP65 California Proposition 65

OSHA (O) Occupational Safety and Health Administration.

ACGIH (G) American Conference of Governmental Industrial Hygienists.

A1 - Confirmed human carcinogen.

A2 - Suspected human carcinogen.

A3 - Animal carcinogen.

A4 - Not classifiable as a human carcinogen.

A5 - Not suspected as a human carcinogen.

# IARC (I) International Agency for Research on Cancer.

1 - The agent (mixture) is carcinogenic to humans.

2A - The agent (mixture) is probably carcinogenic to humans; there is limited evidence of carcinogenicity in humans and sufficient evidence of carcinogenicity in experimental animals.

2B - The agent (mixture) is possibly carcinogenic to humans; there is limited evidence of carcinogenicity in humans in the absence of sufficient evidence of carcinogenicity in experimental animals.

3 - The agent (mixture, exposure circumstance) is not classifiable as to its carcinogenicity to humans.

4 - The agent (mixture, exposure circumstance) is probably not carcinogenic to humans.

# NTP (N) National Toxicology Program.

1 - Known to be carcinogens.

2 - Reasonably anticipated to be carcinogens.

# **Section 16: OTHER INFORMATION**

**Date of Preparation:** November 25, 2013 **Expiry Date:** November 25, 2016

Version: 1.0

Revision Date: November 25, 2013

**Disclaimer:** We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.

Prepared by: Nexreg Compliance Inc.

Phone: (519) 488-5126

www.nexreg.com

Prepared for: Magnaflux

**End of Safety Data Sheet**