

URALANE® 5774 A US

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: |
| 2.0 | 09/19/2022 | 400001008104 | 09/20/2019 |
| | | | Date of first issue: 01/10/2017 |

Print Date 09/20/2022

SECTION 1. IDENTIFICATION

Product name : URALANE® 5774 A US

Manufacturer or supplier's detailsCompany name of supplier : Huntsman Advanced Materials Americas LLC
Address : P.O. Box 4980The Woodlands,
TX 77387
United States of America (USA)

Telephone : Non-Emergency: (800) 257-5547

E-mail address : Global_Product_EHS_AdMat@huntsman.com

Emergency telephone number : Chemtrec: (800) 424-9300 or (703) 527-3887

Recommended use of the chemical and restrictions on use

Recommended use : Adhesives

Restrictions on use : For industrial use only.

SECTION 2. HAZARDS IDENTIFICATION**GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)**

Acute toxicity (Inhalation) : Category 2

Skin irritation : Category 2

Eye irritation : Category 2A

Respiratory sensitisation : Category 1

Skin sensitisation : Category 1

Specific target organ toxicity : Category 3 (Respiratory system)
- single exposure**GHS label elements**

Hazard pictograms :



Signal word : Danger

Hazard statements : H315 Causes skin irritation.
H317 May cause an allergic skin reaction.

URALANE® 5774 A US

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: |
| 2.0 | 09/19/2022 | 400001008104 | 09/20/2019 |
| | | | Date of first issue: 01/10/2017 |

Print Date 09/20/2022

H319 Causes serious eye irritation.
H330 Fatal if inhaled.
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335 May cause respiratory irritation.

Precautionary statements

: **Prevention:**

P260 Do not breathe mist or vapours.
P264 Wash skin thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P272 Contaminated work clothing must not be allowed out of the workplace.
P280 Wear protective gloves/ eye protection/ face protection.
P284 Wear respiratory protection.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.
P304 + P340 + P310 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/ doctor.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.
P337 + P313 If eye irritation persists: Get medical advice/ attention.
P342 + P311 If experiencing respiratory symptoms: Call a POISON CENTER/ doctor.
P362 Take off contaminated clothing and wash before reuse.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
P405 Store locked up.

Disposal:

P501 Dispose of contents/container to an approved facility in accordance with local, regional, national and international regulations.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

| Chemical name | CAS-No. | Concentration (% w/w) |
|---|---------------|-----------------------|
| ACCN # 139812 | ACCN # 139812 | 50 - 70 |
| 2-Oxepanone, polymer with 1,1'-methylenebis[4-isocyanatocyclohexane] and 2,2'-oxybis[ethanol] | 54954-83-5 | 10 - 20 |

URALANE® 5774 A US

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: |
| 2.0 | 09/19/2022 | 400001008104 | 09/20/2019 |
| | | | Date of first issue: 01/10/2017 |

Print Date 09/20/2022

4,4'-methylenedicyclohexyl diisocyanate

5124-30-1

1 - 5

The specific chemical identity and/or exact percentage (concentration) of composition may be withheld as a trade secret.

SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.
Do not leave the victim unattended.
Get medical attention immediately if symptoms occur.
Show this safety data sheet to the doctor in attendance.
- If inhaled : If breathed in, move person into fresh air.
Call a physician or poison control centre immediately.
Keep patient warm and at rest.
Keep respiratory tract clear.
If breathing is difficult, give oxygen.
If breathing is irregular or stopped, administer artificial respiration.
If unconscious, place in recovery position and seek medical advice.
Consult a physician immediately if symptoms such as shortness of breath or asthma are observed.
A hyper-reactive response to even minimal concentrations of diisocyanates may develop in sensitised persons.
The exposed person may need to be kept under medical surveillance for 48 hours.
LC50 (rat) : ca. 490 mg/m³ (4 hours) : using experimentally produced respirable aerosol having aerodynamic diameter <5microns.
Methods used to generate the exposure concentrations in the animal studies use extreme laboratory conditions and does not represent actual exposure conditions of the material in the workplace, storage, transportation or expected use on the market due to the very low vapor pressure. Therefore, these test results cannot be used to for hazard classification of the material. Rather, an acute toxicity estimate is calculated based on weight of evidence and expert judgement and is used to justify a modified classification for acute inhalation toxicity.
- In case of skin contact : In case of contact, immediately flush skin with soap and plenty of water.
Take off contaminated clothing and shoes immediately.
Wash contaminated clothing before reuse.
Thoroughly clean shoes before reuse.
Call a physician if irritation develops or persists.
An MDI study has demonstrated that a polyglycol-based skin cleanser (such as D-Tam™, PEG-400) or corn oil may be more effective than soap and water.

URALANE® 5774 A US

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: |
| 2.0 | 09/19/2022 | 400001008104 | 09/20/2019 |
| | | | Date of first issue: 01/10/2017 |

Print Date 09/20/2022

In case of eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.
If easy to do, remove contact lens, if worn.
Protect unharmed eye.
Keep eye wide open while rinsing.
Seek medical advice.

If swallowed : Gently wipe or rinse the inside of the mouth with water.
DO NOT induce vomiting unless directed to do so by a physician or poison control center.
Keep respiratory tract clear.
Keep at rest.
If a person vomits when lying on his back, place him in the recovery position.
Never give anything by mouth to an unconscious person.
Take victim immediately to hospital.
If symptoms persist, call a physician.

Most important symptoms and effects, both acute and delayed : Severe allergic skin reactions, bronchospasm and anaphylactic shock
This product is a respiratory irritant and potential respiratory sensitizer: repeated inhalation of vapour or aerosol at levels above the occupational exposure limit could cause respiratory sensitisation.
Symptoms may include irritation to the eyes, nose, throat and lungs, possibly combined with dryness of the throat, tightness of chest and difficulty in breathing.
The onset of the respiratory symptoms may be delayed for several hours after exposure.
A hyper-reactive response to even minimal concentrations of MDI may develop in sensitised persons.

Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training.
It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.
If potential for exposure exists refer to Section 8 for specific personal protective equipment.
First Aid responders should pay attention to self-protection and use the recommended protective clothing

Notes to physician : Symptomatic and supportive therapy as needed. Following severe exposure medical follow-up should be monitored for at least 48 hours.

The first aid procedure should be established in consultation with the doctor responsible for industrial medicine.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Foam
Carbon dioxide (CO₂)

URALANE® 5774 A US

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: |
| 2.0 | 09/19/2022 | 400001008104 | 09/20/2019 |
| | | | Date of first issue: 01/10/2017 |

Print Date 09/20/2022

Dry powder

- Unsuitable extinguishing media : Water may be used if no other available and then in copious quantities. Reaction between water and hot isocyanate may be vigorous.
- Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.
The pressure in sealed containers can increase under the influence of heat.
Exposure to decomposition products may be a hazard to health.
- Hazardous combustion products : Combustion products may include: carbon monoxide, carbon dioxide, nitrogen oxides, hydrocarbons and HCN. In the event of extreme heat (>500 degrees C), aniline is suspected of being formed.
- Carbon oxides
Nitrogen oxides (NOx)
Hydrogen cyanide (hydrocyanic acid)
- Specific extinguishing methods : Cool containers/tanks with water spray.
- Further information : Standard procedure for chemical fires.
Due to reaction with water producing CO₂-gas, a hazardous build-up of pressure could result if contaminated containers are re-sealed.
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Prevent fire extinguishing water from contaminating surface water or the ground water system.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
- Special protective equipment for firefighters : Wear an approved positive pressure self-contained breathing apparatus in addition to standard fire fighting gear.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Immediately evacuate personnel to safe areas.
Use personal protective equipment.
If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials.
Ensure adequate ventilation.
Keep people away from and upwind of spill/leak.
Only qualified personnel equipped with suitable protective equipment may intervene.
For additional precautions and advice on safe handling, see section 7.
Never return spills in original containers for re-use.
Make sure that there is a sufficient amount of neutralizing/absorbent material near the storage area.

URALANE® 5774 A US

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: |
| 2.0 | 09/19/2022 | 400001008104 | 09/20/2019 |
| | | | Date of first issue: 01/10/2017 |

Print Date 09/20/2022

The danger areas must be delimited and identified using relevant warning and safety signs.
Treat recovered material as described in the section "Disposal considerations".
For disposal considerations see section 13.

Environmental precautions : Do not allow uncontrolled discharge of product into the environment.
Do not allow material to contaminate ground water system.
Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
Local authorities should be advised if significant spillages cannot be contained.
If the product contaminates rivers and lakes or drains inform respective authorities.

Methods and materials for containment and cleaning up : Clean-up methods - small spillage
Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).
Clean contaminated surface thoroughly.
Sweep up or vacuum up spillage and collect in suitable container for disposal.
Neutralize small spillages with decontaminant.
The compositions of liquid decontaminants are given in Section 16.
Remove and dispose of residues.
Clean-up methods - large spillage
If the product is in its solid form:
Spilled MDI flakes should be picked up carefully.
The area should be vacuum cleaned to remove remaining dust particles completely.
If the product is in its liquid form:
Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Leave to react for at least 30 minutes.
Shovel into open-top drums for further decontamination.
Wash the spillage area with water.
Test atmosphere for MDI vapour.
Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

Technical measures : Ensure that eyewash stations and safety showers are close to the workstation location.

Local/Total ventilation : Use only with adequate ventilation.

Advice on protection against fire and explosion : Normal measures for preventive fire protection.

Advice on safe handling : For personal protection see section 8.

URALANE® 5774 A US

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: |
| 2.0 | 09/19/2022 | 400001008104 | 09/20/2019 |
| | | | Date of first issue: 01/10/2017 |

Print Date 09/20/2022

Avoid formation of aerosol.
 Do not breathe vapours or spray mist.
 Do not breathe vapours/dust.
 Do not swallow.
 Do not get in eyes or mouth or on skin.
 Do not get on skin or clothing.
 Avoid exposure - obtain special instructions before use.
 Smoking, eating and drinking should be prohibited in the application area.
 Provide sufficient air exchange and/or exhaust in work rooms.
 Keep container closed when not in use.
 Open drum carefully as content may be under pressure.
 Dispose of rinse water in accordance with local and national regulations.
 Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
 Industrial use of aprotic polar solvents for cleaning can release hazardous primary aromatic amines (>0.1%)

Conditions for safe storage : Keep containers tightly closed in a dry, cool and well-ventilated place.
 Keep in properly labelled containers.
 Observe label precautions.
 Protect from moisture.
 Electrical installations / working materials must comply with the technological safety standards.
 Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Materials to avoid : For incompatible materials please refer to Section 10 of this SDS.

Recommended storage temperature : 36 - 104 °F / 2 - 40 °C

Further information on storage stability : Stable under normal conditions.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION
Components with workplace control parameters

| Components | CAS-No. | Value type (Form of exposure) | Control parameters / Permissible concentration | Basis |
|---|-----------|----------------------------------|---|-----------|
| 4,4'-methylenedicyclohexyl diisocyanate | 5124-30-1 | TWA | 0.005 ppm | ACGIH |
| | | C | 0.01 ppm 0.11 mg/m3 | NIOSH REL |
| | | C | 0.01 ppm 0.11 mg/m3 | OSHA P0 |

Personal protective equipment

URALANE® 5774 A US

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: |
| 2.0 | 09/19/2022 | 400001008104 | 09/20/2019 |
| | | | Date of first issue: 01/10/2017 |

Print Date 09/20/2022

Respiratory protection : Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.
Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
In emergency, non-routine and unknown exposure situations, including confined space entries, a NIOSH-certified full facepiece pressure demand self-contained breathing apparatus (SCBA) or a full facepiece pressure demand supplied air respirator (SAR) with auxiliary self-contained air supply, should be used.

Hand protection

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.
Protective gloves should be worn when handling freshly made polyurethane products to avoid contact with trace residual materials which may be hazardous in contact with skin.

Use chemical resistant gloves classified under Standard EN374: protective gloves against chemicals and microorganisms. Examples of glove materials that might provide suitable protection include: Butyl rubber, Chlorinated polyethylene, Polyethylene, Ethyl vinyl alcohol copolymers laminated ("EVAL"), Polychloroprene (Neoprene*), Nitrile/butadiene rubber ("nitrile" or "NBR"), Polyvinyl chloride ("PVC" or "vinyl"), Fluoroelastomer (Viton*).

When prolonged or frequently repeated contact may occur, a glove with protection class of 5 or higher (breakthrough time greater than 240 minutes according to EN374) is recommended.

When only brief contact is expected, a glove with protection class of 3 or higher (breakthrough time greater than 60 minutes according to EN374) is recommended.

Notice: The selection of a specific glove for a particular application and duration of use in a workplace should also take into account all requisite workplace factors such as, but not limited to : other chemicals that may be handled, physical requirements (cut/puncture protection, dexterity, thermal protection), as well as instructions/specifications provided by the glove supplier

By industrial use of aprotic polar solvents for cleaning : Butyl rubber (0.7mm), Nitrile rubber (0.4mm), Chloroprene (0.5mm)

Eye protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists or dusts.
Chemical splash goggles.
Always wear eye protection when the potential for inadvertent eye contact with the product cannot be excluded.
Please follow all applicable local/national requirements when

URALANE® 5774 A US

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: |
| 2.0 | 09/19/2022 | 400001008104 | 09/20/2019 |
| | | | Date of first issue: 01/10/2017 |

Print Date 09/20/2022

selecting protective measures for a specific workplace.
Ensure that eyewash stations and safety showers are close to the workstation location.

Skin and body protection : Impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Recommended:
Overall (preferably heavy cotton) or Tyvek-Pro Tech 'C' , Tyvek Pro 'F' disposable coverall.

Protective measures : Personal protective equipment comprising: suitable protective gloves, safety goggles and protective clothing
The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.
Ensure that eye flushing systems and safety showers are located close to the working place.

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice.
Wash face, hands and any exposed skin thoroughly after handling.
Remove contaminated clothing and protective equipment before entering eating areas.
When using do not eat, drink or smoke.
Contaminated work clothing should not be allowed out of the workplace.
Wash hands before breaks and immediately after handling the product.
Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

| | |
|------------------------------|--|
| Appearance | : liquid |
| Colour | : off-white |
| Odour | : slight |
| Odour Threshold | : No data is available on the product itself. |
| pH | : substance/mixture reacts with water |
| Melting point/freezing point | : No data available |
| Boiling point/boiling range | : No information available. |
| Flash point | : 396 °F / 202 °C Method: Pensky-Martens closed cup |
| Evaporation rate | : No data is available on the product itself. |
| Flammability (solid, gas) | : No data is available on the product itself. |

URALANE® 5774 A US

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: |
| 2.0 | 09/19/2022 | 400001008104 | 09/20/2019 |
| | | | Date of first issue: 01/10/2017 |

Print Date 09/20/2022

| | |
|--|---|
| Flammability (liquids) | : No data is available on the product itself. |
| Upper explosion limit / Upper flammability limit | : No data is available on the product itself. |
| Lower explosion limit / Lower flammability limit | : No data is available on the product itself. |
| Vapour pressure | : < 1 hPa (68 °F / 20 °C) |
| Relative vapour density | : No data is available on the product itself. |
| Relative density | : 1.32 (77 °F / 25 °C) |
| Density | : 1.32 g/cm ³ (77 °F / 25 °C) |
| Solubility(ies) | |
| Water solubility | : Water reactive (68 °F / 20 °C) |
| Solubility in other solvents | : No data is available on the product itself. |
| Partition coefficient: n-octanol/water | : No data is available on the product itself. |
| Auto-ignition temperature | : No data is available on the product itself. |
| Decomposition temperature | : > 392 °F / > 200 °C |
| Self-Accelerating decomposition temperature (SADT) | : No data is available on the product itself. |
| Viscosity | |
| Viscosity, dynamic | : 33,000 mPa.s (77 °F / 25 °C) |
| Explosive properties | : No data is available on the product itself. |
| Oxidizing properties | : No data is available on the product itself. |
| Molecular weight | : No data available |
| Particle size | : No data is available on the product itself. |

SECTION 10. STABILITY AND REACTIVITY

| | |
|------------------------------------|--|
| Reactivity | : No dangerous reaction known under conditions of normal use. |
| Chemical stability | : Stable under normal conditions. |
| Possibility of hazardous reactions | : Reaction with water (moisture) produces CO ₂ -gas. Exothermic reaction with materials containing active hydrogen groups. The reaction becomes progressively more vigorous and can be violent at higher temperatures if the miscibility of the |

URALANE® 5774 A US

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: |
| 2.0 | 09/19/2022 | 400001008104 | 09/20/2019 |
| | | | Date of first issue: 01/10/2017 |

Print Date 09/20/2022

reaction partners is good or is supported by stirring or by the presence of solvents.
MDI is insoluble with, and heavier than water and sinks to the bottom but reacts slowly at the interface.
A solid water-insoluble layer of polyurea is formed at the interface by liberating carbon dioxide gas.

- Conditions to avoid : Extremes of temperature and direct sunlight.
Exposure to air or moisture over prolonged periods.
- Incompatible materials : Acids
Amines
Bases
Metals
water
- Hazardous decomposition products : Combustion products may include: carbon monoxide, carbon dioxide, nitrogen oxides, hydrocarbons and HCN. In the event of extreme heat (>500 degrees C), aniline is suspected of being formed.

SECTION 11. TOXICOLOGICAL INFORMATION**Acute toxicity****Product:**

- Acute inhalation toxicity : Assessment: The substance/mixture is not toxic on inhalation as defined by dangerous goods regulations.
Remarks: Methods used to generate the exposure concentrations in the animal studies use extreme laboratory conditions and does not represent actual exposure conditions of the material in the workplace, storage, transportation or expected use on the market due to the very low vapor pressure. Therefore, these test results cannot be used to for hazard classification of the material. Rather, an acute toxicity estimate is calculated based on weight of evidence and expert judgement and is used to justify a modified classification for acute inhalation toxicity.

Acute toxicity estimate: 0.0875 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: Calculation method

- Acute dermal toxicity : Acute toxicity estimate: > 5,000 mg/kg
Method: Calculation method

Components:**ACCN # 139812:**

- Acute inhalation toxicity : Assessment: The component/mixture is highly toxic after short term inhalation.

URALANE® 5774 A US

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: |
| 2.0 | 09/19/2022 | 400001008104 | 09/20/2019 |
| | | | Date of first issue: 01/10/2017 |

Print Date 09/20/2022

2-Oxepanone, polymer with 1,1'-methylenebis[4-isocyanatocyclohexane] and 2,2'-oxybis[ethanol]:

| | |
|---------------------------|---|
| Acute oral toxicity | : LD50 (Rat, male): > 10,000 mg/kg Method: OECD Test Guideline 401 Remarks: Information given is based on data obtained from similar substances. |
| Acute inhalation toxicity | : LC50 (Rat, male and female): Exposure time: 4 h Test atmosphere: dust/mist Method: OECD Test Guideline 403 Assessment: The component/mixture is moderately toxic after short term inhalation. Remarks: Information given is based on data obtained from similar substances. |
| Acute dermal toxicity | : LD50 (Rabbit, male and female): > 9,400 mg/kg Method: OECD Test Guideline 402 Remarks: Information given is based on data obtained from similar substances. |

4,4'-methylenedicyclohexyl diisocyanate:

| | |
|---------------------------|---|
| Acute oral toxicity | : LD50 (Rat, male and female): 18,200 mg/kg |
| Acute inhalation toxicity | : LC50 (Rat, male and female): 0.43 mg/l Exposure time: 4 h Test atmosphere: dust/mist Method: OECD Test Guideline 403 |
| Acute dermal toxicity | : LD50 (Rat, male and female): > 7,000 mg/kg Method: OECD Test Guideline 402 |

Skin corrosion/irritation**Components:****ACCN # 139812:**

| | |
|--------|-------------------|
| Result | : Skin irritation |
|--------|-------------------|

2-Oxepanone, polymer with 1,1'-methylenebis[4-isocyanatocyclohexane] and 2,2'-oxybis[ethanol]:

| | |
|---------|--|
| Species | : Rabbit |
| Method | : OECD Test Guideline 404 |
| Result | : Irritating to skin. |
| Remarks | : Information given is based on data obtained from similar substances. |

4,4'-methylenedicyclohexyl diisocyanate:

| | |
|---------|---------------------------|
| Species | : Rabbit |
| Method | : OECD Test Guideline 404 |
| Result | : Skin irritation |

URALANE® 5774 A US

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: |
| 2.0 | 09/19/2022 | 400001008104 | 09/20/2019 |
| | | | Date of first issue: 01/10/2017 |

Print Date 09/20/2022

Serious eye damage/eye irritation**Components:****ACCN # 139812:**

Result : Eye irritation

2-Oxepanone, polymer with 1,1'-methylenebis[4-isocyanatocyclohexane] and 2,2'-oxybis[ethanol]:

| | | |
|---------|---|--|
| Species | : | Rabbit |
| Result | : | Mild eye irritation |
| Remarks | : | Information given is based on data obtained from similar substances. |

4,4'-methylenedicyclohexyl diisocyanate:

| | | |
|---------|---|-------------------------|
| Species | : | Rabbit |
| Result | : | Eye irritation |
| Method | : | OECD Test Guideline 405 |

Respiratory or skin sensitisation**Components:****ACCN # 139812:**

Result : May cause sensitisation by inhalation.

Result : May cause sensitisation by skin contact.

2-Oxepanone, polymer with 1,1'-methylenebis[4-isocyanatocyclohexane] and 2,2'-oxybis[ethanol]:

| | | |
|-----------------|---|--|
| Exposure routes | : | Skin |
| Species | : | Mouse |
| Method | : | OECD Test Guideline 429 |
| Result | : | May cause sensitisation by skin contact. |
| Remarks | : | Information given is based on data obtained from similar substances. |

| | | |
|-----------------|---|--|
| Exposure routes | : | Respiratory Tract |
| Species | : | Guinea pig |
| Result | : | May cause sensitisation by inhalation. |
| Remarks | : | Information given is based on data obtained from similar substances. |

Assessment : May cause sensitisation by inhalation and skin contact.

4,4'-methylenedicyclohexyl diisocyanate:

| | | |
|-----------------|---|--|
| Exposure routes | : | Skin |
| Species | : | Guinea pig |
| Method | : | OECD Test Guideline 406 |
| Result | : | May cause sensitisation by skin contact. |

| | | |
|-----------------|---|--|
| Exposure routes | : | Respiratory Tract |
| Species | : | Guinea pig |
| Result | : | May cause sensitisation by inhalation. |

URALANE® 5774 A US

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: |
| 2.0 | 09/19/2022 | 400001008104 | 09/20/2019 |
| | | | Date of first issue: 01/10/2017 |

Print Date 09/20/2022

Germ cell mutagenicity**Components:****2-Oxepanone, polymer with 1,1'-methylenebis[4-isocyanatocyclohexane] and 2,2'-oxybis[ethanol]:**

Genotoxicity in vitro : Concentration: 200 ug/plate
Metabolic activation: with and without metabolic activation
Method: Directive 67/548/EEC, Annex, B.13/14
Result: negative
Remarks: Information given is based on data obtained from similar substances.

Genotoxicity in vivo : Application Route: Inhalation
Exposure time: 3 Weeks
Dose: 118 mg/m3
Method: OECD Test Guideline 474
Result: negative
Remarks: Information given is based on data obtained from similar substances.

4,4'-methylenedicyclohexyl diisocyanate:

Genotoxicity in vitro : Concentration: 50 ug/plate
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 471
Result: negative

Concentration: 28 µg/L
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 473
Result: negative

Concentration: 96 µg/L
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 476
Result: negative

Carcinogenicity**Product:**

Remarks : Rats have been exposed for two years to a respirable aerosol of polymeric MDI which resulted in a chronic pulmonary irritation at high concentrations. Only at the top level (6 mg/m3), there was a significant incidence of a benign tumour of the lung (adenoma) and one malignant tumour (adenocarcinoma). There were no lung tumours at 1 mg/m3 and no effects at 0.2 mg/m3. Overall, the tumour incidence, both benign and malignant, and the number of animals with the tumours were not different from controls. The increased incidence of lung tumours is associated with prolonged respiratory irritation and the concurrent accumulation of yellow material in the lung, which occurred throughout the study. In the absence of prolonged exposure to high concentrations leading to chronic irritation and lung damage, it is highly

URALANE® 5774 A US

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: |
| 2.0 | 09/19/2022 | 400001008104 | 09/20/2019 |
| | | | Date of first issue: 01/10/2017 |

Print Date 09/20/2022

unlikely that tumour formation will occur.

Remarks : Industrial use of aprotic polar solvents for cleaning can release hazardous primary aromatic amines (>0.1%)
Based on animal studies, primary aromatic amines are considered as potential carcinogen to humans. Some of those chemicals are proven carcinogens to humans
Provided the recommended personal protective equipment and hygiene measures are applied, no adverse effects to human health are to be expected

Components:**2-Oxepanone, polymer with 1,1'-methylenebis[4-isocyanatocyclohexane] and 2,2'-oxybis[ethanol]:**

| | |
|------------------------|--|
| Species | : Rat, male and female |
| Application Route | : Inhalation |
| Exposure time | : 24 month(s) |
| Dose | : 1 mg/m ³ |
| Frequency of Treatment | : 5 daily |
| Method | : OECD Test Guideline 453 |
| Result | : positive |
| Target Organs | : Lungs |
| Remarks | : Information given is based on data obtained from similar substances. |

IARC No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity**Components:****2-Oxepanone, polymer with 1,1'-methylenebis[4-isocyanatocyclohexane] and 2,2'-oxybis[ethanol]:**

| | |
|-------------------------------|---|
| Effects on foetal development | : Species: Rat, female |
| | Application Route: Inhalation |
| | General Toxicity Maternal: NOAEL: 4 mg/m ³ |
| | Method: OECD Test Guideline 414 |
| | Result: No teratogenic effects |
| | Remarks: Information given is based on data obtained from similar substances. |

4,4'-methylenedicyclohexyl diisocyanate:

| | |
|----------------------|----------------------------------|
| Effects on fertility | : Species: Rat, male and female |
| | Application Route: Inhalation |
| | Target Organs: Respiratory Tract |
| | Method: OECD Test Guideline 421 |
| | Result: negative |

URALANE® 5774 A US

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: |
| 2.0 | 09/19/2022 | 400001008104 | 09/20/2019 |
| | | | Date of first issue: 01/10/2017 |

Print Date 09/20/2022

Effects on foetal development : Species: Rat, female
Application Route: Inhalation
General Toxicity Maternal: NOAEL: 1 mg/m³
Method: OECD Test Guideline 414
Result: No teratogenic effects

STOT - single exposure**Components:****ACCN # 139812:**

Exposure routes : inhalation (dust/mist/fume)
Target Organs : Respiratory Tract
Assessment : May cause respiratory irritation.

2-Oxepanone, polymer with 1,1'-methylenebis[4-isocyanatocyclohexane] and 2,2'-oxybis[ethanol]:

Exposure routes : Inhalation
Target Organs : Respiratory Tract
Assessment : May cause respiratory irritation.
Remarks : Information given is based on data obtained from similar substances.

4,4'-methylenedicyclohexyl diisocyanate:

Exposure routes : Inhalation
Target Organs : Respiratory Tract
Assessment : May cause respiratory irritation.

STOT - repeated exposure

No data available

Repeated dose toxicity**Components:****2-Oxepanone, polymer with 1,1'-methylenebis[4-isocyanatocyclohexane] and 2,2'-oxybis[ethanol]:**

Species : Rat, male and female
NOEC : 0.2 mg/m³
Exposure time : 2 yr
Number of exposures : 5 d
Method : OECD Test Guideline 453
Remarks : Information given is based on data obtained from similar substances.

4,4'-methylenedicyclohexyl diisocyanate:

Species : Rat, male and female
NOEC : 3 mg/m³
Test atmosphere : dust/mist
Exposure time : 13 Weeks
Number of exposures : 6 h
Method : OECD Test Guideline 413

URALANE® 5774 A US

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: |
| 2.0 | 09/19/2022 | 400001008104 | 09/20/2019 |
| | | | Date of first issue: 01/10/2017 |

Print Date 09/20/2022

Aspiration toxicity

No data available

Experience with human exposure

No data available

Toxicology, Metabolism, Distribution

No data available

Neurological effects

No data available

Further information

No data available

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity****Components:****2-Oxepanone, polymer with 1,1'-methylenebis[4-isocyanatocyclohexane] and 2,2'-oxybis[ethanol]:**

Toxicity to fish : LC50 (Brachydanio rerio (zebrafish)): > 1,000 mg/l
Exposure time: 96 h
Test Type: static test
Method: OECD Test Guideline 203
Remarks: Information given is based on data obtained from similar substances.

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): > 1,000 mg/l
aquatic invertebrates
Exposure time: 24 h
Test Type: static test
Test substance: Fresh water
Method: OECD Test Guideline 202
Remarks: Information given is based on data obtained from similar substances.

Toxicity to daphnia and other : NOEC (Daphnia magna (Water flea)): >= 10 mg/l
aquatic invertebrates
(Chronic toxicity)
Exposure time: 21 d
Test Type: semi-static test
Test substance: Fresh water
Method: OECD Test Guideline 211
Remarks: Information given is based on data obtained from similar substances.

4,4'-methylenedicyclohexyl diisocyanate:

Toxicity to fish : LC50 (Brachydanio rerio (zebrafish)): > 8.1 mg/l
Exposure time: 96 h
Test Type: static test
Test substance: Fresh water
Method: Directive 67/548/EEC, Annex V, C.1.

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): > 8.3 mg/l
aquatic invertebrates
Exposure time: 48 h
Test Type: static test

URALANE® 5774 A US

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: |
| 2.0 | 09/19/2022 | 400001008104 | 09/20/2019 |
| | | | Date of first issue: 01/10/2017 |

Print Date 09/20/2022

Test substance: Fresh water
Method: Directive 67/548/EEC, Annex V, C.2.

Toxicity to algae/aquatic plants : EgC50 (Desmodesmus subspicatus (green algae)): > 5 mg/l
Exposure time: 72 h
Test Type: static test
Test substance: Fresh water
Method: Directive 67/548/EEC, Annex V, C.3.

Ecotoxicology Assessment

Acute aquatic toxicity : This product has no known ecotoxicological effects.

Chronic aquatic toxicity : This product has no known ecotoxicological effects.

Persistence and degradability**Components:****2-Oxepanone, polymer with 1,1'-methylenebis[4-isocyanatocyclohexane] and 2,2'-oxybis[ethanol]:**

Biodegradability : Inoculum: Domestic sewage
Concentration: 30 mg/l
Result: Not biodegradable
Biodegradation: 0 %
Exposure time: 28 d
Method: Inherent Biodegradability: Modified MITI Test (II)

4,4'-methylenedicyclohexyl diisocyanate:

Biodegradability : Inoculum: activated sludge
Concentration: 30 mg/l
Result: Not readily biodegradable.
Biodegradation: 0 %
Exposure time: 28 d
Method: Directive 67/548/EEC Annex V, C.4.D.

Bioaccumulative potential**Components:****2-Oxepanone, polymer with 1,1'-methylenebis[4-isocyanatocyclohexane] and 2,2'-oxybis[ethanol]:**

Bioaccumulation : Species: Cyprinus carpio (Carp)
Bioconcentration factor (BCF): 200
Remarks: Bioaccumulation is unlikely.

Mobility in soil

No data available

Other adverse effects**Product:**

Ozone-Depletion Potential : Regulation: 40 CFR Protection of Environment; Part 82
Protection of Stratospheric Ozone - CAA Section 602 Class I
Substances
Remarks: This product neither contains, nor was

URALANE® 5774 A US

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: |
| 2.0 | 09/19/2022 | 400001008104 | 09/20/2019 |
| | | | Date of first issue: 01/10/2017 |

Print Date 09/20/2022

manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

| | | |
|------------------------|---|--|
| Waste from residues | : | Do not dispose of waste into sewer. Do not contaminate ponds, waterways or ditches with chemical or used container. Send to a licensed waste management company. |
| Contaminated packaging | : | Empty remaining contents. Dispose of as unused product. Do not re-use empty containers. |

SECTION 14. TRANSPORT INFORMATION**International Regulations****UNRTDG**

Not regulated as dangerous goods

IATA-DGR

Not regulated as dangerous goods

IMDG-Code

Not regulated as dangerous goods

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations**49 CFR**

Not regulated as dangerous goods

Special precautions for user

| | | |
|---------|---|--|
| Remarks | : | Not classified as dangerous in the meaning of transport regulations. |
|---------|---|--|

SECTION 15. REGULATORY INFORMATION**CERCLA Reportable Quantity**

Listed substances in the product are at low enough levels to not be expected to exceed the RQ

| | | |
|-----------------------------|---|---|
| SARA 311/312 Hazards | : | Acute toxicity (any route of exposure) Respiratory or skin sensitisation Skin corrosion or irritation Serious eye damage or eye irritation Specific target organ toxicity (single or repeated exposure) |
|-----------------------------|---|---|

URALANE® 5774 A US

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: |
| 2.0 | 09/19/2022 | 400001008104 | 09/20/2019 |
| | | | Date of first issue: 01/10/2017 |

Print Date 09/20/2022

SARA 313 : The following components are subject to reporting levels established by SARA Title III, Section 313:

4,4'-methylenedicyclohexyl diisocyanate 5124-30-1 $\geq 1 - < 5 \%$

This product does not contain any hazardous air pollutants (HAP) $\geq 0.1\%$, as defined by the U.S. Clean Air Act Section 112 (40 CFR 61)

California Prop. 65

WARNING: This product can expose you to chemicals including methanol, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

The components of this product are reported in the following inventories:

| | |
|-------|--|
| DSL | : This product contains one or several components that are not on the Canadian DSL nor NDSL. |
| AIIC | : Not in compliance with the inventory |
| NZIoC | : Not in compliance with the inventory |
| ENCS | : On the inventory, or in compliance with the inventory |
| KECI | : Not in compliance with the inventory |
| PICCS | : Not in compliance with the inventory |
| IECSC | : On the inventory, or in compliance with the inventory |
| TCSI | : On the inventory, or in compliance with the inventory |
| TSCA | : All substances listed as active on the TSCA inventory |

Inventories

AIIC (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TECI (Thailand), TSCA (USA)

TSCA - 5(a) Significant New Use Rule List of Chemicals

No substances are subject to a Significant New Use Rule.


US. Toxic Substances Control Act (TSCA) Section 12(b) Export Notification (40 CFR 707, Subpt D)

No substances are subject to TSCA 12(b) export notification requirements.

URALANE® 5774 A US

Version 2.0 Revision Date: 09/19/2022 SDS Number: 400001008104 Date of last issue: 09/20/2019
Date of first issue: 01/10/2017

Print Date 09/20/2022

SECTION 16. OTHER INFORMATION**Further information****NFPA 704:****HMIS® IV:**

| | | |
|------------------------|---|----------|
| HEALTH | * | 3 |
| FLAMMABILITY | | 1 |
| PHYSICAL HAZARD | | 0 |

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard

Liquid decontaminants (percentages by weight or volume) :

Decontaminant 1 : *- sodium carbonate : 5 - 10 % *- liquid detergent : 0.2 - 2 % *- water : to make up to 100 %

Decontaminant 2 : *- concentrated ammonia solution : 3 - 8 % *- liquid detergent : 0.2 - 2 % *- water : to make up to 100 %

Decontaminant 1 reacts slower with diisocyanates but is more environmentally friendly than decontaminant 2.

Decontaminant 2 contains ammonia. Ammonia presents health hazards. (See supplier safety information.)

Revision Date : 09/19/2022

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
NIOSH REL : USA. NIOSH Recommended Exposure Limits
OSHA P0 : USA. Table Z-1-A Limits for Air Contaminants (1989 vacated values)
ACGIH / TWA : 8-hour, time-weighted average
NIOSH REL / C : Ceiling value not be exceeded at any time.
OSHA P0 / C : Ceiling limit

The information and recommendations in this publication are to the best of our knowledge, information and belief accurate at the date of publication, NOTHING HEREIN IS TO BE CONSTRUED AS A WARRANTY, EXPRESS OR OTHERWISE.

IN ALL CASES, IT IS THE RESPONSIBILITY OF THE USER TO DETERMINE THE APPLICABILITY OF SUCH INFORMATION AND RECOMMENDATIONS AND THE SUITABILITY OF ANY PRODUCT FOR ITS OWN PARTICULAR PURPOSE.

THE PRODUCT MAY PRESENT HAZARDS AND SHOULD BE USED WITH CAUTION. WHILE CERTAIN HAZARDS ARE DESCRIBED IN THIS PUBLICATION, NO GUARANTEE IS MADE THAT THESE ARE THE ONLY HAZARDS THAT EXIST.

URALANE® 5774 A US

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: |
| 2.0 | 09/19/2022 | 400001008104 | 09/20/2019 |
| | | | Date of first issue: 01/10/2017 |

Print Date 09/20/2022

Hazards, toxicity and behaviour of the products may differ when used with other materials and are dependent upon the manufacturing circumstances or other processes. Such hazards, toxicity and behaviour should be determined by the user and made known to handlers, processors and end users.

The trademarks above are the property of Huntsman Corporation or an affiliate thereof.

NO PERSON OR ORGANIZATION EXCEPT A DULY AUTHORIZED HUNTSMAN EMPLOYEE IS AUTHORIZED TO PROVIDE OR MAKE AVAILABLE DATA SHEETS FOR HUNTSMAN PRODUCTS. DATA SHEETS FROM UNAUTHORIZED SOURCES MAY CONTAIN INFORMATION THAT IS NO LONGER CURRENT OR ACCURATE.

URALANE® 5774 C US

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: |
| 2.0 | 09/19/2022 | 400001010057 | 03/14/2019 |
| | | | Date of first issue: 09/22/2015 |

Print Date 09/20/2022

SECTION 1. IDENTIFICATION

Product name : URALANE® 5774 C US

Manufacturer or supplier's detailsCompany name of supplier : Huntsman Advanced Materials Americas LLC
Address : P.O. Box 4980The Woodlands,
TX 77387
United States of America (USA)

Telephone : Non-Emergency: (800) 257-5547

E-mail address : Global_Product_EHS_AdMat@huntsman.com

Emergency telephone number : Chemtrec: (800) 424-9300 or (703) 527-3887

Recommended use of the chemical and restrictions on use

Recommended use : Hardener

Restrictions on use : For industrial use only.

SECTION 2. HAZARDS IDENTIFICATION**GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)**

Acute toxicity (Oral) : Category 4

Skin sensitisation : Category 1

Germ cell mutagenicity : Category 2

Carcinogenicity : Category 2

Reproductive toxicity : Category 2

Specific target organ toxicity : Category 2 (Liver)
- single exposure (Oral)Specific target organ toxicity : Category 1 (Liver)
- repeated exposure (Oral)Specific target organ toxicity : Category 2 (Kidney)
- repeated exposure (Oral)

Short-term (acute) aquatic hazard : Category 1

Long-term (chronic) aquatic hazard : Category 1

URALANE® 5774 C US

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: |
| 2.0 | 09/19/2022 | 400001010057 | 03/14/2019 |
| | | | Date of first issue: 09/22/2015 |

Print Date 09/20/2022

GHS label elements

Hazard pictograms



Signal word

: Danger

Hazard statements

: H302 Harmful if swallowed.
H317 May cause an allergic skin reaction.
H341 Suspected of causing genetic defects.
H351 Suspected of causing cancer.
H361 Suspected of damaging fertility or the unborn child.
H371 May cause damage to organs (Liver) if swallowed.
H372 Causes damage to organs (Liver) through prolonged or repeated exposure if swallowed.
H373 May cause damage to organs (Kidney) through prolonged or repeated exposure if swallowed.
H410 Very toxic to aquatic life with long lasting effects.

Precautionary statements

: **Prevention:**
P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P260 Do not breathe mist or vapours.
P264 Wash skin thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.
P272 Contaminated work clothing must not be allowed out of the workplace.
P273 Avoid release to the environment.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
Response:
P301 + P312 + P330 IF SWALLOWED: Call a POISON CENTER/ doctor if you feel unwell. Rinse mouth.
P302 + P352 IF ON SKIN: Wash with plenty of soap and water.
P308 + P311 IF exposed or concerned: Call a POISON CENTER/ doctor.
P308 + P313 IF exposed or concerned: Get medical advice/ attention.
P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.
P363 Wash contaminated clothing before reuse.
P391 Collect spillage.
Storage:
P405 Store locked up.
Disposal:
P501 Dispose of contents/container to an approved facility in accordance with local, regional, national and international regulations.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

URALANE® 5774 C US

Version 2.0 Revision Date: 09/19/2022 SDS Number: 400001010057 Date of last issue: 03/14/2019
Date of first issue: 09/22/2015

Print Date 09/20/2022

Substance / Mixture : Mixture

Hazardous components

| Chemical name | CAS-No. | Concentration (% w/w) |
|---|------------|-----------------------|
| 4,4'-methylenebis(2-ethylaniline) | 19900-65-3 | 10 - 20 |
| tris(methylphenyl) phosphate | 1330-78-5 | 10 - 20 |
| Formaldehyde, polymer with 2-ethylbenzenamine | 69178-41-2 | 5 - 10 |
| 4,4'-methylenebis[N-sec-butyraniline] | 5285-60-9 | 5 - 10 |
| 1,1',1'',1'''-ethylenedinitrilotetrapropan-2-ol | 102-60-3 | 1 - 5 |
| 2-ethylaniline | 578-54-1 | 1 - 5 |
| melamine | 108-78-1 | 0.1 - 1 |
| ethylbenzene | 100-41-4 | 0.1 - 1 |

The specific chemical identity and/or exact percentage (concentration) of composition may be withheld as a trade secret.

SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.
Consult a physician.
Show this safety data sheet to the doctor in attendance.
Treat symptomatically.
Get medical attention if symptoms occur.
- If inhaled : If inhaled, remove to fresh air.
Get medical attention if symptoms occur.
- In case of skin contact : If on skin, rinse well with water.
- In case of eye contact : Flush eyes with water as a precaution.
Remove contact lenses.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Induce vomiting immediately and call a physician.
Keep respiratory tract clear.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
Take victim immediately to hospital.
- Most important symptoms and effects, both acute and : None known.

URALANE® 5774 C US

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: |
| 2.0 | 09/19/2022 | 400001010057 | 03/14/2019 |
| | | | Date of first issue: 09/22/2015 |

Print Date 09/20/2022

delayed

Protection of first-aiders : First Aid responders should pay attention to self-protection and use the recommended protective clothing
If potential for exposure exists refer to Section 8 for specific personal protective equipment.
Avoid inhalation, ingestion and contact with skin and eyes.
No action shall be taken involving any personal risk or without suitable training.
It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

Notes to physician : Treat symptomatically.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Water spray
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical

Unsuitable extinguishing media : Exercise caution when using a high volume water jet as it may scatter and spread fire

Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : Carbon oxides
Nitrogen oxides (NO_x)

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Refer to protective measures listed in sections 7 and 8.

Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

URALANE® 5774 C US

Version 2.0 Revision Date: 09/19/2022 SDS Number: 400001010057 Date of last issue: 03/14/2019
Date of first issue: 09/22/2015

Print Date 09/20/2022

Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion : Normal measures for preventive fire protection.

Advice on safe handling : Repeated or prolonged skin contact may cause skin irritation and/or dermatitis and sensitisation of susceptible persons.
Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product.
Do not breathe vapours/dust.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Dispose of rinse water in accordance with local and national regulations.

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Observe label precautions.
Keep in properly labelled containers.

Materials to avoid : For incompatible materials please refer to Section 10 of this SDS.

Recommended storage temperature : 36 - 104 °F / 2 - 40 °C

Further information on storage stability : Stable under normal conditions.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**Components with workplace control parameters**

| Components | CAS-No. | Value type (Form of exposure) | Control parameters / Permissible concentration | Basis |
|----------------|----------|----------------------------------|---|----------|
| 2-ethylaniline | 578-54-1 | TWA | 5 ppm 19 mg/m3 | OSHA Z-1 |
| | | TWA | 2 ppm 8 mg/m3 | OSHA P0 |

URALANE® 5774 C US

Version 2.0 Revision Date: 09/19/2022 SDS Number: 400001010057 Date of last issue: 03/14/2019
 Date of first issue: 09/22/2015

Print Date 09/20/2022

| | | | | |
|--------------|----------|------|----------------------|-----------|
| ethylbenzene | 100-41-4 | TWA | 20 ppm | ACGIH |
| | | TWA | 100 ppm 435 mg/m3 | NIOSH REL |
| | | ST | 125 ppm 545 mg/m3 | NIOSH REL |
| | | TWA | 100 ppm 435 mg/m3 | OSHA Z-1 |
| | | STEL | 125 ppm 545 mg/m3 | OSHA P0 |
| | | TWA | 100 ppm 435 mg/m3 | OSHA P0 |

Biological occupational exposure limits

| Components | CAS-No. | Control parameters | Biological specimen | Sampling time | Permissible concentration | Basis |
|--------------|----------|--|---------------------|--|---------------------------|-----------|
| ethylbenzene | 100-41-4 | Sum of mandelic acid and phenyl glyoxylic acid | Urine | End of shift (As soon as possible after exposure ceases) | 0.15 g/g creatinine | ACGIH BEI |

Personal protective equipment

Respiratory protection : General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection.

Respiratory protection : In the case of vapour formation use a respirator with an approved filter.

Hand protection

Material : butyl-rubber
 Break through time : > 8 h

Material : Nitrile rubber
 Break through time : 10 - 480 min

Material : Ethyl Vinyl Alcohol Laminate (EVAL)
 Break through time : > 8 h

Remarks : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is

URALANE® 5774 C US

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: |
| 2.0 | 09/19/2022 | 400001010057 | 03/14/2019 |
| | | | Date of first issue: 09/22/2015 |

Print Date 09/20/2022

necessary.

The suitability for a specific workplace should be discussed with the producers of the protective gloves.

| | |
|--------------------------|---|
| Eye protection | : Eye wash bottle with pure water Tightly fitting safety goggles |
| Skin and body protection | : Impervious clothing Choose body protection according to the amount and concentration of the dangerous substance at the work place. |
| Hygiene measures | : When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday. |

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

| | |
|--|--|
| Appearance | : liquid |
| Colour | : beige |
| Odour | : amine-like |
| Odour Threshold | : No data is available on the product itself. |
| pH | : substance/mixture is non-soluble (in water) |
| Melting point/freezing point | : No data available |
| Boiling point/boiling range | : No data available |
| Flash point | : 212 °F / 100 °C Method: estimated, closed cup |
| Evaporation rate | : No data is available on the product itself. |
| Flammability (solid, gas) | : No data is available on the product itself. |
| Flammability (liquids) | : No data is available on the product itself. |
| Upper explosion limit / Upper flammability limit | : No data is available on the product itself. |
| Lower explosion limit / Lower flammability limit | : No data is available on the product itself. |
| Vapour pressure | : < 1 hPa (68 °F / 20 °C) |
| Relative vapour density | : No data is available on the product itself. |
| Relative density | : 1.15 - 1.4 (77 °F / 25 °C) |
| Density | : 1.15 - 1.4 g/cm ³ (77 °F / 25 °C) |

URALANE® 5774 C US

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: |
| 2.0 | 09/19/2022 | 400001010057 | 03/14/2019 |
| | | | Date of first issue: 09/22/2015 |

Print Date 09/20/2022

| | |
|--|---|
| Solubility(ies) | |
| Water solubility | : insoluble (68 °F / 20 °C) |
| Solubility in other solvents | : No data is available on the product itself. |
| Partition coefficient: n-octanol/water | : No data is available on the product itself. |
| Auto-ignition temperature | : No data is available on the product itself. |
| Decomposition temperature | : > 392 °F / > 200 °C |
| Self-Accelerating decomposition temperature (SADT) | : No data is available on the product itself. |
| Viscosity | |
| Viscosity, dynamic | : 60,000 mPa.s (77 °F / 25 °C) |
| Explosive properties | : No data is available on the product itself. |
| Oxidizing properties | : No data is available on the product itself. |
| Molecular weight | : No data available |
| Particle size | : No data is available on the product itself. |

SECTION 10. STABILITY AND REACTIVITY

| | |
|------------------------------------|--|
| Reactivity | : No dangerous reaction known under conditions of normal use. |
| Chemical stability | : Stable under normal conditions. |
| Possibility of hazardous reactions | : No hazards to be specially mentioned. |
| Conditions to avoid | : None known. |
| Incompatible materials | : Strong acids Strong bases Strong oxidizing agents None known. |
| Hazardous decomposition products | : No decomposition if stored and applied as directed. |
| Hazardous decomposition products | : carbon dioxide carbon monoxide Nitrogen oxides (NOx) |

URALANE® 5774 C US

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: |
| 2.0 | 09/19/2022 | 400001010057 | 03/14/2019 |
| | | | Date of first issue: 09/22/2015 |

Print Date 09/20/2022

SECTION 11. TOXICOLOGICAL INFORMATION**Acute toxicity****Product:**

- Acute oral toxicity : Acute toxicity estimate: 1,774 mg/kg
Method: Calculation method
- Acute inhalation toxicity : Assessment: The substance/mixture is not toxic on inhalation as defined by dangerous goods regulations.
- Acute toxicity estimate: 57.56 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: Calculation method
- Acute dermal toxicity : Acute toxicity estimate: > 5,000 mg/kg
Method: Calculation method

Components:**4,4'-methylenebis(2-ethylaniline):**

- Acute oral toxicity : LD50 (Rat): 444 mg/kg
Method: OECD Test Guideline 401
- Acute inhalation toxicity : LC50 (Rat, male and female): > 0.85 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Assessment: The component/mixture is moderately toxic after short term inhalation.
- Acute dermal toxicity : LD50 (Rat, male and female): 2,080 mg/kg
Method: OECD Test Guideline 402
Assessment: The component/mixture is low toxic after single contact with skin.

tris(methylphenyl) phosphate:

- Acute oral toxicity : LD50 (Rat): > 20,000 mg/kg
- Acute inhalation toxicity : LC50 (Rat): > 11.1 mg/l
Exposure time: 1 h
Test atmosphere: dust/mist
Assessment: The substance or mixture has no acute inhalation toxicity
- Acute dermal toxicity : LD50 (Rabbit): 3,700 mg/kg
Assessment: The component/mixture is low toxic after single contact with skin.

Formaldehyde, polymer with 2-ethylbenzenamine:

- Acute oral toxicity : LD50 (Rat): 1,000 mg/kg

4,4'-methylenebis[N-sec-butylaniline]:

URALANE® 5774 C US

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: |
| 2.0 | 09/19/2022 | 400001010057 | 03/14/2019 |
| | | | Date of first issue: 09/22/2015 |

Print Date 09/20/2022

Acute oral toxicity : LD50 (Rat): 1,380 mg/kg

Acute dermal toxicity : LD50 (Rabbit): > 3,000 mg/kg
Assessment: The substance or mixture has no acute dermal toxicity**1,1',1'',1'''-ethylenedinitrilotetrapropan-2-ol:**Acute oral toxicity : LD50 (Rat, male and female): 2,890 mg/kg
Method: OECD Test Guideline 401

Acute dermal toxicity : LD50 (Rat, male and female): > 2,000 mg/kg

2-ethylaniline:Acute oral toxicity : LD50: 1,260 mg/kg
Assessment: The component/mixture is moderately toxic after single ingestion.Acute dermal toxicity : LD50 (Rabbit): 840 mg/kg
Assessment: The component/mixture is toxic after single contact with skin.**melamine:**

Acute oral toxicity : LD50 (Rat, male and female): 3,161 - 3,828 mg/kg

Acute inhalation toxicity : LC50 (Rat, male and female): > 5190 mg/m3
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403
GLP: yes
Assessment: The substance or mixture has no acute inhalation toxicity**ethylbenzene:**Acute oral toxicity : LD50 (Rat): 3,500 - 5,460 mg/kg
Assessment: The substance or mixture has no acute oral toxicityAcute inhalation toxicity : LC50 (Rat): 17.3 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Assessment: The component/mixture is moderately toxic after short term inhalation.Acute dermal toxicity : LD50 (Rabbit): 15,400 mg/kg
Assessment: The substance or mixture has no acute dermal toxicity**Skin corrosion/irritation****Components:****4,4'-methylenebis(2-ethylaniline):**

Species : Rabbit

URALANE® 5774 C US

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 03/14/2019 |
| 2.0 | 09/19/2022 | 400001010057 | Date of first issue: 09/22/2015 |

Print Date 09/20/2022

| | | |
|------------|---|--------------------|
| Assessment | : | No skin irritation |
| Method | : | OPPTS 870.2500 |
| Result | : | No skin irritation |

tris(methylphenyl) phosphate:

| | | |
|---------|---|--------------------|
| Species | : | Rabbit |
| Result | : | No skin irritation |

4,4'-methylenebis[N-sec-butylaniline]:

| | | |
|---------|---|--------------------|
| Species | : | Rabbit |
| Result | : | No skin irritation |

melamine:

| | | |
|------------|---|-------------------------|
| Species | : | Rabbit |
| Assessment | : | No skin irritation |
| Method | : | OECD Test Guideline 404 |
| Result | : | No skin irritation |
| GLP | : | yes |

Serious eye damage/eye irritation**Components:****4,4'-methylenebis(2-ethylaniline):**

| | | |
|------------|---|----------------------|
| Species | : | Rabbit |
| Result | : | No eye irritation |
| Assessment | : | No eye irritation |
| Method | : | Acute Eye Irritation |

tris(methylphenyl) phosphate:

| | | |
|---------|---|-------------------|
| Species | : | Rabbit |
| Result | : | No eye irritation |

4,4'-methylenebis[N-sec-butylaniline]:

| | | |
|---------|---|-------------------|
| Species | : | Rabbit |
| Result | : | No eye irritation |

1,1',1'',1'''-ethylenedinitrilotetrapropan-2-ol:

| | | |
|------------|---|---------------------|
| Species | : | Rabbit |
| Result | : | Irritating to eyes. |
| Assessment | : | Irritant |

2-ethylaniline:

| | | |
|--------|---|----------------|
| Result | : | Eye irritation |
|--------|---|----------------|

melamine:

| | | |
|---------|---|-------------------|
| Species | : | Rabbit |
| Remarks | : | slight irritation |

URALANE® 5774 C US

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: |
| 2.0 | 09/19/2022 | 400001010057 | 03/14/2019 |
| | | | Date of first issue: 09/22/2015 |

Print Date 09/20/2022

Respiratory or skin sensitisation**Components:****4,4'-methylenebis(2-ethylaniline):**

| | | |
|-----------------|---|--|
| Exposure routes | : | Skin |
| Species | : | Humans |
| Result | : | The product is a skin sensitizer, sub-category 1A. |

tris(methylphenyl) phosphate:

| | | |
|-----------------|---|------------------------------------|
| Exposure routes | : | Skin |
| Species | : | Mouse |
| Method | : | OECD Test Guideline 429 |
| Result | : | Does not cause skin sensitisation. |

4,4'-methylenebis[N-sec-butylaniline]:

| | | |
|-----------------|---|------------------------------------|
| Exposure routes | : | Skin |
| Result | : | Does not cause skin sensitisation. |

melamine:

| | | |
|-----------------|---|--|
| Test Type | : | Maximisation Test |
| Exposure routes | : | Skin |
| Species | : | Guinea pig |
| Assessment | : | Did not cause sensitisation on laboratory animals. |
| Method | : | OECD Test Guideline 406 |
| Result | : | Did not cause sensitisation on laboratory animals. |
| GLP | : | yes |

Germ cell mutagenicity**Components:****4,4'-methylenebis(2-ethylaniline):**

| | | |
|-----------------------|---|--|
| Genotoxicity in vitro | : | Test Type: Ames test Test system: Salmonella typhimurium Metabolic activation: with and without metabolic activation Method: Mutagenicity (Salmonella typhimurium - reverse mutation assay) Result: positive |
|-----------------------|---|--|

| | | |
|----------------------|---|--|
| Genotoxicity in vivo | : | Test Type: In vivo micronucleus test Species: Mouse Cell type: Somatic Application Route: Intraperitoneal injection Exposure time: 72 h Dose: 56 - 140 mg/kg Method: OECD Test Guideline 474 Result: Not classified due to inconclusive data. |
|----------------------|---|--|

| | | |
|--|---|---|
| | : | Test Type: In vivo micronucleus test Species: Mouse Cell type: Somatic Application Route: Intraperitoneal injection Dose: 9.3 - 37 mg/kg Method: OECD Test Guideline 474 |
|--|---|---|

URALANE® 5774 C US

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: |
| 2.0 | 09/19/2022 | 400001010057 | 03/14/2019 |
| | | | Date of first issue: 09/22/2015 |

Print Date 09/20/2022

Result: positive

Germ cell mutagenicity - Assessment : Positive result(s) from in vivo somatic cell mutagenicity tests supported by positive results from in vitro mutagenicity assays or chemical structure activity relationship to known germ cell mutagens

tris(methylphenyl) phosphate:

Genotoxicity in vitro : Metabolic activation: with and without metabolic activation
Result: negative

Germ cell mutagenicity - Assessment : In vitro tests did not show mutagenic effects

4,4'-methylenebis[N-sec-butylaniline]:

Genotoxicity in vitro : Method: OECD Test Guideline 471
Result: negative

melamine:

Genotoxicity in vitro : Test Type: reverse mutation assay
Test system: Salmonella typhimurium
Metabolic activation: with and without metabolic activation
Result: negative

Test Type: gene mutation test
Test system: Chinese hamster ovary cells
Metabolic activation: with and without metabolic activation
Result: negative

Test Type: Chromosome aberration test in vitro
Test system: Chinese hamster ovary cells
Metabolic activation: with and without metabolic activation
Result: negative

Genotoxicity in vivo : Test Type: Chromosome aberration test in vitro
Species: Mouse (male)
Cell type: Bone marrow
Application Route: Intraperitoneal injection
Dose: 0 - 150 - 300 - 600 mg/kg
Result: negative

ethylbenzene:

Genotoxicity in vitro : Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 473
Result: negative

Genotoxicity in vivo : Method: OECD Test Guideline 474
Result: negative

Method: OECD Test Guideline 486
Result: negative

URALANE® 5774 C US

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: |
| 2.0 | 09/19/2022 | 400001010057 | 03/14/2019 |
| | | | Date of first issue: 09/22/2015 |

Print Date 09/20/2022

Carcinogenicity**Components:****4,4'-methylenebis(2-ethylaniline):**

| | |
|------------------------|---------------------------|
| Species | : Rat, male and female |
| Application Route | : Oral |
| Exposure time | : 103 weeks |
| Dose | : 9 - 10 mg/kg |
| Frequency of Treatment | : 24 hour |
| Method | : OECD Test Guideline 451 |
| Result | : positive |

| | |
|------------------------------|---|
| Carcinogenicity - Assessment | : Limited evidence of carcinogenicity in animal studies |
|------------------------------|---|

tris(methylphenyl) phosphate:

| | |
|------------------------------|---|
| Carcinogenicity - Assessment | : Animal testing did not show any carcinogenic effects. |
|------------------------------|---|

melamine:

| | |
|-------------------|------------------------|
| Species | : Rat, male and female |
| Application Route | : Oral |
| Exposure time | : 103 weeks |
| NOAEL | : 126 mg/kg bw/day |
| Result | : negative |
| Target Organs | : Urinary bladder |

| | |
|-------------------|--------------------------|
| Species | : Mouse, male and female |
| Application Route | : Oral |
| Exposure time | : 103 weeks |
| NOAEL | : 2,250 mg/kg bw/day |
| Result | : negative |

| | | |
|-------------|---|----------|
| IARC | Group 2B: Possibly carcinogenic to humans melamine | 108-78-1 |
| | Group 2B: Possibly carcinogenic to humans ethylbenzene | 100-41-4 |

| | |
|-------------|--|
| OSHA | No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens. |
|-------------|--|

| | |
|------------|---|
| NTP | No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP. |
|------------|---|

Reproductive toxicity**Components:****tris(methylphenyl) phosphate:**

| | |
|----------------------|--|
| Effects on fertility | : Species: Rat, male and female |
| | Application Route: Oral |
| | General Toxicity - Parent: LOAEL: 62.5 mg/kg body weight |
| | Target Organs: Testes, Ovary |
| | Method: OECD Test Guideline 415 |
| | Result: positive |

URALANE® 5774 C US

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: |
| 2.0 | 09/19/2022 | 400001010057 | 03/14/2019 |
| | | | Date of first issue: 09/22/2015 |

Print Date 09/20/2022

Effects on foetal development : Species: Rat, female
Application Route: Oral
Dose: 20, 100, 400, 750 milligram per kilogram
General Toxicity Maternal: NOEL: 20 mg/kg body weight
Method: OPPTS 870.3700
Result: Teratogenic effects

Reproductive toxicity - Assessment : Some evidence of adverse effects on sexual function and fertility, and/or on development, based on animal experiments.

1,1',1'',1'''-ethylenedinitrilotetrapropan-2-ol:

Effects on fertility : Species: Rat, male and female
Application Route: Oral
Method: OECD Test Guideline 422
Result: negative

Effects on foetal development : Species: Rat, female
Application Route: Oral
General Toxicity Maternal: NOAEL: 400 mg/kg body weight
Result: No teratogenic effects

melamine:

Effects on fertility : Species: Rat, male and female
Application Route: Oral
Dose: 1000/4000/12500 ppm
General Toxicity - Parent: NOAEL: 1,000 ppm
General Toxicity F1: NOAEL: >= 12,500 ppm
General Toxicity F2: NOAEL: >= 12,500 parts per million
Target Organs: Testes
Method: OECD Test Guideline 443
GLP: yes

Effects on foetal development : Species: Rat, female
Application Route: Oral
General Toxicity Maternal: NOAEL: 600 mg/kg body weight
Method: OECD Test Guideline 414
Result: No teratogenic effects

Test Type: Pre-natal
Species: Rat, female
Application Route: Oral
Dose: 136; 400; 1060 mg/kg bw/day
Duration of Single Treatment: 11 d
General Toxicity Maternal: NOAEL: ca. 400 mg/kg body weight
Developmental Toxicity: NOAEL: ca. 1,060 mg/kg body weight
Method: OECD Test Guideline 414
GLP: yes

Test Type: Pre-natal
Species: Rabbit, female
Application Route: Oral
Dose: 15/50/150 mg/kg bw/d
Duration of Single Treatment: 23 d

URALANE® 5774 C US

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 03/14/2019 |
| 2.0 | 09/19/2022 | 400001010057 | Date of first issue: 09/22/2015 |

Print Date 09/20/2022

Frequency of Treatment: 7 days/week
General Toxicity Maternal: NOAEL: 150 mg/kg body weight
Developmental Toxicity: NOAEL: 150 mg/kg body weight
Method: OECD Test Guideline 414
GLP: yes

Reproductive toxicity - Assessment : Suspected of damaging fertility or the unborn child., Some evidence of adverse effects on sexual function and fertility, and/or on development, based on animal experiments.

ethylbenzene:

Effects on fertility : General Toxicity - Parent: NOAEL: 500 ppm
Method: OECD Test Guideline 416

Effects on foetal development : General Toxicity Maternal: NOAEL: 500 ppm
Teratogenicity: NOAEL: 2,000 ppm
Developmental Toxicity: NOAEL: 500 ppm

STOT - single exposure**Components:****4,4'-methylenebis(2-ethylaniline):**

Exposure routes : Ingestion
Target Organs : Liver
Assessment : May cause damage to organs.

STOT - repeated exposure**Components:****4,4'-methylenebis(2-ethylaniline):**

Exposure routes : Ingestion
Target Organs : Liver
Assessment : Causes damage to organs through prolonged or repeated exposure.

Exposure routes : Ingestion
Target Organs : Kidney
Assessment : May cause damage to organs through prolonged or repeated exposure.

ethylbenzene:

Exposure routes : Inhalation
Target Organs : Lungs, Liver, Kidney, Central nervous system
Assessment : May cause damage to organs through prolonged or repeated exposure.

Repeated dose toxicity**Components:****4,4'-methylenebis(2-ethylaniline):**

Species : Rat, male and female
LOAEL : 7.5 - 8 mg/kg/d

URALANE® 5774 C US

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 03/14/2019 |
| 2.0 | 09/19/2022 | 400001010057 | Date of first issue: 09/22/2015 |

Print Date 09/20/2022

Application Route : Ingestion
Exposure time : 2,160 h
Number of exposures : 7 d
Method : Subchronic toxicity

Species : Rat, male and female
NOAEL : 90 mg/kg/d
Application Route : Skin contact
Exposure time : 2,160 h
Number of exposures : 5 d
Method : Subchronic toxicity

tris(methylphenyl) phosphate:

Species : Rat, male and female
NOEL : 1000 mg/kg
Application Route : Ingestion
Exposure time : 2,160 h
Method : Subchronic toxicity

1,1',1'',1'''-ethylenedinitrilotetrapropan-2-ol:

Species : Rat, male and female
NOAEL : 1000 mg/kg/d
Application Route : Ingestion
Exposure time : 1,176 h
Number of exposures : 7 d
Method : Subacute toxicity

Species : Rat, male and female
NOAEL : 300 mg/kg/d
Application Route : Ingestion
Exposure time : 1,176 h
Number of exposures : 7 d
Method : Subacute toxicity

melamine:

Species : Rat, male
NOAEL : 72 mg/kg
Application Route : oral (feed)
Exposure time : 13 Weeks
Method : Subchronic toxicity

ethylbenzene:

Species : Rat, male and female
NOAEL : 75 mg/kg bw
Application Route : oral (gavage)
Exposure time : 28 d
Dose : 75/250/750 mg/kg bw
Control Group : yes
Method : OECD Test Guideline 407
Target Organs : Liver
Remarks : Subacute toxicity

Species : Rat, male and female

URALANE® 5774 C US

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 03/14/2019 |
| 2.0 | 09/19/2022 | 400001010057 | Date of first issue: 09/22/2015 |

Print Date 09/20/2022

NOAEL : 75 mg/kg bw
Application Route : oral (gavage)
Exposure time : 90 d
Dose : 75/250/750 mg/kg bw
Control Group : yes
Method : OECD Test Guideline 408

Species : Mouse, male and female
NOAEL : 3.4 mg/l
Application Route : Inhalation
Exposure time : 28 d
Dose : 0,4/1,7/3,4 mg/L
Control Group : yes
Method : OECD Test Guideline 412

Species : Rat, male and female
NOAEL : 1084
NOAEL : mg/m3
Application Route : inhalation (vapour)
Exposure time : 104 week
Dose : 325/1084/3251 mg/m3
Control Group : yes
Method : OECD Test Guideline 453

Species : Rat, male and female
NOAEL : 4.74 mg/l
Application Route : Inhalation
Exposure time : 13 week
Dose : 0,47/1,18/2,37/3,55/4,74 mg/L
Control Group : yes
Method : OECD Test Guideline 413
Target Organs : Liver

Species : Mouse, male and female
NOAEL : 3251
NOAEL : mg/m3
Application Route : Inhalation
Exposure time : 104 week
Dose : 325/1084/3251 mg/m3
Control Group : yes
Method : OECD Test Guideline 453

Species : Rabbit, male and female
NOAEL : 6.8 mg/l
Application Route : Inhalation
Exposure time : 28 d
Dose : 1,7/3,4/6,8 mg/L
Control Group : yes
Method : OECD Test Guideline 412

Aspiration toxicity**Components:****ethylbenzene:**

May be fatal if swallowed and enters airways.

URALANE® 5774 C US

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 03/14/2019 |
| 2.0 | 09/19/2022 | 400001010057 | Date of first issue: 09/22/2015 |

Print Date 09/20/2022

Experience with human exposure

No data available

Toxicology, Metabolism, Distribution

No data available

Neurological effects

No data available

Further information

No data available

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity****Components:****4,4'-methylenebis(2-ethylaniline):**

Toxicity to fish : LC50 (Oryzias latipes (Orange-red killifish)): 20.6 mg/l
Exposure time: 96 h
Test Type: semi-static test
Test substance: Fresh water
Method: OECD Test Guideline 203

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 0.35 mg/l
aquatic invertebrates
Exposure time: 48 h
Test Type: static test
Method: OECD Test Guideline 202

M-Factor (Acute aquatic : 1
toxicity)

Toxicity to daphnia and other : NOEC (Daphnia magna (Water flea)): 0.00525 mg/l
aquatic invertebrates
Exposure time: 21 d
(Chronic toxicity) Test Type: semi-static test
Test substance: Fresh water
Method: OECD Test Guideline 211

M-Factor (Chronic aquatic : 10
toxicity)

tris(methylphenyl) phosphate:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 0.6 mg/l
Exposure time: 96 h
Test Type: static test

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 0.146 mg/l
aquatic invertebrates
Exposure time: 48 h
Test Type: static test
Method: OECD Test Guideline 202

Toxicity to algae/aquatic : ErC50: 0.4042 mg/l
plants
Exposure time: 72 h
Test Type: static test

URALANE® 5774 C US

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: |
| 2.0 | 09/19/2022 | 400001010057 | 03/14/2019 |
| | | | Date of first issue: 09/22/2015 |

Print Date 09/20/2022

Method: OECD Test Guideline 201

M-Factor (Acute aquatic toxicity) : 1

Toxicity to fish (Chronic toxicity) : NOEC (Other): 0.01 mg/l
Exposure time: 28 d

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 0.1 mg/l
Exposure time: 21 d
Test Type: semi-static test

M-Factor (Chronic aquatic toxicity) : 1

Toxicity to microorganisms : EC50 (activated sludge): > 1,000 mg/l
Exposure time: 3 h

4,4'-methylenebis[N-sec-butylaniline]:
Ecotoxicology Assessment

Chronic aquatic toxicity : This product has no known ecotoxicological effects.

1,1',1'',1'''-ethylenedinitrilotetrapropan-2-ol:

Toxicity to fish : LC50 (Leuciscus idus (Golden orfe)): 4,600 mg/l
Exposure time: 96 h
Test Type: flow-through test
Test substance: Fresh water
Method: DIN 38412

LC50 (Leuciscus idus (Golden orfe)): 2,700 mg/l
Exposure time: 48 h
Test Type: static test
Method: DIN 38412

Toxicity to daphnia and other aquatic invertebrates : IC0 (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 48 h
Test Type: static test
Method: Directive 67/548/EEC, Annex V, C.2.

Toxicity to algae/aquatic plants : EC50 (Other): 150.67 mg/l
Exposure time: 72 h
Test substance: Fresh water
Method: Directive 67/548/EEC, Annex V, C.3.

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 10 mg/l
Exposure time: 21 d
Test Type: semi-static test
Test substance: Fresh water
Method: OECD Test Guideline 211

melamine:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 3,000 mg/l
End point: mortality

URALANE® 5774 C US

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: |
| 2.0 | 09/19/2022 | 400001010057 | 03/14/2019 |
| | | | Date of first issue: 09/22/2015 |

Print Date 09/20/2022

Exposure time: 96 h
 Test Type: semi-static test
 Test substance: Fresh water
 GLP: no

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 200 mg/l
 End point: Immobilization
 Exposure time: 48 h
 Test Type: static test
 Analytical monitoring: no
 Test substance: Fresh water
 GLP: yes

Toxicity to algae/aquatic plants : EC50 (Selenastrum capricornutum (green algae)): 325 mg/l
 Exposure time: 96 h
 Test Type: static test
 Test substance: Fresh water
 GLP: yes

NOEC (Selenastrum capricornutum (green algae)): 98 mg/l
 Exposure time: 96 h
 Test Type: static test
 Test substance: Fresh water
 GLP: yes

Toxicity to fish (Chronic toxicity) : NOEC (Pimephales promelas (fathead minnow)): >= 5 mg/l
 Exposure time: 36 d
 Test Type: flow-through test
 Analytical monitoring: yes
 Test substance: Fresh water
 Method: OECD Test Guideline 210
 GLP: yes

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): >= 11 mg/l
 Exposure time: 21 d
 Test Type: semi-static test
 Analytical monitoring: yes
 Test substance: Fresh water
 Method: OECD Test Guideline 211
 GLP: yes

ethylbenzene:

Toxicity to fish : LC50: 4.2 mg/l
 Exposure time: 96 h

LC50: 9.2 mg/l
 Exposure time: 96 h

LC50: 12.1 mg/l
 Exposure time: 96 h

LC50: 5.1 mg/l
 Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50: 1.81 - 2.38 mg/l
 Exposure time: 48 h

URALANE® 5774 C US

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: |
| 2.0 | 09/19/2022 | 400001010057 | 03/14/2019 |
| | | | Date of first issue: 09/22/2015 |

Print Date 09/20/2022

Toxicity to algae/aquatic plants : IC50: 4.6 mg/l
Exposure time: 72 h

EC50: 3.6 mg/l
Exposure time: 96 h

NOEC: 3.4 mg/l
Exposure time: 96 h

EC50: 7.7 mg/l
Exposure time: 96 h

Toxicity to fish (Chronic toxicity) : NOEL: 0.96 mg/l
Exposure time: 7 d

Ecotoxicology Assessment

Acute aquatic toxicity : This product has no known ecotoxicological effects.

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

Persistence and degradability**Components:****tris(methylphenyl) phosphate:**

Biodegradability : aerobic
Inoculum: Sewage (STP effluent)
Concentration: 100 mg/l
Result: Readily biodegradable.
Biodegradation: 80 %
Exposure time: 28 d
Method: OECD Test Guideline 301C

1,1',1'',1'''-ethylenedinitrilotetrapropan-2-ol:

Biodegradability : Inoculum: activated sludge
Concentration: 107 mg/l
Result: Inherently biodegradable.
Biodegradation: 36 %
Exposure time: 28 d
Method: OECD Test Guideline 302B

Inoculum: Domestic sewage
Concentration: 30 mg/l
Result: Not readily biodegradable.
Biodegradation: 9 %
Exposure time: 28 d
Method: Directive 67/548/EEC Annex V, C.4.D.

melamine:

Biodegradability : Inoculum: activated sludge
Concentration: 100 mg/l
Dissolved organic carbon (DOC)
Result: Not readily biodegradable.

URALANE® 5774 C US

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 03/14/2019 |
| 2.0 | 09/19/2022 | 400001010057 | Date of first issue: 09/22/2015 |

Print Date 09/20/2022

Biodegradation: < 10 %
Exposure time: 28 d
Method: OECD Test Guideline 302B
Test substance: Fresh water

Inoculum: activated sludge
Concentration: 100 parts per million
Result: Not biodegradable
Method: OECD Test Guideline 301C
Test substance: Fresh water

ethylbenzene:

Biodegradability : Result: Readily biodegradable.
Biodegradation: > 60 %
Exposure time: 28 d

Bioaccumulative potential**Components:****tris(methylphenyl) phosphate:**

Partition coefficient: n- : log Pow: 5.93
octanol/water

4,4'-methylenebis[N-sec-butylaniline]:

Bioaccumulation : Bioconcentration factor (BCF): 4,700

Partition coefficient: n- : log Pow: 6.08
octanol/water Method: QSAR

1,1',1'',1'''-ethylenedinitrilotetrapropan-2-ol:

Partition coefficient: n- : log Pow: -2.08 (77 °F / 25 °C)
octanol/water

melamine:

Partition coefficient: n- : log Pow: -1.22 (68 °F / 20 °C)
octanol/water pH: 8
Method: Partition coefficient
GLP: no

ethylbenzene:

Bioaccumulation : Bioconcentration factor (BCF): 1.9

Partition coefficient: n- : log Pow: 3.15
octanol/water

Mobility in soil**Components:****tris(methylphenyl) phosphate:**

Distribution among : Koc: 4.31
environmental compartments Method: OECD Test Guideline 121

URALANE® 5774 C US

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: |
| 2.0 | 09/19/2022 | 400001010057 | 03/14/2019 |
| | | | Date of first issue: 09/22/2015 |

Print Date 09/20/2022

4,4'-methylenebis[N-sec-butylaniline]:

Distribution among : Koc: 4.91
environmental compartments Method: QSAR

melamine:

Distribution among : Koc: 1.7
environmental compartments

ethylbenzene:

Distribution among : Koc: 520
environmental compartments

Other adverse effects**Product:**

Ozone-Depletion Potential : Regulation: 40 CFR Protection of Environment; Part 82
Protection of Stratospheric Ozone - CAA Section 602 Class I
Substances
Remarks: This product neither contains, nor was
manufactured with a Class I or Class II ODS as defined by the
U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A +
B).

Additional ecological : An environmental hazard cannot be excluded in the event of
information unprofessional handling or disposal.
Very toxic to aquatic life with long lasting effects.

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

Waste from residues : Dispose of contents and container in accordance with all local,
regional, national and international regulations.
Do not dispose of waste into sewer.
Do not contaminate ponds, waterways or ditches with
chemical or used container.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.

SECTION 14. TRANSPORT INFORMATION**International Regulations****IATA-DGR**

UN/ID No. : UN 3082
Proper shipping name : Environmentally hazardous substance, liquid, n.o.s.
(4,4'-METHYLENEBIS(2-ETHYLANILINE), TRICRESYL
PHOSPHATE)
Class : 9

URALANE® 5774 C US

Version 2.0 Revision Date: 09/19/2022 SDS Number: 400001010057 Date of last issue: 03/14/2019
Date of first issue: 09/22/2015

Print Date 09/20/2022

Packing group : III
Labels : Miscellaneous
Packing instruction (cargo aircraft) : 964
Packing instruction (passenger aircraft) : 964
Environmentally hazardous : yes

IMDG-Code

UN number : UN 3082
Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (4,4'-METHYLENEBIS(2-ETHYLANILINE), TRICRESYL PHOSPHATE)
Class : 9
Packing group : III
Labels : 9
EmS Code : F-A, S-F
Marine pollutant : yes

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations**49 CFR**

UN/ID/NA number : UN 3082
Proper shipping name : Environmentally hazardous substance, liquid, n.o.s. (4,4'-METHYLENEBIS(2-ETHYLANILINE), TRICRESYL PHOSPHATE)
Class : 9
Packing group : III
Labels : CLASS 9
ERG Code : 171
Marine pollutant : yes
Remarks : Above applies only to containers over 119 gallons or 450 liters. Not regulated if shipped in packages less than or equal to 119 gallons (450 liters).

Special precautions for user

Remarks : 49CFR: no dangerous good in non-bulk packaging

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION**CERCLA Reportable Quantity**

| Components | CAS-No. | Component RQ (lbs) | Calculated product RQ (lbs) |
|------------|-----------|--------------------|-----------------------------|
| xylenes | 1330-20-7 | 100 | 30959 |

SARA 311/312 Hazards : Acute toxicity (any route of exposure)

URALANE® 5774 C US

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: |
| 2.0 | 09/19/2022 | 400001010057 | 03/14/2019 |
| | | | Date of first issue: 09/22/2015 |

Print Date 09/20/2022

Respiratory or skin sensitisation
Germ cell mutagenicity
Carcinogenicity
Reproductive toxicity
Specific target organ toxicity (single or repeated exposure)

SARA 313

: The following components are subject to reporting levels established by SARA Title III, Section 313:

| | | |
|--------------|----------|----------------|
| ethylbenzene | 100-41-4 | >= 0.1 - < 1 % |
|--------------|----------|----------------|

The following chemical(s), >= 0.1%, are listed as HAP under the U.S. Clean Air Act, Section 112 (40 CFR 61):

| | |
|--------------|-----------|
| xylene | 1330-20-7 |
| ethylbenzene | 100-41-4 |

California Prop. 65

WARNING: This product can expose you to chemicals including ethylbenzene, which is/are known to the State of California to cause cancer, and methanol, toluene, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

The components of this product are reported in the following inventories:

| | |
|-------|--|
| DSL | : This product contains one or several components listed in the Canadian NDSL. |
| AIIC | : On the inventory, or in compliance with the inventory |
| NZIoC | : Not in compliance with the inventory |
| ENCS | : On the inventory, or in compliance with the inventory |
| KECI | : Not in compliance with the inventory |
| PICCS | : On the inventory, or in compliance with the inventory |
| IECSC | : On the inventory, or in compliance with the inventory |
| TCSI | : On the inventory, or in compliance with the inventory |
| TSCA | : All substances listed as active on the TSCA inventory |

Inventories

AIIC (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TECI (Thailand), TSCA (USA)

TSCA - 5(a) Significant New Use Rule List of Chemicals

No substances are subject to a Significant New Use Rule.


URALANE® 5774 C US

Version 2.0 Revision Date: 09/19/2022 SDS Number: 400001010057 Date of last issue: 03/14/2019
 Date of first issue: 09/22/2015

Print Date 09/20/2022

US. Toxic Substances Control Act (TSCA) Section 12(b) Export Notification (40 CFR 707, Subpt D)

No substances are subject to TSCA 12(b) export notification requirements.

SECTION 16. OTHER INFORMATION**Further information****NFPA 704:****HMIS® IV:**

| | | |
|------------------------|---|----------|
| HEALTH | * | 3 |
| FLAMMABILITY | | 1 |
| PHYSICAL HAZARD | | 0 |

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard

Revision Date : 09/19/2022

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
 ACGIH BEI : ACGIH - Biological Exposure Indices (BEI)
 NIOSH REL : USA. NIOSH Recommended Exposure Limits
 OSHA P0 : USA. Table Z-1-A Limits for Air Contaminants (1989 vacated values)
 OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
 ACGIH / TWA : 8-hour, time-weighted average
 NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
 NIOSH REL / ST : STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday
 OSHA P0 / TWA : 8-hour time weighted average
 OSHA P0 / STEL : Short-term exposure limit
 OSHA Z-1 / TWA : 8-hour time weighted average

The information and recommendations in this publication are to the best of our knowledge, information and belief accurate at the date of publication, NOTHING HEREIN IS TO BE CONSTRUED AS A WARRANTY, EXPRESS OR OTHERWISE.

IN ALL CASES, IT IS THE RESPONSIBILITY OF THE USER TO DETERMINE THE APPLICABILITY OF SUCH INFORMATION AND RECOMMENDATIONS AND THE SUITABILITY OF ANY PRODUCT FOR ITS OWN PARTICULAR PURPOSE.

URALANE® 5774 C US

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 03/14/2019 |
| 2.0 | 09/19/2022 | 400001010057 | Date of first issue: 09/22/2015 |

Print Date 09/20/2022

THE PRODUCT MAY PRESENT HAZARDS AND SHOULD BE USED WITH CAUTION. WHILE CERTAIN HAZARDS ARE DESCRIBED IN THIS PUBLICATION, NO GUARANTEE IS MADE THAT THESE ARE THE ONLY HAZARDS THAT EXIST.

Hazards, toxicity and behaviour of the products may differ when used with other materials and are dependent upon the manufacturing circumstances or other processes. Such hazards, toxicity and behaviour should be determined by the user and made known to handlers, processors and end users.

The trademarks above are the property of Huntsman Corporation or an affiliate thereof.

NO PERSON OR ORGANIZATION EXCEPT A DULY AUTHORIZED HUNTSMAN EMPLOYEE IS AUTHORIZED TO PROVIDE OR MAKE AVAILABLE DATA SHEETS FOR HUNTSMAN PRODUCTS. DATA SHEETS FROM UNAUTHORIZED SOURCES MAY CONTAIN INFORMATION THAT IS NO LONGER CURRENT OR ACCURATE.