

Version 0.0 Revision Date: 12/28/2015

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : A-A-59601E Type I

Recommended use of the chemical and restrictions on use

Recommended use : Dry-cleaning agent.

Manufacturer or supplier's details

Company : Nexeo Solutions, LLC.

Address 3 Waterway Square Place Suite 1000

> The Woodlands, TX. 77380 United States of America

Cage Code: : 4N760

NSN : 4 FL. OZ. : 6850-00-281-3061

> 1 GL: 6850-00-281-1985 5 GL: 6850-00-264-9038 55 GL: 6850-00-285-8012

Emergency telephone number:

Health North America: 1-855-NEXEO4U (1-855-639-3648) Health International: 1-855-NEXEO4U (1-855-639-3648) Transport North America: CHEMTREC (1-800-424-9300)

Additional Infor-: Responsible Party: Product Safety Group

mation:

E-Mail: msds@nexeosolutions.com SDS Requests: 1-855-429-2661 SDS Requests Fax: 1-281-500-2370 Website: www.nexeosolutions.com

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Flammable liquids : Category 3

Skin irritation : Category 2

Eye irritation : Category 2A

Carcinogenicity : Category 1B

icity - single exposure

Specific target organ tox- : Category 3 (Central nervous system)

Aspiration hazard : Category 1

GHS Label element

SDS Number: 10000009023 1 / 23 A-A-59601E Type I



Version 0.0 Revision Date: 12/28/2015

Hazard pictograms







Signal word : Danger

Hazard statements : H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness.

H350 May cause cancer.

Precautionary statements : **Prevention:**

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have

been read and understood.

P210 Keep away from heat/sparks/open flames/hot

surfaces. - No smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ ventilating/

lighting/ equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static

discharge.

P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/

spray.

P264 Wash skin thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/ eye protection/ face

protection.

P281 Use personal protective equipment as required.

Response:

P301 + P310 IF SWALLOWED: Immediately call a

POISON CENTER or doctor/ physician.

P303 + P361 + P353 IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse

skin with water/ shower.

P304 + P340 + P312 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/ physician if

you feel unwell.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P308 + P313 IF exposed or concerned: Get medical

advice/ attention.

P331 Do NOT induce vomiting.



Version 0.0 Revision Date: 12/28/2015

P332 + P313 If skin irritation occurs: Get medical

advice/ attention.

P337 + P313 If eye irritation persists: Get medical

advice/ attention.

P362 Take off contaminated clothing and wash before

reuse.

P370 + P378 In case of fire: Use dry sand, dry chemical

or alcohol-resistant foam for extinction.

Storage:

P403 + P233 Store in a well-ventilated place. Keep

container tightly closed.

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved

waste disposal plant.

Potential Health Effects

Carcinogenicity:

IARC Group 2B: Possibly carcinogenic to humans

100-41-4 **Ethylbenzene

91-20-3 **Naphthalene

ACGIH Confirmed animal carcinogen with unknown relevance to

humans

100-41-4 **Ethylbenzene

OSHANo component of this product present at levels greater

than or equal to 0.1% is identified as a carcinogen or

potential carcinogen by OSHA.

NTP Reasonably anticipated to be a human carcinogen

91-20-3 **Naphthalene

Emergency Overview

Appearance	liquid
Colour	clear, colourless
Odour	mild, Characteristic
Hazard Summary	No information available.

SDS Number: 100000009023 3 / 23 A-A-59601E Type I



A-A-59601E Type I

Version 0.0 Revision Date: 12/28/2015

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

CAS-No.	Chemical Name	Concentration (%)
64742-47-8 /	Distillates (pet), hydrotreated light AND/OR	70 - 90
64742-88-7	Solvent naphtha (pet), med aliph.	
8052-41-3	Stoddard solvent	20 - 30
1330-20-7	**Mixed Xylenes	1 - 5
95-63-6	**1,2,4-trimethylbenzene	1 - 5
111-84-2	**Nonane	1 - 5
100-41-4	**Ethylbenzene	0.1 - 1
91-20-3	**Naphthalene	0.1 - 1

Special Notes: : ** Other substances in the product which may pre-

sent a health or environmental hazard.

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.

Show this safety data sheet to the doctor in attend-

ance.

Symptoms of poisoning may appear several hours

later.

Do not leave the victim unattended.

If inhaled : Consult a physician after significant exposure.

If unconscious place in recovery position and seek

medical advice.

In case of skin contact : If skin irritation persists, call a physician.

If on skin, rinse well with water. If on clothes, remove clothes.

In case of eye contact : Immediately flush eye(s) with plenty of water.

Remove contact lenses. Protect unharmed eye.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.

Do NOT induce vomiting.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious per-

son.



Version 0.0 Revision Date: 12/28/2015

If symptoms persist, call a physician. Take victim immediately to hospital.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing

media

: Alcohol-resistant foam Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

: High volume water jet

Specific hazards during

firefighting

: Do not allow run-off from fire fighting to enter drains

or water courses.

Hazardous combustion

products

: No hazardous combustion products are known

Specific extinguishing

methods

: Use a water spray to cool fully closed containers.

Further information : Collect contaminated fire extinguishing water sepa-

rately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regu-

lations.

For safety reasons in case of fire, cans should be

stored separately in closed containments.

Special protective equip-

ment for firefighters

: Wear self-contained breathing apparatus for fire-

fighting if necessary.

NFPA Flammable and Combustible Liquids Classification:

Combustible Liquid Class II

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition.

Evacuate personnel to safe areas.

Beware of vapours accumulating to form ex

Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

Environmental precau-

tions

: Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

SDS Number: 100000009023 5 / 23 A-A-59601E Type I



Version 0.0 Revision Date: 12/28/2015

If the product contaminates rivers and lakes or drains

inform respective authorities.

Methods and materials for containment and cleaning up

: Contain spillage, and then collect with noncombustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regula-

tions (see section 13).

SECTION 7. HANDLING AND STORAGE

Advice on safe handling : Avoid formation of aerosol.

Do not breathe vapours/dust.

Avoid exposure - obtain special instructions before

use.

Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in

the application area.

Take precautionary measures against static discharg-

es.

Provide sufficient air exchange and/or exhaust in work

rooms.

Open drum carefully as content may be under pres-

sure.

Dispose of rinse water in accordance with local and

national regulations.

Conditions for safe stor-

age

: No smoking.

Keep container tightly closed in a dry and well-

ventilated place.

Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Observe label precautions.

Electrical installations / working materials must com-

ply with the technological safety standards.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

CAS-No.	Components	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
64742-47-8 / 64742-88-	Distillates (pet), hy- drotreated light AND/OR	TWA	500 ppm 2,000 mg/m3	OSHA Z-1

SDS Number: 100000009023 6 / 23 A-A-59601E Type I



A-A-59601E Type I

Version 0.0 Revision Date: 12/28/2015

7	Solvent naphtha (pet), med aliph.			
		TWA	200 mg/m3 (total hydrocar- bon vapor)	ACGIH
		TWA	400 ppm 1,600 mg/m3	OSHA PO
8052-41-3	Stoddard solvent	TWA	100 ppm	ACGIH
		TWA	350 mg/m3	NIOSH REL
		С	1,800 mg/m3	NIOSH REL
		TWA	500 ppm 2,900 mg/m3	OSHA Z-1
		TWA	100 ppm 525 mg/m3	OSHA PO
1330-20-7	**Mixed Xylenes	TWA	100 ppm 435 mg/m3	OSHA Z-1
		TWA	100 ppm	ACGIH
		STEL	150 ppm	ACGIH
		STEL	150 ppm 655 mg/m3	OSHA P0
		TWA	100 ppm 435 mg/m3	OSHA P0
95-63-6	**1,2,4-trimethylbenzene	TWA	25 ppm 125 mg/m3	NIOSH REL
111-84-2	**Nonane	TWA	200 ppm	ACGIH
		TWA	200 ppm 1,050 mg/m3	NIOSH REL
		TWA	200 ppm 1,050 mg/m3	OSHA PO
100-41-4	**Ethylbenzene	TWA	20 ppm	ACGIH
		TWA	100 ppm 435 mg/m3	NIOSH REL
		ST	125 ppm 545 mg/m3	NIOSH REL
		TWA	100 ppm 435 mg/m3	OSHA Z-1
		TWA	100 ppm 435 mg/m3	OSHA PO
		STEL	125 ppm 545 mg/m3	OSHA PO
91-20-3	**Naphthalene	TWA	10 ppm	ACGIH
		STEL	15 ppm	ACGIH
		TWA	10 ppm 50 mg/m3	NIOSH REL
		ST	15 ppm 75 mg/m3	NIOSH REL
		TWA	10 ppm 50 mg/m3	OSHA Z-1
		TWA	10 ppm	OSHA P0



A-A-59601E Type I

Version 0.0 Revision Date: 12/28/2015

	50 mg/m3	
STEL	15 ppm	OSHA P0
	75 mg/m3	

Biological occupational exposure limits

Components	CAS-No.	Control parame-ters	Biological specimen	Sam- pling time	Permissi- ble con- centration	Basis
**Mixed Xylenes	1330- 20-7	Methylhip puric acids	Urine	End of shift (As soon as possible after expo- sure ceases)	1.5 g/g creatinine	ACGIH BEI
**Ethylbenzene	100-41-	Sum of mandelic acid and phenyl glyoxylic acid	Urine	End of shift at end of work- week	0.7 g/g creatinine	ACGIH BEI

Personal protective equipment

Respiratory protection : No personal respiratory protective equipment normally

required.

In the case of vapour formation use a respirator with

an approved filter.

Hand protection

Remarks : The suitability for a specific workplace should be dis-

cussed with the producers of the protective gloves.

Eye protection : Eye wash bottle with pure water

Tightly fitting safety goggles

Wear face-shield and protective suit for abnormal pro-

cessing problems.

Skin and body protection : impervious clothing

Choose body protection according to the amount and

concentration of the dangerous substance at the work

place.

Hygiene measures : When using do not eat or drink.

When using do not smoke.

Wash hands before breaks and at the end of workday.



Version 0.0 Revision Date: 12/28/2015

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Colour : clear, colourless

Odour : mild, Characteristic

Odour Threshold : No data available

pH : No data available

Freezing Point : No data available

Boiling Point (Boiling

point/boiling range)

: 158 - 198 °C (316 - 388 °F)

Flash point : 39.44 - 45 °C (102.99 - 113 °F)

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Burning rate : No data available

Upper explosion limit : No data available

Lower explosion limit : No data available

Vapour pressure : No data available

Relative vapour density : No data available

Relative density : 0.775 - 0.784 @ 20 °C (68 °F)

Reference substance: (water = 1)

Density : No data available

Bulk density : No data available

Solubility(ies)

Water solubility : Negligible

Solubility in other sol-

vents

: No data available

Partition coefficient: n-

octanol/water

: No data available

Auto-ignition temperature : 276 °C

SDS Number: 100000009023 9 / 23 A-A-59601E Type I



A-A-59601E Type I

Version 0.0 Revision Date: 12/28/2015

Thermal decomposition : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No dangerous reaction known under conditions of

normal use.

Chemical stability : Stable under normal conditions.

Possibility of hazardous

reactions

: Vapours may form explosive mixture with air.

Conditions to avoid : Keep away from heat, flame, sparks and other ignition

sources.

Incompatible materials : Oxidizing agents

Peroxides

Reducing agents Strong bases

Hazardous decomposition

products

: Carbon oxides

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Product:

Acute inhalation toxicity : Acute toxicity estimate : > 40 mg/l

Exposure time: 4 h
Test atmosphere: vapour
Method: Calculation method

Components:

64742-47-8 / 64742-88-7:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : Remarks: No data available

Acute dermal toxicity : LD50 (Rabbit, male and female): > 2,000 mg/kg

Method: Fixed dose procedure

GLP: yes



A-A-59601E Type I

Version 0.0 Revision Date: 12/28/2015

Assessment: The substance or mixture has no acute

dermal toxicity

8052-41-3:

Acute oral toxicity : LD50 (Rat, male and female): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat, male and female): >5500

Exposure time: 4 h

Assessment: The substance or mixture has no acute

inhalation toxicity

Acute dermal toxicity : LD50 (Rabbit): > 3,000 mg/kg

Assessment: The substance or mixture has no acute

dermal toxicity

Skin corrosion/irritation

Product:

Result: Irritating to skin.

Components:

64742-47-8 / 64742-88-7:

Species: Rabbit Exposure time: 24 h Method: In vivo

Result: Irritating to skin.

8052-41-3:

Species: Rabbit Exposure time: 24 h Method: In vivo

Result: Mild skin irritation

Serious eye damage/eye irritation

Product:

Result: Irritating to eyes.

Components:

64742-47-8 / 64742-88-7:

Species: Rabbit

Result: Irritating to eyes.

8052-41-3: Species: Rabbit

Result: Mild eye irritation



A-A-59601E Type I

Version 0.0 Revision Date: 12/28/2015

Method: In vivo

Respiratory or skin sensitisation

Components:

64742-47-8 / 64742-88-7:

Test Type: Buehler Test Species: Guinea pig Method: In vivo

Result: Did not cause sensitisation on laboratory animals.

GLP: yes

8052-41-3:

Exposure routes: Dermal Species: Guinea pig Method: In vivo

Result: Did not cause sensitisation on laboratory animals.

Germ cell mutagenicity

Components:

64742-47-8 / 64742-88-7:

Germ cell mutagenicity- : Tests on bacterial or mammalian cell cultures did not

show mutagenic effects.

8052-41-3:

Assessment

Germ cell mutagenicity-

Assessment

: Mutagenicity classification not possible from current

data

Carcinogenicity

Components:

64742-47-8 / 64742-88-7:

Carcinogenicity - As- : Not classifiable as a human carcinogen.

sessment

8052-41-3:

Carcinogenicity - As-

: Carcinogenicity classification not possible from current

data.

100-41-4:

sessment

Carcinogenicity - As-

sessment

: Not classifiable as a human carcinogen.

Reproductive toxicity

Components:

64742-47-8 / 64742-88-7:

: Animal testing did not show any effects on fertility. Reproductive toxicity -

SDS Number: 10000009023 12 / 23 A-A-59601E Type I



A-A-59601E Type I

Version 0.0 Revision Date: 12/28/2015

Assessment Embryotoxicity classification not possible from current

data.

8052-41-3:

Reproductive toxicity -

Assessment

: Fertility classification not possible from current data. Embryotoxicity classification not possible from current

data.

STOT - single exposure

Product: No data available

Components:

64742-47-8 / 64742-88-7:

Exposure routes:	Target Organs:	Assessment:	Remarks:
Inhalation	Central nervous system	May cause drowsiness or dizziness., The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with narcotic effects.	

8052-41-3:

Exposure routes:	Target Organs:	Assessment:	Remarks:
Inhalation	Central nervous system	May cause drowsiness or dizziness., The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with narcotic effects.	

1330-20-7:No data available

95-63-6:No data available

111-84-2: No data available

100-41-4: No data available

91-20-3:No data available



Version 0.0 Revision Date: 12/28/2015

STOT - repeated exposure

Product:No data available

Components:

64742-47-8 / 64742-88-7: No data available

8052-41-3: No data available

1330-20-7: No data available

95-63-6:No data available

111-84-2:No data available

100-41-4:No data available

91-20-3:No data available

Repeated dose toxicity

Components:

64742-47-8 / 64742-88-7:

Species: Rat, male LOAEL: 750 mg/kg Application Route: Oral Exposure time: 70 - 90 days Number of exposures: daily

Dose: 0, 750, 1500, 3000 mg/kg/d

GLP: yes

Symptoms: weight loss, Liver effects, Stomach/intestinal disorders

Species: Rat, male and female

NOAEL: 24

Application Route: Inhalation Test atmosphere: vapour Exposure time: 4 wks

Number of exposures: 6 h/d, 5 d/wk

Dose: 0, 24 mg/m3

GLP: yes

Remarks: Information given is based on data obtained from similar substances.

SDS Number: 100000009023 14 / 23 A-A-59601E Type I



Version 0.0 Revision Date: 12/28/2015

8052-41-3:

Species: Rat, male and female

NOAEL: 275

Application Route: Inhalation Exposure time: 14 wks

Number of exposures: 6 h/d, 5 d/wk Dose: 138, 275, 550, 1100, 2200mg/m3

Group: yes

Symptoms: nasal symptoms, Testicular effects, Kidney disorders Remarks: male rat hydrocarbon nephropathy not relevant to humans

Species: Mouse, male and female

LOAEL: 138

Application Route: Inhalation Exposure time: 14 wks

Number of exposures: 6 h/d, 5 d/wk Dose: 138, 275, 550, 1100, 2200mg/m3

Group: yes

Symptoms: Spleen effects

Aspiration toxicity

Product:

May be fatal if swallowed and enters airways.

Components:

64742-47-8 / 64742-88-7:

May be fatal if swallowed and enters airways.

8052-41-3:

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting., Concentrations substantially above the TLV value may cause narcotic effects., Solvents may degrease the skin.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

64742-47-8 / 64742-88-7:

SDS Number: 100000009023 15 / 23 A-A-59601E Type I



Version 0.0 Revision Date: 12/28/2015

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): 2 mg/l

Exposure time: 96 h Test Type: semi-static test Analytical monitoring: yes

Method: OECD Test Guideline 203

GLP: yes

Toxicity to daphnia and

other aquatic inverte-

brates

: EL50 (Daphnia magna (Water flea)): 1.4 mg/l

Exposure time: 48 h Test Type: static test Analytical monitoring: yes

Method: OECD Test Guideline 202

GLP: yes

Toxicity to algae : EL50 (Pseudokirchneriella subcapitata (green algae)):

1 mg/l

End point: Growth rate Exposure time: 72 h Test Type: static test Analytical monitoring: yes

Method: OECD Test Guideline 201

GLP: yes

Ecotoxicology Assessment

Acute aquatic toxicity : Toxic to aquatic life.

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

8052-41-3:

Toxicity to fish : Remarks: No data available

Toxicity to daphnia and

other aquatic invertebrates : LL50 (Chaetogammarus marinus (Amphipod)): 3.5

mg/l

Exposure time: 96 h

Toxicity to algae : EbL50 (Pseudokirchneriella subcapitata (green

algae)): 2.5 mg/l End point: Biomass Exposure time: 72 h

Ecotoxicology Assessment

Acute aquatic toxicity : Toxic to aquatic life.

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

Persistence and degradability

Components:

64742-47-8 / 64742-88-7:

SDS Number: 100000009023 16 / 23 A-A-59601E Type I



Version 0.0 Revision Date: 12/28/2015

Biodegradability : aerobic

Concentration: 101 mg/l Biodegradation: 61 % Exposure time: 28 d

GLP: yes

Remarks: Readily biodegradable

8052-41-3:

Biodegradability : Remarks: No data available

Bioaccumulative potential

Components:

1330-20-7:

Partition coefficient: n-

octanol/water

: log Pow: 2.77 - 3.15

95-63-6:

Partition coefficient: n-

octanol/water

: Remarks: No data available

91-20-3:

Partition coefficient: n-

octanol/water

: log Pow: 3.4 (25 °C)

pH: 7 - 7.5

Mobility in soil

No data available

Other adverse effects

No data available

Product:

Regulation 40 CFR Protection of Environment; Part 82 Protection

of Stratospheric Ozone - CAA Section 602 Class I Sub-

stances

Remarks This product neither contains, nor was manufactured

with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A

+ B).

Additional ecological in-

formation

: An environmental hazard cannot be excluded in the

event of unprofessional handling or disposal., Toxic to

aquatic life with long lasting effects.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with all applicable local,

state and federal regulations.

SDS Number: 100000009023 17 / 23 A-A-59601E Type I



A-A-59601E Type I

Version 0.0 Revision Date: 12/28/2015

For assistance with your waste management needs - including disposal, recycling and waste stream reduction, contact NEXEO's Environmental Services Group

at 800-637-7922.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty

drum.

SECTION 14. TRANSPORT INFORMATION

IATA (International Air Transport Association): UN1268, PETROLEUM DISTILLATES, N.O.S., 3, III, Flash Point:39.44 - 45 °C(102.99 - 113 °F)

IMDG (International Maritime Dangerous Goods): UN1268, PETROLEUM DISTILLATES, N.O.S., 3, III, Marine Pollutant (MIXTURE OF PETROLEUM DISTILLATES)

DOT (Department of Transportation): UN1268, PETROLEUM DISTILLATES, N.O.S., 3, III

Special Notes: : The flash point for this material is greater than 100 F

(38 C). Therefore, in accordance with 49 CFR 173.150(f) non-bulk containers (<450L or <119 gallon capacity) of this material may be shipped as non-regulated when transported solely by land, as long as the material is not a hazardous waste, a marine pollutant, or specifically listed as a hazardous substance.

SECTION 15. REGULATORY INFORMATION

OSHA Hazards : Combustible Liquid, Carcinogen, Moderate skin

irritant, Moderate eye irritant, Moderate respiratory irritant, Specific target organ toxicity - single

exposure, Aspiration hazard

WHMIS Classification : B3: Combustible Liquid

D2A: Very Toxic Material Causing Other Toxic Effects D2B: Toxic Material Causing Other Toxic Effects

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

SDS Number: 100000009023 18 / 23 A-A-59601E Type I



A-A-59601E Type I

Version 0.0 Revision Date: 12/28/2015

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
**Mixed Xylenes	1330-20-7	100	2505

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 : Fire Hazard

Hazards Chronic (Delayed) Health Hazard

Immediate (Acute) Health Hazard

SARA 302 : No chemicals in this material are subject to the

reporting requirements of SARA Title III, Section 302.

SARA 313 : The following components are subject to reporting

levels established by SARA Title III, Section 313:

1330-20-7 **Mixed Xylenes 3.9925 %

95-63-6 **1,2,4- 1.0075 %

trimethylbenzene

100-41-4 **Ethylbenzene 0.1798 %

91-20-3 **Naphthalene 0.1798 %

Clean Air Act

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 12 (40 CFR 61):

1330-20-7	**Mixed Xylenes	3.9925 %
100-41-4	**Ethylbenzene	0.1797 %
91-20-3	**Naphthalene	0.1797 %
98-82-8	**Cumene	0.079 %
108-88-3	**Toluene	0.079 %
71-43-2	**Benzene	0.079 %

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 12 (40 CFR 61):

1330-20-7	**Mixed Xylenes	3.9925 %
100-41-4	**Ethylbenzene	0.1798 %
91-20-3	**Naphthalene	0.1798 %
98-82-8	**Cumene	0.079 %
108-88-3	**Toluene	0.079 %
71-43-2	**Benzene	0.079 %

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

The following chemical(s) are listed under the U.S. Clean Air Act Section 111 SOCMI Intermediate or Final VOC's (40 CFR 60.489):

1330-20-7	**Mixed Xylenes	3.9925 %
100-41-4	**Ethylbenzene	0.1798 %
98-82-8	**Cumene	0.079 %
108-88-3	**Toluene	0.079 %

SDS Number: 100000009023 19 / 23 A-A-59601E Type I



A-A-59601E Type I

Version 0.0	Revision Date: 12/28/2015
-------------	---------------------------

71-43-2 **Benzene 0.079 %

Clean Water Act

The following Hazardous Substances are listed under the U.S. CleanWater Act, Section 311, Table 116.4A:

1330-20-7	**Mixed Xylenes	3.9925 %
100-41-4	**Ethylbenzene	0.1798 %
91-20-3	**Naphthalene	0.1798 %
108-88-3	**Toluene	0.079 %
71-43-2	**Benzene	0.079 %

The following Hazardous Chemicals are listed under the U.S. CleanWater Act, Section 311, Table 117.3:

1330-20-7	**Mixed Xylenes	3.9925 %
100-41-4	**Ethylbenzene	0.1798 %
91-20-3	**Naphthalene	0.1798 %
108-88-3	**Toluene	0.079 %
71-43-2	**Benzene	0.079 %

This product does not contain any toxic pollutants listed under the U.S. Clean Water Act Section 307

US State Regulations

Massachusetts Right To Know

8052-41-3	Stoddard solvent	20 - 30 %
1330-20-7	**Mixed Xylenes	1 - 5 %
95-63-6	**1,2,4-trimethylbenzene	1 - 5 %
111-84-2	**Nonane	1 - 5 %
71-43-2	**Benzene	0 - 0.1 %

Pennsylvania Right To Know

64742-47-8 / 64742-88-7	Distillates (pet), hydrotreated light AND/OR Solvent naphtha (pet), med	70 - 90 %
8052-41-3	aliph. Stoddard solvent	20 - 30 %
1330-20-7	**Mixed Xylenes	1 - 5 %
95-63-6	**1,2,4-trimethylbenzene	1 - 5 %
111-84-2	**Nonane	1 - 5 %
100-41-4	**Ethylbenzene	0.1 - 1 %
91-20-3	**Naphthalene	0.1 - 1 %
98-82-8	**Cumene	0 - 0.1 %
108-88-3	**Toluene	0 - 0.1 %
71-43-2	**Benzene	0 - 0.1 %

New Jersey Right To Know

64742-47-8 /	Distillates (pet), hydrotreated light	70 - 90 %
64742-88-7	AND/OR Solvent naphtha (pet), med	
	aliph.	
8052-41-3	Stoddard solvent	20 - 30 %
1330-20-7	**Mixed Xylenes	1 - 5 %

SDS Number: 100000009023 20 / 23 A-A-59601E Type I



A-A-59601E Type I

Version 0.0		F	Revision Date: 12/28/2015	
	95-63-6 111-84-2	**1,2,4-trimethylbenzene **Nonane	1 - 5 % 1 - 5 %	
	100-41-4 91-20-3	**Ethylbenzene **Naphthalene	0.1 - 1 % 0.1 - 1 %	
California Prop 65		WARNING! This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.		
	108-88-3 71-43-2	**Toluene **Benzene WARNING! This product conta the State of California to caus		
	100-41-4 91-20-3 98-82-8 71-43-2	**Ethylbenzene **Naphthalene **Cumene **Benzene	se cancer.	

The components of this product are reported in the following inventories:

United States TSCA Inventory	:	y (positive listing) (On TSCA Invento- ry)
Canadian Domestic Substances List (DSL)	:	y (positive listing) (All components of this product are on the Canadian DSL.)
Australia Inventory of Chemical Substances (AICS)	:	y (positive listing) (On the inventory, or in compliance with the inventory)
Korea. Korean Existing Chemicals Inventory (KECI)	:	y (positive listing) (On the inventory, or in compliance with the inventory)
Philippines Inventory of Chemicals and Chemical Substances (PICCS)	:	y (positive listing) (On the inventory, or in compliance with the inventory)
China. Inventory of Existing Chemical Substances in China (IECSC)	:	y (positive listing) (On the inventory, or in compliance with the inventory)
Switzerland. New notified substances and declared preparations	:	y (positive listing) (The formulation

SDS Number: 100000009023 21 / 23 A-A-59601E Type I




A-A-59601E Type I

Revision Date: 12/28/2015 Version 0.0

SECTION 16. OTHER INFORMATION Further information

NFPA:



Special hazard.

HMIS III:

HEALTH	2*
FLAMMABILITY	2
PHYSICAL HAZARD	0

0 = not significant, 1 = Slight,

2 = Moderate, 3 = High 4 =Extreme, * = Chronic

The information accumulated is based on the data of which we are aware and is believed to be correct as of the date hereof. Since this information may be applied under conditions beyond our control and with which we may be unfamiliar and since data made become available subsequently to the date hereof, we do not assume any responsibility for the results of its use. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This MSDS has been prepared by NEXEO™ Solutions EHS Product Safety Department (1-855-429-2661) MSDS@nexeosolutions.com.

Material number:

16060760, 16072414, 16056892, 16056891, 16056890, 16056374, 16056373

Key or leg	Key or legend to abbreviations and acronyms used in the safety data sheet				
ACGIH	American Conference of Government Industrial Hygienists	LD50	Lethal Dose 50%		
ATCC	, :	1005	Lawart Observed Adverse Effect		
AICS	Australia, Inventory of Chemical Substances	LOAEL	Lowest Observed Adverse Effect Level		
DSL	Canada, Domestic Substances List	NFPA	National Fire Protection Agency		
NDSL	Canada, Non-Domestic Sub-	NIOSH	National Institute for Occupational		
	stances List		Safety & Health		
CNS	Central Nervous System	NTP	National Toxicology Program		
CAS	Chemical Abstract Service	NZIoC	New Zealand Inventory of Chemicals		

SDS Number: 10000009023 22 / 23 A-A-59601E Type I



Version 0.0 Revision Date: 12/28/2015

EC50	Effective Concentration	NOAEL	No Observable Adverse Effect Level
EC50	Effective Concentration 50%	NOEC	No Observed Effect Concentration
EGEST	EOSCA Generic Exposure Scenario Tool	OSHA	Occupational Safety & Health Administration
EOSCA	European Oilfield Specialty Chemicals Association	PEL	Permissible Exposure Limit
EINECS	European Inventory of Existing Chemical Substances	PICCS	Philipines Inventory of Commercial Chemical Substances
MAK	Germany Maximum Concentration Values	PRNT	Presumed Not Toxic
GHS	Globally Harmonized System	RCRA	Resource Conservation Recovery Act
>=	Greater Than or Equal To	STEL	Short-term Exposure Limit
IC50	Inhibition Concentration 50%	SARA	Superfund Amendments and Reauthorization Act.
IARC	International Agency for Research on Cancer	TLV	Threshold Limit Value
IECSC	Inventory of Existing Chemical Substances in China	TWA	Time Weighted Average
ENCS	Japan, Inventory of Existing and New Chemical Substances	TSCA	Toxic Substance Control Act
KECI	Korea, Existing Chemical Inventory	UVCB	Unknown or Variable Compositon, Complex Reaction Products, and Biological Materials
<=	Less Than or Equal To	WHMIS	Workplace Hazardous Materials Information System
LC50		Lethal Concentration 50%	