



# SAFETY DATA SHEET

Issuing Date: 31-Jul-2015

Revision Date: 29-Jan-2017

Revision Number: 2

## 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product Code: PG-6-R103FC

Product Name: POLYURETHANE TOPCOAT GLOSS-FAST  
CURE BAC-1873 RED

Hentzen Coatings, Inc.  
6937 West Mill Road, Milwaukee, WI 53218-1225

Company Phone Number: 1-414-353-4200

Emergency telephone number ChemTrec 1-800-424-9300

Recommended use of the chemical and restrictions on use

Industrial paint (Paint or Paint-Related), Restricted to professional users

## 2. HAZARDS IDENTIFICATION

### Classification

#### OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)


Acute toxicity - Oral	Category 4
Acute toxicity - Inhalation (Dusts/Mists)	Category 4
Skin Corrosion/Irritation	Category 2
Serious eye damage/eye irritation	Category 2
Germ Cell Mutagenicity	Category 1B
Carcinogenicity	Category 1B
Flammable Liquids	Category 2

### Label Elements

#### Emergency Overview

**DANGER**

**Hazard Statements**  
 Harmful if swallowed  
 harmful if inhaled  
 Causes skin irritation  
 Causes serious eye irritation  
 May cause genetic defects  
 May cause cancer  
 Highly flammable liquid and vapor



**Appearance** Opaque                      **Physical state** Liquid                      **Odor** Solvent

### Precautionary Statements - Prevention

- Obtain special instructions before use
- Do not handle until all safety precautions have been read and understood
- Use personal protective equipment as required
- Wash face, hands and any exposed skin thoroughly after handling

Do not eat, drink or smoke when using this product  
 Avoid breathing dust/fume/gas/mist/vapors/spray  
 Use only outdoors or in a well-ventilated area  
 Wear eye/face protection  
 Keep away from heat/sparks/open flames/hot surfaces. - No smoking  
 Keep container tightly closed  
 Ground/Bond container and receiving equipment  
 Use explosion-proof electrical/ ventilating/ lighting/ equipment  
 Use only non-sparking tools  
 Take precautionary measures against static discharge

**Precautionary Statements - Response**

IF exposed or concerned: Get medical advice/attention  
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
 If eye irritation persists: Get medical advice/attention  
 If skin irritation occurs: Get medical advice/attention  
 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower  
 Wash contaminated clothing before reuse  
 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing  
 IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell  
 Rinse mouth  
 In case of fire: Use CO2, dry chemical, or foam for extinction

**Precautionary Statements - Storage**

Store in a well-ventilated place. Keep cool  
 Store in accordance with local regulations

**Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

**Hazards not otherwise classified (HNOC)**

**Other information**

- Harmful to aquatic life

**3. COMPOSITION/INFORMATION ON INGREDIENTS**

**Contains a known or suspected carcinogen**

This product contains substances regulated as hazardous air pollutants (HAPS) under Section 112 of the Clean Air Act Amendments of 1990. See Section 15 for list of HAPS.

Chemical Name	CAS No	Weight-%	ACGIH	OSHA
BARIUM SULFATE	7727-43-7	20% - 30%	TWA: 5 mg/m <sup>3</sup> inhalable particulate matter, particulate matter containing no asbestos and <1% crystalline silica	TWA: 15 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable fraction
METHYL AMYL KETONE	110-43-0	20% - 30%	TWA: 50 ppm	TWA: 100 ppm TWA: 465 mg/m <sup>3</sup>
XYLENE(PURE)	1330-20-7	1% - 5%	STEL: 150 ppm TWA: 100 ppm	TWA: 100 ppm TWA: 435 mg/m <sup>3</sup>
ETHYL ACETATE	141-78-6	1% - 5%	TWA: 400 ppm	TWA: 400 ppm TWA: 1400 mg/m <sup>3</sup>
TITANIUM DIOXIDE	13463-67-7	1% - 5%	TWA: 10 mg/m <sup>3</sup>	TWA: 15 mg/m <sup>3</sup> total dust
BUTYL ACETATE	123-86-4	1% - 5%	STEL: 150 ppm TWA: 50 ppm	TWA: 150 ppm TWA: 710 mg/m <sup>3</sup>
ETHYLBENZENE	100-41-4	0% - 1%	TWA: 20 ppm	TWA: 100 ppm TWA: 435 mg/m <sup>3</sup>
ALIPHATIC PETROLEUM DISTILLATES	64742-89-8	0% - 1%	N/A	N/A
METHYL ISOBUTYL KETONE	108-10-1	0% - 1%	STEL: 75 ppm	TWA: 100 ppm

			TWA: 20 ppm	TWA: 410 mg/m <sup>3</sup>
--	--	--	-------------	----------------------------

**4. FIRST AID MEASURES**

**First Aid Measures**

<b>General advice</b>	Immediate medical attention is required. Show this safety data sheet to the doctor in attendance.
<b>Eye Contact</b>	Immediately flush eyes with water for at least 15 minutes. Get medical attention. If easy to do, remove contact lenses. Keep eye wide open while rinsing. If symptoms persist, call a physician.
<b>Skin Contact</b>	Wash off immediately with plenty of water.
<b>Inhalation</b>	Consult a physician if necessary. If breathing is irregular or stopped, administer artificial respiration. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation.
<b>Ingestion</b>	Do NOT induce vomiting. Call a physician immediately. Never give anything by mouth to an unconscious person.
<b>Self-protection of the first aider</b>	Remove all sources of ignition.
<b>Most important symptoms and effects, both acute and delayed</b>	
<b>Most Important Symptoms and Effects</b>	No information available.
<b>Indication of any immediate medical attention and special treatment needed</b>	
<b>Notes to physician</b>	Treat symptomatically.

**5. FIRE-FIGHTING MEASURES**

**Suitable Extinguishing Media**

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

**Unsuitable Extinguishing Media** No information available.

**Specific hazards arising from the chemical**

Extremely flammable.

**Explosion Data**

**Sensitivity to Mechanical Impact** no data available.

**Sensitivity to Static Discharge** Yes.

**Protective equipment and precautions for firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

**6. ACCIDENTAL RELEASE MEASURES**

**Personal precautions, protective equipment and emergency procedures**

**Personal Precautions** Remove all sources of ignition. Evacuate personnel to safe areas. Ensure adequate ventilation. Use personal protective equipment as required. Avoid breathing vapors or mists. Ventilate the area.

**Environmental Precautions**

**Environmental Precautions** Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. Do

not flush into surface water or sanitary sewer system. Vapors are heavier than air, spread along floors and form explosive mixtures with air.

**Methods and materials for containment and cleaning up**

**Methods for Containment**

Prevent further leakage or spillage if safe to do so.

**Methods for Cleaning Up**

Pick up and transfer to properly labeled containers. Dam up. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Soak up with inert absorbent material.

**7. HANDLING AND STORAGE**

**Precautions for safe handling**

**Advice on safe handling**

Ensure adequate ventilation. Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharges. Use explosion-proof electrical (ventilation and lighting) equipment. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). To dissipate static electricity during transfer, ground drum and connect to receiving container with bonding strap. Use only non-sparking tools.

**Conditions for safe storage, including any incompatibilities**

**Storage Conditions**

Keep tightly closed in a dry and cool place. Keep in properly labeled containers. Keep away from heat, sparks and flame.

**Incompatible Products**

None known based on information supplied.

**8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

**Control parameters**

**Exposure Guidelines**

Chemical Name	ACGIH	OSHA	NIOSH IDLH
BARIUM SULFATE 7727-43-7	TWA: 5 mg/m <sup>3</sup> inhalable particulate matter, particulate matter containing no asbestos and <1% crystalline silica	TWA: 15 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable fraction	TWA: 10 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable dust
METHYL AMYL KETONE 110-43-0	TWA: 50 ppm	TWA: 100 ppm TWA: 465 mg/m <sup>3</sup>	IDLH: 800 ppm TWA: 100 ppm TWA: 465 mg/m <sup>3</sup>
XYLENE(PURE) 1330-20-7	STEL: 150 ppm TWA: 100 ppm	TWA: 100 ppm TWA: 435 mg/m <sup>3</sup>	
ETHYL ACETATE 141-78-6	TWA: 400 ppm	TWA: 400 ppm TWA: 1400 mg/m <sup>3</sup>	IDLH: 2000 ppm TWA: 400 ppm TWA: 1400 mg/m <sup>3</sup>
TITANIUM DIOXIDE 13463-67-7	TWA: 10 mg/m <sup>3</sup>	TWA: 15 mg/m <sup>3</sup> total dust	IDLH: 5000 mg/m <sup>3</sup>
BUTYL ACETATE 123-86-4	STEL: 150 ppm TWA: 50 ppm	TWA: 150 ppm TWA: 710 mg/m <sup>3</sup>	IDLH: 1700 ppm TWA: 150 ppm TWA: 710 mg/m <sup>3</sup> STEL: 200 ppm STEL: 950 mg/m <sup>3</sup>
ETHYLBENZENE 100-41-4	TWA: 20 ppm	TWA: 100 ppm TWA: 435 mg/m <sup>3</sup>	IDLH: 800 ppm TWA: 100 ppm TWA: 435 mg/m <sup>3</sup> STEL: 125 ppm STEL: 545 mg/m <sup>3</sup>
METHYL ISOBUTYL KETONE 108-10-1	STEL: 75 ppm TWA: 20 ppm	TWA: 100 ppm TWA: 410 mg/m <sup>3</sup>	IDLH: 500 ppm TWA: 50 ppm TWA: 205 mg/m <sup>3</sup> STEL: 75 ppm

			STEL: 300 mg/m <sup>3</sup>
--	--	--	-----------------------------

NIOSH IDLH: Immediately Dangerous to Life or Health

**Exposure controls**

**Engineering Measures**                      Showers  
     Eyewash stations  
     Ventilation systems.

**Individual protection measures, such as personal protective equipment**

**Eye/Face Protection**                      Use personal protective equipment as required.

**Skin and Body Protection**                Chemical resistant apron.

**Respiratory Protection**                 If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

**Hygiene Measures**                         Do not eat, drink or smoke when using this product. Regular cleaning of equipment, work area and clothing is recommended.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

<b>Physical state</b>	Liquid	<b>Appearance</b>	Opaque
<b>Odor</b>	Solvent.	<b>Odor Threshold</b>	No data available
<b>pH</b>	No data available	<b>Flash Point</b>	12 °F / -11 °C
<b>Decomposition temperature</b>	No data available	<b>Boiling Point</b>	170 °F / 77 °C
<b>Melting Point / Melting Range</b>	No data available	<b>Freezing Point</b>	No data available
<b>Vapor Pressure @20°C (kPa)</b>	No data available	<b>Partition coefficient:</b>	No data available
<b>Vapor Density</b>	No data available	<b>Density</b>	No data available
<b>Bulk density</b>	No data available	<b>Specific Gravity</b>	1.22
<b>Evaporation Rate</b>	No data available	<b>Water solubility</b>	No data available
<b>Dynamic viscosity</b>	No data available	<b>Weight per Gallon (lbs/gal):</b>	10.13
		<b>Flammability Limits in Air</b>	
		<b>Upper</b>	2.7 %
		<b>Lower</b>	0.41 %

**10. STABILITY AND REACTIVITY**

**Reactivity**  
 No data available

**Chemical stability**  
 Stable under recommended storage conditions.

**Conditions to Avoid**  
 Extremes of temperature and direct sunlight.

**Incompatible Materials**  
 None known based on information supplied.

**Hazardous Decomposition Products**  
 None known based on information supplied.

**11. TOXICOLOGICAL INFORMATION**

**Information on likely routes of exposure**

**Product Information**                         The product has not been tested

**Inhalation** There is no data for this product.  
**Eye Contact** There is no data for this product.  
**Skin Contact** There is no data for this product.  
**Ingestion** There is no data for this product.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
METHYL AMYL KETONE 110-43-0	= 1600 mg/kg ( Rat )	= 12.6 mL/kg ( Rabbit )	> 2000 ppm ( Rat ) 4 h
XYLENE(PURE) 1330-20-7	= 3500 mg/kg ( Rat )	> 4350 mg/kg ( Rabbit )	= 29.08 mg/L ( Rat ) 4 h
ETHYL ACETATE 141-78-6	= 5620 mg/kg ( Rat )	> 18000 mg/kg ( Rabbit )	N/A
TITANIUM DIOXIDE 13463-67-7	> 10000 mg/kg ( Rat )	N/A	N/A
BUTYL ACETATE 123-86-4	= 10768 mg/kg ( Rat )	> 17600 mg/kg ( Rabbit )	= 390 ppm ( Rat ) 4 h
ETHYLBENZENE 100-41-4	= 3500 mg/kg ( Rat )	= 15400 mg/kg ( Rabbit )	= 17.4 mg/L ( Rat ) 4 h
METHYL ISOBUTYL KETONE 108-10-1	= 2080 mg/kg ( Rat )	= 3000 mg/kg ( Rabbit )	= 8.2 mg/L ( Rat ) 4 h

**Information on toxicological effects**

**Symptoms** No information available.

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

**Sensitization** No information available.  
**MUTAGENIC EFFECTS** No information available.  
**Carcinogenicity** This product contains one or more substances which are classified by IARC as carcinogenic to humans (Group I), probably carcinogenic to humans (Group 2A) or possibly carcinogenic to humans (Group 2B).

Chemical Name	ACGIH	IARC	NTP	OSHA
XYLENE(PURE) 1330-20-7	N/A	Group 3	N/A	N/A
TITANIUM DIOXIDE 13463-67-7	N/A	Group 2B	N/A	X
ETHYLBENZENE 100-41-4	A3	Group 2B	N/A	X
METHYL ISOBUTYL KETONE 108-10-1	A3	Group 2B	N/A	X

**Legend:**

ACGIH (American Conference of Governmental Industrial Hygienists)  
A3 - Animal Carcinogen  
IARC (International Agency for Research on Cancer)  
Group 2B - Possibly Carcinogenic to Humans  
Group 3 - Not Classifiable as to Carcinogenicity in Humans  
OSHA (Occupational Safety and Health Administration of the US Department of Labor)  
X - Present

**Reproductive Toxicity** No information available.  
**Specific target organ systemic toxicity (single exposure)** No information available.  
**Specific target organ systemic toxicity (repeated exposure)** No information available.  
**Target Organ Effects** Central nervous system (CNS), Eyes, Lungs, Peripheral Nervous System (PNS), Respiratory system, Skin.  
**Aspiration hazard** No information available.

**Numerical measures of toxicity - Product Information**

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral)	992 mg/kg
ATEmix (dermal)	10686 mg/kg
ATEmix (inhalation-dust/mist)	1.9 mg/l
Oral LD50	1551 mg/kg (rat) Estimated
Dermal LD50	26738 mg/kg (rat) Estimated

**12. ECOLOGICAL INFORMATION**

**Ecotoxicity**

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to daphnia and other aquatic invertebrates
METHYL AMYL KETONE 110-43-0	N/A	126 - 137: 96 h Pimephales promelas mg/L LC50 flow-through	N/A
XYLENE(PURE) 1330-20-7	N/A	13.1 - 16.5: 96 h Lepomis macrochirus mg/L LC50 flow-through 13.5 - 17.3: 96 h Oncorhynchus mykiss mg/L LC50 2.661 - 4.093: 96 h Oncorhynchus mykiss mg/L LC50 static 23.53 - 29.97: 96 h Pimephales promelas mg/L LC50 static 30.26 - 40.75: 96 h Poecilia reticulata mg/L LC50 static 7.711 - 9.591: 96 h Lepomis macrochirus mg/L LC50 static 13.4: 96 h Pimephales promelas mg/L LC50 flow-through 19: 96 h Lepomis macrochirus mg/L LC50 780: 96 h Cyprinus carpio mg/L LC50 semi-static 780: 96 h Cyprinus carpio mg/L LC50	0.6: 48 h Gammarus lacustris mg/L LC50 3.82: 48 h water flea mg/L EC50
ETHYL ACETATE 141-78-6	N/A	220 - 250: 96 h Pimephales promelas mg/L LC50 flow-through 352 - 500: 96 h Oncorhynchus mykiss mg/L LC50 semi-static 484: 96 h Oncorhynchus mykiss mg/L LC50 flow-through	560: 48 h Daphnia magna mg/L EC50 Static
BUTYL ACETATE 123-86-4	674.7: 72 h Desmodesmus subspicatus mg/L EC50	17 - 19: 96 h Pimephales promelas mg/L LC50 flow-through 100: 96 h Lepomis macrochirus mg/L LC50 static	N/A
ETHYLBENZENE 100-41-4	1.7 - 7.6: 96 h Pseudokirchneriella subcapitata mg/L EC50 static 2.6 - 11.3: 72 h Pseudokirchneriella subcapitata mg/L EC50 static 4.6: 72 h Pseudokirchneriella subcapitata mg/L EC50 438: 96 h Pseudokirchneriella subcapitata mg/L EC50	11.0 - 18.0: 96 h Oncorhynchus mykiss mg/L LC50 static 7.55 - 11: 96 h Pimephales promelas mg/L LC50 flow-through 9.1 - 15.6: 96 h Pimephales promelas mg/L LC50 static 32: 96 h Lepomis macrochirus mg/L LC50 static 4.2: 96 h Oncorhynchus mykiss mg/L LC50 semi-static 9.6: 96 h Poecilia reticulata mg/L LC50 static	1.8 - 2.4: 48 h Daphnia magna mg/L EC50
METHYL ISOBUTYL KETONE 108-10-1	400: 96 h Pseudokirchneriella subcapitata mg/L EC50	496 - 514: 96 h Pimephales promelas mg/L LC50 flow-through	170: 48 h Daphnia magna mg/L EC50

**Persistence and degradability**

No information available.

**Bioaccumulation**

No information available.

Chemical Name	Partition coefficient
METHYL AMYL KETONE 110-43-0	1.98

XYLENE(PURE) 1330-20-7	3.15
ETHYL ACETATE 141-78-6	0.6
BUTYL ACETATE 123-86-4	1.81
ETHYLBENZENE 100-41-4	3.2
METHYL ISOBUTYL KETONE 108-10-1	1.19

**Other adverse effects** No information available

### 13. DISPOSAL CONSIDERATIONS

**Waste treatment methods**

**Waste treatment methods** This material, as supplied, is a hazardous waste according to federal regulations (40 CFR 261).

**US EPA Waste Number** D001

Chemical Name	RCRA - Basis for Listing	RCRA - D Series Wastes
XYLENE(PURE) 1330-20-7	Included in waste stream: F039	N/A
ETHYL ACETATE 141-78-6	Included in waste stream: F039	N/A
ETHYLBENZENE 100-41-4	Included in waste stream: F039	N/A
METHYL ISOBUTYL KETONE 108-10-1	Included in waste stream: F039	N/A

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste Status
XYLENE(PURE) 1330-20-7	Toxic Ignitable
ETHYL ACETATE 141-78-6	Toxic Ignitable
BUTYL ACETATE 123-86-4	Toxic
ETHYLBENZENE 100-41-4	Toxic Ignitable

### 14. TRANSPORT INFORMATION

**DOT**

**UN-No** UN1263  
**Proper shipping name** Paint  
**Hazard class** 3  
**Packing Group** II  
**Special Provisions** 149, B52, IB2, T4, TP1, TP8, TP28  
**Description** UN1263, Paint, 3, II, RQ  
**Emergency Response Guide Number** 128

**TDG**

**UN-No** UN1263  
**Proper shipping name** Paint  
**Hazard class** 3  
**Packing Group** II



---

Description UN1263, Paint, 3, II

**MEX**

UN-No UN1263  
Proper shipping name Paint  
Hazard class 3  
Packing Group II  
Description UN1263, Paint, 3, II

**ICAO**

UN-No UN1263  
Proper shipping name Paint  
Hazard class 3  
Packing Group II  
Special Provisions A3, A72  
Description UN1263, Paint, 3, II

**IATA**

UN-No UN1263  
Hazard class 3  
Packing Group II  
ERG Code 3L  
Special Provisions A3, A72, A192

**IMDG/IMO**

UN-No UN1263  
Hazard class 3  
Packing Group II  
EmS-No F-E, S-E  
Special Provisions 163, 367

**RID**

UN-No UN1263  
Proper shipping name Paint  
Hazard class 3  
Packing Group II  
Classification Code F1  
Description UN1263, Paint, 3, II

**ADR/RID**

UN-No UN1263  
Proper shipping name Paint  
Hazard class 3  
Packing Group II  
Classification Code F1  
Tunnel restriction code (D/E)  
Special Provisions 163, 640C, 650, 367  
Description UN1263, Paint, 3, II, (D/E)  
ADR/RID-Labels 3

**ADN**

Proper shipping name Paint  
Hazard class 3  
Packing Group II  
Classification Code F1  
Special Provisions 163, 640C, 650  
Description UN1263, Paint, 3, II  
Hazard Labels 3  
Limited Quantity (LQ) 5 L  
Ventilation VE01

**15. REGULATORY INFORMATION**

**International Inventories**

TSCA	Complies
DSL/NDSL	Complies
EINECS/ELINCS	Complies
ENCS	Complies
IECSC	Complies
KECL	Complies
PICCS	Complies
AICS	Complies

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory  
 DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List  
 EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances  
 ENCS - Japan Existing and New Chemical Substances  
 IECSC - China Inventory of Existing Chemical Substances  
 KECL - Korean Existing and Evaluated Chemical Substances  
 PICCS - Philippines Inventory of Chemicals and Chemical Substances  
 AICS - Australian Inventory of Chemical Substances

**US Federal Regulations**

**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	CAS No	SARA 313 - Threshold Values %
XYLENE(PURE)	1330-20-7	1.0
ETHYLBENZENE	100-41-4	0.1

**SARA 311/312 Hazard Categories**

Acute Health Hazard	Yes
Chronic Health Hazard	No
Fire Hazard	Yes
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

**CAA (Clean Air Act)**

U.S. - CAA (Clean Air Act) - 1990 Hazardous Air Pollutants This product contains the following HAPs:

Chemical Name	CAS No	Hazardous air pollutants (HAPs) content
XYLENE(PURE)	1330-20-7	Present
ETHYLBENZENE	100-41-4	Present
METHYL ISOBUTYL KETONE	108-10-1	Present

**Clean Water Act**

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42):

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
XYLENE(PURE)	100 lb	N/A	N/A	X
BUTYL ACETATE	5000 lb	N/A	N/A	X
ETHYLBENZENE	1000 lb	X	X	X

**CERCLA**

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances	RQ (reportable quantity)
---------------	--------------------------	--------------------------------	--------------------------

		RQs	
XYLENE(PURE)	100 lb	N/A	RQ 100 lb final RQ RQ 45.4 kg final RQ
ETHYL ACETATE	5000 lb	N/A	RQ 5000 lb final RQ RQ 2270 kg final RQ
BUTYL ACETATE	5000 lb	N/A	RQ 5000 lb final RQ RQ 2270 kg final RQ
ETHYLBENZENE	1000 lb	N/A	RQ 1000 lb final RQ RQ 454 kg final RQ
METHYL ISOBUTYL KETONE	5000 lb	N/A	RQ 5000 lb final RQ RQ 2270 kg final RQ

**State Regulations**

**California Proposition 65**

This product contains the following Proposition 65 chemicals

Chemical Name	CAS No	California Proposition 65
TITANIUM DIOXIDE	13463-67-7	Carcinogen
ETHYLBENZENE	100-41-4	Carcinogen
METHYL ISOBUTYL KETONE	108-10-1	Carcinogen Developmental

**U.S. State Right-to-Know Regulations**

Chemical Name	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
BARIUM SULFATE	X	X	X	N/A	X
METHYL AMYL KETONE	X	X	X	N/A	N/A
XYLENE(PURE)	X	X	X	X	X
ETHYL ACETATE	X	X	X	N/A	N/A
TITANIUM DIOXIDE	X	X	X	N/A	X
BUTYL ACETATE	X	X	X	N/A	N/A
ETHYLBENZENE	X	X	X	X	X
METHYL ISOBUTYL KETONE	X	X	X	X	N/A

**International Regulations**

**Mexico - Grade**

Serious risk, Grade 3

Chemical Name	Carcinogenic Status	Exposure Limits
METHYL AMYL KETONE	N/A	Mexico: TWA 50 ppm Mexico: TWA 235 mg/m <sup>3</sup> Mexico: STEL 100 ppm Mexico: STEL 465 mg/m <sup>3</sup>
XYLENE(PURE)	N/A	Mexico: TWA 100 ppm Mexico: TWA 435 mg/m <sup>3</sup> Mexico: STEL 150 ppm Mexico: STEL 655 mg/m <sup>3</sup>
ETHYL ACETATE	N/A	Mexico: TWA 400 ppm Mexico: TWA 1400 mg/m <sup>3</sup>
TITANIUM DIOXIDE	N/A	Mexico: TWA 10 mg/m <sup>3</sup> Mexico: STEL 20 mg/m <sup>3</sup>
BUTYL ACETATE	N/A	Mexico: TWA 150 ppm Mexico: TWA 710 mg/m <sup>3</sup> Mexico: STEL 200 ppm Mexico: STEL 950 mg/m <sup>3</sup>
ETHYLBENZENE	N/A	Mexico: TWA 100 ppm Mexico: TWA 435 mg/m <sup>3</sup> Mexico: STEL 125 ppm Mexico: STEL 545 mg/m <sup>3</sup>
METHYL ISOBUTYL KETONE	N/A	Mexico: TWA 50 ppm Mexico: TWA 205 mg/m <sup>3</sup> Mexico: STEL 75 ppm Mexico: STEL 307 mg/m <sup>3</sup>

**16. OTHER INFORMATION**

**NFPA**                      Health Hazard 2                      Flammability 3                      Instability 0                      Physical and Chemical Hazards -

NFPA Rating



**HMIS**                      Health Hazard 1 \*                      Flammability 3                      Physical Hazard 0                      Personal protection X

*Chronic Hazard Star Legend*

*\* Chronic Health Hazard*

**Issuing Date:**                      31-Jul-2015  
**Revision Date:**                      29-Jan-2017  
**Revision Note**  
No information available

**Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. PG-6-R103FCGV

**end**



# SAFETY DATA SHEET

Issuing Date: 23-Apr-2015

Revision Date: 23-Apr-2015

Revision Number: 1

## 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product Code: PH-34FC

Product Name: POLYURETHANE CURING SOLUTION - FAST CURE

Hentzen Coatings, Inc.  
6937 West Mill Road, Milwaukee, WI 53218-1225

Company Phone Number: 1-414-353-4200  
Emergency telephone number ChemTrec 1-800-424-9300

Recommended use of the chemical and restrictions on use

Industrial paint (Paint or Paint-Related), Restricted to professional users

## 2. HAZARDS IDENTIFICATION

### Classification

#### OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Acute toxicity - Oral	Category 3
Serious eye damage/eye irritation	Category 2
Carcinogenicity	Category 2
Reproductive Toxicity	Category 2
Specific target organ toxicity (repeated exposure)	Category 2
Flammable Liquids	Category 2

### Label Elements

#### Emergency Overview

#### DANGER

#### Hazard Statements

Toxic if swallowed  
Causes serious eye irritation  
Suspected of causing cancer  
Suspected of damaging fertility or the unborn child  
May cause damage to organs through prolonged or repeated exposure  
Highly flammable liquid and vapor



Appearance Opaque

Physical state Liquid

Odor Solvent

**Precautionary Statements - Prevention**

Obtain special instructions before use  
 Do not handle until all safety precautions have been read and understood  
 Use personal protective equipment as required  
 Wash face, hands and any exposed skin thoroughly after handling  
 Do not eat, drink or smoke when using this product  
 Wear eye/face protection  
 Do not breathe dust/fume/gas/mist/vapors/spray  
 Keep away from heat/sparks/open flames/hot surfaces. - No smoking  
 Keep container tightly closed  
 Ground/Bond container and receiving equipment  
 Use explosion-proof electrical/ ventilating/ lighting/ equipment  
 Use only non-sparking tools  
 Take precautionary measures against static discharge

**Precautionary Statements - Response**

IF exposed or concerned: Get medical advice/attention  
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
 If eye irritation persists: Get medical advice/attention  
 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower  
 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician  
 Rinse mouth  
 In case of fire: Use CO2, dry chemical, or foam for extinction

**Precautionary Statements - Storage**

Store in a well-ventilated place. Keep cool  
 Store in accordance with local regulations

**Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

**Hazards not otherwise classified (HNOC)**

Other information

**3. COMPOSITION/INFORMATION ON INGREDIENTS**

Contains a known or suspected carcinogen

This product contains substances regulated as hazardous air pollutants (HAPS) under Section 112 of the Clean Air Act Amendments of 1990. See Section 15 for list of HAPS.

Chemical Name	CAS No	Weight-%	ACGIH	OSHA
METHYL ETHYL KETONE	78-93-3	10% - 20%	STEL: 300 ppm TWA: 200 ppm	TWA: 200 ppm TWA: 590 mg/m <sup>3</sup>
ACETYLACETONE	123-54-6	5% - 10%	TWA: 25 ppm S*	N/A
BUTYL ACETATE	123-86-4	5% - 10%	STEL: 200 ppm TWA: 150 ppm	TWA: 150 ppm TWA: 710 mg/m <sup>3</sup>
METHYL AMYL KETONE	110-43-0	1% - 5%	TWA: 50 ppm	TWA: 100 ppm TWA: 465 mg/m <sup>3</sup>
CYCLOHEXANONE	108-94-1	1% - 5%	STEL: 50 ppm TWA: 20 ppm S*	TWA: 50 ppm TWA: 200 mg/m <sup>3</sup>
METHYL ISOBUTYL KETONE	108-10-1	1% - 5%	STEL: 75 ppm TWA: 20 ppm	TWA: 100 ppm TWA: 410 mg/m <sup>3</sup>
TOLUENE	108-88-3	1% - 5%	TWA: 20 ppm	TWA: 200 ppm Ceiling: 300 ppm

#### 4. FIRST AID MEASURES

##### First Aid Measures

<b>Eye Contact</b>	Rinse thoroughly with plenty of water for at least 15 minutes, lifting lower and upper eyelids. Consult a physician.
<b>Skin Contact</b>	Wash skin with soap and water.
<b>Inhalation</b>	Remove to fresh air.
<b>Ingestion</b>	Call a physician immediately. Never give anything by mouth to an unconscious person. Do NOT induce vomiting.

##### **Most important symptoms and effects, both acute and delayed**

**Most Important Symptoms and Effects** No information available.

##### **Indication of any immediate medical attention and special treatment needed**

**Notes to physician** Treat symptomatically.

#### 5. FIRE-FIGHTING MEASURES

##### Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

**Unsuitable Extinguishing Media** No information available.

##### Specific hazards arising from the chemical

Extremely flammable.

##### Explosion Data

**Sensitivity to Mechanical Impact** no data available.

**Sensitivity to Static Discharge** Yes.

##### Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

#### 6. ACCIDENTAL RELEASE MEASURES

##### Personal precautions, protective equipment and emergency procedures

**Personal Precautions** Use personal protective equipment as required. Remove all sources of ignition. Avoid breathing vapors or mists. Ventilate the area.

##### Environmental Precautions

**Environmental Precautions** Do not flush into surface water or sanitary sewer system. Vapors are heavier than air, spread along floors and form explosive mixtures with air.

##### Methods and materials for containment and cleaning up

**Methods for Containment** Prevent further leakage or spillage if safe to do so.

**Methods for Cleaning Up** Soak up with inert absorbent material.

**7. HANDLING AND STORAGE**

**Precautions for safe handling**

**Advice on safe handling** To dissipate static electricity during transfer, ground drum and connect to receiving container with bonding strap. Use only non-sparking tools.

**Conditions for safe storage, including any incompatibilities**

**Storage Conditions** Keep away from heat, sparks and flame.

**Incompatible Products** None known based on information supplied.

**8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

**Control parameters**

**Exposure Guidelines**

Chemical Name	ACGIH	OSHA	NIOSH IDLH
METHYL ETHYL KETONE 78-93-3	STEL: 300 ppm TWA: 200 ppm	TWA: 200 ppm TWA: 590 mg/m <sup>3</sup>	IDLH: 3000 ppm TWA: 200 ppm TWA: 590 mg/m <sup>3</sup> STEL: 300 ppm STEL: 885 mg/m <sup>3</sup>
TERTIARY BUTYL ACETATE 540-88-5	TWA: 200 ppm	TWA: 200 ppm TWA: 950 mg/m <sup>3</sup>	IDLH: 1500 ppm TWA: 200 ppm TWA: 950 mg/m <sup>3</sup>
ACETYLACETONE 123-54-6	TWA: 25 ppm S*	N/A	
BUTYL ACETATE 123-86-4	STEL: 200 ppm TWA: 150 ppm	TWA: 150 ppm TWA: 710 mg/m <sup>3</sup>	IDLH: 1700 ppm TWA: 150 ppm TWA: 710 mg/m <sup>3</sup> STEL: 200 ppm STEL: 950 mg/m <sup>3</sup>
METHYL AMYL KETONE 110-43-0	TWA: 50 ppm	TWA: 100 ppm TWA: 465 mg/m <sup>3</sup>	IDLH: 800 ppm TWA: 100 ppm TWA: 465 mg/m <sup>3</sup>
CYCLOHEXANONE 108-94-1	STEL: 50 ppm TWA: 20 ppm S*	TWA: 50 ppm TWA: 200 mg/m <sup>3</sup>	IDLH: 700 ppm TWA: 25 ppm TWA: 100 mg/m <sup>3</sup>
METHYL ISOBUTYL KETONE 108-10-1	STEL: 75 ppm TWA: 20 ppm	TWA: 100 ppm TWA: 410 mg/m <sup>3</sup>	IDLH: 500 ppm TWA: 50 ppm TWA: 205 mg/m <sup>3</sup> STEL: 75 ppm STEL: 300 mg/m <sup>3</sup>
TOLUENE 108-88-3	TWA: 20 ppm	TWA: 200 ppm Ceiling: 300 ppm	IDLH: 500 ppm TWA: 100 ppm TWA: 375 mg/m <sup>3</sup> STEL: 150 ppm STEL: 560 mg/m <sup>3</sup>

NIOSH IDLH: Immediately Dangerous to Life or Health

**Exposure controls**

**Engineering Measures** Showers  
Eyewash stations  
Ventilation systems.



**Individual protection measures, such as personal protective equipment**

<b>Eye/Face Protection</b>	If splashes are likely to occur, wear safety glasses with side-shields.
<b>Skin and Body Protection</b>	Chemical resistant apron.
<b>Respiratory Protection</b>	If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.
<b>Hygiene Measures</b>	Handle in accordance with good industrial hygiene and safety practice.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

<b>Physical state</b>	Liquid	<b>Appearance</b>	Opaque
<b>Odor</b>	Solvent.	<b>Odor Threshold</b>	No data available
<b>pH</b>	No data available	<b>Flash Point</b>	12 °F / -11 °C
<b>Decomposition temperature</b>	No data available	<b>Boiling Point</b>	171 °F / 77 °C
<b>Melting Point / Melting Range</b>	No data available	<b>Freezing Point</b>	No data available
<b>Vapor Pressure @20°C (kPa)</b>	No data available	<b>Partition coefficient:</b>	No data available
<b>Vapor Density</b>	No data available	<b>Density</b>	No data available
<b>Bulk density</b>	No data available	<b>Specific Gravity</b>	1.00
<b>Evaporation Rate</b>	No data available	<b>Water solubility</b>	No data available
<b>Dynamic viscosity</b>	No data available	<b>Weight per Gallon (lbs/gal):</b>	8.33
		<b>Flammability Limits in Air</b>	
		Upper	4.18 %
		Lower	0.69 %

**10. STABILITY AND REACTIVITY**

**Reactivity**

No data available

**Chemical stability**

Stable under recommended storage conditions.

**Conditions to Avoid**

Extremes of temperature and direct sunlight.

**Incompatible Materials**

None known based on information supplied.

**Hazardous Decomposition Products**

None known based on information supplied.

**11. TOXICOLOGICAL INFORMATION**

**Information on likely routes of exposure**

<b>Product Information</b>	The product has not been tested
<b>Inhalation</b>	There is no data for this product.
<b>Eye Contact</b>	There is no data for this product.

**Skin Contact** There is no data for this product.

**Ingestion** There is no data for this product.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
METHYL ETHYL KETONE 78-93-3	2483 mg/kg ( Rat )	5000 mg/kg ( Rabbit )	11700 ppm ( Rat ) 4 h
TERTIARY BUTYL ACETATE 540-88-5	N/A	N/A	2230 mg/m <sup>3</sup> ( Rat ) 4 h
ACETYLACETONE 123-54-6	N/A	N/A	1224 ppm ( Rat ) 4 h
BUTYL ACETATE 123-86-4	14.13 mg/kg ( Rat )	17600 mg/kg ( Rabbit )	390 ppm ( Rat ) 4 h
METHYL AMYL KETONE 110-43-0	1600 mg/kg ( Rat )	12.6 mL/kg ( Rabbit )	2000 ppm ( Rat ) 4 h
CYCLOHEXANONE 108-94-1	1544 mg/kg ( Rat )	947 mg/kg ( Rabbit )	8000 ppm ( Rat ) 4 h
METHYL ISOBUTYL KETONE 108-10-1	2080 mg/kg ( Rat )	3000 mg/kg ( Rabbit )	8.2 mg/L ( Rat ) 4 h
TOLUENE 108-88-3	2600 mg/kg ( Rat )	12000 mg/kg ( Rabbit )	12.5 mg/L ( Rat ) 4 h

**Information on toxicological effects**

**Symptoms** No information available.

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

**Sensitization** No information available.

**MUTAGENIC EFFECTS** No information available.

**Carcinogenicity** This product contains one or more substances which are classified by IARC as carcinogenic to humans (Group 1), probably carcinogenic to humans (Group 2A) or possibly carcinogenic to humans (Group 2B).

Chemical Name	ACGIH	IARC	NTP	OSHA
CYCLOHEXANONE 108-94-1	A3	Group 3	N/A	N/A
METHYL ISOBUTYL KETONE 108-10-1	A3	Group 2B	N/A	X
TOLUENE 108-88-3	N/A	Group 3	N/A	N/A

**Legend:**

**ACGIH (American Conference of Governmental Industrial Hygienists)**

A3 - Animal Carcinogen

**IARC (International Agency for Research on Cancer)**

Group 2B - Possibly Carcinogenic to Humans

Group 3 - Not Classifiable as to Carcinogenicity in Humans

**OSHA (Occupational Safety and Health Administration of the US Department of Labor)**

X - Present

**Reproductive Toxicity** No information available.

**Specific target organ systemic toxicity (single exposure)** No information available.

**Specific target organ systemic toxicity (repeated exposure)** No information available.

**Chronic Toxicity** May cause adverse liver effects.

**Target Organ Effects** Central nervous system (CNS), Eyes, Kidney, Liver, Peripheral Nervous System (PNS), Respiratory system, Skin.

**Aspiration hazard** No information available.

**Numerical measures of toxicity - Product Information**

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral)	110 mg/kg
ATEmix (dermal)	6851 mg/kg
ATEmix (inhalation-dust/mist)	7.4 mg/l
Oral LD50	675 mg/kg (rat) Estimated
Dermal LD50	4331 mg/kg (rat) Estimated

## 12. ECOLOGICAL INFORMATION

### Ecotoxicity

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to daphnia and other aquatic invertebrates
METHYL ETHYL KETONE 78-93-3	N/A	3130 - 3320: 96 h Pimephales promelas mg/L LC50 flow-through	520: 48 h Daphnia magna mg/L EC50 5091: 48 h Daphnia magna mg/L EC50 4025 - 6440: 48 h Daphnia magna mg/L EC50 Static
TERTIARY BUTYL ACETATE 540-88-5	N/A	296 - 362: 96 h Pimephales promelas mg/L LC50 flow-through	N/A
ACETYLACETONE 123-54-6	N/A	98.3 - 110: 96 h Pimephales promelas mg/L LC50 flow-through 50.3 - 71.8: 96 h Lepomis macrochirus mg/L LC50 flow-through 64.1 - 80.1: 96 h Oncorhynchus mykiss mg/L LC50 flow-through	34.4: 48 h Daphnia magna mg/L EC50
BUTYL ACETATE 123-86-4	674.7: 72 h Desmodesmus subspicatus mg/L EC50	100: 96 h Lepomis macrochirus mg/L LC50 static 17 - 19: 96 h Pimephales promelas mg/L LC50 flow-through	N/A
METHYL AMYL KETONE 110-43-0	N/A	126 - 137: 96 h Pimephales promelas mg/L LC50 flow-through	N/A
CYCLOHEXANONE 108-94-1	N/A	481 - 578: 96 h Pimephales promelas mg/L LC50 flow-through 8.9: 96 h Pimephales promelas mg/L LC50	N/A
METHYL ISOBUTYL KETONE 108-10-1	400: 96 h Pseudokirchneriella subcapitata mg/L EC50	496 - 514: 96 h Pimephales promelas mg/L LC50 flow-through	170: 48 h Daphnia magna mg/L EC50
TOLUENE 108-88-3	433: 96 h Pseudokirchneriella subcapitata mg/L EC50 12.5: 72 h Pseudokirchneriella subcapitata mg/L EC50 static	15.22 - 19.05: 96 h Pimephales promelas mg/L LC50 flow-through 12.6: 96 h Pimephales promelas mg/L LC50 static 5.89 - 7.81: 96 h Oncorhynchus mykiss mg/L LC50 flow-through 14.1 - 17.16: 96 h Oncorhynchus mykiss mg/L LC50 static 5.8: 96 h Oncorhynchus mykiss mg/L LC50 semi-static 11.0 - 15.0: 96 h Lepomis macrochirus mg/L LC50 static 54: 96 h Oryzias latipes mg/L LC50 static 50.87 - 70.34: 96 h Poecilia reticulata mg/L LC50 static 28.2: 96 h Poecilia reticulata mg/L LC50 semi-static	5.46 - 9.83: 48 h Daphnia magna mg/L EC50 Static 11.5: 48 h Daphnia magna mg/L EC50

### Persistence and degradability

No information available.

### Bioaccumulation

No information available.

Chemical Name	Partition coefficient
---------------	-----------------------

METHYL ETHYL KETONE 78-93-3	0.29
ACETYLACETONE 123-54-6	0.34
BUTYL ACETATE 123-86-4	1.81
METHYL AMYL KETONE 110-43-0	1.98
CYCLOHEXANONE 108-94-1	0.86
METHYL ISOBUTYL KETONE 108-10-1	1.19
TOLUENE 108-88-3	2.65

**Other adverse effects** No information available

**13. DISPOSAL CONSIDERATIONS**

**Waste treatment methods**

**Waste treatment methods** This material, as supplied, is a hazardous waste according to federal regulations (40 CFR 261).

**US EPA Waste Number** D001  
U019 U057 U161 U159 U220

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
METHYL ETHYL KETONE 78-93-3	U159	Included in waste streams: F005, F039	200.0 mg/L regulatory level	U159
CYCLOHEXANONE 108-94-1	N/A	Included in waste stream: F039	N/A	U057
METHYL ISOBUTYL KETONE 108-10-1	N/A	Included in waste stream: F039	N/A	U161
TOLUENE 108-88-3	U220	Included in waste streams: F005, F024, F025, F039, K015, K036, K037, K149, K151	N/A	U220

Chemical Name	RCRA - Halogenated Organic Compounds	RCRA - P Series Wastes	RCRA - F Series Wastes	RCRA - K Series Wastes
TOLUENE 108-88-3	N/A	N/A	Toxic waste waste number F025 Waste description: Condensed light ends, spent filters and filter aids, and spent desiccant wastes from the production of certain chlorinated aliphatic hydrocarbons, by free radical catalyzed processes. These chlorinated aliphatic hydrocarbons are those having carbon chain lengths ranging from one to and including five, with varying amounts and positions of chlorine substitution.	N/A

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste Status
---------------	-----------------------------------

METHYL ETHYL KETONE 78-93-3	Toxic Ignitable
BUTYL ACETATE 123-86-4	Toxic
TOLUENE 108-88-3	Toxic Ignitable

**14. TRANSPORT INFORMATION**

**DOT**

UN-No UN1263  
 Proper shipping name Paint  
 Hazard class 3  
 Packing Group II  
 Special Provisions 149, B52, IB2, T4, TP1, TP8, TP28  
 Description UN1263, Paint, 3, II, RQ  
 Emergency Response Guide Number 128

**TDG**

UN-No UN1263  
 Proper shipping name Paint  
 Hazard class 3  
 Packing Group II  
 Description UN1263, Paint, 3, II

**MEX**

UN-No UN1263  
 Proper shipping name Paint  
 Hazard class 3  
 Packing Group II  
 Description UN1263, Paint, 3, II

**ICAO**

UN-No UN1263  
 Proper shipping name Paint  
 Hazard class 3  
 Packing Group II  
 Special Provisions A3, A72  
 Description UN1263, Paint, 3, II

**ICAO**

UN-No UN1263  
 Proper shipping name Paint  
 Hazard class 3  
 Packing Group II  
 Special Provisions A3, A72  
 Description UN1263, Paint, 3, II

**IMDG/IMO**

UN-No UN1263  
 Proper shipping name Paint  
 Hazard class 3  
 Packing Group II  
 EmS-No F-E, S-E

**Special Provisions** 163  
**Description** UN1263, Paint, 3, II

**RID**

**UN-No** UN1263  
**Proper shipping name** Paint  
**Hazard class** 3  
**Packing Group** II  
**Classification Code** F1  
**Description** UN1263, Paint, 3, II

**ADR/RID**

**UN-No** UN1263  
**Proper shipping name** Paint  
**Hazard class** 3  
**Packing Group** II  
**Classification Code** F1  
**Tunnel restriction code** (D/E)  
**Special Provisions** 163, 640C, 650  
**Description** UN1263, Paint, 3, II, (D/E)  
**ADR/RID-Labels** 3

**ADN**

**Proper shipping name** Paint  
**Hazard class** 3  
**Packing Group** II  
**Classification Code** F1  
**Special Provisions** 163, 640C, 650  
**Description** UN1263, Paint, 3, II  
**Limited Quantity (LQ)** 5 L  
**Ventilation** VE01

**15. REGULATORY INFORMATION**

**International Inventories**

**TSCA** Complies  
**DSL/NDL** Complies  
**EINECS/ELINCS** Complies  
**ENCS** Complies  
**IECSC** Complies  
**KECL** Complies  
**PICCS** Complies  
**AICS** Complies

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory  
**DSL/NDL** - Canadian Domestic Substances List/Non-Domestic Substances List  
**EINECS/ELINCS** - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances  
**ENCS** - Japan Existing and New Chemical Substances  
**IECSC** - China Inventory of Existing Chemical Substances  
**KECL** - Korean Existing and Evaluated Chemical Substances  
**PICCS** - Philippines Inventory of Chemicals and Chemical Substances  
**AICS** - Australian Inventory of Chemical Substances

**US Federal Regulations**

**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	CAS No	SARA 313 - Threshold Values %
METHYL ISOBUTYL KETONE	108-10-1	1.0
TOLUENE	108-88-3	1.0

**SARA 311/312 Hazard Categories**

Acute Health Hazard	Yes
Chronic Health Hazard	No
Fire Hazard	Yes
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

**CAA (Clean Air Act)**

U.S. - CAA (Clean Air Act) - 1990 Hazardous Air Pollutants This product contains the following HAPs:

Chemical Name	CAS No	Hazardous air pollutants (HAPs) content
METHYL ISOBUTYL KETONE	108-10-1	Present
TOLUENE	108-88-3	Present

**Clean Water Act**

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42):

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
TERTIARY BUTYL ACETATE	N/A	N/A	N/A	X
BUTYL ACETATE	5000 lb	N/A	N/A	X
TOLUENE	1000 lb	X	X	X

**CERCLA**

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ (reportable quantity)
METHYL ETHYL KETONE	5000 lb	N/A	RQ 5000 lb final RQ RQ 2270 kg final RQ
TERTIARY BUTYL ACETATE	5000 lb	N/A	RQ 5000 lb final RQ RQ 2270 kg final RQ
BUTYL ACETATE	5000 lb	N/A	RQ 5000 lb final RQ RQ 2270 kg final RQ
CYCLOHEXANONE	5000 lb	N/A	RQ 5000 lb final RQ RQ 2270 kg final RQ
METHYL ISOBUTYL KETONE	5000 lb	N/A	RQ 5000 lb final RQ RQ 2270 kg final RQ
TOLUENE	1000 lb 1 lb	N/A	RQ 1000 lb final RQ RQ 454 kg final RQ RQ 1 lb final RQ RQ 0.454 kg final RQ

**State Regulations**

**California Proposition 65**

This product contains the following Proposition 65 chemicals

Chemical Name	CAS No	California Proposition 65
METHYL ISOBUTYL KETONE	108-10-1	Carcinogen Developmental

TOLUENE	108-88-3	Developmental Female Reproductive
---------	----------	--------------------------------------

**U.S. State Right-to-Know Regulations**

Chemical Name	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
METHYL ETHYL KETONE	X	X	X	X	N/A
TERTIARY BUTYL ACETATE	X	X	X	N/A	N/A
ACETYLACETONE	X	X	X	N/A	N/A
BUTYL ACETATE	X	X	X	N/A	N/A
METHYL AMYL KETONE	X	X	X	N/A	N/A
CYCLOHEXANONE	X	X	X	X	N/A
METHYL ISOBUTYL KETONE	X	X	X	X	N/A
TOLUENE	X	X	X	X	X

**International Regulations**

Mexico - Grade

Serious risk, Grade 3

Chemical Name	Carcinogenic Status	Exposure Limits
METHYL ETHYL KETONE	N/A	Mexico: TWA 200 ppm Mexico: TWA 590 mg/m <sup>3</sup> Mexico: STEL 300 ppm Mexico: STEL 885 mg/m <sup>3</sup>
TERTIARY BUTYL ACETATE	N/A	Mexico: TWA 200 ppm Mexico: TWA 950 mg/m <sup>3</sup> Mexico: STEL 250 ppm Mexico: STEL 1190 mg/m <sup>3</sup>
BUTYL ACETATE	N/A	Mexico: TWA 150 ppm Mexico: TWA 710 mg/m <sup>3</sup> Mexico: STEL 200 ppm Mexico: STEL 950 mg/m <sup>3</sup>
METHYL AMYL KETONE	N/A	Mexico: TWA 50 ppm Mexico: TWA 235 mg/m <sup>3</sup> Mexico: STEL 100 ppm Mexico: STEL 465 mg/m <sup>3</sup>
CYCLOHEXANONE	N/A	Mexico: TWA 50 ppm Mexico: TWA 200 mg/m <sup>3</sup> Mexico: STEL 100 ppm Mexico: STEL 400 mg/m <sup>3</sup>
METHYL ISOBUTYL KETONE	N/A	Mexico: TWA 50 ppm Mexico: TWA 205 mg/m <sup>3</sup> Mexico: STEL 75 ppm Mexico: STEL 307 mg/m <sup>3</sup>
TOLUENE	N/A	Mexico: TWA 50 ppm Mexico: TWA 188 mg/m <sup>3</sup>

**16. OTHER INFORMATION**

**NFPA**

Health Hazard 2


Flammability 3

Instability 0

Physical and Chemical Hazards -



NFPA Rating



**HMIS** Health Hazard 1 \* Flammability 3 Physical Hazard 0 Personal protection X

*Chronic Hazard Star Legend* \* *Chronic Health Hazard*

Issuing Date: 23-Apr-2015  
Revision Date: 23-Apr-2015  
Revision Note  
No information available

**Disclaimer**  
The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. PH-34FC/GV

end