

1. IDENTIFICATION:

PRODUCT NAME: PERMA-SLIK RMAC HMIS CODES H F R P

PRODUCT CODE: PPSRMAC 2*3 1 G

PRODUCT USE .: Low Friction Coating

Manufacturer:

EVERLUBE PRODUCTS
100 COOPER CIRCLE
PEACHTREE CITY, GA 30269

EMERGENCY PHONE (24 hours): CHEMTREC - 800-424-9300

INFORMATION PHONE (8:00 a.m - 5:00 p.m EST): (770) 261-4800

NAME OF PREPARER: CHEMICAL COMMUNICATIONS COORDINATOR

DATE PREPARED: 5/18/2016

2. HAZARDS INDENTIFICATION



CLASSIFICATION:

Highly Flammable Liquid and Vapors - Category 2
Acute Toxicity, Inhalation (Category 3)
Aquatic Chronic Toxicity - Category 3
Aspiration Hazard - Category 1
Carcinogenicity - Category 2
Serious Eye Damage - Category 1
Reproductive Toxicity - Category 1
Skin Irritation - Category 2
Specific target organ toxicity, repeated exposure - Category 2
Specific target organ toxicity, single exposure - Category 2

SIGNAL WORD:

DANGER

HAZARDS STATEMENT:

H225-Highly flammable liquid and vapors

H304-May be fatal if swallowed and enters airways

H315-Causes skin irritation

H318-Causes serious eve damage.

H331-Toxic if inhaled

H336-May cause drowsiness or dizziness

H337-May cause damage to central nervous system

H351-Suspected of causing cancer

H360-May damage fertility or the unborn child.

H373-May cause damage to organs through prolonged or repeated exposure.

H401-Toxic to aquatic life

PRECAUTIONARY STATEMENTS:

P202-Do not handle until all safety precautions have been read and understood.

P210-Keep away from heat/sparks/open flames/hot surfaces - No smoking

P242-Use only non-sparking tools.



SAFETY DATA SHEET

P280-Wear protective gloves/eye protection/face protection. P403-P233-Store in well-ventilated place. Keep container tightly closed. P501-Dispose of contents/container in accordance with local/regional/national/regulation.

3. COMPOSITION/INFORMATION ON INGREDIENTS	CAS# %	BY WT.
HEPTANE	142-82-5	45% - 50%
ACGIH TWA 400 PPM (8-Hours)		
ACGIH STEL 500 PPM (15-Min)		
OSHA TWA 500 PPM (8-Hours)		
LD50 ORAL >15,000 mg/kr Rat		
LD50 INHALATION 103 mg/m3 4h Rat		
LD50 INHALATION 75 g/m3 2h Mouse		
LD50 DERMAL >2,000 mg/kg Rabbit		
1 BUTANOL TITANIUM	9022-96-2	15% - 20%
LD50 ORAL RAT >2000 mg/kg bw		
LD50 DERMAL RAT 5300 mg/kg bw		
LC50 INHALATION RAT 20100 mg/l		
EC10 ALGAE 134 mg/l 96 hr		
EC50 DAPHNIA 1300 mg/l 48 hr		
EC50 ALGAE 225 mg/l 96 hr		
LC50 FISH 1825 mg/l 96 hr		
VM&P NAPHTHA	64742-89-8	10% - 15%
OSHA Z1 TWA 500 PPM		
OSHA Z1 TWA 2,000 mg/m3		
OSHA PO TWA 400 PPM		
OSHA PO TWA 1,600 mg/m3		
LD 50 ORAL >5000 mg/kg (rat)		
LD50 DERMAL >2000 mg/kg (rabbit)		
LC50 FISH 8.2 mg/l 96h		
EC50 ACQUATIC INVERTEBRES 4.5 mg/l 48h		
EC50 ALGAE3.7 mg/l 96h		
ANTIMONY TRIOXIDE	1309-64-4	5% - 10%
OSHA $Z-1$ 0.5 mg/m3 TWA		
OSHA PO: 0.5 mg/m3 TWA		
NOISH REL 0.5 mg/m3		
LD Oral Rat: >34,600 mg/kg		
LC50 Fish: >1,000 mg/l 96hr		
EC50 Daphnia: >1,000 mg/l 48 hr		
ETHYL BENZENE	100-41-4	0% - 5%
ACGIH: 20 ppm TWA		
OSHA 100 ppm TWA; 435 mg/m3 TWA		
OSHA 125 ppm STEL; 545 mg/m3 STEL		
NIOSH 100 ppm TWA; 435 mg/m3 TWA		
NIOSH 125 ppm STEL; 545 mg/m3 STEL		
LD50 ORAL: 3500 mg/kg (rat)		
LC50 Inhalation 17.2 mg/l 4h (rat)		
LD50 Dermal 15354 mg/kg (rabbit)		
LC50 FISH: 11.0-18.0 mg/l 96 hr		
EC50 ALGAE 4.6 mg/l 72 hr		
EC50 DAPHNIA 182.5 mg/l 48 hr		

4. First Aid Measures

Eyes:

With eyelids open, immediately flush eyes with lots of lukewarm water for at least 30 minutes. Get immediate medical assistance.

Skin:



Wash the skin thoroughly with plenty of water for at least 15 minutes, using a mild and non-abrasive soap. Cold water may be used.

Ingestion:

Never give anything by mouth if the victim is semi-conscious, unconscious, or convulsing.

Inhalation:

Evacuate to fresh air and administer artificial respiration if breathing stopped. Obtain medical aid.

5. Fire Fighting Measures

Flammable Properties:

Flash Point (Degree F): 15 F Flash Point Method CC

Explosive Limits:

Upper explosive limit: 7.0 Lower explosive limit: 0.9

Hazardous Combustion Products:

Carbon, Sulfur, Antimony, or their compounds

Extinguishing Media:

CO2, foam, dry chemical or halon

Firefighting Procedures:

Fire-Fighters should wear self-contained breathing apparatus and full protective equipment.

Extinguish all nearby sources of ignition.

6. Accidental Release Measures

Small Spill:

Eliminate all sources of ignition, provide ventilation, contain spill, and absorb with inert absorbent.

Wear appropriate breathing apparatus (if applicable) and protective clothing.

Use only non-sparking tools and equipment.

Large Spill:

Remove by mechanical means and place in containers.

Use only non-sparking tools and equipment.

Environmental Precautions:

Prevent product or wash waters from entering the water system or sewers.

US regulations require reporting spills of this material that could reach any surface waters. In Canada, report to the applicable provincial environment ministry.

7. Handling and Storage

Handling:

Avoid breathing dust/fume/gas/mist/vapors/spray.



Do not get in eyes, on skin, or on clothing.

Wash contaminated clothing thoroughly after handling.

Wash skin thoroughly (with soap and water) after handling.

Storage:

Store in a cool, dry well ventilated place, away from incompatible materials.

Store in a closed/sealed container.

8. Exposure Controls/Personal Protection

Airborne Exposure Limits:

Mixture, see section 3

Engineering Controls:

General mechanical ventilation or local exhaust should be suitable to keep vapor concentrations below the threshold limit values.

Use explosion-proof electrical/ventilating/lighting equipment.

Prevent the product or the wash waters from entering the water system or sewers.

Personal Protective Equipment:







Respiratory Protection:

In case of inadequate ventilation, wear respirator protection.
Use NIOSH/MSHA approved Cartridge Respirator or Mask to keep airborne mists and concentrations below the time weighted threshold limit values.

Skin Protection:

Wear protective gloves (eg Neoprene or Nitrile) for skin protection.

Eye Protection:

Wear eye protection/face protection. Contact lenses should not be worn without goggles.

9. Physical and Chemical Properties

Flammability (solid, gas)....: Data not available Boiling Point: 194 F

Flash Point 15 F

Vapor Pressure: Data not available Vapor Density: Heavier than air. Solubility in Water: Slightly Soluble

Density..... 8. lb/gl

Evaporation Rate Faster than n-Butyl Acetate.

Explosive Limits:

Upper Explosive Limit: 7.0 Lower Explosive Limit: 0.9



SAFETY DATA SHEET

Specific Gravity: .96076
PH: None known

Volatile (% by Weight)..... 70%

Appearance and Odor Gray/Black liquid, organic solvent odor

Odor Threshold: Not applicable Viscosity: Not applicable Partition Coefficient:: Data not available Decomposition Temperature ...: Data not available Autoignition temperature: Data not available

10. Stability and Reactivity

Chemical Stability (Conditions to Avoid):

Stable under normal conditions.

Incompatibility:

Oxidizers, Strong Acids or Alkalies.

Hazardous Decomposition Products:

Irritating and/or toxic fumes including the following may be released: Carbon, Sulfur, Antimony, or their compounds

Hazardous Polymerization:

Will not occur.

11. Toxicological Information

Acute Toxicity Values:

Mixture, see section 3 - Hazardous Ingredients

Germ Cell Mutagenicity:

None known

Chronic/Carcinogenicity:

IARC (International Agency for Research of Cancer):
Group 2B-Possibly carcinogenic to humans

NTP (National Toxicology Program): Not listed as a carcinogen

Reproductive Toxicity:

Product contains chemical(s) that may damage fertility or the unborn child

STOT-single exposure:

May cause respiratory irritation

May cause drowsiness or dizziness

May cause damage to central nervous system

STOT-repeated exposure:

May cause damage to organs through prolonged or repeated exposure.

Aspiration Hazard:

May be fatal if swallowed and enters airways

Routes of Exposure:

Skin contact, skin absorption, eye contact, inhalation

12. Ecological Information



Environmental Fate:

Do not allow product or runoff from fire control to enter storm or sanitary sewers, lakes, rivers, streams, or public waterways. Canadian and U.S. regulations require that environmental and/or other agencies be notified of a spill incident. The spill area must be cleaned and restored to the original condition or to the satisfaction of authorities.

Environmental Toxicity:

Data not available

Persistence and Degradability:

Data not available

Bioaccumulative Potential:

Data not available

Mobility in Soil

Data not available

Other Adverse Effects:

None known

13. Disposal Considerations

Disposal Methods:

Dispose of contents/container to: A licensed waste disposal facility. Do not attempt to combust waste on-site. Incinerate at a licensed waste disposal site with approval of environment authority.

14. Transport Information

Domestic (Land, DOT), International (Water, IMO/IMDG), International (Air, ICAO) Road and Rail (ADR/RID), Air (ICAO/IATA), Vessel (IMO/IMDG):

UN Number:

UN 1263

UN Shipping Name:

PAINT RELATED MATERIAL

Transport Hazard Class:

Class 3



Packing Group:

Group II

ENVIRONMENTAL HAZARDS:

Marine Pollutant:

Toxic to aquatic life
Harmful to aquatic life with long lasting effects

Special Precautions for User:



None known

15. Regulatory Information

U.S. Federal Regulations:

OSHA:

OSHA Regulated

TSCA:

ALL COMPONENTS OF THIS PRODUCT ARE ON THE TSCA INVENTORY OR ARE EXTINCT FROM REQUIREMENTS

CERCLA: SARA Hazard Category:

Section 313:

_ _ _ _ _ _

IF THIS MATERIAL HAS ANY COMPONENTS THAT ARE REPORTABLE UNDER SARA 313 THEY ARE SHOWN IN THE FOLLOWING LISTING. IF THE LISTING IS BLANK, THERE ARE NO REPORTABLE COMPONENTS.

COMPONENT CAS # % BY WT.

VM&P NAPHTHA 64742-89-8 10% - 15% ANTIMONY TRIOXIDE 1309-64-4 5% - 10%

FRANK DODD SECTION 1502:

ALL COMPONENTS OF THIS PRODUCT COMPLY WITH TITLE 15 OF THE US CONSUMER FINANCIAL PROTECTION ACT, DODD-FRANK ACT SECTION 1502 (CONFLICT MINERALS ACT).

State Regulations:

California Prop 65:

This product contains a chemical known to the State of California to cause cancer.

This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

International Regulations:

WHMIS:

B2, D2A, D2B,

CEPA (Canadian Environmental Protection Act)

ALL INGREDIENTS ARE CEPA APPROVED FOR IMPORT TO CANADA. THIS PRODUCT HAS BEEN CLASSIFIED IN ACCORDANCE WITH THE HAZARD CRITERIA OF THE CONTROLLED PRODUCTS REGULATION (CPR) AND THE MSDS CONTAINS ALL THE INFORMATION REQUIRED BY THE CPR.

EINECS (European Inventory of Existing Chemical List)

ALL COMPONENTS OF THIS PRODUCT ARE INCLUDED ON THE EUROPEAN INVENTORY OF EXISTING CHEMICALS LIST

16. Other Information

Date of Preparation: 5/18/2016

KEY/LEGEND

ACGIH: American Conference of Governmental Industrial Hygienists



SAFETY DATA SHEET

ADR: International Carriage of Dangerous Goods by Road RID: International Carriage of Dangerous Goods by Rail

CAS: Chemical Abstracts Service

CERCLA: Comprehensive Environmental Response, Compensation, & Liability Act

DOT: Department of Transportation

HMIS: Hazardous Materials Identification System IATA: International Air Transport Association ICAO: International Civil Aviation Organization

IDL: Immediately Dangerous to Life

IMDG: International Maritime Dangerous Goods
IMO: International Maritime Organization

LC: Lethal Concentration

LD: Lethal Dose

NIOSH: National Institute for Occupational Safety & Health

OSHA: Occupational Safety & Health Administration

PPM: Parts Per Million

REL: Recommended Exposure Limit

SARA: Superfund Amendments and Reauthorization Act

STEL: Short-term Exposure Limits
STOT: Specific Target Organ Toxicity

TLV: Threshold Limit Value

TSCA: Toxic Substances Control Act

TWA: Time Weighted Average

VOC: Volatile Organic Compounds

WHMIS: Workplace Hazardous Materials Information System

Manufacturer Disclaimer:

TO THE BEST OF OUR KNOWLEDGE, THE INFORMATION AND RECOMMENDATION CONTAINED HEREIN IS BELIEVED TO BE ACCURATE AT THE TIME OF PREPARATION OR OBTAINED FROM SOURCES BELIEVED TO BE RELIABLE. HOWEVER, IT IS THE USERS RESPONSIBILITY TO DETERMINE SAFETY, TOXICITY, AND SUITABLITY FOR HIS OWN USE OF THE PRODUCT. EVERLUBE PRODUCTS ASSUMES NO RESPONSIBILITY. THE CUSTOMER OR RECIPIENT OF THIS SDS SHOULD ENSURE THAT THE INFORMATION CONTAINED IN THIS SDS IS MADE AVAILABLE TO ALL EMPLOYEES OR OTHER PERSONS WHOM HE KNOWS OR BELIEVES WILL USE THIS MATERIAL

www.everlubeproducts.com