



RADCOLUBE® FR257 HYDRAULIC FLUID

SAFETY DATA SHEET

**MIL-PRF-87257C HYDRAULIC FLUID, FIRE RESISTANT, LOW TEMPERATURE, SYNTHETIC HYDROCARBON BASE, AIRCRAFT AND MISSILE,
NATO CODE NUMBER H-538**

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name: RADCOLUBE® FR257 HYDRAULIC FLUID, FIRE RESISTANT

This product meets Military Specification MIL-PRF-87257C, NATO Code Number H-538.

Qualification# AFPET/PTPS 19-011 Date of Approval: 18 July 2019

ISO 9001:2015 Certification Number: C2018-00035

Recommended Use

Synthetic hydrocarbon base hydraulic fluid for use in the -54°C to +200°C (-65°F to 392°F) temperature range in aircraft and missile hydraulic systems.

This hydraulic fluid is identified by NATO Code No. H-538.

National Stock Numbers (NSN):

9150-01-388-7769	Quart
9150-01-386-6687	Gallon
9150-01-391-2087	5 Gallon Pail
9150-01-387-4577	55 Gallon Drum

Company Identification

Headquarters
Radco Industries, Inc.
700 Kingsland Drive
Batavia, IL 60510
CAGE Code 6ZS16

Manufacturing Facility
Radco Industries, Inc.
39W930 Midan Drive
LaFox, IL 60147
CAGE Code 1RVC4

Customer information number: 1-630-232-7966

EMERGENCY TELEPHONE NUMBER

Advisory Office in case of poisoning: Chemtrec

Chemtrec (North America): 1-800-424-9300

2. HAZARDS IDENTIFICATION

Classification of mixture:

Aspiration hazard, Category 1



Radco Industries, Inc. 700 Kingsland Drive, Batavia, Illinois 60510, United States

Product Name: RADCOLUBE® FR257 HYDRAULIC FLUID

MIL-PRF-87257C HYDRAULIC FLUID, FIRE RESISTANT, LOW TEMPERATURE, SYNTHETIC HYDROCARBON BASE, AIRCRAFT AND MISSILE, NATO CODE NUMBER H-538

Hazard Pictograms:



Signal Word:

DANGER

Hazard Statements:

H304:	May be fatal if swallowed and enters airways.
-------	---

Precautionary Statements:

P243:	Take precautionary measures against static discharge
P273:	Avoid release to the environment.
P301 + P315 +P331:	IF SWALLOWED: Do NOT induce vomiting. Get immediate medical advice/attention.
P305 + P351:	IF IN EYES: Rinse cautiously with water for several minutes.
P350:	Gently wash with soap and water.
P362:	Take off contaminated clothing and wash before reuse.
P405:	Store locked up.
P501:	Dispose of contents/container to an approved waste disposal plant.

3. COMPOSITION/INFORMATION ON INGREDIENTS

<u>Components</u>	<u>%Content</u>	<u>CAS Number</u>
Polyalphaolefin	Proprietary	Proprietary
Additive Package	Proprietary	Proprietary

4. FIRST-AID MEASURES

Eyes

Immediately flush eyes with plenty of water for at least 15 minutes.

Ingestion

If swallowed, drink plenty of water, DO NOT induce vomiting. Immediately call a doctor.

Inhalation

Move to fresh air. If unconscious place in recovery position and seek medical advice. If respiratory irritation, dizziness, nausea, or unconsciousness occurs, seek immediate medical assistance. Remove from further exposure. Immediately call a doctor.

Skin

Wash exposed skin with soap and water.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

For small fires use carbon dioxide, dry chemical or foam.

For large fires use alcohol-type foam, universal type foam or water fog.

Fire-Fighting Equipment

Firefighter should wear normal protective equipment (full bunker gear) and positive-pressure contained breathing apparatus.

Water can be used to cool fire-exposed containers, to protect personnel and to disperse vapors and spills. Water runoff can cause environmental damage. Dike and collect water used to fight fires.



Special Fire-Fighting Procedures

Use water spray to cool fire-exposed containers and structures. If a rail or tank truck is involved in a fire, isolate for 800 meters (0.5 mile) in all directions. Shut off fuel to fire if it is possible to do so without hazard. If this is impossible, withdraw from the area and let the fire burn out under controlled conditions. Withdraw immediately in case of rising sound from venting safety device or any discoloration of tank due to fire.

6. ACCIDENTAL RELEASE MEASURES

Wear protective clothing when taking up spill. Eliminate sources of ignition. This product is insoluble in water and will float on the surface. Prevent from entering sewers or drains. Should this product enter sewers or drains, it should be pumped out into an open vessel.

7. HANDLING AND STORAGE

Handling

Do not breathe vapors/dust. Smoking, eating and drinking should be prohibited in the application area. Dispose of rinse water in accordance with local and national regulations.

Storage

Do not store in open or unlabeled containers. Keep container tightly closed in a dry and well-ventilated place.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Limits

None established

Respiratory Protection

Use with adequate ventilation. Avoid breathing vapor. If heated and ventilation is inadequate, use NIOSH certified respirator, which will protect against organic vapor.

Hand Protection

Wear clothing and gloves that cannot be penetrated by chemicals or oil.

Eye Protection

Safety glasses, chemical goggles, or face shields recommended to prevent contact.

Other Protection

Do not eat, drink, or smoke when handling this product.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Transparent, red liquid
Odor:	Odorless
Odor threshold:	Not Determined
Auto-ignition temperature:	340°C (644°F)
Decomposition temperature:	Not Determined
Evaporation Rate (ASTM D972):	14% after 6.5 hours at 135°C (275°F)
Flash point Cleveland Open Cup (ASTM D92):	172°C (341.6°F)
Flash point Pensky-Martens (ASTM D93):	Not Determined
Flammability (solid, gas):	Non-flammable
Lower flammability limit:	Not Determined



Radco Industries, Inc. 700 Kingsland Drive, Batavia, Illinois 60510, United States

Product Name: RADCOLUBE® FR257 HYDRAULIC FLUID

MIL-PRF-87257C HYDRAULIC FLUID, FIRE RESISTANT, LOW TEMPERATURE, SYNTHETIC HYDROCARBON BASE, AIRCRAFT AND MISSILE, NATO CODE NUMBER H-538

Upper flammability limit:	Not Determined
Initial boiling point and boiling range:	Not determined
Melting point/freezing point:	< -60°C (-76°F)
Partition coefficient (n-octanol/water), Log P _{ow} :	Not Determined
pH:	Not applicable
Solubility:	Water insoluble
Relative density (ASTM D1298) 15.6°C/15.6°C:	0.84
Vapor density:	Not Determined
Vapor pressure:	< 0.1 mmHg at 20°C (68°F)
Viscosity (ASTM D445):	2.1 mm ² /s (cSt) at 100°C (212°F) 6.8 mm ² /s (cSt) at 40°C(104°F) 470 mm ² /s (cSt) at -40°C (-40°F) 2,350 mm ² /s (cSt) at -54°C (65.2°F)

10. STABILITY AND REACTIVITY INFORMATION

Materials to avoid

Exposure to materials which are highly oxidizing should be avoided.

Hazardous polymerization

Does not occur.

Hazardous decomposition products

Incomplete combustion may give various cracked and oxidized hydrocarbons.

Stability

Stable

11. TOXICOLOGICAL INFORMATION

Acute toxicity	Method	Species	Result
Polyalphaolefin	Dermal	Rat	LD ₅₀ > 2000 mg/kg
	Inhalation	Rat	LC ₅₀ = 5.0 mg/L after 1 hour
	Oral	Rat	LD ₅₀ > 2000 mg/kg
Additive Package	--	--	Not expected to be hazardous.

Aspiration hazard	Test Method	Species	Result
Polyalphaolefin	OECD 403	Rat	Aspiration hazard, Category 1
Additive Package	--	--	No data available

Carcinogenicity

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by ACGIH, IARC, NTP or OSHA.

Eye damage / irritation	Test Method	Species	Results
Polyalphaolefin	OECD 405	Rabbit	Not irritating
Additive Package	--	--	Not classified



Radco Industries, Inc. 700 Kingsland Drive, Batavia, Illinois 60510, United States

Product Name: RADCOLUBE® FR257 HYDRAULIC FLUID

MIL-PRF-87257C HYDRAULIC FLUID, FIRE RESISTANT, LOW TEMPERATURE, SYNTHETIC HYDROCARBON BASE, AIRCRAFT AND MISSILE, NATO CODE NUMBER H-538

Germ cell mutagenicity	Test Method	Species	Results
Polyalphaolefin	OECD 471	<i>S. typhimurium</i>	Not mutagenic
Additive Package	--	--	Not expected to be mutagenic.

Reproductive toxicity	Test Method	Species	Results
Polyalphaolefin	OECD 415	Rat	No reproductive harm
Additive Package	--	--	Not expected to be hazardous.

Respiratory sensitization

No data available

Skin sensitization	Test Method	Species	Results
Polyalphaolefin	OECD 406	Guinea pig	Not sensitizing
Additive Package	--	--	Not classified

Skin corrosion/irritation	Test Method	Species	Results
Polyalphaolefin	OECD 404	Rabbit	Not irritating
Additive Package	--	--	Not expected to be irritant.

Specific target organ toxicity (STOT)-repeated exposure

No data available

Specific target organ toxicity (STOT)-single exposure

No data available

12. ECOLOGICAL CONSIDERATIONS

Aquatic Toxicity	Test Method	Species	Results
Polyalphaolefin	OECD 203 OECD 211 DIN 38412-8	<i>D. magna</i> <i>O. mykiss</i> <i>P. putida</i>	NOEL = 125 mg/L after 21 days LL ₅₀ > 1000g/L after 96 hours EC ₅₀ > 10g/L after 16 hours
Additive Package	--	--	Not expected to be hazardous.

Terrestrial Toxicity	Test Method	Species	Results
1-Decene, homopolymer, hydrogenated	OECD 222	Earthworm	LC50 > 1000 mg/kg after 56 days
Additive Package	--	--	No data available

Biodegradation	Test Method	Results
Polyalphaolefin	OECD 301B	Not readily biodegradable
Additive Package	--	No data available

Partition Coefficient n-octanol / water (Log K _{ow})	Results
Polyalphaolefin	Log K _{ow} = 10.09
Additive Package	No data available

13. DISPOSAL INFORMATION

This unused material, when discarded or disposed of, is not specifically listed as a hazardous waste in Federal regulations; however, it could be considered hazardous if it meets criteria for being toxic, corrosive, ignitable, or reactive according to U.S. EPA definitions (40 CFR Subpart C). This material could also become hazardous waste if it is mixed with or comes into contact with a listed hazardous waste. If it is a hazardous waste, regulations in 40 CFR 262-266, 268, 270, and 279 may apply.

14. TRANSPORT INFORMATION



Radco Industries, Inc. 700 Kingsland Drive, Batavia, Illinois 60510, United States

Product Name: RADCOLUBE® FR257 HYDRAULIC FLUID

MIL-PRF-87257C HYDRAULIC FLUID, FIRE RESISTANT, LOW TEMPERATURE, SYNTHETIC HYDROCARBON
BASE, AIRCRAFT AND MISSILE, NATO CODE NUMBER H-538

U.S. Dept. of Transportation Shipping Name

Not regulated.

Canadian Transportation of Dangerous Goods Shipping Name

Not regulated.

European Rail/Road (ADR/RID) Shipping Name

Not regulated.

Air (ICAO/IATA) Shipping Name

Not regulated.

Sea (IMO/IMDG)

Not regulated.

15. REGULATORY INFORMATION

California (Proposition 65)

This product does not contain any of the substances known to the State of California to cause cancer, birth defects, or reproductive harm.

CERCLA Reportable Quantity

This product is not reportable under 40 CFR Part 302.4.

Environmental Protection Agency

None of the ingredients are listed

National Toxicology Program (NTP)

None of the ingredients are listed.

OSHA Hazard Communication Standard

Not hazardous per 29 CFR 1910.1200(d).

SARA Title III Section 302 Extremely Hazardous Substances (40 CFR Part 355)

This product is not regulated under Section 302 of SARA and 40 CFR Part 355.

SARA Title III Sections 311/312 Hazardous Categorization (40 CFR Part 370)

Hazardous categories for this product are:

Acute = No Chronic = No Fire = No Pressure = No Reactive = No

SARA Title III Section 313 (40 CFR Part 372)

This product is not regulated under Section 313 of SARA and 40 CFR Part 372.

U.S. Inventory (TSCA)

Listed on inventory.

Australia Inventory (AICS)

Listed on inventory.

Canada Inventory (DSL)

All of the ingredients are listed.

China (CICS)



Radco Industries, Inc. 700 Kingsland Drive, Batavia, Illinois 60510, United States

Product Name: RADCOLUBE® FR257 HYDRAULIC FLUID

MIL-PRF-87257C HYDRAULIC FLUID, FIRE RESISTANT, LOW TEMPERATURE, SYNTHETIC HYDROCARBON
BASE, AIRCRAFT AND MISSILE, NATO CODE NUMBER H-538

None of the ingredients are listed.

EC Inventory (EINECS/ELINCS)

In Compliance

International Agency for Research on Cancer (IARC)

None of the ingredients are listed.

Japan Inventory (MITI)

Listed on inventory.

Korea Inventory (ECL)

Listed on inventory.

16. OTHER INFORMATION

Safety Data Sheet Creation Date: 2 February 2010

Safety Data Sheet Revision Date: 18 July 2019

The information herein is given in good faith, but no warranty, expressed or implied, is made. Consult Radco Industries, Inc. for further information.

THIS INFORMATION RELATES TO THE SPECIFIC MATERIAL DESIGNATED AND MAY NOT BE VALID FOR SUCH MATERIAL USED IN COMBINATION WITH ANY OTHER MATERIALS OR IN ANY PARTICULAR PROCESS OR FOR ANY PARTICULAR PURPOSE. SUCH INFORMATION STATED IS TO THE BEST OF RADCO'S KNOWLEDGE AND BELIEF, ACCURATE AND RELIABLE AS OF THE DATE COMPILED. HOWEVER, NO REPRESENTATION, WARRANTY OR GUARANTEE IS MADE TO ITS ACCURACY, RELIABILITY, OR COMPLETENESS, PURCHASERS, USERS AND DISTRIBUTORS ARE NOT RELYING ON ANY PROMISE, REPRESENTATION, OR RECOMMENDATION MADE BY RADCO, AND RADCO DOES NOT ACCEPT LIABILITY FOR ANY LOSS OR DAMAGE THAT MAY OCCUR FROM THE USE OF THIS INFORMATION. FINAL DETERMINATION OF SUITABILITY OF ANY MATERIAL IS THE SOLE RESPONSIBILITY OF THE USER. ALL MATERIAL SHOULD BE USED WITH CAUTION TO GUARD AGAINST UNKNOWN HAZARDS. ALTHOUGH CERTAIN HAZARDS ARE DESCRIBED HEREIN, RADCO DOES NOT GUARANTEE THAT THESE ARE THE ONLY HAZARDS THAT EXIST.

RADCOLUBE® is a registered trademark of Radco Industries, Inc.