

RTV 60/DBT

SAFETY DATA SHEET

Classified in accordance with 29 CFR 1910.1200

1. Identification

Product identifier: RTV 60/DBT

Other means of identification

Synonyms: SILICONE RUBBER

Recommended use and restriction on use

Recommended use: Silicone Elastomer

Restrictions on use: Not known.

Manufacturer/Importer/Distributor Information : Momentive Performance Materials USA LLC
2750 Balltown Road,
Niskayuna, NY 12309

Contact person : commercial.services@momentive.com

Telephone : General information
+1-800-295-2392

Emergency telephone number

Supplier : CHEMTREC
1-800-424-9300

2. Hazard(s) identification

Hazard Classification

Not classified

Label Elements

Hazard Symbol: No symbol

Signal Word: No signal word.

Hazard Statement: Not applicable

Precautionary Statements : Not applicable

Hazard(s) not otherwise classified (HNOC): None.

SDS_US

RTV 60/DBT

3. Composition/information on ingredients

Mixtures

Chemical Identity	CAS number	Content in percent (%)*	Notes
Red iron oxide	1309-37-1	20 - <50%	# This substance has workplace exposure limit(s).
(1) Cristobalite	14464-46-1	5 - <10%	# This substance has workplace exposure limit(s).
Kieselguhr, soda ash flux-calcined	68855-54-9	1 - <5%	# This substance has workplace exposure limit(s).
Silicic acid, ethyl ester	11099-06-2	1 - <5%	No data available.
(1) QUARTZ	14808-60-7	0.1 - <1%	# This substance has workplace exposure limit(s).
Red iron oxide	1309-37-1	20 - <50%	# This substance has workplace exposure limit(s).
(1) Cristobalite	14464-46-1	5 - <10%	# This substance has workplace exposure limit(s).
Kieselguhr, soda ash flux-calcined	68855-54-9	1 - <5%	# This substance has workplace exposure limit(s).
Silicic acid, ethyl ester	11099-06-2	1 - <5%	No data available.
(1) QUARTZ	14808-60-7	0.1 - <1%	# This substance has workplace exposure limit(s).

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

(1) The respirable particle(s) listed above are inextricably bound within the polymer matrix, and therefore does not present an inhalation hazard during normal use of this product. Tooling or machining of the cured product (sanding, cutting, milling) may release hazardous, respirable substances.

4. First-aid measures

RTV 60/DBT

Ingestion:	DO NOT induce vomiting. Get medical attention immediately. Do not give victim anything to drink if he is unconscious. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.
Inhalation:	Move into fresh air and keep at rest. Get medical attention if symptoms occur.
Skin Contact:	Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water. Get medical attention if symptoms occur.
Eye contact:	Get medical attention if symptoms occur. If in eyes, hold eyes open, flood with water for at least 15 minutes and see a doctor.

Most important symptoms/effects, acute and delayed

Symptoms:	None known.
Hazards:	No data available.

Indication of immediate medical attention and special treatment needed

Treatment:	Treatment is symptomatic and supportive.
-------------------	--

5. Fire-fighting measures

General Fire Hazards:	Self-contained breathing apparatus and full protective clothing must be worn in case of fire. Use standard firefighting procedures and consider the hazards of other involved materials. Prevent runoff from fire control or dilution from entering streams, sewers, or drinking water supply.
------------------------------	--

Suitable (and unsuitable) extinguishing media

Suitable extinguishing media:	All standard extinguishing agents are suitable.
Unsuitable extinguishing media:	Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical:	In case of fire, carbon monoxide and carbon dioxide may be formed. Acute overexposure to the products of combustion may result in irritation of the respiratory tract. Measurements at temperatures above 150°C in presence of air (oxygen) have shown that small amounts of formaldehyde are formed due to oxidative degradation.
--	--

Special protective equipment and precautions for fire-fighters

Special fire-fighting procedures:	Use water spray to keep fire-exposed containers cool.
--	---

RTV 60/DBT

Special protective equipment for fire-fighters: Firefighters must wear NIOSH/MSHA approved positive pressure self-contained breathing apparatus with full face mask and full protective clothing.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures: Caution: Contaminated surfaces may be slippery. Avoid contact with skin and eyes. See Section 8 of the SDS for Personal Protective Equipment. Keep out of reach of children.

Methods and material for containment and cleaning up: Wipe, scrape or soak up in an inert material and put in a container for disposal. Wash walking surfaces with detergent and water to reduce slipping hazard. Wear proper protective equipment as specified in the protective equipment section.

Environmental Precautions: Do not allow runoff to sewer, waterway or ground.

7. Handling and storage

Precautions for safe handling: Sensitivity to static discharge is not expected. Do not taste or swallow. Do not get in eyes, on skin, on clothing. Use personal protective equipment as required. Wash hands after handling.

Conditions for safe storage, including any incompatibilities: Keep container closed. Keep away from sources of ignition - No smoking. Use original container or packaging of similar material of construction

8. Exposure controls/personal protection

Control Parameters

Occupational Exposure Limits

Chemical Identity	Type	Exposure Limit Values	Source
Red iron oxide - Respirable fraction.	TWA	5 mg/m ³	US. ACGIH Threshold Limit Values, as amended (03 2015)
Red iron oxide - Dust and fume. - as Fe	REL	5 mg/m ³	US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2010)
Red iron oxide - Fume.	PEL	10 mg/m ³	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
	TWA	10 mg/m ³	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended (1989)
	TWA	10 mg/m ³	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A, as amended (06 2008)
	TWA PEL	5 mg/m ³	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants, as amended (01 2015)
Red iron oxide - Total dust.	TWA	50 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (03 2016)
Red iron oxide - Respirable fraction.	TWA	5 mg/m ³	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (03 2016)
	TWA	15 millions of	US. OSHA Table Z-3 (29 CFR 1910.1000), as

RTV 60/DBT

		particles per cubic foot of air	amended (03 2016)
Red iron oxide - Total dust.	TWA	15 mg/m ³	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (03 2016)
Red iron oxide	IDLH	2,500 mg/m ³	US. NIOSH. Immediately Dangerous to Life or Health (IDLH) Values, as amended (10 2017)
(1) Cristobalite - Respirable fraction.	TWA	0.025 mg/m ³	US. ACGIH Threshold Limit Values, as amended (03 2015)
(1) Cristobalite - Respirable dust.	REL	0.05 mg/m ³	US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2016)
(1) Cristobalite - Respirable dust.	TWA	0.05 mg/m ³	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053), as amended (03 2016)
	OSHA_ACT	0.025 mg/m ³	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053), as amended (03 2016)
(1) Cristobalite - Respirable dust.	PEL	0.05 mg/m ³	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (03 2016)
	TWA	0.05 mg/m ³	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended (1989)
(1) Cristobalite - Particulate.	AN ESL	0.27 µg/m ³	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality), as amended (11 2016)
(1) Cristobalite - Respirable dust.	TWA PEL	0.05 mg/m ³	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants, as amended (01 2015)
(1) Cristobalite - Respirable.	TWA	1.2 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (2000)
	TWA	0.05 mg/m ³	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (2000)
(1) Cristobalite	IDLH	25 mg/m ³	US. NIOSH. Immediately Dangerous to Life or Health (IDLH) Values, as amended (10 2017)
(1) Cristobalite - Respirable dust.	TWA	0.050 mg/m ³	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A, as amended (01 2019)
(1) Cristobalite - Particulate.	ST ESL	14 µg/m ³	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality), as amended (06 2018)
Kieselguhr, soda ash flux-calcined	REL	6 mg/m ³	US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2010)
	TWA	20 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (2000)
	TWA	0.8 mg/m ³	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (2000)
	IDLH	3,000 mg/m ³	US. NIOSH. Immediately Dangerous to Life or Health (IDLH) Values, as amended (10 2017)
Kieselguhr, soda ash flux-calcined - Particulate.	AN ESL	2 µg/m ³	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality), as amended (06 2018)
	ST ESL	27 µg/m ³	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality), as amended (06 2018)
Kieselguhr, soda ash flux-calcined - Respirable particles.	TWA	3 mg/m ³	US. ACGIH Threshold Limit Values, as amended (01 2021)
Kieselguhr, soda ash flux-calcined - Inhalable particles.	TWA	10 mg/m ³	US. ACGIH Threshold Limit Values, as amended (01 2021)
Kieselguhr, soda ash flux-calcined - Total dust.	TWA	15 mg/m ³	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended (1989)
Kieselguhr, soda ash flux-	TWA	5 mg/m ³	US. OSHA Table Z-1-A (29 CFR 1910.1000),

RTV 60/DBT

calcined - Respirable fraction.			as amended (1989)
	TWA	5 mg/m ³	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A, as amended (01 2019)
Kieselguhr, soda ash flux-calcined - Total dust.	TWA	15 mg/m ³	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A, as amended (01 2019)
	TWA PEL	10 mg/m ³	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants, as amended (12 2017)
Kieselguhr, soda ash flux-calcined - Respirable fraction.	TWA PEL	5 mg/m ³	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants, as amended (12 2017)
Kieselguhr, soda ash flux-calcined - Total dust.	TWA	15 mg/m ³	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (09 2016)
	TWA	50 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (09 2016)
Kieselguhr, soda ash flux-calcined - Respirable fraction.	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (09 2016)
	TWA	5 mg/m ³	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (09 2016)
(1) QUARTZ - Respirable dust.	REL	0.05 mg/m ³	US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2010)
(1) QUARTZ - Respirable dust.	TWA	0.05 mg/m ³	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053), as amended (03 2016)
	OSHA_ACT	0.025 mg/m ³	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053), as amended (03 2016)
(1) QUARTZ - Respirable dust.	PEL	0.05 mg/m ³	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (03 2016)
	TWA	0.1 mg/m ³	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended (1989)
(1) QUARTZ - Particulate.	AN ESL	0.27 µg/m ³	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality), as amended (11 2016)
(1) QUARTZ - Respirable dust.	TWA PEL	0.05 mg/m ³	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants, as amended (10 2016)
(1) QUARTZ - Respirable.	TWA	2.4 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (2000)
	TWA	0.1 mg/m ³	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (2000)
(1) QUARTZ	IDLH	50 mg/m ³	US. NIOSH. Immediately Dangerous to Life or Health (IDLH) Values, as amended (10 2017)
(1) QUARTZ - Respirable dust.	TWA	0.050 mg/m ³	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A, as amended (01 2019)
(1) QUARTZ - Particulate.	ST ESL	14 µg/m ³	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality), as amended (06 2018)
(1) QUARTZ - Respirable fraction.	TWA	0.025 mg/m ³	US. ACGIH Threshold Limit Values, as amended (01 2022)

This product contains one or more substances with an occupational exposure limit. However, the respirable particle(s) of this/these substance(s) are inextricably bound within the polymer matrix. Therefore, we do not expect an exposure to this/these substance(s) during normal use of this product. Tooling or machining of the cured product (sanding, cutting, milling) may release hazardous, respirable substances.

RTV 60/DBT

Appropriate Engineering Controls Eyewash bottle with clean water. No special requirements under ordinary conditions of use and with adequate ventilation. Use only in well-ventilated areas.

Individual protection measures, such as personal protective equipment

General information: General (mechanical) room ventilation is expected to be satisfactory if handled at low temperatures or in covered equipment.

Eye/face protection: Safety glasses with side shields

Skin Protection

Hand Protection: Use chemical-resistant, impervious gloves.

Other: Wear suitable protective clothing and eye/face protection.

Respiratory Protection: Use only in well-ventilated areas. If inhalation exposure is expected, NIOSH/MSHA approved respiratory protection should be worn. Supplied air respirators may be required for non-routine or emergency situations. Respiratory protection must be provided in accordance with OSHA regulations (see 29CFR 1910.134).

Hygiene measures: Observe good industrial hygiene practices. Wash hands after handling. When using do not eat, drink or smoke. Provide adequate ventilation.

9. Physical and chemical properties

Appearance

Physical state: liquid

Form: liquid

Color: Red

Odor: Faint

Odor threshold: No data available.

pH: No data available.

Melting point/freezing point: Not applicable

Initial boiling point and boiling range: Not applicable

Flash Point: ca. 109 °C (Closed Cup)

Evaporation rate: No data available.

Flammability (solid, gas): No data available.

Upper/lower limit on flammability or explosive limits

Flammability limit - upper (%): No data available.

Flammability limit - lower (%): No data available.

Explosive limit - upper: No data available.

Explosive limit - lower: No data available.

Heat of combustion: No data available.

Vapor pressure: No data available.

RTV 60/DBT

Vapor density:	> 7
Density:	ca. 1.48 g/cm ³
Relative density:	ca. 1.48
Solubility(ies)	
Solubility in water:	Slightly Soluble
Solubility (other):	No data available.
Partition coefficient (n-octanol/water) Log Pow:	No data available.
Auto-ignition temperature:	No data available.
Decomposition temperature:	No data available.
SADT:	No data available.
Viscosity, dynamic:	No data available.
Viscosity, kinematic:	No data available.
VOC:	15 g/l ;

10. Stability and reactivity

Reactivity:	No dangerous reaction if used as recommended.
Chemical Stability:	Material is stable under normal conditions.
Possibility of hazardous reactions:	Hazardous polymerization does not occur.
Conditions to avoid:	No data available.
Incompatible Materials:	No data available.
Hazardous Decomposition Products:	No data available.

11. Toxicological information

Information on likely routes of exposure

Ingestion:	No data available.
Inhalation:	No data available.
Skin Contact:	No data available.
Eye contact:	No data available.

Symptoms related to the physical, chemical and toxicological characteristics

Ingestion:	No data available.
Inhalation:	No data available.
Skin Contact:	No data available.

RTV 60/DBT

Eye contact: No data available.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral

Product: ATEmix: 33,300.03 mg/kg

Specified substance(s):

(1) Cristobalite LD 50 (Rat): 5,000 mg/kg

Dermal

Product: Not classified for acute toxicity based on available data.

Inhalation

Product: Not classified for acute toxicity based on available data.

Repeated dose toxicity

Product: No data available.

Skin Corrosion/Irritation

Product: No data available.

Serious Eye Damage/Eye Irritation

Product: No data available.

Respiratory or Skin Sensitization

Product: No data available.

Carcinogenicity

Product: No data available.

RTV 60/DBT

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

No carcinogenic components identified

(1) QUARTZ Overall evaluation: 1. Carcinogenic to humans.

US. National Toxicology Program (NTP) Report on Carcinogens:

No carcinogenic components identified

(1) Cristobalite Known To Be Human Carcinogen. Reasonably Anticipated to be a Human Carcinogen.

Kieselguhr, soda Known To Be Human Carcinogen.

ash flux-calcined

(1) QUARTZ Known To Be Human Carcinogen.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050), as amended:

No carcinogenic components identified

Germ Cell Mutagenicity

In vitro

Product: No data available.

In vivo

Product: No data available.

Reproductive toxicity

Product: No data available.

Specific Target Organ Toxicity - Single Exposure

Product: No data available.

Specific Target Organ Toxicity - Repeated Exposure

Product: No data available.

Aspiration Hazard

Product: No data available.

Other effects:

No data available.

12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:

RTV 60/DBT

Fish

Product: No data available.

Aquatic Invertebrates

Product: No data available.

Chronic hazards to the aquatic environment:

Fish

Product: No data available.

Aquatic Invertebrates

Product: No data available.

Toxicity to Aquatic Plants

Product: No data available.

Persistence and Degradability

Biodegradation

Product: No data available.

BOD/COD Ratio

Product: No data available.

Bioaccumulative potential

Bioconcentration Factor (BCF)

Product: No data available.

Partition Coefficient n-octanol / water (log Kow)

Product: No data available.

Mobility in soil: No data available.

Known or predicted distribution to environmental compartments

Red iron oxide No data available.

(1) Cristobalite No data available.

Kieselguhr, soda ash flux-calcined No data available.

Silicic acid, ethyl ester No data available.

(1) QUARTZ No data available.

Known or predicted distribution to environmental compartments

RTV 60/DBT

Red iron oxide	No data available.
(1) Cristobalite	No data available.
Kieselguhr, soda ash flux- calcined	No data available.
Silicic acid, ethyl ester	No data available.
(1) QUARTZ	No data available.

Other adverse effects: No data available.

13. Disposal considerations

Disposal instructions: No data available.

Contaminated Packaging: Dispose of as unused product.

14. Transport information

DOT

Not regulated.

IMDG

Not regulated.

IATA

Not regulated.

Special precautions for user: This product is not regarded as dangerous goods according to the national and international regulations on the transport of dangerous goods.

15. Regulatory information

US Federal Regulations

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

None present or none present in regulated quantities.

US. Toxic Substances Control Act (TSCA) Section 5(a)(2) Final Significant New Use Rules (SNURs) (40 CFR 721, Subpt E)

None present or none present in regulated quantities.

RTV 60/DBT

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050), as amended

<u>Chemical Identity</u>	<u>OSHA hazard(s)</u>
Siloxanes and Silicones, di-Me hydroxy terminated	No OSHA Hazards
Red iron oxide	Causes mild skin irritation.; Respiratory hazard.
(1) Cristobalite	Toxic by inhalation.; Systemic effects
Kieselguhr, soda ash flux-calcined	Toxic by inhalation.; Systemic effects

CERCLA Hazardous Substance List (40 CFR 302.4):

None present or none present in regulated quantities.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Not classified

SARA 302 Extremely Hazardous Substance

None present or none present in regulated quantities.

SARA 304 Emergency Release Notification

None present or none present in regulated quantities.

SARA 311/312 Hazardous Chemical

<u>Chemical Identity</u>	<u>Threshold Planning Quantity</u>
<u>Chemical Identity</u>	<u>Threshold Planning Quantity</u>

US. EPCRA (SARA Title III Section 313 Toxic Chemical Release Inventory (TRI) Reporting

None present or none present in regulated quantities.

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

None present or none present in regulated quantities.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130):

None present or none present in regulated quantities.

US State Regulations

US. California Proposition 65

No ingredient requiring a warning under CA Prop 65.

US. New Jersey Worker and Community Right-to-Know Act

<u>Chemical Identity</u>
Siloxanes and Silicones, di-Me hydroxy terminated
Red iron oxide
(1) Cristobalite
Kieselguhr, soda ash flux-calcined
Silicic acid, ethyl ester

RTV 60/DBT

(1) QUARTZ

US. Massachusetts RTK - Substance List

Chemical Identity

Red iron oxide

(1) Cristobalite

(1) QUARTZ

Chemical Identity

Red iron oxide

(1) Cristobalite

(1) QUARTZ

US. Pennsylvania RTK - Hazardous Substances

Chemical Identity

Red iron oxide

(1) Cristobalite

Kieselguhr, soda ash flux-calcined

Silicic acid, ethyl ester

US. Rhode Island RTK

Chemical Identity

Red iron oxide

RTV 60/DBT

Inventory Status:

Australia Industrial Chem. Act (AIC):	On or in compliance with the inventory	Remarks: None.
Canada DSL Inventory List:	On or in compliance with the inventory	Remarks: None.
Canada NDSL Inventory:	Not in compliance with the inventory.	Remarks: None.
China Inv. Existing Chemical Substances:	On or in compliance with the inventory	Remarks: None.
Japan (ENCS) List:	On or in compliance with the inventory	Remarks: None.
Korea Existing Chemicals Inv. (KECI):	On or in compliance with the inventory	Remarks: None.
New Zealand Inventory of Chemicals:	On or in compliance with the inventory	Remarks: None.
Philippines PICCS:	On or in compliance with the inventory	Remarks: None.
Taiwan Chemical Substance Inventory:	On or in compliance with the inventory	Remarks: None.
US TSCA Inventory:	On or in compliance with the inventory	Remarks: Commercial Status: Active

16. Other information, including date of preparation or last revision

HMIS Hazard ID

Health	<input type="text" value="0"/>
Flammability	<input type="text" value="1"/>
Physical Hazards	<input type="text" value="0"/>
PERSONAL PROTECTION	<input type="text"/>

Hazard rating: 0 - Minimal; 1 - Slight; 2 - Moderate; 3 - Serious; 4 - Severe; RNP - Rating not possible; *Chronic health effect

Issue Date: 03/28/2023
Revision Date: No data available.
Version #: 2.4
Further Information: No data available.

RTV 60/DBT

Disclaimer:

Notice to reader

Unless otherwise specified in section 1, Momentive products are intended for use in the manufacture and/or formulation of products and are not intended for direct consumer use. These products are not intended for long-lasting (> 30 days) implantation, injection or direct ingestion into the human body, nor for use in the manufacture of multiple use contraceptives. Keep out of the reach of children.

Further Information

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

® and TM indicate trademarks owned by or licensed to Momentive.