

Revision Date: 07/02/2020

SS4155

SAFETY DATA SHEET

1. Identification

Product identifier: SS4155

Other means of identification

Synonyms: SILICON PRIMER MIXTURE

Recommended use and restriction on use

Recommended use: Primer

Restrictions on use: None known.

Manufacturer/Importer/Distr :

ibutor Information

Momentive Performance Materials LLC

260 Hudson River Road Waterford NY 12188

Contact person : commercial.services@momentive.com

Telephone : General information

+1-800-295-2392

Emergency telephone

number

Supplier : CHEMTREC

1-800-424-9300

2. Hazard(s) identification

Hazard Classification

Physical Hazards

Flammable liquids Category 3

Health Hazards

Serious Eye Damage/Eye Irritation Category 1
Specific Target Organ Toxicity - Category 3¹

Single Exposure

Specific Target Organ Toxicity - Category 12.

Repeated Exposure

Target Organs

Respiratory tract irritation.
 Central nervous system.

Unknown toxicity - Health

-	· · · · · · · · · · · · · · · · · · ·	
	Acute toxicity, oral	0 %
	Acute toxicity, dermal	0 %

SDS_US 1/16



Revision Date: 07/02/2020

SS4155

Acute toxicity, inhalation, vapor	0 %
Acute toxicity, inhalation, dust or mist	0 %

Label Elements

Hazard Symbol:



Signal Word: Danger

Hazard Statement: H226; Flammable liquid and vapor.

H318; Causes serious eye damage. H335; May cause respiratory irritation.

H372; Causes damage to organs through prolonged or repeated exposure.

Precautionary Statements

Prevention: Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking. Keep container tightly closed. Ground and bond

container and receiving equipment. Use explosion-proof

electrical/ventilating/lighting equipment Use non-sparking tools. Take action to prevent static discharges. Wear protective gloves/protective clothing/eye protection/face protection. Use only outdoors or in a well-ventilated area. Do

not breathe dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Do not eat, drink or smoke when using this product.

Response: IF INHALED: Remove person to fresh air and keep comfortable for

breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. Immediately call a POISON CENTER/doctor. In case

of fire: Use alcohol resistant foam for extinction.

Storage: Store in a well-ventilated place. Keep cool. Keep container tightly closed.

Store locked up.

Disposal: Dispose of contents/container to an appropriate treatment and disposal

facility in accordance with applicable laws and regulations, and product

characteristics at time of disposal.

Other hazards which do not result in GHS classification:

Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and

vapor. May cause flash fire or explosion.

SDS_US 2/16



Revision Date: 07/02/2020

SS4155

3. Composition/information on ingredients

Mixtures

Chemical Identity	CAS number	Content in percent (%)*	Notes
STODDARD SOLVENT	8052-41-3	50 - <100%	# This substance has workplace exposure limit(s).
Tetraethyl Silicate	78-10-4	20 - <50%	# This substance has workplace exposure limit(s).
1-butanol, titanium (4+) salt	5593-70-4	5 - <10%	# This substance has workplace exposure limit(s).
1,2,4-TRIMETHYLBENZENE	95-63-6	1 - <5%	# This substance has workplace exposure limit(s).
Silicic acid, ethyl ester	11099-06-2	1 - <5%	No data available.

^{*} All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Ingestion: Do NOT induce vomiting. If conscious, drink plenty of water. Seek medical

attention.

Inhalation: Move the exposed person to fresh air at once. Remove from contaminated

area. Apply artificial respiration if not breathing. Call a physician or poison control center immediately. For breathing difficulties, oxygen may be

necessary.

Skin Contact: Wash off promptly and flush contaminated skin with water. Promptly

remove clothing if soaked through and flush skin with water. Get medical attention if symptoms persist. Wash contaminated clothing before reuse.

Eye contact: Rinse immediately with plenty of water, also under the eyelids, for at least

15 minutes. Obtain medical attention without delay, preferably from an

ophthalmologist.

Most important symptoms/effects, acute and delayed

Symptoms: No data available.

Hazards: No data available.

Indication of immediate medical attention and special treatment needed

SDS_US 3/16



Revision Date: 07/02/2020

SS4155

Treatment: Treatment is symptomatic and supportive.

5. Fire-fighting measures

General Fire Hazards: Do not use water jet as an extinguisher, as this will spread the fire. Use

water spray to keep fire-exposed containers cool.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing

media:

All standard extinguishing agents are suitable.

Unsuitable extinguishing

media:

No data available.

Specific hazards arising from

the chemical:

Vapors are flammable and heavier than air. Vapors may travel across the ground and reach remote ignition sources causing a flashback fire danger. Ground container and transfer equipment to eliminate static electric sparks.

Special protective equipment and precautions for firefighters

Special fire fighting

procedures:

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. Product may charge electrostatically during pouring or filling. All equipment used when handling the product must be grounded.

Special protective equipment

for fire-fighters:

Firefighters must wear NIOSH/MSHA approved positive pressure selfcontained breathing apparatus with full face mask and full protective

clothing.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures:

Avoid contact with eyes, skin, and clothing. Keep out of reach of children. Attention: Not for injection into humans.

Methods and material for containment and cleaning

up:

Warn other workers of spill. Wear proper protective equipment as specified in the protective equipment section. Wipe, scrape, or soak up in an inert material and put in a container intended for flammable materials for

disposal.

Notification Procedures: ELIMINATE all ignition sources (no smoking, flares, sparks or flames in

immediate area).

Environmental Precautions: Avoid discharge into drains, water courses or onto the ground.

SDS_US 4/16



Revision Date: 07/02/2020

SS4155

7. Handling and storage

Precautions for safe handling:

Sensitivity to static discharge is expected; material has a flash point below 200 F. Do not breathe vapor/spray. Do not taste or swallow. Avoid contact with eyes, skin, and clothing. See Section 8 of the SDS for Personal Protective Equipment. Wash hands after handling. Material can accumulate static charges which may cause an electrical spark (ignition source). Use proper bonding and/or grounding procedures.

Conditions for safe storage, including any incompatibilities:

Keep away from heat, sparks and open flame. Keep container closed. Store in original container.

8. Exposure controls/personal protection

Control Parameters

Occupational Exposure Limits

Chemical Identity	Туре	Exposure Lir	nit Values	Source
STODDARD SOLVENT	TWA	100 ppm		US. ACGIH Threshold Limit Values, as amended (03 2015)
	REL		350 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2010)
	Ceil_Time		1,800 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2010)
	PEL	500 ppm	2,900 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
	TWA	100 ppm	525 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended (1989)
	TWA	100 ppm	525 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A, as amended (06 2008)
	AN ESL		350 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality), as amended (11 2016)
	ST ESL		3,500 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality), as amended (11 2016)
	ST ESL		670 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality), as amended (11 2016)
	AN ESL		67 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality), as amended (11 2016)
	TWA PEL	100 ppm	525 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants, as amended (01 2015)
	IDLH		20,000 mg/m3	US. NIOSH. Immediately Dangerous to Life or Health (IDLH) Values, as amended (10 2017)
Tetraethyl Silicate	TWA	10 ppm		US. ACGIH Threshold Limit Values, as amended (03 2015)
	REL	10 ppm	85 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2010)
	PEL	100 ppm	850 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
	TWA	10 ppm	85 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended (1989)
	TWA	10 ppm	85 mg/m3	US. Tennessee. OELs. Occupational Exposure

SDS_US 5/16



Revision Date: 07/02/2020

SS4155

	1			Limits Table 74A as assessed at (00,000)
	TAVA DEL	40	05 / 0	Limits, Table Z1A, as amended (06 2008)
	TWA PEL	10 ppm	85 mg/m3	US. California Code of Regulations, Title 8,
				Section 5155. Airborne Contaminants, as
				amended (01 2015)
	IDLH	700 ppm		US. NIOSH. Immediately Dangerous to Life or
				Health (IDLH) Values, as amended (10 2017)
	ST ESL		100 ppb	US. Texas. Effects Screening Levels (Texas
				Commission on Environmental Quality), as
				amended (06 2018)
	ANESL		85 µg/m3	US. Texas. Effects Screening Levels (Texas
				Commission on Environmental Quality), as
				amended (06 2018)
	ST ESL		850 µg/m3	US. Texas. Effects Screening Levels (Texas
			222 Jug. 112	Commission on Environmental Quality), as
				amended (06 2018)
	AN ESL		10 ppb	US. Texas. Effects Screening Levels (Texas
	7		.0 PP2	Commission on Environmental Quality), as
				amended (06 2018)
1,2,4-TRIMETHYLBENZENE	TWA	25 ppm		US. ACGIH Threshold Limit Values, as
1,2,11111111111111111111111111111111111		20 pp		amended (03 2015)
	REL	25 ppm	125 mg/m3	US. NIOSH: Pocket Guide to Chemical
	INCL	25 ppm	123 Hg/Hb	Hazards, as amended (2010)
	TWA	25 ppm	125 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000),
	IVVA	23 ppm	123 Hg/H5	as amended (1989)
	TWA	25 ppm	125 mg/m3	US. Tennessee. OELs. Occupational Exposure
	IVVA	23 ppm	123 Hg/H5	Limits, Table Z1A, as amended (06 2008)
	TWA PEL	25 ppm	125 mg/m3	US. California Code of Regulations, Title 8,
	IVVA FEL	25 ppm	123 Hg/H5	Section 5155. Airborne Contaminants, as
	ANIFOL		F.4/- 2	amended (01 2015)
	AN ESL		54 μg/m3	US. Texas. Effects Screening Levels (Texas
				Commission on Environmental Quality), as
				amended (06 2018)
	AN ESL		11 ppb	US. Texas. Effects Screening Levels (Texas
				Commission on Environmental Quality), as
				amended (06 2018)
	ST ESL		4,400 µg/m3	US. Texas. Effects Screening Levels (Texas
				Commission on Environmental Quality), as
				amended (06 2018)
	ST ESL		890 ppb	US. Texas. Effects Screening Levels (Texas
				Commission on Environmental Quality), as
				amended (06 2018)
				amended (06 2018)

Appropriate Engineering Controls

Provide eyewash station and safety shower. General (mechanical) room ventilation is expected to be satisfactory if handled at low temperatures or in covered equipment. Provide adequate ventilation if fumes or vapors are generated.

Individual protection measures, such as personal protective equipment

General information: General (mechanical) room ventilation is expected to be satisfactory if

handled at low temperatures or in covered equipment.

Eye/face protection: Monogoggles Use safety goggles and face shield in case of splash risk.

Skin Protection

Hand Protection: Chemical resistant gloves

Other: Wear suitable protective clothing and eye/face protection.

SDS_US 6/16



Revision Date: 07/02/2020

SS4155

Respiratory Protection: If exposure limits are exceeded or respiratory irritation is experienced,

NIOSH/MSHA approved respiratory protection should be worn. Supplied air respirators may be required for non-routine or emergency situations. Respiratory protection must be provided in accordance with OSHA

regulations (see 29CFR 1910.134).

Hygiene measures: Avoid inhalation of vapors and spray mists. Avoid contact with eyes, skin,

and clothing. When using do not eat, drink or smoke. Wash thoroughly after

handling.

9. Physical and chemical properties

Appearance

Physical state: liquid
Form: liquid
Color: Blue
Odor: Faint

Odor threshold:

pH:

No data available.

Not applicable

Very applicable

Very applicable

Very applicable

Very applicable

Very applicable

Very applicable

Initial boiling point and boiling range: > 98 °C (1,013 hPa)
Flash Point: 36.60 °C (Closed Cup)
Evaporation rate: No data available.
Flammability (solid, gas): No data available.

Upper/lower limit on flammability or explosive limits

Flammability limit - upper (%): 6.00 %(V)
Flammability limit - lower (%): 1.00 %(V)

Explosive limit - upper:

Explosive limit - lower:

No data available.

No data available.

No data available.

Vapor pressure: Not applicable

Vapor density:No data available.Density:calculated 0.86 g/cm3

Relative density: 0.81

Solubility(ies)

Solubility in water: Negligible

Solubility (other): No data available.

Partition coefficient (n-octanol/water) Log No data available.

Pow:

Auto-ignition temperature: 245.00 °C

Decomposition temperature:No data available.

SDS_US 7/16



Revision Date: 07/02/2020

SS4155

SADT: No data available.

Viscosity, dynamic: No data available.

Viscosity, kinematic: < 20.5 mm2/s (40 °C)

VOC: 765 g/l ;

10. Stability and reactivity

Reactivity: No dangerous reaction if used as recommended.

Chemical Stability: Material is stable under normal conditions.

Possibility of hazardous

reactions:

Hazardous polymerization does not occur.

Conditions to avoid: Keep away from sources of ignition - No smoking. Keep away from sources

of ignition - No smoking.

Incompatible Materials: Oxidizing agents.

Hazardous Decomposition

Products:

Carbon oxides Oxides of silicon. Measurements at temperatures above 150°C in presence of air (oxygen) have shown that small amounts of

formaldehyde are formed due to oxidative degradation.

11. Toxicological information

Information on likely routes of exposure

Ingestion: No data available.

Inhalation: No data available.

Skin Contact: No data available.

Eye contact: No data available.

Symptoms related to the physical, chemical and toxicological characteristics

Ingestion: No data available.

Inhalation: No data available.

Skin Contact: No data available.

Eye contact: No data available.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral

Product:

ATEmix: 24,693.8 mg/kg

SDS_US 8/16



Revision Date: 07/02/2020

SS4155

Dermal

Product: Not classified for acute toxicity based on available data.

Inhalation

Product:

ATEmix: 41.83 mg/l ATEmix: 5.7 mg/l

Repeated dose toxicity

Product: No data available.

Skin Corrosion/Irritation

Product: No data available.

Serious Eye Damage/Eye Irritation

Product: No data available.

Respiratory or Skin Sensitization

Product: No data available.

Carcinogenicity

Product: No data available.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

No carcinogenic components identified

US. National Toxicology Program (NTP) Report on Carcinogens:

No carcinogenic components identified

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050), as amended:

No carcinogenic components identified

Germ Cell Mutagenicity

In vitro

Product: No data available.

In vivo

Product: No data available.

SDS_US 9/16



Revision Date: 07/02/2020

SS4155

Reproductive toxicity

Product: No data available.

Specific Target Organ Toxicity - Single Exposure
Product:

No data available.

Specific Target Organ Toxicity - Repeated Exposure

Product: No data available.

Target Organs

Specific Target Organ Toxicity - Single Exposure: Respiratory tract irritation. Specific Target Organ Toxicity - Repeated Exposure: Central nervous system.

Aspiration Hazard

Product: No data available.

Other effects: No data available.

12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:

Fish

Product: No data available.

Specified substance(s):

Tetraethyl Silicate LC100 (No data available., 24 h): 9,000 mg/l

LC50 (Brachydanio rerio, 96 h): > 245 mg/l

Aquatic Invertebrates

Product: No data available.

Specified substance(s):

Tetraethyl Silicate EC50 (Blue Crab): 7,800 mg/l

Chronic hazards to the aquatic environment:

Fish

Product: No data available.

Aquatic Invertebrates

Product: No data available.

Toxicity to Aquatic Plants

Product: No data available.

SDS_US 10/16



Revision Date: 07/02/2020

SS4155

Persistence and Degradability

Biodegradation

Product: No data available.

Specified substance(s):

Tetraethyl Silicate 98 % (28 d, OECD-Guideline 301 A (DOC Die-Away Test)) Readily

biodegradable

BOD/COD Ratio

Product: No data available.

Bioaccumulative potential

Bioconcentration Factor (BCF)

Product: No data available.

Partition Coefficient n-octanol / water (log Kow)
Product:
No data available.

Mobility in soil: No data available.

Known or predicted distribution to environmental compartments

STODDARD SOLVENT
Tetraethyl Silicate
1-butanol, titanium(4+)salt
1,2,4No data available.
No data available.
No data available.
No data available.

TRIMETHYLBENZENE

Silicic acid, ethyl ester No data available.

Other adverse effects: No data available.

13. Disposal considerations

General information: The generation of waste should be avoided or minimized wherever

possible. Do not discharge into drains, water courses or onto the ground.

See Section 8 for information on appropriate personal protective

equipment.

Disposal instructions: Disposal should be made in accordance with federal, state and local

regulations.

Contaminated Packaging: Dispose of as unused product.

SDS_US 11/16



Revision Date: 07/02/2020

SS4155

14. Transport information

DOT

UN Number: UN 1993

UN Proper Shipping Name: Flammable liquids, n.o.s.(STODDARD SOLVENT, TETRAETHYL

SILICATE)

Transport Hazard Class(es)

Class: 3
Label(s): 3
Packing Group: III
Marine Pollutant: No

IMDG

UN Number: UN 1993

UN Proper Shipping Name: FLAMMABLE LIQUID, N.O.S.(STODDARD SOLVENT,

TETRAETHYL SILICATE)

Transport Hazard Class(es)

Class: 3 Label(s): 3

EmS No.: F-E, S-E

Packing Group: III
Marine Pollutant: No
Limited quantity 5.00L

Excepted quantity E1

IATA

UN Number: UN 1993

Proper Shipping Name: Flammable liquid, n.o.s.(STODDARD SOLVENT, TETRAETHYL

SILICATE)

366

Transport Hazard Class(es):

Class: 3
Label(s): 3
Packing Group: III
Cargo aircraft only Packing 366

Instructions:

Passenger and cargo aircraft

Packing Instructions:

Limited quantity: Y344

Packing Instructions:

Excepted quantity E1

Environmental Hazards: Not regulated.

Marine Pollutant: No

15. Regulatory information

US Federal Regulations

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

None present or none present in regulated quantities.

SDS_US 12/16



Revision Date: 07/02/2020

SS4155

CERCLA Hazardous Substance List (40 CFR 302.4):

None present or none present in regulated quantities.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Hazards Not Otherwise Classified (HNOC)
Flammable (gases, aerosols, liquids, or solids)
Serious eye damage or eye irritation

Specific target organ toxicity (single or repeated exposure)

SARA 302 Extremely Hazardous Substance

None present or none present in regulated quantities.

SARA 304 Emergency Release Notification

None present or none present in regulated quantities.

SARA 311/312 Hazardous Chemical

Chemical Identity	Threshold Planning Quantity
STODDARD SOLVENT	10000 lbs
Tetraethyl Silicate	10000 lbs
1-butanol, titanium(4+)salt	10000 lbs
1,2,4-	10000 lbs
TRIMETHYLBENZENE	
Silicic acid, ethyl ester	10000 lbs

SARA 313 (TRI Reporting)

Reporting Reporting threshold for manufacturing and other users processing

Chemical Identity 1,2,4-

TRIMETHYLBENZENE

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

None present or none present in regulated quantities.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130):

None present or none present in regulated quantities.

US State Regulations

US. California Proposition 65

No ingredient requiring a warning under CA Prop 65.

US. New Jersey Worker and Community Right-to-Know Act

Chemical Identity

STODDARD SOLVENT
Tetraethyl Silicate
1-butanol, titanium(4+)salt
1,2,4-TRIMETHYLBENZENE

SDS_US 13/16



Revision Date: 07/02/2020

SS4155

Silicic acid, ethyl ester

US. Massachusetts RTK - Substance List

Chemical Identity

STODDARD SOLVENT Tetraethyl Silicate 1,2,4-TRIMETHYLBENZENE

US. Pennsylvania RTK - Hazardous Substances

Chemical Identity

STODDARD SOLVENT Tetraethyl Silicate 1,2,4-TRIMETHYLBENZENE Silicic acid, ethyl ester

US. Rhode Island RTK

<u>Chemical Identity</u> STODDARD SOLVENT

Tetraethyl Silicate

SDS_US 14/16



Revision Date: 07/02/2020

SS4155

Inventory Status:

Australia AICS:	y (positive listing)	Remarks: None.
EU EINECS List:	y (positive listing)	Remarks: None.
Japan (ENCS) List:	y (positive listing)	Remarks: None.
China Inventory of Existing	y (positive listing)	Remarks: None.
Chemical Substances:		
Korea Existing Chemicals Inv.	y (positive listing)	Remarks: None.
(KECI):		
Canada DSL Inventory List:	y (positive listing)	Remarks: None.
Canada NDSL Inventory:	n (Negative listing)	Remarks: None.
Philippines PICCS:	y (positive listing)	Remarks: None.
US TSCA Inventory:	y (positive listing)	Remarks: None.
Taiwan. Taiwan inventory	y (positive listing)	Remarks: None.
(CSNN):		
REACH:	If purchased from Momentive	Remarks: None.
	Performance Materials GmbH in	
	Leverkusen, Germany, all	
	substances in this product have	
	been registered by Momentive	
	Performance Materials GmbH or	
	upstream in our supply chain or are	
	exempt from registration under	
	Regulation (EC) No 1907/2006	
	(REACH). For polymers, this	
	includes the constituent monomers	
	and other reactants.	

16.Other information, including date of preparation or last revision

HMIS Hazard ID

Health	*	3
Flammability		3
Physical Hazards	0	
PERSONAL PROTECTION		

Hazard rating: 0 - Minimal; 1 - Slight; 2 - Moderate; 3 - Serious; 4 - Severe; RNP - Rating not possible; *Chronic health effect

Issue Date: 07/02/2020

Revision Date: No data available.

Version #: 3.1

Further Information: No data available.

SDS_US 15/16



Revision Date: 07/02/2020

SS4155

Disclaimer:

Notice to reader

Unless otherwise specified in section 1, Momentive products are intended for use in the manufacture and/or formulation of products and are not intended for direct consumer use. These products are not intended for long-lasting (> 30 days) implantation, injection or direct ingestion into the human body, nor for use in the manufacture of multiple use contraceptives. Keep out of the reach of children.

Further Information

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warrantyor quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

® and TM indicate trademarks owned by or licensed to Momentive.

SDS_US 16/16