

SECTION 1: Identification

1.1. Identification

Product form : Mixture
 Product name : Super Vinall
 Product code : 1485-618

1.2. Recommended use and restrictions on use

Use of the substance/mixture : Cleaners, liquids (all purpose cleaners, sanitary products, floor cleaners, glass cleaners, carpet cleaners, metal cleaners)

1.3. Supplier

Mirandy Products, LLC
 1078 Grand Avenue
 South Hempstead, NY 11550
 T (516) 489-6800

1.4. Emergency telephone number

Emergency number : (800) 535-5053

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Flammable liquids Category 4 H227 Combustible liquid
 Skin corrosion/irritation Category 1A H314 Causes severe skin burns and eye damage
 Serious eye damage/eye irritation Category 1 H318 Causes serious eye damage

Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS-US) :



Signal word (GHS-US) : Danger

Hazard statements (GHS-US) : H227 - Combustible liquid
 H314 - Causes severe skin burns and eye damage

Precautionary statements (GHS-US) : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P260 - Do not breathe dust/mist/spray
 P264 - Wash hands and forearms thoroughly after handling
 P280 - Wear protective gloves/eye protection/face protection
 P301+P330+P331 - If swallowed: rinse mouth. Do NOT induce vomiting
 P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower
 P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing
 P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
 P310 - Immediately call a poison center/doctor
 P321 - Specific treatment (see First aid measures on this label)
 P363 - Wash contaminated clothing before reuse
 P370+P378 - In case of fire: Use appropriate media to extinguish
 P403+P235 - Store in a well-ventilated place. Keep cool
 P405 - Store locked up
 P501 - Dispose of contents/container in accordance with local/regional/national/international regulations

2.3. Other hazards which do not result in classification

No additional information available

Super Vinall

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS US classification
Trisodium orthophosphate, dodecahydrate	(CAS-No.) 10101-89-0	1 - 5	Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H335
Disodium metasilicate	(CAS-No.) 6834-92-0	1 - 5	Acute Tox. 4 (Oral), H302 Skin Corr. 1A, H314 STOT SE 3, H335

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

- First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
- First-aid measures after inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately call a poison center or doctor/physician.
- First-aid measures after skin contact : Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. Immediately call a poison center or doctor/physician.
- First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center or doctor/physician.
- First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Immediately call a poison center or doctor/physician.

4.2. Most important symptoms and effects (acute and delayed)

- Potential Adverse human health effects and symptoms : Based on available data, the classification criteria are not met.
- Symptoms/effects : Causes severe skin burns and eye damage.
- Symptoms/effects after eye contact : Causes serious eye damage.

4.3. Immediate medical attention and special treatment, if necessary

No additional information available

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

- Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Sand.
- Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

- Fire hazard : Combustible liquid.
- Explosion hazard : May form flammable/explosive vapor-air mixture.

5.3. Special protective equipment and precautions for fire-fighters

- Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment.
- Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Remove ignition sources. Use special care to avoid static electric charges. No open flames. No smoking.

6.1.1. For non-emergency personnel

- Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

- Protective equipment : Equip cleanup crew with proper protection.
- Emergency procedures : Ventilate area.

Super Vinall

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Handle empty containers with care because residual vapors are flammable. Keep away from heat/sparks/open flames}. - No smoking.

Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. No open flames. No smoking. Do not breathe dust/mist/spray. Avoid contact during pregnancy/while nursing.

Hygiene measures : Wash hands and forearms thoroughly after handling.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Proper grounding procedures to avoid static electricity should be followed. Comply with applicable regulations.

Storage conditions : Keep only in the original container in a cool, well ventilated place away from heat, hot surfaces, sparks, open flame and other ignition sources. No smoking. Keep container closed when not in use. Keep in fireproof place.

Incompatible products : Strong bases. Strong acids.

Incompatible materials : Sources of ignition. Direct sunlight. Heat sources.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Super Vinall
No additional information available
Disodium metasilicate (6834-92-0)
No additional information available
Trisodium orthophosphate, dodecahydrate (10101-89-0)
No additional information available

8.2. Appropriate engineering controls

No additional information available

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Avoid all unnecessary exposure.

Hand protection:

Wear protective gloves/eye protection/face protection protective gloves

Eye protection:

Chemical goggles or face shield

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

Wear appropriate mask

Other information:

Do not eat, drink or smoke during use.

Super Vinall

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Color	: Green
Odor	: Solvent
Odor threshold	: No data available
pH	: 13
Melting point	: No data available
Freezing point	: No data available
Boiling point	: 212 °F
Flash point	: 150 °F
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: Combustible liquid.
Vapor pressure	: No data available
Relative vapor density at 20 °C	: No data available
Relative density	: 1.013
Solubility	: Soluble in water.
Log Pow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Thermal decomposition generates : corrosive vapors.

10.2. Chemical stability

Combustible liquid. May form flammable/explosive vapor-air mixture.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures. Open flame. Overheating. Heat. Sparks.

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products

Fume. Carbon monoxide. Carbon dioxide. May release flammable gases. Thermal decomposition generates : corrosive vapors.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

Disodium metasilicate (6834-92-0)	
LD50 oral rat	1152 - 1349 mg/kg body weight (Rat, Male / female, Experimental value, Oral)
LD50 dermal rat	> 5000 mg/kg body weight (EPA OPPTS 870.1200: Acute Dermal Toxicity, 24 h, Rat, Male / female, Experimental value, Dermal, 14 day(s))

Super Vinall

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Disodium metasilicate (6834-92-0)	
LC50 inhalation rat (mg/l)	> 2.06 mg/l/4h (OECD 403: Acute Inhalation Toxicity, 4 h, Rat, Male/female, Read-across)
ATE US (oral)	1152 mg/kg body weight

Trisodium orthophosphate, dodecahydrate (10101-89-0)	
LD50 oral rat	> 2000 mg/kg body weight (OECD 420: Acute Oral toxicity – Acute Toxic Class Method, Rat, Female, Experimental value, Anhydrous form, Oral, 14 day(s))
LD50 dermal rat	> 2000 mg/kg (OECD 402: Acute Dermal Toxicity, 24 h, Rat, Male / female, Read-across, Dermal, 14 day(s))
LC50 inhalation rat (mg/l)	> 0.83 mg/l (OECD 403: Acute Inhalation Toxicity, 4 h, Rat, Male / female, Read-across, (maximum achievable concentration), Inhalation (dust), 14 day(s))

Skin corrosion/irritation : Causes severe skin burns and eye damage.

pH: 13

Serious eye damage/irritation : Causes serious eye damage.

pH: 13

Respiratory or skin sensitization : Not classified

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

Reproductive toxicity : Not classified

Specific target organ toxicity – single exposure : Not classified

Disodium metasilicate (6834-92-0)	
Specific target organ toxicity – single exposure	May cause respiratory irritation.

Trisodium orthophosphate, dodecahydrate (10101-89-0)	
Specific target organ toxicity – single exposure	May cause respiratory irritation.

Specific target organ toxicity – repeated exposure : Not classified

Aspiration hazard : Not classified

Viscosity, kinematic : No data available

Potential Adverse human health effects and symptoms : Based on available data, the classification criteria are not met.

Symptoms/effects : Causes severe skin burns and eye damage.

Symptoms/effects after eye contact : Causes serious eye damage.

SECTION 12: Ecological information

12.1. Toxicity

Disodium metasilicate (6834-92-0)	
LC50 fish 1	210 mg/l (ISO 7346-1, 96 h, Danio rerio, Semi-static system, Fresh water, Experimental value)
EC50 Daphnia 1	1700 mg/l (EU Method C.2, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, GLP)

Trisodium orthophosphate, dodecahydrate (10101-89-0)	
LC50 fish 1	> 100 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Oncorhynchus mykiss, Semi-static system, Fresh water, Read-across, Anhydrous form)
EC50 Daphnia 1	100 mg/l (48 h; Daphnia magna)
ErC50 (algae)	> 100 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Desmodesmus subspicatus, Static system, Fresh water, Experimental value, Anhydrous form)

12.2. Persistence and degradability

Super Vinall	
Persistence and degradability	Not established.

Disodium metasilicate (6834-92-0)	
Persistence and degradability	Biodegradability: not applicable. No (test)data on mobility of the substance available. Not established.

Super Vinall

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Disodium metasilicate (6834-92-0)	
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
BOD (% of ThOD)	Not applicable
Trisodium orthophosphate, dodecahydrate (10101-89-0)	
Persistence and degradability	Biodegradability in soil: not applicable. Biodegradability: not applicable.
Chemical oxygen demand (COD)	Not applicable (inorganic)
ThOD	Not applicable (inorganic)

12.3. Bioaccumulative potential

Super Vinall	
Bioaccumulative potential	Not established.
Disodium metasilicate (6834-92-0)	
Bioaccumulative potential	Bioaccumulation: not applicable. Not established.
Trisodium orthophosphate, dodecahydrate (10101-89-0)	
Bioaccumulative potential	Not bioaccumulative.

12.4. Mobility in soil

Disodium metasilicate (6834-92-0)	
Ecology - soil	No (test) data on mobility of the substance available.
Trisodium orthophosphate, dodecahydrate (10101-89-0)	
Ecology - soil	Adsorbs into the soil.

12.5. Other adverse effects

Other information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Disposal methods

Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container in accordance with local/regional/national/international regulations.

Additional information : Handle empty containers with care because residual vapors are flammable.

Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Transport document description : NA1760 Compounds, cleaning liquid (Contains Sodium Metasilicate), 8, II

UN-No.(DOT) : NA1760

Proper Shipping Name (DOT) : Compounds, cleaning liquid
Contains Sodium Metasilicate

Class (DOT) : 8 - Class 8 - Corrosive material 49 CFR 173.136

Packing group (DOT) : II - Medium Danger

Hazard labels (DOT) : 8 - Corrosive



DOT Packaging Non Bulk (49 CFR 173.xxx) : 202

DOT Packaging Bulk (49 CFR 173.xxx) : 242

Super Vinall

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT Symbols	: D - Proper shipping name for domestic use only, or to and from Canada, G - Identifies PSN requiring a technical name
DOT Special Provisions (49 CFR 172.102)	: B2 - MC 300, MC 301, MC 302, MC 303, MC 305, and MC 306 and DOT 406 cargo tanks are not authorized. IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized. N37 - This material may be shipped in an integrally-lined fiber drum (1G) which meets the general packaging requirements of subpart B of part 173 of this subchapter, the requirements of part 178 of this subchapter at the packing group assigned for the material and to any other special provisions of column 7 of the 172.101 table. T11 - 6 178.274(d)(2) Normal..... 178.275(d)(3) TP2 - a. The maximum degree of filling must not exceed the degree of filling determined by the following: (image) Where: tr is the maximum mean bulk temperature during transport, tf is the temperature in degrees celsius of the liquid during filling, and a is the mean coefficient of cubical expansion of the liquid between the mean temperature of the liquid during filling (tf) and the maximum mean bulk temperature during transportation (tr) both in degrees celsius. b. For liquids transported under ambient conditions may be calculated using the formula: (image) Where: d15 and d50 are the densities (in units of mass per unit volume) of the liquid at 15 C (59 F) and 50 C (122 F), respectively. TP27 - A portable tank having a minimum test pressure of 4 bar (400 kPa) may be used provided the calculated test pressure is 4 bar or less based on the MAWP of the hazardous material, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.
DOT Packaging Exceptions (49 CFR 173.xxx)	: 154
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: 1 L
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 30 L
DOT Vessel Stowage Location	: B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded.
DOT Vessel Stowage Other	: 40 - Stow "clear of living quarters"
Other information	: No supplementary information available.

Transportation of Dangerous Goods

Transport by sea

Air transport

SECTION 15: Regulatory information

15.1. US Federal regulations

Super Vinall	
Not listed on the United States TSCA (Toxic Substances Control Act) inventory	
Disodium metasilicate (6834-92-0)	
Not listed on the United States TSCA (Toxic Substances Control Act) inventory	
Trisodium orthophosphate, dodecahydrate (10101-89-0)	
Not listed on the United States TSCA (Toxic Substances Control Act) inventory Not subject to reporting requirements of the United States SARA Section 313	
CERCLA RQ	5000 lb

15.2. International regulations

CANADA

EU-Regulations

Super Vinall

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

National regulations

No additional information available

15.3. US State regulations

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date : 07/07/2015

Other information : None.

Full text of H-phrases:

H227	Combustible liquid
H302	Harmful if swallowed
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H318	Causes serious eye damage
H335	May cause respiratory irritation

Hazard Rating

Health : 1 Slight Hazard - Irritation or minor reversible injury possible

Flammability : 1 Slight Hazard - Materials that must be preheated before ignition will occur. Includes liquids, solids and semi solids having a flash point above 200 F. (Class IIIB)

Physical : 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT react with water, polymerize, decompose, condense, or self-react. Non-Explosives.

Personal protection : B
B - Safety glasses, Gloves

SDS US (GHS HazCom 2012)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product