

SAFETY DATA SHEET

Eclipse High Solids Polyurethane Enamel PC-233

Section 1. Identification

GHS product identifier Other means of identification	 Eclipse High Solids Polyurethane Enamel PC-233 PC-233_Curing Solution
Product type Relevant identified uses of the s	: Liquid. substance or mixture and uses advised against : FOR INDUSTRIAL USE ONLY
Supplier/Manufacturer	: Akzo Nobel Coatings, Inc. 1 East Water Street Waukegan, IL 60085 USA Tel. 1 847 623 4200 Email: customer. service@akzonobel.com
Canadian Supplier	 Akzo Nobel Coatings Ltd. 110 Woodbine Downs Blvd. Unit #4 Etobicoke, Ontario Canada M9W 5S6 +1 (800) 618-1010
Emergency telephone number	: CHEMTREC +1 (800) 424-9300 (Inside the US) CHEMTREC International +1 (703) 527-3887 (Outside the US, collect calls accepted)
Date of issue / Date of revision Version Date of printing	 30 November 2015 17.01 30 November 2015

Akzo Nobel Coatings Inc. encourages and expects you to read and understand this entire MSDS, as there is important information throughout the document. Further, Akzo Nobel Coatings Inc. expects you to follow the precautions identified in this document unless your use conditions would necessitate other appropriate methods or actions.

To promote safe handling, each customer or recipient should: 1) Notify its employees, agents, contractors, and others whom it knows or believes will use this material of the information contained in this MSDS and any other information regarding hazards and safety; 2) Furnish this same information to each of its customers for the product; 3) Request its customers to notify their employees, customers, and other users of the product of this information; and 4) Notify its employees, agents, contractors, and others that the precautions identified for this product and any other products with which mixtures may be created are transferable and cumulative to the mixture.

Section 2. Hazards identification

OSHA/HCS status

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

For additional information call Akzo Nobel at (847) 625-4200

To request an updated SDS please visit http://www.formstack.com/forms/AkzoNobel-document_request_form

Page: 2/13

Section 2. Hazards identification			
Classification of the substance or mixture	: ACUTE TOXICITY (inhalation) - Category 4 SKIN CORROSION/IRRITATION - Category 2 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A SKIN SENSITIZATION - Category 1 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3 Percentage of the mixture consisting of ingredient(s) of unknown hazards to the		
	aquatic environment: 99.8%		
GHS label elements Hazard pictograms			
Signal word	: Warning		
Hazard statements	 Harmful if inhaled. Causes serious eye irritation. Causes skin irritation. May cause an allergic skin reaction. May cause respiratory irritation. 		
Precautionary statements			
Prevention	: Wear protective gloves. Wear eye or face protection. Use only outdoors or in a well-ventilated area. Avoid breathing vapor. Wash hands thoroughly after handling.		
Response	: IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or physician if you feel unwell. IF ON SKIN: Wash with plenty of soap and water. Take off contaminated clothing and wash it before reuse. If skin irritation or rash occurs: Get medical attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.		
Storage	: Not applicable.		
Disposal	: Dispose of contents and container in accordance with all local, regional, national and international regulations.		
Other hazards which do not	: None known.		

result in classification

Section 3. Composition/information on ingredients

Substance/mixture

: Mixture

Hazardous ingredientsCAS numberIngredient name / Chemical name%CAS numberHexamethylene diisocyanate, oligomers75 - 10028182-81-2hexamethylene-di-isocyanate0 - 1822-06-0

Occupational exposure limits, if available, are listed in Section 8.

For additional information call Akzo Nobel at (847) 625-4200

To request an updated SDS please visit http://www.formstack.com/forms/AkzoNobel-document_request_form

Section 4. First aid measures					
Description of necessa	Description of necessary first aid measures				
Eye contact	 Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention. 				
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth- to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.				
Skin contact	Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.				
Ingestion	: Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.				

Most important symptoms/effects	, acute and delayed

Potential acute health effects				
Eye contact	: Causes serious eye irritation.			
Inhalation	: Harmful if inhaled. May cause respiratory irritation. Exposure to decomposition products may cause a health hazard. Serious effects may be delayed following exposure.			
Skin contact	: Causes skin irritation. May cause an allergic skin reaction.			
Ingestion	: Irritating to mouth, throat and stomach.			
Over-exposure signs/symptoms				
Eye contact	: Adverse symptoms may include the following: pain or irritation watering redness			
Inhalation	: Adverse symptoms may include the following: respiratory tract irritation coughing			

For additional information call Akzo Nobel at (847) 625-4200 To request an updated SDS please visit http://www.formstack.com/forms/AkzoNobel-document_request_form

Section 4. First aid measures					
Skin contact	: Adverse symptoms may include the following: irritation redness				
Ingestion	: No specific data.				
Indication of immediate medical attention and special treatment needed, if necessary					
Notes to physician	: In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.				
Specific treatments	: No specific treatment.				
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.				

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
Specific hazards arising from the chemical	: In a fire or if heated, a pressure increase will occur and the container may burst.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide nitrogen oxides
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	 Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency	: No action shall be taken involving any personal risk or without suitable training.
personnel	Evacuate surrounding areas. Keep unnecessary and unprotected personnel from
	entering. Do not touch or walk through spilled material. Avoid breathing vapor or
	mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is
	inadequate. Put on appropriate personal protective equipment.

For additional information call Akzo Nobel at (847) 625-4200

Page: 4/13

To request an updated SDS please visit http://www.formstack.com/forms/AkzoNobel-document_request_form

Section 6. Accidental release measures

For emergency responders	If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Methods and materials for co	ntainment and cleaning up
Small spill	: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling		
Protective measures	: Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.	
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.	
Conditions for safe storage, including any incompatibilities	: Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.	

To request an updated SDS please visit http://www.formstack.com/forms/AkzoNobel-document_request_form

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

	Ingredient name			E	xposure limits
	hexamethylene-di-isocyanate			-	CGIH TLV (United States, 3/2015). TWA: 0.03 mg/m³ 8 hours. TWA: 0.005 ppm 8 hours.
	ppropriate engineering ontrols	:	Use only with adequate ventilation. ventilation or other engineering contricontaminants below any recommended	trol	s to keep worker exposure to airborne
	nvironmental exposure ontrols	:		of ei gine	
<u>lı</u>	ndividual protection measures	È			
	Hygiene measures	:	before eating, smoking and using the Appropriate techniques should be us Contaminated work clothing should r	ie la sec not ig.	ughly after handling chemical products, avatory and at the end of the working period. It to remove potentially contaminated clothing. It be allowed out of the workplace. Wash Ensure that eyewash stations and safety potential.
	Eye/face protection	:	assessment indicates this is necessing gases or dusts. If contact is possible	ary le, t	roved standard should be used when a risk to avoid exposure to liquid splashes, mists, the following protection should be worn, her degree of protection: chemical splash
	Skin protection				
	Hand protection	:	be worn at all times when handling of this is necessary. Considering the p check during use that the gloves are should be noted that the time to brea	che bara e st akt ture	complying with an approved standard should emical products if a risk assessment indicates ameters specified by the glove manufacturer, ill retaining their protective properties. It hrough for any glove material may be ers. In the case of mixtures, consisting of a of the gloves cannot be accurately
	Body protection	:			body should be selected based on the task and should be approved by a specialist
	Other skin protection	:	Appropriate footwear and any addition selected based on the task being per approved by a specialist before hand	erfo	al skin protection measures should be rmed and the risks involved and should be ng this product.
	Respiratory protection	:	standard if a risk assessment indicat	ites xpc	-fed respirator complying with an approved this is necessary. Respirator selection must osure levels, the hazards of the product and espirator.

For additional information call Akzo Nobel at (847) 625-4200

To request an updated SDS please visit http://www.formstack.com/forms/AkzoNobel-document_request_form

Section 9. Physical and chemical properties

Appearance

Physical state	:	Liquid.
Color	:	Colorless.
Odor	:	Mild.
Odor threshold	:	Not available.
рН	:	Not available.
Melting/freezing point	:	Not available.
Boiling point	:	45°C (113°F)
boiling range	:	Not available.
Flash point	:	Closed cup: 166°C (330.8°F)
Evaporation rate	:	Not available.
Flammability (solid, gas)	:	
Upper/lower flammability or exp		
••		Not determined.
Lower:	:	Not determined.
Vapor pressure	:	Not available.
Vapor density	:	Not available.
Relative density	:	1.16
Density	:	9.68 lbs/gal 1.16 g/cm ³
Solubility	:	Not available.
Solubility in water	:	Not available.
Partition coefficient: n- octanol/water	:	Not available.
Auto-ignition temperature	:	Not available.
Decomposition temperature	:	Not available.
Viscosity	:	Kinematic (room temperature): 4.74 cm ² /s (474 cSt)
Weight Volatiles	:	0% (w/w)
Volume Volatiles	:	0 %(v/v)
Weight Solids	:	100.00 %(w/w)
Volume Solids	:	100.00 %(v/v)
Regulatory VOC	:	0 lbs/gal (0 g/l) minus water and exempt solvents
Section 10 Stability		

Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: No specific data.

For additional information call Akzo Nobel at (847) 625-4200

To request an updated SDS please visit http://www.formstack.com/forms/AkzoNobel-document_request_form

Page: 8/13

Section 10. Stability and reactivity

- Incompatible materials
- : No specific data.

Hazardous decomposition products

: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Not available.

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Hexamethylene diisocyanate, oligomers	Eyes - Moderate irritant Skin - Moderate irritant	Rabbit Rabbit	-	100 milligrams 500 milligrams	-

Sensitization

Not available.

Mutagenicity

Not available.

Carcinogenicity

Not available.

Reproductive toxicity

Not available.

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

Name	Category	Route of exposure	Target organs
Hexamethylene diisocyanate, oligomers	Category 3		Respiratory tract irritation
hexamethylene-di-isocyanate	Category 3		Respiratory tract irritation

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

Information on the likely : Not available. routes of exposure

For additional information call Akzo Nobel at (847) 625-4200

To request an updated SDS please visit http://www.formstack.com/forms/AkzoNobel-document_request_form

Page: 9/13

Potential acute health effects	2
Eye contact	: Causes serious eye irritation.
Inhalation	: Harmful if inhaled. May cause respiratory irritation. Exposure to decomposition products may cause a health hazard. Serious effects may be delayed following exposure.
Skin contact	: Causes skin irritation. May cause an allergic skin reaction.
Ingestion	: Irritating to mouth, throat and stomach.
Symptoms related to the phy	sical, chemical and toxicological characteristics
Eye contact	: Adverse symptoms may include the following: pain or irritation watering redness
Inhalation	: Adverse symptoms may include the following: respiratory tract irritation coughing
Skin contact	 Adverse symptoms may include the following: irritation redness
Ingestion	: No specific data.
Delaved and immediate effect	ts and also chronic effects from short and long term exposure
Delayed and immediate effect Short term exposure	ts and also chronic effects from short and long term exposure
	ts and also chronic effects from short and long term exposure : Not available.
Short term exposure Potential immediate	: Not available.
Short term exposure Potential immediate effects	: Not available.
Short term exposure Potential immediate effects Potential delayed effects	: Not available.
Short term exposure Potential immediate effects Potential delayed effects Long term exposure Potential immediate	: Not available.
Short term exposure Potential immediate effects Potential delayed effects Long term exposure Potential immediate effects	 Not available. Not available. Not available. Not available.
Short term exposure Potential immediate effects Potential delayed effects Long term exposure Potential immediate effects Potential delayed effects	 Not available. Not available. Not available. Not available.
Short term exposure Potential immediate effects Potential delayed effects Long term exposure Potential immediate effects Potential delayed effects Potential chronic health effe	 Not available. Not available. Not available. Not available.
Short term exposure Potential immediate effects Potential delayed effects Long term exposure Potential immediate effects Potential delayed effects Potential chronic health effects Not available.	 Not available. Not available. Not available. Not available. Not available. ects Once sensitized, a severe allergic reaction may occur when subsequently exposed
Short term exposure Potential immediate effects Potential delayed effects Long term exposure Potential immediate effects Potential delayed effects Potential chronic health effe Not available. General	 Not available. Not available. Not available. Not available. Not available. ects Once sensitized, a severe allergic reaction may occur when subsequently expose to very low levels.
Short term exposure Potential immediate effects Potential delayed effects Long term exposure Potential immediate effects Potential delayed effects Potential chronic health effects Not available. General Carcinogenicity	 Not available. Not available. Not available. Not available. Not available. ects Once sensitized, a severe allergic reaction may occur when subsequently expose to very low levels. No known significant effects or critical hazards.
Short term exposure Potential immediate effects Potential delayed effects Long term exposure Potential immediate effects Potential delayed effects Potential delayed effects Potential chronic health effe Not available. General Carcinogenicity Mutagenicity	 Not available. Not available. Not available. Not available. Not available. ects Once sensitized, a severe allergic reaction may occur when subsequently expose to very low levels. No known significant effects or critical hazards. No known significant effects or critical hazards.

Acute toxicity estimates

For additional information call Akzo Nobel at (847) 625-4200 To request an updated SDS please visit http://www.formstack.com/forms/AkzoNobel-document_request_form

Page: 10/13

Section 11. Toxicological information

Route	ATE value	
Inhalation (gases) Inhalation (vapors) Inhalation (dusts and mists)	4506.8 ppm 11.02 mg/l 1.502 mg/l	

Section 12. Ecological information

Toxicity

Not available.

Persistence and degradability

Not available.

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
Hexamethylene diisocyanate, oligomers	5.54	367.7	low
hexamethylene-di-isocyanate	0.02	57.63	low

Mobility in soil

Soil/water partition : Not available. coefficient (Koc)

Other adverse eff	ects
-------------------	------

: No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods: The generation of waste should be avoided or minimized wherever possible.
Disposal of this product, solutions and any by-products should at all times comply
with the requirements of environmental protection and waste disposal legislation
and any regional local authority requirements. Dispose of surplus and non-
recyclable products via a licensed waste disposal contractor. Waste should not be
disposed of untreated to the sewer unless fully compliant with the requirements of
all authorities with jurisdiction. Waste packaging should be recycled. Incineration
or landfill should only be considered when recycling is not feasible. This material
and its container must be disposed of in a safe way. Care should be taken when
handling emptied containers that have not been cleaned or rinsed out. Empty
containers or liners may retain some product residues. Avoid dispersal of spilled
material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

Special precautions for user : The actual shipping description for this product may vary based several factors including, but not limited to, the volume of material, size of the container, mode of transport and use of exemptions or exceptions found in the applicable regulations. The information provided in Section 14 is one possible shipping description for this product. Consult your shipping specialist or supplier for appropriate assignment of the DOT information.

Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

	DOT Classification	TDG Classification	Mexico Classification	IMDG	ΙΑΤΑ
UN number	-	Not available.	Not available.	Not regulated.	Not regulated.
UN proper shipping name	NOT REGULATED	Not regulated.	Not regulated.	Not regulated.	Not regulated.
Transport hazard class(es)	-	Not regulated.	Not regulated.	Not regulated.	Not regulated.
Packing group	-	-	-	-	-
Environmental hazards	No.	No.	No.	No.	No.

Section 15. Regulatory information

U.S. Federal regulations	
United States inventory (TSCA 8b)	: All components are listed or exempted.

SARA 311/312

Classification

: Immediate (acute) health hazard

International lists National inventory	
Australia	: All components are listed or exempted.
Canada	: All components are listed or exempted.
China	: All components are listed or exempted.
Europe	: All components are listed or exempted.
Japan	: All components are listed or exempted.

For additional information call Akzo Nobel at (847) 625-4200

To request an updated SDS please visit http://www.formstack.com/forms/AkzoNobel-document_request_form


Page: 12/13

Section 15. Regulatory information

Malaysia	: All components are listed or exempted.
New Zealand	: All components are listed or exempted.
Philippines	: All components are listed or exempted.
Republic of Korea	: All components are listed or exempted.
Taiwan	: All components are listed or exempted.

Section 16. Other information

Hazardous Material Information System (U.S.A.)



Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks Although HMIS® ratings are not required on SDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material.

National Fire Protection Association (U.S.A.)



Reprinted with permission from NFPA 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

History

Date of issue/Date of revision	:	30 November 2015
Version	:	17.01
MSDS #	:	007899
		0007

To request an updated SDS please visit http://www.formstack.com/forms/AkzoNobel-document_request_form

Page: 13/13

Section 16. Other information

Key to abbreviations	 ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = Internediate Bulk Container IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL 73/78 = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
	UN = United Nations

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.