MATERIAL SAFETY DATA SHEET

MANUFACTURER'S NAME			
GRANITIZE AVIATION INT.			
STREET ADDRESS			
11022 VULC	AN STREET		
CITY, STATE AND ZIP CODE			
SOUTH GATE, CALI	FORNIA 90280-0893		
PHONE, FAX, e-MAIL			
562.923.5438 562-861-3475	info@granitizeaviation.com		
EMERGENCY PHONE NUMBER (24 Hours):			
Transportation Emergencies Call: CHEMTREC (800 Health Emergencies Call: Los Angeles P	0) 424-9300 International: 202-483-7616 oison Information Center (800) 876-4766		
PRODUCT: XMPRC-G, XMPRC-5, XMPRC-55	Caution: Harmful if swallowed. DO NOT induce vomiting. Contact a physician immediately. Avoid eye and prolonged skin contact KEEP AWAY FROM CHILDREN.		
CAS NUMBER: N/A	FOR INDUSTRIAL USE.		
DOT (Proper Shipping Name) ISOPROPANOL,3,UN1219, PGII	IMO/IMDG (PROPER SHIPPING NAME) ISOPROPANOL,3,UN1219, PGII		
HAZARD RATING NFPA 0-LEAST FIRE3 1-SLIGHT TOXICITY2_ 2-MODERATE REACTIVITY2	MARINE POLLUTANT: NO STOWAGE AND SEGREGATION: B		
3-HIGH SPECIA 4-EXTREME	EMERGENCY SCHEDULE F-E S-D		

SECTION I INGREDIENTS				
PRODUCT	CAS#	TLV		
Isopropanol	67-63-0	400ppm		
Ethylene Glycol M	Ionobutyl Ether 111-76-2	50ppm		
* Throshold Limit Value			_	

Threshold Limit Value

A, Osha [X] B, ACGII [] C, See Section III [] D, Other [] Cal Osha []

Section II EMERGENCY AND FIRST AID PROCEDURES			
Transportation	Emergencies Call: CHEMTREC (800) 424-9300	International: 202-483-7616	
Health	Emergencies Call: Los Angeles Poison Information	n Center (800) 876-4766	
EYE CONTACT	Gently flush with large quantities of water for at least 15 minutes. Seek medical attention immediately.		
SKIN CONTACT	Remove any contaminated clothing. Wash with soap Seek medical attention if irritated.	and large quantities of water.	
INHALATION	If breathing difficulties, dizziness, or light-headedness high vapor concentration, move to outside air immedia artificial respiration and seek immediate medical atten	ately. If breathing stops, begin	
INGESTION	If this product is swallowed, seek medical attention im vomiting unless directed by a physician.	mediately. <u>DO NOT</u> induce	

Section III PHYSIOLOGICAL EFFECTS AND HEALTH INFORMATION			
EYE EFFECTS	This product may be an eye irritant.		
SKIN EFFECTS	Prolonged skin contact may result in irritation and/or Dermatitis.		
SYSTEMIC EFFECTS	Various studies have shown a possible association with exposure to this product and the following:		

CARCINOGEN: NTP IARC MONOGRAPHS OSHA

NONE KNOWN

	SECTION IV SPECIAL PROTECTION INFORMATION
RESPIRATORY PROTECTION (Specify Type)	The use of respiratory protection depends on vapor concentration of the time- weighted TLV. Use a respirator/gas mask with appropriate cartridges and canister (NIOSH approved, if available), or supplied air equipment, depending on airborne concentration.
VENTILATION	If general mechanical ventilation proves inadequate to maintain safe vapor concentrations, supplemental local exhaust may be required. Other special precautions, such as respiratory protection, may be required if vapor concentrations cannot be reduced to below the TLV by ventilation.
EYE PROTECTION	Safety glasses and/or face shields are recommended.
PROTECTIVE GLOVES	The use of heavy rubber gloves is advised to prevent skin irritation and absorption.
OTHER PROTECTIVE EQUIPMENT	Impermeable aprons, availability of eye washes and safety washes are recommended.

SECTION V REACTIVITY DATA			
STABILITY	Stable		
Conditions to avoid:	NONE		
INCOMPATIBILITY (Materials to avoid)	NONE		
HAZARDOUS DECOMPOSITION PRODUCTS	Thermal decomposition in the presence of air may yield carbon monoxide and/or carbon dioxide.		
HAZARDOUS POLYMERIZATION	Will Not Occur		

SECTION VI SPILL OR LEAK PROCEDURES			
HIGHWAY OR RAILWAY SPILLS - CALL CHEMTREC (800) 424-9300			
PRECAUTIONS IN CASE OF RELEASE OR SPILL	Stay upwind and away from spill unless wearing appropriate protective equipment. Stop and/or contain spill if it can be done safely. Keep all sources of ignition away.		
WASTE DISPOSAL METHOD	Dispose of product in accordance with applicable local, county, state and Federal regulations.		

SECTION VII STORAGE AND SPECIAL PRECAUTIONS			
HANDLING AND STORING PRECAUTIONS	Keep product containers cool, dry and away from sources of ignition. Use and store with adequate ventilation.		
OTHER PRECAUTIONS	Personnel should avoid inhalation of vapors. Should contact be made, remove saturated clothing and flush with water.		

SECTION VIII FIRE AND EXPLOSION HAZARD DATA			
DOT FLAMMABILITY CLASSIFICATION	Flash Point: 55°F / 12.7°C		
EXTINGUISHING MEDIA	Use Foam, CO ₂ or dry chemical fire fighting apparatus.		
UNUSUAL FIRE & EXPLOSION HAZARDS	Keep work areas free of hot metal surfaces and other sources of ignition.		
HAZARDOUS POLYMERIZATION	The use of self-contained breathing apparatus is recommended for fire fighters. Avoid spreading burning liquid with water. Contact Fire Dept. immediately.		

SECTION IX PHYSICAL DATA			
BOILING POINT RANGE 180 °F / 82.2 °C			
Vapor Density: (AIR=1): 21	V.O.C. 390 gpl		
Vapor Pressure:6.05kPa @77F / 25C			
EVAPORATION RATE: N-BU ACETATE=1: 1.7	Percent Volatile: N/A	Solubility in water: COMPLETE	
SPECIFIC GRAVITY: Water=1: .786	Weight Per Gallon: .6.5 lbs		
APPEARANCE AND ODOR: Blue with an Isopropar	nol Aroma		

SECTION X .. DOCUMENTARY INFORMATION Product Code No Alcohol 30 / 55 Issue date JUNE- 2009 Prepared By: Marty Raymondo

All information appearing herein is based upon data obtained from the manufacturer and/or recognized technical sources. While the information is believed to be accurate, we make no representations as to its accuracy or sufficiency. Conditions of use are beyond our control and therefore users are responsible to verify this data under their own operating conditions to determine whether the product is suitable for their particular purposes and they assume all risks of their use, handling, and disposal of the product, or from the publication of use of, or reliance upon, information contained herein. This information relates only to the product designated herein, and does not relate to its use in combination with any other material or in any other process.