



SAFETY DATA SHEET

Issuing Date 22-Jul-2014

Revision Date 30-Mar-2016

Revision Number 1

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY/UNDERTAKING

GHS product identifier

Product Name Cross Check™ (All Colors)

Other means of identification

Part Number 83314 (Orange), 83315 (Green), 83316 (Red), 83317 (Yellow), 83318 (Blue), 83319 (White), 83320 (Pink), 83321 (Gray)

Formula Code A498M (Orange), A991M (Green), A992M (Red), A993M (Yellow), A994M (Blue), B095M (White), B100M (Pink), B101M (Gray)

UN-Number UN1993

Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use Inspection Paint

Uses advised against No information available

Supplier's details

Supplier Address
ITW PRO BRANDS
805 E. Old 56 Highway
Olathe, KS 66061
TEL: 1-800-443-9536

Emergency telephone number

Emergency Telephone Number 800-535-5053 Infotrac

2. HAZARDS IDENTIFICATION


Classification

This chemical is considered hazardous according to the OSHA Hazard Communication Standard 2012 (29 CFR 1910.1200).

Serious Eye Damage/Eye Irritation	Category 2A
Skin Sensitization	Category 1
Germ Cell Mutagenicity	Category 1B
Carcinogenicity	Category 1B
Reproductive Toxicity	Category 1B
Specific Target Organ Toxicity (Repeated Exposure)	Category 1

Aspiration Toxicity	Category 1
Flammable liquids	Category 3

GHS Label elements, including precautionary statements**Emergency Overview**

Signal Word	Danger
Hazard Statements	
<ul style="list-style-type: none"> • Causes serious eye irritation • May cause an allergic skin reaction • May cause genetic defects • May cause cancer • May damage fertility or the unborn child • Causes damage to organs through prolonged or repeated exposure • May be fatal if swallowed and enters airways • • Flammable liquid and vapor. 	
	
Appearance Opaque, Varies.	Physical State Viscous liquid.
	Odor Mild.

Precautionary Statements**Prevention**

- Obtain special instructions before use.
- Do not handle until all safety precautions have been read and understood.
- Use personal protective equipment as required.
- Wash face, hands and any exposed skin thoroughly after handling.
- Contaminated work clothing should not be allowed out of the workplace.
- Do not breathe dust/fume/gas/mist/vapors/spray.
- Do not eat, drink or smoke when using this product.
- Keep away from heat/sparks/open flames/hot surfaces - No smoking.
- Keep container tightly closed.
- Ground/bond container and receiving equipment.
- Use explosion-proof electrical/ventilating/lighting/equipment.
- Use only non-sparking tools.
- Take precautionary measures against static discharge.
- Wear protective gloves/protective clothing/eye protection/face protection.

General Advice

- If exposed or concerned: Get medical attention/advice
- Specific treatment (see supplemental first aid instructions on this label)

Eyes

- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- If eye irritation persists: Get medical advice/attention.

Skin

- If skin irritation or rash occurs: Get medical advice/attention.
- Wash contaminated clothing before reuse.
- IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

Ingestion

- IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
- Do NOT induce vomiting.

Fire

- In case of fire: Use CO₂, dry chemical, or foam for extinction.

Storage

- Store locked up.
- Store in a well-ventilated place. Keep cool.

Disposal

- Dispose of contents/container to an approved waste disposal plant.

Hazard Not Otherwise Classified (HNOC)

Not applicable.

Other information

Harmful to aquatic life with long lasting effects.

71.57% of the mixture consists of ingredient(s) of unknown toxicity.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS-No	Weight %	Trade secret
Solvent naphtha (petroleum), medium aliphatic	64742-88-7	30-60	*
Titanium dioxide	13463-67-7	10-30	*
Manganese	7439-96-5	5-10	*
Ci 15865	5280-66-0	5-10	*
Silicon dioxide	7631-86-9	1-5	*
Petroleum distillates, hydrotreated light	64742-47-8	1-5	*
Aluminum hydroxide	21645-51-2	1-5	*
Methyl ethyl ketoxime	96-29-7	1-5	*
Kaolin	1332-58-7	1-5	*
Diacetone alcohol	123-42-2	1-5	*
Ethylbenzene	100-41-4	0.1-1	*
Carbon black	1333-86-4	0.1-1	*
Methyl-2-benzimidazole carbamate	10605-21-7	0.1-1	*
Stoddard solvent	8052-41-3	0.1-1	*

**The exact percentage (concentration) of composition has been withheld as a trade secret.*

4. FIRST AID MEASURES

Description of necessary first-aid measures**General Advice**

Immediate medical attention is required. Show this safety data sheet to the doctor in attendance.

Eye Contact

Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Keep eye wide open while rinsing. If symptoms persist, call a physician.

Skin Contact

Wash off immediately with soap and plenty of water removing all contaminated clothes and shoes. In the case of skin irritation or allergic reactions see a physician.

Inhalation

Move to fresh air. If symptoms persist, call a physician.

Ingestion Do NOT induce vomiting. Drink plenty of water. Rinse mouth. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician. Aspiration hazard if swallowed - can enter lungs and cause damage.

Protection of First-aiders Remove all sources of ignition.

Most important symptoms/effects, acute and delayed

Most Important Symptoms/Effects May cause allergic skin reaction. Eye irritation/reactions. Aspiration into lungs can produce severe lung damage.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to Physician May cause sensitization of susceptible persons. Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Water fog. Foam. Dry chemical. Carbon dioxide (CO₂).

Unsuitable Extinguishing Media No information available.

Specific Hazards Arising from the Chemical

Vapors may travel to source of ignition and flash back. Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks).

Explosion Data

Sensitivity to Mechanical Impact

None.

Sensitivity to Static Discharge

Yes.

Protective Equipment and Precautions for Firefighters

Cool closed containers exposed to fire with water spray. As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions Remove all sources of ignition. Take precautionary measures against static discharges. Evacuate personnel to safe areas. Ensure adequate ventilation. Use personal protective equipment. Stop leak if you can do it without risk.

Environmental Precautions

Environmental Precautions Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. Do not flush into surface water or sanitary sewer system. See Section 12 for additional Ecological Information.

Methods and materials for containment and cleaning up

Methods for Containment Prevent further leakage or spillage if safe to do so.

Methods for Cleaning Up Small spillage: Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Large spillage: Pump or vacuum transfer spilled product to clean containers for recovery. Absorb unrecoverable product.

7. HANDLING AND STORAGE

Precautions for safe handling

Handling Ensure adequate ventilation. Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharges. Use only in an area containing flame proof equipment. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Avoid contact with skin, eyes and clothing. Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers. Ground and bond all lines and equipment associated with product system. All equipment should be non-sparking and explosion proof.

Conditions for safe storage, including any incompatibilities

Storage Keep away from open flames, hot surfaces and sources of ignition. Keep away from incompatible materials. Keep containers tightly closed in a cool, well-ventilated place. Keep out of the reach of children. Keep container closed when not in use.

Incompatible Products Strong oxidizing agents. Strong acids. Strong reducing agents. Strong alkalis.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Titanium dioxide 13463-67-7	TWA: 10 mg/m ³	TWA: 15 mg/m ³ total dust (vacated) TWA: 10 mg/m ³ total dust	IDLH: 5000 mg/m ³
Ci 15865 5280-66-0	-	(vacated) Ceiling: 5 mg/m ³ Ceiling: 5 mg/m ³ Mn	IDLH: 500 mg/m ³ Mn TWA: 1 mg/m ³ Mn STEL: 3 mg/m ³ Mn
Manganese 7439-96-5	TWA: 0.2 mg/m ³	(vacated) TWA: 1 mg/m ³ fume (vacated) STEL: 3 mg/m ³ fume (vacated) Ceiling: 5 mg/m ³ Ceiling: 5 mg/m ³ fume	IDLH: 500 mg/m ³ TWA: 1 mg/m ³ fume STEL: 3 mg/m ³
Petroleum distillates, hydrotreated light 64742-47-8	TWA: 5 mg/m ³ STEL: 10 mg/m ³ (as oil mist)	TWA: 5 mg/m ³ (as oil mist)	-
Aluminum hydroxide 21645-51-2	TWA: 1 mg/m ³ respirable fraction	-	-
Kaolin 1332-58-7	-	TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction (vacated) TWA: 10 mg/m ³ total dust (vacated) TWA: 5 mg/m ³ respirable fraction	TWA: 10 mg/m ³ total dust TWA: 5 mg/m ³ respirable dust
Diacetone alcohol 123-42-2	TWA: 50 ppm	TWA: 50 ppm TWA: 240 mg/m ³ (vacated) TWA: 50 ppm (vacated) TWA: 240 mg/m ³	IDLH: 1800 ppm TWA: 50 ppm TWA: 240 mg/m ³
Ethylbenzene 100-41-4	TWA: 20 ppm	TWA: 100 ppm TWA: 435 mg/m ³ (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m ³ (vacated) STEL: 150 ppm (vacated) STEL: 655 mg/m ³	IDLH: 800 ppm TWA: 100 ppm TWA: 435 mg/m ³ STEL: 125 ppm STEL: 545 mg/m ³
Stoddard solvent 8052-41-3	TWA: 100 ppm	TWA: 500 ppm TWA: 2900 mg/m ³ (vacated) TWA: 100 ppm (vacated) TWA: 525 mg/m ³	IDLH: 20000 mg/m ³ Ceiling: 1800 mg/m ³ 15 min TWA: 350 mg/m ³

Immediately Dangerous to Life or Health. ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value. OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits. NIOSH IDLH:

Other Exposure Guidelines Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

Appropriate engineering controls

Engineering Measures
Showers
Eyewash stations
Ventilation systems

Individual protection measures, such as personal protective equipment

Eye/Face Protection Goggles.
Skin and Body Protection Chemical resistant gloves. Risk of contact: Apron. Boots.
Respiratory Protection No special protective equipment required. If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn.

Hygiene Measures When using, do not eat, drink or smoke. Provide regular cleaning of equipment, work area and clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical State	Viscous liquid.	Appearance	Opaque, Varies.
Odor	Mild.	Odor Threshold	No information available.

<u>Property</u>	<u>Values</u>	<u>Remarks/ - Method</u>
pH	No data available	None known
Melting Point/Range	No data available	None known
Boiling Point/Boiling Range	136.1-251.7 °C / 277- 485 °F	None known
Flash Point	40.6 °C / 105 °F	None known
Evaporation rate	< 1 (BuAc = 1)	None known
Flammability (solid, gas)	No data available	None known
Flammability Limits in Air		
upper flammability limit	7.0	
lower flammability limit	1.10	
Vapor Pressure	No data available	None known
Vapor Density	> 1 (air = 1)	None known
Specific Gravity	No data available	None known
Water Solubility	Negligible	None known
Solubility in other solvents	No data available	None known
Partition coefficient: n-octanol/water	No data available	None known
Autoignition Temperature	No data available	None known
Decomposition Temperature	No data available	None known
Viscosity	No data available	None known

Flammable Properties Flammable; may be ignited by heat, sparks or flames.

Explosive Properties No data available

Oxidizing Properties No data available

Other information

VOC Content (%)	A498M Orange: 42.28% A991M Green: 38.74% A992M Red: 39.94% A993M Yellow: 40.08% A994M Blue: 37.62% B095M White: 30.83% B100M Pink: 30.83% B101M Gray: 30.83%
VOC (g/l)	A498M Orange: 430 g/L A991M Green: 377 g/L A992M Red: 385 g/L A993M Yellow: 374 g/L A994M Blue: 364 g/L B095M White: 384 g/L B100M Pink: 384 g/L B101M Gray: 384 g/L

10. STABILITY AND REACTIVITY

Reactivity

No data available.

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

None under normal processing.

Hazardous Polymerization

Hazardous polymerization does not occur.

Conditions to avoid

Heat, flames and sparks. Incompatible products.

Incompatible materials

Strong oxidizing agents. Strong acids. Strong reducing agents. Strong alkalis.

Hazardous decomposition products

Carbon oxides. Smoke Soot.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Inhalation

Inhalation of vapors in high concentration may cause irritation of respiratory system.

Eye Contact

Causes serious eye irritation.

Skin Contact

May cause irritation. May cause allergic skin reaction

Ingestion

Ingestion may cause nausea and vomiting. Potential for aspiration if swallowed. Aspiration may cause pulmonary edema and pneumonitis.

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Solvent naphtha (petroleum), medium aliphatic	> 5000 mg/kg (Rat)	= 3000 mg/kg (Rabbit)	> 5.28 mg/L (Rat) 4 h
Titanium dioxide	> 10000 mg/kg (Rat)	-	-
Manganese	= 9 g/kg (Rat)	-	-
Silicon dioxide	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	>2.2 mg/L (Rat) 4 h
Petroleum distillates, hydrotreated light	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 5.2 mg/L (Rat) 4 h
Propylene glycol monomethyl ether acetate	= 8532 mg/kg (Rat)	> 5000 mg/kg (Rabbit)	5321 mg/m ³
Aluminum hydroxide	> 5000 mg/kg (Rat)	-	-
Methyl ethyl ketoxime	= 930 mg/kg (Rat)	= 0.2 mg/kg (Rabbit)	= 20 mg/L (Rat) 4 h
Diacetone alcohol	= 4 g/kg (Rat)	= 13500 mg/kg (Rabbit)	-
Ethylbenzene	= 3500 mg/kg (Rat)	= 15400 mg/kg (Rabbit)	= 17.2 mg/L (Rat) 4 h
Methyl-2-benzimidazole carbamate	= 6400 mg/kg (Rat)	= 8500 mg/kg (Rabbit) = 2 g/kg (Rat)	-

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms

No information available.

Delayed and immediate effects and also chronic effects from short and long term exposure

Sensitization May cause sensitization of susceptible persons. May cause sensitization by skin contact.
Mutagenic Effects Contains a known or suspected mutagen. May cause genetic defects.
Carcinogenicity Contains a known or suspected carcinogen. May cause cancer. The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
Titanium dioxide		Group 2B	-	-
Silicon dioxide		Group 3		
Ethylbenzene	A3	Group 2B	-	-
Carbon black	A3	Group 2B	-	X

ACGIH: (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC: (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans

OSHA: (Occupational Safety & Health Administration)

X - Present

Reproductive Toxicity Contains a known or suspected reproductive toxin. May damage fertility or the unborn child
STOT - single exposure No information available.
STOT - repeated exposure Causes damage to organs through prolonged or repeated exposure.
Chronic Toxicity Avoid repeated exposure. Repeated contact may cause allergic reactions in very susceptible persons. Ethylbenzene has been classified by the International Agency for Research on Cancer (IARC) as possibly carcinogenic to humans (Group 2B). Prolonged or repeated overexposure to ethylbenzene may result in adverse effects to the kidneys, liver, respiratory system, thyroid, testicles, and pituitary glands. May cause adverse liver effects. Liver. Kidney. Respiratory system. Eyes. Skin. Central nervous system (CNS).
Target Organ Effects Liver. Kidney. Respiratory system. Eyes. Skin. Central nervous system (CNS).
Aspiration Hazard May be fatal if swallowed and enters airways.

Numerical measures of toxicity - Product**Acute Toxicity** 71.57% of the mixture consists of ingredient(s) of unknown toxicity.*The following values are calculated based on chapter 3.1 of the GHS document:***LD50 Oral** 7269 mg/kg; Acute toxicity estimate**LD50 Dermal** 5845 mg/kg; Acute toxicity estimate**Inhalation****dust/mist** 678 mg/L; Acute toxicity estimate mg/L**12. ECOLOGICAL INFORMATION**

This product contains a chemical which is listed as a marine pollutant according to DOT.

Ecotoxicity

Harmful to aquatic life with long lasting effects.

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Solvent naphtha (petroleum), medium aliphatic 64742-88-7	EC50 96 h: = 450 mg/L (Pseudokirchneriella subcapitata)	LC50 96 h: = 800 mg/L static (Pimephales promelas)		EC50 48 h: > 100 mg/L (Daphnia magna)
Silicon dioxide 7631-86-9	EC50 72 h: = 440 mg/L (Pseudokirchneriella subcapitata)	LC50 96 h: = 5000 mg/L static (Brachydanio rerio)		EC50 48 h: = 7600 mg/L (Ceriodaphnia dubia)
Petroleum distillates, hydrotreated light 64742-47-8		LC50 96 h: = 45 mg/L flow-through (Pimephales promelas) LC50 96 h: = 2.2 mg/L static (Lepomis macrochirus) LC50 96 h: = 2.4 mg/L static (Oncorhynchus mykiss)		LC50 96 h: = 4720 mg/L (Den-dronereides heteropoda)

Propylene glycol monomethyl ether acetate 108-65-6		LC50 96 h: = 161 mg/L static (Pimephales promelas)		EC50 48 h: > 500 mg/L (Daphnia magna)
Methyl ethyl ketoxime 96-29-7	EC50 72 h: = 83 mg/L (Desmodesmus subspicatus)	LC50 96 h: 777 - 914 mg/L flow-through (Pimephales promelas) LC50 96 h: = 760 mg/L static (Poecilia reticulata) LC50 96 h: 320 - 1000 mg/L static (Leuciscus idus)	EC50 = 281 mg/L 17 h EC50 = 950 mg/L 5 min	EC50 48 h: = 750 mg/L (Daphnia magna)
Diacetone alcohol 123-42-2		LC50 96 h: = 420 mg/L static (Lepomis macrochirus) LC50 96 h: = 420 mg/L (Lepomis macrochirus)		EC50 24 h: = 8750 mg/L (Daphnia magna)
Ethylbenzene 100-41-4	EC50 72 h: = 4.6 mg/L (Pseudokirchneriella subcapitata) EC50 96 h: > 438 mg/L (Pseudokirchneriella subcapitata) EC50 72 h: 2.6 - 11.3 mg/L static (Pseudokirchneriella subcapitata) EC50 96 h: 1.7 - 7.6 mg/L static (Pseudokirchneriella subcapitata) EC50 72 h: = 11 mg/L (Pseudokirchneriella subcapitata)	LC50 96 h: 11.0 - 18.0 mg/L static (Oncorhynchus mykiss) LC50 96 h: = 4.2 mg/L semi-static (Oncorhynchus mykiss) LC50 96 h: 7.55 - 11 mg/L flow-through (Pimephales promelas) LC50 96 h: = 32 mg/L static (Lepomis macrochirus) LC50 96 h: 9.1 - 15.6 mg/L static (Pimephales promelas) LC50 96 h: = 9.6 mg/L static (Poecilia reticulata)	EC50 = 9.68 mg/L 30 min EC50 = 96 mg/L 24 h	EC50 48 h: 1.8 - 2.4 mg/L (Daphnia magna)

Persistence and Degradability No information available.

Bioaccumulation

Chemical Name	Log Pow
Methyl ethyl ketoxime	0.65
Diacetone alcohol	1.03
Ethylbenzene	3.118

Other Adverse Effects

No information available.

13. DISPOSAL CONSIDERATIONS

Waste Disposal Methods Dispose of in accordance with federal, state, and local regulations

Contaminated Packaging Do not re-use empty containers.

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Ethylbenzene - 100-41-4		Included in waste stream: F039		
Methyl-2-benzimidazole carbamate - 10605-21-7	U372	Included in waste streams: K156, K158		U372

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste
Manganese	Ignitable powder
Ethylbenzene	Toxic Ignitable

14. TRANSPORT INFORMATION

DOT

UN-Number UN1993
Proper shipping name Flammable liquids, n.o.s.
Hazard Class 3
Packing Group III

Marine Pollutant Description	This product contains a chemical which is listed as a marine pollutant according to DOT. UN1993, Flammable liquids, n.o.s. (Solvent naphtha (petroleum), medium aliphatic, Petroleum distillates, hydrotreated light), 3, III
Emergency Response Guide Number	128

TDG

UN-Number	UN1993
Proper Shipping Name	Flammable liquid, n.o.s.
Hazard Class	3
Packing Group	III
Description	UN1993, Flammable liquid, n.o.s. (Solvent naphtha (petroleum), medium aliphatic, Petroleum distillates, hydrotreated light), 3, III

MEX

UN-Number	UN1993
Proper Shipping Name	Flammable liquid, n.o.s.
Hazard Class	3
Packing Group	III
Description	UN1993, Flammable liquid, n.o.s. (Solvent naphtha (petroleum), medium aliphatic, Petroleum distillates, hydrotreated light), 3, III

ICAO

UN-Number	UN1993
Proper shipping name	Flammable liquid, n.o.s.
Hazard Class	3
Packing Group	III
Description	UN1993, Flammable liquid, n.o.s. (Solvent naphtha (petroleum), medium aliphatic, Petroleum distillates, hydrotreated light), 3, III

IATA

UN-Number	UN1993
Proper Shipping Name	Flammable liquid, n.o.s.
Hazard Class	3
Packing Group	III
ERG Code	3L
Description	UN1993, Flammable liquid, n.o.s. (Solvent naphtha (petroleum), medium aliphatic, Petroleum distillates, hydrotreated light), 3, III

IMDG/IMO

UN-Number	UN1993
Proper Shipping Name	Flammable liquid, n.o.s.
Hazard Class	3
Packing Group	III
EmS No.	F-E, S-E
Description	UN1993, Flammable liquid, n.o.s. (Solvent naphtha (petroleum), medium aliphatic, Petroleum distillates, hydrotreated light), 3, III, (40.6°C c.c.)

RID

UN-Number	UN1993
Proper Shipping Name	Flammable liquid, n.o.s.
Hazard Class	3
Packing Group	III
Classification Code	F1
Description	UN1993, Flammable liquid, n.o.s. (Solvent naphtha (petroleum), medium aliphatic, Petroleum distillates, hydrotreated light), 3, III

ADR

UN-Number	UN1993
Proper Shipping Name	Flammable liquid, n.o.s.
Hazard Class	3
Packing Group	III
Classification Code	F1
Tunnel Restriction Code	(D/E)

Description UN1993, Flammable liquid, n.o.s. (Solvent naphtha (petroleum), medium aliphatic, Petroleum distillates, hydrotreated light), 3, III, (D/E)

ADN

Proper Shipping Name Flammable liquid, n.o.s.
Hazard Class 3
Packing Group III
Classification Code F1
Special Provisions 274, 601, 640E
Description UN1993, Flammable liquid, n.o.s. (Solvent naphtha (petroleum), medium aliphatic, Petroleum distillates, hydrotreated light), 3, III
Limited Quantity 5 L
Ventilation VE01

15. REGULATORY INFORMATION

International Inventories

TSCA Complies
DSL Not determined

Legend

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

U.S. Federal Regulations

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

Chemical Name	CAS-No	Weight %	SARA 313 - Threshold Values %
Ci 15865	5280-66-0	0-10	1.0
Manganese	7439-96-5	0-10	1.0
Ethylbenzene	100-41-4	< 1	0.1

SARA 311/312 Hazard Categories

Acute Health Hazard Yes
Chronic Health Hazard Yes
Fire Hazard Yes
Sudden Release of Pressure Hazard No
Reactive Hazard No

Clean Water Act

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42):

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Ethylbenzene	1000 lb	X	X	X

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302):

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
Ethylbenzene	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ
Methyl-2-benzimidazole carbamate	10 lb		RQ 10 lb final RQ RQ 4.54 kg final RQ

U.S. State Regulations**California Proposition 65**

This product contains the following Proposition 65 chemicals:

Chemical Name	CAS-No	California Prop. 65
Titanium dioxide	13463-67-7	Carcinogen

Ethylbenzene	100-41-4	Carcinogen
Carbon black	1333-86-4	Carcinogen
Formaldehyde	50-00-0	Carcinogen
Toluene	108-88-3	Developmental
Cumene	98-82-8	Carcinogen
2-Ethylhexanoic acid	149-57-5	Developmental
Quartz	14808-60-7	Carcinogen

U.S. State Right-to-Know Regulations

"X" designates that the ingredients are listed on the state right to know list.

Chemical Name	New Jersey	Massachusetts	Pennsylvania	Illinois	Rhode Island
Solvent naphtha (petroleum), medium aliphatic	X				
Titanium dioxide		X			X
Ci 15865			X	X	
Manganese	X	X	X	X	X
Silicon dioxide	X	X	X		

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

16. OTHER INFORMATION

NFPA	Health Hazard 2	Flammability 2	Instability 0	Physical and Chemical Hazards - Personal Protection X
HMIS	Health Hazard 2*	Flammability 2	Physical Hazard 0	

*Indicates a chronic health hazard.

Prepared By Product Stewardship
23 British American Blvd.
Latham, NY 12110
1-800-572-6501

Issuing Date 22-Jul-2014
Revision Date 30-Mar-2016
Revision Note Change to composition.

General Disclaimer

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

End of Safety Data Sheet