

**DOW CORNING(R) Q4-2805 FLUOROSILICONE
CHANNEL SEALANT**

Version 4.0 Revision Date: 09/22/2015 SDS Number: 656907-00005 Date of last issue: 05/06/2015
Date of first issue: 10/22/2014

SECTION 1. IDENTIFICATION

Product name : DOW CORNING(R) Q4-2805 FLUOROSILICONE CHANNEL SEALANT

Product code : 000000000001705652

Manufacturer or supplier's details

Company name of supplier : Dow Corning Corporation

Address : South Saginaw Road
Midland Michigan 48686

Telephone : (989) 496-6000

Emergency telephone : 24 Hour Emergency Telephone : (989) 496-5900
CHEMTREC : (800) 424-9300

Recommended use of the chemical and restrictions on use

Recommended use : Construction materials and additives

SECTION 2. HAZARDS IDENTIFICATION**GHS Classification**

Carcinogenicity : Category 2

Reproductive toxicity : Category 2

GHS Label element

Hazard pictograms :



Signal Word : Warning

Hazard Statements : H351 Suspected of causing cancer.
H361 Suspected of damaging fertility or the unborn child.

Precautionary Statements : **Prevention:**
P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
Response:
P308 + P313 IF exposed or concerned: Get medical advice/ attention.

**DOW CORNING(R) Q4-2805 FLUOROSILICONE
CHANNEL SEALANT**

Version 4.0	Revision Date: 09/22/2015	SDS Number: 656907-00005	Date of last issue: 05/06/2015 Date of first issue: 10/22/2014
----------------	------------------------------	-----------------------------	---

P370 + P261 In case of fire: Avoid breathing fume.

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture
Chemical nature : Fluorosilicone

Hazardous ingredients

Chemical name	CAS-No.	Concentration (% w/w)
Hexamethyldisilazane reaction with Silica	68909-20-6	>= 5 - < 10
Titanium dioxide	13463-67-7	>= 0.1 - < 1
Styrene	100-42-5	>= 0.1 - < 1

SECTION 4. FIRST AID MEASURES

General advice	:	In the case of accident or if you feel unwell, seek medical advice immediately. When symptoms persist or in all cases of doubt seek medical advice.
If inhaled	:	If inhaled, remove to fresh air. Get medical attention.
In case of skin contact	:	In case of contact, immediately flush skin with soap and plenty of water. Remove contaminated clothing and shoes. Get medical attention. Wash clothing before reuse. Thoroughly clean shoes before reuse.
In case of eye contact	:	Flush eyes with water as a precaution. Get medical attention if irritation develops and persists.
If swallowed	:	If swallowed, DO NOT induce vomiting. Get medical attention. Rinse mouth thoroughly with water.
Most important symptoms and effects, both acute and delayed	:	Suspected of causing cancer. Suspected of damaging fertility or the unborn child.

**DOW CORNING(R) Q4-2805 FLUOROSILICONE
CHANNEL SEALANT**

Version 4.0	Revision Date: 09/22/2015	SDS Number: 656907-00005	Date of last issue: 05/06/2015 Date of first issue: 10/22/2014
----------------	------------------------------	-----------------------------	---

Protection of first-aiders	: First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists.
Notes to physician	: Treat symptomatically and supportively.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media	: Water spray Alcohol-resistant foam Carbon dioxide (CO ₂) Dry chemical
Unsuitable extinguishing media	: None known.
Specific hazards during fire fighting	: Very toxic vapors are evolved. Exposure to combustion products may be a hazard to health.
Hazardous combustion products	: Carbon oxides Silicon oxides Fluorine compounds Formaldehyde Nitrogen oxides (NO _x)
Specific extinguishing methods	: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Use water spray to cool unopened containers. Remove undamaged containers from fire area if it is safe to do so. Evacuate area.
Special protective equipment for fire-fighters	: In the event of fire, wear self-contained breathing apparatus. Wear self-contained breathing apparatus for firefighting if necessary. Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	: Use personal protective equipment. Follow safe handling advice and personal protective equipment recommendations.
Environmental precautions	: Discharge into the environment must be avoided. Prevent further leakage or spillage if safe to do so. Retain and dispose of contaminated wash water. Local authorities should be advised if significant spillages cannot be contained.
Methods and materials for containment and cleaning up	: Soak up with inert absorbent material. For large spills, provide diking or other appropriate contain-

**DOW CORNING(R) Q4-2805 FLUOROSILICONE
CHANNEL SEALANT**

Version 4.0	Revision Date: 09/22/2015	SDS Number: 656907-00005	Date of last issue: 05/06/2015 Date of first issue: 10/22/2014
----------------	------------------------------	-----------------------------	---

ment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container. Clean up remaining materials from spill with suitable absorbent.

Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.

Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

SECTION 7. HANDLING AND STORAGE

- Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.
- Local/Total ventilation : Use only with adequate ventilation.
- Advice on safe handling : Do not swallow.
Avoid contact with eyes.
Avoid prolonged or repeated contact with skin.
Handle in accordance with good industrial hygiene and safety practice.
Take care to prevent spills, waste and minimize release to the environment.
- Conditions for safe storage : Keep in properly labeled containers.
Store in accordance with the particular national regulations.
- Materials to avoid : Do not store with the following product types:
Strong oxidizing agents

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**Ingredients with workplace control parameters**

Ingredients	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Hexamethyldisilazane reaction with Silica	68909-20-6	TWA (Dust)	20 Million particles per cubic foot (Silica)	OSHA Z-3
		TWA (Dust)	80 mg/m ³ / %SiO ₂ (Silica)	OSHA Z-3
Titanium dioxide	13463-67-7	TWA (total dust)	15 mg/m ³	OSHA Z-1
		TWA	10 mg/m ³ (Titanium dioxide)	ACGIH
Styrene	100-42-5	TWA	50 ppm 215 mg/m ³	NIOSH REL

DOW CORNING(R) Q4-2805 FLUOROSILICONE CHANNEL SEALANT

Version 4.0 Revision Date: 09/22/2015 SDS Number: 656907-00005 Date of last issue: 05/06/2015
 Date of first issue: 10/22/2014

		ST	100 ppm 425 mg/m ³	NIOSH REL
		TWA	100 ppm	OSHA Z-2
		CEIL	200 ppm	OSHA Z-2
		Peak	600 ppm (5 mins. in any 3 hrs.)	OSHA Z-2
		TWA	20 ppm	ACGIH
		STEL	40 ppm	ACGIH
Trifluoropropylmethyl cyclotrisiloxane	2374-14-3	TWA	5 ppb	DCC OEL
Further information: Skin				

Biological occupational exposure limits

Ingredients	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
Styrene	100-42-5	Mandelic acid plus phenylglyoxylic acid	Urine	End of shift (As soon as possible after exposure ceases)	400 mg/g Creatinine	ACGIH BEI
		Styrene	In venous blood	End of shift (As soon as possible after exposure ceases)	0.2 mg/l	ACGIH BEI

Engineering measures : Processing may form hazardous compounds (see section 10).
 Ensure adequate ventilation, especially in confined areas.
 Minimize workplace exposure concentrations.
 Dust formation may be relevant in the processing of this product. In addition to substance-specific OELs, general limitations of concentrations of particulates in the air at workplaces have to be considered in workplace risk assessment. Relevant limits include: OSHA PEL for Particulates Not Otherwise Regulated of 15 mg/m³ - total dust, 5 mg/m³ - respirable fraction; and ACGIH TWA for Particles (insoluble or poorly soluble) Not Otherwise Specified of 3 mg/m³ - respirable particles, 10 mg/m³ - inhalable particles.

Personal protective equipment

Respiratory protection : No personal respiratory protective equipment normally required.

Hand protection

II Material : Impervious gloves

**DOW CORNING(R) Q4-2805 FLUOROSILICONE
CHANNEL SEALANT**

Version	Revision Date:	SDS Number:	Date of last issue: 05/06/2015
4.0	09/22/2015	656907-00005	Date of first issue: 10/22/2014

Remarks	: Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. Breakthrough time is not determined for the product. Change gloves often! For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.
Eye protection	: Wear the following personal protective equipment: Safety glasses
Skin and body protection	: Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential. Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).
Hygiene measures	: Ensure that eye flushing systems and safety showers are located close to the working place. When using do not eat, drink or smoke. Wash contaminated clothing before re-use. These precautions are for room temperature handling. Use at elevated temperature or aerosol/spray applications may require added precautions.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: paste
Color	: white
Odor	: slight
Odor Threshold	: No data available
pH	: Not applicable
Melting point/freezing point	: No data available
Initial boiling point and boiling range	: Not applicable
Flash point	: 100 °C Method: closed cup
Evaporation rate	: Not applicable
Flammability (solid, gas)	: Not classified as a flammability hazard
Upper explosion limit	: No data available

**DOW CORNING(R) Q4-2805 FLUOROSILICONE
CHANNEL SEALANT**

Version	Revision Date:	SDS Number:	Date of last issue: 05/06/2015
4.0	09/22/2015	656907-00005	Date of first issue: 10/22/2014

Lower explosion limit	: No data available
Vapor pressure	: Not applicable
Relative vapor density	: No data available
Relative density	: 1.36
Solubility(ies)	
Water solubility	: No data available
Partition coefficient: n-octanol/water	: No data available
Autoignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity	
Viscosity, dynamic	: Not applicable
Explosive properties	: Not explosive
Oxidizing properties	: The substance or mixture is not classified as oxidizing.
Molecular weight	: No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: Not classified as a reactivity hazard.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: Use at elevated temperatures may form highly hazardous compounds. Can react with strong oxidizing agents. When heated to temperatures above 180 °C (356 °F) in the presence of air, trace quantities of formaldehyde may be released. Adequate ventilation is required. See OSHA formaldehyde standard, 29 CFR 1910.1048 Hazardous decomposition products will be formed at elevated temperatures.
Conditions to avoid	: None known.
Incompatible materials	: Oxidizing agents
Hazardous decomposition products	
Thermal decomposition	: Formaldehyde Trifluoropropionaldehyde Hydrogen fluoride

**DOW CORNING(R) Q4-2805 FLUOROSILICONE
CHANNEL SEALANT**

Version 4.0 Revision Date: 09/22/2015 SDS Number: 656907-00005 Date of last issue: 05/06/2015
Date of first issue: 10/22/2014

SECTION 11. TOXICOLOGICAL INFORMATION**Information on likely routes of exposure**

Skin contact
Ingestion
Eye contact

Acute toxicity

Not classified based on available information.

Ingredients:**Hexamethyldisilazane reaction with Silica:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Assessment: The substance or mixture has no acute oral toxicity
Remarks: Based on data from similar materials

Titanium dioxide:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Acute inhalation toxicity : LC50 (Rat): > 6.82 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Assessment: The substance or mixture has no acute inhalation toxicity

Styrene:

Acute oral toxicity : LD50 (Hamster): > 5,000 mg/kg
Acute inhalation toxicity : LC50 (Rat): 11.8 mg/l
Exposure time: 4 h
Test atmosphere: vapor
Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity

Skin corrosion/irritation

Not classified based on available information.

Ingredients:**Hexamethyldisilazane reaction with Silica:**

Assessment: Repeated exposure may cause skin dryness or cracking.

Titanium dioxide:

Species: Rabbit
Result: No skin irritation

Styrene:

Species: Rabbit

**DOW CORNING(R) Q4-2805 FLUOROSILICONE
CHANNEL SEALANT**

Version 4.0 Revision Date: 09/22/2015 SDS Number: 656907-00005 Date of last issue: 05/06/2015
Date of first issue: 10/22/2014

Result: Skin irritation

Serious eye damage/eye irritation

Not classified based on available information.

Ingredients:**Hexamethyldisilazane reaction with Silica:**

Species: Rabbit

Result: No eye irritation

Remarks: Based on data from similar materials

Titanium dioxide:

Species: Rabbit

Result: No eye irritation

Styrene:

Species: Rabbit

Result: Irritation to eyes, reversing within 21 days

Respiratory or skin sensitization

Skin sensitization: Not classified based on available information.

Respiratory sensitization: Not classified based on available information.

Ingredients:**Titanium dioxide:**

Test Type: Local lymph node assay (LLNA)

Routes of exposure: Skin contact

Species: Mouse

Result: negative

Germ cell mutagenicity

Not classified based on available information.

Ingredients:**Hexamethyldisilazane reaction with Silica:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

Remarks: Based on data from similar materials

Titanium dioxide:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

Genotoxicity in vivo : Test Type: In vivo micronucleus test

Species: Mouse

Result: negative

Styrene:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo)

**DOW CORNING(R) Q4-2805 FLUOROSILICONE
CHANNEL SEALANT**

Version 4.0	Revision Date: 09/22/2015	SDS Number: 656907-00005	Date of last issue: 05/06/2015 Date of first issue: 10/22/2014
----------------	------------------------------	-----------------------------	---

cytogenetic assay)
Species: Mouse
Application Route: inhalation (vapor)
Method: OECD Test Guideline 474
Result: negative

Carcinogenicity

Suspected of causing cancer.

Ingredients:**Titanium dioxide:**

Species: Rat
Application Route: inhalation (dust/mist/fume)
Exposure time: 24 Months
Method: OECD Test Guideline 453
Result: positive
Remarks: The mechanism or mode of action may not be relevant in humans.
The substance is inextricably bound in the product and therefore does not contribute to a dust inhalation hazard.

Carcinogenicity - Assessment : Limited evidence of carcinogenicity in inhalation studies with animals.

Styrene:

Species: Rat
Application Route: inhalation (vapor)
Exposure time: 104 weeks
Result: positive
Remarks: The mechanism or mode of action may not be relevant in humans.

Carcinogenicity - Assessment : Limited evidence of carcinogenicity in animal studies

IARC

Group 2B: Possibly carcinogenic to humans

Titanium dioxide 13463-67-7

Styrene 100-42-5

OSHA

No ingredient of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

NTP

Reasonably anticipated to be a human carcinogen

Styrene 100-42-5

Reproductive toxicity

Suspected of damaging fertility or the unborn child.

Ingredients:**Styrene:**

Effects on fertility : Test Type: Three-generation reproduction toxicity study

**DOW CORNING(R) Q4-2805 FLUOROSILICONE
CHANNEL SEALANT**

Version	Revision Date:	SDS Number:	Date of last issue: 05/06/2015
4.0	09/22/2015	656907-00005	Date of first issue: 10/22/2014

Species: Rat
Application Route: Ingestion
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: inhalation (vapor)
Result: positive

Reproductive toxicity - Assessment : Some evidence of adverse effects on development, based on animal experiments.

STOT-single exposure

Not classified based on available information.

Ingredients:**Styrene:**

Assessment: May cause respiratory irritation.

STOT-repeated exposure

Not classified based on available information.

Ingredients:**Styrene:**

Target Organs: hearing organs
Assessment: Causes damage to organs through prolonged or repeated exposure.

Repeated dose toxicity**Ingredients:****Titanium dioxide:**

Species: Rat
NOAEL: 24,000 mg/kg
Application Route: Ingestion
Exposure time: 28 d

Species: Rat
NOAEL: 10 mg/m³
Application Route: inhalation (dust/mist/fume)
Exposure time: 2 y
Remarks: The substance is inextricably bound in the product and therefore does not contribute to a dust inhalation hazard.

Styrene:

Species: Rat
NOAEL: 1.28 mg/l
Application Route: inhalation (vapor)
Exposure time: 4 Weeks

Species: Rat
NOAEL: 1,000 - 2,000 mg/kg
Application Route: Ingestion

**DOW CORNING(R) Q4-2805 FLUOROSILICONE
CHANNEL SEALANT**

Version	Revision Date:	SDS Number:	Date of last issue: 05/06/2015
4.0	09/22/2015	656907-00005	Date of first issue: 10/22/2014

Exposure time: 78 - 100 Weeks

Aspiration toxicity

Not classified based on available information.

Ingredients:**Styrene:**

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity****Ingredients:****Titanium dioxide:**

Toxicity to fish	: LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l Exposure time: 96 h Method: OECD Test Guideline 203
Toxicity to daphnia and other aquatic invertebrates	: EC50 (Daphnia magna (Water flea)): > 100 mg/l Exposure time: 48 h
Toxicity to algae	: EC50 (Skeletonema costatum (marine diatom)): > 10,000 mg/l Exposure time: 72 h
Toxicity to bacteria	: EC50: > 1,000 mg/l Exposure time: 3 h Method: OECD Test Guideline 209

Styrene:

Toxicity to fish	: LC50 (Pimephales promelas (fathead minnow)): 10 mg/l Exposure time: 96 h Method: OECD Test Guideline 203
Toxicity to daphnia and other aquatic invertebrates	: EC50 (Daphnia magna (Water flea)): 4.7 mg/l Exposure time: 48 h Method: OECD Test Guideline 202
Toxicity to algae	: EC50 (Pseudokirchneriella subcapitata (green algae)): 4.9 mg/l Exposure time: 72 h
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	: NOEC (Daphnia magna (Water flea)): 1.01 mg/l Exposure time: 21 d Method: OECD Test Guideline 211
Toxicity to bacteria	: NOEC (Pseudomonas putida): 72 mg/l Exposure time: 16 h

**DOW CORNING(R) Q4-2805 FLUOROSILICONE
CHANNEL SEALANT**

Version 4.0	Revision Date: 09/22/2015	SDS Number: 656907-00005	Date of last issue: 05/06/2015 Date of first issue: 10/22/2014
----------------	------------------------------	-----------------------------	---

Persistence and degradability**Ingredients:****Styrene:**

Biodegradability	: Result: Readily biodegradable. Biodegradation: 100 % Exposure time: 28 d
------------------	--

Bioaccumulative potential**Ingredients:****Styrene:**

Partition coefficient: n-octanol/water	: log Pow: 2.96
--	-----------------

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

Resource Conservation and Recovery Act (RCRA)	: This product has been evaluated for RCRA characteristics and does not meet the criteria of hazardous waste if discarded in its purchased form.
---	--

Waste from residues	: Dispose of in accordance with local regulations.
---------------------	--

Contaminated packaging	: Empty containers should be taken to an approved waste handling site for recycling or disposal. If not otherwise specified: Dispose of as unused product.
------------------------	---

SECTION 14. TRANSPORT INFORMATION**International Regulation****UNRTDG**

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

**DOW CORNING(R) Q4-2805 FLUOROSILICONE
CHANNEL SEALANT**

Version 4.0	Revision Date: 09/22/2015	SDS Number: 656907-00005	Date of last issue: 05/06/2015 Date of first issue: 10/22/2014
----------------	------------------------------	-----------------------------	---

49 CFR

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION**EPCRA - Emergency Planning and Community Right-to-Know****CERCLA Reportable Quantity**

Ingredients	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
Disodium dichromate	10588-01-9	10	*
Styrene	100-42-5	1000	*

*: Calculated RQ exceeds reasonably attainable upper limit.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Chronic Health Hazard**SARA 302** : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.**SARA 313** : The following components are subject to reporting levels established by SARA Title III, Section 313:

Styrene	100-42-5	0.3 %
---------	----------	-------

US State Regulations**Pennsylvania Right To Know**

Trifluoropropylmethyl siloxane, hydroxy-terminated	68607-77-2	30 - 50 %
Polytetrafluoroethylene	9002-84-0	10 - 20 %
Styrene-divinylbenzene-ethylstyrene polymer	9052-95-3	10 - 20 %
Methylvinyl, trifluoropropylmethyl siloxane	68952-02-3	10 - 20 %
Hexamethyldisilazane reaction with Silica	68909-20-6	5 - 10 %
Styrene	100-42-5	0.1 - 1 %

New Jersey Right To Know

Trifluoropropylmethyl siloxane, hydroxy-terminated	68607-77-2	30 - 50 %
Polytetrafluoroethylene	9002-84-0	10 - 20 %
Styrene-divinylbenzene-ethylstyrene polymer	9052-95-3	10 - 20 %
Methylvinyl, trifluoropropylmethyl siloxane	68952-02-3	10 - 20 %
Hexamethyldisilazane reaction with Silica	68909-20-6	5 - 10 %
Styrene	100-42-5	0.1 - 1 %

**DOW CORNING(R) Q4-2805 FLUOROSILICONE
CHANNEL SEALANT**

Version	Revision Date:	SDS Number:	Date of last issue: 05/06/2015
4.0	09/22/2015	656907-00005	Date of first issue: 10/22/2014


	California Prop. 65	WARNING! This product contains a chemical known in the State of California to cause cancer.
		Disodium dichromate 10588-01-9
		WARNING: This product contains a chemical known in the State of California to cause birth defects or other reproductive harm.
		Disodium dichromate 10588-01-9

The ingredients of this product are reported in the following inventories:

REACH	: All ingredients (pre-)registered or exempt.
TSCA	: All chemical substances in this material are included on or exempted from listing on the TSCA Inventory of Chemical Substances.
AICS	: All ingredients listed or exempt.
IECSC	: All ingredients listed or exempt.
ENCS/ISHL	: All components are listed on ENCS/ISHL or exempted from inventory listing.
KECI	: All ingredients listed, exempt or notified.
PICCS	: All ingredients listed or exempt.
DSL	: All chemical substances in this product comply with the CEPA 1999 and NSNR and are on or exempt from listing on the Canadian Domestic Substances List (DSL).
TCSI	: All ingredients listed or exempt.

**DOW CORNING(R) Q4-2805 FLUOROSILICONE
CHANNEL SEALANT**

Version 4.0 Revision Date: 09/22/2015 SDS Number: 656907-00005 Date of last issue: 05/06/2015
Date of first issue: 10/22/2014

SECTION 16. OTHER INFORMATION**Further information****NFPA:****HMIS III:**

HEALTH	0*
FLAMMABILITY	1
PHYSICAL HAZARD	0

0 = not significant, 1 = Slight,
2 = Moderate, 3 = High
4 = Extreme, * = Chronic

Full text of other abbreviations

ACGIH	: USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI	: ACGIH - Biological Exposure Indices (BEI)
DCC OEL	: Dow Corning Guide
NIOSH REL	: USA. NIOSH Recommended Exposure Limits
OSHA Z-1	: USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
OSHA Z-2	: USA. Occupational Exposure Limits (OSHA) - Table Z-2
OSHA Z-3	: USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts
ACGIH / TWA	: 8-hour, time-weighted average
ACGIH / STEL	: Short-term exposure limit
DCC OEL / TWA	: Time weighted average
NIOSH REL / TWA	: Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
NIOSH REL / ST	: STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday
OSHA Z-1 / TWA	: 8-hour time weighted average
OSHA Z-2 / TWA	: 8-hour time weighted average
OSHA Z-2 / CEIL	: Acceptable ceiling concentration
OSHA Z-2 / Peak	: Acceptable maximum peak above the acceptable ceiling concentration for an 8-hr shift
OSHA Z-3 / TWA	: 8-hour time weighted average

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized

**DOW CORNING(R) Q4-2805 FLUOROSILICONE
CHANNEL SEALANT**

Version	Revision Date:	SDS Number:	Date of last issue: 05/06/2015
4.0	09/22/2015	656907-00005	Date of first issue: 10/22/2014

System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 09/22/2015

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8