

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date: 02/07/2020 Date of issue: 03/26/2019 Version: 2.0

SECTION 1: Identification

Identification

Product form : Mixture

Product name : COR-BAN 23 BULK

Recommended use and restrictions on use

Use of the substance/mixture : Corrosion inhibitors

1.3. **Supplier**

Manufacturer

Zip-Chem Products 400 Jarvis Drive Morgan Hill, CA 95037 - United States T 408-782-2335 - F 408-782-6304 4info@zipchem.com

Emergency telephone number

Emergency number : 1-800-424-9300

SECTION 2: Hazard(s) identification

Classification of the substance or mixture

GHS US classification

Flammable liquids, Category 3

H226 Flammable liquid and vapour.

On basis of test

data

Specific target organ toxicity — Repeated exposure,

Category 1

H372 Causes damage to organs through prolonged or repeated

Expert judgment

exposure.

Full text of H statements: see section 16

GHS Label elements, including precautionary statements

GHS US labelling

Hazard pictograms (GHS US)





Signal word (GHS US) : Danger

Hazard statements (GHS US) : H226 - Flammable liquid and vapour.

H372 - Causes damage to organs through prolonged or repeated exposure.

Precautionary statements (GHS US) : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233 - Keep container tightly closed.

P240 - Ground/Bond container and receiving equipment.

P241 - Use explosion-proof electrical/ventilating/lighting equipment.

P242 - Use only non-sparking tools.

P243 - Take precautionary measures against static discharge. P260 - Do not breathe dust/fume/gas/mist/vapours/spray.

P264 - Wash hands, forearms and face thoroughly after handling. P270 - Do not eat, drink or smoke when using this product.

P280 - Wear eye protection, face protection, protective gloves.

P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P314 - Get medical advice/attention if you feel unwell.

P370+P378 - In case of fire: Use alcohol resistant foam, ABC-powder, carbon dioxide (CO2),

dry extinguishing powder, foam to extinguish.

P403+P235 - Store in a well-ventilated place. Keep cool.

P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

Other hazards which do not result in classification

No additional information available

02/07/2020 EN (English) Page 1

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

2.4. **Unknown acute toxicity (GHS US)**

Not applicable

SECTION 3: Composition/information on ingredients

Substances 3.1.

Not applicable

Mixtures 3.2.

Name	Product identifier	%	GHS US classification
hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics	(CAS-No.) 64742-47-8	15-35	Flam. Liq. 4, H227 Asp. Tox. 1, H304
STRAIGHT RUN KEROSINE - SOLVENT NAPHTHA (PETROLEUM), MEDIUM ALIPH.	(CAS-No.) 64742-88-7	10-15	STOT RE 1, H372 Asp. Tox. 1, H304
LOW BOILING POINT HYDROGEN TREATED NAPHTHA - NAPHTHA (PETROLEUM), HYDROTREATED HEAVY	(CAS-No.) 64742-48-9	2-8	Flam. Liq. 3, H226 Muta. Not classified Carc. Not classified Asp. Tox. 1, H304
naphtha,heavy aromatic	(CAS-No.) 64742-94-5	0-3	Asp. Tox. 1, H304

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

Description of first aid measures

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.

First-aid measures after skin contact Rinse skin with water/shower. Take off immediately all contaminated clothing.

First-aid measures after eye contact Rinse eyes with water as a precaution.

First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell.

Most important symptoms and effects (acute and delayed)

No additional information available

Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

5.2. Specific hazards arising from the chemical

Fire hazard : Flammable liquid and vapour. Hazardous decomposition products in case of : Toxic fumes may be released.

Special protective equipment and precautions for fire-fighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing

apparatus. Complete protective clothing

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures 6.1.

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public

waters.

Other information : Dispose of materials or solid residues at an authorized site.

02/07/2020 EN (English) 2/8

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling

: Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapours may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment.

Hygiene measures

: Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Ground/bond container and receiving equipment.

Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

COR-BAN 23 BULK

No additional information available

naphtha, heavy aromatic (64742-94-5)

No additional information available

STRAIGHT RUN KEROSINE - SOLVENT NAPHTHA (PETROLEUM), MEDIUM ALIPH. (64742-88-7)

No additional information available

LOW BOILING POINT HYDROGEN TREATED NAPHTHA - NAPHTHA (PETROLEUM), HYDROTREATED HEAVY (64742-48-9)

No additional information available

hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics (64742-47-8)

No additional information available

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.

Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Hand protection:

Protective gloves

Eye protection:

Safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

Personal protective equipment symbol(s):



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid

02/07/2020 EN (English) 3/8

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Appearance : Liquid.
Colour : Red-brown
Odour : Solvent-like

Odour Codour threshold : Solvent-like odour Codour threshold : No data available pH : No data available Melting point : Not applicable Freezing point : No data available Boiling point : No data available colong point : No data avai

Flash point : > 41 °C

Relative evaporation rate (butylacetate=1) : No data available Flammability (solid, gas) : Not applicable. Vapour pressure : 1.2 mm Hg Relative vapour density at 20 °C : No data available Relative density : No data available

Density : 0.87 g/ml

Solubility : Soluble in aromatic hydrocarbons. Soluble in naphtha. Soluble in petroleum spirit. Substance

floats in water.

Partition coefficient n-octanol/water (Log Pow) : No data available Auto-ignition temperature : No data available Decomposition temperature No data available Viscosity, kinematic : 20 - 24 mm²/s : 30 - 46 cP Viscosity, dynamic Explosive limits : No data available Explosive properties : No data available Oxidising properties No data available

9.2. Other information

 VOC content
 : 429 g/l

 Percent Solids
 : 40 – 44 %

SECTION 10: Stability and reactivity

10.1. Reactivity

Flammable liquid and vapour.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

STRAIGHT RUN KEROSINE - SOLVENT NAPHTHA (PETROLEUM), MEDIUM ALIPH. (64742-88-7)	
LD50 oral rat	> 5000 mg/kg bodyweight (Equivalent or similar to OECD 420, Rat, Male / female, Experimental value, Oral)

02/07/2020 EN (English) 4/8

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

	· · · · · · · · · · · · · · · · · · ·
STRAIGHT RUN KEROSINE - SOLVE	NT NAPHTHA (PETROLEUM), MEDIUM ALIPH. (64742-88-7)
LD50 dermal rabbit	> 2000 mg/kg bodyweight (Equivalent or similar to OECD 402, 24 h, Rabbit, Male / female, Experimental value, Dermal)
LC50 inhalation rat (mg/l)	> 5.28 mg/l air (Equivalent or similar to OECD 403, 4 h, Rat, Male / female, Experimental value, Inhalation (vapours))
LOW BOILING POINT HYDROGEN TO	REATED NAPHTHA - NAPHTHA (PETROLEUM), HYDROTREATED HEAVY (64742-48-9)
LD50 oral rat	> 15000 mg/kg (Rat, Oral)
LD50 dermal rabbit	> 3160 mg/kg (Rabbit, Dermal)
hydrocarbons, C11-C14, n-alkanes, i	soalkanes, cyclics, < 2% aromatics (64742-47-8)
LD50 dermal rabbit	> 5000 mg/kg bodyweight (Rabbit, Literature, Dermal)
Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
TOT-single exposure	: Not classified
TOT-repeated exposure	: Causes damage to organs through prolonged or repeated exposure.
STRAIGHT RUN KEROSINE - SOLVE	NT NAPHTHA (PETROLEUM), MEDIUM ALIPH. (64742-88-7)
STOT-repeated exposure	Causes damage to organs through prolonged or repeated exposure.

Aspiration hazard	: Not classified
Viscosity, kinematic	: $20 - 24 \text{ mm}^2/\text{s}$

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.

LOW BOILING POINT HYDROGEN TREATED NAPHTHA - NAPHTHA (PETROLEUM), HYDROTREATED HEAVY (64742-48-9)		
LC50 fish 1	2200 mg/l (96 h, Pimephales promelas, Fresh water)	
hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics (64742-47-8)		
LC50 fish 1	> 100 mg/l (Pisces)	
EC50 Daphnia 1	> 100 mg/l (Invertebrata)	

12.2. Persistence and degradability

naphtha,heavy aromatic (64742-94-5)		
Persistence and degradability	Not readily biodegradable in water.	
STRAIGHT RUN KEROSINE - SOLVENT NAPHTHA (PETROLEUM), MEDIUM ALIPH. (64742-88-7)		
Persistence and degradability	Readily biodegradable in water.	
LOW BOILING POINT HYDROGEN TREATED	NAPHTHA - NAPHTHA (PETROLEUM), HYDROTREATED HEAVY (64742-48-9)	
LOW BOILING POINT HYDROGEN TREATED Persistence and degradability	NAPHTHA - NAPHTHA (PETROLEUM), HYDROTREATED HEAVY (64742-48-9) Not readily biodegradable in water.	
	Not readily biodegradable in water.	

12.3. Bioaccumulative potential

naphtha,heavy aromatic (64742-94-5)	
Partition coefficient n-octanol/water (Log Pow)	2.9 – 6.1
Bioaccumulative potential	Bioaccumable.

02/07/2020 EN (English) 5/8

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

STRAIGHT RUN KEROSINE - SOLVENT NAPHTHA (PETROLEUM), MEDIUM ALIPH. (64742-88-7)		
Bioaccumulative potential	No bioaccumulation data available.	
LOW BOILING POINT HYDROGEN TREATED NAPHTHA - NAPHTHA (PETROLEUM), HYDROTREATED HEAVY (64742-48-9)		
Partition coefficient n-octanol/water (Log Pow)	2.1 – 6.5 (Calculated)	
hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics (64742-47-8)		
Partition coefficient n-octanol/water (Log Pow)	6 – 8.2	
Bioaccumulative potential	High potential for bioaccumulation (Log Kow > 5).	

12.4. Mobility in soil

STRAIGHT RUN KEROSINE - SOLVENT NAPHTHA (PETROLEUM), MEDIUM ALIPH. (64742-88-7)	
Ecology - soil	Adsorbs into the soil.
hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics (64742-47-8)	
Surface tension	0.026 N/m (20 °C)
Ecology - soil	Adsorbs into the soil.

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

Additional information : Flammable vapours may accumulate in the container.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Transport document description : UN1993 Flammable liquids, n.o.s. (Naphtha), 3, III

UN-No.(DOT) : UN1993

Proper Shipping Name (DOT) : Flammable liquids, n.o.s.

Naphtha

Class (DOT) : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120

Packing group (DOT) : III - Minor Danger Hazard labels (DOT) : 3 - Flammable liquid



DOT Packaging Non Bulk (49 CFR 173.xxx) : 203 DOT Packaging Bulk (49 CFR 173.xxx) : 242

02/07/2020 EN (English) 6/8

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT Special Provisions (49 CFR 172.102)

: B1 - If the material has a flash point at or above 38 C (100 F) and below 93 C (200 F), then the bulk packaging requirements of 173.241 of this subchapter are applicable. If the material has a flash point of less than 38 C (100 F), then the bulk packaging requirements of 173.242 of this subchapter are applicable.

B52 - Notwithstanding the provisions of 173.24b of this subchapter, non-reclosing pressure relief devices are authorized on DOT 57 portable tanks.

IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672).

T4 - 2.65 178.274(d)(2) Normal..... 178.275(d)(3)

TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = 97 / (1 + a (tr - tf)) Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.

TP29 - A portable tank having a minimum test pressure of 1.5 bar (150.0 kPa) may be used provided the calculated test pressure is 1.5 bar or less based on the MAWP of the hazardous materials, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.

DOT Packaging Exceptions (49 CFR 173.xxx) : 150 DOT Quantity Limitations Passenger aircraft/rail : 60 L

(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 220 L

CFR 175.75)

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a

passenger vessel.

Emergency Response Guide (ERG) Number : 128

Other information : No supplementary information available.

Transportation of Dangerous Goods

Not applicable

Transport by sea

Transport document description (IMDG) : UN 1993 FLAMMABLE LIQUID, N.O.S., 3, III

UN-No. (IMDG) : 1993

Proper Shipping Name (IMDG) : FLAMMABLE LIQUID, N.O.S.

Class (IMDG) : 3 - Flammable liquids

Packing group (IMDG) : III - substances presenting low danger

Limited quantities (IMDG) : 5 L

Air transport

Transport document description (IATA) : UN 1993 Flammable liquid, n.o.s., 3, I

UN-No. (IATA) : 1993

Proper Shipping Name (IATA) : Flammable liquid, n.o.s.

Class (IATA) : 3 - Flammable Liquids

Packing group (IATA) : I - Great Danger

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

15.2. International regulations

CANADA

02/07/2020 EN (English) 7/8

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

naphtha, heavy aromatic (64742-94-5)

Listed on the Canadian DSL (Domestic Substances List)

STRAIGHT RUN KEROSINE - SOLVENT NAPHTHA (PETROLEUM), MEDIUM ALIPH. (64742-88-7)

Listed on the Canadian DSL (Domestic Substances List)

LOW BOILING POINT HYDROGEN TREATED NAPHTHA - NAPHTHA (PETROLEUM), HYDROTREATED HEAVY (64742-48-9)

Listed on the Canadian DSL (Domestic Substances List)

hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics (64742-47-8)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

National regulations

COR-BAN 23 BULK

One or all of the ingredients in this product are listed on the (AICS) Inventory list

15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date : 02/07/2020

Full text of H-statements:

H226	Flammable liquid and vapour.
H227	Combustible liquid
H304	May be fatal if swallowed and enters airways.
H372	Causes damage to organs through prolonged or repeated exposure.

Hazard Rating

Health : 1 Slight Hazard - Irritation or minor reversible injury possible

Flammability : 2 Moderate Hazard - Materials which must be moderately heated or exposed to high ambient

temperatures before ignition will occur. Includes liquids having a flash point at or above 100 F

but below 200 F. (Classes II & IIIA)

Physical : 1 Slight Hazard - Materials that are normally stable but can become unstable (self-react) at high

temperatures and pressures. Materials may react non-violently with water or undergo

hazardous polymerization in the absence of inhibitors.

Personal protection : G

G - Safety glasses, Gloves, Vapor respirator

SDS US (GHS HazCom 2012)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

02/07/2020 EN (English) 8/8