

SAFETY DATA SHEET

Effective Date: JULY 2019

ITEM: Coastal Alerter Kit

PART # 572 **UPC** 077403105724

CONTENTS12 Ga HP Red Aerial Signal SDS

SHIPPING INFORMATION

UN0403, Flares, aerial, 1.4G (ERG 114) EX2004110275



SAFETY DATA SHEET

1. Product and Company Identification

12 Ga HP (High Performance) Red Aerial Signal

Manufacturer's Information: Orion Safety Products

 3157 N 500 W
 EMERGENCY
 CHEMTREC

 Peru, Indiana 46970
 RESPONSE
 1-800-424-9300

 US 1-800-851-5260
 1-703-527-3887

Int'l (11) 1-765-472-4375

2. Hazards Identification

GHS Classifications Explosive Category 1.4 Skin Irritation Category 2

Eye Irritation Category 1
Carcinogenicity Category 2
STOT-Single Exposure Category 3

GHS Label Elements

Hazard Statements Pictog H204 Fire or projection hazard H315 Causes skin irritation H318 Causes serious eye damage

H351 Suspected of causing cancer H335 May cause respiratory irritation





Signal Word Danger

Precautionary Statements

P102	Keep out of reach of children.	P301/315	IF SWALLOWED: Get immediate medical advice /attention.
P103	Read carefully and follow all instructions.	P302/352	IF ON SKIN: Wash with plenty of soap and water.
P210	Keep away from heat/sparks/open flames/hot surfaces.	P304/340/342	IF INHALED: Remove victim to fresh air and keep at rest in a position
1 210	No smoking		comfortable for breathing. If experiencing respiratory symptoms: Call a
P232	Protect from moisture		POISON CENTER or doctor/physician.
P261	Avoid breathing dust/fumes.	P305/351/338	IF IN EYES: Rinse cautiously with water for several minutes. Remove
P264	Wash hands thoroughly after handling.		contact lenses, if present and easy to do. Continue rinsing.
P270	Do not eat, drink or smoke when using this product.	P333/313	If skin irritation or rash occurs, get medical advice/attention.
P271	Use only outdoors.	P370	In case of fire: use water deluge
P280	Wear protective eye protection.		

Hazards Not Otherwise Classified (HNOC): none

3. Composition / Information on Ingredients

Component	CAS#	EINCS #	Percentage
High Density Polyethylene	9002-88-4	Polymer	<60%
Talc	14807-96-6	238-877-9	<20%
Strontium Nitrate	10042-76-9	233-131-9	<20%
Magnesium	7439-95-4	231-104-6	<20%
Strontium Peroxide	1314-18-7	215-224-6	<10%
Aluminum	7429-90-5	231-072-3	<5%
Polyvinyl Chloride	9002-86-2	None	<5%
Dextrin	9004-53-9	232-675-4	<1%
Potassium Nitrate	7757-79-1	231-818-8	<4%
Charcoal	16291-96-6	240-383-3	<1%
Sulfur	7704-34-9	231-722-6	<2%
Iron	1309-37-1	231-096-4	<5%
Copper	7440-50-8	231-159-6	<3%

Note: Due to Confidential Business Information, "Trade Secrets", the exact percentage of each ingredient has not been disclosed. CBI information will be shared with appropriate authorities if circumstances warrant.



4. First Aid Measures

Description of first aid measures

If contents are inhaled, remove to fresh air. Watch for signs of allergic reaction. If other symptoms develop, Inhalation

get medical aid immediately.

Skin If contents are contacted, wash with area with soap and water for 15 minutes. Remove contaminated clothing

and wash before reuse. Get medical aid if irritation occurs.

If contents get into eyes, flush with plenty of water for at least 15 minutes, occasionally lifting the upper and lower lids.

Remove contact lenses if easily possible. Get medical aid immediately.

Ingestion Get medical aid immediately.

Most important symptoms and effects both acute and delayed

See section 2 labeling and section 11

Indication of any immediate medical attention and special treatment needed

No data available

5. Firefighting Measures

Foam and dry chemical extinguishers Extinguishing Media Water deluge Unsuitable Extinguishing Media and suffocation are ineffective.

Protective Equipment and **Precautions for Firefighters**

Wear full protective clothing and NIOSH-approved self-contained breathing apparatus with full face piece operated in the pressure demand or other positive pressure mode. Prevent further propagation of fire by spraying unburnt

nearby product with water. Combat fire from a sheltered position.

Specific Hazards Arising from the Chemical Only use outdoors. Use copious amounts of water to extinguish fire. Using small quantity of water on contents / broken shells can cause auto / re-ignition as contents contain magnesium. Use of water on a magnesium fire will generate hydrogen gas that

may cause an explosion. Irritating fumes. Flaming projectiles may be ejected during a fire. Trace amounts of lead vapor may be

produced (from ignition primer) in a fire situation.

Further Information No data available

6. Accidental Release Measures

Personal Precautions / Protective Equipment / Emergency Procedures

Do not breathe smoke or contents. Avoid contact with skin and eyes. Wear flame retardant clothing with long sleeves, dust mask, rubber or nitrile gloves, safety goggles, safety shoes when cleaning up contents. Avoid friction on the released product. Keep away from ignition sources.

Environmental Precautions

Prevent dispersion of contents on soil and in water. Prevent contents from spreading or entering into drains, ditches, groundwater or rivers by using appropriate barriers.

Methods for Containment and Clean-up

Use caution when cleaning up spilled contents. Remove heat, flames, sparks and other sources of ignition. Use non-sparking tools and equipment. Prevent buildup of electrostatic charges by grounding. Clean spills in a manner that does not disperse dust into the air. Do not absorb in sawdust or other combustible absorbents. Pick up spill for recovery of disposal and place in an approved container. Wash away remainder with plenty of water. Collect wash water for approved disposal. Be very careful - magnesium powder may spontaneously ignite in presence of moisture. Magnesium powder reacts with water, producing flammable hydrogen gas.

7. Handling and Storage

Precautions for Safe Handling

Use product only in designated launcher – do not attempt to use in 12 gauge shotgun. Point launcher away from body, other people, animals or combustible products when firing. Wear appropriate eye protection during use. Turn face from launcher when firing. Follow instructions on package. Avoid contact with clothing and other combustible materials. Use outdoors only! Do not ignite or launch product inside a vehicle or building. Avoid ingestion of smoke and inhalation of contents. Wash thoroughly after handling. Avoid contact with heat sparks, and flame. Do no disassemble signals.

Conditions for Safe Storage, Including Any Incompatibilities

Store in a dry place away from direct sunlight, heat and incompatible materials. See section 10. Store away from food and beverages. Store away from flammable materials, sources of heat, flame and sparks. Store at ambient temperature.

8. Exposure Controls / Personal Protection

Control Parameters

Exposure Limits	OSHA PEL	ACGIH TLV
High Density Polyethylene	5mg/ml for respirable portion and 15mg/ml' for total dust	3mg/ml for respirable portion and 10mg/ml' for total dust
Talc	2.0 mg/m³	2.0 mg/m ³
Strontium Nitrate	Not Established	Not Established
Magnesium	Not Established	Not Established
Strontium Peroxide	Nuisance dust 15mg/m ³	Nuisance dust 15mg/m ³
Aluminum	TWA: 15 mg/m³	TWA: 1 mg/m³
Polyvinyl Chloride	5mg/ml for respirable portion and 15mg/ml' for total dust	5 and 10 mg/ml, respectively
Dextrin	15 mg/m³	15 mg/m³
Charcoal	3.5 mg/m³	3 mg/m³
Sulfur	20 ppm	Not Established
Potassium Nitrate	15 mg/m³	10 mg/m³

TWA: 10 mg/m³ Iron 0.1 mg/m³(fume) 1 mg/m³(dusts and mists) Copper

Not Established 0.2 mg/m³(fume), 1 mg/m³ (dusts and mists)

4 0 0 H I T I V



Exposure Controls

Personal Protective Equipment

Eye / Face Protection Skin Protection Turn face from launcher when firing. Wear safety glasses or goggles during use and when cleaning up spilled contents.

None under normal conditions when using product unless prolonged handling is anticipated. When cleaning up spilled contents, wear impervious protective clothing, including gloves, boots, and a lab coat, apron or coveralls as appropriate.

Wash hands and face before eating, drinking, or using tobacco products.

Respiratory Protection None under normal conditions when using product. A particulate respirator (NIOSH t N195 or better filters) may be worn

during the cleanup of spilled contents.

General Hygiene Use product outdoors away from combustible products. For cleanup of spilled contents, emergency showers and eye wash

stations should be available. Educate and train employees in the safe use and handling of hazardous materials. Maintain good housekeeping and safety practices. Do not let contents accumulate in storage or work areas. Clean spills up

promptly

9. Physical and Chemical Properties

Appearance (color, physical form, shape): Grey powder

No data available Melting Point: No data available Solubility: No data available Boiling Point / Range: Not applicable Freezing Point: Not applicable Evaporation Rate: Not applicable Vapor Pressure: Not applicable Specific Gravity: Not applicable Vapor Density: Not applicable No data available Odor Threshold: No data available Flash Point: No data available Odor: Flammability: No data available Flammability Limits: No data available Relative Density: No data available

Partition Coefficient: No data available Viscosity: No data available

Auto Ignition Temperature: No data available Decomposition Temperature: No data available

10. Stability and Reactivity

Chemical Stability: Stable Reactivity: No information available Possibility of Hazardous Reactions: Hazardous polymerization will not occur.

Conditions to Avoid Incompatible Materials

Excessive temperatures, Reducing Agents, Organic Materials, Finely Powdered Metals,

Acids, Water, Halogens

moisture, acids, and ignition Acids, Water, Haloge

Hazardous Decomposition Products Strontium Oxides, Carbon Monoxide and Dioxide, Nitrous Oxides, Magnesium Hydroxides and Oxides.

I CEA

11. Toxicology Information

Ingredient acute toxicity information

Oral LD50	Skin LD50	LC50
4000mg/kg	not available	12,000 mg/m ³ /30min
not available	not available	not available
Rat 2750 mg/kg	not available	not available
Rat 230 mg/kg	not available	not available
Rat 980 mg/kg	not available	not available
Rat: >2000 mg/kg	Rat – 4h - >888 mg/l	not available
Rat: >5000 mg/kg	not available	not available
None Known	Not Sensitizing	None Known
Rat 3015 mg/kg	not available	not available
Rat 10000 mg/kg	Rabbit >3000 mg/kg	not available
Rat 175 mg/kg	Rabbit >2000 mg/kg	Rat 9.23 mg/l/4hr
Rat: 30000 mg/kg	not available	not available
Rat: 5800 mg/kg	not available	not available
	4000mg/kg not available Rat 2750 mg/kg Rat 230 mg/kg Rat 980 mg/kg Rat: >2000 mg/kg Rat: >5000 mg/kg None Known Rat 3015 mg/kg Rat 10000 mg/kg Rat 175 mg/kg Rat: 30000 mg/kg	4000mg/kg not available not available not available not available Rat 2750 mg/kg not available Rat 230 mg/kg not available Rat 230 mg/kg not available Rat 980 mg/kg not available Rat: >2000 mg/kg Rat – 4h - >888 mg/l Rat: >5000 mg/kg not available None Known Not Sensitizing Rat 3015 mg/kg not available Rat 10000 mg/kg Rat: 3000 mg/kg Rat: 30000 mg/kg Nat: 30000 mg/kg

Product toxicological information

Acute Toxicity Not classified – Acute Toxicity Estimate yields oral LD₅o over 5000 mg/kg bw 17% unknown

CLim I DEO

Skin Irritation / Corrosion
Category 2 – over 0.1% of ingredients classified as a Category 2 skin irritant
Category 1 – over .01% of ingredients classified as a Category 1 eye irritant

Respiratory / Skin Sensitization No information found Germ Cell Mutagen No information found

Carcinogen Category 2 – over 0.1% of ingredients classified as a Category 2 carcinogens

Reproductive Toxicity No information found

STOT – single exposure Category 3 – respiratory over 20% of ingredients classified as a Category 3 respiratory STOT hazard

STOT – repeated exposure
Aspiration Hazard
No information found

Likely routes of exposure Skin, ingestion, inhalation

Symptoms related to the physical, Irritation to the eyes will cause watering and redness. Reddening, scaling, and itching are chemical and toxicological characteristics of skin inflammation. Ingestion of contents may cause gastrointestinal irritation with

Delayed and immediate effects and chronic

Mosorption of strontium peroxide into the body leads to the formation of methemoglobin which in sufficient concentration causes cyanosis. Onset may be delayed 2 to 4 hours or longer.

effects from short and long term exposure

Suincient concentration causes cyanosis. Onset may be delayed 2 to 4 if
Prolonged or repeated skin contact with contents may cause dermatitis.

Interactive effects No information found

3



12. Ecological Information

Ingredient toxicity / persistence / degradability / bioaccumulation / mobility in soil and water

Aquatic Toxicity Strontium Nitrate: Acute toxicity - Fishes, Carassius auratus, LC100, 9,615 mg/l; Chronic toxicity - Fishes,

Gasterosteus aculeatus, LC100, 2.912 mg/l

Magnesium: LC50 1355 mg/l fish

Persistence / Degradability Bioaccumulation / Accumulation

No information found No information found

Bioaccumulation / Accumulation No in Mobility in Environmental Media Stron

Strontium Nitrate: Water:: considerable solubility and mobility; Soil/sediments non-significant adsorption

Other adverse effects No information found

13. Disposal Considerations (for spills and leakage)

Dispose of contaminated product and materials used in cleaning up spills or leaks in the manner approved for pyrotechnic material. Consult appropriate federal, state, and local regulatory agencies to ascertain proper disposal procedures. Open burning is preferred method of disposal for pyrotechnic materials.

14. Transportation Information

	ID Number	Proper Shipping Name	Hazard Class	Packing Group	EX Number	Reportable Quantities	
Domestic & International	UN0403	Flares, aerial	1.4G	n/a	EX2004110275	none	
Marine pollutant: ne	0		Special preca	utions for user:	no information availa	able	

15. Regulatory Information

US Regulations	TSCA	CERCLA	CWA	CAA	SARA 313	SARA 302	Acute	Chronic	Fire	Reactivity	Pressure
HD Polyethylene	yes	no	no	no	no	no	no	no	no	no	no
Talc	yes	no	no	no	no	no	no	no	no	no	no
Strontium Nitrate	yes	no	no	no	yes	no	yes	no	no	yes	no
Magnesium	yes	no	no	no	no	no	no	no	yes	yes	no
Strontium Peroxide	yes	no	no	no	no	no	yes	no	yes	yes	no
Aluminum	yes	no	no	no	yes	no	no	no	no	no	no
Polyvinyl Chloride	yes	no	no	no	no	no	yes	no	no	no	no
Dextrin	yes	no	no	no	no	no	no	no	no	no	no
Potassium Nitrate	Yes	no	no	no	yes	no	no	no	yes	no	no
Charcoal	yes	no	no	no	no	no	yes	yes	yes	no	no
Sulfur	yes	no	no	no	no	no	yes	yes	yes	no	no
Iron	yes	no	no	no	no	no	no	no	yes	no	no
Copper	yes	yes	yes	no	yes	no	yes	no	yes	no	no

US States	Prop 65	NJ	PA	Canada	WHMIS	DSL	Europe	wgk
HD Polyethylene	no	yes	yes		Not Controlled	yes	•	not listed
Talc	yes	yes	yes	yes	Class D2A – Very toxic material C Oxidizing materials	yes		not listed
Strontium Nitrate	no	yes	no		D1B Toxic materials D2B Toxic materials	yes		2
Magnesium	no	yes	yes		B6 Reactive flammable material; B4 Flammable solid; F Dangerously reactive material	yes		nwg
Strontium Peroxide	no	yes	no		C oxidizing material	yes		not listed
Aluminum	no	yes	yes		Not controlled	yes		nwg
Polyvinyl Chloride	no	yes	no		Not controlled	yes		not listed
Dextrin	no	no	no		Not controlled	,		
Potassium Nitrate	no	no	no	yes	No information found	yes		nwg
Charcoal	yes	yes	yes	•	No information found	yes		nwg
Sulfur	•	yes	yes	yes	No information found	yes		nwg
Iron	no	yes	yes	•	B4 flammable solid	yes		nwg
Copper	no	yes	yes		B4 Flammable solid D2B Toxic materials	yes		nwg



16. Other Information

Revision Information: July 2019

NFPA RatingHMIS RatingFlammability2Flammability1Health2Health3Reactivity1Physical Hazard1

Key / Legend

HMIS: hazardous material identification system NFPA: national fire protection association CAS: Chemical Abstracts Service number

EINECS: European inventory of existing chemical substances

OSHA PEL: occupational safety and health administration permissible exposure limit NIOSH TLV: national institute of occupational safety

and health Threshold Limit Value NTP: National Toxicology Program

IARC: International Agency for Research on Cancer

CWA: clean water act - US

TSCA: toxic substance control act - US CERCLA: comprehensive environmental response

compensation and liability act – US

CAA: clean air act - US

SARA: superfund amendments and reauthorization

act - US

PROP 65:California's Proposition 65 list WHMIS: workplace hazardous materials

information system - Canada

DSL: Domestic Substances List - Canada WGK: water hazard classes - Germany

Legal Statement

This information is accurate to the best knowledge of Orion Safety Products. Orion Safety Products makes no representations or warranties, either express or implied, including without limitation any warranties of merchantability or fitness for a particular purpose, with respect to the information set forth herein or the product to which the information refers. Accordingly, Orion Safety Products will not be responsible for damages resulting from use of or reliance upon this information. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation