MOLYKOTE® M Gear Oil Additive



Version Revision Date: SDS Number: Date of last issue: 05/02/2017 4.0 10/22/2018 1587878-00008 Date of first issue: 03/18/2015

SECTION 1. IDENTIFICATION

Product name : MOLYKOTE® M Gear Oil Additive

Product code : 01156373

Manufacturer or supplier's details

Company Identification : DDP SPECIALTY ELECTRONIC MATERIALS

US 9, LLC 974 Centre Road Wilmington DE 19805 UNITED STATES

Telephone : 833-338-7668

24-Hour Emergency Contact : 1-800-424-9300

Local Emergency Number : 800-424-9300

E-mail address : SDSQuestion-NA@dupont.com

Recommended use of the chemical and restrictions on use

Recommended use : Lubricants and lubricant additives

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with 29 CFR 1910.1200

Not a hazardous substance or mixture.

GHS label elements

Not a hazardous substance or mixture.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Chemical nature : Inorganic compounds in mineral oil

Hazardous ingredients

Chemical name	CAS-No.	Concentration (% w/w)
Distillates (petroleum), solvent-dewaxed	64742-65-0	>= 70 - < 90
heavy paraffinic		
Distillates (petroleum), hydrotreated heavy	64742-54-7	>= 5 - < 10
paraffinic		
Distillates (petroleum), solvent refined	64741-88-4	>= 5 - < 10
heavy paraffinic		
Molybdenum sulfide	1317-33-5	>= 1 - < 5

MOLYKOTE® M Gear Oil Additive



Version Revision Date: SDS Number: Date of last issue: 05/02/2017 4.0 10/22/2018 1587878-00008 Date of first issue: 03/18/2015

Distillates (petroleum), hydrotreated light | 64742-55-8 | >= 1 - < 5

paraffinic

SECTION 4. FIRST AID MEASURES

If inhaled : If inhaled, remove to fresh air.

Get medical attention if symptoms occur.

In case of skin contact : Wash with water and soap as a precaution.

Get medical attention if symptoms occur.

In case of eye contact : Flush eyes with water as a precaution.

Get medical attention if irritation develops and persists.

If swallowed, DO NOT induce vomiting.

Get medical attention if symptoms occur. Rinse mouth thoroughly with water.

Most important symptoms and effects, both acute and

delayed

None known.

Protection of first-aiders : No special precautions are necessary for first aid responders.

Notes to physician : Treat symptomatically and supportively.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Water spray

Alcohol-resistant foam Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

None known.

Specific hazards during fire

fighting

Exposure to combustion products may be a hazard to health.

Hazardous combustion prod-

ucts

Carbon oxides
Metal oxides
Sulfur oxides

Specific extinguishing meth-

ods

Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

Use water spray to cool unopened containers.

Remove undamaged containers from fire area if it is safe to do

SO.

Evacuate area.

Special protective equipment :

for fire-fighters

Wear self-contained breathing apparatus for firefighting if

necessary.

MOLYKOTE® M Gear Oil Additive



Version Revision Date: SDS Number: Date of last issue: 05/02/2017 10/22/2018 1587878-00008 Date of first issue: 03/18/2015 4.0

Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec: : tive equipment and emer-

gency procedures

Follow safe handling advice and personal protective

equipment recommendations.

Environmental precautions Discharge into the environment must be avoided.

Prevent further leakage or spillage if safe to do so.

Prevent spreading over a wide area (e.g., by containment or

oil barriers).

Retain and dispose of contaminated wash water.

Local authorities should be advised if significant spillages

cannot be contained.

Methods and materials for containment and cleaning up Soak up with inert absorbent material.

For large spills, provide diking or other appropriate

containment to keep material from spreading. If diked material

can be pumped, store recovered material in appropriate

container.

Clean up remaining materials from spill with suitable

absorbent.

Local or national regulations may apply to releases and disposal of this material, as well as those materials and items

employed in the cleanup of releases. You will need to

determine which regulations are applicable.

Sections 13 and 15 of this SDS provide information regarding

certain local or national requirements.

SECTION 7. HANDLING AND STORAGE

Technical measures See Engineering measures under EXPOSURE

CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation Use only with adequate ventilation.

Advice on safe handling Handle in accordance with good industrial hygiene and safety

practice.

Take care to prevent spills, waste and minimize release to the

environment.

Conditions for safe storage Keep in properly labeled containers.

Store in accordance with the particular national regulations.

Materials to avoid Do not store with the following product types:

Strong oxidizing agents

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

MOLYKOTE® M Gear Oil Additive



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 05/02/2017

 4.0
 10/22/2018
 1587878-00008
 Date of first issue: 03/18/2015

Ingredients	CAS-No.	Value type (Form of	Control parameters / Permissible	Basis
Distillates (petroleum), solvent- dewaxed heavy paraffinic	64742-65-0	exposure) TWA (Mist)	concentration 5 mg/m³	OSHA Z-1
, , , , , , , , , , , , , , , , , , , ,		TWA (Inhalable fraction)	5 mg/m³	ACGIH
		TWA (Mist)	5 mg/m³	NIOSH REL
		ST (Mist)	10 mg/m ³	NIOSH REL
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	TWA (Mist)	5 mg/m³	OSHA Z-1
		TWA (Mist)	5 mg/m³	NIOSH REL
		ST (Mist)	10 mg/m ³	NIOSH REL
Distillates (petroleum), solvent refined heavy paraffinic	64741-88-4	TWA (Mist)	5 mg/m³	OSHA Z-1
		TWA (Inhal- able fraction)	5 mg/m³	ACGIH
		TWA (Mist)	5 mg/m³	NIOSH REL
		ST (Mist)	10 mg/m ³	NIOSH REL
Molybdenum sulfide	1317-33-5	TWA (total dust)	15 mg/m³ (Molybdenum)	OSHA Z-1
		TWA (Inhal- able fraction)	10 mg/m³ (Molybdenum)	ACGIH
		TWA (Respirable fraction)	3 mg/m³ (Molybdenum)	ACGIH
Distillates (petroleum), hydrotreated light paraffinic	64742-55-8	TWA (Mist)	5 mg/m³	OSHA Z-1
		TWA (Inhalable fraction)	5 mg/m³	ACGIH
		TWA (Mist)	5 mg/m³	NIOSH REL
		ST (Mist)	10 mg/m ³	NIOSH REL

Engineering measures : Ensure adequate ventilation, especially in confined areas.

Minimize workplace exposure concentrations.

Personal protective equipment

Respiratory protection : General and local exhaust ventilation is recommended to

maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided

by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled

release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide

adequate protection.

Hand protection

MOLYKOTE® M Gear Oil Additive



Version **Revision Date:** SDS Number: Date of last issue: 05/02/2017 10/22/2018 1587878-00008 Date of first issue: 03/18/2015 4.0

Wash hands before breaks and at the end of workday. Remarks

Eye protection Wear the following personal protective equipment:

Safety glasses

Skin should be washed after contact. Skin and body protection

Hygiene measures Ensure that eye flushing systems and safety showers are

> located close to the working place. When using do not eat, drink or smoke. Wash contaminated clothing before re-use.

These precautions are for room temperature handling. Use at

elevated temperature or aerosol/spray applications may

require added precautions.

For further information regarding the use of silicones / organic oils in consumer aerosol applications, please refer to the guidance document regarding the use of these type of materials in consumer aerosol applications that has been developed by the silicone industry (www.SEHSC.com) or contact the Dow Chemical customer service group.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance liquid

Color dark gray

Odor slight

Odor Threshold No data available

рΗ No data available

Melting point/freezing point No data available

Initial boiling point and boiling

range

> 35 °C

Flash point 200 °C

Method: closed cup

No data available Evaporation rate

Flammability (solid, gas) Not applicable

Self-ignition The substance or mixture is not classified as pyrophoric. The

substance or mixture is not classified as self heating.

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower No data available

MOLYKOTE® M Gear Oil Additive



Version Revision Date: SDS Number: Date of last issue: 05/02/2017 4.0 10/22/2018 1587878-00008 Date of first issue: 03/18/2015

flammability limit

Vapor pressure : No data available

Relative vapor density : No data available

Relative density : 0.91

Solubility(ies)

Water solubility : No data available

Partition coefficient: n-

octanol/water

No data available

Autoignition temperature : No data available

Decomposition temperature : No data available

Viscosity

Viscosity, kinematic : 90 cSt

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Molecular weight : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not classified as a reactivity hazard.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reac-

tions

Can react with strong oxidizing agents.

Conditions to avoid : None known.

Incompatible materials : Oxidizing agents

Hazardous decomposition

products

No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation Skin contact Ingestion Eye contact

MOLYKOTE® M Gear Oil Additive



Version Revision Date: SDS Number: Date of last issue: 05/02/2017 4.0 10/22/2018 1587878-00008 Date of first issue: 03/18/2015

Acute toxicity

Not classified based on available information.

Ingredients:

Distillates (petroleum), solvent-dewaxed heavy paraffinic:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Method: OECD Test Guideline 401

Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 5.53 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Method: OECD Test Guideline 403

Assessment: The substance or mixture has no acute inhala-

tion toxicity

Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

Method: OECD Test Guideline 402

Remarks: Based on data from similar materials

Distillates (petroleum), hydrotreated heavy paraffinic:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Method: OECD Test Guideline 401

Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 5.53 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Method: OECD Test Guideline 403

Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

Method: OECD Test Guideline 402

Remarks: Based on data from similar materials

Distillates (petroleum), solvent refined heavy paraffinic:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Method: OECD Test Guideline 401

Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 5.53 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Method: OECD Test Guideline 403

Assessment: The substance or mixture has no acute inhala-

tion toxicity

Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

Method: OECD Test Guideline 402

Remarks: Based on data from similar materials

MOLYKOTE® M Gear Oil Additive



Version Revision Date: SDS Number: Date of last issue: 05/02/2017 4.0 10/22/2018 1587878-00008 Date of first issue: 03/18/2015

II

Molybdenum sulfide:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg

Method: OECD Test Guideline 401

Assessment: The substance or mixture has no acute oral tox-

icity

Acute inhalation toxicity : LC50 (Rat): > 2.82 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg

Method: OECD Test Guideline 402

Assessment: The substance or mixture has no acute dermal

toxicity

Distillates (petroleum), hydrotreated light paraffinic:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 4 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Assessment: The substance or mixture has no acute inhala-

tion toxicity

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

Remarks: Based on data from similar materials

Skin corrosion/irritation

Not classified based on available information.

Ingredients:

Distillates (petroleum), solvent-dewaxed heavy paraffinic:

Species: Rabbit

Result: No skin irritation

Remarks: Based on data from similar materials

Distillates (petroleum), hydrotreated heavy paraffinic:

Species: Rabbit

Result: No skin irritation

Remarks: Based on data from similar materials

Distillates (petroleum), solvent refined heavy paraffinic:

Species: Rabbit

Result: No skin irritation

Remarks: Based on data from similar materials

Molybdenum sulfide:

MOLYKOTE® M Gear Oil Additive



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 05/02/2017

 4.0
 10/22/2018
 1587878-00008
 Date of first issue: 03/18/2015

Species: Rabbit

Method: OECD Test Guideline 404

Result: No skin irritation

Distillates (petroleum), hydrotreated light paraffinic:

Species: Rabbit

Result: No skin irritation

Serious eye damage/eye irritation

Not classified based on available information.

Ingredients:

Distillates (petroleum), solvent-dewaxed heavy paraffinic:

Species: Rabbit

Result: No eye irritation

Method: OECD Test Guideline 405

Remarks: Based on data from similar materials

Distillates (petroleum), hydrotreated heavy paraffinic:

Species: Rabbit

Result: No eye irritation

Method: OECD Test Guideline 405

Remarks: Based on data from similar materials

Distillates (petroleum), solvent refined heavy paraffinic:

Species: Rabbit

Result: No eye irritation

Method: OECD Test Guideline 405

Remarks: Based on data from similar materials

Molybdenum sulfide:

Species: Rabbit

Result: No eye irritation

Method: OECD Test Guideline 405

Distillates (petroleum), hydrotreated light paraffinic:

Species: Rabbit

Result: No eye irritation

Respiratory or skin sensitization

Skin sensitization

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

MOLYKOTE® M Gear Oil Additive



Version Revision Date: SDS Number: Date of last issue: 05/02/2017 4.0 10/22/2018 1587878-00008 Date of first issue: 03/18/2015

Ingredients:

Distillates (petroleum), solvent-dewaxed heavy paraffinic:

Test Type: Buehler Test

Routes of exposure: Skin contact

Species: Guinea pig

Method: OECD Test Guideline 406

Result: negative

Remarks: Based on data from similar materials

Distillates (petroleum), hydrotreated heavy paraffinic:

Test Type: Buehler Test

Routes of exposure: Skin contact

Species: Guinea pig

Method: OECD Test Guideline 406

Result: negative

Remarks: Based on data from similar materials

Distillates (petroleum), solvent refined heavy paraffinic:

Test Type: Buehler Test

Routes of exposure: Skin contact

Species: Guinea pig

Method: OECD Test Guideline 406

Result: negative

Remarks: Based on data from similar materials

Molybdenum sulfide:

Test Type: Maximization Test Routes of exposure: Skin contact

Species: Guinea pig Result: negative

Distillates (petroleum), hydrotreated light paraffinic:

Test Type: Buehler Test

Routes of exposure: Skin contact

Species: Guinea pig

Method: OECD Test Guideline 406

Result: negative

Remarks: Based on data from similar materials

Germ cell mutagenicity

Not classified based on available information.

Ingredients:

Distillates (petroleum), solvent-dewaxed heavy paraffinic:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Method: OECD Test Guideline 471

Result: negative

Remarks: Based on data from similar materials

MOLYKOTE® M Gear Oil Additive



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 05/02/2017

 4.0
 10/22/2018
 1587878-00008
 Date of first issue: 03/18/2015

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay) Species: Mouse

Application Route: Intraperitoneal injection

Method: OECD Test Guideline 474

Result: negative

Remarks: Based on data from similar materials

Distillates (petroleum), hydrotreated heavy paraffinic:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay) Species: Mouse Result: negative

Remarks: Based on data from similar materials

Distillates (petroleum), solvent refined heavy paraffinic:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Method: OECD Test Guideline 471

Result: negative

Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay) Species: Mouse

Application Route: Intraperitoneal injection Method: OECD Test Guideline 474

Result: negative

Remarks: Based on data from similar materials

Molybdenum sulfide:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Method: OECD Test Guideline 471

Result: negative

Distillates (petroleum), hydrotreated light paraffinic:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

Remarks: Based on data from similar materials

Carcinogenicity

Not classified based on available information.

Ingredients:

Distillates (petroleum), solvent-dewaxed heavy paraffinic:

Species: Mouse

Application Route: Skin contact

MOLYKOTE® M Gear Oil Additive



Version Revision Date: SDS Number: Date of last issue: 05/02/2017 4.0 10/22/2018 1587878-00008 Date of first issue: 03/18/2015

Exposure time: 78 weeks

Method: OECD Test Guideline 451

Result: negative

Distillates (petroleum), solvent refined heavy paraffinic:

Species: Mouse

Application Route: Skin contact Exposure time: 78 weeks

Method: OECD Test Guideline 451

Result: negative

Remarks: Based on data from similar materials

Molybdenum sulfide:

Species: Rat

Application Route: Ingestion Exposure time: 232 days

Result: negative

IARC No ingredient of this product present at levels greater than or

equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

OSHA No component of this product present at levels greater than or

equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No ingredient of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

Reproductive toxicity

Not classified based on available information.

Ingredients:

Distillates (petroleum), solvent-dewaxed heavy paraffinic:

Effects on fertility : Test Type: Reproduction/Developmental toxicity screening

test

Species: Rat

Application Route: Ingestion

Result: negative

Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Embryo-fetal development

Species: Rat

Application Route: Skin contact Method: OECD Test Guideline 414

Result: negative

Remarks: Based on data from similar materials

Distillates (petroleum), hydrotreated heavy paraffinic:

Effects on fertility : Test Type: Reproduction/Developmental toxicity screening

test

MOLYKOTE® M Gear Oil Additive



Version Revision Date: SDS Number: Date of last issue: 05/02/2017 4.0 10/22/2018 1587878-00008 Date of first issue: 03/18/2015

Species: Rat

Application Route: Ingestion Method: OECD Test Guideline 421

Result: negative

Remarks: Based on data from similar materials

Distillates (petroleum), solvent refined heavy paraffinic:

Effects on fertility : Test Type: Reproduction/Developmental toxicity screening

test

Species: Rat

Application Route: Ingestion

Result: negative

Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Embryo-fetal development

Species: Rat

Application Route: Skin contact Method: OECD Test Guideline 414

Result: negative

Remarks: Based on data from similar materials

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Not classified based on available information.

Repeated dose toxicity

Ingredients:

Distillates (petroleum), solvent-dewaxed heavy paraffinic:

Species: Rabbit NOAEL: 1,000 mg/kg

Application Route: Skin contact Exposure time: 4 Weeks

Method: OECD Test Guideline 410

Remarks: Based on data from similar materials

Species: Rat

NOAEL: > 980 mg/m³

Application Route: inhalation (dust/mist/fume)

Exposure time: 4 Weeks

Remarks: Based on data from similar materials

Distillates (petroleum), solvent refined heavy paraffinic:

Species: Rabbit NOAEL: 1,000 mg/kg

Application Route: Skin contact Exposure time: 4 Weeks

Method: OECD Test Guideline 410

Remarks: Based on data from similar materials

MOLYKOTE® M Gear Oil Additive



Version Revision Date: SDS Number: Date of last issue: 05/02/2017 4.0 10/22/2018 1587878-00008 Date of first issue: 03/18/2015

Species: Rat

NOAEL: > 980 mg/m³

Application Route: inhalation (dust/mist/fume)

Exposure time: 4 Weeks

Remarks: Based on data from similar materials

Distillates (petroleum), hydrotreated light paraffinic:

Species: Rabbit NOAEL: 1,000 mg/kg

Application Route: Skin contact

Exposure time: 4 Weeks

Method: OECD Test Guideline 410

Remarks: Based on data from similar materials

Species: Rat

NOAEL: > 980 mg/m³

Application Route: inhalation (dust/mist/fume)

Exposure time: 4 Weeks

Remarks: Based on data from similar materials

Aspiration toxicity

Not classified based on available information.

Ingredients:

Distillates (petroleum), solvent-dewaxed heavy paraffinic:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

Distillates (petroleum), hydrotreated heavy paraffinic:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

Distillates (petroleum), solvent refined heavy paraffinic:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

Distillates (petroleum), hydrotreated light paraffinic:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Ingredients:

Distillates (petroleum), solvent-dewaxed heavy paraffinic:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 100 mg/l

Exposure time: 96 h

MOLYKOTE® M Gear Oil Additive



Version Revision Date: SDS Number: Date of last issue: 05/02/2017 4.0 10/22/2018 1587878-00008 Date of first issue: 03/18/2015

Method: OECD Test Guideline 203

Remarks: Based on data from similar materials

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 10,000 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Remarks: Based on data from similar materials

Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (green algae)): > 100

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Remarks: Based on data from similar materials

Toxicity to daphnia and other : aquatic invertebrates (Chron-

ic toxicity)

NOEC (Daphnia magna (Water flea)): 10 mg/l

Exposure time: 21 d

Method: OECD Test Guideline 211

Remarks: Based on data from similar materials

Toxicity to microorganisms : NOEC: > 1.93 mg/l

Exposure time: 10 min Method: DIN 38 412 Part 8

Remarks: Based on data from similar materials

Distillates (petroleum), hydrotreated heavy paraffinic:

Toxicity to fish : LL50 (Pimephales promelas (fathead minnow)): > 100 mg/l

Exposure time: 96 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 203

Remarks: Based on data from similar materials

Toxicity to daphnia and other :

aquatic invertebrates

EL50 (Daphnia magna (Water flea)): > 100 mg/l

Exposure time: 48 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 202

Remarks: Based on data from similar materials

Toxicity to algae : ErC50 (Pseudokirchneriella subcapitata (green algae)): > 100

mg/l

Exposure time: 72 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 201

Remarks: Based on data from similar materials

NOELR (Pseudokirchneriella subcapitata (green algae)): >

100 ma/l

Exposure time: 72 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 201

Remarks: Based on data from similar materials

Toxicity to daphnia and other :

aquatic invertebrates (Chron-

NOELR (Daphnia magna (Water flea)): > 1 mg/l

Exposure time: 21 d

MOLYKOTE® M Gear Oil Additive



Version Revision Date: SDS Number: Date of last issue: 05/02/2017 4.0 10/22/2018 1587878-00008 Date of first issue: 03/18/2015

ic toxicity) Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 211

Remarks: Based on data from similar materials

Toxicity to microorganisms : NOEC: > 1.93 mg/l

Exposure time: 10 min Method: DIN 38 412 Part 8

Remarks: Based on data from similar materials

Distillates (petroleum), solvent refined heavy paraffinic:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 100 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Remarks: Based on data from similar materials

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 10,000 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Remarks: Based on data from similar materials

Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (green algae)): > 100

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Remarks: Based on data from similar materials

Toxicity to daphnia and other :

aquatic invertebrates (Chron-

ic toxicity)

NOEC (Daphnia magna (Water flea)): 10 mg/l

Exposure time: 21 d

Method: OECD Test Guideline 211

Remarks: Based on data from similar materials

Toxicity to microorganisms : NOEC: > 1.93 mg/l

Exposure time: 10 min Method: DIN 38 412 Part 8

Remarks: Based on data from similar materials

Molybdenum sulfide:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 644.2 mg/l

Exposure time: 96 h

Remarks: Based on data from similar materials

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 130.9 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Remarks: Based on data from similar materials

Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (green algae)): 289.2

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Remarks: Based on data from similar materials

Toxicity to fish (Chronic tox- : NOEC (Oncorhynchus mykiss (rainbow trout)): > 17 mg/l

MOLYKOTE® M Gear Oil Additive



Version **Revision Date:** SDS Number: Date of last issue: 05/02/2017 10/22/2018 1587878-00008 Date of first issue: 03/18/2015 4.0

icity) Exposure time: 12 Months

Remarks: Based on data from similar materials

NOEC (Ceriodaphnia dubia (water flea)): 156.5 mg/l

Toxicity to daphnia and other: aquatic invertebrates (Chron-

Exposure time: 21 d

ic toxicity)

Remarks: Based on data from similar materials

Toxicity to microorganisms

NOEC: > 950 mg/l Exposure time: 17 d

Remarks: Based on data from similar materials

Distillates (petroleum), hydrotreated light paraffinic:

Toxicity to daphnia and other: LL50 (Daphnia magna (Water flea)): > 10,000 mg/l

aquatic invertebrates

Exposure time: 48 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 202

NOEC (Pseudokirchneriella subcapitata (green algae)): > 100 Toxicity to algae

mg/l

Exposure time: 72 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 201

Toxicity to daphnia and other:

aquatic invertebrates (Chron-

NOEC (Daphnia magna (Water flea)): 10 mg/l Exposure time: 21 d

ic toxicity)

Test substance: Water Accommodated Fraction

Persistence and degradability

Ingredients:

Distillates (petroleum), solvent-dewaxed heavy paraffinic:

Biodegradability Result: Not readily biodegradable.

> Biodegradation: 2 - 8 % Exposure time: 28 d

Method: OECD Test Guideline 301B

Distillates (petroleum), hydrotreated heavy paraffinic:

Result: Not readily biodegradable. Biodegradability

> Biodegradation: 31 % Exposure time: 28 d

Method: OECD Test Guideline 301F

Distillates (petroleum), solvent refined heavy paraffinic:

Biodegradability Result: Not readily biodegradable.

Biodegradation: 2 - 4 % Exposure time: 28 d

Method: OECD Test Guideline 301B

Distillates (petroleum), hydrotreated light paraffinic:

Biodegradability Result: Not readily biodegradable.

MOLYKOTE® M Gear Oil Additive



Version Revision Date: SDS Number: 4.0 10/22/2018 1587878-00008

Date of last issue: 05/02/2017 Date of first issue: 03/18/2015

Biodegradation: 31 % Exposure time: 28 d

Method: OECD Test Guideline 301F

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Resource Conservation and

Recovery Act (RCRA)

This product has been evaluated for RCRA characteristics and does not meet the criteria of hazardous waste if discarded

in its purchased form.

Waste from residues : Dispose of in accordance with local regulations.

Contaminated packaging : Empty containers should be taken to an approved waste

handling site for recycling or disposal.

If not otherwise specified: Dispose of as unused product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

49 CFR

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know

CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

MOLYKOTE® M Gear Oil Additive



Version Revision Date: SDS Number: Date of last issue: 05/02/2017 4.0 10/22/2018 1587878-00008 Date of first issue: 03/18/2015

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : No SARA Hazards

SARA 313 : This material does not contain any chemical components with

known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

US State Regulations

Pennsylvania Right To Know

Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7
Distillates (petroleum), solvent refined heavy paraffinic	64741-88-4
Molybdenum sulfide	1317-33-5
Distillates (petroleum), hydrotreated light paraffinic	64742-55-8

California Prop. 65

This product does not contain any chemicals known to the State of California to cause cancer, birth, or any other reproductive defects.

California List of Hazardous Substances

Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7
Distillates (petroleum), solvent refined heavy paraffinic	64741-88-4
Molybdenum sulfide	1317-33-5
Distillates (petroleum), hydrotreated light paraffinic	64742-55-8

California Permissible Exposure Limits for Chemical Contaminants

Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7
Distillates (petroleum), solvent refined heavy paraffinic	64741-88-4
Molybdenum sulfide	1317-33-5
Distillates (petroleum), hydrotreated light paraffinic	64742-55-8

The ingredients of this product are reported in the following inventories:

TSCA : All chemical substances in this product are either listed on the

TSCA Inventory or are in compliance with a TSCA Inventory

exemption.

AICS : All ingredients listed or exempt.

ENCS/ISHL : All components are listed on ENCS/ISHL or exempted from

inventory listing.

PICCS : All ingredients listed or exempt.

DSL : All chemical substances in this product comply with the CEPA

1999 and NSNR and are on or exempt from listing on the

Canadian Domestic Substances List (DSL).

MOLYKOTE® M Gear Oil Additive




Version Revision Date: SDS Number: Date of last issue: 05/02/2017 4.0 10/22/2018 1587878-00008 Date of first issue: 03/18/2015

SECTION 16. OTHER INFORMATION

Further information

NFPA:



Special hazard.

HMIS® IV:



HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
NIOSH REL : USA. NIOSH Recommended Exposure Limits

OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Lim-

its for Air Contaminants

ACGIH / TWA : 8-hour, time-weighted average

NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour

workday during a 40-hour workweek

NIOSH REL / ST : STEL - 15-minute TWA exposure that should not be exceeded

at any time during a workday

OSHA Z-1 / TWA : 8-hour time weighted average

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC -International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Pre-

MOLYKOTE® M Gear Oil Additive



Version Revision Date: SDS Number: Date of last issue: 05/02/2017 4.0 10/22/2018 1587878-00008 Date of first issue: 03/18/2015

vention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Sources of key data used to compile the Material Safety

Data Sheet

Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agen-

cy, http://echa.europa.eu/

Revision Date : 10/22/2018

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8