


SAFETY DATA SHEET

SECTION 1 : IDENTIFICATION

Product Name: SW420182
Product Code: 3025
SDS Manufacturer Number: 3025LTDQTY
Product Description: Presaturated wipes containing Methyl Ethyl Ketone
Manufacturer Name: Contec, Inc.
Address: 525 Locust Grove
Spartanburg, South Carolina 29303
USA
Website: www.contecinc.com
General Phone Number: 1-864-503-8333
Emergency Phone Number: Chemtrec® US: 1-800-424-9300 International: 1-703-527-3887
SDS Creation Date: September 22, 2014
SDS Revision Date: September 22, 2014



HMIS	
Health Hazard	2*
Fire Hazard	3
Reactivity	0
Personal Protection	X

* Chronic Health Effects

SECTION 2 : HAZARD(S) IDENTIFICATION

GHS Pictograms:



Signal Word: DANGER!

GHS Class: Flammable Liquid, Category 2..
Eye Irritant, Category 2..
Specific Target Organ Toxicity, Single Exposure, Category 3.

Hazard Statements: Highly flammable liquid and vapor.
Causes serious eye irritation.
May cause drowsiness or dizziness.

Precautionary Statements: Keep away from heat/sparks/open flames — No smoking.
In case of fire: Use dry chemical, carbon dioxide to extinguish small fires. Use water for large fires.
Wear protective gloves, protective clothing, and eye protection.
Avoid breathing vapors.
Store in a well-ventilated place. Keep container tightly closed.
IF IN EYES: Rinse cautiously with water for several minutes.
If eye irritation persists: Get medical advice/attention.
IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
Call a POISON CENTER or doctor/physician if you feel unwell.
IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
Dispose of contents/container in accordance with Local, State, Federal and Provincial regulations.

Emergency Overview: DANGER! Flammable. Irritant.

Route of Exposure: Eyes. Skin. Inhalation.

Potential Health Effects:

Eye: Can cause moderate irritation, burning sensation, tearing, redness, and swelling. Overexposure may cause lacrimation, conjunctivitis, corneal damage and permanent injury.

Skin: Can cause skin irritation; itching, redness, rashes, hives, burning, and swelling.

Inhalation: Respiratory tract irritant. High concentration may cause dizziness, headache, and anesthetic effects.

Ingestion: Causes irritation, a burning sensation of the mouth, throat and gastrointestinal tract and abdominal pain.

Chronic Health Effects: Prolonged skin contact may lead to burning associated with severe reddening, swelling, and possible tissue destruction.

Signs/Symptoms: Overexposure can cause headaches, dizziness, nausea, and vomiting.

Target Organs: Eyes. Skin. Respiratory system. Digestive system. Central nervous system.

Aggravation of Pre-Existing Conditions: Individuals with pre-existing skin disorders, asthma, allergies or known sensitization may be more susceptible to the effects of this product.

SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS#	Ingredient Percent	EC Num.
---------------	------	--------------------	---------

SECTION 4 : FIRST AID MEASURES

Eye Contact:	Immediately flush eyes with plenty of water for at least 15 to 20 minutes. Ensure adequate flushing of the eyes by separating the eyelids with fingers. Get immediate medical attention.
Skin Contact:	Immediately wash skin with plenty of soap and water for 15 to 20 minutes, while removing contaminated clothing and shoes. Get medical attention if irritation develops or persists.
Inhalation:	If inhaled, remove to fresh air. If not breathing, give artificial respiration or give oxygen by trained personnel. Seek immediate medical attention.
Ingestion:	If swallowed, do NOT induce vomiting. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person.
Other First Aid:	Due to possible aspiration into the lungs, DO NOT induce vomiting if ingested. Provide a glass of water to dilute the material in the stomach. If vomiting occurs naturally, have the person lean forward to reduce the risk of aspiration.

SECTION 5 : FIRE FIGHTING MEASURES

Flammable Properties:	Flammable. Flammable liquid. Class I B.
Flash Point:	-5°C (23°F)
Flash Point Method:	Tag closed cup. (TCC)
Auto Ignition Temperature:	Not determined.
Lower Flammable/Explosive Limit:	1.8%
Upper Flammable/Explosive Limit:	11.5%
Fire Fighting Instructions:	Evacuate area of unprotected personnel. Use cold water spray to cool fire exposed containers to minimize risk of rupture. Do not enter confined fire space without full protective gear. If possible, contain fire run-off water.
Extinguishing Media:	Use carbon dioxide (CO2) or dry chemical when fighting fires involving this material.
Protective Equipment:	In the event of a fire, wear Self-Contained Breathing Apparatus (SCBA), approved or in accordance to NFPA, NIOSH, and/or European Standard EN 137 guidelines or equivalent and full protective gear.
NFPA Ratings:	
NFPA Health:	2
NFPA Flammability:	3
NFPA Reactivity:	0

SECTION 6 : ACCIDENTAL RELEASE MEASURES

Personal Precautions:	Evacuate area and keep unnecessary and unprotected personnel from entering the spill area.
Environmental Precautions:	Avoid runoff into storm sewers, ditches, and waterways. Comply with all government regulations on reporting releases.
Spill Cleanup Measures:	Absorb spill with inert material (e.g., dry sand or earth), then place in a chemical waste container. Provide ventilation. Collect spill with a non-sparking tool. Place into a suitable container for disposal. Clean up spills immediately observing precautions in the protective equipment section. After removal, flush spill area with soap and water to remove trace residue. Flammable, eliminate ignition sources. Vapors can form an ignitable mixture with air. Vapors can flow along surfaces to distant ignition sources and flash back. Ventilate area. Use proper personal protective equipment as listed in Section 8.
Methods for containment:	Spills are very unlikely, because the wiper fabric has absorbed the liquid solvent solution. In the event of a spill, contain with an inert absorbent.
Other Precautions:	Pump or shovel to storage/salvage vessels.

SECTION 7 : HANDLING and STORAGE

Handling:	Use with adequate ventilation. Avoid breathing vapor, aerosol or mist. Do not reuse containers without proper cleaning or reconditioning.
Storage:	Store in a cool, dry, well ventilated area away from sources of heat, combustible materials, direct sunlight, and incompatible substances. Keep container tightly closed when not in use.
Special Handling Procedures:	Hazardous liquid or vapor residue may remain in emptied container. Do not reuse, heat, burn, pressurize, cut, weld, braze, solder, drill, grind, expose to sparks, flame, or ignition sources of empty containers without proper commercial cleaning or reconditioning.
Hygiene Practices:	Wash thoroughly after handling.

SECTION 8: EXPOSURE CONTROLS, PERSONAL PROTECTION

Engineering Controls:	Use appropriate engineering control such as process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Good general
------------------------------	---

ventilation should be sufficient to control airborne levels. Where such systems are not effective wear suitable personal protective equipment, which performs satisfactorily and meets OSHA or other recognized standards. Consult with local procedures for selection, training, inspection and maintenance of the personal protective equipment.

- Eye/Face Protection:** Safety glasses with side shields must be worn at all times. If splash hazard exists, wear chemical splash goggles and/or face shield.
- Skin Protection Description:** Wear appropriate protective gloves and other protective apparel to prevent skin contact. Consult manufacturer's data for permeability data.
- Respiratory Protection:** Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced. Comply with the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149 Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection.
- Other Protective:** Facilities storing or utilizing this material should be equipped with an eyewash and a deluge shower safety station.
- PPE Pictograms:**



EXPOSURE GUIDELINES

methyl ethyl ketone :

- Guideline ACGIH:** TLV-TWA: 200 ppm
TLV-STEL: 300 ppm
- Guideline OSHA:** PEL-TWA: 200 ppm

SECTION 9 : PHYSICAL and CHEMICAL PROPERTIES

- Physical State Appearance:** Mobile Liquid..
- Color:** colourless.
- Odor:** Pungent.
- Boiling Point:** 175°F (79.4°C)
- Melting Point:** -124°F (-86.6°C)
- Specific Gravity:** 0.81
- Solubility:** APPRECIABLE.
- Vapor Density:** 2.5 (air = 1)
- Vapor Pressure:** 70.9 mmHg @68°F
- Percent Volatile:** 100
- Evaporation Rate:** 3.8 (butyl acetate = 1)
- pH:** Not determined.
- Molecular Formula:** Mixture
- Molecular Weight:** Mixture
- Flash Point:** -5°C (23°F)
- Flash Point Method:** Tag closed cup. (TCC)
- Auto Ignition Temperature:** Not determined.
- VOC Content:** 810 g/L
- Percent Solids by Weight** 0

SECTION 10 : STABILITY and REACTIVITY

- Chemical Stability:** Stable under normal temperatures and pressures.
- Hazardous Polymerization:** Not reported.
- Conditions to Avoid:** Extreme heat, sparks, and open flame. Incompatible materials, oxidizers and oxidizing conditions.
- Incompatible Materials:** Oxidizing agents. Strong acids and alkalis.

SECTION 11 : TOXICOLOGICAL INFORMATION

methyl ethyl ketone :

- Eye:** Eye - Human Standard Draize test.: 350 ppm
Eye - Rabbit Standard Draize test.: 80 mg
- Skin:** Administration onto the skin - Rabbit Open irritation test: 14 mg/24H [Mild]
Administration onto the skin - Rabbit Standard Draize test.: 402 mg/24H [Mild]
Administration onto the skin - Rabbit LD50: 6480 mg/kg [Details of toxic effects not reported other than lethal dose value]
- Inhalation:** Inhalation - Rat LC50: 23500 mg/m³ [Details of toxic effects not reported other than lethal dose value]
Inhalation - Mouse LC50: 32 gm/m³/4H [Details of toxic effects not reported other than lethal dose

value]

Ingestion: Oral - Rat LD50: 2737 mg/kg [Details of toxic effects not reported other than lethal dose value]
Oral - Mouse LD50: 3000 mg/kg [Details of toxic effects not reported other than lethal dose value]

SECTION 12 : ECOLOGICAL INFORMATION

Ecotoxicity: No ecotoxicity data was found for the product.
Environmental Fate: No environmental information found for this product.

SECTION 13 : DISPOSAL CONSIDERATIONS

Waste Disposal: Consult with the US EPA Guidelines listed in 40 CFR Part 261.3 or the EU Directive 2008/98/EC on waste for the classifications of hazardous waste prior to disposal. Furthermore, consult with your state, local, or provincial waste requirements or guidelines, if applicable, to ensure compliance. Arrange disposal in accordance to the EPA and/or state and local guidelines.
RCRA Number: U159, D001, D035
Important Disposal Information: DANGER! Rags, steel wool and waste soaked with this product may spontaneously catch fire if improperly discarded or stored. To avoid a spontaneous combustion fire, immediately after use, place rags, steel wool or waste in a sealed, water-filled, metal container.

SECTION 14 : TRANSPORT INFORMATION

DOT Shipping Name: Solids Containing Flammable Liquid, n.o.s. (Ethyl methyl ketone) (Limited Quantity)
DOT Hazard Class: 4.1
DOT Packing Group: II
IATA Shipping Name: Solids Containing Flammable Liquid, n.o.s. (Ethyl methyl ketone)
IATA Hazard Class: 4.1
IATA Packing Group: II
IMDG UN Number: UN3175 (Limited Quantity)
IMDG Shipping Name: Solids Containing Flammable Liquid, n.o.s. (Ethyl methyl ketone) (Limited Quantity)
IMDG Hazard Class: 4.1
IMDG Packing Group: II
Marine Pollutant: No.

SECTION 15 : REGULATORY INFORMATION

methyl ethyl ketone :

TSCA Inventory Status: Listed
Canada DSL: Listed
EC Number: 201-159-0
Canadian Regulations: WHMIS Hazard Class(es): B2
All components of this product are on the Canadian Domestic Substances List.

WHMIS Pictograms:



SECTION 16 : ADDITIONAL INFORMATION

HMIS Ratings:

HMIS Health Hazard: 2*
HMIS Fire Hazard: 3
HMIS Reactivity: 0
HMIS Personal Protection: X

SDS Creation Date: September 22, 2014
SDS Revision Date: September 22, 2014
MSDS Author: Actio Corporation

Disclaimer: The information provided in this Safety Data Sheet is correct to our knowledge at the date of its revision. The information given only describes the products with regard to safety arrangements and is not to be considered as a warranty or quality specification and does not constitute a legal relationship. The information contained in this Safety Data Sheet relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

