# Safety Data Sheet SKILCRAFT®AERO CLEAN

**SDS Revision Date:** 

08/23/2018



## 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Identity AERO CLEAN

Alternate Names Specification: A-A-59921, Class 1A

LHB Part Number: 0864---002

National Stock Number: 6850-00-005-5305

CAGE Code: 0FTT5

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended useSee product label.Application MethodSee product label.

1.3. Details of the supplier of the safety data sheet

Company Name LHB Industries

8833 Fleischer Place Berkeley, MO 63134

**Emergency** 

24 hour Emergency Telephone No. (800) 633-8253 (PERS)

Customer Service: LHB Industries (314) 423-4333

## 2. Hazard identification of the product

### 2.1. Classification of the substance or mixture

Flam. Aerosol 1;H222 Extremely flammable aerosol.

Press. Gas;H280 Contains gas under pressure; may explode if heated.

#### 2.2. Label elements

Using the Toxicity Data listed in section 11 and 12 the product is labeled as follows.



**Danger** 

**SDS Revision Date:** 

08/23/2018



H222 Extremely flammable aerosol.

H280 Contains gas under pressure; may explode if heated.

## [Prevention]:

No GHS prevention statements

P210 Keep away from heat / sparks / open flames / hot surfaces - No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Pressurized container: Do not pierce or burn, even after use.

## [Response]:

No GHS response statements

## [Storage]:

P410+412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C / 122 °F.

#### [Disposal]:

No GHS disposal statements

## 3. Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of the relevant State and Federal Hazardous Substances regulations.

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
Petroleum gases, liquefied, sweetened CAS Number: 0068476-86-8		Press. Gas;H280 Flam. Gas 1;H220	[1]
Solvent naphtha (petroleum), heavy aromatic CAS Number: 0064742-94-5	1.0 - 10	Asp. Tox. 1;H304	[1]

<sup>[1]</sup> Substance classified with a health or environmental hazard.

## 4. First aid measures

#### 4.1. Description of first aid measures

General Move victim to fresh air.

Call 911 or emergency medical service if deemed necessary.

Give artificial respiration if victim is not breathing.

Administer oxygen if breathing is difficult.

<sup>[2]</sup> Substance with a workplace exposure limit.

<sup>[3]</sup> PBT-substance or vPvB-substance.
\*The full texts of the phrases are shown in Section 16.

**SDS Revision Date:** 

08/23/2018



Remove and isolate contaminated clothing and shoes.

In case of contact with liquefied gas, thaw frosted parts with lukewarm water.

Keep victim warm and quiet.

Ensure that medical personnel are aware of the material(s) involved and take precautions

to protect themselves.

**Inhalation** Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, give

artificial respiration. If unconscious place in the recovery position and obtain immediate

medical attention. Give nothing by mouth.

Eyes Irrigate copiously with clean water for at least 15 minutes, holding the eyelids apart and

seek medical attention.

**Skin** Remove and isolate contaminated clothing and shoes. Clothing frozen to the skin should

be thawed before being removed. In case of contact with liquefied gas, thaw frosted parts

with lukewarm water.

**Ingestion** If swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

#### 4.2. Most important symptoms and effects, both acute and delayed

Overview

Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage. See section 2 for further details.

# 5. Fire-fighting measures

### 5.1. Extinguishing media

Carbon Dioxide, Dry Chemical, Foam

#### 5.2. Special hazards arising from the substance or mixture

Hazardous decomposition: High temperatures and fires may produce such toxic substances as carbon monoxide and carbon dioxide.

Keep away from heat / sparks / open flames / hot surfaces - No smoking.

Do not spray on an open flame or other ignition source.

08/23/2018

SDS Revision Date:



Pressurized container: Do not pierce or burn, even after use.

### 5.3. Advice for fire-fighters

Wear positive pressure self-contained breathing apparatus (SCBA).

Wear chemical protective clothing that is specifically recommended by the manufacturer. It may provide little or no thermal protection.

Structural firefighters' protective clothing will only provide limited protection.

Some may burn but none ignite readily.

Containers may explode when heated.

Ruptured cylinders may rocket.

Vapors may cause dizziness or asphyxiation without warning.

Vapors from liquefied gas are initially heavier than air and spread along ground.

Contact with gas or liquefied gas may cause burns, severe injury and/or frostbite.

Fire may produce irritating, corrosive and/or toxic gases.

ERG Guide No. 126

## 6. Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

Do not touch or walk through spilled material.

Stop leak if you can do it without risk.

Do not direct water at spill or source of leak.

Use water spray to reduce vapors or divert vapor cloud drift. Avoid allowing water runoff to contact spilled material. If possible, turn leaking containers so that gas escapes rather than liquid.

Prevent entry into waterways, sewers, basements or confined areas.

Allow substance to evaporate.

Ventilate the area.

### 6.2. Environmental precautions

Do not allow spills to enter drains or waterways.

Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

#### 6.3. Methods and material for containment and cleaning up

Stay upwind.

Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks).

Keep out of low areas.

Ventilate closed spaces before entering.

## 7. Handling and storage

**SDS Revision Date:** 

08/23/2018



## 7.1. Precautions for safe handling

See section 2 for further details. - [Prevention]:

## 7.2. Conditions for safe storage, including any incompatibilities

Handle containers carefully to prevent damage and spillage.

Store this product below 120°F, in a cool, dry, well ventilated area away from heat, sparks, flame, oxidizers and out of direct sunlight.

Incompatible materials: Strong oxidizing agents and acids.

See section 2 for further details. - [Storage]:

## 7.3. Specific end use(s)

No data available.

## 8. Exposure controls and personal protection

## 8.1. Control parameters

#### **Exposure**

CAS No.	Ingredient	Source	Value
0064742-94-5 Solvent naphtha (petroleum), heavy	OSHA	No Established Limit	
	aromatic	ACGIH	No Established Limit
		NIOSH	No Established Limit
	Supplier	No Established Limit	
0068476-86-8	Petroleum gases, liquefied, sweetened	OSHA	No Established Limit
	ACGIH	No Established Limit	
		NIOSH	No Established Limit
		Supplier	No Established Limit

## **Carcinogen Data**

CAS No.	Ingredient	Source	Value
0064742-94-5	Solvent naphtha (petroleum),	OSHA	Select Carcinogen: No
	heavy aromatic	NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
068476-86-8	Petroleum gases, liquefied,	OSHA	Select Carcinogen: No
sweetened		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;

SDS Revision Date:

08/23/2018

8.2. Exposure controls

**Respiratory** If workers are exposed to concentrations above the exposure limit they must use the

appropriate, certified respirators.

**Eyes** Wear safety eyewear, e.g. safety spectacles, goggles or visors to protect against the

splash of liquids.

**Skin** Overalls which cover the body, arms and legs should be worn. Skin should not be exposed.

All parts of the body should be washed after contact.

**Engineering Controls** Provide adequate ventilation. Where reasonably practicable this should be achieved by the

use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and any vapor below occupational exposure limits

suitable respiratory protection must be worn.

using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

See section 2 for further details. - [Prevention]:

# 9. Physical and chemical properties

Appearance Milky white Liquid

**Odor** Solvent

Odor threshold Not Measured

**pH** 8-10

Melting point / freezing point Not Measured

Initial boiling point and boiling range

Not Measured Nonflammable (ASTM D3065)

Flash Point slower than ether

**Evaporation rate (Ether = 1)** Flam. Aerosol 1; H222 Extremely flammable aerosol.

Flammability (solid, gas)

Lower Explosive Limit: ND

Upper/lower flammability or explosive limits

Upper Explosive Limit: ND

Vapor pressure (Pa) Not Measured

Vapor Density >1

Specific Gravity 0.935 (7.94 lb/gal)

Solubility in Water Emulsifiable
Partition coefficient n-octanol/water (Log Not Measured
Kow) Auto-ignition temperature Not Measured
Decomposition temperature Not Measured
Viscosity (cSt) Not Measured

**SDS Revision Date:** 

08/23/2018



**VOC %** 14.4% by wt. (137.8 g/L)

Maximum Incremental ReactivityNot MeasuredHAPS (Ibs/gal)Not DeterminedHAPS (Ibs/gal of Solids)Not Determined

HAPS (lbs/lb of Solids)% Volatile (by volume)Not DeterminedNot Measured

9.2. Other information

No other relevant information.

## 10. Stability and reactivity

## 10.1. Reactivity

Hazardous Polymerization will not occur.

#### 10.2. Chemical stability

Stable under normal circumstances.

## 10.3. Possibility of hazardous reactions

No data available.

## 10.4. Conditions to avoid

Excessive heat and open flame.

#### 10.5. Incompatible materials

Strong oxidizing agents and acids.

### 10.6. Hazardous decomposition products

High temperatures and fires may produce such toxic substances as carbon monoxide and carbon dioxide.

## 11. Toxicological information

#### **Acute toxicity**

Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage.

**SDS Revision Date:** 

08/23/2018



Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LD50, mg/L/4hr	Inhalation Dust/Mist LD50, mg/L/4hr	Inhalation Gas LD50, ppm
Petroleum gases, liquefied, sweetened - (68476-86-8)	No data available	No data available	No data available	No data available	No data available
Solvent naphtha (petroleum), heavy aromatic - (64742-94-5)	5,000.00, Rat - Category: 5	2,000.00, Rabbit - Category: 4	No data available	No data available	No data available

Note: When no route specific LD50 data is available for an acute toxin, the converted acute toxicity point estimate was used in the calculation of the product's ATE (Acute Toxicity Estimate).

Classification	Category	Hazard Description
Acute toxicity (oral)		Not Applicable
Acute toxicity (dermal)		Not Applicable
Acute toxicity (inhalation)		Not Applicable
Skin corrosion/irritation		Not Applicable
Serious eye damage/irritation		Not Applicable
Respiratory sensitization		Not Applicable
Skin sensitization		Not Applicable
Germ cell mutagenicity		Not Applicable
Carcinogenicity		Not Applicable
Reproductive toxicity		Not Applicable
STOT-single exposure		Not Applicable
STOT-repeated exposure		Not Applicable
Aspiration hazard		Not Applicable

# 12. Ecological information

## 12.1. Toxicity

No additional information provided for this product. See Section 3 for chemical specific data.

## **Aquatic Ecotoxicity**

Ingredient	96 hr LC50 fish,	48 hr EC50 crustacea,	ErC50 algae,	
	mg/l	mg/l	mg/l	
Petroleum gases, liquefied, sweetened - (68476-86-8)	Not Available	Not Available	Not Available	

SDS Revision Date:

08/23/2018



Solvent naphtha (petroleum), heavy aromatic - (64742-	45.00, Pimephales	12.00, Daphnia magna	2.50 (72 hr), Skeletonema
94-5)	promelas		costatum

#### 12.2. Persistence and degradability

There is no data available on the preparation itself.

### 12.3. Bioaccumulative potential

Not Measured

### 12.4. Mobility in soil

No data available.

#### 12.5. Results of PBT and vPvB assessment

This product contains no PBT/vPvB chemicals.

#### 12.6. Other adverse effects

No data available.

## 13. Disposal considerations

#### 13.1. Waste treatment methods

Do not allow into drains or water courses. Wastes and emptied containers should be disposed of in accordance with regulations made under the Control of Pollution Act and the Environmental Protection Act.

Using information provided in this data sheet advice should be obtained from the Waste Regulation Authority, whether the special waste regulations apply.

# 14. Transport information

	DOT (Domestic Surface Transportation)	IMO / IMDG (Ocean Transportation)	ICAO/IATA
14.1. UN number	UN1950	UN1950	UN1950
14.2. UN proper shipping name	UN1950, Aerosols, Limited Quantity, 2.1,	Aerosols, Limited Quantity	Aerosols, Limited Quantity
14.3. Transport hazard class(es)	DOT Hazard Class: 2.1	IMDG: 2.1	Air Class: 2.1
14.4. Packing group	Not Applicable	Not Applicable	Not Applicable
14.5. Environmental hazar	rds		

**IMDG** Marine Pollutant: Yes

## 14.6. Special precautions for user

No further information



SDS Revision Date: 08/23/2018

## 15. Regulatory information

Regulatory Overview The regulatory data in Section 15 is not intended to be all-inclusive, only selected

regulations are represented.

Toxic Substance Control Act (TSCA) All components of this material are either listed or exempt from listing on the TSCA

Inventory.

WHMIS Classification A B5

US EPA Tier II Hazards Fire: No

Sudden Release of Pressure: Yes

Reactive: No

Immediate (Acute): No Delayed (Chronic): No

EPCRA 311/312 Chemicals and RQs:

(No Product Ingredients Listed)

**EPCRA 302 Extremely Hazardous:** 

(No Product Ingredients Listed)

**EPCRA 313 Toxic Chemicals:** 

(No Product Ingredients Listed)

Proposition 65 - Carcinogens (>0.0%):

(No Product Ingredients Listed)

Proposition 65 - Developmental Toxins (>0.0%):

(No Product Ingredients Listed)

Proposition 65 - Female Repro Toxins (>0.0%):

(No Product Ingredients Listed)

**Proposition 65 - Male Repro Toxins (>0.0%):** 

(No Product Ingredients Listed)

N.J. RTK Substances (>1%):

(No Product Ingredients Listed)

Penn RTK Substances (>1%):

(No Product Ingredients Listed)

**SDS Revision Date:** 

08/23/2018



## 16. Other information

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

H220 Extremely flammable gas.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

IMPORTANT NOTE: This information is furnished without warranty, expressed or implied, as to accuracy or completeness. The information is obtained from various sources including the manufacturer and other third party sources. The information may not be valid under all conditions nor if this material is used in combination with other materials or any process. Final determination of suitability of any material is the sole responsibility of the user.

**End of Document**