SAFETY DATA SHEET



Date of issue/Date of revision19 June 2021Version 20

Section 1. Identification		
Product name	: PR 1440 B 1 Part A	
Product code	: PR 1440 B 1 Part A	
Other means of identification	: Not available.	
Product type	: Liquid.	
Relevant identified uses o	of the substance or mixture and uses advised against	
Product use	: Industrial applications.	
Use of the substance/ mixture	: Sealants	
Uses advised against	: Not applicable.	
Manufacturer	: PPG Aerospace PRC-DeSoto 12780 San Fernando Road Sylmar, CA 91342	
<u>Emergency telephone</u> <u>number</u>	Phone: 818 362 6711 : (412) 434-4515 (U.S.) (514) 645-1320 (Canada) 01-800-00-21-400 (Mexico)	

Section 2. Hazards identification

OSHA/HCS status	 This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).
Classification of the substance or mixture	: ACUTE TOXICITY (oral) - Category 4 ACUTE TOXICITY (inhalation) - Category 4 CARCINOGENICITY - Category 2 TOXIC TO REPRODUCTION - Category 2 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2
	Percentage of the mixture consisting of ingredient(s) of unknown acute toxicity: 6.3% (oral), 94.9% (dermal), 48.3% (inhalation)
GHS label elements	
Hazard pictograms	
Signal word	: Warning

Product name PR 1440 B 1 Part A

Section 2. Hazards identification

Hazard statements	 Harmful if swallowed or if inhaled. Suspected of causing cancer. Suspected of damaging fertility or the unborn child. May cause damage to organs through prolonged or repeated exposure. (brain)
Precautionary statements	
Prevention	: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing and eye or face protection. Use only outdoors or in a well-ventilated area. Do not breathe vapor. Do not eat, drink or smoke when using this product. Wash thoroughly after handling.
Response	: IF exposed or concerned: Get medical advice or attention. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor if you feel unwell. IF SWALLOWED: Call a POISON CENTER or doctor if you feel unwell. Rinse mouth.
Storage	: Store locked up.
Disposal	: Dispose of contents and container in accordance with all local, regional, national and international regulations.
Supplemental label elements	: Sanding and grinding dusts may be harmful if inhaled. Avoid contact with skin and clothing. Wash thoroughly after handling. Emits toxic fumes when heated.
Hazards not otherwise classified	: Oxidising potential : Contact with combustible material may cause fire. Keep away from clothing, incompatible materials and combustible materials. This material increases the risk of fire and may aid combustion. Prolonged or repeated contact may dry skin and cause irritation.

Section 3. Composition/information on ingredients

Substance/mixture	: Mixture
Product name	: PR 1440 B 1 Part A

Ingredient name	%	CAS number
manganese dioxide	≥20 - ≤50	1313-13-9
Terphenyl, hydrogenated	≥20 - ≤50	61788-32-7
Zeolites	≥5.0 - ≤10	1318-02-1
Polyphenyls, quater- and higher, partially hydrogenated	≥5.0 - ≤10	68956-74-1
Talc, not containing asbestiform fibers	≥1.0 - ≤5.0	14807-96-6
carbon black	≥1.0 - ≤5.0	1333-86-4
terphenyl	≥1.0 - ≤5.0	26140-60-3
magnesium carbonate	≥1.0 - ≤5.0	546-93-0
1,3-diphenylguanidine	≥1.0 - ≤4.6	102-06-7

SUB codes represent substances without registered CAS Numbers.

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

If ingestion, irritation, any type of overexposure or symptoms of overexposure occur during or persists after use of this product, contact a POISON CONTROL CENTER, EMERGENCY ROOM OR PHYSICIAN immediately; have Safety Data Sheet information available. Never give anything by mouth to an unconscious or convulsing person. Description of necessary first aid measures

Eye contact	: Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids
Inhalation	 apart for at least 10 minutes and seek immediate medical advice. Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
Skin contact	 Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.
Ingestion	 If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting.

Most important symptoms/effects, acute and delayed

Potential acute health effect	ts
Eye contact	: No known significant effects or critical hazards.
Inhalation	: Harmful if inhaled.
Skin contact	: Defatting to the skin. May cause skin dryness and irritation.
Ingestion	: Harmful if swallowed.
Over-exposure signs/symp	<u>toms</u>
Eye contact	: No specific data.
Inhalation	: Adverse symptoms may include the following:
	reduced fetal weight
	increase in fetal deaths
	skeletal malformations
Skin contact	: Adverse symptoms may include the following: irritation
	dryness
	cracking
	reduced fetal weight
	increase in fetal deaths
	skeletal malformations
Ingestion	: Adverse symptoms may include the following:
	reduced fetal weight
	increase in fetal deaths skeletal malformations
	skeletal mailonnations
Indication of immediate med	lical attention and special treatment needed, if necessary
Notes to physician	: In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Specific treatments	: No specific treatment.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
Specific hazards arising from the chemical	: In a fire or if heated, a pressure increase will occur and the container may burst.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon oxides nitrogen oxides sulfur oxides metal oxide/oxides
Special protective actions for fire-fighters	 Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

	United States Page: 4/14	
upwind. Prevent entry into sewers, water courses, basements or confined a spillages into an effluent treatment plant or proceed as follows. Contain an spillage with non-combustible, absorbent material e.g. sand, earth, vermicu diatomaceous earth and place in container for disposal according to local re (see Section 13). Dispose of via a licensed waste disposal contractor. Cor absorbent material may pose the same hazard as the spilled product. Note Section 1 for emergency contact information and Section 13 for waste disposal		
Small spill Large spill	 Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor. Stop leak if without risk. Move containers from spill area. Approach release from 	
Methods and materials for co		
Environmental precautions	: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).	
For non-emergency personnel For emergency responders	 No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment. If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non- emergency personnel". 	

Product name PR 1440 B 1 Part A

Section 7. Handling and storage

Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Special precautions	: Keep away from combustible materials. If this material is part of a multiple component system, read the Safety Data Sheet(s) for the other component or components before blending as the resulting mixture may have the hazards of all of its parts.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	: Do not store below the following temperature: 5°C (41°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
manganese dioxide	ACGIH TLV (United States, 3/2020).
	TWA: 0.1 mg/m ³ , (as Mn) 8 hours. Form:
	Inhalable fraction
	TWA: 0.02 mg/m ³ , (as Mn) 8 hours. Form:
	Respirable fraction
	OSHA PEL (United States, 5/2018).
	CEIL: 5 mg/m³, (as Mn)
Terphenyl, hydrogenated	ACGIH TLV (United States, 3/2020).
	TWA: 4.9 mg/m ³ 8 hours.
	TWA: 0.5 ppm 8 hours.
Zeolites	ACGIH TLV (United States, 3/2020).
	TWA: 1 mg/m ³ 8 hours. Form: Respirable
	fraction
Polyphenyls, quater- and higher, partially hydrogenated	None.
Talc, not containing asbestiform fibers	ACGIH TLV (United States, 3/2020).
	TWA: 2 mg/m ³ 8 hours. Form: Respirable
	OSHA PEL Z3 (United States).
	TWA: 2 mg/m ³
carbon black	ACGIH TLV (United States, 3/2020).
	United States Page: 5/14

Product name PR 1440 B 1 Part A

Section 8. Exposure controls/personal protection

Key to abbreviations		
1,3-diphenylguanidine	None.	
	TWA: 15 mg/m ³ 8 hours. Form: Total dust	
	TWA: 5 mg/m ³ 8 hours. Form: Respirable fraction	
magnesium carbonate	OSHA PEL (United States, 5/2018).	
	CEIL: 1 ppm	
	CEIL: 9 mg/m ³	
	OSHA PEL (United States, 5/2018).	
	C: 0.53 ppm	
	C: 5 mg/m ³	
terphenyl	ACGIH TLV (United States, 3/2020).	
	TWA: 3.5 mg/m ³ 8 hours.	
	OSHA PEL (United States, 5/2018).	
	fraction	
	TWA: 3 mg/m ³ 8 hours. Form: Inhalable	

А	= Acceptable Maximum Peak	S	 Potential skin absorption
ACGIH	 American Conference of Governmental Industrial Hygienists. 	SR	 Respiratory sensitization
С	= Ceiling Limit	SS	 Skin sensitization
F	= Fume	STEL	 Short term Exposure limit values
IPEL	= Internal Permissible Exposure Limit	TD	= Total dust
OSHA	 Occupational Safety and Health Administration. 	TLV	= Threshold Limit Value
R	= Respirable	TWA	= Time Weighted Average
Z	= OSHA 29 CFR 1910.1200 Subpart Z - Toxic and Hazardous Substances		

Consult local authorities for acceptable exposure limits.

Recommended monitoring procedures	:	If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
Appropriate engineering controls	:	Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.
Environmental exposure controls	:	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Individual protection measure	<u>es</u>	
Hygiene measures	:	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	:	Safety glasses with side shields.
Skin protection		

Product name PR 1440 B 1 Part A

Section 8. Exposure controls/personal protection

Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Gloves	: For prolonged or repeated handling, use the following type of gloves:
	Recommended: nitrile rubber, natural rubber (latex)
Body protection	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. The respiratory protection shall be in accordance to 29 CFR 1910.134.

Section 9. Physical and chemical properties

		· · ·
Appearance		
Physical state	1	Liquid.
Color	:	Black.
Odor	:	Not available.
Odor threshold	1	Not available.
рН	1	Not applicable.
Melting point	1	Not available.
Boiling point	1	360°C (680°F)
Flash point	:	Closed cup: Not applicable.
Auto-ignition temperature	:	Not available.
Decomposition temperature	:	Not available.
Flammability (solid, gas)	:	Not available.
Lower and upper explosive (flammable) limits	:	Not available.
Evaporation rate	:	Not available.
Vapor pressure	:	Not available.
Vapor density	:	Not available.
Relative density	:	1.76
Density(lbs / gal)	:	14.69
Solubility	:	Insoluble in the following materials: cold water.

Product name PR 1440 B 1 Part A

Section 9. Physical and chemical properties

Partition coefficient: n- octanol/water	: Not applicable.
Viscosity	: K inematic (40°C (104°F)): >21 mm²/s (>21 cSt)
VOC	: 0
% Solid. (w/w)	: 100

Section 10. Stability and reactivity					
Reactivity	: No specific test data related to reactivity available for this product or its ingredients.				
Chemical stability	: The product is stable.				
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.				
Conditions to avoid	: When exposed to high temperatures may produce hazardous decomposition products. Refer to protective measures listed in sections 7 and 8.				
Incompatible materials	: Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids.				
Hazardous decomposition products	: Depending on conditions, decomposition products may include the following materials: carbon oxides nitrogen oxides sulfur oxides metal oxide/oxides				

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
manganese dioxide	LD50 Oral	Rat	3478 mg/kg	-
Terphenyl, hydrogenated	LD50 Oral	Rat	17500 mg/kg	-
Zeolites	LD50 Oral	Rat	>5 g/kg	-
carbon black	LD50 Oral	Rat	>10 g/kg	-
terphenyl	LD50 Oral	Rat - Female	2304 mg/kg	-
magnesium carbonate	LD50 Oral	Rat	8000 mg/kg	-
1,3-diphenylguanidine	LD50 Oral	Rat	323 mg/kg	-
Conclusion/Summary rritation/Corrosion Conclusion/Summary	There are no data available			
Skin	: There are no data available	on the mixture itself.		
Eyes	: There are no data available	on the mixture itself.		
Respiratory	: There are no data available	on the mixture itself.		
Sensitization				
Conclusion/Summary				
Skin	: There are no data available	on the mixture itself		

Date of issue 19 June 2021

Version 20

Product name PR 1440 B 1 Part A

Section 11. Toxicological information

Respiratory	1	There are	e no data av	ailable on the mixture itself.
Mutagenicity				
Conclusion/Summary	:	There are	e no data av	ailable on the mixture itself.
Carcinogenicity				
Conclusion/Summary	:	There are	e no data av	ailable on the mixture itself.
Classification				
Product/ingredient name		OSHA	IARC	NTP

Zeolites-3-carbon black-2B-	Product/ingredient name	OSHA	IARC	NTP
carbon black - 2B -	Zeolites	-	3	-
	carbon black	-	2B	-

Carcinogen Classification code:

IARC: 1, 2A, 2B, 3, 4 NTP: Known to be a human carcinogen; Reasonably anticipated to be a human carcinogen OSHA: + Not listed/not regulated: -

Reproductive toxicity

Conclusion/Summary : There are no data available on the mixture itself.

Teratogenicity

: There are no data available on the mixture itself. **Conclusion/Summary**

Specific target organ toxicity (single exposure)

Name	Category	Route of exposure	Target organs
✓alc, not containing asbestiform fibers	Category 3	-	Respiratory tract irritation
1,3-diphenylguanidine	Category 3	-	Respiratory tract irritation

Specific target organ toxicity (repeated exposure)

Name		Route of exposure	Target organs
manganese dioxide	Category 2	inhalation	brain

Target organs

: Contains material which causes damage to the following organs: lungs, skin, central nervous system (CNS).

Contains material which may cause damage to the following organs: blood, kidneys, the nervous system, liver, spleen, lymphatic system, cardiovascular system, upper respiratory tract, bone marrow, eye, lens or cornea.

Aspiration hazard

Not available.

Information on the likely routes of exposure

Potential acute health effects

Eye contact	:	No known significant effects or critical hazards.
Inhalation	:	Harmful if inhaled.
Skin contact	:	Defatting to the skin. May cause skin dryness and irritation.

Version 20

Product name PR 1440 B 1 Part A

Section 11. Toxicological information

Ingestion	: Harmful if swallowed.	
Over-exposure signs/sympt	<u>ms</u>	
Eye contact	: No specific data.	
Inhalation	: Adverse symptoms may include the following:	
	reduced fetal weight	
	increase in fetal deaths skeletal malformations	
Skin contact	: Adverse symptoms may include the following:	
	irritation	
	dryness	
	cracking reduced fetal weight	
	increase in fetal deaths	
	skeletal malformations	
Ingestion	: Adverse symptoms may include the following:	
	reduced fetal weight increase in fetal deaths	
	skeletal malformations	
Delayed and immediate effec	s and also chronic effects from short and long term exposure	
Conclusion/Summary	: There are no data available on the mixture itself. If splashed in the eyes, the liquid ma	ау
	cause irritation and reversible damage. Ingestion may cause nausea, diarrhea and	
	vomiting. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral,	
	inhalation and dermal routes of exposure and eye contact.	
Short term exposure		
Potential immediate	: There are no data available on the mixture itself.	
effects		
Potential delayed effects	: There are no data available on the mixture itself.	
<u>Long term exposure</u>		
Potential immediate	: There are no data available on the mixture itself.	
effects	The second state of the se	
Potential delayed effects Potential chronic health effe	: There are no data available on the mixture itself.	
		-
General	: May cause damage to organs through prolonged or repeated exposure. Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis.	
Carcinogenicity	Suspected of causing cancer. Risk of cancer depends on duration and level of	
	exposure.	
Mutagenicity	: No known significant effects or critical hazards.	
Reproductive toxicity	: Suspected of damaging fertility or the unborn child.	
Numerical measures of toxic	¥	
Acute toxicity estimates		

Section 11. Toxicological information

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/ I)
PR 1440 B 1 Part A	1016.8	N/A	N/A	N/A	1.7
manganese dioxide	500	N/A	N/A	N/A	1.5
Terphenyl, hydrogenated	17500	N/A	N/A	N/A	N/A
terphenyl	2304	N/A	N/A	N/A	N/A
magnesium carbonate	8000	N/A	N/A	N/A	N/A
1,3-diphenylguanidine	323	N/A	N/A	N/A	N/A

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
Zeolites terphenyl		Fish Daphnia Daphnia	96 hours 48 hours 72 hours

Persistence and degradability

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
terphenyl	-	-	Not readily

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
,3-diphenylguanidine	2.42	19.95	low

Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

Section 13. Disposal considerations

```
Disposal methods
```

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains

United States Page: 11/14

Product name PR 1440 B 1 Part A

Section 13. Disposal considerations

and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations. Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees. Section 6. Accidental release measures

14. Transport information

	DOT	IMDG	ΙΑΤΑ
UN number	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-
Transport hazard class (es)	-	-	-
Packing group	-	-	-
Environmental hazards Marine pollutant	No. Not applicable.	No. Not applicable.	No. Not applicable.
substances			

Additional information

DOT	: None identified.
IMDG	: None identified.
ΙΑΤΑ	: None identified.

Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according : Not applicable. to IMO instruments

Section 15. Regulatory information

United States

United States inventory (TSCA 8b) : All components are active or exempted.

SARA 302/304

SARA 304 RQ : Not applicable.

Composition/information on ingredients

No products were found.

SARA 311/312

Product name PR 1440 B 1 Part A

Section 15. Regulatory information

Classification	: ACUTE TOXICITY (oral) - Category 4
	ACUTE TOXICITY (inhalation) - Category 4
	CARCINOGENICITY - Category 2
	TOXIC TO REPRODUCTION - Category 2
	SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2
	HNOC - Defatting irritant
	HNOC - Avoid contact with organic materials.

Composition/information on ingredients

Name	%	Classification
manganese dioxide	≥20 - ≤50	ACUTE TOXICITY (oral) - Category 4 ACUTE TOXICITY (inhalation) - Category 4 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2
		HNOC - Avoid contact with organic materials.
Polyphenyls, quater- and higher, partially hydrogenated	≥5.0 - ≤10	HNOC - Defatting irritant
Talc, not containing asbestiform fibers	≥1.0 - ≤5.0	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3
carbon black	≥1.0 - ≤5.0	COMBUSTIBLE DUSTS CARCINOGENICITY - Category 2
1,3-diphenylguanidine	≥1.0 - ≤4.6	COMBUSTIBLE DUSTS
		ACUTE TOXICITY (oral) - Category 4
		SKIN IRRITATION - Category 2
		EYE IRRITATION - Category 2A
		TOXIC TO REPRODUCTION - Category 2
		SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE)
		(Respiratory tract irritation) - Category 3

SARA 313

Supplier notification

Chemical name

on : manganese dioxide

name so diovido CAS number 1313-13-9 Concentration 30 - 60

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

California Prop. 65

MARNING: Cancer - www.P65Warnings.ca.gov.

Section 16. Other information

Hazardous Material Information System (U.S.A.)

Health : 3 * Flammability : 0 Physical hazards : 1

(*) - Chronic effects

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on MSDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

National Fire Protection Association (U.S.A.)

Health : 3 Flammability : 0 Instability : 1

United States Page: 13/14

SAFETY DATA SHEET



Date of issue/Date of revision10 August 2021Version 15

Section 1. Identification		
Product name	: PR 1440 B 1 Part B	
Product code	: PR 1440 B 1 Part B	
Other means of identification	: Not available.	
Product type	: Solid.	
Relevant identified uses o	f the substance or mixture and uses advised against	
Product use	: Industrial applications.	
Use of the substance/ mixture	: Sealants	
Uses advised against	: Not applicable.	
Manufacturer	: PPG Aerospace PRC-DeSoto 12780 San Fernando Road Sylmar, CA 91342	
<u>Emergency telephone</u> <u>number</u>	Phone: 818 362 6711 : (412) 434-4515 (U.S.) (514) 645-1320 (Canada) 01-800-00-21-400 (Mexico)	

Section 2. Hazards identification

OSHA/HCS status Classification of the	 This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200). CARCINOGENICITY - Category 2
substance or mixture	TOXIC TO REPRODUCTION - Category 2
	Percentage of the mixture consisting of ingredient(s) of unknown acute toxicity: 8.3% (oral), 54.1% (dermal), 91.5% (inhalation)
GHS label elements	
Hazard pictograms	
Signal word	: Warning
Hazard statements	: Suspected of causing cancer. Suspected of damaging fertility or the unborn child.
Precautionary statements	

United States Page: 1/13

Section 2. Hazards identification

Prevention	: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing and eye or face protection.
Response	: IF exposed or concerned: Get medical advice or attention.
Storage	: Store locked up.
Disposal	 Dispose of contents and container in accordance with all local, regional, national and international regulations.
Supplemental label elements	This product either contains formaldehyde or is capable of releasing formaldehyde above 0.5 ppm under certain conditions. Formaldehyde is a known cancer hazard, a skin sensitizer and a respiratory sensitizer. Emits toxic fumes when heated.
Hazards not otherwise classified	: None known.

Section 3. Composition/information on ingredients

Substance/mixture	:	Mixture
Product name	:	PR 1440 B 1 Part B

Ingredient name	%	CAS number
titanium dioxide	≥20 - ≤50 ≥1.0 - ≤5.0 <1.0	471-34-1 13463-67-7 108-88-3

SUB codes represent substances without registered CAS Numbers.

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

If ingestion, irritation, any type of overexposure or symptoms of overexposure occur during or persists after use of this product, contact a POISON CONTROL CENTER, EMERGENCY ROOM OR PHYSICIAN immediately; have Safety Data Sheet information available. Never give anything by mouth to an unconscious or convulsing person.

Description of necessary first aid measures

Eye contact	 Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
Inhalation	 Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
Skin contact	 Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.
Ingestion	 If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting.

Most important symptoms/effects, acute and delayed

Potential acute health effects

Product name PR 1440 B 1 Part B

Section 4. First aid measures

Eye contact	: No known significant effects or critical hazards.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: No known significant effects or critical hazards.
Ingestion	: No known significant effects or critical hazards.
Over-exposure signs	/symptoms
Eye contact	: No specific data.
Inhalation	: Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations
Skin contact	 Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations
Ingestion	: Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations
Indication of immediat	e medical attention and special treatment needed, if necessary
Notes to physician	Troat symptomatically Contact poison treatment specialist i

Notes to physician	 Treat symptomatically. Contact poison treatment specialist immediately if large guantities have been ingested or inhaled.
Specific treatments	: No specific treatment.
Protection of first-aiders	. No action shall be taken involving any personal risk or without suitable training. It may
	be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
Specific hazards arising from the chemical	: No specific fire or explosion hazard.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon oxides halogenated compounds metal oxide/oxides Formaldehyde.
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Product name PR 1440 B 1 Part B

Section 5. Fire-fighting measures

Special protective equipment for fire-fighters

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures			
For non-emergency personnel	: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.		
For emergency responders	: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".		
Environmental precautions	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).		
Methods and materials for containment and cleaning up			
Small spill	: Move containers from spill area. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Dispose of via a licensed waste disposal contractor.		
Large spill	: Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.		

Section 7. Handling and storage

Precautions for safe handling	
Protective measures	: Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Special precautions	: If this material is part of a multiple component system, read the Safety Data Sheet(s) for the other component or components before blending as the resulting mixture may have the hazards of all of its parts.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

= Total dust

= Threshold Limit Value

= Time Weighted Average

TD

TLV

TWA

Product name PR 1440 B 1 Part B

Section 7. Handling and storage

Conditions for safe storage, including any incompatibilities	: Do not store below the following temperature: 5°C (41°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to
	Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
calcium carbonate	ACGIH TLV (United States). TWA: 3 mg/m ³ Form: Respirable TWA: 10 mg/m ³ Form: Total dust OSHA PEL (United States).
titanium dioxide	TWA: 5 mg/m ³ Form: Respirable TWA: 15 mg/m ³ OSHA PEL (United States, 5/2018). TWA: 15 mg/m ³ 8 hours. Form: Total dust ACGIH TLV (United States, 3/2020).
toluene	TWA: 10 mg/m ³ 8 hours. OSHA PEL Z2 (United States, 2/2013). AMP: 500 ppm 10 minutes. CEIL: 300 ppm TWA: 200 ppm 8 hours. ACGIH TLV (United States, 3/2020). TWA: 20 ppm 8 hours.
Key to abbreviations A = Acceptable Maximum Peak ACGIH = American Conference of Governmental Industrial Hygienists. C = Ceiling Limit F = Fume	s S = Potential skin absorption SR = Respiratory sensitization SS = Skin sensitization STEL = Short term Exposure limit values

F = Fume IPEL = Internal Permissible Exposure Limit

OSHA = Occupational Safety and Health Administration. R = Respirable

Z = OSHA 29 CFR 1910.1200 Subpart Z - Toxic and Hazardous Substances

Consult local authorities for acceptable exposure limits.

Recommended monitoring procedures If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

Appropriate engineering controls : If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Product name PR 1440 B 1 Part B

Section 8. Exposure controls/personal protection

Environmental exposure	:	Emissions from ventilation or work process equipment should be checked to ensure
controls		they comply with the requirements of environmental protection legislation. In some
		cases, fume scrubbers, filters or engineering modifications to the process equipment
		will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	: Safety glasses with side shields.
Skin protection	
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Gloves	: For prolonged or repeated handling, use the following type of gloves:
	Recommended: natural rubber (latex)
Body protection	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. The respiratory protection shall be in accordance to 29 CFR 1910.134.

Section 9. Physical and chemical properties

		United States	Page: 6/13
Auto-ignition temperature	: Not applicable.		
Flash point	: Closed cup: Not applicable.		
Boiling point	: Not available.		
Melting point	: Not available.		
рН	: Not applicable.		
Odor threshold	: Not available.		
Odor	: Not available.		
Color	: Beige.		
Physical state	: Solid.		
<u>Appearance</u>			

Section 9. Physical and chemical properties

•	
Decomposition temperature	: Not available.
Flammability (solid, gas)	: Not available.
Lower and upper explosive (flammable) limits	: Not applicable.
Evaporation rate	: Not available.
Vapor pressure	: Not available.
Vapor density	: Not applicable.
Relative density	: 1.57
Density(lbs / gal)	: 13.1
Solubility	: Insoluble in the following materials: cold water.
Partition coefficient: n- octanol/water	: Not applicable.
Viscosity	: Kinematic (40°C (104°F)): Not applicable.
VOC	: 16 g/l
% Solid. (w/w)	: 99

Section 10. Stability and reactivity

Section 11 Toxic	alogical information
Hazardous decomposition products	: Depending on conditions, decomposition products may include the following materials: carbon oxides halogenated compounds Formaldehyde. metal oxide/oxides
Incompatible materials	: Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids.
Conditions to avoid	: When exposed to high temperatures may produce hazardous decomposition products. Refer to protective measures listed in sections 7 and 8.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Chemical stability	: The product is stable.
Reactivity	: No specific test data related to reactivity available for this product or its ingredients.

Section 11. Toxicological information

Information on toxicological effects Acute toxicity

Product name PR 1440 B 1 Part B

Section 11. Toxicological information

Product/ingredient name	Result		Species	Dose	Exposure
calcium carbonate	LD50 Dern	nal	Rat	>2000 mg/kg	-
	LD50 Oral		Rat	6450 mg/kg	-
titanium dioxide		ation Dusts and mist		>6.82 mg/l	4 hours
	LD50 Dern	nal	Rabbit	>5000 mg/kg	-
4 - I	LD50 Oral		Rat	>5000 mg/kg	-
toluene	LD50 Innal	ation Vapor	Rat Rabbit	49 g/m³ 8.39 g/kg	4 hours
	LD50 Den	Idi	Rat	5580 mg/kg	-
O an alvai an IO ann an a					
Conclusion/Summary	: There are	e no data available o	n the mixture itse	IT.	
Irritation/Corrosion					
Conclusion/Summary	— .				
Skin		e no data available o			
Eyes		e no data available o			
Respiratory	: There are	e no data available o	n the mixture itse	lf.	
Sensitization					
Conclusion/Summary					
Skin	: There are	e no data available o	n the mixture itse	lf.	
Respiratory	: There are	e no data available o	n the mixture itse	lf.	
<u>Mutagenicity</u>					
Conclusion/Summary	: There are	e no data available o	n the mixture itse	lf.	
Carcinogenicity					
Conclusion/Summary	: There are	e no data available o	n the mixture itse	lf.	
Classification					
Product/ingredient name	OSHA	IARC NTP			
titanium dioxide	-	2B -			
toluene	-	3 -			
Carcinogen Classification	n code:				
IARC: 1, 2A, 2B, 3					
NTP: Known to b OSHA: +	e a human carc	inogen; Reasonably ant	cipated to be a hum	nan carcinogen	
Not listed/not reg	ulated: -				
Reproductive toxicity	. These	na data availakta ar	4 h a mais de ma 14 1	£	
Conclusion/Summary	: mere are	no data available on	the mixture itsel	Ι.	
<u>Feratogenicity</u>	-			<i>.</i>	
Conclusion/Summary		no data available on	the mixture itsel	t.	
Specific target organ toxicity	<u>/ (single exp</u>	<u>osure)</u>			

Name		Route of exposure	Target organs
toluene	Category 3	-	Narcotic effects

Specific target organ toxicity (repeated exposure)

l	United States	Page: 8/13
---	---------------	------------

Section 11. Toxicological information

Name	•••	Route of exposure	Target organs
toluene	Category 2	-	-

Target organs

: Contains material which may cause damage to the following organs: upper respiratory tract, skin, eyes.

Aspiration hazard

Name	Result
toluene	ASPIRATION HAZARD - Category 1

Information on the likely routes of exposure

Potential acute health effects

Eye contact	1	No known significant effects or critical hazards.
Inhalation	1	No known significant effects or critical hazards.
Skin contact	1	No known significant effects or critical hazards.
Ingestion	1	No known significant effects or critical hazards.
Over-exposure signs/sympt	ton	<u>ns</u>
Eye contact	1	No specific data.
Inhalation	1	Adverse symptoms may include the following:
		reduced fetal weight
		increase in fetal deaths
Okin contect		skeletal malformations
Skin contact	-	Adverse symptoms may include the following: reduced fetal weight
		increase in fetal deaths
		skeletal malformations
Ingestion	:	Adverse symptoms may include the following:
5		reduced fetal weight
		increase in fetal deaths
		skeletal malformations
		and also chronic effects from short and long term exposure
Conclusion/Summary	1	There are no data available on the mixture itself. This product either contains formaldehyde or is capable of releasing formaldehyde above 0.5 ppm under certain
		conditions. Formaldehyde is a known cancer hazard, a skin sensitizer and a respiratory
		sensitizer. Exposure to component solvent vapor concentrations in excess of the stated
		occupational exposure limit may result in adverse health effects such as mucous
		membrane and respiratory system irritation and adverse effects on the kidneys, liver
		and central nervous system. Symptoms and signs include headache, dizziness, fatigue,
		muscular weakness, drowsiness and, in extreme cases, loss of consciousness.
		Solvents may cause some of the above effects by absorption through the skin. There is some evidence that repeated exposure to organic solvent vapors in combination with
		constant loud noise can cause greater hearing loss than expected from exposure to
		noise alone. Ingestion may cause nausea, diarrhea and vomiting. This takes into
		account, where known, delayed and immediate effects and also chronic effects of
		components from short-term and long-term exposure by oral, inhalation and dermal
		routes of exposure and eye contact.

Short term exposure

Section 11. Toxicological information

		•
Potential immediate effects	•	There are no data available on the mixture itself.
Potential delayed effects	1	There are no data available on the mixture itself.
<u>Long term exposure</u>		
Potential immediate effects	:	There are no data available on the mixture itself.
Potential delayed effects	1	There are no data available on the mixture itself.
Potential chronic health eff	ect	<u>s</u>
General	:	No known significant effects or critical hazards.
Carcinogenicity	1	Suspected of causing cancer. Risk of cancer depends on duration and level of exposure.
Mutagenicity	1	No known significant effects or critical hazards.
Reproductive toxicity	:	Suspected of damaging fertility or the unborn child.

Numerical measures of toxicity

Acute toxicity estimates

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)		(vapors)	Inhalation (dusts and mists) (mg/ I)
	N/A 6450 5580	2500	N/A N/A N/A	N/A N/A 49	N/A N/A N/A

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
calcium carbonate	Acute EC10 >14 mg/l	Algae	72 hours
titanium dioxide	Acute LC50 >100 mg/l Fresh water	Daphnia - Daphnia magna	48 hours

Persistence and degradability

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
toluene	-	-	Readily

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
toluene	2.73	8.32	low

Mobility in soil

Soil/water partition coefficient (Koc) : Not available.

United States Page: 10/13

Section 12. Ecological information

Section 13. Disposal considerations

Disposal methods : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations. Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees. Section 6. Accidental release measures

14. Transport information

	DOT	IMDG	ΙΑΤΑ		
UN number	Not regulated.	Not regulated.	Not regulated.		
UN proper shipping name	-	-	-		
Transport hazard class (es)	-	-	-		
Packing group	-	-	-		
Environmental hazards Marine pollutant substances	No. Not applicable.	No. Not applicable.	No. Not applicable.		

Additional information

- DOT: None identified.IMDG: None identified.IATA: None identified.
- **Special precautions for user**: **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according : Not applicable. to IMO instruments

Section 15. Regulatory information

United States

United States inventory (TSCA 8b) : All components are active or exempted.

SARA 302/304

SARA 304 RQ : Not applicable.

Composition/information on ingredients

No products were found.

SARA 311/312

Classification

: CARCINOGENICITY - Category 2 TOXIC TO REPRODUCTION - Category 2

Composition/information on ingredients

Name	%	Classification
titanium dioxide toluene	≥1.0 - ≤5.0 <1.0	CARCINOGENICITY - Category 2 FLAMMABLE LIQUIDS - Category 2 SKIN IRRITATION - Category 2 TOXIC TO REPRODUCTION - Category 2 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2 ASPIRATION HAZARD - Category 1 HNOC - Defatting irritant

California Prop. 65

MARNING: Reproductive Harm - www.P65Warnings.ca.gov.

Section 16. Other information

Hazardo	ous	Mate	rial I	nformation Sys	ten	n (U	.S.A.)		
Health	:	1	*	Flammability	:	0	Physical hazards	:	0
(*) - Chro	nic e	effects							

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on MSDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

National Fire Protection Association (U.S.A.)Health1Flammability:0Instability:0

Date of previous issue : 6/10/2021 Organization that prepared : EHS the SDS

Product name PR 1440 B 1 Part B

Section 16. Other information

Key to abbreviations	: ATE = Acute Toxicity Estimate
-	BCF = Bioconcentration Factor
	GHS = Globally Harmonized System of Classification and Labelling of Chemicals
	IATA = International Air Transport Association
	IBC = Intermediate Bulk Container
	IMDG = International Maritime Dangerous Goods
	LogPow = logarithm of the octanol/water partition coefficient
	MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
	N/A = Not available
	SGG = Segregation Group
	UN = United Nations

Indicates information that has changed from previously issued version.

Disclaimer

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.

Product name PR 1440 B 1 Part A

Section 16. Other information

Date of previous issue	1	4/2/2021
Organization that prepared the SDS	:	EHS
Key to abbreviations	:	ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = International Air Transport Association IBC = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) N/A = Not available SGG = Segregation Group UN = United Nations

Indicates information that has changed from previously issued version.

Disclaimer

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.