Section: 1 CHEMICAL PRODUCT AND COMPANY INFORMATION

Product Name:	Calla 805
Chemical Family:	Aqueous Cleaner

Manufacturer: Zip-Chem Products 400 Jarvis Drive Morgan Hill, CA 95037 For Additional Product 1 (800) 648-2661 Information:

In Emergency: 1 (800) 424-9300

Section: 2 COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

FOR EXPOSURE LIMITS SEE SECTION 8 FOR OTHER TOXICOLOGICAL INFORMATION SEE SECTION 11

HAZARDOUS INGREDIENTS

Descriptive Name	CAS Number	Percentage Range	Hazard Type per CFR 1910.1200	Exposure Limits	LD ₅₀	LC ₅₀	NTP, IARC, Or OSHA Carcinogen
Sodium Hydroxide	1310-73-2	<2%	Hazardous: Corrosive	OSHA PEL: 2 mg/cc ACGIH TLV: 2 mg/cc	Not Determined	Not Determined	No
Propanol, (2-Methoxy- Methylethoxy)	34590-94-8	<3%	Physical Hazard: Combustible	OSHA PEL: 100 ppm ACGIH TLV: 100 ppm	Not Determined	Not Determined	No

Section: 3 HAZARDS IDENTIFICATION

PHYSICAL HAZARDS:	
ACUTE HEALTH EFFECTS:	May cause irritation to the skin and eyes. Ingestion may cause upset stomach.
CHRONIC HEALTH EFFECTS:	Prolonged or repeated contact with the skin can cause irritation and dry
	skin.
IATA CLASSIFICATION:	
HMIS RATINGS:	
Health:	2
Flammability:	0
Reactivity:	0
Protective Equipment	: E

Section: 4 FIRST AID MEASURES

EYES: May be an eye irritant. Flush immediately with water for 15 minutes and take to physician.

SKIN: Wash affected area with water.

- INGESTION: Do not induce vomiting so as to avoid aspiration of material into the lungs. If conscious, drink large amounts of water and contact a physician.
- INHALATION: Remove from exposure and restore breathing. Keep person calm. If not breathing, give artificial respiration and call emergency response. If breathing is difficult, give oxygen and call emergency response.

Section: 5 FIRE AND EXPLOSION HAZARDS

FLAMMABILITY DATA: FLAMMABLE/COMBUSTIBLE/PYROPHORIC: Not flammable FLASH POINT AND METHOD: None PMCC AUTOIGNITION TEMPERATURE: Not established

FLAMMABLE LIMITS AT NORMAL TEMPERATURE AND PRESSURE (PERCENT VOLUME IN AIR): LEL: N/A UEL: N/A

EXPLOSION DATA:

SENSITIVITY TO MECHANICAL IMPACT: SENSITIVITY TO STATIC DISCHARGE:

EXTINGUISHING MEDIA: Foam, Alcohol Foam, CO2, Dry Chemical, Water Fog

FIRE FIGHTING TECHNIQUES AND COMMENTS:

Use standard firefighting techniques to fight fires involving this material. The material itself is not flammable.

HAZARDOUS COMBUSTION PRODUCTS: Carbon dioxide, carbon monoxide

Section: 6 ACCIDENTAL SPILL/RELEASE INFORMATION

FOR ALL TRANSPORTATION ACCIDENTS CALL CHEMTREC AT 1-800-424-9300.

REPORTABLE QUANTITY: Not Applicable

SPILL MITIGATION PROCEDURES:

Stop source of spill as soon as possible and notify appropriate personnel. Burm around spill area to prevent spill from spreading. Ventilate area. Do not flush into sewers.

Not Sensitive

Not Sensitive

AIR RELEASE:

Vapors may be suppressed by use of water fog or spray. Contain all liquid for treatment or neutralization.

WATER RELEASE:

Material is soluble in water. Contain liquid for neutralization of the pH.

LAND SPILL:

Create a trench to contain materials. Spilled materials may be contained using sand, clay, earth or a commercial absorbent. Do not place materials back in their original container.

SPILL RESIDUES:

Dispose of per guidelines under section 13, DISPOSAL CONSIDERATIONS.

PERSONNEL PROTECTION FOR EMERGENCY SPILL AND FIRE FIGHTING SITUATIONS: Additional protective clothing must be worn to prevent personal contact with this material. Those items include but are not limited to gloves and safety glasses.

Section: 7 HANDLING AND STORAGE

DO NOT TAKE INTERNALLY. AVOID CONTACT WITH EYES. UPON CONTACT WITH SKIN OR EYES WASH OFF WITH WATER.

STORAGE CONDITIONS:

Store in a cool, dry, well-ventilated place.

STORE AT TEMPERATURES BELOW 120°F. DO NOT STORE OR USE NEAR HEAT, SPARKS, OR FLAMES. AVOID BREATHING VAPORS. VAPORS ARE HEAVIER THAN AIR AND WILL COLLECT IN LOW AREAS AND OTHER CONFINED AREAS.

PRODUCT STABILITY AND COMPATIBILITY:

SHELF LIFE LIMITATIONS: 36 months from date of shipment (DOS). INCOMPATIBLE MATERIALS FOR STORAGE OR TRANSPORT: Strong oxidizing agents INCOMPATIBLE MATERIALS FOR PACKAGING: N/A

Section: 8 PREVENTIVE MEASURES

PERSONAL PROTECTION FOR ROUTINE USE OF THIS PRODUCT:

RESPIRATORY PROTECTION: Breathing apparatus is not be required for use of this product. SKIN AND EYE PROTECTIVE EQUIPMENT: Impervious gloves are recommended to prevent skin contact. Safety glasses to prevent eye contact are recommended.

ENGINEERING CONTROLS

VENTILATION: Local or mechanical to keep Section II ingredients below their exposure limits. EQUIPMENT SPECIFICATIONS (WHEN APPLICABLE):

RESPIRATOR TYPE: None required

PROTECTIVE CLOTHING TYPE: (This includes: gloves, boots, apron, protective suit): Impervious gloves, safety glasses

WASTE DISPOSAL:

Spilled material collected in absorbent material should be transferred to steel disposal or recovery drums. If this product becomes a waste, it DOES NOT meet the criteria of a hazardous waste as defined under 40 CFR 261, in that it does not exhibit the characteristics of hazardous waste under Subpart D. If this product becomes a waste, it should be disposed of in accordance with local, state and federal regulations by incineration.

Section: 9 PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE(gas, liquid, solid): Liquid Green APPEARANCE: ODOR: Slight odor FREEZING POINT: Not Determined BOILING RANGE: Not Determined **DECOMPOSITION TEMPERATURE:** Not Determined SPECIFIC GRAVITY (H20=1): 1.0 BULK DENSITY: 8.7 lbs/gal @ 70 Deg F pH @ 25 Deg C: 12.0-12.5 VAPOR PRESSURE @ 25 Deg C: Not Determined SOLUBILITY IN WATER: Soluble VOLATILES, PERCENT BY WEIGHT: 90% EVAPORATION RATE: Slower than Ether VAPOR DENSITY: Heavier than air VOLATILE ORGANIC COMPOUND (VOC) G/L: 26 grams/Liter

Section: 10 STABILITY AND REACTIVITY DATA

CONDITIONS UNDER WHICH THIS PRODUCT MAY BE UNSTABLE: MECHANICAL SHOCK OR IMPACT: No ELECTRICAL (STATIC) DISCHARGE: No HAZARDOUS POLYMERIZATION: Will Not Occur INCOMPATIBLE MATERIALS: Strong oxidizing agents. CONDITIONS OF REACTIVITY: None known HAZARDOUS DECOMPOSITION PRODUCTS: Carbon dioxide, carbon monoxide

Section: 11 TOXICOLOGICAL PROPERTIES

ROUTES OF ABSORPTION

Ingestion can cause upset stomach and burning sensation in digestive tract.

WARNING STATEMENTS AND WARNING PROPERTIES:

DO NOT TAKE INTERNALLY.

SIGNS, SYMPTOMS AND EFFECTS OF EXPOSURE

INHALATION

ACUTE: None known.

CHRONIC: None known

SKIN

ACUTE: May cause irritation.

CHRONIC: Prolonged or repeated contact may cause dry skin.

EYE

May cause irritation.

INGESTION

ACUTE: May cause nausea or vomiting.

CHRONIC: If large quantities are swallowed, do not induce vomiting as it might cause aspiration of vomitus into the lungs. Drink lots of water and see physician.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: None known.

INTERACTIONS WITH OTHER CHEMICALS THAT ENHANCE TOXICITY: None Known ACUTE TARGET ORGAN TOXICITY: No organs know to be damaged from exposure to this product. CHRONIC TARGET ORGAN TOXICITY: There are no known effects from repeated exposure. REPRODUCTIVE AND DEVELOPMENTAL TOXICITY: There are no known or reported effects on

reproductive function or fetal development.

CARCINOGENICITY: NTP? NO IARC MONOGRAPHS? NO OSHA REGULATED? NO MUTAGENICITY: This product is not known to be mutagenic.

EXPOSURE LIMITS: Not Determined

Section: 12 ECOLOGICAL INFORMATION

AQUATIC TOXICITY: None known or reported.

Section: 13 DISPOSAL CONSIDERATIONS

Spilled material collected in absorbent material should be transferred to steel disposal or recovery drums.

If this product becomes a waste, it DOES NOT meet the criteria of a hazardous waste as defined under 40 CFR 261, in that it does not exhibit the characteristics of hazardous waste under Subpart D. If this product becomes a waste, it should be disposed of in accordance with local, state and federal regulations by incineration.

Section: 14 TRANSPORT INFORMATION

DOT SHIPPING NAME: DOT Non-Regulated (Soap) DOT HAZARD CLASS: None DOT PACKING GROUP: None DOT REPORTABLE QUANTITY: None

Section: 15 REGULATORY INFORMATION

INTERNATIONAL

All components of this product are listed on the following inventories: MITI (Japan) EINECS (EEC) DSL (Canada).

FEDERAL

TOXIC SUBSTANCES CONTROL ACT (TSCA):

The components of this product are listed on the TSCA inventory. SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT TITLE III (SARA): Section 302/304

Requires emergency planning based on 'Threshold Planning Quantities' (TPQs), and release reporting based on Reportable Quantities (RQs) of 'Extremely Hazardous Substances' (EHS) listed in Appendix A of 40 CFR 355. There are no components of this material with known CAS numbers that are on the EHS list.

Section 311 & 312

Based upon the available information, this material and/or components is classified as a health and/or physical hazards according to Section 311 & 312:

Descriptive Name	CAS Number	Percentage Range	Hazard Type per CFR 1910.1200	Exposure Limits	LD ₅₀	LC ₅₀	NTP, IARC, Or OSHA Carcinogen
Sodium Hydroxide	1310-73-2	<2%	Hazardous: Corrosive	OSHA PEL: 2 mg/cc ACGIH TLV: 2 mg/cc	Not Determined	Not Determined	No
Propanol, (2-Methoxy- Methylethoxy)	34590-94-8	<3%	Not Hazardous	OSHA PEL: 100 ppm ACGIH TLV: 100 ppm	Not Determined	Not Determined	No

Section 313

This material does not contain chemicals with known CAS numbers subject to the reporting requirements of SARA Title III, Section 313 and 40 CFR 372:

Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA)

This material does not contain chemical(s) with known CAS numbers classified as hazardous substances subject to the reporting requirements of CERCLA (40 CFR 302) and to the release reporting requirements of SARA (Section 302) based on reportable quantities (RQs):

OSHA Regulations

'Chemical-specific' U. S. Occupational Safety and Health Administration (OSHA) regulations (1910.1002 to 1910.1050) presented under 29 CFR 1910 do not apply to this material or its components.

Other EPA Regulations

No additional information available.

State

California Safe Drinking Water and Toxic Enforcement Act of 1988- Proposition 65

This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins under California Proposition 65 at levels that would be subject to the proposition

California South Coast Air Quality Management District (SCAQMD) Rule 443.1 (VOC's)

A Volatile Organic Compound (VOC) is any volatile compound of carbon excluding methane, carbon monoxide, carbonic acid, metallic carbides or carbonates, ammonium carbonate, 1,1,1-trichloroethane, methylene chloride, FC-23, CFC-113, CFC-12, CFC-11, CFC-22, CFC-114, and CFC-115. By this definition, this is a VOC material.

Massachusetts Right to Know Substance List (MSL) [105 CMR 670.000]

Hazardous Substances (MSL-HS) on the MSL must be identified when present in materials at levels greater than state specified criterion. The criterion is: >=1%. Components with CAS numbers present in this material at a level which could require reporting under the statute are:

<u>Chemical</u>	CAS Number
Sodium Hydroxide	1310-73-2

Extraordinarily Hazardous Substances (MSL-EHS) on the MSL must be identified when present in materials at levels greater than state specified criterion. The criterion is >= 0.0001%. There are no materials present that could require reporting under this statute.

Pennsylvania Right to Know Hazardous Substance List

Hazardous Substances (PA-HS) must be identified when present in materials at levels greater than the state specified criterion. The criterion is >=1%. Components with CAS numbers present in this material at a level that could require reporting under the statute are:

Chemical Sodium Hydroxide

CAS Number

1310-73-2

Section: 16 PREPARATION INFORMATION

REVISION INFORMATION: PREPARED BY: APPROVAL DATE: SUPERSEDES: Periodic review J Smith 2/8/10 2/13/06

This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of Zip-Chem Products Company. The data in this sheet is related only to the specific material designated herein. Zip-Chem Products Company assumes no legal responsibility for use or reliance upon these data.