print date : 06/19/19 E859-T49 (page 1)

SECTION 1

manufacturer : SANDSTROM PRODUCTS COMPANY

address : 224 South Main Street

: Port Byron, IL 61275

: USA

telephone# : (309) 523-2121

emergency# : (800) 424-9300

: (703) 527-3887

mfg. code id : E859-T49 Revision level : 10-06/19/19

trade name : POXYLUBE #859 - TAN

Recommended use of chemical: SOLID FILM LUBRICANT

Restrictions on use: Do not use where there is a potential for contact with food.

SECTION 2

HAZARD IDENTIFICATION





HAZARD CLASSIFICATION:

DANGER!

EYE DAMAGE: CATEGORY 1
SKIN IRRITANT: CATEGORY 2
STOT SE: CATEGORY 3 (RESP)

HAZARD & PRECAUTIONARY STATEMENTS:

FLAMMABILITY

NOT CLASSIFIED AS A HAZARDOUS SUBSTANCE OR MIXTURE WITH FLAMMABILITY.

EYE CONTACT

H318: CAUSES SERIOUS EYE DAMAGE. P280: WEAR PROTECTIVE GLOVES/ PROTECTIVE CLOTHING/ EYE PROTECTION/ FACE PROTECT ION.
P305,P351,P338: IF IN EYES: RINSE CAUTIOUSLY WITH WATER FOR SEVERAL MINUTES. REMOVE CONTACT LENSES, IF PRESENT AND EASY TO DO.
CONTINUE RINSING. P310: IMMEDIATELY CALL A POISON CENTER OR DOCTOR/ PHYSICIAN.

SKIN CONTACT

H315: CAUSES SKIN IRRITATION. P264: WASH HANDS AND EXPOSED BODY PARTS THOROUGHLY AFTER HANDLING. P280: WEAR PROTECTIVE GLOVES/
PROTECTIVE CLOTHING/ EYE PROTECTION/ FACE PROTECT ION. P302, P352: IF ON SKIN: WASH WITH PLENTY OF SOAP AND WATER. P362: TAKE OFF
CONTAMINATED CLOTHING AND WASH BEFORE REUSE. P332, P313: IF SKIN IRRITATION OCCURS: GET MEDICAL ADVICE/ ATTENTION.

INHALATION

NOT CLASSIFIED AS A HAZARDOUS SUBSTANCE OR MIXTURE FOR INHALATION.

INGESTION

NOT CLASSIFIED AS A HAZARDOUS SUBSTANCE OR MIXTURE FOR INGESTION.

HAZARDS NOT CLASSIFIED

NO DATA AVAILABLE.

OTHER HEALTH EFFECTS

print date : 06/19/19 E859-T49 (page 2)

H335: MAY CAUSE RESPIRATORY IRRITATION. P261: AVOID BREATHING DUST/ FUME/ GAS/ MIST/ VAPORS/ SPRAY. P271: USE ONLY OUTDOORS OR IN A WELL-VENTILATED AREA. P304+P340: IF INHALED: REMOVE PERSON TO FRESH AIR AND KEEP COMFORTABLE FOR BREA THING. P312: CALL A POISON CENTER OR DOCTOR/PHYSICIAN IF YOU FEEL UNWELL. P405: STORE LOCKED UP. P403+P233: STORE IN A WELL-VENTILATED PLACE. KEEP CONTAINER TIGHTLY CLOSED. P501: DISPOSE OF CONTENTS/ CONTAINER IN ACCORDANCE WITH LOCAL/ REGIONAL/ NATION AL/ INTERNATIONAL REGULATIONS.

OTHER HAZARDS:

USE ONLY IN A WELL-VENTILATED AREA OR IN A HOOD WHERE NO FLAME OR OTHER IGNITION SOURCES ARE PRESENT.DO NOT USE PRODUCT IN FOOD-PROCESSING OR FOOD-HANDLING EQUIPMENT OR ON SURFACES THAT MAY CONTACT FOOD. DO NOT ALLOW PRODUCT TO CONTAMINATE FOODSTUFFS. DO NOT EAT, DRINK OR SMOKE WHEN USING PRODUCT. WASHHANDS THOROUGHLY AFTER HANDLING. DO NOT BREATHE VAPORS. WEAR SUITABLE EYE AND SKIN PROTECTION. KEEP CONTAINER CLOSED WHEN NOT IN USE. PROTECT FROM TEMPERATURE EXTREMES. IN CASE OF SPILL OR LEAK, REMOVE IGNITION SOURCES AND VENTILATE AREA.

E859-T49 (page 3) print date : 06/19/19

vapor pressure component CAS# % by wt. SARA (mm Hg @ 20 C) (@ 25 C) no. 2-PROPOXYPROPANOL 1569-01-3 1 - 5 NO 2-AMINO-2-METHYL-1-PROPANOL 124-68-5 1.00 N/A POLYTETRAFLUORETHYLENE 9002-84-0 1 - 5 NO N/A N/A 1 ~ 5 YES N/A IRON MANGANESE OXIDE BLACK 33 75864-23-2 N/A (N/A = not applicable)

SECTION 4 FIRST AID MEASURES

EYE CONTACT

IMMEDIATELY FLUSH EYES WITH COPIOUS AMOUNTS OF WATER FOR AT LEAST 15 MINUTES WHILE HOLDING EYELIDS OPEN. SEEK PROMPT MEDICAL ATTENTION.

SKIN CONTACT

IMMEDIATELY REMOVE CONTAMINATED CLOTHING AND SHOES. WIPE EXCESS FROM SKIN AND FLUSH WITH WATER FOR AT LEAST 15 MINUTES USING SOAP IF AVAILABLE. SEEK PROMPT MEDICAL ATTENTION. DO NOT REUSE CLOTHING UNTIL THOROUGHLY DECONTAMINATED.

INHALATION

REMOVE VICTIM TO FRESH AIR AND TREAT SYMPTOMATICALLY. PROVIDE OXYGEN IF BREATHING IS DIFFICULT. GIVE ARTIFICIAL RESPIRATION IF THE VICTIM IS NOT BREATHING. SEEK PROMPT MEDICAL ATTENTION.

INGESTION

DILUTE WITH LIQUID UNLESS THE VICTIM IS UNCONSCIOUS OR VERY DROWSY. IF VOMITING SPONTANEOUSLY OCCURS, KEEP THE VICTIM'S HEAD BELOW THE HIPS TO PREVENT ASPIRATION INTO THE LUNGS. CONSULT A PHYSICIAN, HOSPITAL OR POISON CONTROL CENTER AND/OR TRANSPORT TO AN EMERGENCY FACILITY IMMEDIATELY.

SECTION 5

FIRE FIGHTING MEASURES ______

flammability classification - OSHA : COMBUSTIBLE LIQUID - CLASS IIIB

- DOT : NOT REGULATED

EXTINGUISHING MEDIA

USE WATER FOG, FOAM, DRY CHEMICAL OR CARBON DIOXIDE.

SPECIAL FIRE FIGHTING PROCEDURES AND PRECAUTIONS

CLEAR FIRE AREA OF UNPROTECTED PERSONNEL. DO NOT ENTER CONFINED FIRE SPACE WITHOUT HELMET, FACE SHIELD, BUNKER COAT, GLOVES, RUBBER BOOTS, AND A POSITIVE PRESSURE NIOSH-APPROVED SELF-CONTAINED BREATHING APPARATUS.

UNUSUAL FIRE AND EXPLOSION HAZARDS

CONTAINERS EXPOSED TO INTENSE HEAT FROM FIRES SHOULD BE COOLED WITH WATER TO PREVENT VAPOR PRESSURE BUILDUP WHICH COULD RESULT IN CONTAINER RUPTURE, CONTAINER AREAS EXPOSED TO DIRECT FLAME CONTACT SHOULD BE COOLED WITH LARGE QUANTITIES OF WATER AS NEEDED TO PREVENT WEAKENING OF CONTAINER STRUCTURE.

E859-T49 (page 4) print date : 06/19/19

ACCIDENTAL RELEASE MEASURES

SPILL OR LEAK PROCEDURES

LARGE SPILLS >> EVACUATE THE HAZARD AREA OF UNPROTECTED PERSONNEL. WEAR APPROPRIATE RESPIRATOR AND PROTECTIVE CLOTHING. SHUT OFF SOURCE OF LEAK ONLY IF SAFE TO DO SO. DIKE AND CONTAIN. IF VAPOR CLOUD FORMS, WATER FOG MAY BE USED TO SUPPRESS; CONTAIN RUN-OFF. REMOVE WITH VACUUM TRUCKS OR PUMP TO STORAGE/SALVAGE VESSELS. SOAK UP RESIDUE WITH AN ABSORBENT SUCH AS CLAY, SAND OR OTHER SUITABLE MATERIAL; PLACE IN NON-LEAKING CONTAINERS FOR PROPER DISPOSAL. FLUSH AREA WITH WATER TO REMOVE TRACE RESIDUE; DISPOSE OF FLUSH SOLUTIONS AS ABOVE. SMALL SPILLS >> TAKE UP WITH AN ABSORBENT MATERIAL AND PLACE IN NON-LEAKING CONTAINERS; SEAL TIGHTLY FOR PROPER DISPOSAL.

SECTION 7

HANDLING AND STORAGE

FLAMMABILITY

NOT CLASSIFIED AS A HAZARDOUS SUBSTANCE OR MIXTURE WITH FLAMMABILITY.

EMPLOYEE PROTECTION

RESPIRATORY PROTECTION

AVOID PROLONGED OR REPEATED BREATHING OF VAPORS/MIST. IF EXPOSURE EXCEEDS TLV USE A NIOSH-APPROVED POSITIVE PRESSURE SUPPLIED AIR RESPIRATOR TO PREVENT OVER EXPOSURE.

PROTECTIVE CLOTHING

AVOID CONTACT WITH EYES. WEAR GOGGLES IF THERE IS A LIKELIHOOD OF CONTACT WITH EYES. DO NOT GET ON SKIN OR ON CLOTHING.

ADDITIONAL PROTECTIVE MEASURES

USE VENTILATION AS REQUIRED TO CONTROL VAPOR/DUST CONCENTRATIONS. EYE WASH FOUNTAINS AND SAFETY SHOWERS SHOULD BE AVAILABLE FOR USE IN AN EMERGENCY.

SECTION 9 PHYSICAL PROPERTIES

: 10.01 +/- .2 % volatile by volume : 68.46 +/-2% weight per gallon VOC as supplied is .8577 pounds per gallon. % volatile by weight : 56.24 +/-2%

: LIQUID FLAMMABILITY (SOLID, GAS: NOT AVAILABLE PHYSICAL STATE FLAMMABILITY/EXPLOSIVE LIMITS: NOT AVAILABLE COLOR : (T) Tan/Beige

: MILD SOLVENT VAPOR PRESSURE : NOT AVAILABLE ODOR VAPOR DENSITY : NOT AVAILABLE ODOR THRESHOLD : NOT AVAILABLE

RELATIVE DENSITY : 1.1260 : 9.0 - 11.0

SOLUBILITY MELTING/FREEZING POINT: NOT AVAILABLE : NOT AVAILABLE

INITIAL BOILING POINT : NOT AVAILABLE PARTITION COEFFICIENT : NOT RELEVANT : NOT AVAILABLE AUTO-IGNITION TEMPERATURE: NOT AVAILABLE BOILING RANGE

: NOT AVAILABLE DECOMPOSITION TEMPERATURE : NOT AVAILABLE EVAPORATION RANGE

VISCOSITY (AT 77F) : 55-60 KU, STORMER

flash point : 215 +/-2 degrees F. SETAFLASH

STABILITY AND REACTIVITY

STABILITY : STABLE

HAZARDOUS POLYMERIZATION : WILL NOT OCCUR

CONDITIONS AND MATERIALS TO AVOID

BASED ON THE PRESENCE OF COMPONENTS 1 AND 2 AVOID OXIDIZING MATERIALS.

E859-T49 (page 5) print date : 06/19/19

HAZARDOUS DECOMPOSITION PRODUCTS

CARBON DIOXIDE, CARBON MONOXIDE AND UNIDENTIFIED ORGANIC COMPOUNDS MAY BE FORMED DURING COMBUSTION. TOXICOLOGICAL INFORMATION SECTION 11 PEL/CEILING (OSHA) PEL/TWA ______ N/E 1 N/E N/E N/E N/E N/E N/E N/E N/E N/E ______ TLV/STEL no. (ACGIH) TLV/TWA TLV/CEILING N/E >> The dried film of this product may become a dust nuisance when removed by sanding or grinding. OSHA recommends a PEL/TWA of 15 mg/m3 for total dust and 5 mg/m3 for the respirable fraction. ACGIH recommends a TLV/TWA of 10 mg/m3 for total dust.

>> (SKIN) absorption may contribute to the overall exposure to this material. Take appropriate measures to prevent skin contact. (N/E = not established)

>> None of the components of this product are recognized as carcinogenic. ECOLOGICAL INFORMATION ______

001569-01-3 2-PROPOXYPROPANOL

Component

May be Harmful to Aquatic: Y Harmful to Aquatic Life : N Not Harmful to Aquatic Life: N

000124-68-5 2-AMINO-2-METHYL-1-PROPANOL

Harmful to Aquatic Life : N Not Harmful to Aquatic Life: Y May be Harmful to Aquatic: N

009002-84-0 POLYTETRAFLUORETHYLENE

Harmful to Aquatic Life : N Not Harmful to Aquatic Life: Y May be Harmful to Aquatic: N

075864-23-2 IRON MANGANESE OXIDE BLACK 33

Harmful to Aquatic Life : N Not Harmful to Aquatic Life: Y May be Harmful to Aquatic: N

DISPOSAL CONSIDERATIONS SECTION 13

WASTE DISPOSAL

CAS#

WASTE CHARACTERIZATIONS AND COMPLIANCE WITH APPLICABLE LAWS ARE THE SOLE RESPONSIBILITY OF THE END USER. ALL DISPOSAL PRACTICES USED FOR THIS PRODUCT AND ITS CONTAINER(S) MUST BE IN COMPLIANCE WITH ALL FEDERAL, STATE AND LOCAL LAWS AND REGULATIONS. THE INFORMATION PRESENTED IN THIS SDS PERTAINS ONLY TO THE PRODUCT AS SHIPPED.

print date : 06/19/19 E859-T49 (page 6) TRANSPORTATION INFORMATION Land Transport USDOT PAINT, NOI Proper shipping name: NOS Components Hazard class: ID-number: Packing group: Aquatic Toxicity: YES Sea Transport IMDG Proper shipping name: ENVIROMENTALLY HAZ SUBSTNCE NOS NOS Components FORMALIN Hazard class: 9 ID-number: UN3082 Packing group: III Aquatic Toxicity: YES Air Transport IATA/ICAO ENVIROMENTALLY HAZ SUBSTNCE NOS Proper shipping name: NOS Components : FORMALIN Hazard class: UN3082 ID-number: Packing group: III Aquatic Toxicity: YES ______ SECTION 15 REGULATORY INFORMATION CAS# Component 001569-01-3 2-PROPOXYPROPANOL US TSCA Inventory : YES Canada Domestic Substance List : YES EC : YES Philippines : YES Japan : UNKNOWN Korea : UNKNOWN China : YES Australia : YES 000124-68-5 2-AMINO-2-METHYL-1-PROPANOL US TSCA Inventory : YES Canada Domestic Substance List : YES EC : YES Philippines : YES Japan : YES Korea : YES China : UNKNOWN Australia : YES 009002-84-0 POLYTETRAFLUORETHYLENE US TSCA Inventory : YES Canada Domestic Substance List : YES EC : YES : YES Japan : YES Philippines Korea : YES

: YES

China

: YES

Australia

print date : 06/19/19 E859-T49 (page 7)

SECTION 15 075864-23-2 IRON MANGANESE OXIDE BLACK 33

US TSCA Inventory : YES Canada Domestic Substance List : YES EC : YES

: UNKNOWN Korea : UNKNOWN : YES Philippines Japan

REGULATORY INFORMATION CONTINUED

: UNKNOWN Australia : YES China

SECTION 15

REGULATORY INFORMATION CONTINUED

WARNING This product can expose you to chemicals including POLYETHER MODIFIED DIMETHYLPOLYSILXOANE, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

component CAS# SARA 2-PROPOXYPROPANOL 1569-01-3 NO 2-AMINO-2-METHYL-1-PROPANOL NO 124-68-5 POLYTETRAFLUORETHYLENE 9002-84-0 NO IRON MANGANESE OXIDE BLACK 33 75864-23-2 YES Under the reporting requirements of Section 313 of Title III of the Superfund

Amendments and Reauthorization Act of 1986 (SARA) and 40 CFR Part 372, chemicals listed on the Section 313 List (40 CFR Part 372.65) are identified under the heading 'SARA 313'.

SECTION 16 OTHER INFORMATION

- H M I S -

| HEALTH : 1 |
| FLAMMABILITY : 1 |
| REACTIVITY : 0 |
| PERSONAL PROTECT : X

(X = ask your supervisor for specialized handling directions)

CONTAINERS CAN CONTAIN HAZARDOUS PRODUCT RESIDUES EVEN WHEN EMPTY. WASH WITH SOAP AND WATER BEFORE EATING, DRINKING, SMOKING,

OR USING TOILET FACILITIES.

THE INFORMATION CONTAINED HEREIN IS BASED ON THE DATA AVAILABLE TO US AND IS BELIEVED TO BE CORRECT. HOWEVER, WE MAKE

NO WARRANTY, EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THIS DATA OR THE RESULTS TO BE OBTAINED FROM THE USE

THEREOF. WE ASSUME NO RESPONSIBILITY FOR INJURY FROM THE USE OF THE PRODUCT DESCRIBED HEREIN.