

**Safety Data Sheet**  
**DS-108F - P28201-NA**

Safety Data Sheet dated 8/27/2018, version 4

**1. IDENTIFICATION**

Product identifier

Mixture identification:

Trade name: DS-108F

Other means of identification:

SDS code: P28201-NA

Recommended use of the chemical and restrictions on use

Recommended use:

Solvent

Industrial uses

Professional uses

Restrictions on use:

No uses advised against are identified.

Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Company:

Dysol Inc. - 791 Westport Parkway - Fort Worth, TX 76177 / Phone: 1-817-335-1826 /  
csr-na@socomore.com/ Fax Number: 817-335-2405Distributor: SOCOMORE S.A.S. - Zone Industrielle du Prat - CS 23707 - 56037 VANNES  
CEDEX - France - Tel : +33 (0)2 97 43 76 83 - Fax : +33 (0)2 97 54 20 26Distributor: Socomore Ltd - 5, Coe Avenue - Loughborough - Leicestershire - LE11 4SE - UK  
- Tel: +44 1509 262040 - Fax: +44 1509 262046Distributor: Socomore Iberia - Calle Diputacio, 260 - 08007 Barcelona - Espana - Tel: +34 917  
693 962 - Fax: +34 902 908 966Distributor: MagChem Inc. 1271, rue Ampere, suite 101, Boucherville, QC, J4B 5Z5 Canada -  
Tel: 1-450 641 8500 - Fax: 1-450 655 1717Distributor: Socomore GmbH - c/o MAZARS GmbH - Theodor-Stern-Kai 1 - 60596 Frankfurt  
am Main - Deutschland - Tel: +49 (0)89 20 70 28 83 - Fax: +49 (0) 89 88 91 98 16Distributor: Socomore Trading Shangai - 355 East Kang Qiao Road - Kang Qiao Industrial  
Zone - Pudong - 201315 Shangai - Tel: 862158131133 - Fax: 862158131933Dystrybutor : SOCOMORE SPzoo - Ul. Piekna 18, 00-549 Warszawa Polska - Tel : +48 608  
454 114 - Fax : +48 (22) 621 61 09

Competent person responsible for the safety data sheet:

techdirsocomore@socomore.com

Emergency phone number

CHEMTEL: 1-800-255-3924 (USA) / CANUTEC: 1-613-996-6666 (CANADA)

**2. HAZARD(S) IDENTIFICATION**

Classification of the chemical



Warning, Flam. Liq. 3, Flammable liquid and vapour.



Danger, Eye Dam. 1, Causes serious eye damage.



Warning, STOT SE 3, May cause respiratory irritation.



Danger, Asp. Tox. 1, May be fatal if swallowed and enters airways.

**Safety Data Sheet**  
**DS-108F - P28201-NA**

Label elements

Hazard pictograms:



Danger

Hazard statements:

H226 Flammable liquid and vapour.

H318 Causes serious eye damage.

H335 May cause respiratory irritation.

H304 May be fatal if swallowed and enters airways.

Precautionary statements:

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ventilating/lighting/equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P261 Avoid breathing vapours.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves and eye/face protection.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor/...

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing.

Rinse skin with water/shower.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P312 Call a POISON CENTER/doctor if you feel unwell.

P331 Do NOT induce vomiting.

P370+P378 In case of fire, use a CO2 fire extinguisher to extinguish.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P403+P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

P501 Dispose of contents/container in accordance with applicable regulations.

Special Provisions:

None

Hazards not otherwise classified identified during the classification process:

None

Ingredient(s) with unknown acute toxicity:

None.

---

**3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substances

N.A.

Mixtures

Hazardous components within the meaning of 29 CFR 1910.1200 and related classification:

## Safety Data Sheet

### DS-108F - P28201-NA

>= 60% - < 70% ethyl lactate; ethyl DL-lactate;  
Index number: 607-129-00-7, CAS: 97-64-3, EC: 202-598-0

 B.6/3 Flam. Liq. 3 H226


 A.8/3 STOT SE 3 H335

 A.3/1 Eye Dam. 1 H318

>= 20% - < 25% Isoparaffinic Hydrocarbon

CAS: 64742-48-9

B.6/4 Flam. Liq. 4 H227

 A.10/1 Asp. Tox. 1 H304

>= 15% - < 20% 1-PROPOXY-2-PROPANOL

REACH No.: 01-2119474443-37, CAS: 1569-01-3, EC: 216-372-4

 B.6/3 Flam. Liq. 3 H226

 A.3/2A Eye Irrit. 2A H319

---

#### 4. FIRST-AID MEASURES

Description of necessary measures

In case of skin contact:

Immediately take off all contaminated clothing.

OBTAIN IMMEDIATE MEDICAL ATTENTION.

Remove contaminated clothing immediately and dispose off safely.

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

Protect uninjured eye.

In case of Ingestion:

Do NOT induce vomiting.

In case of Inhalation:

In case of inhalation, consult a doctor immediately and show him packing or label.

Most important symptoms/effects, acute and delayed

None

Indication of immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

No particular treatment.

---

#### 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media:

In case of fire, use a CO2 fire extinguisher to extinguish.

Unsuitable extinguishing media:

None in particular.

Specific hazards arising from the chemical

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

## Safety Data Sheet

### DS-108F - P28201-NA

Hazardous combustion products:

None

Explosive properties: N.A.

Oxidizing properties: N.A.

Special protective equipment and precautions for fire-fighters

Use suitable breathing apparatus .

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

---

#### 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment, and emergency procedures

Wear personal protection equipment.

Remove all sources of ignition.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

Provide adequate ventilation.

Remove persons to safety.

Use appropriate respiratory protection.

See protective measures under point 7 and 8.

Methods and materials for containment and cleaning up

Wash with plenty of water.

---

#### 7. HANDLING AND STORAGE

Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Do not use on extensive surface areas in premises where there are occupants.

Use localized ventilation system.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

Contaminated clothing should be changed before entering eating areas.

Do not eat or drink while working.

See also section 8 for recommended protective equipment.

Conditions for safe storage, including any incompatibilities

Always keep in a well ventilated place.

Keep away from unguarded flame, sparks, and heat sources. Avoid direct exposure to sunlight.

Avoid accumulating electrostatic charge.

Keep away from food, drink and feed.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Cool and adequately ventilated.

Safety electric system.

Storage temperature:

Store at ambient temperature.

---

#### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Isoparaffinic Hydrocarbon - CAS: 64742-48-9

- OEL Type: OSHA - TWA: 400 mg/m<sup>3</sup>, 100 ppm

1-PROPOXY-2-PROPANOL - CAS: 1569-01-3

- OEL Type: ACGIH - TWA: 25 ppm

## Safety Data Sheet

### DS-108F - P28201-NA

#### DNEL Exposure Limit Values

1-PROPOXY-2-PROPANOL - CAS: 1569-01-3

Worker Industry: 217 mg/m<sup>3</sup> - Consumer: 26 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Long Term, systemic effects

Consumer: 2.2 mg/kg bw/day - Exposure: Human Oral - Frequency: Long Term, systemic effects

#### PNEC Exposure Limit Values

1-PROPOXY-2-PROPANOL - CAS: 1569-01-3

Target: Fresh Water - Value: 0.1 mg/l

Target: Marine water - Value: 0.01 mg/l

Target: Microorganisms in sewage treatments - Value: 4 mg/l

Target: Freshwater sediments - Value: 0.386 mg/l - Notes:: mg/kg p.s.

Target: Marine water sediments - Value: 0.0386 mg/kg - Notes:: mg/kg p.s.

Target: Soil (agricultural) - Value: 0.0185 mg/kg - Notes:: mg/kg p.s.

Target: PNEC intermittent - Value: 1 mg/l

#### Appropriate engineering controls:

None

#### Individual protection measures

##### Eye protection:

Use close fitting safety goggles, don't use eye lens.

##### Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

##### Protection for hands:

Use protective gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber.

##### Respiratory protection:

Use respiratory protection where ventilation is insufficient or exposure is prolonged.

##### Thermal Hazards:

None

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Properties	Value	Method:	Notes
Appearance and colour:	CLEAR LIQUID	--	--
Odour:	LEMON-LIME	--	--
Odour threshold:	N.A.	--	--
pH:	Not Relevant	--	--
Melting point / freezing point:	N.A.	--	--
Initial boiling point and boiling range:	160 191 196 °C/ 320 376 385 °F	--	--
Flash Point (°F):	115°F	--	--
Flash point (°C):	46°C	--	--
Evaporation rate:	0.30-0.40	--	--
Solid/gas flammability:	Not Relevant	--	--
Upper/lower flammability or explosive limits:	1.5	--	--
Vapour pressure:	1.1 (mm of Hg)@20 C	--	--
Vapour density:	4.9	--	--

## Safety Data Sheet

### DS-108F - P28201-NA

Relative density:	0.95	--	--
Solubility in water:	soluble	--	--
Solubility in oil:	N.A.	--	--
Partition coefficient (n-octanol/water):	N.A.	--	--
Auto-ignition temperature:	349°C/660°F	--	--
Decomposition temperature:	Not Relevant	--	--
Viscosity:	Not Relevant	--	--
Explosive properties:	N.A.	--	--
Oxidizing properties:	N.A.	--	--

#### 9.2. Other information

Properties	Value	Method:	Notes
Miscibility:	N.A.	--	--
Fat Solubility:	N.A.	--	--
Conductivity:	Not Relevant	--	--
Substance Groups relevant properties	N.A.	--	--

## 10. STABILITY AND REACTIVITY

#### Reactivity

It may generate dangerous reactions (See subsections below)

#### Chemical stability

It may generate dangerous reactions (See subsections below)

#### Possibility of hazardous reactions

None

#### Conditions to avoid

Avoid accumulating electrostatic charge.

#### Incompatible materials

Avoid contact with combustible materials. The product could catch fire.

#### Hazardous decomposition products

None.

## 11. TOXICOLOGICAL INFORMATION

#### Information on toxicological effects

#### Toxicological information of the product:

N.A.

#### Toxicological information of the main substances found in the product:

1-PROPOXY-2-PROPANOL - CAS: 1569-01-3

##### a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat > 2.000 mg/kg

Test: LC50 - Route: Inhalation Vapour - Species: Rat = 8.34 mg/l - Duration: 4h

#### Substance(s) listed on the NTP report on Carcinogens:

None.

#### Substance(s) listed on the IARC Monographs:

None.

#### Substance(s) listed as OSHA Carcinogen(s):

None.

#### Substance(s) listed as NIOSH Carcinogen(s):

None.

**Safety Data Sheet**  
**DS-108F - P28201-NA**

**12. ECOLOGICAL INFORMATION**

Ecotoxicity

Adopt good working practices, so that the product is not released into the environment.

1-PROPOXY-2-PROPANOL - CAS: 1569-01-3

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish > 100 mg/l - Duration h: 96

Endpoint: LC50 - Species: Daphnia > 100 mg/l - Duration h: 48

Endpoint: EC50 - Species: Algae = 1.466 mg/l - Duration h: 96

c) Bacteria toxicity:

Endpoint: EC50 - Species: bacteria = 3.800 mg/l - Duration h: 16

Persistence and degradability

1-PROPOXY-2-PROPANOL - CAS: 1569-01-3

Biodegradability: Biodegradability rate - Test: OECD 301A - Duration: 28 days - %: 91.5

- Notes: N.A.

Bioaccumulative potential

1-PROPOXY-2-PROPANOL - CAS: 1569-01-3

BCF - Test: N.A. <100 - Duration: N.A. - Notes: N.A.

Log Pow - Test: N.A. 0.621 - Duration: N.A. - Notes: N.A.

Mobility in soil

1-PROPOXY-2-PROPANOL - CAS: 1569-01-3

Log Koc - Test: N.A. 1-1,9 - Duration: N.A. - Notes: N.A.

Volality (H: Henry's Law Constant) - Test: N.A.  $3,44 \cdot 10^{-7}$  atm m<sup>3</sup>/mol - Duration: N.A. -

Notes: 25°C

Other adverse effects

No harmful effects expected.

**13. DISPOSAL CONSIDERATIONS**

Waste treatment and disposal methods

Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force.

**14. TRANSPORT INFORMATION**

As defined in the general regulation 49 CFR 173.120(b), this product when shipped as non- bulk can be reclassified as not dangerous.



UN number

ADR-UN Number: UN1993

DOT number: UN1993

IATA-UN Number: UN1993

IMDG-UN Number: UN1993

UN proper shipping name

ADR-Shipping Name: FLAMMABLE LIQUID, N.O.S. (ethyl lactate; ethyl DL-lactate; 1-Propoxy-2-propanol)

DOT-Shipping Name: FLAMMABLE LIQUID, N.O.S. (ethyl lactate; ethyl DL-lactate; 1-Propoxy-2-propanol)

IATA-Shipping Name: FLAMMABLE LIQUID, N.O.S. (ethyl lactate; ethyl DL-lactate; 1-Propoxy-2-propanol)

## Safety Data Sheet

### DS-108F - P28201-NA

IMDG-Shipping Name:	FLAMMABLE LIQUID, N.O.S. (ethyl lactate; ethyl DL-lactate;, 1-Propoxy-2-propanol)
Transport hazard class(es)	
ADR-Class:	3
DOT Hazard Class:	3
IATA-Class:	3
IATA-Label:	3
IMDG-Class:	3
Packing group	
ADR-Packing Group:	III
DOT Packing group:	III
IATA-Packing group:	III
IMDG-Packing group:	III
Environmental hazards	
ADR-Environmental Pollutant:	No
IMDG-Marine pollutant:	No
Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code)	N.A.
Special precautions	
DOT Special provisions:	B1, B52, IB3, T4, TP1, TP29
DOT Labels:	3
ADR-Subsidiary risks:	-
ADR-S.P.:	B1, B52, IB3, T4, TP1, TP29
ADR-Transport category (Tunnel restriction code): (D/E)	
IATA-Passenger Aircraft:	355
IATA-Subsidiary risks:	-
IATA-Cargo Aircraft:	366
IATA-S.P.:	A3
IATA-ERG:	3L
IMDG-EmS:	F-E , S-E
IMDG-Subsidiary risks:	-
IMDG-Stowage and handling:	Category A
IMDG-Segregation:	-
Q.L.: 5L	
Q.E.: E1	

## 15. REGULATORY INFORMATION

### USA - Federal regulations

TSCA - Toxic Substances Control Act

TSCA inventory: all the components are listed on the TSCA inventory.

TSCA listed substances:

ethyl lactate; ethyl DL-lactate; is listed in TSCA Section 8b

Isoparaffinic Hydrocarbon is listed in TSCA Section 8b

1-PROPOXY-2-PROPANOL is listed in TSCA Section 8b.

SARA - Superfund Amendments and Reauthorization Act

Section 302 - Extremely Hazardous Substances: no substances listed.

Section 304 - Hazardous substances: no substances listed.

Section 313 - Toxic chemical list: no substances listed.

CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act

No substances listed.

CAA - Clean Air Act

CAA listed substances:

None.



## Safety Data Sheet

### DS-108F - P28201-NA

CWA - Clean Water Act  
CWA listed substances:  
None.

USA - State specific regulations

California Proposition 65

Substance(s) listed under California Proposition 65:

None.

Massachusetts Right to know

Substance(s) listed under Massachusetts Right to know:

ethyl lactate; ethyl DL-lactate;.

New Jersey Right to know

Substance(s) listed under New Jersey Right to know:

ethyl lactate; ethyl DL-lactate;.

Pennsylvania Right to know

Substance(s) listed under Pennsylvania Right to know:

ethyl lactate; ethyl DL-lactate;.

The following substance(s) in this product has/have an identification by CAS number either in countries not affected by the REACH regulation or in regulations not yet updated to reflect the new naming convention for hydrocarbon solvents:

---

## 16. OTHER INFORMATION

Full text of phrases referred to in Section 3:

H226 Flammable liquid and vapour.

H335 May cause respiratory irritation.

H318 Causes serious eye damage.

H227 Combustible liquid.

H304 May be fatal if swallowed and enters airways.

H319 Causes serious eye irritation.

Safety Data Sheet dated 8/27/2018, version 4

Disclaimer:

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality. The information relates only to the specific material and may not be valid for such material used in combination with any other material or in any process.

This Safety Data Sheet cancels and replaces any preceding release.

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

CAS: Chemical Abstracts Service (division of the American Chemical Society).

CLP: Classification, Labeling, Packaging.

DNEL: Derived No Effect Level.

EINECS: European Inventory of Existing Commercial Chemical Substances.

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

HMIS: Hazardous Materials Identification System

IARC: International Agency for Research on Cancer

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO: International Civil Aviation Organization.

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization"

## Safety Data Sheet

### DS-108F - P28201-NA

	(ICAO).
IMDG:	International Maritime Code for Dangerous Goods.
INCI:	International Nomenclature of Cosmetic Ingredients.
KSt:	Explosion coefficient.
LC50:	Lethal concentration, for 50 percent of test population.
LD50:	Lethal dose, for 50 percent of test population.
NFPA:	National Fire Protection Association
NIOSH:	National Institute for Occupational Safety and Health
NTP:	National Toxicology Program
OSHA:	Occupational Safety and Health Administration
PNEC:	Predicted No Effect Concentration.
RID:	Regulation Concerning the International Transport of Dangerous Goods by Rail.
STEL:	Short Term Exposure limit.
STOT:	Specific Target Organ Toxicity.
TLV:	Threshold Limiting Value.
TWA:	Time-weighted average