# **SAFETY DATA SHEET**



#### 1. PRODUCT AND COMPANY IDENTIFICATION

Product name: INSTAbond ® M-100

Part Numbers: A-A 3097 Notice 4 Type 1, Class 2

Product type: Cyanoacrylate Restriction of Use: None Issue Date: March 15, 2019

Company address: ACCRAbond Corporation 8848 Hacks Cross Road Olive Branch, MS 38654

**Contact Information:** 

Telephone: (662) 895-4480

CHEMTREC 1-800-424-9300 (toll free) or

1-703-527-3887

Internet: www.accrabond.com

#### 2. HAZARDS IDENTIFICATION

**EMERGENCY OVERVIEW** 

DANGER: BONDS SKIN IN SECONDS.

COMBUSTIBLE LIQUID. CAUSES EYE IRRITATION.

MAY CAUSE RESPIRATORY IRRITATION. MAY CAUSE GENETIC DEFECTS.

HAZARD CLASS	HAZARD CATEGORY
FLAMMABLE LIQUID	4
EYE IRRITATION	2B
GERM CELL MUTAGENICITY	1B
SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE	3





#### **Precautionary Statements**

**Prevention:** 

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, sparks, open flames, hot surfaces - no smoking. Avoid breathing vapors, mist, or spray. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves, eye protection, and face protection. Use

personal protective equipment as required.

Response:

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

**IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to remove. Continue rinsing. IF exposed or concerned: Get medical attention. If eye irritation persists: Get medical attention. In case of fire: Use foam, dry chemical or carbon dioxide to extinguish.

Storage:

Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place.

Keep cool. Store locked up.

Disposal:

Dispose of contents and/or container according to Federal, State/Provincial and local

governmental regulations.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

# 3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*
Methyl 2-cyanoacrylate	7085-85-0	60- 100
Thickener	Proprietary	5 - 10
Hydroquinone	123-31-9	0.1 - 1

<sup>·</sup> Exact percentage is a trade secret.

#### 4. FIRST AID MEASURES

**Inhalation:** Move to fresh air. If breathing is difficult, give oxygen. If not breathing, give

artificial respiration. If symptoms develop and persist, get medical attention.

**Skin contact:**Do not pull bonded skin apart. Soak in warm soapy water. Gently peel apart using a blunt instrument. If skin is burned due to the rapid generation of heat

using a blunt instrument. If skin is burned due to the rapid generation of heat by a large drop, seek medical attention. If lips are bonded, apply warm water to the lips and encourage wetting and pressure from saliva in mouth. Peel or

roll lips apart. Do not pull lips apart with direct opposing force.

**Eye contact:** Immediately flush with plenty of water for at least 15 minutes. Get medical

attention. If eyelids are bonded closed, release eyelashes with warm water by covering with a wet pad. Do not force eye open. Cyanoacrylate will bond to eye protein and will cause a lachrymatory effect which will help to debond the adhesive. Keep eye covered until debonding is complete, usually within 1-3 days. Medical attention should be sought in case solid particles of polymerized cyanoacrylate trapped behind the eyelid caused abrasive damage.

**Ingestion:** Ensure breathing passages are not obstructed. The product will polymerize

rapidly and bond to the mouth making it almost impossible to swallow. Saliva will separate any solidified product in several hours. Prevent the patient from

swallowing any separated mass.

Symptoms: See Section 11.

**Notes to physician:** Surgery is not necessary to separate accidentally bonded tissues. Experience

has shown that bonded tissues are best treated by passive, non-surgical first aid. If rapid curing has caused thermal burns they should be treated

symptomatically after adhesive is removed.

## 5. FIRE FIGHTING MEASURES

Extinguishing media: Water spray (fog), foam, dry chemical or carbon dioxide.

Special firefighting procedures: Wear a self-contained breathing apparatus with a full face piece operated in

pressure-demand or other positive pressure mode.

Unusual fire or explosion hazards: None

Hazardous combustion products: Trace amounts of irritating fumes may be released. Use in well ventilated

area or with a breathing apparatus.

#### **6. ACCIDENTAL RELEASE MEASURES**

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

**Environmental precautions:** Ventilate area. Do not allow product to enter sewer or waterways.

Clean-up methods: Do not use cloths for mopping up. Flood with water to complete polymerization

and scrape off the floor. Cured material can be disposed of as non-hazardous waste. Refer to Section 8 "Exposure Controls / Personal Protection" prior to

dean up.

# 7. HANDLING AND STORAGE

**Handling:** Prevent contact with eyes, skin and dothing. Do not breathe vapor and mist.

Wash thoroughly after handling. Avoid contact with fabric or paper goods. Contact with these materials may cause rapid polymerization which can generate smoke and strong irritating vapors, and cause thermal burns.

Storage: Keep in a cool, well ventilated area away from heat, sparks and open flame.

Keep container tightly closed until ready for use.

# 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Methyl 2-cyanoacrylate	0.2 ppm TWA	None	None	None
Thickener	None	None	None	None
Hydroquinone	1 mg/m3 TWA (Dermal sensitization)	2 mg/m3 PEL	None	None

**Engineering controls:**Use positive down-draft exhaus ventilation if general ventilation is

insufficient to maintain vapor concentration below established exposure

limits.

Use a NIOSH approved supplied air respirator with an organic cartridge if the

potential to exceed established exposure limits exists.

Eye/face protection:

Skin protection:

Respiratory protection:

Safety goggles or safety glasses with side shields. Full face protection should

be used if the potential for splashing  ${f or}$  spraying of product exists.

Only use nitrile gloves and aprons as necessary to prevent contact.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Liquid

 Color:
 Clear, Colorless

 Odor:
 Sharp, Imitating

 Odor threshold:
 1 - 2 ppm

 pH:
 Not applicable

 Vapor pressure:
 <0.2 mm hg</th>

 Boiling point/range:
 > 149 °C (>300.2

Boiling point/range:  $> 149 \,^{\circ}\text{C} \, (>300.2 \,^{\circ}\text{F})$  Melting point/ range: Not determined Specific gravity:  $1.09 \, \text{at } 23.9 \,^{\circ}\text{C} \, (75.02 \,^{\circ}\text{F})$ 

Vapor density: 3 Approximately
Flash point: 80 -93 °C (176°F - 199.4 °F) Tagliabue closed cup

Flammable/Explosive limits -lower:

Flammable/Explosive limits -upper:

Autoignition temperature:

Not determined
485°C (905°F)
Not determined

Evaporation rate:

Solubility in water:

Not determined
Polymerises in presence of water

VOC content:

# 10. STABILITY AND REACTIVITY

**Stability:** Stable under recommended storage conditions.

Hazardous reactions: Rapid exothermic polymerization will occur in the presence of water, amines, alkalis and

alcohols.

Hazardous decomposition

products:

None

**Incompatible materials:** Water, amines, alkalis and alcohols.

**Reactivity:** Not available.

Conditions to avoid: Spontaneous polymerization,

# 11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure: Skin, Inhalation, Eyes

**Potential Health Effects/Symptoms** 

Inhalation: May cause respiratory tract irritation. Exposure to vapors above the established exposure limit

results in respiratory irritation, which may lead to difficulty in breathing and tightness in the

chest.

**Skin contact:** Bonds skin in seconds. May cause skin irritation. Cyanoacrylates have been reported to cause

allergic reaction but due to rapid polymerization at the skin surface, an allergic response is rare. Cyanoacrylates generate heat on solidification. In rare circumstances a large drop will burn the

skin. Cured adhesive does not present a health hazard even if bonded to the skin.

Thirty ting to pure Causes puressing topping. Fuelide may bond

Irritating to eyes. Causes excessive tearing. Eyelids may bond.

Ingestion:

Not expected to be harmful by inaction. Papidly polymerizes (see

Ingestion: Not expected to be harmful by ingestion. Rapidly polymerizes (solidifies) and bonds in mouth.

It is almost impossible to swallow.

Hazardous Component(s)	LD5Os and LC5D5	Immediate and Delayed Health Effects
Ethyl 2-cyanoacrylate	None	Irritant, Allergen, Respiratory
Thickener	None	Irritant
	Oral LD50 (RAT) = 320 mg/kg	Blood, Bone Marrow, Central nervous
Hydroquinone	Oral LD50 (RABBIT) = $540 \text{ mg/kg}$	system, Developmental, Eyes, Immune
	Dermal LD50 (RAT) = $> 900 \text{ mg/kg}$	system, Irritant, Liver, Mutagen, Skin, Thyroid

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Ethyl 2-cyanoacrylate	No	No	No
Thickener	No	No	No
Hydroguinone	No	No	No

## 12. ECOLOGICAL INFORMATION

**Ecological information:** Not available.

#### 13. DISPOSAL CONSIDERATIONS

Recommended method of disposal: Follow all local, state, federal and provincial regulations for disposal.

**Hazardous waste number:**Not a RCRA hazardous waste.

## 14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

U.S. Department of Transportation Ground (49 CFR)

Combustible liquid, n.o.s. (Cyanoacrylate ester) Proper shipping name:

Hazard class or division: Combustible Liquid

**Identification number:** NA 1993

Packing group:

**DOT Hazardous Substance(s):** Hydroquinone

International Air Transportation (ICAO/IATA)

Proper shipping name: Hazard class or division: Aviation regulated liquid, n.o.s. (Cyanoacrylate ester)

**Identification number:** UN 3334 Packing group:

(Not more than 500m1) Unrestricted **Exceptions:** 

Water Transportation (IMO/IMDG)

Not regulated Proper shipping name: Hazard class or division: None **Identification number:** None Packing group: None

# 15. REGULATORY INFORMATION

**United States Regulatory Information** 

All components are listed or are exempt from listing on the Toxic Substances Control Act TSCA 8 (b) Inventory Status:

Inventory.

None above reporting de minimis TSCA 12 (b) Export Notification:

None above reporting de minimis

**CERCLAISARA Section 302 EHS:** Immediate Health, Delayed Health, Fire, Reactive CERCLA/SARA Section 3111312:

None above reporting de minimis

CERCLA/SARA Section 313: Hydroquinone (CAS# 123-31-9) 100 lbs. (45.4 kg) **CERCLA Reportable quantity:** 

No California Proposition 65 listed chemicals are known to be present. California Proposition 65:

## 16. OTHER INFORMATION

#### GLOSSARY:

ACGIH- American Conference of Governmental Industrial Hygienists; ANSI- American National Standards Institute; Canadian TDG-Canadian Transportation of Dangerous Goods; CAS- Chemical Abstract Service; Chemtrec- Chemical Transportation Emergency Center (US); CHIP- Chemical Hazard Information and Packaging; DSL- Domestic Substances List; EC- Equivalent Concentration; EH40 (UK)- HSE Guidance Note EH40 Occupational Exposure Limits; EPCRA- Emergency Planning and Community Right-To-Know Act; ESL- Effects screening levels; HMIS- Hazardous Material Information Service; LC- Lethal Concentration; LD- Lethal Dose; NFPA-National Fire Protection Association; OEL- Occupational Exposure Limits; OSHA- Occupational Safety and Health Administration, US Department of Labor; PEL- Permissible Exposure Limit; SARA (Title III)- Superfund Amendments and Reauthorization Act; SARA 313-Superfund Amendments and Reauthorization Act, Section 313; SCBA- Self-Contained Breathing Apparatus; STEL- Short Term Exposure Limit; TCEQ- Texas Commission on Environmental Quality; TLV- Threshold Limit Value; TSCA- Toxic Substances Control Act Public Law 94-469; TWA- Time Weighted Value; US DOT- US Department of Transportation; WHMIS- Workplace Hazardous Materials Information System.

#### Disclaimer:

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.