



SAFETY DATA SHEET

Issuing Date: 18-Mar-2021

Revision Date: 25-Mar-2021

Print Date: 25-Mar-2021

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product Code: 08628KUZ-ULVOC

Product Name: SAE AMS-STD-595 37038 AIRCRAFT BLACK
1.0 VOC ZENTHANE® MIL-DTL-53039E, TYPE IV

Hentzen Coatings, Inc.
6937 West Mill Road, Milwaukee, WI 53218-1225

Company Phone Number: 1-414-353-4200

Emergency telephone number ChemTrec 1-800-424-9300

Recommended use of the chemical and restrictions on use

Industrial paint (Paint or Paint-Related), Restricted to professional users

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Carcinogenicity	Category 2
Reproductive Toxicity	Category 1B
Flammable Liquids	Category 3

Label Elements

Emergency Overview

DANGER

Hazard Statements

Suspected of causing cancer
May damage fertility or the unborn child
Flammable liquid and vapor



Appearance Opaque

Physical state Liquid

Odor Solvent

Precautionary Statements - Prevention

Obtain special instructions before use
Do not handle until all safety precautions have been read and understood
Use personal protective equipment as required
Keep away from heat/sparks/open flames/hot surfaces. - No smoking
Keep container tightly closed
Ground/Bond container and receiving equipment
Use explosion-proof electrical/ ventilating/ lighting/ equipment
Use only non-sparking tools
Take precautionary measures against static discharge

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
In case of fire: Use CO₂, dry chemical, or foam for extinction

Precautionary Statements - Storage

Store in a well-ventilated place. Keep cool
Store in accordance with local regulations

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Other information

- May be harmful in contact with skin
- Toxic to aquatic life with long lasting effects
- Toxic to aquatic life

3. COMPOSITION/INFORMATION ON INGREDIENTS

Contains a known or suspected carcinogen

This product does not contain any substances regulated as hazardous air pollutants (HAPS) under Section 112 of the Clean Air Act Amendments of 1990.

Chemical Name	CAS No	Weight-%	ACGIH	OSHA
p-CHLOROBENZOTRIFLUORIDE	98-56-6	40% - 50%	TWA: 2.5 mg/m ³ F	TWA: 2.5 mg/m ³ F
POLYPROPYLENE	9003-07-0	10% - 20%	N/A	N/A
HOMOPOLYMER OF HEXAMETHYLENE DIISOCYANATE	28182-81-2	10% - 20%	N/A	N/A
MIXTURE OF AROMATIC HYDROCARBONS	64742-94-5	1% - 5%	N/A	N/A
CARBON BLACK	1333-86-4	1% - 5%	TWA: 3 mg/m ³ inhalable particulate matter	TWA: 3.5 mg/m ³
DIBUTYL TIN DILAURATE	77-58-7	0% - 1%	STEL: 0.2 mg/m ³ Sn TWA: 0.1 mg/m ³ Sn S*	TWA: 0.1 mg/m ³ Sn

4. FIRST AID MEASURES

First Aid Measures

General advice

Immediate medical attention is required. Show this safety data sheet to the doctor in attendance. If symptoms persist, call a physician.

Eye Contact

Immediately flush eyes with water for at least 15 minutes. Get medical attention. If easy to do, remove contact lenses. Keep eye wide open while rinsing. If symptoms persist, call a physician.

Skin Contact

Wash off immediately with soap and plenty of water. Consult a physician if necessary. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

Inhalation

Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Consult a physician if necessary. If breathing is irregular or stopped, administer artificial respiration. Immediate medical attention is not required. Move to fresh air in case of accidental inhalation of vapors or decomposition products. If symptoms persist, call a physician. Asthma-like and/ or skin allergy-like symptoms.

Ingestion

Do NOT induce vomiting. Drink plenty of water. Rinse mouth. If symptoms persist, call a physician. Clean mouth with water and afterwards drink plenty of water. Never give

anything by mouth to an unconscious person. Consult a physician if necessary.

Self-protection of the first aider Remove all sources of ignition. Use personal protective equipment as required.

Most important symptoms and effects, both acute and delayed

Most Important Symptoms and Effects No information available.

Indication of any immediate medical attention and special treatment needed

Notes to physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable Extinguishing Media No information available.

Specific hazards arising from the chemical

Flammable. Containers may explode when heated or if contaminated with water.

Explosion Data

Sensitivity to Mechanical Impact no data available.

Sensitivity to Static Discharge Yes.

Protective equipment and precautions for firefighters

Wear self-contained breathing apparatus and protective suit.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions Evacuate personnel to safe areas. Ensure adequate ventilation. Remove all sources of ignition. Use personal protective equipment as required. Keep people away from and upwind of spill/leak. Avoid breathing vapors or mists. Ventilate the area.

Other information DECONTAMINATION SOLUTION: Concentrated ammonia (3 - 8%), detergent (2%) and water (90 - 95%), a solution of Union Carbide's Tergitol TMN-10 (20%) and water (80%) or a solution of 50% isopropanol, 45% water, and 5% concentrated ammonia solution(% by weight).

Environmental Precautions

Environmental Precautions Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. Do not flush into surface water or sanitary sewer system. Vapors are heavier than air, spread along floors and form explosive mixtures with air.

Methods and materials for containment and cleaning up

Methods for Containment Prevent further leakage or spillage if safe to do so. Dike far ahead of liquid spill for later disposal. Decontaminate floor with decontamination solution letting stand for at least 15 minutes. Soak up with inert absorbent material.

Methods for Cleaning Up Pick up and transfer to properly labeled containers. Dam up. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Soak up with inert absorbent material.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Ensure adequate ventilation. Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharges. Use explosion-proof electrical (ventilation and lighting) equipment. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Use with local exhaust ventilation. Wear protective gloves/protective clothing/eye protection/face protection. Do not breathe vapor or mist. To dissipate static electricity during transfer, ground drum and connect to receiving container with bonding strap. Use only non-sparking tools.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep tightly closed in a dry and cool place. Keep in properly labeled containers. Keep away from heat, sparks and flame. Keep containers tightly closed in a cool, well-ventilated place. Protect from moisture.

Incompatible Products Water. Glycol ethers. Alcohols. Epoxies. Bases.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH	OSHA	NIOSH IDLH
p-CHLOROBENZOTRIFLUORIDE 98-56-6	TWA: 2.5 mg/m ³ F	TWA: 2.5 mg/m ³ F	IDLH: 250 mg/m ³ F
CARBON BLACK 1333-86-4	TWA: 3 mg/m ³ inhalable particulate matter	TWA: 3.5 mg/m ³	IDLH: 1750 mg/m ³ TWA: 3.5 mg/m ³ TWA: 0.1 mg/m ³ Carbon black in presence of Polycyclic aromatic hydrocarbons PAH
DIBUTYL TIN DILAURATE 77-58-7	STEL: 0.2 mg/m ³ Sn TWA: 0.1 mg/m ³ Sn S*	TWA: 0.1 mg/m ³ Sn	IDLH: 25 mg/m ³ Sn TWA: 0.1 mg/m ³ except Cyhexatin Sn

NIOSH IDLH: *Immediately Dangerous to Life or Health*

Exposure controls

Engineering Measures Persons allergic to isocyanates, and particularly those suffering from asthma or other respiratory conditions, should not work with isocyanates.

Individual protection measures, such as personal protective equipment

- Eye/Face Protection** Use personal protective equipment as required.
- Skin and Body Protection** Chemical resistant apron.
- Respiratory Protection** If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

Hygiene Measures Do not eat, drink or smoke when using this product. Regular cleaning of equipment, work area and clothing is recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state	Liquid	Appearance	Opaque
Odor	Solvent.	Odor Threshold	No data available

pH	No data available	Flash Point	100 °F / 38 °C
Decomposition temperature	No data available	Boiling Point	277 °F / 136 °C
Melting Point / Melting Range	No data available	Freezing Point	No data available
Vapor Pressure @20°C (kPa)	No data available	Partition coefficient:	No data available
Vapor Density	No data available	Density	No data available
Bulk density	No data available	Specific Gravity	1.25
Evaporation Rate	No data available	Water solubility	No data available
Dynamic viscosity	No data available	Weight per Gallon (lbs/gal):	10.40
		EPA VOC (lb/gal)	0.86
Flammability Limits in Air			
Upper	0.03 %		
Lower	0 %		

10. STABILITY AND REACTIVITY

Reactivity

No data available

Chemical stability

Stable under recommended storage conditions.

Conditions to Avoid

Heat, flames and sparks.

Incompatible Materials

Water. Glycol ethers. Alcohols. Epoxies. Bases.

Hazardous Decomposition Products

Thermal decomposition can lead to release of irritating gases and vapors.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information	The product has not been tested
Inhalation	There is no data for this product.
Eye Contact	There is no data for this product.
Skin Contact	There is no data for this product.
Ingestion	There is no data for this product.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
p-CHLOROBENZOTRIFLUORIDE 98-56-6	= 13 g/kg (Rat)	> 2 mL/kg (Rabbit)	= 33 mg/L (Rat) 4 h
CARBON BLACK 1333-86-4	> 15400 mg/kg (Rat)	N/A	> 4.6 mg/m ³ (Rat) 4 h
DIBUTYL TIN DILAURATE 77-58-7	= 45 mg/kg (Rat)	= 630 mg/kg (Rabbit)	N/A

Information on toxicological effects

Symptoms No information available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization No information available.
MUTAGENIC EFFECTS No information available.
Carcinogenicity This product contains one or more substances which are classified by IARC as carcinogenic to humans (Group I), probably carcinogenic to humans (Group 2A) or possibly

carcinogenic to humans (Group 2B).

Chemical Name	ACGIH	IARC	NTP	OSHA
p-CHLOROBENZOTRIFLUORIDE 98-56-6	N/A	Group 2B	N/A	X
POLYPROPYLENE 9003-07-0	N/A	Group 3	N/A	N/A
CARBON BLACK 1333-86-4	A3	Group 2B	N/A	X

Legend:

ACGIH (American Conference of Governmental Industrial Hygienists)
 A3 - Animal Carcinogen
 IARC (International Agency for Research on Cancer)
 Group 2B - Possibly Carcinogenic to Humans
 Group 3 - Not Classifiable as to Carcinogenicity in Humans
 OSHA (Occupational Safety and Health Administration of the US Department of Labor)
 X - Present

Reproductive Toxicity	No information available.
Specific target organ systemic toxicity (single exposure)	No information available.
Specific target organ systemic toxicity (repeated exposure)	No information available.
Chronic Toxicity	Prolonged or repeated exposure increases the risk. Avoid repeated exposure. May cause adverse liver effects.
Target Organ Effects	Eyes, Gastrointestinal tract (GI), Liver, Lymphatic System, Respiratory system, Skin.
Aspiration hazard	No information available.

Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral)	11340 mg/kg
ATEmix (dermal)	2606 mg/kg
ATEmix (inhalation-dust/mist)	6610.1 mg/l
Oral LD50	10684 mg/kg (rat) Estimated
Dermal LD50	4117 mg/kg (rat) Estimated
Inhalation LC50	41553 mg/l (mist) (dust) mg/m ³ Estimated
Inhalation LC50	

12. ECOLOGICAL INFORMATION

Ecotoxicity

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to daphnia and other aquatic invertebrates
p-CHLOROBENZOTRIFLUORIDE 98-56-6	N/A	3: 96 h Danio rerio mg/L LC50 semi-static	3.68: 48 h Daphnia magna mg/L EC50

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Chemical Name	Partition coefficient
p-CHLOROBENZOTRIFLUORIDE 98-56-6	3.7
MIXTURE OF AROMATIC HYDROCARBONS 64742-94-5	6.1

Other adverse effects No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Waste treatment methods This material, as supplied, is a hazardous waste according to federal regulations (40 CFR 261).

US EPA Waste Number D001

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste Status
DIBUTYLTIN DILAUATE 77-58-7	Toxic

14. TRANSPORT INFORMATION

DOT

UN-No UN1263
Proper shipping name Paint
Hazard class 3
Packing Group III
Special Provisions B1, B52, IB3, T2, TP1, TP29
Description UN1263, Paint, 3, III
Emergency Response Guide Number 128

TDG

UN-No UN1263
Proper shipping name Paint
Hazard class 3
Packing Group III
Description UN1263, Paint, 3, III

MEX

UN-No UN1263
Proper shipping name Paint
Hazard class 3
Packing Group III
Description UN1263, Paint, 3, III

ICAO

UN-No UN1263
Proper shipping name Paint
Hazard class 3
Packing Group III
Special Provisions A3, A72
Description UN1263, Paint, 3, III

IATA

UN-No UN1263
Hazard class 3
Packing Group III
ERG Code 3L
Special Provisions A3, A72, A192

IMDG/IMO

UN-No UN1263
Hazard class 3
Packing Group III
EmS-No F-E, S-E
Special Provisions 163, 223, 367 955

RID

UN-No UN1263
Proper shipping name Paint
Hazard class 3
Packing Group III
Classification Code F1
Description UN1263, Paint, 3, III

ADR/RID

UN-No UN1263
Proper shipping name Paint
Hazard class 3
Packing Group III
Classification Code F1
Tunnel restriction code (D/E)
Special Provisions 163, 640E, 650, 367
Description UN1263, Paint, 3, III, (D/E)
ADR/RID-Labels 3

ADN

Proper shipping name Paint
Hazard class 3
Packing Group III
Classification Code F1
Special Provisions 163, 640E, 650
Description UN1263, Paint, 3, III
Hazard Labels 3
Limited Quantity (LQ) 5 L
Ventilation VE01

15. REGULATORY INFORMATION

International Inventories

TSCA Complies
DSL/NDSL Complies
EINECS/ELINCS Complies
ENCS Complies
IECSC Complies
KECL Complies
PICCS Complies
AICS Complies

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List
EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances
ENCS - Japan Existing and New Chemical Substances
IECSC - China Inventory of Existing Chemical Substances
KECL - Korean Existing and Evaluated Chemical Substances
PICCS - Philippines Inventory of Chemicals and Chemical Substances
AICS - Australian Inventory of Chemical Substances

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any

chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

SARA 311/312 Hazard Categories

Acute Health Hazard	Yes
Chronic Health Hazard	No
Fire Hazard	Yes
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

CAA (Clean Air Act)

This product does not contain any substances regulated as hazardous air pollutants (HAPS) under Section 112 of the Clean Air Act Amendments of 1990.

Clean Water Act

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material

State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals

Chemical Name	CAS No	California Proposition 65
p-CHLOROBENZOTRIFLUORIDE	98-56-6	Carcinogen
CARBON BLACK	1333-86-4	Carcinogen

U.S. State Right-to-Know Regulations

Chemical Name	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
p-CHLOROBENZOTRIFLUORIDE	N/A	X	N/A	N/A	N/A
CARBON BLACK	X	X	X	X	X

International Regulations

Mexico - Grade Moderate risk, Grade 2

Chemical Name	Carcinogenic Status	Exposure Limits
p-CHLOROBENZOTRIFLUORIDE	N/A	Mexico: TWA 2.5 mg/m ³
CARBON BLACK	A3	Mexico: TWA 3 mg/m ³
DIBUTYL TIN DILAURATE	N/A	Mexico: TWA 0.1 mg/m ³ Mexico: STEL 0.2 mg/m ³

16. OTHER INFORMATION

NFPA Health Hazard 0 Flammability 2 Instability 0 Physical and Chemical Hazards -

NFPA Rating



HMIS **Health Hazard 2 * Flammability 2 Physical Hazard 1 Personal protection X**

Chronic Hazard Star Legend

** Chronic Health Hazard*

Issuing Date: 18-Mar-2021

Revision Date: 25-Mar-2021

Revision Note

No information available

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. 08628KUZ-ULVOC

end