



# SAFETY DATA SHEET

Issuing Date: 05-Mar-2021

Revision Date: 17-Mar-2021

Print Date: 17-Mar-2021

## 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product Code: 16628WEF-LVOC

Product Name: 27875 WHITE EPOXZEN, MIL-PRF-22750G(I),PART A,TY II,CL H,GR A

Hentzen Coatings, Inc.  
6937 West Mill Road, Milwaukee, WI 53218-1225

Company Phone Number: 1-414-353-4200  
Emergency telephone number ChemTrec 1-800-424-9300

Recommended use of the chemical and restrictions on use Industrial paint (Paint or Paint-Related), Restricted to professional users

## 2. HAZARDS IDENTIFICATION

### Classification

### OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin Corrosion/Irritation	Category 2
Serious eye damage/eye irritation	Category 2
Skin sensitization	Category 1
Carcinogenicity	Category 2
Flammable Liquids	Category 2

### Label Elements

### Emergency Overview

**DANGER**

### Hazard Statements

Causes skin irritation  
Causes serious eye irritation  
May cause an allergic skin reaction  
Suspected of causing cancer  
Highly flammable liquid and vapor



Appearance Opaque

Physical state Liquid

Odor Solvent

### Precautionary Statements - Prevention

Obtain special instructions before use  
Do not handle until all safety precautions have been read and understood  
Use personal protective equipment as required  
Wash face, hands and any exposed skin thoroughly after handling  
Avoid breathing dust/fume/gas/mist/vapors/spray  
Contaminated work clothing should not be allowed out of the workplace  
Keep away from heat/sparks/open flames/hot surfaces. - No smoking  
Keep container tightly closed

Ground/Bond container and receiving equipment  
Use explosion-proof electrical/ ventilating/ lighting/ equipment  
Use only non-sparking tools  
Take precautionary measures against static discharge  
Wear protective gloves/protective clothing/eye protection/face protection

**Precautionary Statements - Response**

IF exposed or concerned: Get medical advice/attention  
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
If eye irritation persists: Get medical advice/attention  
If skin irritation or rash occurs: Get medical advice/attention  
IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower  
Wash contaminated clothing before reuse  
In case of fire: Use CO2, dry chemical, or foam for extinction

**Precautionary Statements - Storage**

Store in a well-ventilated place. Keep cool  
Store in accordance with local regulations

**Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

**Hazards not otherwise classified (HNOC)**

**Other information**

- May be harmful if swallowed
- Toxic to aquatic life with long lasting effects
- Harmful to aquatic life

**3. COMPOSITION/INFORMATION ON INGREDIENTS**

**Contains a known or suspected carcinogen**

This product does not contain any substances regulated as hazardous air pollutants (HAPS) under Section 112 of the Clean Air Act Amendments of 1990.

Chemical Name	CAS No	Weight-%	ACGIH	OSHA
TITANIUM DIOXIDE	13463-67-7	20% - 30%	TWA: 10 mg/m <sup>3</sup>	TWA: 15 mg/m <sup>3</sup> total dust
EPOXY RESIN	25068-38-6	10% - 20%	N/A	N/A
METHYL ACETATE	79-20-9	10% - 20%	STEL: 250 ppm TWA: 200 ppm	TWA: 200 ppm TWA: 610 mg/m <sup>3</sup>
p-CHLOROBENZOTRIFLUORIDE	98-56-6	10% - 20%	TWA: 2.5 mg/m <sup>3</sup> F	TWA: 2.5 mg/m <sup>3</sup> F
METHYL AMYL KETONE	110-43-0	5% - 10%	TWA: 50 ppm	TWA: 100 ppm TWA: 465 mg/m <sup>3</sup>
SYNTHETIC AMORPHOUS SILICA (PRECIPITATED)	112926-00-8	1% - 5%	N/A	TWA: 20 mppcf : (80)/(%) SiO <sub>2</sub> mg/m <sup>3</sup> TWA

**4. FIRST AID MEASURES**

**First Aid Measures**

**General advice**

Show this safety data sheet to the doctor in attendance. If symptoms persist, call a physician.

**Eye Contact**

If symptoms persist, call a physician. Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Immediately flush eyes with water for at least 15 minutes. Get medical attention. If easy to do, remove contact lenses. Keep eye wide open while rinsing.

---

<b>Skin Contact</b>	Remove and wash contaminated clothing and gloves, including the inside, before re-use. If skin irritation persists, call a physician. Immediate medical attention is not required. Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes.
<b>Inhalation</b>	Remove to fresh air. If symptoms persist, call a physician. Immediate medical attention is not required. Move to fresh air in case of accidental inhalation of vapors.
<b>Ingestion</b>	Do NOT induce vomiting. Drink plenty of water. Immediate medical attention is not required. Rinse mouth. Clean mouth with water and afterwards drink plenty of water. Never give anything by mouth to an unconscious person. Consult a physician if necessary.
<b>Self-protection of the first aider</b>	Remove all sources of ignition. Use personal protective equipment as required.
<b>Most important symptoms and effects, both acute and delayed</b>	
<b>Most Important Symptoms and Effects</b>	No information available.
<b>Indication of any immediate medical attention and special treatment needed</b>	
<b>Notes to physician</b>	Treat symptomatically. May cause sensitization of susceptible persons.

## 5. FIRE-FIGHTING MEASURES

### Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

**Unsuitable Extinguishing Media** No information available.

### Specific hazards arising from the chemical

Thermal decomposition can lead to release of irritating gases and vapors. In the event of fire and/or explosion do not breathe fumes. May cause sensitization by inhalation and skin contact. Extremely flammable.

### Explosion Data

**Sensitivity to Mechanical Impact** no data available.

**Sensitivity to Static Discharge** Yes.

### Protective equipment and precautions for firefighters

Wear self-contained breathing apparatus and protective suit.

## 6. ACCIDENTAL RELEASE MEASURES

### Personal precautions, protective equipment and emergency procedures

**Personal Precautions** Remove all sources of ignition. Evacuate personnel to safe areas. Ensure adequate ventilation. Use personal protective equipment as required. Keep people away from and upwind of spill/leak. Avoid breathing vapors or mists. Ventilate the area.

### Environmental Precautions

**Environmental Precautions** Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. Do not flush into surface water or sanitary sewer system. Vapors are heavier than air, spread along floors and form explosive mixtures with air.

### Methods and materials for containment and cleaning up

**Methods for Containment** Prevent further leakage or spillage if safe to do so.

**Methods for Cleaning Up** Pick up and transfer to properly labeled containers. Dam up. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Soak up with inert

absorbent material.

## 7. HANDLING AND STORAGE

### Precautions for safe handling

#### **Advice on safe handling**

Ensure adequate ventilation. Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharges. Use explosion-proof electrical (ventilation and lighting) equipment. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Use with local exhaust ventilation. Wear protective gloves/protective clothing/eye protection/face protection. Do not breathe vapor or mist. To dissipate static electricity during transfer, ground drum and connect to receiving container with bonding strap. Use only non-sparking tools.

### Conditions for safe storage, including any incompatibilities

#### **Storage Conditions**

Keep tightly closed in a dry and cool place. Keep in properly labeled containers. Keep away from heat, sparks and flame. Keep containers tightly closed in a cool, well-ventilated place.

#### **Incompatible Products**

None known based on information supplied.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control parameters

#### **Exposure Guidelines**

Chemical Name	ACGIH	OSHA	NIOSH IDLH
TITANIUM DIOXIDE 13463-67-7	TWA: 10 mg/m <sup>3</sup>	TWA: 15 mg/m <sup>3</sup> total dust	IDLH: 5000 mg/m <sup>3</sup> TWA: 2.4 mg/m <sup>3</sup> CIB 63 fine TWA: 0.3 mg/m <sup>3</sup> CIB 63 ultrafine, including engineered nanoscale
CALCIUM CARBONATE 1317-65-3	N/A	TWA: 15 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable fraction	TWA: 10 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable dust
METHYL ACETATE 79-20-9	STEL: 250 ppm TWA: 200 ppm	TWA: 200 ppm TWA: 610 mg/m <sup>3</sup>	IDLH: 3100 ppm TWA: 200 ppm TWA: 610 mg/m <sup>3</sup> STEL: 250 ppm STEL: 760 mg/m <sup>3</sup>
p-CHLOROBENZOTRIFLUORIDE 98-56-6	TWA: 2.5 mg/m <sup>3</sup> F	TWA: 2.5 mg/m <sup>3</sup> F	IDLH: 250 mg/m <sup>3</sup> F
METHYL AMYL KETONE 110-43-0	TWA: 50 ppm	TWA: 100 ppm TWA: 465 mg/m <sup>3</sup>	IDLH: 800 ppm TWA: 100 ppm TWA: 465 mg/m <sup>3</sup>

NIOSH IDLH: *Immediately Dangerous to Life or Health*

### Exposure controls

#### **Engineering Measures**

Showers  
Eyewash stations  
Ventilation systems.

### Individual protection measures, such as personal protective equipment

#### **Eye/Face Protection**

Use personal protective equipment as required.

#### **Skin and Body Protection**

Chemical resistant apron.

#### **Respiratory Protection**

If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

**Hygiene Measures**

Do not eat, drink or smoke when using this product. Regular cleaning of equipment, work area and clothing is recommended.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

<b>Physical state</b>	Liquid	<b>Appearance</b>	Opaque
<b>Odor</b>	Solvent.	<b>Odor Threshold</b>	No data available
<b>pH</b>	No data available	<b>Flash Point</b>	14 °F / -10 °C
<b>Decomposition temperature</b>	No data available	<b>Boiling Point</b>	133 °F / 56 °C
<b>Melting Point / Melting Range</b>	No data available	<b>Freezing Point</b>	No data available
<b>Vapor Pressure @20°C (kPa)</b>	No data available	<b>Partition coefficient:</b>	No data available
<b>Vapor Density</b>	No data available	<b>Density</b>	No data available
<b>Bulk density</b>	No data available	<b>Specific Gravity</b>	1.61
<b>Evaporation Rate</b>	No data available	<b>Water solubility</b>	No data available
<b>Dynamic viscosity</b>	No data available	<b>Weight per Gallon (lbs/gal):</b>	13.44
		<b>EPA VOC (lb/gal)</b>	1.32
<b>Flammability Limits in Air</b>			
<b>Upper</b>	0 %		
<b>Lower</b>	0 %		

**10. STABILITY AND REACTIVITY**

**Reactivity**

No data available

**Chemical stability**

Stable under recommended storage conditions.

**Conditions to Avoid**

Heat, flames and sparks.

**Incompatible Materials**

None known based on information supplied.

**Hazardous Decomposition Products**

Thermal decomposition can lead to release of irritating gases and vapors.

**11. TOXICOLOGICAL INFORMATION**

**Information on likely routes of exposure**

<b>Product Information</b>	The product has not been tested
<b>Inhalation</b>	There is no data for this product.
<b>Eye Contact</b>	There is no data for this product.
<b>Skin Contact</b>	There is no data for this product.
<b>Ingestion</b>	There is no data for this product.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
TITANIUM DIOXIDE 13463-67-7	> 10000 mg/kg ( Rat )	N/A	N/A
METHYL ACETATE 79-20-9	> 5 g/kg ( Rat )	> 5 g/kg ( Rabbit )	> 49000 mg/m <sup>3</sup> ( Rat ) 4 h
p-CHLOROBENZOTRIFLUORIDE 98-56-6	= 13 g/kg ( Rat )	> 2 mL/kg ( Rabbit )	= 33 mg/L ( Rat ) 4 h
METHYL AMYL KETONE 110-43-0	= 1600 mg/kg ( Rat )	= 12.6 mL/kg ( Rabbit )	2000 - 4000 ppm ( Rat ) 6 h

**Information on toxicological effects**

**Symptoms** No information available.

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

**Sensitization** No information available.  
**MUTAGENIC EFFECTS** No information available.  
**Carcinogenicity** This product contains one or more substances which are classified by IARC as carcinogenic to humans (Group I), probably carcinogenic to humans (Group 2A) or possibly carcinogenic to humans (Group 2B).

Chemical Name	ACGIH	IARC	NTP	OSHA
TITANIUM DIOXIDE 13463-67-7	N/A	Group 2B	N/A	X
p-CHLOROBENZOTRIFLUORIDE 98-56-6	N/A	Group 2B	N/A	X
SYNTHETIC AMORPHOUS SILICA (PRECIPITATED) 112926-00-8	N/A	Group 3	N/A	N/A

**Legend:**

*IARC (International Agency for Research on Cancer)*  
*Group 2B - Possibly Carcinogenic to Humans*  
*Group 3 - Not Classifiable as to Carcinogenicity in Humans*  
*OSHA (Occupational Safety and Health Administration of the US Department of Labor)*  
*X - Present*

**Reproductive Toxicity** No information available.  
**Specific target organ systemic toxicity (single exposure)** No information available.  
**Specific target organ systemic toxicity (repeated exposure)** No information available.  
**Chronic Toxicity** Prolonged or repeated exposure increases the risk. Avoid repeated exposure. Repeated contact may cause allergic reactions in very susceptible persons.  
**Target Organ Effects** Central nervous system (CNS), Eyes, Lungs, Peripheral Nervous System (PNS), Respiratory system, Skin.  
**Aspiration hazard** No information available.

**Numerical measures of toxicity - Product Information**

The following values are calculated based on chapter 3.1 of the GHS document .

**ATEmix (oral)** 4301 mg/kg  
**ATEmix (dermal)** 9229 mg/kg  
**ATEmix (inhalation-dust/mist)** 22.7 mg/l  
**Oral LD50** 5417 mg/kg (rat) Estimated  
**Dermal LD50** 11641 mg/kg (rat) Estimated  
**Inhalation LC50** 157080 mg/l (mist) (dust) mg/m<sup>3</sup> Estimated  
**Inhalation LC50** ml/m<sup>3</sup> (vapor) Estimated

**12. ECOLOGICAL INFORMATION**

**Ecotoxicity**

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to daphnia and other aquatic invertebrates
METHYL ACETATE 79-20-9	120: 72 h Desmodesmus subspicatus mg/L EC50	250 - 350: 96 h Brachydanio rerio mg/L LC50 static 295 - 348: 96 h Pimephales promelas mg/L LC50 flow-through	1026.7: 48 h Daphnia magna mg/L EC50
p-CHLOROBENZOTRIFLUORIDE 98-56-6	N/A	3: 96 h Danio rerio mg/L LC50 semi-static	3.68: 48 h Daphnia magna mg/L EC50
METHYL AMYL KETONE 110-43-0	N/A	126 - 137: 96 h Pimephales promelas mg/L LC50 flow-through	N/A

**Persistence and degradability**

No information available.

**Bioaccumulation**

No information available.

Chemical Name	Partition coefficient
METHYL ACETATE 79-20-9	0.18
p-CHLOROBENZOTRIFLUORIDE 98-56-6	3.7
METHYL AMYL KETONE 110-43-0	1.98

**Other adverse effects** No information available

**13. DISPOSAL CONSIDERATIONS**

**Waste treatment methods**

**Waste treatment methods** This material, as supplied, is a hazardous waste according to federal regulations (40 CFR 261).

**US EPA Waste Number** D001

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste Status
METHYL ACETATE 79-20-9	Toxic Ignitable

**14. TRANSPORT INFORMATION**

**DOT**

**UN-No** UN1263  
**Proper shipping name** Paint  
**Hazard class** 3  
**Packing Group** II  
**Special Provisions** 149, B52, IB2, T4, TP1, TP8, TP28  
**Description** UN1263, Paint, Marine Pollutant, 3, II  
**Emergency Response Guide Number** 128

**TDG**

**UN-No** UN1263  
**Proper shipping name** Paint  
**Hazard class** 3  
**Packing Group** II  
**Description** UN1263, Paint, Marine Pollutant, 3, II

**MEX**

**UN-No** UN1263  
**Proper shipping name** Paint  
**Hazard class** 3  
**Packing Group** II  
**Description** UN1263, Paint, 3, II

**ICAO**

**UN-No** UN1263  
**Proper shipping name** Paint

Hazard class 3  
 Packing Group II  
 Special Provisions A3, A72  
 Description UN1263, Paint, 3, II

**IATA**

UN-No UN1263  
 Hazard class 3  
 Packing Group II  
 ERG Code 3L  
 Special Provisions A3, A72, A192

**IMDG/IMO**

UN-No UN1263  
 Hazard class 3  
 Packing Group II  
 EmS-No F-E, S-E  
 Special Provisions 163, 367

**RID**

UN-No UN1263  
 Proper shipping name Paint  
 Hazard class 3  
 Packing Group II  
 Classification Code F1  
 Description UN1263, Paint, Environmentally Hazardous, 3, II

**ADR/RID**

UN-No UN1263  
 Proper shipping name Paint  
 Hazard class 3  
 Packing Group II  
 Classification Code F1  
 Tunnel restriction code (D/E)  
 Special Provisions 163, 640C, 650, 367  
 Description UN1263, Paint, Environmentally Hazardous, 3, II, (D/E)  
 ADR/RID-Labels 3

**ADN**

Proper shipping name Paint  
 Hazard class 3  
 Packing Group II  
 Classification Code F1  
 Special Provisions 163, 640C, 650  
 Description UN1263, Paint, Environmentally Hazardous, 3, II  
 Hazard Labels 3  
 Limited Quantity (LQ) 5 L  
 Ventilation VE01

**15. REGULATORY INFORMATION**

**International Inventories**

TSCA Complies  
 DSL/NDSL Complies  
 EINECS/ELINCS Complies  
 ENCS Complies  
 IECS Complies  
 KECL Complies  
 PICCS Complies  
 AICS Complies



TSCA - United States Toxic Substances Control Act Section 8(b) Inventory  
 DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List  
 EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances  
 ENCS - Japan Existing and New Chemical Substances  
 IECSC - China Inventory of Existing Chemical Substances  
 KECL - Korean Existing and Evaluated Chemical Substances  
 PICCS - Philippines Inventory of Chemicals and Chemical Substances  
 AICS - Australian Inventory of Chemical Substances

**US Federal Regulations**

**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

**SARA 311/312 Hazard Categories**

Acute Health Hazard	Yes
Chronic Health Hazard	No
Fire Hazard	Yes
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

**CAA (Clean Air Act)**

This product does not contain any substances regulated as hazardous air pollutants (HAPS) under Section 112 of the Clean Air Act Amendments of 1990.

**Clean Water Act**

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

**CERCLA**

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material

**State Regulations**

**California Proposition 65**

This product contains the following Proposition 65 chemicals

Chemical Name	CAS No	California Proposition 65
TITANIUM DIOXIDE	13463-67-7	Carcinogen
p-CHLOROBENZOTRIFLUORIDE	98-56-6	Carcinogen

**U.S. State Right-to-Know Regulations**

Chemical Name	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
TITANIUM DIOXIDE	X	X	X	N/A	X
CALCIUM CARBONATE	X	X	X	N/A	X
METHYL ACETATE	X	X	X	N/A	N/A
p-CHLOROBENZOTRIFLUORIDE	N/A	X	N/A	N/A	N/A
METHYL AMYL KETONE	X	X	X	N/A	N/A
SYNTHETIC AMORPHOUS SILICA (PRECIPITATED)	X	X	X	N/A	N/A
BUTYL ACETATE	X	X	X	N/A	N/A

**International Regulations**

**Mexico - Grade** Serious risk, Grade 3

Chemical Name	Carcinogenic Status	Exposure Limits
TITANIUM DIOXIDE	N/A	Mexico: TWA 10 mg/m <sup>3</sup>
METHYL ACETATE	N/A	Mexico: TWA 200 ppm Mexico: TWA 610 mg/m <sup>3</sup> Mexico: STEL 250 ppm
p-CHLOROBENZOTRIFLUORIDE	N/A	Mexico: TWA 2.5 mg/m <sup>3</sup>
METHYL AMYL KETONE	N/A	Mexico: TWA 50 ppm

**16. OTHER INFORMATION**

**NFPA** Health Hazard 2 Flammability 3 Instability 0 Physical and Chemical Hazards -

NFPA Rating



**HMIS** Health Hazard 2 \* Flammability 3 Physical Hazard 1 Personal protection X

*Chronic Hazard Star Legend*

*\* Chronic Health Hazard*

**Issuing Date:** 05-Mar-2021

**Revision Date:** 17-Mar-2021

**Revision Note**

No information available

**Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. 16628WEF-LVOC

end



# SAFETY DATA SHEET

Issuing Date: 10-Jun-2021

Revision Date: 11-Jun-2021

Print Date: 11-Jun-2021

## 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product Code: 16062CEH-LVOC

Product Name: CLEAR EPOXY HARDENER,  
MIL-PRF-22750G(I),PART B,TY II,CL H,GR A

Hentzen Coatings, Inc.  
6937 West Mill Road, Milwaukee, WI 53218-1225

Company Phone Number: 1-414-353-4200

Emergency telephone number ChemTrec 1-800-424-9300

Recommended use of the chemical and restrictions on use Industrial paint (Paint or Paint-Related), Restricted to professional users

## 2. HAZARDS IDENTIFICATION

### Classification

#### OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin Corrosion/Irritation	Category 2
Serious eye damage/eye irritation	Category 1
Skin sensitization	Category 1
Carcinogenicity	Category 2
Flammable Liquids	Category 3

### Label Elements

#### Emergency Overview

**DANGER**

#### Hazard Statements

Causes skin irritation  
Causes serious eye damage  
May cause an allergic skin reaction  
Suspected of causing cancer  
Flammable liquid and vapor



Appearance Clear

Physical state Liquid

Odor Solvent

#### Precautionary Statements - Prevention

Obtain special instructions before use  
Do not handle until all safety precautions have been read and understood  
Use personal protective equipment as required  
Wash face, hands and any exposed skin thoroughly after handling  
Avoid breathing dust/fume/gas/mist/vapors/spray  
Contaminated work clothing should not be allowed out of the workplace  
Wear protective gloves  
Keep away from heat/sparks/open flames/hot surfaces. - No smoking

Keep container tightly closed  
Ground/Bond container and receiving equipment  
Use explosion-proof electrical/ ventilating/ lighting/ equipment  
Use only non-sparking tools  
Take precautionary measures against static discharge

**Precautionary Statements - Response**

IF exposed or concerned: Get medical advice/attention  
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
Immediately call a POISON CENTER or doctor/physician  
If skin irritation or rash occurs: Get medical advice/attention  
IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower  
Wash contaminated clothing before reuse  
In case of fire: Use CO2, dry chemical, or foam for extinction

**Precautionary Statements - Storage**

Store in a well-ventilated place. Keep cool  
Store in accordance with local regulations

**Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

**Hazards not otherwise classified (HNOC)**

**Other information**

- May be harmful if swallowed
- May be harmful in contact with skin
- Toxic to aquatic life with long lasting effects
- Toxic to aquatic life

**3. COMPOSITION/INFORMATION ON INGREDIENTS**

**Contains a known or suspected carcinogen**

This product does not contain any substances regulated as hazardous air pollutants (HAPS) under Section 112 of the Clean Air Act Amendments of 1990.

Chemical Name	CAS No	Weight-%	ACGIH	OSHA
p-CHLOROBENZOTRIFLUORIDE	98-56-6	40% - 50%	TWA: 2.5 mg/m <sup>3</sup> F	TWA: 2.5 mg/m <sup>3</sup> F
BUTYL ALCOHOL	71-36-3	5% - 10%	TWA: 20 ppm	TWA: 100 ppm TWA: 300 mg/m <sup>3</sup>
BENZYL ALCOHOL	100-51-6	5% - 10%	N/A	N/A
TETRAETHYLENAPENTAMINE(TEPA)	112-57-2	0% - 1%	N/A	N/A

**4. FIRST AID MEASURES**

**First Aid Measures**

**General advice**

Show this safety data sheet to the doctor in attendance. If symptoms persist, call a physician.

**Eye Contact**

If symptoms persist, call a physician. Immediately flush eyes with water for at least 15 minutes. Get medical attention. If easy to do, remove contact lenses. Keep eye wide open while rinsing.

**Skin Contact**

Immediate medical attention is not required. Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician.

**Inhalation**

Remove to fresh air. Consult a physician if necessary. If breathing is irregular or stopped,

administer artificial respiration. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Immediate medical attention is not required. Move to fresh air in case of accidental inhalation of vapors. If symptoms persist, call a physician.

**Ingestion** Do NOT induce vomiting. Drink plenty of water. Rinse mouth. If symptoms persist, call a physician. Clean mouth with water and afterwards drink plenty of water. Never give anything by mouth to an unconscious person. Consult a physician if necessary.

**Self-protection of the first aider** Remove all sources of ignition. Use personal protective equipment as required.

**Most important symptoms and effects, both acute and delayed**

**Most Important Symptoms and Effects** No information available.

**Indication of any immediate medical attention and special treatment needed**

**Notes to physician** Treat symptomatically.

## 5. FIRE-FIGHTING MEASURES

### Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

**Unsuitable Extinguishing Media** No information available.

### Specific hazards arising from the chemical

Flammable.

#### Explosion Data

**Sensitivity to Mechanical Impact** no data available.

**Sensitivity to Static Discharge** Yes.

### Protective equipment and precautions for firefighters

Wear self-contained breathing apparatus and protective suit.

## 6. ACCIDENTAL RELEASE MEASURES

### Personal precautions, protective equipment and emergency procedures

**Personal Precautions** Evacuate personnel to safe areas. Ensure adequate ventilation. Remove all sources of ignition. Use personal protective equipment as required. Keep people away from and upwind of spill/leak. Avoid breathing vapors or mists. Ventilate the area.

### Environmental Precautions

**Environmental Precautions** Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. Do not flush into surface water or sanitary sewer system. Vapors are heavier than air, spread along floors and form explosive mixtures with air.

### Methods and materials for containment and cleaning up

**Methods for Containment** Prevent further leakage or spillage if safe to do so.

**Methods for Cleaning Up** Pick up and transfer to properly labeled containers. Dam up. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Soak up with inert absorbent material.

## 7. HANDLING AND STORAGE

### Precautions for safe handling

**Advice on safe handling** Ensure adequate ventilation. Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharges. Use explosion-proof electrical (ventilation and lighting) equipment. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Use with local exhaust ventilation. Wear protective gloves/protective clothing/eye protection/face protection. Do not breathe vapor or mist. To dissipate static electricity during transfer, ground drum and connect to receiving container with bonding strap. Use only non-sparking tools.

**Conditions for safe storage, including any incompatibilities**

**Storage Conditions** Keep tightly closed in a dry and cool place. Keep in properly labeled containers. Keep containers tightly closed in a cool, well-ventilated place. Keep away from heat, sparks and flame.

**Incompatible Products** None known based on information supplied.

**8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

Control parameters

**Exposure Guidelines**

Chemical Name	ACGIH	OSHA	NIOSH IDLH
p-CHLOROBENZOTRIFLUORIDE 98-56-6	TWA: 2.5 mg/m <sup>3</sup> F	TWA: 2.5 mg/m <sup>3</sup> F	IDLH: 250 mg/m <sup>3</sup> F
BUTYL ALCOHOL 71-36-3	TWA: 20 ppm	TWA: 100 ppm TWA: 300 mg/m <sup>3</sup>	IDLH: 1400 ppm Ceiling: 50 ppm Ceiling: 150 mg/m <sup>3</sup>

NIOSH IDLH: *Immediately Dangerous to Life or Health*

Exposure controls

**Engineering Measures** Showers  
Eyewash stations  
Ventilation systems.

Individual protection measures, such as personal protective equipment

**Eye/Face Protection** Use personal protective equipment as required.

**Skin and Body Protection** Chemical resistant apron.

**Respiratory Protection** If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

**Hygiene Measures** Do not eat, drink or smoke when using this product. Regular cleaning of equipment, work area and clothing is recommended.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

<b>Physical state</b>	Liquid	<b>Appearance</b>	Clear
<b>Odor</b>	Solvent.	<b>Odor Threshold</b>	No data available
<b>pH</b>	No data available	<b>Flash Point</b>	95 °F / 35 °C
<b>Decomposition temperature</b>	No data available	<b>Boiling Point</b>	242 °F / 117 °C
<b>Melting Point / Melting Range</b>	No data available	<b>Freezing Point</b>	No data available
<b>Vapor Pressure @20°C (kPa)</b>	No data available	<b>Partition coefficient:</b>	No data available
<b>Vapor Density</b>	No data available	<b>Density</b>	No data available
<b>Bulk density</b>	No data available	<b>Specific Gravity</b>	1.13
<b>Evaporation Rate</b>	No data available	<b>Water solubility</b>	No data available

<b>Dynamic viscosity</b>	No data available	<b>Weight per Gallon (lbs/gal):</b>	9.38
		<b>EPA VOC (lb/gal)</b>	2.42
<b>Flammability Limits in Air</b>			
Upper	0 %		
Lower	0 %		

## 10. STABILITY AND REACTIVITY

### Reactivity

No data available

### Chemical stability

Stable under recommended storage conditions.

### Conditions to Avoid

Heat, flames and sparks.

### Incompatible Materials

None known based on information supplied.

### Hazardous Decomposition Products

Thermal decomposition can lead to release of irritating gases and vapors.

## 11. TOXICOLOGICAL INFORMATION

### Information on likely routes of exposure

<b>Product Information</b>	The product has not been tested
<b>Inhalation</b>	There is no data for this product.
<b>Eye Contact</b>	There is no data for this product.
<b>Skin Contact</b>	There is no data for this product.
<b>Ingestion</b>	There is no data for this product.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
p-CHLOROBENZOTRIFLUORIDE 98-56-6	= 13 g/kg ( Rat )	> 2 mL/kg ( Rabbit )	= 33 mg/L ( Rat ) 4 h
BUTYL ALCOHOL 71-36-3	= 700 mg/kg ( Rat )	= 3402 mg/kg ( Rabbit )	> 8000 ppm ( Rat ) 4 h
BENZYL ALCOHOL 100-51-6	= 1230 mg/kg ( Rat )	= 2 g/kg ( Rabbit )	= 8.8 mg/L ( Rat ) 4 h

### Information on toxicological effects

**Symptoms** No information available.

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Sensitization** No information available.

**MUTAGENIC EFFECTS** No information available.

**Carcinogenicity** This product contains one or more substances which are classified by IARC as carcinogenic to humans (Group I), probably carcinogenic to humans (Group 2A) or possibly carcinogenic to humans (Group 2B).

Chemical Name	ACGIH	IARC	NTP	OSHA
p-CHLOROBENZOTRIFLUORIDE 98-56-6	N/A	Group 2B	N/A	X

### **Legend:**

IARC (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

<b>Reproductive Toxicity</b>	No information available.
<b>Specific target organ systemic toxicity (single exposure)</b>	No information available.
<b>Specific target organ systemic toxicity (repeated exposure)</b>	No information available.
<b>Chronic Toxicity</b>	Prolonged or repeated exposure increases the risk. Avoid repeated exposure.
<b>Target Organ Effects</b>	Central nervous system (CNS), Eyes, Respiratory system, Skin.
<b>Aspiration hazard</b>	No information available.

**Numerical measures of toxicity - Product Information**

The following values are calculated based on chapter 3.1 of the GHS document .

<b>ATEmix (oral)</b>	3313 mg/kg
<b>ATEmix (dermal)</b>	2129 mg/kg
<b>ATEmix (inhalation-dust/mist)</b>	16.1 mg/l
<b>Oral LD50</b>	5977 mg/kg (rat) Estimated
<b>Dermal LD50</b>	3715 mg/kg (rat) Estimated
<b>Inhalation LC50</b>	32540 mg/l (mist) (dust) mg/m <sup>3</sup> Estimated
<b>Inhalation LC50</b>	

**12. ECOLOGICAL INFORMATION**

**Ecotoxicity**

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to daphnia and other aquatic invertebrates
p-CHLOROBENZOTRIFLUORIDE 98-56-6	N/A	3: 96 h Danio rerio mg/L LC50 semi-static	3.68: 48 h Daphnia magna mg/L EC50
BUTYL ALCOHOL 71-36-3	500: 72 h Desmodesmus subspicatus mg/L EC50 500: 96 h Desmodesmus subspicatus mg/L EC50	100000 - 500000: 96 h Lepomis macrochirus µg/L LC50 static 1730 - 1910: 96 h Pimephales promelas mg/L LC50 static 1740: 96 h Pimephales promelas mg/L LC50 flow-through 1910000: 96 h Pimephales promelas µg/L LC50 static	1897 - 2072: 48 h Daphnia magna mg/L EC50 Static 1983: 48 h Daphnia magna mg/L EC50
BENZYL ALCOHOL 100-51-6	N/A	10: 96 h Lepomis macrochirus mg/L LC50 static 460: 96 h Pimephales promelas mg/L LC50 static	23: 48 h water flea mg/L EC50

**Persistence and degradability**

No information available.

**Bioaccumulation**

No information available.

Chemical Name	Partition coefficient
p-CHLOROBENZOTRIFLUORIDE 98-56-6	3.7
BUTYL ALCOHOL 71-36-3	0.785
BENZYL ALCOHOL 100-51-6	1.1
TETRAETHYENEPENTAMINE(TEPA) 112-57-2	1

**Other adverse effects**

No information available

**13. DISPOSAL CONSIDERATIONS**

**Waste treatment methods**



**Waste treatment methods** This material, as supplied, is a hazardous waste according to federal regulations (40 CFR 261).

**US EPA Waste Number** D001

Chemical Name	RCRA - Basis for Listing	RCRA - D Series Wastes
BUTYL ALCOHOL 71-36-3	Included in waste stream: F039	N/A

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste Status
BUTYL ALCOHOL 71-36-3	Toxic

**14. TRANSPORT INFORMATION**

**DOT**

**UN-No** UN1263  
**Proper shipping name** PAINT RELATED MATERIAL  
**Hazard class** 3  
**Packing Group** III  
**Special Provisions** B1, B52, IB3, T2, TP1, TP29  
**Description** UN1263, Paint related material, 3, III  
**Emergency Response Guide Number** 128

**TDG**

**UN-No** UN1263  
**Proper shipping name** PAINT RELATED MATERIAL  
**Hazard class** 3  
**Packing Group** III  
**Description** UN1263, Paint related material, 3, III

**MEX**

**UN-No** UN1263  
**Proper shipping name** PAINT RELATED MATERIAL  
**Hazard class** 3  
**Packing Group** III  
**Description** UN1263, Paint related material, 3, III

**ICAO**

**UN-No** UN1263  
**Proper shipping name** PAINT RELATED MATERIAL  
**Hazard class** 3  
**Packing Group** III  
**Special Provisions** A3, A72  
**Description** UN1263, Paint related material, 3, III

**IATA**

**UN-No** UN1263  
**Proper shipping name** PAINT RELATED MATERIAL  
**Hazard class** 3  
**Packing Group** III  
**ERG Code** 3L  
**Special Provisions** A3, A72, A192  
**Description** UN1263, Paint, 3, III1 Paint related material UN1263, Paint, 3, III2

**IMDG/IMO**

<b>UN-No</b>	UN1263
<b>Proper shipping name</b>	PAINT RELATED MATERIAL
<b>Hazard class</b>	3
<b>Packing Group</b>	III
<b>EmS-No</b>	F-E, S-E
<b>Special Provisions</b>	163, 223, 367 955
<b>Description</b>	UN1263, Paint, 3, III, (35°C c.c.)1 Paint related materialUN1263, Paint, 3, III, (35°C c.c.)2

**RID**

<b>UN-No</b>	UN1263
<b>Proper shipping name</b>	PAINT RELATED MATERIAL
<b>Hazard class</b>	3
<b>Packing Group</b>	III
<b>Classification Code</b>	F1
<b>Description</b>	UN1263, Paint related material, 3, III

**ADR/RID**

<b>UN-No</b>	UN1263
<b>Proper shipping name</b>	PAINT RELATED MATERIAL
<b>Hazard class</b>	3
<b>Packing Group</b>	III
<b>Classification Code</b>	F1
<b>Tunnel restriction code</b>	(D/E)
<b>Special Provisions</b>	163, 640E, 650, 367
<b>Description</b>	UN1263, Paint related material, 3, III, (D/E)
<b>ADR/RID-Labels</b>	3

**ADN**

<b>Proper shipping name</b>	PAINT RELATED MATERIAL
<b>Hazard class</b>	3
<b>Packing Group</b>	III
<b>Classification Code</b>	F1
<b>Special Provisions</b>	163, 640E, 650
<b>Description</b>	UN1263, Paint related material, 3, III
<b>Hazard Labels</b>	3
<b>Limited Quantity (LQ)</b>	5 L
<b>Ventilation</b>	VE01

**15. REGULATORY INFORMATION**

**International Inventories**

<b>TSCA</b>	Complies
<b>DSL/NDSL</b>	Complies
<b>EINECS/ELINCS</b>	Complies
<b>ENCS</b>	Complies
<b>IECSC</b>	Complies
<b>KECL</b>	Complies
<b>PICCS</b>	Complies
<b>AICS</b>	Complies

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory  
**DSL/NDSL** - Canadian Domestic Substances List/Non-Domestic Substances List  
**EINECS/ELINCS** - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances  
**ENCS** - Japan Existing and New Chemical Substances  
**IECSC** - China Inventory of Existing Chemical Substances  
**KECL** - Korean Existing and Evaluated Chemical Substances  
**PICCS** - Philippines Inventory of Chemicals and Chemical Substances  
**AICS** - Australian Inventory of Chemical Substances

**US Federal Regulations**

**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	CAS No	SARA 313 - Threshold Values %
BUTYL ALCOHOL	71-36-3	1.0

**SARA 311/312 Hazard Categories**

Acute Health Hazard	Yes
Chronic Health Hazard	No
Fire Hazard	Yes
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

**CAA (Clean Air Act)**

This product does not contain any substances regulated as hazardous air pollutants (HAPS) under Section 112 of the Clean Air Act Amendments of 1990.

**Clean Water Act**

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

**CERCLA**

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ (reportable quantity)
BUTYL ALCOHOL	5000 lb	N/A	RQ 5000 lb final RQ RQ 2270 kg final RQ

**State Regulations**

**California Proposition 65**

This product contains the following Proposition 65 chemicals

Chemical Name	CAS No	California Proposition 65
p-CHLOROBENZOTRIFLUORIDE	98-56-6	Carcinogen

**U.S. State Right-to-Know Regulations**

Chemical Name	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
p-CHLOROBENZOTRIFLUORIDE	N/A	X	N/A	N/A	N/A
BUTYL ALCOHOL	X	X	X	N/A	N/A
TETRAETHYENEPENTAMINE (TEPA)	X	X	X	N/A	N/A

**International Regulations**

**Mexico - Grade**

Serious risk, Grade 3

Chemical Name	Carcinogenic Status	Exposure Limits
p-CHLOROBENZOTRIFLUORIDE	N/A	Mexico: TWA 2.5 mg/m <sup>3</sup>
BUTYL ALCOHOL	N/A	Mexico: TWA 20 ppm

**16. OTHER INFORMATION**

**NFPA**

Health Hazard 2

Flammability 3

Instability 0

Physical and Chemical Hazards -

**NFPA Rating**



**HMIS**

Health Hazard 1 \*

Flammability 3

Physical Hazard 0

Personal protection X

*Chronic Hazard Star Legend*

*\* Chronic Health Hazard*

**Issuing Date:**

10-Jun-2021

**Revision Date:**

11-Jun-2021

**Revision Note**

No information available

**Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. 16062CEH-LVOC

end