

Revision Number: 005.3 Issue date: 02/14/2019

## 1. PRODUCT AND COMPANY IDENTIFICATION

Product name: **BONDERITE M-CR 600RTU** 

**CHROMATE COATING AERO** 

Product type/use: Conversion coating

Restriction of Use: None identified Company address: Henkel Corporation

One Henkel Way

Rocky Hill, Connecticut 06067

IDH number: 2300922

Region: United States

**Contact information:** 

Telephone: +1 (860) 571-5100

MEDICAL EMERGENCY Phone: Poison Control Center 1-877-671-4608 (toll free) or 1-303-592-1711 TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887

Internet: www.henkelna.com

## 2. HAZARDS IDENTIFICATION

**EMERGENCY OVERVIEW** 

DANGER: CAUSES SKIN IRRITATION.

MAY CAUSE AN ALLERGIC SKIN REACTION.

CAUSES SERIOUS EYE IRRITATION.

HARMFUL IF INHALED.

MAY CAUSE ALLERGY OR ASTHMA SYMPTOMS OR BREATHING

DIFFICULTIES IF INHALED. MAY CAUSE GENETIC DEFECTS.

MAY CAUSE CANCER.

MAY DAMAGE FERTILITY OR THE UNBORN CHILD.

HAZARD CLASS	HAZARD CATEGORY
ACUTE TOXICITY INHALATION	4
SKIN IRRITATION	2
EYE IRRITATION	2A
RESPIRATORY SENSITIZATION	1
SKIN SENSITIZATION	1
GERM CELL MUTAGENICITY	1B
CARCINOGENICITY	1A
REPRODUCTIVE TOXICITY	1B

PICTOGRAM(S)



#### **Precautionary Statements**

IDH number: 2300922

Prevention:

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid breathing vapors, mist, or spray. Wash affected area thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves, clothing, eye and face protection. In case of inadequate ventilation wear respiratory protection.

Product name: BONDERITE M-CR 600RTU CHROMATE COATING AERO Page 1 of 7

Response: IF ON SKIN: Wash with plenty of water. IF INHALED: Remove victim to fresh air and keep at

rest in a position comfortable for breathing. Call a POISON CENTER or physician if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical attention. If skin irritation or rash occurs: Get medical attention. If eye irritation persists: Get medical

attention. Take off contaminated clothing.

Storage: Store locked up.

Disposal: Dispose of contents and/or container according to Federal, State/Provincial and local

governmental regulations.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

## 3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*
Sodium borofluoride	13755-29-8	0.1 - 1
Chromic acid	7738-94-5	0.1 - 1
Sodium chromate	7775-11-3	0.1 - 1
Dipotassium hexafluorozirconate	16923-95-8	0.1 - 1
Sodium nitrate	7631-99-4	0.1 - 1

<sup>\*</sup> Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections

## 4. FIRST AID MEASURES

Inhalation: If mist or vapor of this product is inhaled, remove person immediately to fresh

air. Seek medical attention if symptoms develop or persist.

Skin contact: Remove contaminated clothing and footwear. For skin contact, flush with large

amounts of water. Seek immediate medical attention. If irritation persists, repeat flushing and get medical attention. Discard any shoes or clothing items

that cannot be decontaminated.

**Eye contact:** In case of contact with the eyes, rinse immediately with plenty of water for 15

minutes, and seek immediate medical attention.

**Ingestion:** Get immediate medical attention. Do not induce vomiting. Give one to two

glasses of water or milk. Never give anything by mouth to a victim who is

unconscious or is having convulsions.

Symptoms: See Section 11.

IDH number: 2300922

### 5. FIRE FIGHTING MEASURES

Extinguishing media: Use media appropriate for surrounding material.

Special firefighting procedures: Wear full protective clothing. Wear self-contained breathing apparatus.

Unusual fire or explosion hazards: This product is an aqueous mixture which will not burn. If evaporated to

dryness, solid residue is an oxidizing agent and may cause spontaneous

ignition of combustible materials.

**Hazardous combustion products:** Oxides of nitrogen.

IDH number: 2300922

## 6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

**Environmental precautions:** Prevent further leakage or spillage if safe to do so. Wear appropriate

protective equipment and clothing during clean-up. Do not allow product to

enter sewer or waterways.

Clean-up methods: Absorb spill with inert material. Shovel material into appropriate container for

disposal. Dispose of according to Federal, State and local governmental

egulations.

## 7. HANDLING AND STORAGE

Handling: Avoid contact with eyes, skin and clothing. Avoid breathing mists or aerosols

of this product. Wash thoroughly after handling. Provide adequate ventilation.

For industrial use only. Do not take internally.

Storage: For safe storage, store between 5 °C (41°F) and 40 °C (104°F)

Keep container tightly closed and in a cool, well-ventilated place away from

incompatible materials. Protect from freezing.

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Sodium borofluoride	None	None	None	None
Chromic acid	0.0005 mg/m3 STEL (as Cr(VI)) Inhalable fraction. 0.0002 mg/m3 TWA (as Cr(VI)) Inhalable fraction. (SKIN) (as Cr(VI)) Inhalable fraction. 0.0005 mg/m3 STEL (as Cr(VI)) Inhalable fraction. (Dermal sensitization) (Respiratory sensitization)	0.005 mg/m3 TWA 0.0025 mg/m3 OSHA_ACT 0.1 mg/m3 Ceiling	None	None
Sodium chromate	0.0005 mg/m3 STEL (as Cr(VI)) Inhalable fraction. (SKIN) (as Cr(VI)) Inhalable fraction. 0.0005 mg/m3 STEL (as Cr(VI)) Inhalable fraction. 0.0002 mg/m3 TWA (as Cr(VI)) Inhalable fraction. (Dermal sensitization) (Respiratory sensitization)	0.005 mg/m3 TWA 0.0025 mg/m3 OSHA_ACT 0.1 mg/m3 Ceiling	None	None
Dipotassium hexafluorozirconate	5 mg/m3 TWA (as Zr) 10 mg/m3 STEL (as Zr)	5 mg/m3 PEL (as Zr)	None	None
Sodium nitrate	None	None	None	None

Engineering controls: Provide local and general exhaust ventilation to effectively remove and

prevent buildup of any vapors or mists generated from the handling of this

product.

Respiratory protection: If ventilation is not sufficient to effectively prevent buildup of aerosols, mists or

vapors, appropriate NIOSH/MSHA respiratory protection must be provided.

Eye/face protection: Wear chemical goggles; face shield (if splashing is possible).

**Skin protection:** Wear impervious gloves for prolonged contact. Gloves should be tested to

determine suitability for prolonged contact. Use of impervious apron and boots

are recommended.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

 Physical state:
 Liquid

 Color:
 Orange

 Odor:
 Bland

 Odor threshold:
 Not available.

 pH:
 < 2</td>

 Vapor pressure:
 Not determined

 Boiling point/range:
 > 100 °C (> 212

Boiling point/range: > 100 °C (> 212°F)

Melting point/ range: Not determined

Specific gravity: 1.01 - 1.03

IDH number: 2300922

Product name: BONDERITE M-CR 600RTU CHROMATE COATING AERO
Page 4 of 7

Vapor density: Not determined Flash point: > 93 °C (> 199.4 °F) Flammable/Explosive limits - lower: Not applicable Flammable/Explosive limits - upper: Not applicable Autoignition temperature: Not applicable Flammability: Not applicable **Evaporation rate:** Not determined Solubility in water: Complete Partition coefficient (n-octanol/water): Not determined **VOC** content: 0 % (calculated) Viscosity: Not available. **Decomposition temperature:** Not available.

## 10. STABILITY AND REACTIVITY

**Stability:** Stable at normal conditions.

**Hazardous reactions:** None under normal processing.

**Hazardous decomposition** 

products:

Decomposes with heat to produce oxides of nitrogen.

**Incompatible materials:** Avoid contact with organic materials, oils, greases, and any oxidizable materials.

Reactivity: Not available.

Conditions to avoid: None identified.

# 11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure: Skin, Inhalation, Eyes, Ingestion

#### Potential Health Effects/Symptoms

Inhalation: Mists, vapors or liquid may cause severe irritation or burns. Prolonged or repeated breathing

may cause ulceration of nasal membranes. Harmful if inhaled. May cause allergic respiratory reaction. These symptoms, which can include chest tightness, wheezing, cough, shortness of breath or asthma attack, could be immediate or delayed (up to several hours after exposure).

Skin contact: Contact with broken skin may lead to formation of firmly marginated "chrome sores". Product

contains chromium, which may cause an allergic skin sensitization reaction. Massive

overexposures may lead to kidney failure and death. Causes skin burns.

**Eye contact:** This product is severely irritating to the eyes and may cause irreversible damage including

burns and blindness. Causes serious eve damage.

**Ingestion:** This product may produce corrosive damage to the gastrointestinal tract if it is swallowed.

Acute inhalation product

toxicity:

IDH number: 2300922

Acute toxicity estimate (ATE) 4 h 4.4 mg/l

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects	
Sodium borofluoride	None	Cardiac, Central nervous system, Developmental, Gastrointestinal, Irritant, Kidney, Metabolic, Reproductive	
Chromic acid	None	Allergen, Blood, Carcinogen, Central nervous system, Corrosive, Developmental, Eyes, Gastrointestinal, Irritant, Kidney, Liver, Mutagen, Reproductive, Respiratory	
Sodium chromate	Oral LD50 (Rat) = 13 - 28 mg/kg Oral LD50 (Rat) = 51.91 mg/kg Oral LD50 (Rat) = 51.91 mg/kg Oral LD50 (Rat) = 13 mg/kg Oral LD50 (Rat) = 28 mg/kg Oral LD50 (Rat) = 28 mg/kg Dermal LD50 (Rabbit) = 426 mg/kg Dermal LD50 (Rabbit) = 553 mg/kg Dermal LD50 (Rabbit) = 1,600 mg/kg	Irritant, Respiratory, Central nervous system, Allergen, Liver, Kidney, Developmental, Reproductive, Corrosive, Carcinogen, Mutagen, Blood	
Dipotassium hexafluorozirconate	Oral LD50 (Mouse) = 98 mg/kg	Allergen, Blood, Cardiac, Central nervous system, Corrosive, Gastrointestinal tract, Irritant, Kidney, Lung, Metabolic, Muscle, Teeth, Less weight gain and food intake.	
Sodium nitrate	Oral LD50 (Rat) = 1,267 mg/kg Oral LD50 (Mouse) = 2,480 mg/kg Oral LD50 (Rabbit) = 1,600 mg/kg Oral LD50 (Rabbit) = 1,955 mg/kg Oral LD50 (Rabbit) = 2,680 mg/kg	Blood, Central nervous system, Corrosive, Gastrointestinal, Irritant	

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Sodium borofluoride	No	No	No
Chromic acid	Known To Be Human Carcinogen.	Group 1	Yes
Sodium chromate	Known To Be Human Carcinogen.	Group 1	Yes
Dipotassium hexafluorozirconate	No	No	No
Sodium nitrate	No	Group 2A	No

# 12. ECOLOGICAL INFORMATION

**Ecological information:** Not available.

## 13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

**Recommended method of disposal:** Follow all local, state, federal and provincial regulations for disposal.

**Hazardous waste number:** This product contains chromium which is a hazardous waste (D007).

# 14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

U.S. Department of Transportation Ground (49 CFR)

IDH number: 2300922

**Proper shipping name:** RQ, Environmentally hazardous substance, liquid, n.o.s.

Hazard class or division: 9
Identification number: UN 3082
Packing group: III

DOT Hazardous Substance(s): Sodium bichromate, Chromic acid

Product name: BONDERITE M-CR 600RTU CHROMATE COATING AERO Page 6 of 7

International Air Transportation (ICAO/IATA)

Proper shipping name: RQ, Environmentally hazardous substance, liquid, n.o.s.

Hazard class or division:

Identification number: UN 3082 Packing group: Ш

Water Transportation (IMO/IMDG)

Proper shipping name: RQ, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

Hazard class or division: Identification number: UN 3082 Ш

Packing group:

### 15. REGULATORY INFORMATION

**United States Regulatory Information** 

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act

Inventory.

TSCA 12 (b) Export Notification: Sodium chromate (CAS# 7775-11-3). Chromic acid (CAS# 7738-94-5).

CERCLA/SARA Section 302 EHS: None above reporting de minimis. CERCLA/SARA Section 311/312: Immediate Health, Delayed Health

CERCLA/SARA Section 313: This product contains the following toxic chemicals subject to the reporting requirements of

section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40

CFR 372). Sodium chromate (CAS# 7775-11-3). Chromic acid (CAS# 7738-94-5).

Chromic acid (CAS# 7738-94-5) 10 lbs. (4.54 kg) **CERCLA Reportable quantity:** Sodium chromate (CAS# 7775-11-3) 10 lbs. (4.54 kg)

California Proposition 65: This product contains a chemical known in the State of California to cause cancer. This

product contains a chemical known to the State of California to cause birth defects or other

reproductive harm.

**Canada Regulatory Information** 

IDH number: 2300922

**CEPA DSL/NDSL Status:** All components are listed on or are exempt from listing on the Canadian Domestic

Substances List.

### 16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: New Safety Data Sheet format.

Prepared by: Product Safety and Regulatory Affairs

Issue date: 02/14/2019

**DISCLAIMER:** The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

This Safety Data Sheet has been generated based on OSHA Hazard Communication Standard (29 CFR 1910.1200) and provides information in accordance with U.S. federal law only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.