

**PRIAM 32005 NOIR MAT PARTIE A**

Version	Revision Date:	SDS Number:	Date of last issue: 10/16/2020
1.5	03/31/2021	102000070000	Date of first issue: 12/18/2017

---

**SECTION 1. IDENTIFICATION****1.1 Product identifier**

Trade name : PRIAM 32005 NOIR MAT PARTIE A  
Identification of the article : 040231005R

**1.2 Relevant identified uses of the substance or mixture and uses advised against**

Use of the Sub-  
stance/Mixture : Industrial paint

**1.3 Details of the supplier of the safety data sheet****Supplier**

Company : Dysol Inc. Socomore  
5475 E State Hwy 114  
US - 76078 Rhome  
Telephone : +118173351826  
Telefax :  
E-mail address of person  
responsible for the SDS : techsupport-na@socomore.com  
Website : www.socomore.com/store.socomore.com

**Manufacturer**

Company : MÄDER AERO  
Rue Jean Baptiste Réveillon 2  
FR – 61300 L'AIGLE  
Telephone : +33320127950  
E-mail address of person  
responsible for the SDS : products-safety.mader-france@mader-group.com

**1.4 Emergency telephone number**

Emergency telephone  
number : CHEMTEL: +1-813-248-0585 (International); 1-800-255-3924  
(USA)

---

**SECTION 2. HAZARDS IDENTIFICATION****GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)**

Flammable liquids : Category 2  
Skin irritation : Category 2  
Eye irritation : Category 2A  
Reproductive toxicity : Category 2  
Specific target organ toxicity  
- single exposure : Category 3 (Central nervous system)

## PRIAM 32005 NOIR MAT PARTIE A

Version	Revision Date:	SDS Number:	Date of last issue: 10/16/2020
1.5	03/31/2021	102000070000	Date of first issue: 12/18/2017

---

Specific target organ toxicity : Category 2  
 - repeated exposure

### GHS label elements

Hazard pictograms :



Signal word : Danger

Hazard statements : H225 Highly flammable liquid and vapour.  
 H315 Causes skin irritation.  
 H319 Causes serious eye irritation.  
 H336 May cause drowsiness or dizziness.  
 H361d Suspected of damaging the unborn child.  
 H373 May cause damage to organs through prolonged or repeated exposure.

Precautionary statements :

#### Prevention:

P201 Obtain special instructions before use.  
 P202 Do not handle until all safety precautions have been read and understood.  
 P210 Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.  
 P233 Keep container tightly closed.  
 P240 Ground/bond container and receiving equipment.  
 P241 Use explosion-proof electrical/ ventilating/ lighting equipment.  
 P242 Use only non-sparking tools.  
 P243 Take precautionary measures against static discharge.  
 P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.  
 P264 Wash skin thoroughly after handling.  
 P271 Use only outdoors or in a well-ventilated area.  
 P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

#### Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.  
 P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.  
 P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 P308 + P313 IF exposed or concerned: Get medical advice/ attention.  
 P332 + P313 If skin irritation occurs: Get medical advice/ attention.  
 P337 + P313 If eye irritation persists: Get medical advice/ attention.

## PRIAM 32005 NOIR MAT PARTIE A

Version	Revision Date:	SDS Number:	Date of last issue: 10/16/2020
1.5	03/31/2021	102000070000	Date of first issue: 12/18/2017

P362 Take off contaminated clothing and wash before reuse.  
 P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

### Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.  
 P403 + P235 Store in a well-ventilated place. Keep cool.  
 P405 Store locked up.

### Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

### Other hazards

None known.

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature : Industrial paint

### Components

Chemical name	CAS-No.	Concentration (% w/w)
Toluene	108-88-3	>= 10 - < 20
Methyl isobutyl ketone	108-10-1	>= 10 - < 20
Butyl acetate	123-86-4	>= 10 - < 20
silica gel (Amorphous and Dust)	112926-00-8	>= 5 - < 10
2-Propanol, 1-methoxy-, acetate	108-65-6	>= 1 - < 5
Xylene	1330-20-7	>= 1 - < 5
Carbon black	1333-86-4	>= 1 - < 5
Ethylbenzene	100-41-4	>= 0.1 - < 1

Actual concentration is withheld as a trade secret

## SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.  
 Show this safety data sheet to the doctor in attendance.  
 Do not leave the victim unattended.

If inhaled : If unconscious, place in recovery position and seek medical advice.  
 If symptoms persist, call a physician.

In case of skin contact : If skin irritation persists, call a physician.  
 If on skin, rinse well with water.  
 If on clothes, remove clothes.

In case of eye contact : Immediately flush eye(s) with plenty of water.  
 Remove contact lenses.  
 Protect unharmed eye.  
 Keep eye wide open while rinsing.

## PRIAM 32005 NOIR MAT PARTIE A

Version	Revision Date:	SDS Number:	Date of last issue: 10/16/2020
1.5	03/31/2021	102000070000	Date of first issue: 12/18/2017

---

- If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.  
Take victim immediately to hospital.
- Most important symptoms and effects, both acute and delayed : Causes skin irritation.  
Causes serious eye irritation.  
May cause drowsiness or dizziness.  
Suspected of damaging the unborn child.  
May cause damage to organs through prolonged or repeated exposure.
- Notes to physician : No information available.

## SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during fire-fighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : No hazardous combustion products are known
- Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.  
For safety reasons in case of fire, cans should be stored separately in closed containments.  
Use a water spray to cool fully closed containers.
- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

## SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.  
Ensure adequate ventilation.  
Remove all sources of ignition.  
Evacuate personnel to safe areas.  
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.  
No conditions to be specially mentioned.

## PRIAM 32005 NOIR MAT PARTIE A

Version 1.5	Revision Date: 03/31/2021	SDS Number: 102000070000	Date of last issue: 10/16/2020 Date of first issue: 12/18/2017
----------------	------------------------------	-----------------------------	---

- Environmental precautions : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

### SECTION 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material.  
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours).  
Use only explosion-proof equipment.  
Keep away from open flames, hot surfaces and sources of ignition.
- Advice on safe handling : Avoid formation of aerosol.  
Do not breathe vapours/dust.  
Avoid exposure - obtain special instructions before use.  
Avoid contact with skin and eyes.  
For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
Take precautionary measures against static discharges.  
Provide sufficient air exchange and/or exhaust in work rooms.  
Open drum carefully as content may be under pressure.  
Dispose of rinse water in accordance with local and national regulations.
- Conditions for safe storage : No smoking.  
Keep container tightly closed in a dry and well-ventilated place.  
Containers which are opened must be carefully resealed and kept upright to prevent leakage.  
Observe label precautions.  
Electrical installations / working materials must comply with the technological safety standards.
- Further information on storage stability : No decomposition if stored and applied as directed.

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis

**SAFETY DATA SHEET**



**PRIAM 32005 NOIR MAT PARTIE A**

Version 1.5      Revision Date: 03/31/2021      SDS Number: 102000070000      Date of last issue: 10/16/2020  
 Date of first issue: 12/18/2017

Toluene	108-88-3	TWA	200 ppm	OSHA Z-2
		CEIL	300 ppm	OSHA Z-2
		Peak	500 ppm (10 minutes)	OSHA Z-2
		TWA	20 ppm	ACGIH
		TWA	100 ppm 375 mg/m3	OSHA P0
		STEL	150 ppm 560 mg/m3	OSHA P0
		TWA	100 ppm 375 mg/m3	NIOSH REL
		ST	150 ppm 560 mg/m3	NIOSH REL
Methyl isobutyl ketone	108-10-1	TWA	100 ppm 410 mg/m3	OSHA Z-1
		TWA	20 ppm	ACGIH
		STEL	75 ppm	ACGIH
		TWA	50 ppm 205 mg/m3	OSHA P0
		STEL	75 ppm 300 mg/m3	OSHA P0
		TWA	50 ppm 205 mg/m3	NIOSH REL
		ST	75 ppm 300 mg/m3	NIOSH REL
Butyl acetate	123-86-4	TWA	50 ppm	ACGIH
		STEL	150 ppm	ACGIH
		TWA	150 ppm 710 mg/m3	OSHA Z-1
		TWA	150 ppm 710 mg/m3	OSHA P0
		STEL	200 ppm 950 mg/m3	OSHA P0
		TWA	150 ppm 710 mg/m3	NIOSH REL
		ST	200 ppm 950 mg/m3	NIOSH REL
silica gel (Amorphous and Dust)	112926-00-8	TWA (Dust)	20 Million particles per cubic foot (Silica)	OSHA Z-3
		TWA (Dust)	80 mg/m3 / %SiO2 (Silica)	OSHA Z-3
		TWA	6 mg/m3	OSHA P0
		TWA	6 mg/m3 (Silica)	NIOSH REL
2-Propanol, 1-methoxy-, acetate	108-65-6	TWA	50 ppm	US WEEL
Xylene	1330-20-7	TWA	100 ppm 435 mg/m3	OSHA Z-1
		TWA	100 ppm	ACGIH
		STEL	150 ppm	ACGIH

## PRIAM 32005 NOIR MAT PARTIE A

Version 1.5      Revision Date: 03/31/2021      SDS Number: 102000070000      Date of last issue: 10/16/2020  
 Date of first issue: 12/18/2017

		TWA	100 ppm 435 mg/m <sup>3</sup>	OSHA P0
		STEL	150 ppm 655 mg/m <sup>3</sup>	OSHA P0
Carbon black	1333-86-4	TWA	3.5 mg/m <sup>3</sup>	OSHA Z-1
		TWA (Inhalable particulate matter)	3 mg/m <sup>3</sup>	ACGIH
		TWA	3.5 mg/m <sup>3</sup>	OSHA P0
		TWA	3.5 mg/m <sup>3</sup>	NIOSH REL
		TWA	0.1 mg/m <sup>3</sup> (PAHs)	NIOSH REL
Ethylbenzene	100-41-4	TWA	20 ppm	ACGIH
		TWA	100 ppm 435 mg/m <sup>3</sup>	NIOSH REL
		ST	125 ppm 545 mg/m <sup>3</sup>	NIOSH REL
		TWA	100 ppm 435 mg/m <sup>3</sup>	OSHA Z-1
		TWA	100 ppm 435 mg/m <sup>3</sup>	OSHA P0
		STEL	125 ppm 545 mg/m <sup>3</sup>	OSHA P0

## Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
Toluene	108-88-3	Toluene	In blood	Prior to last shift of work-week	0.02 mg/l	ACGIH BEI
		Toluene	Urine	End of shift (As soon as possible after exposure ceases)	0.03 mg/l	ACGIH BEI
		o-Cresol	Urine	End of shift (As soon as possible after exposure ceases)	0.3 mg/g Creatinine	ACGIH BEI
Methyl isobutyl ketone	108-10-1	methyl isobutyl ketone	Urine	End of shift (As soon as possible after exposure ceases)	1 mg/l	ACGIH BEI

**PRIAM 32005 NOIR MAT PARTIE A**

Version 1.5      Revision Date: 03/31/2021      SDS Number: 102000070000      Date of last issue: 10/16/2020  
 Date of first issue: 12/18/2017

Xylene	1330-20-7	Methylhippuric acids	Urine	End of shift (As soon as possible after exposure ceases)	1.5 g/g creatinine	ACGIH BEI
--------	-----------	----------------------	-------	--	--------------------	-----------

**Personal protective equipment**

- Respiratory protection : In the case of vapour formation use a respirator with an approved filter.
- Hand protection
- Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.
- Eye protection : Eye wash bottle with pure water  
 Tightly fitting safety goggles  
 Wear face-shield and protective suit for abnormal processing problems.
- Skin and body protection : Impervious clothing  
 Choose body protection according to the amount and concentration of the dangerous substance at the work place.
- Hygiene measures : When using do not eat or drink.  
 When using do not smoke.  
 Wash hands before breaks and at the end of workday.

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

- Appearance : liquid
- Colour : black
- Odour : solvent-like
- pH : Not applicable
- Melting point/range : Not applicable
- Boiling point/boiling range : > 97 °F / > 36 °C
- Flash point : ca. 39 °F / 4 °C
- Evaporation rate : No data available



## PRIAM 32005 NOIR MAT PARTIE A

Version	Revision Date:	SDS Number:	Date of last issue: 10/16/2020
1.5	03/31/2021	102000070000	Date of first issue: 12/18/2017

---

Self-ignition	:	No data available
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapour pressure	:	< 1,000 hPa (122 °F / 50 °C)
Relative vapour density	:	No data available
Density	:	ca. 1.06 g/cm <sup>3</sup> (73 °F / 23 °C)
Solubility(ies)	:	
Water solubility	:	immiscible
Partition coefficient: n-octanol/water	:	No data available
Auto-ignition temperature	:	No data available
Decomposition temperature	:	Not applicable
Viscosity	:	
Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	> 20.6 mm <sup>2</sup> /s (104 °F / 40 °C)
Explosive properties	:	No data available
Oxidizing properties	:	No data available

---

### SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	No decomposition if stored and applied as directed.
Chemical stability	:	No decomposition if stored and applied as directed.
Possibility of hazardous reactions	:	No dangerous reaction known under conditions of normal use. No decomposition if stored and applied as directed. Vapours may form explosive mixture with air.
Conditions to avoid	:	Heat, flames and sparks.
Incompatible materials	:	Strong oxidizing agents  Strong oxidizing agents
Hazardous decomposition products	:	Stable under recommended storage conditions.

## PRIAM 32005 NOIR MAT PARTIE A

Version	Revision Date:	SDS Number:	Date of last issue: 10/16/2020
1.5	03/31/2021	102000070000	Date of first issue: 12/18/2017

---

### SECTION 11. TOXICOLOGICAL INFORMATION

#### Acute toxicity

Not classified based on available information.

#### Product:

Acute inhalation toxicity : Acute toxicity estimate: 77.91 mg/l  
 Exposure time: 4 h  
 Test atmosphere: vapour  
 Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 5,000 mg/kg  
 Method: Calculation method

#### Components:

##### 2-Propanol, 1-methoxy-, acetate:

Acute inhalation toxicity : LC<sub>Lo</sub> (Rat): > 11 mg/l  
 Exposure time: 3 h

#### Skin corrosion/irritation

Causes skin irritation.

#### Product:

Remarks : May cause skin irritation in susceptible persons.

#### Serious eye damage/eye irritation

Causes serious eye irritation.

#### Product:

Remarks : May cause irreversible eye damage.

#### Respiratory or skin sensitisation

##### Skin sensitisation

Not classified based on available information.

##### Respiratory sensitisation

Not classified based on available information.

##### Germ cell mutagenicity

Not classified based on available information.

#### Carcinogenicity

Not classified based on available information.

<b>IARC</b>	Group 2B: Possibly carcinogenic to humans	
	Methyl isobutyl ketone	108-10-1
	Group 2B: Possibly carcinogenic to humans	
	Carbon black	1333-86-4
	Group 2B: Possibly carcinogenic to humans	
	Ethylbenzene	100-41-4

**PRIAM 32005 NOIR MAT PARTIE A**

Version	Revision Date:	SDS Number:	Date of last issue: 10/16/2020
1.5	03/31/2021	102000070000	Date of first issue: 12/18/2017

---

**OSHA** No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

**NTP** No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

**Reproductive toxicity**

Suspected of damaging the unborn child.

**STOT - single exposure**

May cause drowsiness or dizziness.

**STOT - repeated exposure**

May cause damage to organs through prolonged or repeated exposure.

**Aspiration toxicity**

Not classified based on available information.

**Further information****Product:**

Remarks : Solvents may degrease the skin.

---

**SECTION 12. ECOLOGICAL INFORMATION****Ecotoxicity**

No data available

**Persistence and degradability**

No data available

**Bioaccumulative potential**

No data available

**Mobility in soil**

No data available

**Other adverse effects****Product:**

Ozone-Depletion Potential : Regulation: 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances  
Remarks: This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological information : No data available

**PRIAM 32005 NOIR MAT PARTIE A**

Version	Revision Date:	SDS Number:	Date of last issue: 10/16/2020
1.5	03/31/2021	102000070000	Date of first issue: 12/18/2017

---

**SECTION 13. DISPOSAL CONSIDERATIONS****Disposal methods**

- Waste from residues : Do not dispose of waste into sewer.  
Do not contaminate ponds, waterways or ditches with chemical or used container.  
Send to a licensed waste management company.
- Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.  
Do not burn, or use a cutting torch on, the empty drum.
- 

**SECTION 14. TRANSPORT INFORMATION****International Regulations****UNRTDG**

- UN number : UN 1263  
Proper shipping name : PAINT  
Class : 3  
Packing group : II  
Labels : 3

**IATA-DGR**

- UN/ID No. : UN 1263  
Proper shipping name : PAINT  
Class : 3  
Packing group : II  
Labels : Flammable Liquids  
Packing instruction (cargo aircraft) : 364  
Packing instruction (passenger aircraft) : 353

**IMDG-Code**

- UN number : UN 1263  
Proper shipping name : PAINT
- Class : 3  
Packing group : II  
Labels : 3  
EmS Code : F-E, S-E  
Marine pollutant : no

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

Not applicable for product as supplied.

**National Regulations****49 CFR**

- UN/ID/NA number : UN 1263  
Proper shipping name : PAINT

## PRIAM 32005 NOIR MAT PARTIE A

Version	Revision Date:	SDS Number:	Date of last issue: 10/16/2020
1.5	03/31/2021	102000070000	Date of first issue: 12/18/2017

Class	:	3
Packing group	:	II
Labels	:	FLAMMABLE LIQUID
ERG Code	:	128
Marine pollutant	:	no

### Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

## SECTION 15. REGULATORY INFORMATION

### CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
Toluene	108-88-3	100	100 (F005)
Methyl isobutyl ketone	108-10-1	100	100 (F003)
Xylene	1330-20-7	100	100 (F003)
Ethylbenzene	100-41-4	100	100 (F003)
Xylene	1330-20-7	100	*

\*: Calculated RQ exceeds reasonably attainable upper limit.

### SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

### SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

**SARA 311/312 Hazards** : Flammable (gases, aerosols, liquids, or solids)  
 Reproductive toxicity  
 Specific target organ toxicity (single or repeated exposure)  
 Skin corrosion or irritation  
 Serious eye damage or eye irritation

**SARA 313** : The following components are subject to reporting levels established by SARA Title III, Section 313:

Toluene	108-88-3	>= 10 - < 20 %
Methyl isobutyl ketone	108-10-1	>= 10 - < 20 %
Xylene	1330-20-7	>= 1 - < 5 %
Ethylbenzene	100-41-4	>= 0.1 - < 1 %

### Clean Air Act

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 112 (40 CFR 61):

**PRIAM 32005 NOIR MAT PARTIE A**

Version	Revision Date:	SDS Number:	Date of last issue: 10/16/2020
1.5	03/31/2021	102000070000	Date of first issue: 12/18/2017

Toluene	108-88-3	>= 10 - < 20 %
Methyl isobutyl ketone	108-10-1	>= 10 - < 20 %
Xylene	1330-20-7	>= 1 - < 5 %

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

The following chemical(s) are listed under the U.S. Clean Air Act Section 111 SOCM I Intermediate or Final VOC's (40 CFR 60.489):

Toluene	108-88-3	>= 10 - < 20 %
Methyl isobutyl ketone	108-10-1	>= 10 - < 20 %
Butyl acetate	123-86-4	>= 10 - < 20 %
Xylene	1330-20-7	>= 1 - < 5 %

**Clean Water Act**

The following Hazardous Substances are listed under the U.S. CleanWater Act, Section 311, Table 116.4A:

Toluene	108-88-3	>= 10 - < 20 %
Butyl acetate	123-86-4	>= 10 - < 20 %
Xylene	1330-20-7	>= 1 - < 5 %
Ethylbenzene	100-41-4	>= 0.1 - < 1 %

The following Hazardous Chemicals are listed under the U.S. CleanWater Act, Section 311, Table 117.3:

Toluene	108-88-3	>= 10 - < 20 %
Butyl acetate	123-86-4	>= 10 - < 20 %
Xylene	1330-20-7	>= 1 - < 5 %
Ethylbenzene	100-41-4	>= 0.1 - < 1 %

This product contains the following toxic pollutants listed under the U.S. Clean Water Act Section 307

Toluene	108-88-3	>= 10 - < 20 %
---------	----------	----------------

This product contains the following priority pollutants related to the U.S. Clean Water Act:

Toluene	108-88-3	>= 10 - < 20 %
---------	----------	----------------

**US State Regulations****Massachusetts Right To Know**

Toluene	108-88-3
Methyl isobutyl ketone	108-10-1
Butyl acetate	123-86-4
silica gel (Amorphous and Dust)	112926-00-8
Xylene	1330-20-7
Carbon black	1333-86-4

**Pennsylvania Right To Know**

polyester polyol, non hazardous	Not Assigned
Toluene	108-88-3
Methyl isobutyl ketone	108-10-1
Butyl acetate	123-86-4
silica gel (Amorphous and Dust)	112926-00-8
Xylene	1330-20-7
Carbon black	1333-86-4
Ethylbenzene	100-41-4

**Maine Chemicals of High Concern**

Toluene	108-88-3
---------	----------

The following chemicals are listed as Maine Chemicals of High Concern:

**Maine Chemicals of High Concern**

## PRIAM 32005 NOIR MAT PARTIE A

Version	Revision Date:	SDS Number:	Date of last issue: 10/16/2020
1.5	03/31/2021	102000070000	Date of first issue: 12/18/2017

---

Toluene	108-88-3
---------	----------

### Vermont Chemicals of High Concern

Toluene	108-88-3
Ethylbenzene	100-41-4

### Washington Chemicals of High Concern

Toluene	108-88-3
Ethylbenzene	100-41-4

### California Prop. 65

WARNING: This product can expose you to chemicals including Methyl isobutyl ketone, Carbon black, Ethylbenzene, which is/are known to the State of California to cause cancer, and Toluene, Methyl isobutyl ketone, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

### California List of Hazardous Substances

Toluene	108-88-3
Methyl isobutyl ketone	108-10-1
Butyl acetate	123-86-4
Xylene	1330-20-7
Carbon black	1333-86-4

### California Permissible Exposure Limits for Chemical Contaminants

Toluene	108-88-3
Methyl isobutyl ketone	108-10-1
Butyl acetate	123-86-4
silica gel (Amorphous and Dust)	112926-00-8
2-Propanol, 1-methoxy-, acetate	108-65-6
Xylene	1330-20-7
Carbon black	1333-86-4

### The components of this product are reported in the following inventories:

TSCA	:	In compliance with the TSCA inventory
DSL	:	This product contains the following components that are not on the Canadian DSL nor NDSL.
		polyester polyol, non hazardous
		Poly-acrylate
		polysiloxane, non hazardous

### TSCA list

No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.


---

## SECTION 16. OTHER INFORMATION

### Further information

## PRIAM 32005 NOIR MAT PARTIE A

Version 1.5      Revision Date: 03/31/2021      SDS Number: 102000070000      Date of last issue: 10/16/2020  
 Date of first issue: 12/18/2017

**NFPA 704:****HMIS® IV:**

<b>HEALTH</b>	*	<b>2</b>
<b>FLAMMABILITY</b>		<b>4</b>
<b>PHYSICAL HAZARD</b>		<b>0</b>

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "\*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

**Full text of other abbreviations**

ACGIH	: USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI	: ACGIH - Biological Exposure Indices (BEI)
NIOSH REL	: USA. NIOSH Recommended Exposure Limits
OSHA P0	: USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000
OSHA Z-1	: USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
OSHA Z-2	: USA. Occupational Exposure Limits (OSHA) - Table Z-2
OSHA Z-3	: USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts
US WEEL	: USA. Workplace Environmental Exposure Levels (WEEL)
ACGIH / TWA	: 8-hour, time-weighted average
ACGIH / STEL	: Short-term exposure limit
NIOSH REL / TWA	: Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
NIOSH REL / ST	: STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday
OSHA P0 / TWA	: 8-hour time weighted average
OSHA P0 / STEL	: Short-term exposure limit
OSHA Z-1 / TWA	: 8-hour time weighted average
OSHA Z-2 / TWA	: 8-hour time weighted average
OSHA Z-2 / CEIL	: Acceptable ceiling concentration
OSHA Z-2 / Peak	: Acceptable maximum peak above the acceptable ceiling concentration for an 8-hr shift
OSHA Z-3 / TWA	: 8-hour time weighted average
US WEEL / TWA	: 8-hr TWA

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely



**PRIAM 32005 NOIR MAT PARTIE A**

Version	Revision Date:	SDS Number:	Date of last issue: 10/16/2020
1.5	03/31/2021	102000070000	Date of first issue: 12/18/2017

---

Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 03/31/2021

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN