

Aircraft Deicing Fluid Type 1 RTU

1 PRODUCT AND COMPANY IDENTIFICATION

Product Identifier: Aircraft Deicing Fluid Type I
Common Name: Aircraft Deicing Fluid Type I
Revision Date: 07/26/2016
Supplier Details: Aircraft Deicing Inc
Woodstock, IL 60098
Emergency: (800) 424-9300 (CHEMTREC)

2 HAZARDS IDENTIFICATION

Classification of the Substance or Mixture

GHS Classification in Accordance with 29 CFR 1910 (OSHA HCS):

Health, Serious Eye Damage/Eye Irritation, 2 B
Health, Skin corrosion/irritation, 3

GHS Label Elements, Including Precautionary Statements

GHS Signal Word: **WARNING**

GHS Hazard Pictograms:

no GHS pictograms indicated for this product

GHS Hazard Statements:

H320 - Causes eye irritation
H316 - Causes mild skin irritation

GHS Precautionary Statements:

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Hazards not Otherwise Classified (HNOC) or not Covered by GHS

Route of Entry: Eyes; Ingestion; Inhalation; Skin;
Inhalation: None under normal use
Skin Contact: None expected with normal use
Eye Contact: May cause irritation.
Ingestion: None expected with normal use.

3 COMPOSITION/INFORMATION OF INGREDIENTS

Ingredients:

Cas#	%	Chemical Name
57-55-6	<50%	Propylene glycol

4 FIRST AID MEASURES

Aircraft Deicing Fluid Type 1 RTU

Inhalation: If symptoms develop, move victim to fresh air. If symptoms persist, obtain medical attention.
Skin Contact: Wash with soap and water.
Eye Contact: Immediately flush eyes with large amounts of water for at least 15 minutes, lifting eyelids occasionally to facilitate irrigation.
Ingestion: Bring to the attention of a physician.

5 FIRE FIGHTING MEASURES

Flash Point: 255 F
Flash Point Method: Closed Cup

Dry powder, foam, carbon dioxide.

6 ACCIDENTAL RELEASE MEASURES

Collect balance and small spills onto absorbant material.

Dispose in accordance with local, state & federal regulations

7 HANDLING AND STORAGE

Handling Precautions: Avoid contact with eyes, skin, or clothing.
Local exhaust adequate

Storage Requirements: Store in cool/dry area.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Personal Protective Equipment: Propylene glycol cas#:(57-55-6) [<50%]

Personal protective equipment

Hand protection: Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching gloves outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands. Full contact Material: Nitrile rubber Minimum layer thickness: 0.11 mm Break through time: 480 min Material tested: Dermatril (KCL 740 / Aldrich Z677272, Size M) Splash contact data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail sales@kcl.de, test method: EN374 If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

Eye protection: Safety glasses with side-shields conforming to EN166 Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

Skin and body protection: impervious clothing, The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Hygiene measures: Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

Aircraft Deicing Fluid Type 1 RTU

Propylene glycol cas#:(57-55-6) [<50%]

Components with workplace control parameters

TWA 10 mg/m3 (WEEL) USA. Workplace Environmental Exposure Levels

9 PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Clear Orange liquid	Odor:	Mild chemical smell
Physical State:	Liquid	Solubility:	Complete
Spec Grav./Density:	1.044	Flash Point:	255 F
Boiling Point:	255 F		
Vapor Pressure:	<13.3 hPa		
pH:	8.0		
Evap. Rate:	<Ether		

10 STABILITY AND REACTIVITY

Reactivity:	None
Chemical Stability:	Product is stable under normal conditions.
Conditions to Avoid:	None
Materials to Avoid:	None
Hazardous Polymerization:	Will not occur.

11 TOXICOLOGICAL INFORMATION

Propylene glycol cas#:(57-55-6) [<50%]

Information on toxicological effects

Acute toxicity:

Oral LD50 LD50 Oral - rat - 20,000 mg/kg

Inhalation LC50 no data available

Dermal LD50 LD50 Dermal - rabbit - 20,800 mg/kg

Other information on acute toxicity LD50 Intramuscular - rat - 14 g/kg

LD50 Intravenous - dog - 26 g/kg

LD50 Intraperitoneal - rat - 6,660 mg/kg

LD50 Subcutaneous - rat - 22,500 mg/kg

LD50 Intravenous - rat - 6,423 mg/kg

LD50 Intraperitoneal - mouse - 9,718 mg/kg

Remarks: Lungs, Thorax, or Respiration:Chronic pulmonary edema. Kidney, Ureter, Bladder:Changes in both tubules and glomeruli.

Blood:Changes in spleen.

LD50 Subcutaneous - mouse - 17,370 mg/kg

Remarks: Behavioral:Change in motor activity (specific assay). Behavioral:Muscle contraction or spasticity. Cyanosis

LD50 Intravenous - mouse - 6,630 mg/kg

LD50 Intravenous - rabbit - 6,500 mg/kg

Skin corrosion/irritation: Skin - Human - Mild skin irritation - 7 d

Aircraft Deicing Fluid Type 1 RTU

Serious eye damage/eye irritation: Eyes - rabbit - Mild eye irritation

Respiratory or skin sensitisation: no data available

Germ cell mutagenicity: no data available

Carcinogenicity:

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

ACGIH: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Reproductive toxicity: no data available

Teratogenicity: no data available

Specific target organ toxicity - single exposure (Globally Harmonized System):
no data available

Specific target organ toxicity - repeated exposure (Globally Harmonized System):
no data available

Aspiration hazard: no data available

Potential health effects: Inhalation May be harmful if inhaled. May cause respiratory tract irritation. Ingestion May be harmful if swallowed. Skin May be harmful if absorbed through skin. May cause skin irritation. Eyes May cause eye irritation.

Signs and Symptoms of Exposure: Gastrointestinal disturbance, Nausea, Headache, Vomiting, Central nervous system depression

Synergistic effects: no data available

Additional Information:

RTECS: TY2000000

12

ECOLOGICAL INFORMATION

Propylene glycol cas#:(57-55-6) [<50%]

Information on ecological effects

Toxicity:

Toxicity to fish mortality NOEC - Pimephales promelas (fathead minnow) - 52,930 mg/l - 96 h.

Toxicity to daphnia mortality NOEC - Daphnia - 13,020 mg/l - 48 h.

and other aquatic invertebrates

EC50 - Daphnia magna (Water flea) - > 10,000 mg/l - 48 h

Persistence and degradability: no data available

Bioaccumulative potential: no data available

Mobility in soil: no data available

Aircraft Deicing Fluid Type 1 RTU

PBT and vPvB assessment: no data available

Other adverse effects: no data available

13 DISPOSAL CONSIDERATIONS

Propylene glycol cas#:(57-55-6) [<50%]

Waste treatment methods

Product: Offer surplus and non-recyclable solutions to a licensed disposal company.

Contaminated packaging: Dispose of as unused product.

14 TRANSPORT INFORMATION

Not hazardous product according to these transport classifications.

15 REGULATORY INFORMATION

Component (CAS#) [%] - CODES

Propylene glycol (57-55-6) [<50%] HAP, PA, TSCA

Regulatory CODE Descriptions

HAP = Hazardous Air Pollutants

PA = PA Right-To-Know List of Hazardous Substances

TSCA = Toxic Substances Control Act

16 OTHER INFORMATION

SDS *GHS Safety Data Sheet*


Aircraft Deicing Inc.

Aircraft Deicing Fluid Type 1 RTU

NFPA: Health = 1, Fire = 0, Reactivity = 0, Specific Hazard = n/a

HMIS III: Health = 1, Fire = 0, Physical Hazard = 0

HMIS PPE: B - Safety Glasses, Gloves



HMIS	
HEALTH	1
FLAMMABILITY	0
PHYSICAL HAZARD	0
PERSONAL PROTECTION	B

Aircraft Deicing, Inc. makes no representations or warranties, either express or implied, including without limitation any warranties of merchantability, fitness for a particular purpose with respect to the information set forth herein or the product to which the information refers.