

## SAFETY DATA SHEET

**HUNTSMAN**

Enriching lives through innovation

## ARATHANE® 5753 A

Version 3.0      Revision Date: 05/02/2022      SDS Number: 400001009994      Date of last issue: 08/26/2020  
 Date of first issue: 12/09/2015

Print Date 05/03/2022

## SECTION 1. IDENTIFICATION

Product name : ARATHANE® 5753 A

**Manufacturer or supplier's details**

Company name of supplier : Huntsman Advanced Materials Americas LLC  
 Address : P.O. Box 4980  
 The Woodlands,  
 TX 77387  
 United States of America (USA)

Telephone : Non-Emergency: (800) 257-5547

E-mail address of person responsible for the SDS : Global\_Product\_EHS\_AdMat@huntsman.com

Emergency telephone number : Chemtrec: (800) 424-9300 or (703) 527-3887

**Recommended use of the chemical and restrictions on use**

Recommended use : Component used for the manufacture of electrical insulation parts

## SECTION 2. HAZARDS IDENTIFICATION

**GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)**

Acute toxicity (Inhalation) : Category 4

Skin irritation : Category 2

Eye irritation : Category 2A

Respiratory sensitisation : Category 1

Skin sensitisation : Category 1

Specific target organ toxicity - single exposure : Category 3 (Respiratory system)

Specific target organ toxicity - repeated exposure (Inhalation) : Category 2

Short-term (acute) aquatic hazard : Category 2

**GHS label elements**

## SAFETY DATA SHEET

**HUNTSMAN**

Enriching lives through innovation

## ARATHANE® 5753 A

Version 3.0      Revision Date: 05/02/2022      SDS Number: 400001009994      Date of last issue: 08/26/2020  
 Date of first issue: 12/09/2015

Print Date 05/03/2022

Hazard pictograms :



Signal word : Danger

Hazard statements : H315 Causes skin irritation.  
 H317 May cause an allergic skin reaction.  
 H319 Causes serious eye irritation.  
 H332 Harmful if inhaled.  
 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
 H335 May cause respiratory irritation.  
 H373 May cause damage to organs through prolonged or repeated exposure if inhaled.  
 H401 Toxic to aquatic life.

Precautionary statements : **Prevention:**  
 P260 Do not breathe the mist or vapours.  
 P264 Wash skin thoroughly after handling.  
 P271 Use only outdoors or in a well-ventilated area.  
 P272 Contaminated work clothing must not be allowed out of the workplace.  
 P273 Avoid release to the environment.  
 P280 Wear protective gloves/ eye protection/ face protection.  
 P285 In case of inadequate ventilation wear respiratory protection.  
**Response:**  
 P302 + P352 IF ON SKIN: Wash with plenty of soap and water.  
 P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.  
 P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention..  
 P337 + P313 If eye irritation persists: Get medical advice/ attention.  
 P342 + P311 If experiencing respiratory symptoms: Call a POISON CENTER/ doctor.  
 P362 Take off contaminated clothing and wash before reuse.  
**Storage:**  
 P403 + P233 Store in a well-ventilated place. Keep container tightly closed.  
 P405 Store locked up.  
**Disposal:**  
 P501 Dispose of contents/container to an approved facility in accordance with local, regional, national and international regulations.

**Other hazards**

None known.

## SAFETY DATA SHEET

**HUNTSMAN**

Enriching lives through innovation

## ARATHANE® 5753 A

Version 3.0    Revision Date: 05/02/2022    SDS Number: 400001009994    Date of last issue: 08/26/2020  
 Date of first issue: 12/09/2015

Print Date 05/03/2022

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

## Hazardous components

Chemical name	CAS-No.	Concentration (% w/w)
4,4'-methylenediphenyl diisocyanate	101-68-8	50 - 70
Benzene, 1,1'-methylenebis(isocyanato-, homopolymer	39310-05-9	20 - 30
2,4'-methylenediphenyl diisocyanate	5873-54-1	1 - 5
triethyl phosphate	78-40-0	1 - 5

The specific chemical identity and/or exact percentage (concentration) of composition may be withheld as a trade secret.

## SECTION 4. FIRST AID MEASURES

- General advice** : Move out of dangerous area.  
 Do not leave the victim unattended.  
 Get medical attention immediately if symptoms occur.  
 Show this safety data sheet to the doctor in attendance.
- If inhaled** : If breathed in, move person into fresh air.  
 Call a physician or poison control centre immediately.  
 Keep patient warm and at rest.  
 Keep respiratory tract clear.  
 If breathing is difficult, give oxygen.  
 If breathing is irregular or stopped, administer artificial respiration.  
 If unconscious, place in recovery position and seek medical advice.  
 Consult a physician immediately if symptoms such as shortness of breath or asthma are observed.  
 A hyper-reactive response to even minimal concentrations of diisocyanates may develop in sensitised persons.  
 The exposed person may need to be kept under medical surveillance for 48 hours.  
 LC50 (rat) : ca. 490 mg/m<sup>3</sup> (4 hours) : using experimentally produced respirable aerosol having aerodynamic diameter <5microns.  
 Methods used to generate the exposure concentrations in the animal studies use extreme laboratory conditions and does not represent actual exposure conditions of the material in the workplace, storage, transportation or expected use on the market due to the very low vapor pressure. Therefore, these test results cannot be used to for hazard classification of the

## SAFETY DATA SHEET

**HUNTSMAN**

Enriching lives through innovation

## ARATHANE® 5753 A

Version 3.0    Revision Date: 05/02/2022    SDS Number: 400001009994    Date of last issue: 08/26/2020  
 Date of first issue: 12/09/2015

Print Date 05/03/2022

- In case of skin contact** : material. Rather, an acute toxicity estimate is calculated based on weight of evidence and expert judgement and is used to justify a modified classification for acute inhalation toxicity.  
 In case of contact, immediately flush skin with soap and plenty of water.  
 Take off contaminated clothing and shoes immediately.  
 Wash contaminated clothing before reuse.  
 Thoroughly clean shoes before reuse.  
 Call a physician if irritation develops or persists.  
 An MDI study has demonstrated that a polyglycol-based skin cleanser (such as D-Tam™, PEG-400) or corn oil may be more effective than soap and water.
- In case of eye contact** : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.  
 If easy to do, remove contact lens, if worn.  
 Protect unharmed eye.  
 Keep eye wide open while rinsing.  
 Seek medical advice.
- If swallowed** : Gently wipe or rinse the inside of the mouth with water.  
 DO NOT induce vomiting unless directed to do so by a physician or poison control center.  
 Keep respiratory tract clear.  
 Keep at rest.  
 If a person vomits when lying on his back, place him in the recovery position.  
 Never give anything by mouth to an unconscious person.  
 Take victim immediately to hospital.  
 If symptoms persist, call a physician.
- Most important symptoms and effects, both acute and delayed** : Severe allergic skin reactions, bronchospasm and anaphylactic shock  
 This product is a respiratory irritant and potential respiratory sensitiser: repeated inhalation of vapour or aerosol at levels above the occupational exposure limit could cause respiratory sensitisation.  
 Symptoms may include irritation to the eyes, nose, throat and lungs, possibly combined with dryness of the throat, tightness of chest and difficulty in breathing.  
 The onset of the respiratory symptoms may be delayed for several hours after exposure.  
 A hyper-reactive response to even minimal concentrations of MDI may develop in sensitised persons.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training.  
 It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.  
 If potential for exposure exists refer to Section 8 for specific personal protective equipment.  
 First Aid responders should pay attention to self-protection and use the recommended protective clothing

## SAFETY DATA SHEET

**HUNTSMAN**

Enriching lives through innovation

**ARATHANE® 5753 A**

Version 3.0      Revision Date: 05/02/2022      SDS Number: 400001009994      Date of last issue: 08/26/2020  
 Date of first issue: 12/09/2015

Print Date 05/03/2022

- Notes to physician : Symptomatic and supportive therapy as needed. Following severe exposure medical follow-up should be monitored for at least 48 hours.
- The first aid procedure should be established in consultation with the doctor responsible for industrial medicine.

**SECTION 5. FIREFIGHTING MEASURES**

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry powder
- Unsuitable extinguishing media : Water may be used if no other available and then in copious quantities. Reaction between water and hot isocyanate may be vigorous.
- Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.  
The pressure in sealed containers can increase under the influence of heat.  
Exposure to decomposition products may be a hazard to health.
- Hazardous combustion products : Combustion products may include: carbon monoxide, carbon dioxide, nitrogen oxides, hydrocarbons and HCN. In the event of extreme heat (>500 degrees C), aniline is suspected of being formed.
- Specific extinguishing methods : Cool containers/tanks with water spray.
- Further information : Standard procedure for chemical fires.  
Due to reaction with water producing CO<sub>2</sub>-gas, a hazardous build-up of pressure could result if contaminated containers are re-sealed.  
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Prevent fire extinguishing water from contaminating surface water or the ground water system.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
- Special protective equipment for firefighters : Wear an approved positive pressure self-contained breathing apparatus in addition to standard fire fighting gear.

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

- Personal precautions, protective equipment and emergency procedures : Immediately evacuate personnel to safe areas.  
Use personal protective equipment.  
If specialised clothing is required to deal with the spillage, take

## SAFETY DATA SHEET

**HUNTSMAN**

Enriching lives through innovation

**ARATHANE® 5753 A**

Version 3.0      Revision Date: 05/02/2022      SDS Number: 400001009994      Date of last issue: 08/26/2020  
 Date of first issue: 12/09/2015

Print Date 05/03/2022

- note of any information in Section 8 on suitable and unsuitable materials.  
Ensure adequate ventilation.  
Keep people away from and upwind of spill/leak.  
Only qualified personnel equipped with suitable protective equipment may intervene.  
For additional precautions and advice on safe handling, see section 7.  
Never return spills in original containers for re-use.  
Make sure that there is a sufficient amount of neutralizing/absorbent material near the storage area.  
The danger areas must be delimited and identified using relevant warning and safety signs.  
Treat recovered material as described in the section "Disposal considerations".  
For disposal considerations see section 13.
- Environmental precautions : Do not allow uncontrolled discharge of product into the environment.  
Do not allow material to contaminate ground water system.  
Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
Local authorities should be advised if significant spillages cannot be contained.  
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Clean-up methods - small spillage  
Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).  
Clean contaminated surface thoroughly.  
Sweep up or vacuum up spillage and collect in suitable container for disposal.  
Neutralize small spillages with decontaminant.  
The compositions of liquid decontaminants are given in Section 16.  
Remove and dispose of residues.  
Clean-up methods - large spillage  
If the product is in its solid form:  
Spilled MDI flakes should be picked up carefully.  
The area should be vacuum cleaned to remove remaining dust particles completely.  
If the product is in its liquid form:  
Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).  
Leave to react for at least 30 minutes.  
Shovel into open-top drums for further decontamination.  
Wash the spillage area with water.  
Test atmosphere for MDI vapour.  
Keep in suitable, closed containers for disposal.

## SAFETY DATA SHEET

**HUNTSMAN**

Enriching lives through innovation

## ARATHANE® 5753 A

Version 3.0      Revision Date: 05/02/2022      SDS Number: 400001009994      Date of last issue: 08/26/2020  
 Date of first issue: 12/09/2015

Print Date 05/03/2022

## SECTION 7. HANDLING AND STORAGE

- Technical measures** : Ensure that eyewash stations and safety showers are close to the workstation location.
- Local/Total ventilation** : Use only with adequate ventilation.
- Advice on protection against fire and explosion** : Normal measures for preventive fire protection.
- Advice on safe handling** : For personal protection see section 8.  
 Avoid formation of aerosol.  
 Do not breathe vapours or spray mist.  
 Do not breathe vapours/dust.  
 Do not swallow.  
 Do not get in eyes or mouth or on skin.  
 Do not get on skin or clothing.  
 Avoid exposure - obtain special instructions before use.  
 Smoking, eating and drinking should be prohibited in the application area.  
 Provide sufficient air exchange and/or exhaust in work rooms.  
 Keep container closed when not in use.  
 Open drum carefully as content may be under pressure.  
 Dispose of rinse water in accordance with local and national regulations.  
 Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.  
 Industrial use of aprotic polar solvents for cleaning can release hazardous primary aromatic amines (>0.1%)
- Conditions for safe storage** : Keep containers tightly closed in a dry, cool and well-ventilated place.  
 Keep in properly labelled containers.  
 Observe label precautions.  
 Protect from moisture.  
 Electrical installations / working materials must comply with the technological safety standards.  
 Containers which are opened must be carefully resealed and kept upright to prevent leakage.
- Materials to avoid** : For incompatible materials please refer to Section 10 of this SDS.
- Recommended storage temperature** : 64 - 104 °F / 18 - 40 °C

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

## Components with workplace control parameters

Components	CAS-No.	Value type	Control	Basis
------------	---------	------------	---------	-------

## SAFETY DATA SHEET

**HUNTSMAN**

Enriching lives through innovation

## ARATHANE® 5753 A

Version 3.0      Revision Date: 05/02/2022      SDS Number: 400001009994      Date of last issue: 08/26/2020  
 Date of first issue: 12/09/2015

Print Date 05/03/2022

		(Form of exposure)	parameters / Permissible concentration	
4,4'-methylenediphenyl diisocyanate	101-68-8	TWA	0.005 ppm	ACGIH
		TWA	0.005 ppm 0.05 mg/m3	NIOSH REL
		C	0.02 ppm 0.2 mg/m3	NIOSH REL
		C	0.02 ppm 0.2 mg/m3	OSHA Z-1
		C	0.02 ppm 0.2 mg/m3	OSHA P0
2,4'-methylenediphenyl diisocyanate	5873-54-1	C	0.02 ppm 0.2 mg/m3	OSHA Z-1
		TWA	0.005 ppm 0.05 mg/m3	NIOSH REL
		C	0.02 ppm 0.2 mg/m3	NIOSH REL
		C	0.02 ppm 0.2 mg/m3	OSHA P0

## Personal protective equipment

- Respiratory protection** : Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.  
 Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.  
 In emergency, non-routine and unknown exposure situations, including confined space entries, a NIOSH-certified full facepiece pressure demand self-contained breathing apparatus (SCBA) or a full facepiece pressure demand supplied air respirator (SAR) with auxiliary self-contained air supply, should be used.

## Hand protection

- Remarks** : The suitability for a specific workplace should be discussed with the producers of the protective gloves.  
 Protective gloves should be worn when handling freshly made polyurethane products to avoid contact with trace residual materials which may be hazardous in contact with skin.

Use chemical resistant gloves classified under Standard EN374: protective gloves against chemicals and microorganisms. Examples of glove materials that might provide suitable protection include: Butyl rubber, Chlorinated polyethylene, Polyethylene, Ethyl vinyl alcohol copolymers laminated ("EVAL"), Polychloroprene (Neoprene), Nitrile/butadiene rubber ("nitrile" or "NBR"), Polyvinyl chloride ("PVC" or "vinyl"), Fluoroelastomer (Viton®).

When prolonged or frequently repeated contact may occur, a glove with protection class of 5 or higher (breakthrough time

## SAFETY DATA SHEET

**HUNTSMAN**

Enriching lives through innovation

## ARATHANE® 5753 A

Version 3.0      Revision Date: 05/02/2022      SDS Number: 400001009994      Date of last issue: 08/26/2020  
 Date of first issue: 12/09/2015

Print Date 05/03/2022

greater than 240 minutes according to EN374) is recommended.

When only brief contact is expected, a glove with protection class of 3 or higher (breakthrough time greater than 60 minutes according to EN374) is recommended.

Notice: The selection of a specific glove for a particular application and duration of use in a workplace should also take into account all requisite workplace factors such as, but not limited to : other chemicals that may be handled, physical requirements (cut/puncture protection, dexterity, thermal protection), as well as instructions/specifications provided by the glove supplier

By industrial use of aprotic polar solvents for cleaning : Butyl rubber (0.7mm), Nitrile rubber (0.4mm), Chloroprene (0.5mm)

Eye protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists or dusts. Chemical splash goggles.

Always wear eye protection when the potential for inadvertent eye contact with the product cannot be excluded.

Please follow all applicable local/national requirements when selecting protective measures for a specific workplace.

Ensure that eyewash stations and safety showers are close to the workstation location.

Skin and body protection : Impervious clothing  
 Choose body protection according to the amount and concentration of the dangerous substance at the work place.  
 Recommended:  
 Overall (preferably heavy cotton) or Tyvek-Pro Tech 'C', Tyvek Pro 'F' disposable coverall.

Protective measures : Personal protective equipment comprising: suitable protective gloves, safety goggles and protective clothing  
 The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.  
 Ensure that eye flushing systems and safety showers are located close to the working place.

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice.  
 Wash face, hands and any exposed skin thoroughly after handling.  
 Remove contaminated clothing and protective equipment before entering eating areas.  
 When using do not eat, drink or smoke.  
 Contaminated work clothing should not be allowed out of the workplace.  
 Wash hands before breaks and immediately after handling the product.  
 Wash hands before breaks and at the end of workday.

## SAFETY DATA SHEET

**HUNTSMAN**

Enriching lives through innovation

## ARATHANE® 5753 A

Version 3.0      Revision Date: 05/02/2022      SDS Number: 400001009994      Date of last issue: 08/26/2020  
 Date of first issue: 12/09/2015

Print Date 05/03/2022

## SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: liquid
Colour	: yellow
Odour	: slight
Odour Threshold	: No data is available on the product itself.
pH	: substance/mixture reacts with water
Melting point/freezing point	: No data available
Boiling point/boiling range	: 597 °F / 314 °C
Flash point	: > 351 °F / > 177 °C Method: Pensky-Martens closed cup
Evaporation rate	: No data is available on the product itself.
Flammability (solid, gas)	: No data is available on the product itself.
Flammability (liquids)	: No data is available on the product itself.
Upper explosion limit / Upper flammability limit	: No data is available on the product itself.
Lower explosion limit / Lower flammability limit	: No data is available on the product itself.
Vapour pressure	: < 0.0004 hPa (77 °F / 25 °C)
Relative vapour density	: No data is available on the product itself.
Relative density	: 1.2
Density	: 1.2 g/cm3
Solubility(ies)	
Water solubility	: Water reactive
Solubility in other solvents	: No data is available on the product itself.
Partition coefficient: n-octanol/water	: No data is available on the product itself.
Auto-ignition temperature	: No data is available on the product itself.
Decomposition temperature	: No data is available on the product itself.
Self-Accelerating decomposition temperature (SADT)	: No data is available on the product itself.

## SAFETY DATA SHEET

**HUNTSMAN**

Enriching lives through innovation

## ARATHANE® 5753 A

Version 3.0      Revision Date: 05/02/2022      SDS Number: 400001009994      Date of last issue: 08/26/2020  
 Date of first issue: 12/09/2015

Print Date 05/03/2022

Assessment : May cause sensitisation by inhalation.  
 Result : Causes sensitisation.

Assessment : Mild eye irritation

**triethyl phosphate:**

Exposure routes : Skin  
 Species : Mouse  
 Method : OECD Test Guideline 429  
 Result : Does not cause skin sensitisation.

**Germ cell mutagenicity****Components:****4,4'-methylenediphenyl diisocyanate:**

Genotoxicity in vitro : Test Type: reverse mutation assay  
 Test system: Salmonella typhimurium  
 Metabolic activation: with and without metabolic activation  
 Method: Directive 67/548/EEC, Annex, B.13/14  
 Result: negative

Genotoxicity in vivo : Test Type: Micronucleus test  
 Species: Rat (male)  
 Cell type: Somatic  
 Application Route: Inhalation  
 Exposure time: 3 Weeks  
 Dose: 113 mg/m<sup>3</sup>  
 Method: OECD Test Guideline 474  
 Result: negative

Test Type: comet assay  
 Species: Rat (male)  
 Cell type: Liver cells  
 Application Route: inhalation (dust/mist/fume)  
 Dose: 2.5/4.9/12 mg/m<sup>3</sup>  
 Method: OECD Test Guideline 489  
 Result: negative

**Benzene, 1,1'-methylenebis(isocyanato-, homopolymer:**

Genotoxicity in vitro : Concentration: ca 50 ug/plate  
 Metabolic activation: with and without metabolic activation  
 Method: OECD Test Guideline 471  
 Result: negative

Genotoxicity in vivo : Application Route: Inhalation  
 Exposure time: 3 Weeks  
 Dose: 118 mg/m<sup>3</sup>  
 Method: OECD Test Guideline 474  
 Result: negative

Germ cell mutagenicity - Assessment : Animal testing did not show any mutagenic effects.

## SAFETY DATA SHEET

**HUNTSMAN**

Enriching lives through innovation

## ARATHANE® 5753 A

Version 3.0      Revision Date: 05/02/2022      SDS Number: 400001009994      Date of last issue: 08/26/2020  
 Date of first issue: 12/09/2015

Print Date 05/03/2022

**2,4'-methylenediphenyl diisocyanate:**

Genotoxicity in vitro : Metabolic activation: with and without metabolic activation  
 Method: OECD Test Guideline 471  
 Result: negative

Genotoxicity in vivo : Application Route: Inhalation  
 Exposure time: 3 w  
 Dose: 118 mg/m<sup>3</sup>  
 Method: OECD Test Guideline 474  
 Result: negative

**triethyl phosphate:**

Genotoxicity in vitro : Metabolic activation: with and without metabolic activation  
 Method: OECD Test Guideline 476  
 Result: negative

Method: OECD Test Guideline 482  
 Result: negative

Genotoxicity in vivo : Application Route: Intraperitoneal injection  
 Method: OECD Test Guideline 478  
 Result: negative

**Carcinogenicity****Product:**

Remarks : Rats have been exposed for two years to a respirable aerosol of polymeric MDI which resulted in a chronic pulmonary irritation at high concentrations. Only at the top level (6 mg/m<sup>3</sup>), there was a significant incidence of a benign tumour of the lung (adenoma) and one malignant tumour (adenocarcinoma). There were no lung tumours at 1 mg/m<sup>3</sup> and no effects at 0.2 mg/m<sup>3</sup>. Overall, the tumour incidence, both benign and malignant, and the number of animals with the tumours were not different from controls. The increased incidence of lung tumours is associated with prolonged respiratory irritation and the concurrent accumulation of yellow material in the lung, which occurred throughout the study. In the absence of prolonged exposure to high concentrations leading to chronic irritation and lung damage, it is highly unlikely that tumour formation will occur.

Remarks : Industrial use of aprotic polar solvents for cleaning can release hazardous primary aromatic amines (>0.1%) Based on animal studies, primary aromatic amines are considered as potential carcinogen to humans. Some of those chemicals are proven carcinogens to humans Provided the recommended personal protective equipment and hygiene measures are applied, no adverse effects to human health are to be expected

**Components:****4,4'-methylenediphenyl diisocyanate:**

Species : Rat, female

## SAFETY DATA SHEET

**HUNTSMAN**

Enriching lives through innovation

**ARATHANE® 5753 A**

Version 3.0      Revision Date: 05/02/2022      SDS Number: 400001009994      Date of last issue: 08/26/2020  
 Date of first issue: 12/09/2015

Print Date 05/03/2022

Application Route : Inhalation  
 Exposure time : 24 month(s)  
 Activity duration : 17 h  
 Dose : 0, 0.2, 0.7, 2.1 mg/m<sup>3</sup> mg/m<sup>3</sup>  
 Frequency of Treatment : 5 days/week  
 NOEL : 0.7 mg/m<sup>3</sup>  
 LOAEL : 0.23 mg/m<sup>3</sup>  
 Result : positive  
 Target Organs : Lungs

**Benzene, 1,1'-methylenebis[isocyanato-, homopolymer:**

Species : Rat, male and female  
 Application Route : Inhalation  
 Exposure time : 24 month(s)  
 Dose : 1 mg/m<sup>3</sup>  
 Frequency of Treatment : 5 daily  
 Method : OECD Test Guideline 453  
 Result : negative

**2,4'-methylenediphenyl diisocyanate:**

Species : Rat, male and female  
 Application Route : Inhalation  
 Exposure time : 24 month(s)  
 Dose : 1 mg/m<sup>3</sup>  
 Frequency of Treatment : 5 daily  
 Method : OECD Test Guideline 453  
 Result : positive  
 Target Organs : Lungs

**IARC** No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

**OSHA** No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

**NTP** No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

**Reproductive toxicity****Components:****4,4'-methylenediphenyl diisocyanate:**

Effects on foetal development : Test Type: Pre-natal  
 Species: Rat, female  
 Application Route: Inhalation  
 Dose: 0/1/3/9 mg/m<sup>3</sup>  
 Duration of Single Treatment: 10 d  
 Frequency of Treatment: 7 days/week  
 General Toxicity Maternal: LOAEL: 9 mg/m<sup>3</sup>  
 Developmental Toxicity: NOAEC: 3 mg/m<sup>3</sup>  
 Method: OECD Test Guideline 414

**Benzene, 1,1'-methylenebis[isocyanato-, homopolymer:**

## SAFETY DATA SHEET

**HUNTSMAN**

Enriching lives through innovation

**ARATHANE® 5753 A**

Version 3.0      Revision Date: 05/02/2022      SDS Number: 400001009994      Date of last issue: 08/26/2020  
 Date of first issue: 12/09/2015

Print Date 05/03/2022

Effects on foetal development : Species: Rat, female  
 Application Route: Inhalation  
 General Toxicity Maternal: NOAEL: 4 mg/m<sup>3</sup>  
 Method: OECD Test Guideline 414  
 Result: No teratogenic effects

Reproductive toxicity - Assessment : No evidence of adverse effects on sexual function and fertility, or on development, based on animal experiments.

**2,4'-methylenediphenyl diisocyanate:**

Effects on fertility : Species: Rat, female  
 Application Route: Inhalation  
 Method: OECD Test Guideline 414  
 Result: Animal testing did not show any effects on fertility.

Species: Rat, male and female  
 Application Route: Inhalation  
 Method: OECD Test Guideline 414  
 Result: Animal testing did not show any effects on fertility.

Effects on foetal development : Species: Rat, male and female  
 Application Route: Inhalation  
 General Toxicity Maternal: NOAEL: 4 mg/m<sup>3</sup>  
 Method: OECD Test Guideline 414  
 Result: No teratogenic effects

**triethyl phosphate:**

Effects on foetal development : Species: Rat  
 Application Route: Oral  
 General Toxicity Maternal: NOAEL: 125 mg/kg body weight  
 Method: OECD Test Guideline 414  
 Result: No teratogenic effects

**STOT - single exposure****Components:****4,4'-methylenediphenyl diisocyanate:**

Exposure routes : Inhalation  
 Target Organs : Respiratory Tract  
 Assessment : May cause respiratory irritation., The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with respiratory tract irritation.

**Benzene, 1,1'-methylenebis[isocyanato-, homopolymer:**

Exposure routes : inhalation (dust/mist/fume)  
 Target Organs : Respiratory Tract  
 Assessment : May cause respiratory irritation.

**2,4'-methylenediphenyl diisocyanate:**

Exposure routes : Inhalation  
 Target Organs : Respiratory system  
 Assessment : The substance or mixture is classified as specific target organ

## SAFETY DATA SHEET

**HUNTSMAN**

Enriching lives through innovation

## ARATHANE® 5753 A

Version 3.0      Revision Date: 05/02/2022      SDS Number: 400001009994      Date of last issue: 08/26/2020  
 Date of first issue: 12/09/2015

Print Date 05/03/2022

toxicant, single exposure, category 3 with respiratory tract irritation.

## STOT - repeated exposure

Components:**4,4'-methylenediphenyl diisocyanate:**

Exposure routes : Inhalation  
 Target Organs : Respiratory system  
 Assessment : May cause damage to organs through prolonged or repeated exposure., The substance or mixture is classified as specific target organ toxicant, repeated exposure, category 2.

## Repeated dose toxicity

Components:**4,4'-methylenediphenyl diisocyanate:**

Species : Rat, female  
 LOEC : 1 mg/m3  
 Application Route : Inhalation  
 Test atmosphere : dust/mist  
 Exposure time : 2 years 17 h  
 Number of exposures : 5 days/week  
 Dose : 0, 0.2, 0.7, 2.1 mg/m3  
 Method : Chronic toxicity  
 Assessment : The substance or mixture is classified as specific target organ toxicant, repeated exposure, category 2.

**Benzene, 1,1'-methylenebis[isocyanato-, homopolymer:**

Species : Rat, male and female  
 NOEC : 0.2 mg/m3  
 Test atmosphere : dust/mist  
 Exposure time : 2 yr  
 Number of exposures : 5 d  
 Method : OECD Test Guideline 453

Repeated dose toxicity - Assessment : No adverse effect has been observed in chronic toxicity tests.

**2,4'-methylenediphenyl diisocyanate:**

Species : Rat, male and female  
 NOEC : 0.2 mg/m3  
 Exposure time : 2 yr  
 Number of exposures : 5 d  
 Method : OECD Test Guideline 453

Repeated dose toxicity - Assessment : Mild eye irritation

**triethyl phosphate:**

Species : Rat, male and female  
 NOAEL : 1000 mg/kg

## SAFETY DATA SHEET

**HUNTSMAN**

Enriching lives through innovation

## ARATHANE® 5753 A

Version 3.0      Revision Date: 05/02/2022      SDS Number: 400001009994      Date of last issue: 08/26/2020  
 Date of first issue: 12/09/2015

Print Date 05/03/2022

Application Route : Ingestion  
 Exposure time : 4 Weeks  
 Number of exposures : 7 d  
 Method : Subacute toxicity

**Aspiration toxicity**

No data available

**Experience with human exposure**

No data available

**Toxicology, Metabolism, Distribution**

No data available

**Neurological effects**

No data available

**Further information**

No data available

## SECTION 12. ECOLOGICAL INFORMATION

**Ecotoxicity**Components:**4,4'-methylenediphenyl diisocyanate:**

Toxicity to fish : LC50 (Brachydanio rerio (zebrafish)): > 100 mg/l  
 End point: mortality  
 Exposure time: 96 h  
 Test substance: Fresh water  
 Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): 9 mg/l  
 End point: Immobilization  
 Exposure time: 48 h  
 Test Type: semi-static test  
 Test substance: Fresh water  
 Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : EC50 (Desmodesmus subspicatus (green algae)): > 100 mg/l  
 Exposure time: 72 h  
 Test Type: static test  
 Test substance: Fresh water  
 Method: OECD Test Guideline 201  
 GLP: yes

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): >= 10 mg/l  
 Exposure time: 21 d  
 Test Type: semi-static test  
 Test substance: Fresh water  
 Method: OECD Test Guideline 211  
 Remarks: Information given is based on data obtained from similar substances.

Toxicity to microorganisms : EC50 (activated sludge): > 1,000 mg/l  
 Exposure time: 3 h

## SAFETY DATA SHEET

**HUNTSMAN**

Enriching lives through innovation

**ARATHANE® 5753 A**

Version 3.0      Revision Date: 05/02/2022      SDS Number: 400001009994      Date of last issue: 08/26/2020  
 Date of first issue: 12/09/2015

Print Date 05/03/2022

- Test Type: static test  
 Method: OECD Test Guideline 209
- Toxicity to soil dwelling organisms : NOEC (Eisenia fetida (earthworms)): >= 1,000 mg/kg  
 Exposure time: 336 h
- Plant toxicity : EC50: >1000 milligram per kilogram  
 Exposure time: 14 d  
 Species: Avena sativa (oats)
- EC50: >1000 milligram per kilogram  
 Exposure time: 14 d  
 Species: Lactuca sativa (lettuce)

**Ecotoxicology Assessment**

- Acute aquatic toxicity : Toxic to aquatic life.

**Benzene, 1,1'-methylenebis[isocyanato-, homopolymer:**

- Toxicity to fish : LC50 (Brachydanio rerio (zebrafish)): > 1,000 mg/l  
 Exposure time: 96 h  
 Test Type: static test  
 Test substance: Fresh water  
 Method: OECD Test Guideline 203
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 1,000 mg/l  
 Exposure time: 24 h  
 Test Type: static test  
 Test substance: Fresh water  
 Method: OECD Test Guideline 202
- Toxicity to algae/aquatic plants : EC50 (Desmodesmus subspicatus (green algae)): > 1,640 mg/l  
 Exposure time: 72 h  
 Test Type: static test  
 Test substance: Fresh water  
 Method: OECD Test Guideline 201
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): >= 10 mg/l  
 Exposure time: 21 d  
 Test Type: semi-static test  
 Test substance: Fresh water  
 Method: OECD Test Guideline 211
- Toxicity to microorganisms : EC50 (activated sludge): > 100 mg/l  
 Exposure time: 3 h  
 Test Type: static test  
 Test substance: Fresh water  
 Method: OECD Test Guideline 209
- Toxicity to soil dwelling organisms : EC50 (Eisenia fetida (earthworms)): > 1,000 mg/kg  
 Exposure time: 336 h  
 Method: OECD Test Guideline 207

**2,4'-methylenediphenyl diisocyanate:**

## SAFETY DATA SHEET

**HUNTSMAN**

Enriching lives through innovation

**ARATHANE® 5753 A**

Version 3.0      Revision Date: 05/02/2022      SDS Number: 400001009994      Date of last issue: 08/26/2020  
 Date of first issue: 12/09/2015

Print Date 05/03/2022

- Toxicity to fish : LC50 (Brachydanio rerio (zebrafish)): > 1,000 mg/l  
 Exposure time: 96 h  
 Test Type: static test  
 Test substance: Fresh water  
 Method: OECD Test Guideline 203
- Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): 3.7 mg/l  
 Exposure time: 48 h  
 Test Type: semi-static test  
 Test substance: Fresh water  
 Method: OECD Test Guideline 202
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): >= 10 mg/l  
 Exposure time: 21 d  
 Test Type: semi-static test  
 Test substance: Fresh water  
 Method: OECD Test Guideline 211
- Toxicity to microorganisms : EC50 (activated sludge): > 100 mg/l  
 Exposure time: 3 h  
 Test Type: static test  
 Test substance: Fresh water  
 Method: OECD Test Guideline 209
- Toxicity to soil dwelling organisms : NOEC (Eisenia fetida (earthworms)): >= 1,000 mg/kg  
 Exposure time: 336 h  
 Method: OECD Test Guideline 207

**Ecotoxicology Assessment**

- Acute aquatic toxicity : Toxic to aquatic life.

**triethyl phosphate:**

- Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 100 mg/l  
 Exposure time: 96 h  
 Test Type: static test  
 Test substance: Fresh water
- Toxicity to daphnia and other aquatic invertebrates : LC50: > 100 mg/l  
 Exposure time: 96 h  
 Test Type: static test  
 Test substance: Fresh water
- Toxicity to algae/aquatic plants : EC50 (Desmodesmus subspicatus (green algae)): 901 mg/l  
 Exposure time: 72 h  
 Test Type: static test  
 Test substance: Fresh water
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 31.6 mg/l  
 Exposure time: 21 d  
 Test substance: Fresh water  
 Method: OECD Test Guideline 211
- Toxicity to microorganisms : (Pseudomonas putida): 2,985 mg/l  
 Exposure time: 0.5 h  
 Test Type: static test

## SAFETY DATA SHEET

**HUNTSMAN**

Enriching lives through innovation

## ARATHANE® 5753 A

Version 3.0      Revision Date: 05/02/2022      SDS Number: 400001009994      Date of last issue: 08/26/2020  
 Date of first issue: 12/09/2015

Print Date 05/03/2022

Test substance: Fresh water

**Persistence and degradability****Components:****4,4'-methylenediphenyl diisocyanate:**

Biodegradability : aerobic  
 Inoculum: activated sludge, non-adapted  
 Result: Not readily biodegradable.  
 Biodegradation: 0 %  
 Exposure time: 28 d  
 Method: OECD Test Guideline 301F  
 Test substance: Fresh water

Stability in water : Degradation half life (DT50): 20 hrs (25 °C)  
 Remarks: Fresh water

**Benzene, 1,1'-methylenebis[isocyanato-, homopolymer:**

Biodegradability : Inoculum: Domestic sewage  
 Concentration: 30 mg/l  
 Result: Not biodegradable  
 Biodegradation: 0 %  
 Exposure time: 28 d  
 Method: Inherent Biodegradability: Modified MITI Test (II)

**2,4'-methylenediphenyl diisocyanate:**

Biodegradability : Inoculum: Domestic sewage  
 Concentration: 30 mg/l  
 Result: Not biodegradable  
 Biodegradation: 0 %  
 Exposure time: 28 d  
 Method: Inherent Biodegradability: Modified MITI Test (II)

**triethyl phosphate:**

Biodegradability : Inoculum: activated sludge  
 Result: Not readily biodegradable.  
 Biodegradation: 0 %  
 Exposure time: 28 d  
 Method: OECD Test Guideline 301C

Inoculum: activated sludge  
 Result: Inherently biodegradable.  
 Biodegradation: 98 %  
 Exposure time: 28 d  
 Method: OECD Test Guideline 302B

Stability in water : Degradation half life (DT50): 5.5 yr (25 °C) pH: 7

## SAFETY DATA SHEET

**HUNTSMAN**

Enriching lives through innovation

## ARATHANE® 5753 A

Version 3.0      Revision Date: 05/02/2022      SDS Number: 400001009994      Date of last issue: 08/26/2020  
 Date of first issue: 12/09/2015

Print Date 05/03/2022

Remarks: Fresh water

**Bioaccumulative potential****Components:****4,4'-methylenediphenyl diisocyanate:**

Bioaccumulation : Species: Cyprinus carpio (Carp)  
 Bioconcentration factor (BCF): 200  
 Exposure time: 28 d  
 Concentration: 0.08 µg/l  
 Method: OECD Test Guideline 305  
 Remarks: Bioaccumulation is unlikely.

Partition coefficient: n-octanol/water : log Pow: 4.51 (72 °F / 22 °C)  
 pH: 7  
 Method: OECD Test Guideline 117

**Benzene, 1,1'-methylenebis[isocyanato-, homopolymer:**

Bioaccumulation : Species: Cyprinus carpio (Carp)  
 Bioconcentration factor (BCF): 200  
 Remarks: Bioaccumulation is unlikely.

Partition coefficient: n-octanol/water : log Pow: 8.56 (68 °F / 20 °C)

**2,4'-methylenediphenyl diisocyanate:**

Bioaccumulation : Species: Cyprinus carpio (Carp)  
 Bioconcentration factor (BCF): 200  
 Remarks: Bioaccumulation is unlikely.

Partition coefficient: n-octanol/water : log Pow: 4.51 (68 °F / 20 °C)  
 pH: 7  
 Method: OECD Test Guideline 117

**triethyl phosphate:**

Bioaccumulation : Species: Cyprinus carpio (Carp)  
 Bioconcentration factor (BCF): 0.5 - 0.8  
 Exposure time: 42 d  
 Test substance: Fresh water  
 Method: semi-static test

Partition coefficient: n-octanol/water : log Pow: 1.11  
 Method: Partition coefficient

**Mobility in soil****Components:****4,4'-methylenediphenyl diisocyanate:**

Distribution among environmental compartments : log Koc: 4.5  
 Method: QSAR

Stability in soil : Soil temperature: 72 °F / 22 °C

## SAFETY DATA SHEET

**HUNTSMAN**

Enriching lives through innovation

## ARATHANE® 5753 A

Version: 3.0    Revision Date: 05/02/2022    SDS Number: 400001009994    Date of last issue: 08/26/2020  
 Date of first issue: 12/09/2015

Print Date 05/03/2022

Dissipation time: 24 h  
 Method: OECD Test Guideline 307

**Other adverse effects****Product:**

Ozone-Depletion Potential : Regulation: 40 CFR Protection of Environment; Part 82  
 Protection of Stratospheric Ozone - CAA Section 602 Class I  
 Substances  
 Remarks: This product neither contains, nor was  
 manufactured with a Class I or Class II ODS as defined by the  
 U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A +  
 B).

Additional ecological information : No data available

## SECTION 13. DISPOSAL CONSIDERATIONS

**Disposal methods**

Waste from residues : Do not dispose of waste into sewer.  
 Do not contaminate ponds, waterways or ditches with  
 chemical or used container.  
 Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.  
 Dispose of as unused product.  
 Do not re-use empty containers.

## SECTION 14. TRANSPORT INFORMATION

**International Regulations****UNRTDG**

Not regulated as dangerous goods

**IATA-DGR**

Not regulated as dangerous goods

**IMDG-Code**

Not regulated as dangerous goods

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

Not applicable for product as supplied.

**National Regulations****49 CFR**

UN/ID/NA number : NA 3082  
 Proper shipping name : Other regulated substances, liquid, n.o.s.  
 (Methylene Diphenyl Diisocyanate)  
 Class : 9  
 Packing group : III  
 Labels : CLASS 9  
 ERG Code : 171

## SAFETY DATA SHEET

**HUNTSMAN**

Enriching lives through innovation

## ARATHANE® 5753 A

Version: 3.0    Revision Date: 05/02/2022    SDS Number: 400001009994    Date of last issue: 08/26/2020  
 Date of first issue: 12/09/2015

Print Date 05/03/2022

Marine pollutant : no

**Special precautions for user**

Remarks : 49CFR: no dangerous good in non-bulk packaging

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, packagesizes, and variations in regional or country regulations.

## SECTION 15. REGULATORY INFORMATION

**CERCLA Reportable Quantity**

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
4,4'-methylenediphenyl diisocyanate.	101-68-8	5000	7575

**SARA 311/312 Hazards** : Acute toxicity (any route of exposure)  
 Respiratory or skin sensitisation  
 Skin corrosion or irritation  
 Serious eye damage or eye irritation  
 Specific target organ toxicity (single or repeated exposure)

**SARA 313** : The following components are subject to reporting levels established by SARA Title III, Section 313:

4,4'-methylenediphenyl diisocyanate    101-68-8    >= 50 - < 70 %

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 112 (40 CFR 61):

4,4'-methylenediphenyl diisocyanate    101-68-8

**California Prop. 65**

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

**The components of this product are reported in the following inventories:**

DSL : All components of this product are on the Canadian DSL

AIRC : On the inventory, or in compliance with the inventory

NZIoC : On the inventory, or in compliance with the inventory

ENCS : On the inventory, or in compliance with the inventory

KECI : On the inventory, or in compliance with the inventory

PICCS : On the inventory, or in compliance with the inventory

IECSC : On the inventory, or in compliance with the inventory

## SAFETY DATA SHEET

**HUNTSMAN**

Enriching lives through innovation

## ARATHANE® 5753 A

Version 3.0      Revision Date: 05/02/2022      SDS Number: 400001009994      Date of last issue: 08/26/2020  
 Date of first issue: 12/09/2015

Print Date 05/03/2022

TCSI : On the inventory, or in compliance with the inventory

TSCA : All substances listed as active on the TSCA inventory

**Inventories**


AIIIC (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECl (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TECl (Thailand), TSCA (USA)

**TSCA - 5(a) Significant New Use Rule List of Chemicals**

No substances are subject to a Significant New Use Rule.

**US. Toxic Substances Control Act (TSCA) Section 12(b) Export Notification (40 CFR 707, Subpt D)**

No substances are subject to TSCA 12(b) export notification requirements.

**SECTION 16. OTHER INFORMATION****Further information****NFPA 704:****HMIS® IV:**

<b>HEALTH</b>	* 2
<b>FLAMMABILITY</b>	1
<b>PHYSICAL HAZARD</b>	0

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "\*" represents a chronic hazard, while the "0" represents the absence of a chronic hazard

Liquid decontaminants (percentages by weight or volume) :

Decontaminant 1 : \* sodium carbonate : 5 - 10 % \* liquid detergent : 0.2 - 2 % \* water : to make up to 100 %

Decontaminant 2 : \* concentrated ammonia solution : 3 - 8 % \* liquid detergent : 0.2 - 2 % \* water : to make up to 100 %

Decontaminant 1 reacts slower with diisocyanates but is more environmentally friendly than decontaminant 2.

Decontaminant 2 contains ammonia. Ammonia presents health hazards. (See supplier safety information.)

Revision Date : 05/02/2022

ACGIH : USA. ACGIH Threshold Limit Values (TLV)  
 NIOSH REL : USA. NIOSH Recommended Exposure Limits  
 OSHA P0 : USA. Table Z-1-A Limits for Air Contaminants (1989 vacated values)

## SAFETY DATA SHEET

**HUNTSMAN**

Enriching lives through innovation

## ARATHANE® 5753 A

Version 3.0      Revision Date: 05/02/2022      SDS Number: 400001009994      Date of last issue: 08/26/2020  
 Date of first issue: 12/09/2015

Print Date 05/03/2022

OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1  
 Limits for Air Contaminants  
 ACGIH / TWA : 8-hour, time-weighted average  
 NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour  
 workday during a 40-hour workweek  
 NIOSH REL / C : Ceiling value not be exceeded at any time.  
 OSHA P0 / C : Ceiling limit  
 OSHA Z-1 / C : Ceiling

The information and recommendations in this publication are to the best of our knowledge, information and belief accurate at the date of publication, NOTHING HEREIN IS TO BE CONSTRUED AS A WARRANTY, EXPRESS OR OTHERWISE.

IN ALL CASES, IT IS THE RESPONSIBILITY OF THE USER TO DETERMINE THE APPLICABILITY OF SUCH INFORMATION AND RECOMMENDATIONS AND THE SUITABILITY OF ANY PRODUCT FOR ITS OWN PARTICULAR PURPOSE.

THE PRODUCT MAY PRESENT HAZARDS AND SHOULD BE USED WITH CAUTION. WHILE CERTAIN HAZARDS ARE DESCRIBED IN THIS PUBLICATION, NO GUARANTEE IS MADE THAT THESE ARE THE ONLY HAZARDS THAT EXIST.

Hazards, toxicity and behaviour of the products may differ when used with other materials and are dependent upon the manufacturing circumstances or other processes. Such hazards, toxicity and behaviour should be determined by the user and made known to handlers, processors and end users.

The trademarks above are the property of Huntsman Corporation or an affiliate thereof.

NO PERSON OR ORGANIZATION EXCEPT A DULY AUTHORIZED HUNTSMAN EMPLOYEE IS AUTHORIZED TO PROVIDE OR MAKE AVAILABLE DATA SHEETS FOR HUNTSMAN PRODUCTS. DATA SHEETS FROM UNAUTHORIZED SOURCES MAY CONTAIN INFORMATION THAT IS NO LONGER CURRENT OR ACCURATE.

## SAFETY DATA SHEET



## ARATHANE® 5753 B(LV)

Version 2.2    Revision Date: 05/02/2022    SDS Number: 400001010201    Date of last issue: 04/25/2022  
 Date of first issue: 12/16/2016

Print Date 05/17/2022

## SECTION 1. IDENTIFICATION

Product name : ARATHANE® 5753 B(LV)

## Manufacturer or supplier's details

Company name of supplier : Huntsman Advanced Materials Americas LLC  
 Address : P.O. Box 4980  
 The Woodlands,  
 TX 77387  
 United States of America (USA)

Telephone : Non-Emergency: (800) 257-5547

E-mail address of person responsible for the SDS : Global\_Product\_EHS\_AdMat@huntsman.com

Emergency telephone number : Chemtrec: (800) 424-9300 or (703) 527-3887

## Recommended use of the chemical and restrictions on use

Recommended use : Component used for the manufacture of electrical insulation parts

## SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Serious eye damage : Category 1

## GHS label elements

Hazard pictograms :



Signal word : Danger

Hazard statements : H318 Causes serious eye damage.

Precautionary statements : **Prevention:**  
 P280 Wear eye protection/ face protection.  
**Response:**  
 P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.  
**Storage:**  
 Not available  
**Disposal:**  
 Not available

## SAFETY DATA SHEET



## ARATHANE® 5753 B(LV)

Version 2.2    Revision Date: 05/02/2022    SDS Number: 400001010201    Date of last issue: 04/25/2022  
 Date of first issue: 12/16/2016

Print Date 05/17/2022

Other hazards  
None known.

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

## Hazardous components

Chemical name	CAS-No.	Concentration (% w/w)
1,1'-phenyliminodipropan-2-ol	3077-13-2	5 - 10

The specific chemical identity and/or exact percentage (concentration) of composition may be withheld as a trade secret.

## SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.  
 Consult a physician.  
 Show this safety data sheet to the doctor in attendance.  
 Treat symptomatically.  
 Get medical attention if symptoms occur.
- If inhaled : If inhaled, remove to fresh air.  
 Get medical attention if symptoms occur.
- In case of skin contact : Wash with water and soap as a precaution.
- In case of eye contact : Small amounts splashed into eyes can cause irreversible tissue damage and blindness.  
 In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.  
 Continue rinsing eyes during transport to hospital.  
 Remove contact lenses.  
 Keep eye wide open while rinsing.  
 If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.  
 Never give anything by mouth to an unconscious person.  
 If symptoms persist, call a physician.  
 Take victim immediately to hospital.
- Most important symptoms and effects, both acute and delayed : None known.
- Protection of first-aiders : First Aid responders should pay attention to self-protection and use the recommended protective clothing  
 If potential for exposure exists refer to Section 8 for specific personal protective equipment.  
 No action shall be taken involving any personal risk or without

## SAFETY DATA SHEET



## ARATHANE® 5753 B(LV)

Version 2.2      Revision Date: 05/02/2022      SDS Number: 400001010201      Date of last issue: 04/25/2022  
 Date of first issue: 12/16/2016

Print Date 05/17/2022

Notes to physician : suitable training.  
 : Treat symptomatically.

## SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Water spray  
 Alcohol-resistant foam  
 Carbon dioxide (CO<sub>2</sub>)  
 Dry chemical

Unsuitable extinguishing media : Exercise caution when using a high volume water jet as it may scatter and spread fire

Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : No hazardous combustion products are known

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
 Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

## SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.  
 Refer to protective measures listed in sections 7 and 8.

Environmental precautions : Prevent product from entering drains.  
 Prevent further leakage or spillage if safe to do so.  
 If the product contaminates rivers and lakes or drains inform respective authorities.

Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).  
 Keep in suitable, closed containers for disposal.

## SECTION 7. HANDLING AND STORAGE

Advice on protection against : Normal measures for preventive fire protection.

SDS\_US-AM – EN – 400001010201

3 / 11

## SAFETY DATA SHEET



## ARATHANE® 5753 B(LV)

Version 2.2      Revision Date: 05/02/2022      SDS Number: 400001010201      Date of last issue: 04/25/2022  
 Date of first issue: 12/16/2016

Print Date 05/17/2022

fire and explosion

Advice on safe handling : Do not breathe vapours/dust.  
 Avoid contact with skin and eyes.  
 For personal protection see section 8.  
 Smoking, eating and drinking should be prohibited in the application area.  
 To avoid spills during handling keep bottle on a metal tray.  
 Dispose of rinse water in accordance with local and national regulations.

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.  
 Keep in properly labelled containers.

Materials to avoid : For incompatible materials please refer to Section 10 of this SDS.

Recommended storage temperature : 64 - 104 °F / 18 - 40 °C

Further information on storage stability : Stable under normal conditions.

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

## Components with workplace control parameters

Contains no substances with occupational exposure limit values.

## Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines  
 Recommended Filter type:  
 Combined particulates and organic vapour type

Filter type : Filter type A-P

Hand protection  
 Material : butyl-rubber  
 Break through time : > 8 h

Material : Nitrile rubber  
 Break through time : 10 - 480 min

Material : Solvent-resistant gloves (butyl-rubber)

Remarks : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.  
 The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection : Eye wash bottle with pure water

SDS\_US-AM – EN – 400001010201

4 / 11

## SAFETY DATA SHEET



## ARATHANE® 5753 B(LV)

Version 2.2    Revision Date: 05/02/2022    SDS Number: 400001010201    Date of last issue: 04/25/2022  
 Date of first issue: 12/16/2016

Print Date 05/17/2022

Tightly fitting safety goggles  
 Wear face-shield and protective suit for abnormal processing problems.

Skin and body protection : Impervious clothing  
 Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Hygiene measures : When using do not eat or drink.  
 When using do not smoke.  
 Wash hands before breaks and at the end of workday.

## SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Colour : amber

Odour : hydrocarbon-like

Odour Threshold : No data is available on the product itself.

pH : No data is available on the product itself.

Melting point/freezing point : No data available

Boiling point/boiling range : No data available

Flash point : 450 °F / 232 °C  
 Method: Pensky-Martens closed cup

Evaporation rate : < 1

Flammability (solid, gas) : No data is available on the product itself.

Flammability (liquids) : No data is available on the product itself.

Upper explosion limit / Upper flammability limit : No data is available on the product itself.

Lower explosion limit / Lower flammability limit : No data is available on the product itself.

Vapour pressure : < 1.333 hPa (68 °F / 20 °C)

Relative vapour density : 1

Relative density : 1.05

Density : No data is available on the product itself.

Solubility(ies)  
 Water solubility : partly soluble

## SAFETY DATA SHEET



## ARATHANE® 5753 B(LV)

Version 2.2    Revision Date: 05/02/2022    SDS Number: 400001010201    Date of last issue: 04/25/2022  
 Date of first issue: 12/16/2016

Print Date 05/17/2022

Solubility in other solvents : No data is available on the product itself.

Partition coefficient: n-octanol/water : No data is available on the product itself.

Auto-ignition temperature : No data is available on the product itself.

Decomposition temperature : No data is available on the product itself.

Self-Accelerating decomposition temperature (SADT) : No data is available on the product itself.

Viscosity  
 Viscosity, dynamic : 8,500 mPa.s

Explosive properties : No data is available on the product itself.

Oxidizing properties : No data is available on the product itself.

Molecular weight : No data available

Particle size : No data is available on the product itself.

## SECTION 10. STABILITY AND REACTIVITY

Reactivity : No dangerous reaction known under conditions of normal use.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reactions : No hazards to be specially mentioned.

Conditions to avoid : None known.

Incompatible materials : None known.

Hazardous decomposition products : No decomposition if stored and applied as directed.

## SECTION 11. TOXICOLOGICAL INFORMATION

## Acute toxicity

## Components:

## 1,1'-phenylimino-dipropan-2-ol:

Acute oral toxicity : LD50 (Rat): 3,800 mg/kg  
 Assessment: The substance or mixture has no acute oral toxicity

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg  
 Assessment: The substance or mixture has no acute dermal toxicity

## SAFETY DATA SHEET



## ARATHANE® 5753 B(LV)

Version 2.2    Revision Date: 05/02/2022    SDS Number: 400001010201    Date of last issue: 04/25/2022  
 Date of first issue: 12/16/2016

Print Date 05/17/2022

## Skin corrosion/irritation

Components:

## 1,1'-phenyliminodipropan-2-ol:

Result : Mild skin irritation

## Serious eye damage/eye irritation

Components:

## 1,1'-phenyliminodipropan-2-ol:

Result : Risk of serious damage to eyes.

## Respiratory or skin sensitisation

No data available

## Germ cell mutagenicity

No data available

## Carcinogenicity

IARC No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

## Reproductive toxicity

No data available

## STOT - single exposure

No data available

## STOT - repeated exposure

No data available

## Repeated dose toxicity

No data available

## Aspiration toxicity

No data available

## Experience with human exposure

No data available

## Toxicology, Metabolism, Distribution

No data available

## Neurological effects

No data available

## Further information

No data available

## SAFETY DATA SHEET



## ARATHANE® 5753 B(LV)

Version 2.2    Revision Date: 05/02/2022    SDS Number: 400001010201    Date of last issue: 04/25/2022  
 Date of first issue: 12/16/2016

Print Date 05/17/2022

## SECTION 12. ECOLOGICAL INFORMATION

## Ecotoxicity

No data available

## Persistence and degradability

No data available

## Bioaccumulative potential

No data available

## Mobility in soil

No data available

## Other adverse effects

Product:

Ozone-Depletion Potential : Regulation: 40 CFR Protection of Environment; Part 82  
 Protection of Stratospheric Ozone - CAA Section 602 Class I  
 Substances  
 Remarks: This product neither contains, nor was  
 manufactured with a Class I or Class II ODS as defined by the  
 U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A +  
 B).

## SECTION 13. DISPOSAL CONSIDERATIONS

## Disposal methods

Waste from residues : Dispose of contents and container in accordance with all local,  
 regional, national and international regulations.  
 Do not dispose of waste into sewer.  
 Do not contaminate ponds, waterways or ditches with  
 chemical or used container.

Contaminated packaging : Empty remaining contents.  
 Dispose of as unused product.  
 Do not re-use empty containers.

## SECTION 14. TRANSPORT INFORMATION

## International Regulations

## UNRTDG

Not regulated as dangerous goods

## IATA-DGR

Not regulated as dangerous goods

## IMDG-Code

Not regulated as dangerous goods

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

## National Regulations

## SAFETY DATA SHEET



## ARATHANE® 5753 B(LV)

Version 2.2    Revision Date: 05/02/2022    SDS Number: 400001010201    Date of last issue: 04/25/2022  
 Date of first issue: 12/16/2016

Print Date 05/17/2022

**49 CFR**  
 UN/ID/NA number : NA 3082  
 Proper shipping name : Other regulated substances, liquid, n.o.s.  
 (XYLENE)  
 Class : 9  
 Packing group : III  
 Labels : CLASS 9  
 ERG Code : 171  
 Marine pollutant : no

**Special precautions for user**  
 Remarks : 49CFR: no dangerous good in non-bulk packaging

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

## SECTION 15. REGULATORY INFORMATION

## CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
xylenes	1330-20-7	100	43956

**SARA 311/312 Hazards** : Serious eye damage or eye irritation

**SARA 313** : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

## California Prop. 65

**WARNING:** This product can expose you to chemicals including 4-vinylcyclohexene, buta-1,3-diene, which is/are known to the State of California to cause cancer, and 4-vinylcyclohexene, buta-1,3-diene, methanol, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

## The components of this product are reported in the following inventories:

DSL : All components of this product are on the Canadian DSL  
 AIIIC : On the inventory, or in compliance with the inventory  
 NZIoC : On the inventory, or in compliance with the inventory  
 ENCS : On the inventory, or in compliance with the inventory  
 KECI : On the inventory, or in compliance with the inventory  
 PICCS : On the inventory, or in compliance with the inventory

SDS\_US-AM – EN – 400001010201

9 / 11

## SAFETY DATA SHEET



## ARATHANE® 5753 B(LV)

Version 2.2    Revision Date: 05/02/2022    SDS Number: 400001010201    Date of last issue: 04/25/2022  
 Date of first issue: 12/16/2016

Print Date 05/17/2022

IECSC : On the inventory, or in compliance with the inventory  
 TCSI : On the inventory, or in compliance with the inventory  
 TSCA : All substances listed as active on the TSCA inventory

## Inventories

AIIIC (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TECI (Thailand), TSCA (USA)

**TSCA - 5(a) Significant New Use Rule List of Chemicals**  
 No substances are subject to a Significant New Use Rule.


**US. Toxic Substances Control Act (TSCA) Section 12(b) Export Notification (40 CFR 707, Subpt D)**

No substances are subject to TSCA 12(b) export notification requirements.

## SECTION 16. OTHER INFORMATION

## Further Information

## NFPA 704:



## HMIS® IV:

HEALTH	3
FLAMMABILITY	1
PHYSICAL HAZARD	0

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "3" represents a chronic hazard, while the "0" represents the absence of a chronic hazard.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Sources of key data used to compile the Safety Data Sheet : Information taken from reference works and the literature, Information derived from practical experience.

Revision Date : 05/02/2022

SDS\_US-AM – EN – 400001010201

10 / 11

SAFETY DATA SHEET

**HUNTSMAN**

Enriching lives through innovation

**ARATHANE® 5753 B(LV)**

Version	Revision Date:	SDS Number:	Date of last issue: 04/25/2022
2.2	05/02/2022	400001010201	Date of first issue: 12/16/2016

Print Date 05/17/2022

The information and recommendations in this publication are to the best of our knowledge, information and belief accurate at the date of publication, NOTHING HEREIN IS TO BE CONSTRUED AS A WARRANTY, EXPRESS OR OTHERWISE.

IN ALL CASES, IT IS THE RESPONSIBILITY OF THE USER TO DETERMINE THE APPLICABILITY OF SUCH INFORMATION AND RECOMMENDATIONS AND THE SUITABILITY OF ANY PRODUCT FOR ITS OWN PARTICULAR PURPOSE.

THE PRODUCT MAY PRESENT HAZARDS AND SHOULD BE USED WITH CAUTION. WHILE CERTAIN HAZARDS ARE DESCRIBED IN THIS PUBLICATION, NO GUARANTEE IS MADE THAT THESE ARE THE ONLY HAZARDS THAT EXIST.

Hazards, toxicity and behaviour of the products may differ when used with other materials and are dependent upon the manufacturing circumstances or other processes. Such hazards, toxicity and behaviour should be determined by the user and made known to handlers, processors and end users.

The trademarks above are the property of Huntsman Corporation or an affiliate thereof.

NO PERSON OR ORGANIZATION EXCEPT A DULY AUTHORIZED HUNTSMAN EMPLOYEE IS AUTHORIZED TO PROVIDE OR MAKE AVAILABLE DATA SHEETS FOR HUNTSMAN PRODUCTS. DATA SHEETS FROM UNAUTHORIZED SOURCES MAY CONTAIN INFORMATION THAT IS NO LONGER CURRENT OR ACCURATE.