Revision Date: 8/31/2021 Revision Number: 001.14



1. PRODUCT AND COMPANY INFORMATION				
Product Name:	High Temperature Anti Seize- Contains Lead	Item number(s):	27-01, 27-02, 27-03, 27-06, 27-07, 27-08	
	MIL907 (Formerly qualified to MIL-PRF-907 Rev. F – Rev. F is inactive) Armite's MIL907 is NOT qualified to MIL- PRF-907 Rev. H	NSN(s)	8030-00-059-2761, 8030-00-251-3980, 8030-01-607-8134, 8030-00-597-5367, 8030-00-286-5453	
Product Type:	Anti-Seize Compound	Region(s):	U.S.A	
Company Address:	Armite Laboratories Inc.	Telephone:	720-262-5480	
	dba Armite Lubricants 1218 Commerce Court Suite B Lafayette, CO 80026	Product Emergency:	CHEM-TEL 800-225-3924	

	2. HAZARD IDENTIFICATION			
Signal Word	Hazard Class	Hazard Category	Hazard Pictograms	
DANGER	Acute Toxicity (oral) Acute Toxicity (inhalation as mist) Carcinogenicity STOT RE (Specific Target Organ Toxicity - Repeated Exposure) Aquatic Acute Aquatic Chronic	4 4 1B 1 1 1		
		1 1 1A		

### Hazard Statements (GHS-US)

May cause cancer. May damage fertility or the unborn child. Causes damage to organs through prolonged or repeated exposure. Very toxic to aquatic life. Very toxic to aquatic life with long lasting effects. Harmful if swallowed or inhaled.

### Precautionary Statements (GHS-US)

Prevention: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wash hands thoroughly after handling. Do not eat, drink, or smoke when using this product. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face protection. Keep out of reach of children. Response: IF SWALLOWED, INHALED, EXPOSED or CONCERNED: Get medical advice/attention. Call a POISON CENTER, doctor/physician, or get medical attention if you feel unwell. Collect spillage. Hazardous to the aquatic environment. Protect from sunlight. Store in a well-ventilated place. Store locked up. Storage: Disposal: Dispose of contents/container to hazardous material waste-site according to local, regional, national, federal & international regulations. Other Hazards: Other hazards not contributing to the classification: Exposure may aggravate those with pre-existing eye,

ther Hazards: Other hazards not contributing to the classification: Exposure may aggravate those with pre-existing eye, skin, or respiratory conditions. **ATTENTION! –Contains Lead**. Exposure may aggravate individuals with pre-existing skin, kidney, liver, and pulmonary disorders.

Revision Date: 8/31/2021 Revision Number: 001.14



Unknown Acute Toxicity (GHS-US): Not available

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200 and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of chemicals (GHS).

### 3. COMPOSITION / INFORMATION ON INGREDIENTS

Component(s)	CAS Number	Percentage*
Lead Powder	7439-92-1	68-72%
Petroleum Hydrocarbons (Highly Refined Mineral Oil (C15-C50)	Mixture (53%) 64742-58-1 (47%) 64742-01-4	*
Highly Refined Mineral Oil & Additives (containing <3% (w/w) DSMO-extract, according to IP346	Mixture	*
Microcrystalline Wax	63231-60-7	*

\*Exact percentage is a trade secret, concentration range is provided to assist user in providing appropriate protections.

### 4. FIRST AID MEASURES

**General:** Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

**Inhalation:** When symptoms occur: go into open air and ventilate area. Obtain medical attention if breathing difficulty persists.

**Skin contact:** Wash thoroughly with soap & water after exposure. Launder contaminated clothing. Obtain medical attention if irritation persists.

**Eye contact:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue Rinsing. Obtain medical attention is irritation persists.

**Ingestion:** Rinse mouth. Do not induce vomiting. Seek medical attention if large amount is swallowed. If vomiting occurs spontaneously keep head below hips to prevent aspiration seek medical attention.

### Symptoms: Most Important Symptoms ad Effects Both Chronic and Delayed

**General:** May cause cancer. May damage fertility. May damage the unborn child. Causes damage to organs through prolonged or repeated exposure. Harmful if swallowed. Harmful if inhaled.

**Inhalation**: Harmful if inhaled. Respiratory tract irritation. If material enters lungs, signs & symptoms may include coughing, wheezing, chocking, difficulty in breathing, chest congestion, shortness of breath, and/or fever.

Skin Contact: May cause skin irritation.

Eye contact: May cause mechanical irritation if gets into eyes.

Ingestion: Harmful if swallowed. May cause nausea, vomiting, and diarrhea.

<u>Chronic Symptoms</u>: ATTENTION! CONTAINS LEAD. Lead: Exposure can result in lassitude (weakness, exhaustion). Insomnia; facial pallor; anorexia, weight loss, malnutrition; constipation, abdominal pain, colic; anemia; gingival lead line; tremor; encephalopathy; kidney disease; hypertension. Prolonged exposure may cause effects in specific organs such as the liver, kidneys, blood and nervous system.

### Indications of Any Immediate Medical Attention and Special Treatment Needed:

If exposed or concerned get medical advice and attention.



### 5. FIRE FIGHTING MEASURES

Suitable extinguishing media: Treat as oil fire: Water spray (fog), foam, dry chemical or carbon dioxide.

Unsuitable extinguishing media: Do not use water jet as oil will float on water and can spread fire.

Unusual fire or explosion hazard: Closed container may explode when exposed to extreme heat.

Hazardous combustion products: Oxides of lead and carbon.

**Protective equipment:** Self contained breathing apparatus and protective clothing.

### 6. ACCIDENTAL RELEASE MEASURES

**General Measures:** Keep away from heat/spark/open flames/hot surfaces. NO Smoking. Handle in accordance with good industrial hygiene and safety practice. Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

**Environmental precautions:** Prevent further leakage or spillage if safe to do so. Do not allow product to enter sewer or public waters. Do not allow to enter drains or water courses.

**Clean-up method**: Contaminated surfaces will be extremely slippery. Scrape up as much material as possible. Use absorbent material to clean up spill as much as possible. Do not dispose of material in trash. Follow local regulations to dispose of hazardous waste safely.

### 7. HANDLING AND STORAGE

**Handling:** Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist. Wash thoroughly after handling. Keep container closed. Do not cut weld or reuse containers. WARNING! Contains Lead.

**Storage**: Keep container tightly closed in a cool, well ventilated area. Incompatible materials: Strong oxidizers, strong acids & bases.

### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Recommendation(s): Protective gloves for hypersensitive persons. Protective goggles or face shield when working with moving parts.

Hazardous Component(s)	ACGIH TLV OSHA PEL	
Lead	0.05 mg/m3 TWA as (Pb)	50µg/m3 (TWA)
Petroleum Hydrocarbons	TVL 5mg/m3 (oil Mist) 8 hr day	Not available
Industrial Grease (Oil mist mineral)	5mg/m3 TWA (Inhalable fraction)	PEL 5mg/m3 (mist) TWA 5mg/m3 (mist)

### Exposure Controls

### Appropriate Engineering Controls:

Ensure all national /local regulations are observed. Use explosion proof equipment. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposures. Ensure adequate ventilation, especially in confined areas.

Revision Date: 8/31/2021 Revision Number: 001.14



### PERSONAL PROTECTIVE EQUIPMENT:

Hand Protection: Wear chemically resistant protective gloves.

Eye Protection: Chemical goggles or safety glasses.

Skin & Body Protection: Wear suitable protective clothing.

(>400° F)

Respirator Protection: Use NIOSH-approved air purifying or supplied-air respirator where airborne concentrations (oil mist/dust) are expected to exceed exposure limits.

Physical state:	Paste
Color :	Dark Grey
Odor:	Mild petroleum
Odor threshold:	Not available
pH:	Not available
Melting point /range:	54.4°C (130°F)
Boiling point / range:	>204° C (>400°
Flash point:	Undetermined
Flammable/Explosive	limits
Lower limits:	Not available
Upper limits:	Not available

### 9. PHYSICAL AND CHEMICAL PROPERTIES

Vapor Pressure: Vapor density: **Relative Density:** Solubility(ies): VOC content: Specific gravity: Viscosity: Auto-ignition temp: Evaporation rate: Partition coefficient: n-octanol/water:

Not available Not Determined Not Determined Insoluble in water Essential nil 1.93 Not available Not determined Not available

Not determined

10. STABILITY AD REACTIVITY			
Stability:	Stable under normal conditions.		
Reactivity:	Not available.		
Conditions to avoid: Direct sunlight. Heat sources such as direct flame.			
Hazardous polymerization: Will not occur.			
Incompatible materials:	Strong oxidizing agents. Hydrogen peroxide. Strong acids & strong bases.		
Hazardous decomposition products:	Oxides of lead & carbon. At temperatures above melting point, lead fumes may be evolved.		

#### **11. TOXICOLOGICAL INFORMATION**

Relevant routes of exposure: Potential Health Effects/Symptoms	Skin, Eyes, Inhalation, Ingestion		
Inhalation:	Harmful if inhaled. Inhalation of vapors from heated material may cause irritation.		
Skin contact:	May cause skin irritation.		
Eye contact:	May cause mechanical eye irritation.		
Ingestion:	Harmful if swallowed. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.		

Chronic Symptoms (LEAD): Exposure can result in weakness, exhaustion, insomnia, facial pallor; anorexia, weight loss, malnutrition; constipation, abdominal pain, colic; anemia; gingival lead line; tremor; encephalopathy; kidney disease; hypertension. Prolonged exposure may cause effects in specific organs such as: liver, kidneys, blood, and nervous systems.

Revision Date: 8/31/2021 Revision Number: 001.14



Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Effects
Lead	ATE (oral) 500.00mg/kg body wt. ATE (dust, mist) 1.500 mg/l/4h	Reproductivity-may damage fertility or the unborn child Target Organ- Kidney, Blood, Liver & nervous system, gingival tissue. Developmental Toxicity
Petroleum Hydrocarbons	Acute oral Rat LD50 >5g/kg body wt	Not available
Industrial Grease	(Oral) Rat >5000 mg/kg (Dermal) Rabbit >5000 mg/kg	None known

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Lead	Reasonably Anticipated Carcinogen	Group 2A	No
Petroleum Hydrocarbons	No	No	No
Industrial Grease Mixture	No	No	No

### **12. ECOLOGICAL INFORMATION**

**Toxicity Ecology** – General: Very toxic to aquatic life with long lasting effects.

Lead (7439-92-1) LC Fish 1 EC50 Daphnia 1 LC 50 Fish 2
0.44 mg/l (Exposure time: 96 h - Species: Cyprinus carpio [semi-static]) 600µg/l (Exposure time: 48 h – Species: water flea) 1.17mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [flow-through])

#### Persistence and Degradability

Lead Powder - May cause long-term adverse effects in the environment.

Bioaccumulation Potential: Contains components with the potential to bioaccumulate.

Mobility in Soil: Not available

Other Adverse Effects: Avoid release to the environment.

### **13. DISPOSAL CONSIDERATIONS**

Waste Disposal Recommendations: Recover and recycle whenever possible.

The materials contained in the product are hazardous to the environment, DO NOT release into the environment. Dispose of contents and container properly in accordance with all local, regional, national, provincial, territorial, and international regulations.

It is the responsibility of the waste generator to determine proper waste classification and disposal methods in compliance with applicable regulations.

Danger: Contains Lead!! DO NOT dispose of into the environment, in drains or in water courses.

Revision Date: 8/31/2021 Revision Number: 001.14



### **14. TRANSPORTATION INFORMATION**

(49 CFR ) DOT ORM D / LTD QTY (IMDG / IMO) Regulated (See below) (IATA / ICAO) Regulated (See below)\*\*

Additional Shipping information **UN number: 3077 Proper shipping name:** Environmentally hazardous substance, solid, n.o.s. (lead mixture) **Hazard class**: 9 **Packing group:** III

\*\*Under Special Provision A197: Not regulated for transport by air for per package net weight of 5 kg or less.

### **15. REGULATORY INFORMATION**

#### **United States Regulatory Information**

TSCA: Listed on the US TSCA (Toxic Substance Control Act) inventory.
SARA Section 302: None listed.
SARA Section 311/312: None Listed
SARA Section 313: Listed (lead)

California Proposition 65 Listings:

**Carcinogens List** – WARNING: This product contains chemicals known to the State of CA to cause cancer.

Developmental Toxicity – WARNING: This product contains chemicals known to the State of CA to cause birth defects.

**Reproductive Toxicity Female** – WARNING: This product contains chemicals known to the State of CA to cause (Female) reproductive harm.

**Reproductive Toxicity Male** – WARNING: This product contains chemicals known to the State of CA to cause (Male) reproductive harm.

### **16. OTHER INFORMATION**

This safety data sheet contains changes from the previous version in sections: New Safety Data Sheet format.

This SDS has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard CFR 1910.1200

Prepared by: Armite Laboratories Inc.

Original Issue date: April 1, 2015

**Disclaimer:** The information contained herein is believed to be reliable. However, Armite Laboratories does not assume responsibility for any results obtained by anyone over whose methods Armite has no control. It is the user's responsibility to determine the suitability of any of Armite's products or any production method mentioned herein for a particular use or purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any of Armite's products. As such, Armite Laboratories specifically disclaims all warranties or guarantees, expressed or implied, as to the suitability of a particular purpose, arising from the sales or use of any Armite product. Armite Laboratories Inc. further disclaims any liability for consequential or incidental damages of any, including loss of profits.