

### SECTION 1: Identification

#### 1.1. Identification

Product form : Mixture  
 Product name : Bioact™ 105 Precision Cleaner  
 Product code : PC105

#### 1.2. Recommended use and restrictions on use

Use of the substance/mixture : Cleaning/washing agents and additives  
 Restrictions on use : Product for industrial use only

#### 1.3. Supplier

Vantage Specialties, Inc.  
 3938 Porett Drive  
 Gurnee, IL 60031  
 USA  
 T +1 847-244-3410  
[msds.pm.us@vantagegrp.com](mailto:msds.pm.us@vantagegrp.com)

#### 1.4. Emergency telephone number

Emergency number : For Chemical Emergency Call CHEMTREC 24hr/day 7days/week  
 Within USA and Canada: 1-800-424-9300  
 Outside USA and Canada: 1-703-527-3887  
 (collect calls accepted)

### SECTION 2: Hazard(s) identification

#### 2.1. Classification of the substance or mixture

##### GHS US classification

Flammable liquids Category 3	H226	Flammable liquid and vapor
Skin corrosion/irritation Category 2	H315	Causes skin irritation
Serious eye damage/eye irritation Category 2A	H319	Causes serious eye irritation
Skin sensitization, Category 1	H317	May cause an allergic skin reaction
Aspiration hazard Category 1	H304	May be fatal if swallowed and enters airways
Hazardous to the aquatic environment – Chronic Hazard Category 2	H411	Toxic to aquatic life with long lasting effects

Full text of H statements : see section 16

#### 2.2. GHS Label elements, including precautionary statements

##### GHS US labeling

Hazard pictograms (GHS US) :



Signal word (GHS US) :

Danger

Hazard statements (GHS US) :

H226 - Flammable liquid and vapor  
 H304 - May be fatal if swallowed and enters airways  
 H315 - Causes skin irritation  
 H317 - May cause an allergic skin reaction  
 H319 - Causes serious eye irritation  
 H411 - Toxic to aquatic life with long lasting effects

# Bioact™ 105 Precision Cleaner

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Precautionary statements (GHS US) : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P233 - Keep container tightly closed.  
P240 - Ground/Bond container and receiving equipment.  
P241 - Use explosion-proof electrical/ventilating/lighting equipment.  
P242 - Use only non-sparking tools.  
P243 - Take precautionary measures against static discharge.

### 2.3. Other hazards which do not result in classification

No additional information available

### 2.4. Unknown acute toxicity (GHS US)

Not applicable

## SECTION 3: Composition/Information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%	GHS US classification
Naphtha (petroleum), hydrotreated heavy	CAS-No.: 64742-48-9	50 – 75	Flam. Liq. 3, H226 Asp. Tox. 1, H304
Propylene glycol propyl ether	CAS-No.: 1569-01-3	30 - 60	Flam. Liq. 3, H226 Eye Irrit. 2, H319
D-Limonene	CAS-No.: 5989-27-5	10 - 20	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

Full text of hazard classes and H-statements : see section 16

## SECTION 4: First-aid measures

### 4.1. Description of first aid measures

First-aid measures general : Call a physician immediately.  
First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.  
First-aid measures after skin contact : Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.  
First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.  
First-aid measures after ingestion : Do not induce vomiting. Call a physician immediately.

### 4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after skin contact : Irritation. May cause an allergic skin reaction.  
Symptoms/effects after eye contact : Eye irritation.  
Symptoms/effects after ingestion : Risk of lung edema.

### 4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

# Bioact™ 105 Precision Cleaner

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 5: Fire-fighting measures

#### 5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

#### 5.2. Specific hazards arising from the chemical

Fire hazard : Materials such as cleaning rags, paper wipes and protective clothing, which are contaminated with the product may spontaneously self-ignite some hours later. To avoid the risks of fires, all contaminated materials should be placed in a closed metal container soaked with water.  
Flammable liquid and vapor.

Hazardous decomposition products in case of fire : Carbon dioxide. Carbon monoxide.

#### 5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

##### 6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapors/spray.

##### 6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

#### 6.2. Environmental precautions

Avoid release to the environment.

#### 6.3. Methods and material for containment and cleaning up

For containment : Collect spillage.

Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.

Other information : Dispose of materials or solid residues at an authorized site.

#### 6.4. Reference to other sections

For further information refer to section 13.

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapors may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapors/spray.

Hygiene measures : Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

# Bioact™ 105 Precision Cleaner

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures	: Ground/bond container and receiving equipment.
Storage conditions	: Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.
Incompatible materials	: Strong oxidizing agents. Strong acids.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Bioact™ 105 Precision Cleaner

No additional information available

#### Propylene glycol propyl ether (1569-01-3)

No additional information available

#### D-Limonene (5989-27-5)

##### USA - AIHA - Occupational Exposure Limits

WEEL TWA [ppm]	30 ppm
----------------	--------

#### Naphtha (petroleum), hydrotreated heavy (64742-48-9)

No additional information available

### 8.2. Appropriate engineering controls

Appropriate engineering controls	: Ensure good ventilation of the work station.
Environmental exposure controls	: Avoid release to the environment.

### 8.3. Individual protection measures/Personal protective equipment

#### Hand protection:

Protective gloves

#### Eye protection:

Safety glasses

#### Skin and body protection:

Wear suitable protective clothing

#### Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

#### Personal protective equipment symbol(s):



## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state : Liquid

# Bioact™ 105 Precision Cleaner

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Color	: Colorless
Odor	: characteristic
Odor threshold	: No data available
pH	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: > 150 °C
Flash point	: 41 °C (Closed cup)
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability	: No data available
Vapor pressure	: 1.5 mm Hg
Relative vapor density at 20°C	: > 1 (air = 1)
Relative density	: 0.8
Solubility	: Partially soluble.
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: 1.6 mm <sup>2</sup> /s @ 25 °C
Viscosity, dynamic	: No data available
Explosion limits	: Lower explosion limit: 0.7 vol % Upper explosion limit: 6.1 vol %
Explosive properties	: None reported.
Oxidizing properties	: None reported.

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Flammable liquid and vapor.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

### 10.5. Incompatible materials

Strong oxidizing agents. Strong acids.

### 10.6. Hazardous decomposition products

Carbon dioxide. Carbon monoxide.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified

# Bioact™ 105 Precision Cleaner

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Acute toxicity (inhalation) : Not classified

Propylene glycol propyl ether (1569-01-3)	
LD50 oral rat	2490 mg/kg
LD50 dermal rabbit	3550 mg/kg

D-Limonene (5989-27-5)	
LD50 oral rat	4400 mg/kg
LD50 dermal rabbit	> 5 g/kg

Naphtha (petroleum), hydrotreated heavy (64742-48-9)	
LD50 oral rat	> 6000 mg/kg
LD50 dermal rabbit	> 5000 mg/kg
LC50 Inhalation - Rat	> 8500 mg/m <sup>3</sup> (Exposure time: 4 h)

Skin corrosion/irritation : Causes skin irritation.  
Serious eye damage/irritation : Causes serious eye irritation.  
Respiratory or skin sensitization : May cause an allergic skin reaction.  
Germ cell mutagenicity : Not classified  
Carcinogenicity : Not classified

D-Limonene (5989-27-5)	
IARC group	3 - Not classifiable
National Toxicity Program (NTP) Status	Evidence of Carcinogenicity

Reproductive toxicity : Not classified  
STOT-single exposure : Not classified  
STOT-repeated exposure : Not classified  
Aspiration hazard : May be fatal if swallowed and enters airways.  
Viscosity, kinematic : 1.6 mm<sup>2</sup>/s @ 25 °C  
Symptoms/effects after skin contact : Irritation. May cause an allergic skin reaction.  
Symptoms/effects after eye contact : Eye irritation.  
Symptoms/effects after ingestion : Risk of lung edema.

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general : Toxic to aquatic life with long lasting effects.

Propylene glycol propyl ether (1569-01-3)	
LC50 - Fish [1]	> 100 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])

D-Limonene (5989-27-5)	
LC50 - Fish [1]	0.619 – 0.796 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 - Crustacea [1]	0.36 mg/l Test organisms (species): Daphnia magna
LC50 - Fish [2]	35 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)
EC50 - Crustacea [2]	0.51 mg/l Test organisms (species): Daphnia magna
NOEC (chronic)	0.115 mg/l Test organisms (species): other:For freshwater invertebrates, species frequently include Daphnia magna or Daphnia pulex. Duration: '16 d'

# Bioact™ 105 Precision Cleaner

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### Naphtha (petroleum), hydrotreated heavy (64742-48-9)

LC50 - Fish [1]	2200 mg/l (Exposure time: 96 h - Species: Pimephales promelas)
LC50 - Other aquatic organisms [1]	2.6 mg/l Source: IUCLID

### 12.2. Persistence and degradability

#### Propylene glycol propyl ether (1569-01-3)

Persistence and degradability	Readily biodegradable in water.
-------------------------------	---------------------------------

#### D-Limonene (5989-27-5)

Persistence and degradability	Readily biodegradable in water.
-------------------------------	---------------------------------

ThOD	3.29 g O <sub>2</sub> /g substance
------	------------------------------------

### 12.3. Bioaccumulative potential

#### Propylene glycol propyl ether (1569-01-3)

BCF - Other aquatic organisms [1]	3.16 l/kg (Literature study, Fresh weight)
-----------------------------------	--

Partition coefficient n-octanol/water (Log Pow)	0.621 (Calculated, EPIWIN, 20 °C)
---	-----------------------------------

Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
---------------------------	--

#### D-Limonene (5989-27-5)

BCF - Fish [1]	864.8 l/kg (BCFBAF v3.01, Pisces, QSAR, Fresh weight)
----------------	---

Partition coefficient n-octanol/water (Log Pow)	4.38 (Experimental value, Equivalent or similar to OECD 117, 37 °C)
---	---

Bioaccumulative potential	Potential for bioaccumulation (4 ≤ Log Kow ≤ 5).
---------------------------	--

#### Naphtha (petroleum), hydrotreated heavy (64742-48-9)

Partition coefficient n-octanol/water (Log Pow)	2.1 – 6 Source: IUCLID
---	------------------------

### 12.4. Mobility in soil

#### Propylene glycol propyl ether (1569-01-3)

Mobility in soil	3
------------------	---

Organic Carbon Normalized Adsorption Coefficient (Log Koc)	0.376 – 0.694 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
--	--

Ecology - soil	Highly mobile in soil.
----------------	------------------------

#### D-Limonene (5989-27-5)

Surface tension	No data available in the literature
-----------------	-------------------------------------

Organic Carbon Normalized Adsorption Coefficient (Log Koc)	3.049 – 3.801 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
--	--

Ecology - soil	Low potential for mobility in soil.
----------------	-------------------------------------

### 12.5. Other adverse effects

No additional information available

# Bioact™ 105 Precision Cleaner

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations





### SECTION 13: Disposal considerations

#### 13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.  
 Additional information : Flammable vapors may accumulate in the container.

### SECTION 14: Transport information

In accordance with DOT / TDG / IMDG / IATA

DOT	TDG	IMDG	IATA
<b>14.1. UN number</b>			
3295	UN3295	3295	3295
<b>14.2. Proper Shipping Name</b>			
Hydrocarbons, liquid, n.o.s.	HYDROCARBONS, LIQUID, N.O.S.	HYDROCARBONS, LIQUID, N.O.S.	Hydrocarbons, liquid, n.o.s.
<b>Transport document description</b>			
UN3295 Hydrocarbons, liquid, n.o.s., 3, III	UN3295 HYDROCARBONS, LIQUID, N.O.S., 3, III	UN 3295 HYDROCARBONS, LIQUID, N.O.S., 3, III, MARINE POLLUTANT/ENVIRONMENTALLY HAZARDOUS	UN 3295 Hydrocarbons, liquid, n.o.s., 3, III, ENVIRONMENTALLY HAZARDOUS
<b>14.3. Transport hazard class(es)</b>			
3	3	3	3
			
<b>14.4. Packing group</b>			
III	III	III	III
<b>14.5. Environmental hazards</b>			
Dangerous for the environment: Yes	Dangerous for the environment: Yes	Dangerous for the environment: Yes Marine pollutant: Yes	Dangerous for the environment: Yes
No supplementary information available			

#### 14.6. Special precautions for user

**DOT**  
 Transport regulations (DOT) : Exempt from regulation by US DOT when shipped in the USA solely by land in containers less than 119 gallons, refer to 49 CFR 173.150(f).  
 UN-No.(DOT) : UN3295



# Bioact™ 105 Precision Cleaner

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT Special Provisions (49 CFR 172.102)	: 144 - If transported as a residue in an underground storage tank (UST), as defined in 40 CFR 280.12, that has been cleaned and purged or rendered inert according to the American Petroleum Institute (API) Standard 1604 (IBR, see 171.7 of this subchapter), then the tank and this material are not subject to any other requirements of this subchapter. However, sediments remaining in the tank that meet the definition for a hazardous material are subject to the applicable regulations of this subchapter. B1 - If the material has a flash point at or above 38 C (100 F) and below 93 C (200 F), then the bulk packaging requirements of 173.241 of this subchapter are applicable. If the material has a flash point of less than 38 C (100 F), then the bulk packaging requirements of 173.242 of this subchapter are applicable. IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672). T4 - 2.65 178.274(d)(2) Normal..... 178.275(d)(3) TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $97 / 1 + a (tr - tf)$ Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling. TP29 - A portable tank having a minimum test pressure of 1.5 bar (150.0 kPa) may be used provided the calculated test pressure is 1.5 bar or less based on the MAWP of the hazardous materials, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.
DOT Packaging Exceptions (49 CFR 173.xxx)	: 150
DOT Packaging Non Bulk (49 CFR 173.xxx)	: 203
DOT Packaging Bulk (49 CFR 173.xxx)	: 242
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: 60 L
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 220 L
DOT Vessel Stowage Location	: A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.
<b>TDG</b>	
UN-No. (TDG)	: UN3295
TDG Special Provisions	: 150 - An approved ERAP is required for the dangerous goods referred to in paragraph 7.2(1)(f) of Part 7 (Emergency Response Assistance Plan). SOR-2019-101
Explosive Limit and Limited Quantity Index	: 5 L
Excepted quantities (TDG)	: E1
Passenger Carrying Road Vehicle or Passenger Carrying Railway Vehicle Index	: 60 L
Emergency Response Guide (ERG) Number	: 128
<b>IMDG</b>	
Special provision (IMDG)	: 223
Limited quantities (IMDG)	: 5 L
Excepted quantities (IMDG)	: E1
Packing instructions (IMDG)	: P001, LP01
IBC packing instructions (IMDG)	: IBC03
Tank instructions (IMDG)	: T4
Tank special provisions (IMDG)	: TP1, TP29
EmS-No. (Fire)	: F-E - FIRE SCHEDULE Echo - NON-WATER-REACTIVE FLAMMABLE LIQUIDS
EmS-No. (Spillage)	: S-D - SPILLAGE SCHEDULE Delta - FLAMMABLE LIQUIDS
Stowage category (IMDG)	: A
Properties and observations (IMDG)	: Immiscible with water.
<b>IATA</b>	
PCA Excepted quantities (IATA)	: E1
PCA Limited quantities (IATA)	: Y344

# Bioact™ 105 Precision Cleaner

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

PCA limited quantity max net quantity (IATA)	: 10L
PCA packing instructions (IATA)	: 355
PCA max net quantity (IATA)	: 60L
CAO packing instructions (IATA)	: 366
CAO max net quantity (IATA)	: 220L
Special provision (IATA)	: A3, A324
ERG code (IATA)	: 3L

### 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

## SECTION 15: Regulatory information

### 15.1. US Federal regulations

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

### 15.2. International regulations

No additional information available

### 15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm


## SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date : 11/02/2022

Full text of H-phrases	
H226	Flammable liquid and vapor
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H400	Very toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects
H411	Toxic to aquatic life with long lasting effects

NFPA health hazard	: 1 - Materials that, under emergency conditions, can cause significant irritation.
NFPA fire hazard	: 2 - Materials that must be moderately heated or exposed to relatively high ambient temperatures before ignition can occur.
NFPA reactivity	: 0 - Material that in themselves are normally stable, even under fire conditions.



Hazard Rating

# Bioact™ 105 Precision Cleaner

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

---

Health	: 1 Slight Hazard - Irritation or minor reversible injury possible
Flammability	: 2 Moderate Hazard - Materials which must be moderately heated or exposed to high ambient temperatures before ignition will occur. Includes liquids having a flash point at or above 100 F but below 200 F. (Classes II & IIIA)
Physical	: 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT react with water, polymerize, decompose, condense, or self-react. Non-Explosives.
Personal protection	: B - Safety glasses, Gloves

Vantage - Safety Data Sheet (SDS), USA

The information in this safety data sheet (SDS) is believed to be accurate and is given in good faith but no representation or warranty as to its completeness or accuracy is made. Suggestions for uses or applications are only opinions. Users are responsible for determining the suitability of these products for their own particular purpose. No representation or warranty, express or implied, is made with respect to information or products including without limitation warranties of merchantability or fitness for a particular purpose or non-infringement of any third-party patent or other intellectual property rights including without limit copyright, trademark and designs. Any trademarks identified herein are trademarks of Vantage Specialties, Inc.