

SAFETY DATA SHEET

Aerowave 2501 Filler

Section 1. Identification

GHS product identifier Other means of identification	 Aerowave 2501 Filler 57610/000000 Aerowave 2501 beige RAL 1019
Relevant identified uses of the	e substance or mixture and uses advised against : FOR INDUSTRIAL USE ONLY
Supplier/Manufacturer	: Akzo Nobel Coatings, Inc. 1 East Water Street Waukegan, IL 60085 USA Tel. 1 847 623 4200 Email: customer. service@akzonobel.com
Canadian Supplier	 Akzo Nobel Coatings Ltd. 110 Woodbine Downs Blvd. Unit #4 Etobicoke, Ontario Canada M9W 5S6 +1 (800) 618-1010
Emergency telephone number	: CHEMTREC +1 (800) 424-9300 (Inside the US) CHEMTREC International +1 (703) 527-3887 (Outside the US, collect calls accepted)
Date of issue / Date of revision Safety Data Sheet Version Date of printing	 25 April 2017 1.02 25 April 2017

Akzo Nobel Coatings Inc. encourages and expects you to read and understand this entire MSDS, as there is important information throughout the document. Further, Akzo Nobel Coatings Inc. expects you to follow the precautions identified in this document unless your use conditions would necessitate other appropriate methods or actions.

To promote safe handling, each customer or recipient should: 1) Notify its employees, agents, contractors, and others whom it knows or believes will use this material of the information contained in this MSDS and any other information regarding hazards and safety; 2) Furnish this same information to each of its customers for the product; 3) Request its customers to notify their employees, customers, and other users of the product of this information; and 4) Notify its employees, agents, contractors, and others that the precautions identified for this product and any other products with which mixtures may be created are transferable and cumulative to the mixture.

Section 2. Hazards identification

OSHA/HCS status	: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).
Classification of the substance or mixture	: SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A CARCINOGENICITY - Category 1A

GHS label elements

For additional information call Akzo Nobel at (847) 625-4200

Page: 2/14

Section 2. Hazards identification	
Hazard pictograms	
Signal word Hazard statements	 Danger Causes serious eye irritation. Causes skin irritation. May cause cancer.
Precautionary statement	ts
Prevention	: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves. Wear eye or face protection. Wear protective clothing. Wash hands thoroughly after handling.
Response	: IF exposed or concerned: Get medical attention. IF ON SKIN: Wash with plenty of soap and water. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.
Storage	: Store locked up.
Disposal	: Dispose of contents and container in accordance with all local, regional, national and international regulations.
Hazards not otherwise classified	: None known.

Section 3. Composition/information on ingredients

: Mixture

Substance/mixture

Ingredient name	%	CAS number
Talc , not containing asbestiform fibres	15 - 20	14807-96-6
Chlorite-group minerals	15 - 20	1318-59-8
Propylidynetrimethanol, ethoxylated, esters with acrylic acid	5 - 10	28961-43-5
titanium dioxide	5 - 10	13463-67-7
benzyl alcohol	5 - 10	100-51-6
Zeolites	0 - 1	1318-02-1
crystalline silica, respirable powder	0 - 1	14808-60-7

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

For additional information call Akzo Nobel at (847) 625-4200

Section 4. First aid measures

Eye contact	: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Skin contact	: Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	: Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects		
Eye contact	Causes serious eye irritation.	
Inhalation :	No known significant effects or critical hazards.	
Skin contact	Causes skin irritation.	
Ingestion :	No known significant effects or critical hazards.	
Over-exposure signs/symptoms		
Eye contact :	Adverse symptoms may include the following: pain or irritation watering redness	
Inhalation :	No specific data.	
Skin contact	Adverse symptoms may include the following: irritation redness	
Ingestion :	No specific data.	
Indication of immediate medical attention and special treatment needed, if necessary		
Notes to physician	Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.	
Specific treatments	No specific treatment.	

For additional information call Akzo Nobel at (847) 625-4200

Section 4. First aid measures

Protection of first-aiders	No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.
	belote territoving it, of wear gloves.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

: Use an extinguishing agent suitable for the surrounding fire.
: None known.
: In a fire or if heated, a pressure increase will occur and the container may burst.
 Decomposition products may include the following materials: carbon dioxide carbon monoxide metal oxide/oxides
Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

For additional information call Akzo Nobel at (847) 625-4200

Section 6. Accidental release measures

Small spill	: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling		
Protective measures	:	Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	:	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	:	Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
Talc , not containing asbestiform fibres	NIOSH REL (United States, 10/2013). TWA: 2 mg/m ³ 10 hours. Form: Respirable fraction ACGIH TLV (United States, 3/2015). TWA: 2 mg/m ³ 8 hours. Form: Respirable fraction OSHA PEL Z3 (United States, 2/2013). TWA: 0.1 f/cc 8 hours. Form: containing asbestos STEL: 1 f/cc 30 minutes. Form: containing

For additional information call Akzo Nobel at (847) 625-4200

Page: 6/14

Section 8. Exposu	ire controls/personal p	rotection		
		asbestos STEL: 1 f/cc 30 minutes. Form: not containing asbestos TWA: 20 mppcf 8 hours. Form: not containing asbestos		
Chlorite-group minerals Propylidynetrimethanol, etho titanium dioxide	xylated, esters with acrylic acid	None. None. OSHA PEL (United States, 2/2013). TWA: 15 mg/m³ 8 hours. Form: Total dust ACGIH TLV (United States, 3/2015).		
benzyl alcohol		TWA: 10 mg/m ³ 8 hours. AIHA WEEL (United States, 10/2011).		
Zeolites		TWA: 10 ppm 8 hours. ACGIH TLV (United States, 3/2015). TWA: 1 mg/m ³ 8 hours. Form: Respirable		
crystalline silica, respirable p	owder	fraction OSHA PEL Z3 (United States, 2/2013). TWA: 250 mppcf / (%SiO2+5) 8 hours. Form: Respirable TWA: 10 mg/m ³ / (%SiO2+2) 8 hours. Form: Respirable ACGIH TLV (United States, 3/2015). TWA: 0.025 mg/m ³ 8 hours. Form: Respirable fraction NIOSH REL (United States, 10/2013). TWA: 0.05 mg/m ³ 10 hours. Form: respirable dust		
Appropriate engineering controls		umes, gas, vapor or mist, use process enclosures, engineering controls to keep worker exposure to recommended or statutory limits.		
Environmental exposure controls	: Emissions from ventilation or work they comply with the requirements	process equipment should be checked to ensure of environmental protection legislation. In some ngineering modifications to the process equipment		
Individual protection measured	res			
Hygiene measures	eating, smoking and using the lave Appropriate techniques should be	horoughly after handling chemical products, before atory and at the end of the working period. used to remove potentially contaminated clothing. re reusing. Ensure that eyewash stations and safety ion location.		
Eye/face protection	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.			
Skin protection	5			

For additional information call Akzo Nobel at (847) 625-4200 To request an updated SDS please visit http://www.formstack.com/forms/AkzoNobel-document_request_form

Section 8. Exposure controls/personal protection

Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Body protection	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Section 9. Physical and chemical properties

Appearance

Appearance		
Physical state	:	Liquid.
Color	:	Blue.
Odor	:	Typical.
Odor threshold	:	Not available.
рН	:	Not available.
Melting/freezing point	:	Not available.
Boiling point	:	205.3°C (401.5°F)
boiling range	:	Not available.
Flash point	:	Closed cup: >100°C (>212°F)
Evaporation rate	:	Not available.
Flammability (solid, gas)	:	Not available.
Upper/lower flammability or exp	olo	osive limits
Upper:	:	Not determined.
Lower:	:	Not determined.
Vapor pressure	:	Not available.
Vapor density	:	Not available.
Relative density	:	1.559
Density	:	13.01 lbs/gal 1.559 g/cm ³
Solubility	:	Not available.
Solubility in water	:	Not available.
Partition coefficient: n- octanol/water	:	Not available.
Auto-ignition temperature	:	Not available.
Decomposition temperature	:	Not available.
Viscosity	:	Kinematic (room temperature): >3.591876 cm ² /s (>359.1876 cSt)

For additional information call Akzo Nobel at (847) 625-4200

Page: 8/14

Section 9. Physica	al and chemical properties
Weight Volatiles	: 5.21% (w/w)
Volume Volatiles	: 7.86 %(v/v)
Weight Solids	: 94.79 %(w/w)
Volume Solids	: 92.14 %(v/v)
Regulatory VOC	: 0.676 lbs/gal (81 g/l) minus water and exempt solvents
Section 10. Stabil	ity and reactivity
Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: No specific data.
Incompatible materials	: No specific data.
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Propylidynetrimethanol, ethoxylated, esters with acrylic acid	LD50 Dermal	Rabbit	>13 g/kg	-
benzyl alcohol	LC50 Inhalation Vapor LD50 Dermal LD50 Oral	Rabbit	1000 ppm 2000 mg/kg 1230 mg/kg	8 hours - -

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Talc , not containing asbestiform fibres	Skin - Mild irritant	Human	-	72 hours 300 Micrograms Intermittent	-
Propylidynetrimethanol, ethoxylated, esters with acrylic acid	Eyes - Moderate irritant	Rabbit	-	100 milligrams	-
,	Skin - Moderate irritant	Rabbit	-	500 milligrams	-
titanium dioxide	Skin - Mild irritant	Human	-	72 hours 300 Micrograms Intermittent	-
benzyl alcohol	Skin - Mild irritant	Man	-	48 hours 16	-

For additional information call Akzo Nobel at (847) 625-4200 To request an updated SDS please visit http://www.formstack.com/forms/AkzoNobel-document_request_form

Page: 9/14

Section 11. Toxicological information

Skin - Moderate irritant Skin - Moderate irritant	Pig Rabbit	-	milligrams 100 Percent 24 hours 100 milligrams	-	
			milligrams		

Sensitization

Not available.

Mutagenicity

Not available.

Carcinogenicity

Not available.

Classification

Product/ingredient name	OSHA	IARC	NTP
Talc , not containing asbestiform fibres titanium dioxide	-	3 2B	-
Zeolites crystalline silica, respirable powder	-	3	- - Known to be a human carcinogen.

Reproductive toxicity

Not available.

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

Information on the likely : Not available. routes of exposure

Potential acute health effects

Eye contact	: Causes serious eye irritation.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: Causes skin irritation.
Ingestion	: No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

For additional information call Akzo Nobel at (847) 625-4200

Page: 10/14

Eye contact	Adverse symptoms may include the following: pain or irritation watering redness			
Inhalation	: No specific data.			
Skin contact	: Adverse symptoms may include the following: irritation redness			
Ingestion	: No specific data.			
Delayed and immediate effe	cts and also chronic effects from short and long term exposure			
<u>Short term exposure</u>				
Potential immediate effects	: Not available.			
Potential delayed effects	: Not available.			
Long term exposure				
Potential immediate effects	: Not available.			
Potential delayed effects	: Not available.			
Potential chronic health eff Not available.	ects			
General	: No known significant effects or critical hazards.			
Carcinogenicity	: May cause cancer. Risk of cancer depends on duration and level of exposure.			
Mutagenicity	: No known significant effects or critical hazards.			
Teratogenicity	: No known significant effects or critical hazards.			
Developmental effects	: No known significant effects or critical hazards.			
	: No known significant effects or critical hazards.			

Numerical measures of toxicity

Acute toxicity estimates

Route	ATE value
Oral	3906.8 mg/kg
Dermal	6352.5 mg/kg

Section 12. Ecological information

Toxicity			
Product/ingredient name	Result	Species	Exposure
benzyl alcohol Zeolites	Acute LC50 10000 μg/l Fresh water Chronic NOEC 200000 μg/l Fresh water	Fish - Lepomis macrochirus Daphnia - Daphnia magna	96 hours 21 days

Persistence and degradability

For additional information call Akzo Nobel at (847) 625-4200

To request an updated SDS please visit http://www.formstack.com/forms/AkzoNobel-document_request_form

Page: 11/14

Section 12. Ecological information

Not available.

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
Propylidynetrimethanol, ethoxylated, esters with acrylic acid	2.89	-	low
benzyl alcohol	0.87	-	low
Zeolites	-	0.59 to 0.95	low
Soil/water partition coefficient (K _{oc}) Other adverse effects	 Not available. No known significant effects or critical hazards. 		
Other adverse effects	. No known significant ene		
Section 13. Dispo	sal consideration	S	
Disposal methods	: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the		

	of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
--	---

Section 14. Transport information

Special precautions for user : The actual shipping description for this product may vary based several factors including, but not limited to, the volume of material, size of the container, mode of transport and use of exemptions or exceptions found in the applicable regulations. The information provided in Section 14 is one possible shipping description for this product. Consult your shipping specialist or supplier for appropriate assignment of the DOT information.

Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

For additional information call Akzo Nobel at (847) 625-4200

Section 14. Transport information

	DOT Classification	TDG Classification	Mexico Classification	IMDG	ΙΑΤΑ
UN number	Not regulated.	Not regulated.	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-	-	-
Transport hazard class(es)	-	-	-	-	-
Packing group	-	-	-	-	-
Environmental hazards	No.	No.	No.	No.	No.

Section 15. Regulatory information

U.S. Federal regulations

United States inventory (TSCA 8b): All components are listed or exempted.

SARA 311/312

Classification

: Immediate (acute) health hazard Delayed (chronic) health hazard

California Prop. 65

WARNING: This product contains a chemical known to the State of California to cause cancer. **WARNING:** This product contains less than 1% of a chemical known to the State of California to cause birth defects or other reproductive harm.

International lists	
National inventory	
Australia	: At least one component is not listed.
Canada	: At least one component is not listed in DSL but all such components are listed in NDSL.
China	: All components are listed or exempted.
Europe	: At least one component is not listed.
Japan	: Japan inventory (ENCS): At least one component is not listed. Japan inventory (ISHL): At least one component is not listed.
Malaysia	: At least one component is not listed.
New Zealand	: All components are listed or exempted.
Philippines	: All components are listed or exempted.
Republic of Korea	: All components are listed or exempted.
Taiwan	: At least one component is not listed.

For additional information call Akzo Nobel at (847) 625-4200


To request an updated SDS please visit http://www.formstack.com/forms/AkzoNobel-document_request_form

Page: 12/14

Page: 13/14

Section 16. Other information

Hazardous Material Information System (U.S.A.)



Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks Although HMIS® ratings are not required on SDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material.

National Fire Protection Association (U.S.A.)



Reprinted with permission from NFPA 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

<u>History</u>

Date of issue/Date of revision Version	:	1.02
MSDS #	:	A45908 0017
Key to abbreviations	:	ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = International Air Transport Association IBC = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) UN = United Nations

Notice to reader

For additional information call Akzo Nobel at (847) 625-4200

Section 16. Other information

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.