

Safety Data Sheet

Naftoseal MC-780 C-60 Base (BULK)

Revision date : 2024/01/10
Version: 6.0

Page: 1/12
(30691277/SDS_GEN_US/EN)

1. Identification

Product identifier used on the label

Naftoseal MC-780 C-60 Base (BULK)

Recommended use of the chemical and restriction on use

Recommended use*: Sealant

Unsuitable for use: Uses other than recommended

* The "Recommended use" identified for this product is provided solely to comply with a Federal requirement and is not part of the seller's published specification. The terms of this Safety Data Sheet (SDS) do not create or infer any warranty, express or implied, including by incorporation into or reference in the seller's sales agreement.

Details of the supplier of the safety data sheet

Company:

Chemetall U.S., Inc.
675 Central Avenue
New Providence, NJ 07974 – USA
+1 800 526-4473
sds.na-chemetall@basf.com

Emergency telephone number

24 Hour Emergency Response Information
CHEMTREC: 800-424-9300, +1-703-527-3887

Other means of identification

Chemical family: fillers, organic compounds, polymers, organic solvent

2. Hazards Identification

According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

Classification of the product

STOT RE	2	Specific target organ toxicity — repeated exposure
Aquatic Chronic	3	Hazardous to the aquatic environment - chronic
Flam. Liq.	3	Flammable liquids
Aquatic Acute	3	Hazardous to the aquatic environment - acute

Safety Data Sheet

Naftoseal MC-780 C-60 Base (BULK)

Revision date: 2024/01/10
Version: 6.0

Page: 2/12
(30691277/SDS_GEN_US/EN)

Label elements

Pictogram:



Signal Word:
Warning

Hazard Statement:

H226	Flammable liquid and vapour.
H412	Harmful to aquatic life with long lasting effects.
H373	May cause damage to organs (Auditory organ, Central nervous system, Liver, Kidney) through prolonged or repeated exposure.

Precautionary Statements (Prevention):

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P273	Avoid release to the environment.
P280	Wear protective gloves, protective clothing and eye protection or face protection.
P260	Do not breathe mist or vapour or spray.
P242	Use non-sparking tools.
P241	Use explosion-proof electrical, ventilating and lighting equipment.
P243	Take action to prevent static discharges.
P233	Keep container tightly closed.
P240	Ground and bond container and receiving equipment.

Precautionary Statements (Response):

P314	Get medical advice/attention if you feel unwell.
P370 + P378	In case of fire: Use water spray for extinction.
P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.

Precautionary Statements (Storage):

P403 + P235	Store in a well-ventilated place. Keep cool.
-------------	--

Precautionary Statements (Disposal):

P501	Dispose of contents and container to hazardous or special waste collection point.
------	---

Hazards not otherwise classified

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

3. Composition / Information on Ingredients

According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

Liquid polysulphide polymer with thiol end groups (MW>1800)

Safety Data Sheet

Naftoseal MC-780 C-60 Base (BULK)

Revision date: 2024/01/10
Version: 6.0

Page: 3/12
(30691277/SDS_GEN_US/EN)

CAS Number: 68611-50-7
Content (W/W): ≥ 25.0 - $< 50.0\%$
Synonym: No data available.

Liquid polysulphide polymer with thiol end groups (MW<1800)
CAS Number: 68611-50-7
Content (W/W): ≥ 15.0 - $< 20.0\%$
Synonym: No data available.

Calcium carbonate
CAS Number: 471-34-1
Content (W/W): ≥ 5.0 - $< 7.0\%$
Synonym: Calcium carbonate

Xylene
CAS Number: 1330-20-7
Content (W/W): ≥ 5.0 - $< 7.0\%$
Synonym: Xylene; Dimethylbenzene

ethylbenzene
CAS Number: 100-41-4
Content (W/W): ≥ 1.0 - $< 3.0\%$
Synonym: Ethylbenzene

4. First-Aid Measures

Description of first aid measures

General advice:

In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.

If inhaled:

Remove the affected individual into fresh air and keep the person calm. If symptoms persist, seek medical advice. If breathing is irregular or stopped, administer artificial respiration.

If on skin:

If symptoms persist, seek medical advice. Remove contaminated clothing. Wash skin with soap and water, rinse abundantly. Do NOT use solvents or thinners.

If in eyes:

If symptoms persist, seek medical advice. Contact lenses should be removed. Hold eyelids open and flush with copious amounts of clean, fresh water or a special eyewash solution.

If swallowed:

Do not induce vomiting. Rinse mouth thoroughly with water, seek medical attention. If adverse health effects develop seek medical attention.

Most important symptoms and effects, both acute and delayed

Symptoms: Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11.

Safety Data Sheet

Naftoseal MC-780 C-60 Base (BULK)

Revision date: 2024/01/10
Version: 6.0

Page: 4/12
(30691277/SDS_GEN_US/EN)

Information on: ethylbenzene

Symptoms: Overexposure may cause: Eye irritation, skin irritation, irritation of the mucous membranes, erythema, nausea, headache, dizziness, diarrhea, abdominal cramps, dermatitis, loss of hearing, Ingestion may provoke the following symptoms: asphyxia, dyspnea, choking, respiratory arrest, circulatory collapse

Information on: Xylene

Symptoms: Overexposure may cause: coma, weakness, lethargy, confusion, dyspnea, nausea, headache, dizziness

Indication of any immediate medical attention and special treatment needed

Note to physician

Antidote: No known specific antidote.
Treatment: Symptomatic treatment (decontamination, vital functions).

5. Fire-Fighting Measures

Extinguishing media

Suitable extinguishing media:
carbon dioxide, alcohol-resistant foam, dry powder, water spray

Unsuitable extinguishing media for safety reasons:
water jet

Special hazards arising from the substance or mixture

Hazards during fire-fighting:
Fire will produce dense black smoke. Inhalation of dangerous decomposition products may cause serious damage to health.

Advice for fire-fighters

Protective equipment for fire-fighting:
Appropriate breathing apparatus may be required.

Further information:

Cool closed containers in the vicinity of the source of fire. Dispose of fire debris and contaminated extinguishing water in accordance with official regulations. Collect contaminated extinguishing water separately, do not allow to reach sewage or effluent systems.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Avoid breathing vapours. For non-emergency personnel: Use personal protective clothing. Ensure adequate ventilation. Keep away from sources of ignition. For emergency responders: Advice on product handling can be found in sections 7 and 8 of this safety data sheet. Information regarding personal protective measures, see section 8.

Environmental precautions

Safety Data Sheet

Naftoseal MC-780 C-60 Base (BULK)

Revision date: 2024/01/10
Version: 6.0

Page: 5/12
(30691277/SDS_GEN_US/EN)

Do not allow to enter drains or waterways. Do not discharge into the subsoil/soil. If the product enters drains or sewers, the local water company should be contacted immediately; in the case of contamination of streams, rivers or lakes, the Environment Agency.

Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in a suitable container for disposal according with the waste regulations (see section 13). Clean preferably with a detergent; avoid the use of solvents. Ensure adequate ventilation.

7. Handling and Storage

Precautions for safe handling

Provide good ventilation of working area (local exhaust ventilation if necessary). Do not return residues to the storage containers. Smoking, eating and drinking are forbidden in application area. For personal protection see section 8. Comply with the health and safety at work laws. Avoid inhalation of vapour and spray mist. The workplace should be equipped with an emergency shower and eye-rinsing facility. Avoid contact with the skin, eyes and clothing. Handle in accordance with good industrial hygiene and safety practice.

Protection against fire and explosion:

Avoid all sources of ignition: heat, sparks, open flame. Product may charge electrostatically: always use earthing leads when transferring from one container to another and earth containers. It is recommended that operators should wear antistatic clothing and footwear. Solvent vapours are heavier than air and spread along floors. Vapour forms explosive mixtures with air. The relevant fire protection measures should be noted. Use explosion-proof equipment.

Conditions for safe storage, including any incompatibilities

Keep away from oxidising agents, from strongly alkaline and strongly acid materials.

Suitable materials for containers: tinned carbon steel (Tinplate), Carbon steel (Iron), Polypropylene (PP), Polyethylenetherephtalate (PET), Low density polyethylene (LDPE), High density polyethylene (HDPE), Stove-lacquer C222A/C221A, Stove-lacquer NOVOCAN S-G 500, Stove-lacquer Vitalure 745, Stove-lacquer Valspar HXR008F red, Stove-lacquer KNS L-5X, Stove-lacquer EHD0022, Stove-lacquer 79/14/3 (Müller/CH), Stove-lacquer R 78433, Stove-lacquer RDL 50

Further information on storage conditions: Keep container dry. Keep away from heat. Keep in a cool, well-ventilated place. Avoid direct sunlight. Close containers carefully once opened and store them upright in order to prevent any leakage. No smoking. No admission for unauthorised personnel. Always keep in containers of same material as the original one. Observe label precautions.

Storage stability:

Storage temperature: < 26 °C

8. Exposure Controls/Personal Protection

Components with occupational exposure limits

Safety Data Sheet

Naftoseal MC-780 C-60 Base (BULK)

Revision date: 2024/01/10
Version: 6.0

Page: 6/12
(30691277/SDS_GEN_US/EN)

Formaldehyde	ACGIH, US: STEL value 0.3 ppm ; ACGIH, US: TWA value 0.1 ppm ; OSHA, US: STEL value 2 ppm ; OSHA, US: OSHA Action level 0.5 ppm ; OSHA, US: TWA value 0.75 ppm ;
ethylbenzene	ACGIH, US: TWA value 20 ppm ; OSHA Z1: PEL 100 ppm 435 mg/m3 ;
Calcium carbonate	ACGIH, US: TWA value 3 mg/m3 Respirable particles ; ACGIH, US: TWA value 10 mg/m3 Inhalable particles ; OSHA Z1: PEL 15 mg/m3 Total dust ; OSHA Z1: PEL 5 mg/m3 Respirable fraction ; OSHA Z3: TWA value 15 millions of particles per cubic foot of air Respirable fraction ; OSHA Z3: TWA value 5 mg/m3 Respirable fraction ; OSHA Z3: TWA value 50 millions of particles per cubic foot of air Total dust ; OSHA Z3: TWA value 15 mg/m3 Total dust ; OSHA Z1: PEL 5 mg/m3 Respirable fraction ; OSHA Z1: PEL 15 mg/m3 Total dust ;
Xylene	OSHA Z1: PEL 100 ppm 435 mg/m3 ; ACGIH, US: TWA value 20 ppm ;

Personal protective equipment

Respiratory protection:

Respiratory protection required if exposure limit (if available) may be exceeded

Hand protection:

Chemical resistant protective gloves (EN ISO 374-1), nitrile rubber (NBR) - 0.4 mm coating thickness, Performance level 6, corresponding to a breakthrough time of >480 min according to EN ISO 374-1, The protection glove should be tested for its specific suitability (e.g. mechanical strength, product compatibility, anti-static properties)., The gloves should be replaced immediately in case of damage or signs of wear. It is recommended to use preventative skin protection (skin cream).

Eye protection:

Tightly fitting safety goggles (splash goggles) (e.g. EN 166)

Body protection:

Chemical resistant protective clothing according to DIN EN 13034 (Type 6)

General safety and hygiene measures:

Do not breathe vapour/spray. Eye wash fountains and safety showers must be easily accessible. Avoid contact with the skin, eyes and clothing. Handle in accordance with good industrial hygiene and safety practice. Ensure adequate ventilation. This can be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations at the workplace below the occupational exposure limits, appropriate certified respirators must be worn. Remove contaminated clothing immediately and dispose of safely. Hands and/or face should be washed before breaks and at the end of the shift. Keep separated from food stuffs and feed stocks.

Safety Data Sheet

Naftoseal MC-780 C-60 Base (BULK)

Revision date: 2024/01/10
Version: 6.0

Page: 7/12
(30691277/SDS_GEN_US/EN)

9. Physical and Chemical Properties

Form:	liquid
Odour:	No applicable information available.
Odour threshold:	No applicable information available.
Colour:	beige
pH value:	substance/mixture is non-soluble (in water)
Melting point:	not determined
Freezing point:	not determined
onset of boiling:	not determined
Boiling range:	not determined
Sublimation point:	No applicable information available.
Flash point:	51 °C
Flammability:	Flammable liquid and vapour.
Lower explosion limit:	not determined
Upper explosion limit:	No applicable information available.
Autoignition:	No applicable information available.
Vapour pressure:	(20 °C) not determined
Density:	1.300 g/cm ³ (20 °C)
Relative density:	No applicable information available. No applicable information available.
Vapour density:	Heavier than air.
Partitioning coefficient n-octanol/water (log Pow):	not applicable for mixtures
Thermal decomposition:	No decomposition if stored and handled as prescribed/indicated.
Viscosity, dynamic:	No applicable information available.
Viscosity, kinematic:	6.0 mm ² /s (20 °C)
Solubility in water:	practically insoluble
Miscibility with water:	immiscible
Solubility (quantitative):	No applicable information available.
Solubility (qualitative):	No applicable information available.
Molar mass:	No applicable information available.
Evaporation rate:	No applicable information available.

10. Stability and Reactivity

Reactivity

No hazardous reactions if stored and handled as prescribed/indicated.

Oxidizing properties:
not fire-propagating

Chemical stability

The product is stable if stored and handled as prescribed/indicated.

Possibility of hazardous reactions

No hazardous reactions when stored and handled according to instructions.

Conditions to avoid

Avoid all sources of ignition: heat, sparks, open flame. Avoid heat. Avoid direct sunlight.

Safety Data Sheet

Naftoseal MC-780 C-60 Base (BULK)

Revision date: 2024/01/10
Version: 6.0

Page: 8/12
(30691277/SDS_GEN_US/EN)

Incompatible materials

Keep away from highly acidic or alkaline substances as well as oxidants in order to prevent exothermic reactions.

Hazardous decomposition products

Decomposition products:

When exposed to high temperatures hazardous decomposition products such as carbon monoxide, carbon dioxide, smoke, oxides of nitrogen may be produced., No hazardous decomposition products if stored and handled as prescribed/indicated.

Thermal decomposition:

No decomposition if stored and handled as prescribed/indicated.

11. Toxicological information

Primary routes of exposure

Routes of entry for solids and liquids are ingestion and inhalation, but may include eye or skin contact. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquefied gases.

Acute Toxicity/Effects

Acute toxicity

Assessment of acute toxicity: Based on available data, the classification criteria are not met.

Oral

Type of value: ATE

Value: > 2,000 mg/kg

The product has not been tested. The statement has been derived from the properties of the individual components.

Inhalation

Type of value: ATE

Value: 551 mg/l

The product has not been tested. The statement has been derived from the properties of the individual components.

Dermal

Type of value: ATE

Value: > 2,000 mg/kg

The product has not been tested. The statement has been derived from the properties of the individual components.

Assessment other acute effects

Assessment of STOT single:

Based on available data, the classification criteria are not met.

Irritation / corrosion

Assessment of irritating effects: Based on available data, the classification criteria are not met.

Information on: ethylbenzene

Safety Data Sheet

Naftoseal MC-780 C-60 Base (BULK)

Revision date: 2024/01/10
Version: 6.0

Page: 9/12
(30691277/SDS_GEN_US/EN)

Assessment of irritating effects: May cause slight irritation to the skin. May cause slight irritation to the eyes.

Information on: Xylene

Assessment of irritating effects: Skin contact causes irritation. Eye contact causes irritation.

Sensitization

Assessment of sensitization: Based on available data, the classification criteria are not met.

Aspiration Hazard

No aspiration hazard expected.

Chronic Toxicity/Effects

Repeated dose toxicity

Assessment of repeated dose toxicity: Repeated exposure may affect certain organs.

Information on: ethylbenzene

Assessment of repeated dose toxicity: The substance may cause damage to the liver after repeated ingestion of high doses, as shown in animal studies. The substance may cause deafness after repeated inhalation. The substance may cause deafness after repeated ingestion.

Information on: Xylene

Assessment of repeated dose toxicity: Overexposure may cause liver and kidney toxicity.

Repeated exposure may affect certain organs. Damages the central nerve system. The substance can cause changes in the following organs after repeated exposure to large quantities: Liver Kidney

Genetic toxicity

Assessment of mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity

Assessment of carcinogenicity: Based on available data, the classification criteria are not met.

Information on: ethylbenzene

Assessment of carcinogenicity: Indication of possible carcinogenic effect in animal tests. The effect is caused by an animal specific mechanism that has no human counter part. A clear indication of an increased risk of cancer in humans has so far not been shown. IARC (International Agency for Research on Cancer) has classified this substance as group 2B (The agent is possibly carcinogenic to humans).

Reproductive toxicity

Assessment of reproduction toxicity: Based on available data, the classification criteria are not met.

Teratogenicity

Assessment of teratogenicity: Based on available data, the classification criteria are not met.

12. Ecological Information

Toxicity

Safety Data Sheet

Naftoseal MC-780 C-60 Base (BULK)

Revision date: 2024/01/10
Version: 6.0

Page: 10/12
(30691277/SDS_GEN_US/EN)

Aquatic toxicity

Assessment of aquatic toxicity:

Harmful to aquatic life. Harmful to aquatic life with long lasting effects. There are no test results available for this product. Do not allow to enter drains or waterways.

Persistence and degradability

Assessment biodegradation and elimination (H2O)

No data available concerning biodegradation and elimination.

Bioaccumulative potential

Bioaccumulation potential

No data available.

Mobility in soil

Assessment transport between environmental compartments

No data available.

13. Disposal considerations

Waste disposal of substance:

Do not discharge into drains/surface waters/groundwater. Observe national and local legal requirements.

Container disposal:

Contaminated packaging should be emptied as far as possible and disposed of in the same manner as the substance/product.

14. Transport Information

Land transport

USDOT

Hazard class: 3
Packing group: III
ID number: UN 1133
Hazard label: 3
Proper shipping name: ADHESIVES

Sea transport

IMDG

Hazard class: 3
Packing group: III
ID number: UN 1133
Hazard label: 3
Marine pollutant: NO
Proper shipping name: ADHESIVES

Air transport

IATA/ICAO

Hazard class: 3
Packing group: III
ID number: UN 1133

Safety Data Sheet

Naftoseal MC-780 C-60 Base (BULK)

Revision date: 2024/01/10
Version: 6.0

Page: 11/12
(30691277/SDS_GEN_US/EN)

Hazard label: 3
Proper shipping name: ADHESIVES

Further information

Not dangerous goods of class 3 in packages up to 450 litres capacity (valid for ADR, ADNR, RID, TDG and USDOT).

15. Regulatory Information

Federal Regulations

Registration status:

Chemical TSCA, US released / listed

EPCRA 311/312 (Hazard categories): Refer to SDS section 2 for GHS hazard classes applicable for this product.

EPCRA 313:

<u>CAS Number</u>	Chemical name
1330-20-7	Xylene
100-41-4	ethylbenzene

<u>CERCLA RQ</u>	<u>CAS Number</u>	<u>Chemical name</u>
100 LBS	1330-20-7	Xylene

State regulations

<u>State RTK</u>	<u>CAS Number</u>	<u>Chemical name</u>
NJ	1330-20-7	Xylene
	100-41-4	ethylbenzene
	471-34-1	Calcium carbonate
PA	50-00-0	Formaldehyde
	100-41-4	ethylbenzene
	471-34-1	Calcium carbonate
	1330-20-7	Xylene

Safe Drinking Water & Toxic Enforcement Act, CA Prop. 65:

WARNING: This product can expose you to chemicals including ETHYLBENZENE, which is known to the State of California to cause cancer. For more information, go to www.P65Warnings.ca.gov.

NFPA Hazard codes:

Health: 2 Fire: 2 Reactivity: 1 Special:

HMIS III rating

Health: 2⁺ Flammability: 2 Physical hazard: 1

16. Other Information

SDS Prepared by:

Chemetall (now part of BASF Group) NA Product Regulations
SDS Prepared on: 2024/01/10

Safety Data Sheet

Naftoseal MC-780 C-60 Base (BULK)

Revision date: 2024/01/10

Version: 6.0

Page: 12/12

(30691277/SDS_GEN_US/EN)

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.
END OF DATA SHEET

Safety Data Sheet

Naftoseal MC-780 C-60 Hardener (BULK)

Revision date : 2024/01/10
Version: 6.0

Page: 1/11
(30737273/SDS_GEN_US/EN)

1. Identification

Product identifier used on the label

Naftoseal MC-780 C-60 Hardener (BULK)

Recommended use of the chemical and restriction on use

Recommended use*: Hardener for coating materials or adhesives for industrial or professional use
Unsuitable for use: Uses other than recommended

* The "Recommended use" identified for this product is provided solely to comply with a Federal requirement and is not part of the seller's published specification. The terms of this Safety Data Sheet (SDS) do not create or infer any warranty, express or implied, including by incorporation into or reference in the seller's sales agreement.

Details of the supplier of the safety data sheet

Company:
Chemetall U.S., Inc.
675 Central Avenue
New Providence, NJ 07974 – USA
+1 800 526-4473
sds.na-chemetall@basf.com

Emergency telephone number

24 Hour Emergency Response Information
CHEMTREC: 800-424-9300, +1-703-527-3887

Other means of identification

Chemical family: inorganic compounds, organic compounds

2. Hazards Identification

According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

Classification of the product

Acute Tox.	4 (oral)	Acute toxicity
Skin Corr./Irrit.	2	Skin corrosion/irritation
Eye Dam./Irrit.	1	Serious eye damage/eye irritation
Resp. Sens.	1	Respiratory sensitization
Skin Sens.	1	Skin sensitization
STOT RE	1	Specific target organ toxicity — repeated

Safety Data Sheet

Naftoseal MC-780 C-60 Hardener (BULK)

Revision date: 2024/01/10
Version: 6.0

Page: 2/11
(30737273/SDS_GEN_US/EN)

exposure

Label elements

Pictogram:



Signal Word:
Danger

Hazard Statement:

H302	Harmful if swallowed.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H372	Causes damage to organs (Central nervous system) through prolonged or repeated exposure.

Precautionary Statements (Prevention):

P280	Wear protective gloves, protective clothing and eye protection or face protection.
P272	Contaminated work clothing should not be allowed out of the workplace.
P270	Do not eat, drink or smoke when using this product.
P264	Wash contaminated body parts thoroughly after handling.
P260	Do not breathe mist or vapour or spray.

Precautionary Statements (Response):

P314	Get medical advice/attention if you feel unwell.
P342 + P311	If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P330	Rinse mouth.
P333 + P313	If skin irritation or rash occurs: Get medical attention.
P310	Immediately call a POISON CENTER or physician.
P362 + P364	Take off contaminated clothing and wash it before reuse.
P302 + P352	IF ON SKIN: Wash with plenty of soap and water.

Precautionary Statements (Disposal):

P501	Dispose of contents and container to hazardous or special waste collection point.
------	---

Hazards not otherwise classified

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

Safety Data Sheet

Naftoseal MC-780 C-60 Hardener (BULK)

Revision date: 2024/01/10

Version: 6.0

Page: 3/11

(30737273/SDS_GEN_US/EN)

3. Composition / Information on Ingredients

According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

manganese dioxide

CAS Number: 1313-13-9

Content (W/W): ≥ 25.0 - $< 50.0\%$

Synonym: Manganese dioxide

phthalic anhydride

CAS Number: 85-44-9

Content (W/W): ≥ 5.0 - $< 7.0\%$

Synonym: 1,3-Isobenzofurandione; Phthalic anhydride

Ethoxylated Nonylphenolphosphate

CAS Number: 68412-53-3

Content (W/W): ≥ 1.0 - $< 3.0\%$

Synonym: No data available.

tetrakis(phenylmethyl)thioperoxydi(carbothioamide)

CAS Number: 10591-85-2

Content (W/W): ≥ 1.0 - $< 3.0\%$

Synonym: Tetrakis(phenylmethyl)thioperoxydi(carbothioamid)

4. First-Aid Measures

Description of first aid measures

General advice:

In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.

If inhaled:

Remove the affected individual into fresh air and keep the person calm. If symptoms persist, seek medical advice. If breathing is irregular or stopped, administer artificial respiration.

If on skin:

If symptoms persist, seek medical advice. Remove contaminated clothing. Wash skin with soap and water, rinse abundantly. Do NOT use solvents or thinners.

If in eyes:

Remove contact lenses, if present. Immediately wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist. Immediate medical attention required.

If swallowed:

Summon medical aid without delay. Do not induce vomiting due to aspiration hazard. Rinse mouth immediately with water. Keep at rest.

Most important symptoms and effects, both acute and delayed

Safety Data Sheet

Naftoseal MC-780 C-60 Hardener (BULK)

Revision date: 2024/01/10
Version: 6.0

Page: 4/11
(30737273/SDS_GEN_US/EN)

Symptoms: Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11.

Information on: phthalic anhydride

Symptoms: Overexposure may cause: asthma, atrophy of the nasal mucosa, bloody diarrhea, bronchitis, conjunctivitis, hoarseness, emphysema, coughing

Information on: manganese dioxide

Symptoms: Overexposure may cause: dyspnea, pneumonitis, fever, coughing

Indication of any immediate medical attention and special treatment needed

Note to physician

Antidote: No known specific antidote.
Treatment: Symptomatic treatment (decontamination, vital functions).

5. Fire-Fighting Measures

Extinguishing media

Suitable extinguishing media:
carbon dioxide, alcohol-resistant foam, dry powder, water spray

Unsuitable extinguishing media for safety reasons:
water jet

Special hazards arising from the substance or mixture

Hazards during fire-fighting:
carbon oxides, sulfur oxides
Fire will produce dense black smoke. Inhalation of dangerous decomposition products may cause serious damage to health.

Advice for fire-fighters

Protective equipment for fire-fighting:
Appropriate breathing apparatus may be required.

Further information:

Cool closed containers in the vicinity of the source of fire. Dispose of fire debris and contaminated extinguishing water in accordance with official regulations. Product itself is non-combustible; fire extinguishing method of surrounding areas must be considered. Collect contaminated extinguishing water separately, do not allow to reach sewage or effluent systems.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Avoid breathing vapours. For non-emergency personnel: Use personal protective clothing. Ensure adequate ventilation. Keep away from sources of ignition. For emergency responders: Advice on product handling can be found in sections 7 and 8 of this safety data sheet. Information regarding personal protective measures, see section 8.

Safety Data Sheet

Naftoseal MC-780 C-60 Hardener (BULK)

Revision date: 2024/01/10

Version: 6.0

Page: 5/11

(30737273/SDS_GEN_US/EN)

Environmental precautions

Do not allow to enter drains or waterways. Do not discharge into the subsoil/soil. If the product enters drains or sewers, the local water company should be contacted immediately; in the case of contamination of streams, rivers or lakes, the Environment Agency.

Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in a suitable container for disposal according with the waste regulations (see section 13). Clean preferably with a detergent; avoid the use of solvents. Ensure adequate ventilation.

7. Handling and Storage

Precautions for safe handling

Provide good ventilation of working area (local exhaust ventilation if necessary). Do not return residues to the storage containers. Smoking, eating and drinking are forbidden in application area. For personal protection see section 8. Comply with the health and safety at work laws. Avoid inhalation of vapour and spray mist. The workplace should be equipped with an emergency shower and eye-rinsing facility. Avoid contact with the skin, eyes and clothing. Handle in accordance with good industrial hygiene and safety practice.

Protection against fire and explosion:

Avoid all sources of ignition: heat, sparks, open flame. The relevant fire protection measures should be noted.

Conditions for safe storage, including any incompatibilities

Keep away from oxidising agents, from strongly alkaline and strongly acid materials.

Suitable materials for containers: tinned carbon steel (Tinplate), Carbon steel (Iron), Stainless steel 1.4301 (V2), Polypropylene (PP), Polyethylenetherephtalate (PET), Low density polyethylene (LDPE), High density polyethylene (HDPE), Stove-lacquer C222A/C221A, Stove-lacquer NOVOCAN S-G 500, Stove-lacquer Vitalure 745, Stove-lacquer Valspar HXR008F red, Stove-lacquer KNS L-5X, Stove-lacquer EHD0022, Stove-lacquer 79/14/3 (Müller/CH), Stove-lacquer R 78433, Stove-lacquer RDL 50

Further information on storage conditions: Keep container dry. Keep away from heat. Keep in a cool, well-ventilated place. Avoid direct sunlight. Close containers carefully once opened and store them upright in order to prevent any leakage. No smoking. No admission for unauthorised personnel. Always keep in containers of same material as the original one. Observe label precautions.

Storage stability:

Storage temperature: < 26 °C

8. Exposure Controls/Personal Protection

Components with occupational exposure limits

Safety Data Sheet

Naftoseal MC-780 C-60 Hardener (BULK)

Revision date: 2024/01/10

Version: 6.0

Page: 6/11

(30737273/SDS_GEN_US/EN)

phthalic anhydride	OSHA Z1:	PEL 2 ppm 12 mg/m ³ ;
	ACGIH, US:	TWA value 0.002 mg/m ³ Inhalable fraction and vapor ;
	ACGIH, US:	STEL value 0.005 mg/m ³ Inhalable fraction and vapor ;
	ACGIH, US:	Skin Designation Inhalable fraction and vapor ; Danger of cutaneous absorption
	ACGIH, US:	Skin Designation Inhalable fraction and vapor ; Danger of cutaneous absorption

Personal protective equipment

Respiratory protection:

Respiratory protection required if exposure limit (if available) may be exceeded

Hand protection:

Chemical resistant protective gloves (EN ISO 374-1), nitrile rubber (NBR) - 0.4 mm coating thickness, butyl rubber gloves - material thickness: 0.5 mm, Performance level 6, corresponding to a breakthrough time of >480 min according to EN ISO 374-1, The protection glove should be tested for its specific suitability (e.g. mechanical strength, product compatibility, anti-static properties)., The gloves should be replaced immediately in case of damage or signs of wear. It is recommended to use preventative skin protection (skin cream).

Eye protection:

Tightly fitting safety goggles (splash goggles) (e.g. EN 166)

Body protection:

Chemical resistant protective clothing according to DIN EN 13034 (Type 6)

General safety and hygiene measures:

Do not breathe vapour/spray. Eye wash fountains and safety showers must be easily accessible. Persons with a history of allergies, asthma, recurrent or chronic respiratory disease must not be employed in any process in which this product is used. Persons using this product should undergo lung function tests at regular intervals. Avoid contact with the skin, eyes and clothing. Handle in accordance with good industrial hygiene and safety practice. Ensure adequate ventilation. This can be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations at the workplace below the occupational exposure limits, appropriate certified respirators must be worn. Remove contaminated clothing immediately and dispose of safely. Hands and/or face should be washed before breaks and at the end of the shift. Keep separated from food stuffs and feed stocks.

9. Physical and Chemical Properties

Form:	liquid
Odour:	No data available.
Odour threshold:	No applicable information available.
Colour:	brown
pH value:	substance/mixture is non-soluble (in water)
Freezing point:	not determined
Melting point:	not determined
onset of boiling:	not determined
Boiling range:	not determined

Safety Data Sheet

Naftoseal MC-780 C-60 Hardener (BULK)

Revision date: 2024/01/10

Version: 6.0

Page: 7/11

(30737273/SDS_GEN_US/EN)

Sublimation point:	No applicable information available.
Flash point:	> 100 °C
Flammability:	not applicable
Lower explosion limit:	not determined
Upper explosion limit:	No applicable information available.
Autoignition:	not determined
Vapour pressure:	(20 °C) not determined
Density:	1.700 g/cm ³ (20 °C)
Relative density:	No applicable information available. No applicable information available.
Vapour density:	Heavier than air.
Partitioning coefficient n-octanol/water (log Pow):	not applicable for mixtures
Thermal decomposition:	No decomposition if stored and handled as prescribed/indicated.
Viscosity, dynamic:	No applicable information available.
Viscosity, kinematic:	6.0 mm ² /s (20 °C)
Solubility in water:	insoluble
Miscibility with water:	immiscible
Solubility (quantitative):	No applicable information available.
Solubility (qualitative):	No applicable information available.
Molar mass:	No applicable information available.
Evaporation rate:	No applicable information available.

10. Stability and Reactivity

Reactivity

No hazardous reactions if stored and handled as prescribed/indicated.

Oxidizing properties:
not fire-propagating

Chemical stability

The product is stable if stored and handled as prescribed/indicated.

Possibility of hazardous reactions

No hazardous reactions when stored and handled according to instructions.

Conditions to avoid

Avoid heat. Avoid direct sunlight.

Incompatible materials

Keep away from highly acidic or alkaline substances as well as oxidants in order to prevent exothermal reactions.

Hazardous decomposition products

Decomposition products:

When exposed to high temperatures hazardous decomposition products such as carbon monoxide, carbon dioxide, smoke, oxides of nitrogen may be produced., No hazardous decomposition products if stored and handled as prescribed/indicated.

Safety Data Sheet

Naftoseal MC-780 C-60 Hardener (BULK)

Revision date: 2024/01/10
Version: 6.0

Page: 8/11
(30737273/SDS_GEN_US/EN)

Thermal decomposition:
No decomposition if stored and handled as prescribed/indicated.

11. Toxicological information

Primary routes of exposure

Routes of entry for solids and liquids are ingestion and inhalation, but may include eye or skin contact. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquefied gases.

Acute Toxicity/Effects

Acute toxicity

Assessment of acute toxicity: Of moderate toxicity after single ingestion.

Oral

Type of value: ATE

Value: 983 mg/kg

The product has not been tested. The statement has been derived from the properties of the individual components.

Information on: phthalic anhydride

Type of value: LD50

Species: rat (male)

Value: 1,530 mg/kg

Inhalation

Type of value: ATE

Value: 22 mg/l

The product has not been tested. The statement has been derived from the properties of the individual components.

Dermal

Type of value: ATE

Value: > 2,000 mg/kg

The product has not been tested. The statement has been derived from the properties of the individual components.

Assessment other acute effects

Assessment of STOT single:

Based on available data, the classification criteria are not met.

Irritation / corrosion

Assessment of irritating effects: Skin contact causes irritation. May cause severe damage to the eyes.

Information on: phthalic anhydride

Assessment of irritating effects: Skin contact causes irritation. May cause severe damage to the eyes. EU-classification

Sensitization

Safety Data Sheet

Naftoseal MC-780 C-60 Hardener (BULK)

Revision date: 2024/01/10
Version: 6.0

Page: 9/11
(30737273/SDS_GEN_US/EN)

Assessment of sensitization: The substance may cause sensitization of the respiratory tract. Sensitization after skin contact possible.

Information on: phthalic anhydride

Assessment of sensitization:

The substance may cause sensitization of the respiratory tract. Sensitization after skin contact possible.

Aspiration Hazard

No aspiration hazard expected.

Chronic Toxicity/Effects

Repeated dose toxicity

Assessment of repeated dose toxicity: Based on available data, the classification criteria are not met.

Information on: manganese dioxide

Assessment of repeated dose toxicity: The substance may cause damage to the central nervous system after repeated inhalation.

Genetic toxicity

Assessment of mutagenicity: Based on available data, the classification criteria are not met.

Information on: manganese dioxide

Assessment of mutagenicity: The substance was not mutagenic in bacteria. The substance was mutagenic in a mammalian cell culture test system. The substance was not mutagenic in a test with mammals.

Carcinogenicity

Assessment of carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity

Assessment of reproduction toxicity: Based on available data, the classification criteria are not met.

Teratogenicity

Assessment of teratogenicity: Based on available data, the classification criteria are not met.

12. Ecological Information

Toxicity

Aquatic toxicity

Assessment of aquatic toxicity:

There are no test results available for this product. Do not allow to enter drains or waterways. Based on available data, the classification criteria are not met.

Persistence and degradability

Assessment biodegradation and elimination (H₂O)

Safety Data Sheet

Naftoseal MC-780 C-60 Hardener (BULK)

Revision date: 2024/01/10
Version: 6.0

Page: 10/11
(30737273/SDS_GEN_US/EN)

No data available concerning biodegradation and elimination.

Bioaccumulative potential

Bioaccumulation potential
No data available.

Mobility in soil

Assessment transport between environmental compartments
No data available.

13. Disposal considerations

Waste disposal of substance:

Do not discharge into drains/surface waters/groundwater. Observe national and local legal requirements.

Container disposal:

Contaminated packaging should be emptied as far as possible and disposed of in the same manner as the substance/product.

14. Transport Information

Land transport

USDOT

Not classified as a dangerous good under transport regulations

Sea transport

IMDG

Not classified as a dangerous good under transport regulations

Air transport

IATA/ICAO

Not classified as a dangerous good under transport regulations

15. Regulatory Information

Federal Regulations

Registration status:

Chemical TSCA, US released / listed

EPCRA 311/312 (Hazard categories): Refer to SDS section 2 for GHS hazard classes applicable for this product.

EPCRA 313:

CAS Number

85-44-9

1313-13-9

68412-53-3

Chemical name

phthalic anhydride

manganese dioxide

Ethoxylated Nonylphenolphosphate

Safety Data Sheet

Naftoseal MC-780 C-60 Hardener (BULK)

Revision date: 2024/01/10

Version: 6.0

Page: 11/11

(30737273/SDS_GEN_US/EN)

State regulations

State RTK

NJ

CAS Number

85-44-9

1313-13-9

PA

85-44-9

1313-13-9

68515-40-2

Chemical name

phthalic anhydride

manganese dioxide

phthalic anhydride

manganese dioxide

Benzyl-octyl-phthalate

NFPA Hazard codes:

Health: 3

Fire: 1

Reactivity: 1

Special:

HMIS III rating

Health: 3 α

Flammability: 1

Physical hazard: 1

16. Other Information

SDS Prepared by:

Chemetall (now part of BASF Group) NA Product Regulations

SDS Prepared on: 2024/01/10

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.
END OF DATA SHEET