

**1 Identification****Product identifier:** DP407761**Trade name:** Foam Spray Adhesive 79 Fast and Strong**Article number:** 100079**Application of the substance / the mixture** Adhesive**Details of the supplier of the safety data sheet**  
**Manufacturer/Supplier:****Delaware Paint Company**  
**8455 Rausch Dr.**  
**Plain City, Ohio 43064 USA****Information department:**  
740-368-9981**Emergency telephone number:**  
Chemtel: 1-800-255-3924  
#MIS8662760**2 Hazard(s) identification****Classification of the substance or mixture**

GHS02 Flame

Flam. Aerosol 1 H222 Extremely flammable aerosol.



GHS08 Health hazard

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

**Label elements****GHS label elements**

The product is classified and labeled according to the CLP regulation.

**GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

**Hazard pictograms**

GHS02



GHS07



GHS08

**Signal word** Danger**Hazard-determining components of labeling:**

hexane (containing &lt; 5 % n-hexane (203-777-6))

Methylacetat

heptane

ethyl acetate

# Safety Data Sheet

acc. to OSHA HCS

Printing date 01/16/2019

Reviewed on 10/23/2018

**Trade name: Foam Spray Adhesive Fast and Strong 79**

(Contd. of page 1)

**Hazard statements**

H222 Extremely flammable aerosol.  
 H315 Causes skin irritation.  
 H319 Causes serious eye irritation.  
 H336 May cause drowsiness or dizziness.  
 H304 May be fatal if swallowed and enters airways.

**Precautionary statements**

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
 P211 Do not spray on an open flame or other ignition source.  
 P251 Pressurized container: Do not pierce or burn, even after use.  
 P261 Avoid breathing dust/fume/gas/mist/vapors/spray  
 P264 Wash thoroughly after handling.  
 P271 Use only outdoors or in a well-ventilated area.  
 P280 Wear protective gloves / eye protection / face protection.  
 P301+P310 If swallowed: Immediately call a poison center/doctor.  
 P321 Specific treatment (see on this label).  
 P331 Do NOT induce vomiting.  
 P302+P352 If on skin: Wash with plenty of water.  
 P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
 P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 P312 Call a poison center/doctor if you feel unwell.  
 P362+P364 Take off contaminated clothing and wash it before reuse.  
 P332+P313 If skin irritation occurs: Get medical advice/attention.  
 P337+P313 If eye irritation persists: Get medical advice/attention.  
 P403+P233 Store in a well-ventilated place. Keep container tightly closed.  
 P405 Store locked up.  
 P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.  
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

**Classification system:****NFPA ratings (scale 0 - 4)**

Health = 2  
 Fire = 4  
 Reactivity = 3

**HMIS-ratings (scale 0 - 4)**

HEALTH 2 Health = 2  
 FIRE 4 Fire = 4  
 REACTIVITY 3 Reactivity = 3

**Other hazards****Results of PBT and vPvB assessment** Not applicable.**PBT:** Not applicable.**vPvB:** Not applicable.

## 3 Composition/information on ingredients

**Chemical characterization: Mixtures****Description:**

Mixture of the substances listed below with nonhazardous additions.  
 Active substance with propellant

**Dangerous components:**

|          |  |          |
|----------|--|----------|
| 115-10-6 | Dimethylether                                  | 25-75%   |
| 107-83-5 | hexane (containing < 5 % n-hexane (203-777-6)) | ≥10-<20% |

(Contd. on page 3)

US

# Safety Data Sheet

acc. to OSHA HCS

Printing date 01/16/2019

Reviewed on 10/23/2018

**Trade name: Foam Spray Adhesive Fast and Strong 79**

(Contd. of page 2)

|          |               |      |
|----------|---------------|------|
| 79-20-9  | Methylacetat  | <10% |
| 141-78-6 | ethyl acetate | <3%  |

## 4 First-aid measures

### Description of first aid measures

**General information:** Immediately remove any clothing soiled by the product.

**After inhalation:** In case of unconsciousness place patient stably in side position for transportation.

**After skin contact:** Immediately wash with water and soap and rinse thoroughly.

**After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

**Information for doctor:**

**Most important symptoms and effects, both acute and delayed** No further relevant information available.

**Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

## 5 Fire-fighting measures

### Extinguishing media

**Suitable extinguishing agents:**

CO<sub>2</sub>, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

**Special hazards arising from the substance or mixture** No further relevant information available.

**Advice for firefighters**

**Protective equipment:** Wear self-contained respiratory protective device.

## 6 Accidental release measures

### Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

**Environmental precautions:** Do not allow to enter sewers/ surface or ground water.

**Methods and material for containment and cleaning up:**

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

No special measures required.

**Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

**Protective Action Criteria for Chemicals**

#### PAC-1:

|           |  |                      |
|-----------|--|----------------------|
| 107-83-5  | hexane (containing < 5 % n-hexane (203-777-6)) | 1,000 ppm            |
| 9003-53-6 | Polystyrene                                    | 85 mg/m <sup>3</sup> |

#### PAC-2:

|           |  |                       |
|-----------|--|-----------------------|
| 107-83-5  | hexane (containing < 5 % n-hexane (203-777-6)) | 11000** ppm           |
| 9003-53-6 | Polystyrene                                    | 550 mg/m <sup>3</sup> |

#### PAC-3:

|           |  |                         |
|-----------|--|-------------------------|
| 107-83-5  | hexane (containing < 5 % n-hexane (203-777-6)) | 66000*** ppm            |
| 9003-53-6 | Polystyrene                                    | 4,700 mg/m <sup>3</sup> |

(Contd. on page 4)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 01/16/2019

Reviewed on 10/23/2018

Trade name: Foam Spray Adhesive Fast and Strong 79

(Contd. of page 3)

## 7 Handling and storage

### Handling:

**Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace.

### Information about protection against explosions and fires:

Do not spray on a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

### Conditions for safe storage, including any incompatibilities

#### Storage:

#### Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings with pressurized containers.

**Information about storage in one common storage facility:** Not required.

**Further information about storage conditions:** Keep receptacle tightly sealed.

**Storage class:** 2 B

**Specific end use(s)** No further relevant information available.

## 8 Exposure controls/personal protection

**Additional information about design of technical systems:** No further data; see item 7.

### Control parameters

#### Components with limit values that require monitoring at the workplace:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the remaining constituent has no known exposure limits.

#### 107-83-5 hexane (containing < 5 % n-hexane (203-777-6))

REL Long-term value: 350 mg/m<sup>3</sup>, 100 ppm  
Ceiling limit value: 1800\* mg/m<sup>3</sup>, 510\* ppm  
\*15-min

TLV Short-term value: 3500 mg/m<sup>3</sup>, 1000 ppm  
Long-term value: 1760 mg/m<sup>3</sup>, 500 ppm

#### 79-20-9 Methylacetat

PEL Long-term value: 610 mg/m<sup>3</sup>, 200 ppm

REL Short-term value: 760 mg/m<sup>3</sup>, 250 ppm  
Long-term value: 610 mg/m<sup>3</sup>, 200 ppm

TLV Short-term value: 757 mg/m<sup>3</sup>, 250 ppm  
Long-term value: 606 mg/m<sup>3</sup>, 200 ppm

#### 141-78-6 ethyl acetate

PEL Long-term value: 1400 mg/m<sup>3</sup>, 400 ppm

REL Long-term value: 1400 mg/m<sup>3</sup>, 400 ppm

TLV Long-term value: 1440 mg/m<sup>3</sup>, 400 ppm

**Additional information:** The lists that were valid during the creation were used as basis.

### Exposure controls

#### Personal protective equipment:

#### General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

**Breathing equipment:** Not required.

#### Protection of hands:

Protective gloves

(Contd. on page 5)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 01/16/2019

Reviewed on 10/23/2018

**Trade name: Foam Spray Adhesive Fast and Strong 79**

(Contd. of page 4)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

**Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

**Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

**For the permanent contact in work areas without heightened risk of injury (e.g. Laboratory) gloves made of the following material are suitable:**

Butyl rubber, BR

Nitrile rubber, NBR

**For the permanent contact gloves made of the following materials are suitable: Butyl rubber, BR**

**For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:**

Nitrile rubber, NBR

Chloroprene rubber, CR

**Eye protection:**

Safety glasses

Tightly sealed goggles

## 9 Physical and chemical properties

**Information on basic physical and chemical properties**

**General Information**

**Appearance:**

|               |           |
|---------------|-----------|
| <b>Form:</b>  | Aerosol   |
| <b>Color:</b> | Colorless |
| <b>Odor:</b>  | Mild      |

**Change in condition**

**Boiling point/Boiling range:** 57 °C (134.6 °F)  
Not applicable, as aerosol.

**Flash point:** -97 °C (-142.6 °F)

**Ignition temperature:** 235 °C (455 °F)

**Danger of explosion:** Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

**Explosion limits:**

**Lower:** 2.7 Vol %  
**Upper:** 32 Vol %

**Vapor pressure at 20 °C (68 °F):** 5 hPa (3.8 mm Hg)

**Density at 20 °C (68 °F):** 0.77 g/cm<sup>3</sup> (6.43 lbs/gal)

**Solubility in / Miscibility with**

**Water:** Not miscible or difficult to mix.  
**Organic solvents:** 79.1 %  
**VOC content:** 69.45 %  
581.1 g/l / 4.85 lb/gal

(Contd. on page 6)

US

# Safety Data Sheet

acc. to OSHA HCS

Printing date 01/16/2019

Reviewed on 10/23/2018

**Trade name: Foam Spray Adhesive Fast and Strong 79**

(Contd. of page 5)

**Other information** No further relevant information available.

## 10 Stability and reactivity

**Reactivity** No further relevant information available.

**Chemical stability**

**Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.

**Possibility of hazardous reactions** No dangerous reactions known.

**Conditions to avoid** No further relevant information available.

**Incompatible materials:** No further relevant information available.

**Hazardous decomposition products:** No dangerous decomposition products known.

## 11 Toxicological information

**Information on toxicological effects**

**Acute toxicity:**

**Primary irritant effect:**

**on the skin:** Irritant to skin and mucous membranes.

**on the eye:** Irritating effect.

**Sensitization:** No sensitizing effects known.

**Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

Irritant

**Carcinogenic categories**

**IARC (International Agency for Research on Cancer)**

|           |                                |   |
|-----------|--------------------------------|---|
| 9003-53-6 | Polystyrene                    | 3 |
| 9003-55-8 | Styrol-Butadien-Styrol Polymer | 3 |
| 67-63-0   | propan-2-ol                    | 3 |

**NTP (National Toxicology Program)**

None of the ingredients is listed.

**OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

## 12 Ecological information

**Toxicity**

**Aquatic toxicity:** No further relevant information available.

**Persistence and degradability** No further relevant information available.

**Behavior in environmental systems:**

**Bioaccumulative potential** No further relevant information available.

**Mobility in soil** No further relevant information available.

**Additional ecological information:**

**General notes:**

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

**Results of PBT and vPvB assessment** Not applicable.

**Other adverse effects** No further relevant information available.

-US

(Contd. on page 7)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 01/16/2019

Reviewed on 10/23/2018

**Trade name: Foam Spray Adhesive Fast and Strong 79**

(Contd. of page 6)

## 13 Disposal considerations

### Waste treatment methods

#### Recommendation:

Smaller quantities can be disposed of with household waste.

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

#### Uncleaned packagings:

Recommendation: Disposal must be made according to official regulations.

## \* 14 Transport information

### UN-Number

DOT, ADR, IMDG, IATA

UN1950

### UN proper shipping name

DOT

Aerosols, flammable

ADR

1950 AEROSOLS

IMDG

AEROSOLS, MARINE POLLUTANT

IATA

AEROSOLS, flammable

### Transport hazard class(es)

DOT



Class

2.1

Label

2.1

ADR



Class

2.5F Gases

Label

2.1

IMDG



Class

2.1

Label

2.1

IATA



Class

2.1

Label

2.1

### Packing group

DOT, ADR, IMDG, IATA

Void

(Contd. on page 8)

US

# Safety Data Sheet

acc. to OSHA HCS

Printing date 01/16/2019

Reviewed on 10/23/2018

**Trade name: Foam Spray Adhesive Fast and Strong 79**

(Contd. of page 7)

|  |   |
|--|---|
| <b>Environmental hazards:</b>  | Product contains environmentally hazardous substances:<br>hexane (containing < 5 % n-hexane (203-777-6))  |
| <b>Marine pollutant:</b>   | Yes<br>Symbol (fish and tree)   |
| <b>Special precautions for user</b>  | Warning: Gases  |
| <b>Danger code (Kemler):</b>   | -   |
| <b>EMS Number:</b>   | F-D,S-U   |
| <b>Stowage Code</b>  | SW1 Protected from sources of heat.<br>SW22 For AEROSOLS with a maximum capacity of 1 litre:<br>Category A. For AEROSOLS with a capacity above 1 litre:<br>Category B. For WASTE AEROSOLS: Category C, Clear of<br>living quarters.   |
| <b>Segregation Code</b>  | SG69 For AEROSOLS with a maximum capacity of 1 litre:<br>Segregation as for class 9. Stow "separated from" class 1 except<br>for division 1.4. For AEROSOLS with a capacity above 1 litre:<br>Segregation as for the appropriate subdivision of class 2. For<br>WASTE AEROSOLS: Segregation as for the appropriate<br>subdivision of class 2. |
| <b>Transport in bulk according to Annex II of<br/>MARPOL73/78 and the IBC Code</b> | Not applicable.   |
| <b>Transport/Additional information:</b>   |   |
| <b>ADR</b>   |   |
| <b>Excepted quantities (EQ)</b>  | Code: E0<br>Not permitted as Excepted Quantity  |
| <b>IMDG</b>  |   |
| <b>Limited quantities (LQ)</b>   | 1L  |
| <b>Excepted quantities (EQ)</b>  | Code: E0<br>Not permitted as Excepted Quantity  |
| <b>UN "Model Regulation":</b>  | UN 1950 AEROSOLS, 2.1   |

## 15 Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture  
Sara

### Section 355 (extremely hazardous substances):

None of the ingredients is listed.

### Section 313 (Specific toxic chemical listings):

67-63-0 propan-2-ol

### TSCA (Toxic Substances Control Act):

107-83-5 hexane (containing < 5 % n-hexane (203-777-6))

88526-47-0 Polymeres Bindemittel

25133-97-5 ACRYLATES COPOLYMER

9003-53-6 Polystyrene

9003-55-8 Styrol-Butadien-Styrol Polymer

heptane

### TSCA new (21st Century Act) (Substances not listed)

115-10-6 Dimethylether

79-20-9 Methylacetat

141-78-6 ethyl acetate

(Contd. on page 9)



# Safety Data Sheet

acc. to OSHA HCS

Printing date 01/16/2019

Reviewed on 10/23/2018

**Trade name: Foam Spray Adhesive Fast and Strong 79**

(Contd. of page 8)

**Proposition 65****Chemicals known to cause cancer:**

None of the ingredients is listed.

**Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

**Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

**Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

**Carcinogenic categories****EPA (Environmental Protection Agency)**

heptane

D

**TLV (Threshold Limit Value established by ACGIH)**

67-63-0 propan-2-ol

A4

**NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

**Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

## 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

**Department issuing SDS:** Abteilung Produktsicherheit**Contact:** Hr. Dr. Pohle**Date of preparation / last revision** 01/16/2019 / 1.2**Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety &amp; Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Flam. Aerosol 1: Aerosols – Category 1

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Asp. Tox. 1: Aspiration hazard – Category 1

**\* Data compared to the previous version altered.**