



Safety Data Sheet according to (EC) No 1907/2006 as amended

Page 1 of 18

LOCTITE SF 7400 known as LOCTITE 7400 20ml Blist. M/L

SDS No. : 290260
V009.2

Revision: 26.07.2024

printing date: 03.12.2024

Replaces version from: 05.09.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

LOCTITE SF 7400 known as LOCTITE 7400 20ml Blist. M/L
UFI: GJ5E-6WGA-E200-A4UT

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:
Coating

1.3. Details of the supplier of the safety data sheet

Henkel Ltd
Adhesives
Wood Lane End
HP2 4RQ Hemel Hempstead

Great Britain

Phone: +44 (1442) 278000

For Safety Data Sheet updates please visit our website www.mysds.henkel.com or www.henkel-adhesives.com.

1.4. Emergency telephone number

24 Hours Emergency Tel: +44 (0)1442 278497

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (CLP):

Flammable liquids	Category 2
H225 Highly flammable liquid and vapour.	
Serious eye irritation	Category 2
H319 Causes serious eye irritation.	
Carcinogenicity	Category 2
H351 Suspected of causing cancer.	
Specific target organ toxicity - single exposure	Category 3
H336 May cause drowsiness or dizziness.	
Target organ: Central nervous system	

2.2. Label elements

Label elements (CLP):

Hazard pictogram:



Contains

4-methylpentan-2-one

n-butyl acetate

Signal word:

Danger

Hazard statement:

H225 Highly flammable liquid and vapour.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H351 Suspected of causing cancer.

Supplemental information

EUH066 Repeated exposure may cause skin dryness or cracking.

Precautionary statement:

"***" ***For consumer use only: P101 If medical advice is needed, have product container or label at hand. P102 Keep out of reach of children. P501 Dispose of contents/container in accordance with national regulation.***

**Precautionary statement:
Prevention**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.
No smoking.
P261 Avoid breathing vapors.
P280 Wear protective gloves/protective clothing.

**Precautionary statement:
Response**

P337+P313 If eye irritation persists: Get medical advice/attention.

**Precautionary statement:
Storage**

P403+P235 Store in a well-ventilated place. Keep cool.

2.3. Other hazards

None if used properly.

Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

Following substances are present in a concentration \geq the concentration limit for depiction in Section 3 and fulfill the criteria for PBT/vPvB, or were identified as endocrine disruptor (ED):

This mixture does not contain any substances in a concentration \geq the concentration limit for depiction in Section 3 that are assessed to be a PBT, vPvB or ED.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components CAS-No. EC Number REACH-Reg No.	Concentration	Classification	Specific Conc. Limits, M- factors and ATEs	Add. Information
4-methylpentan-2-one 108-10-1 203-550-1 01-2119473980-30	25- < 50 %	Acute Tox. 4, Inhalation, H332 Carc. 2, H351 Flam. Liq. 2, H225 STOT SE 3, H336 Eye Irrit. 2, H319	inhalation:ATE = 11 mg/l;vapour	EU OEL
n-butyl acetate 123-86-4 204-658-1 01-2119485493-29	25- < 50 %	Flam. Liq. 3, H226 STOT SE 3, H336		EU OEL
cellulose nitrate 9004-70-0	10- < 25 %	Expl. 1.1, H201		
2-Naphthalenol, 1-[[4-(phenylazo)phenyl]azo]-, ar-heptyl ar',ar"-Me derivs. 92257-31-3 296-120-8	0,1- < 1 %	Carc. 2, H351 Repr. 2, H361 Aquatic Chronic 4, H413 STOT RE 2, H373		

**If no ATE values are displayed, please refer to LD/LC50 values in Section 11.
For full text of the H - statements and other abbreviations see section 16 "Other information".**

SECTION 4: First aid measures**4.1. Description of first aid measures****Inhalation:**

Move to fresh air. If symptoms persist, seek medical advice.

Skin contact:

Rinse with running water and soap.

Obtain medical attention if irritation persists.

Eye contact:

Rinse immediately with plenty of running water (for 10 minutes), seek medical attention from a specialist.

Ingestion:

Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

RESPIRATORY: Irritation, coughing, shortness of breath, chest tightness.

EYE: Irritation, conjunctivitis.

Repeated exposure may cause skin dryness or cracking.

Vapors may cause drowsiness and dizziness.

4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

Carbon dioxide, foam, powder

Extinguishing media which must not be used for safety reasons:

High pressure waterjet

5.2. Special hazards arising from the substance or mixture

In the event of a fire, carbon monoxide (CO), carbon dioxide (CO₂) and nitrogen oxides (NO_x) can be released.

5.3. Advice for firefighters

Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

Additional information:

In case of fire, keep containers cool with water spray.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Wear protective equipment.

Avoid contact with skin and eyes.

Ensure adequate ventilation.

6.2. Environmental precautions

Do not empty into drains / surface water / ground water.

6.3. Methods and material for containment and cleaning up

For small spills wipe up with paper towel and place in container for disposal.

For large spills absorb onto inert absorbent material and place in sealed container for disposal.

Dispose of contaminated material as waste according to Section 13.

6.4. Reference to other sections

See advice in section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Use only in well-ventilated areas.

Vapours should be extracted to avoid inhalation.

Keep away from sources of ignition - no smoking.

Avoid skin and eye contact.

See advice in section 8

Hygiene measures:

Wash hands before work breaks and after finishing work.

Do not eat, drink or smoke while working.

Good industrial hygiene practices should be observed.

7.2. Conditions for safe storage, including any incompatibilities

Store in a cool, well-ventilated place.

Keep away from heat and direct sunlight.

Refer to Technical Data Sheet.

7.3. Specific end use(s)

Coating

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Occupational Exposure Limits**Valid for
Great Britain

Ingredient [Regulated substance]	ppm	mg/m ³	Value type	Short term exposure limit category / Remarks	Regulatory list
4-Methylpentan-2-one 108-10-1 [4-METHYLPENTAN-2-ONE]			Skin designation:	Can be absorbed through the skin.	EH40 WEL
4-Methylpentan-2-one 108-10-1 [4-METHYLPENTAN-2-ONE]	50	208	Time Weighted Average (TWA):		EH40 WEL
4-Methylpentan-2-one 108-10-1 [4-METHYLPENTAN-2-ONE]	20	83	Time Weighted Average (TWA):	Indicative	ECTLV
4-Methylpentan-2-one 108-10-1 [4-METHYLPENTAN-2-ONE]	50	208	Short Term Exposure Limit (STEL):	Indicative	ECTLV
4-Methylpentan-2-one 108-10-1 [4-METHYLPENTAN-2-ONE]	100	416	Short Term Exposure Limit (STEL):	15 minutes	EH40 WEL
n-Butyl acetate 123-86-4 [BUTYL ACETATE]	150	724	Time Weighted Average (TWA):		EH40 WEL
n-Butyl acetate 123-86-4 [N-BUTYL ACETATE]	150	723	Short Term Exposure Limit (STEL):	Indicative	ECTLV
n-Butyl acetate 123-86-4 [N-BUTYL ACETATE]	50	241	Time Weighted Average (TWA):	Indicative	ECTLV
n-Butyl acetate 123-86-4 [BUTYL ACETATE]	200	966	Short Term Exposure Limit (STEL):	15 minutes	EH40 WEL

Occupational Exposure LimitsValid for
Ireland

Ingredient [Regulated substance]	ppm	mg/m ³	Value type	Short term exposure limit category / Remarks	Regulatory list
4-Methylpentan-2-one 108-10-1 [METHYL ISOBUTYL KETONE (MIBK)]	20	83	Time Weighted Average (TWA):	Indicative OELV	IR_OEL
4-Methylpentan-2-one 108-10-1 [METHYL ISOBUTYL KETONE (MIBK)]			Skin designation:	Can be absorbed through the skin.	IR_OEL
4-Methylpentan-2-one 108-10-1 [4-METHYLPENTAN-2-ONE]	20	83	Time Weighted Average (TWA):	Indicative	ECTLV
4-Methylpentan-2-one 108-10-1 [4-METHYLPENTAN-2-ONE]	50	208	Short Term Exposure Limit (STEL):	Indicative	ECTLV
4-Methylpentan-2-one 108-10-1 [METHYL ISOBUTYL KETONE (MIBK)]	50	208	Short Term Exposure Limit (STEL):	15 minutes Indicative OELV	IR_OEL
n-Butyl acetate 123-86-4 [N-BUTYL ACETATE]	150	723	Short Term Exposure Limit (STEL):	Indicative	ECTLV
n-Butyl acetate 123-86-4 [N-BUTYL ACETATE]	50	241	Time Weighted Average (TWA):	Indicative	ECTLV
n-Butyl acetate 123-86-4 [Butyl acetate]	150	723	Short Term Exposure Limit (STEL):	15 minutes Indicative OELV	IR_OEL

n-Butyl acetate 123-86-4 [Butyl acetate]	50	241	Time Weighted Average (TWA):	Indicative OELV	IR_OEL
--	----	-----	---------------------------------	-----------------	--------

Predicted No-Effect Concentration (PNEC):

Name on list	Environmental Compartment	Exposure period	Value				Remarks
			mg/l	ppm	mg/kg	others	
4-methylpentan-2-one 108-10-1	aqua (freshwater)		0,6 mg/l				
4-methylpentan-2-one 108-10-1	aqua (marine water)		0,06 mg/l				
4-methylpentan-2-one 108-10-1	sediment (freshwater)				8,27 mg/kg		
4-methylpentan-2-one 108-10-1	sediment (marine water)				0,83 mg/kg		
4-methylpentan-2-one 108-10-1	Soil				1,3 mg/kg		
4-methylpentan-2-one 108-10-1	sewage treatment plant (STP)		27,5 mg/l				
4-methylpentan-2-one 108-10-1	aqua (intermittent releases)		1,5 mg/l				
n-Butyl acetate 123-86-4	aqua (freshwater)		0,18 mg/l				
n-Butyl acetate 123-86-4	aqua (marine water)		0,018 mg/l				
n-Butyl acetate 123-86-4	aqua (intermittent releases)		0,36 mg/l				
n-Butyl acetate 123-86-4	sewage treatment plant (STP)		35,6 mg/l				
n-Butyl acetate 123-86-4	sediment (freshwater)				0,981 mg/kg		
n-Butyl acetate 123-86-4	sediment (marine water)				0,0981 mg/kg		
n-Butyl acetate 123-86-4	Soil				0,0903 mg/kg		
n-Butyl acetate 123-86-4	Air						no hazard identified
n-Butyl acetate 123-86-4	Predator						no potential for bioaccumulation

Derived No-Effect Level (DNEL):

Name on list	Application Area	Route of Exposure	Health Effect	Exposure Time	Value	Remarks
4-methylpentan-2-one 108-10-1	Workers	Inhalation	Acute/short term exposure - systemic effects		208 mg/m ³	
4-methylpentan-2-one 108-10-1	Workers	Inhalation	Acute/short term exposure - local effects		208 mg/m ³	
4-methylpentan-2-one 108-10-1	Workers	Inhalation	Long term exposure - systemic effects		83 mg/m ³	
4-methylpentan-2-one 108-10-1	Workers	Inhalation	Long term exposure - local effects		83 mg/m ³	
4-methylpentan-2-one 108-10-1	Workers	dermal	Long term exposure - systemic effects		11,8 mg/kg	
4-methylpentan-2-one 108-10-1	General population	Inhalation	Acute/short term exposure - systemic effects		155,2 mg/m ³	
4-methylpentan-2-one 108-10-1	General population	Inhalation	Acute/short term exposure - local effects		155,2 mg/m ³	
4-methylpentan-2-one 108-10-1	General population	Inhalation	Long term exposure - systemic effects		14,7 mg/m ³	
4-methylpentan-2-one 108-10-1	General population	Inhalation	Long term exposure - local effects		14,7 mg/m ³	
4-methylpentan-2-one 108-10-1	General population	dermal	Long term exposure - systemic effects		4,2 mg/kg	
4-methylpentan-2-one 108-10-1	General population	oral	Long term exposure - systemic effects		4,2 mg/kg	
n-Butyl acetate 123-86-4	Workers	inhalation	Long term exposure - systemic effects		300 mg/m ³	no hazard identified
n-Butyl acetate 123-86-4	Workers	inhalation	Acute/short term exposure - systemic effects		600 mg/m ³	no hazard identified
n-Butyl acetate 123-86-4	Workers	inhalation	Long term exposure - local effects		300 mg/m ³	no hazard identified
n-Butyl acetate 123-86-4	Workers	inhalation	Acute/short term exposure - local effects		600 mg/m ³	no hazard identified
n-Butyl acetate 123-86-4	Workers	dermal	Long term exposure - systemic effects		11 mg/kg	no hazard identified
n-Butyl acetate 123-86-4	Workers	dermal	Acute/short term exposure - systemic effects		11 mg/kg	no hazard identified
n-Butyl acetate 123-86-4	General population	inhalation	Long term exposure - systemic effects		35,7 mg/m ³	no hazard identified
n-Butyl acetate 123-86-4	General population	inhalation	Acute/short term exposure - systemic effects		300 mg/m ³	no hazard identified
n-Butyl acetate 123-86-4	General population	inhalation	Acute/short term exposure - local effects		300 mg/m ³	no hazard identified
n-Butyl acetate 123-86-4	General population	dermal	Long term exposure - systemic effects		6 mg/kg	no hazard identified
n-Butyl acetate 123-86-4	General population	dermal	Acute/short term exposure - systemic effects		6 mg/kg	no hazard identified
n-Butyl acetate 123-86-4	General population	oral	Long term exposure -		2 mg/kg	no hazard identified

n-Butyl acetate 123-86-4	General population	oral	systemic effects Acute/short term exposure - systemic effects		2 mg/kg	no hazard identified
n-Butyl acetate 123-86-4	General population	inhalation	Long term exposure - local effects		35,7 mg/m ³	no hazard identified

Biological Exposure Indices:

Ingredient [Regulated substance]	Parameters	Biological specimen	Sampling time	Conc.	Basis of biol. exposure index	Remark	Additional Information
4-Methylpentan-2-one 108-10-1 [4-METHYLPENTAN-2-ONE]	4-methylpentan-2-one	Urine	Sampling time: End of shift.		UKEH40BMG V		

8.2. Exposure controls:

Engineering controls:
Ensure good ventilation/extraction.

Respiratory protection:
Ensure adequate ventilation.
An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly ventilated area
Filter type: A (EN 14387)

Hand protection:
Chemical-resistant protective gloves (EN 374).
Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):
nitrile rubber (NBR; >= 0.4 mm thickness)
Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):
nitrile rubber (NBR; >= 0.4 mm thickness)
This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:
Safety glasses with sideshields or chemical safety goggles should be worn if there is a risk of splashing.
Protective eye equipment should conform to EN166.

Skin protection:
Wear suitable protective clothing.
Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Advices to personal protection equipment:

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions. Personal protective equipment should conform to the relevant EN standard.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Delivery form	liquid
Colour	red
Odor	characteristic
Physical state	liquid

Melting point	Not applicable, Product is a liquid
Initial boiling point	114 - 117 °C (237.2 - 242.6 °F)
Flammability	Flammable liquid
Explosive limits	
lower	1,7 % (V);
upper	10,4 % (V);
	Upper/lower explosion limit
Flash point	14 °C (57.2 °F)
Auto-ignition temperature	370 °C (698 °F)
Decomposition temperature	Not applicable, Substance/mixture is not self-reactive, no organic peroxide and does not decompose under foreseen conditions of use
pH	Not applicable, Product is non-polar/aprotic.
Viscosity (kinematic) (20 °C (68 °F);)	1.302 mm ² /s
Solubility (qualitative) (20 °C (68 °F); Solvent: Water)	Not miscible
Partition coefficient: n-octanol/water	Not applicable
Vapour pressure (20 °C (68 °F))	Mixture
Vapour pressure (50 °C (122 °F))	10,7 mbar
Density (20 °C (68 °F))	> 10,7 mbar
Relative vapour density:	0,97 g/cm ³ None
Particle characteristics	Not available.
	Not applicable
	Product is a liquid

9.2. Other information

Other information not applicable for this product

SECTION 10: Stability and reactivity

10.1. Reactivity

Reaction with strong acids.
Reacts with strong oxidants.

10.2. Chemical stability

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

See section reactivity

10.4. Conditions to avoid

No decomposition if used according to specifications.

10.5. Incompatible materials

See section reactivity.

10.6. Hazardous decomposition products

Irritating organic vapours.

SECTION 11: Toxicological information**General toxicological information:**

Prolonged or repeated contact may cause skin irritation.

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**Acute oral toxicity:**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
4-methylpentan-2-one 108-10-1	LD50	2.080 mg/kg	rat	equivalent or similar to OECD Guideline 401 (Acute Oral Toxicity)
n-butyl acetate 123-86-4	LD50	10.760 mg/kg	rat	OECD Guideline 423 (Acute Oral toxicity)
cellulose nitrate 9004-70-0	LD50	> 5.000 mg/kg	rat	not specified
2-Naphthalenol, 1-[[4-(phenylazo)phenyl]azo]-, ar-heptyl ar',ar"-Me derivs. 92257-31-3	LD50	> 5.000 mg/kg	rat	not specified

Acute dermal toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
4-methylpentan-2-one 108-10-1	LD50	> 2.000 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)
4-methylpentan-2-one 108-10-1	LD0	>= 2.000 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)
n-butyl acetate 123-86-4	LD50	> 14.112 mg/kg	rabbit	OECD Guideline 402 (Acute Dermal Toxicity)
2-Naphthalenol, 1-[[4-(phenylazo)phenyl]azo]-, ar-heptyl ar',ar"-Me derivs. 92257-31-3	LD50	> 5.000 mg/kg	rabbit	not specified

Acute inhalative toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Test atmosphere	Exposure time	Species	Method
4-methylpentan-2-one 108-10-1	Acute toxicity estimate (ATE)	11 mg/l	vapour			Expert judgement
4-methylpentan-2-one 108-10-1	LC50	8,2 - 16,4 mg/l	vapour	4 h	rat	equivalent or similar to OECD Guideline 403 (Acute Inhalation Toxicity)
n-butyl acetate 123-86-4	LC50	> 23,4 mg/l	mist	4 h	rat	OECD Guideline 403 (Acute Inhalation Toxicity)

Skin corrosion/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
4-methylpentan-2-one 108-10-1	not irritating	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
n-butyl acetate 123-86-4	not irritating		rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)

Serious eye damage/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
4-methylpentan-2-one 108-10-1	slightly irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
n-butyl acetate 123-86-4	not irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)

Respiratory or skin sensitization:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Test type	Species	Method
4-methylpentan-2-one 108-10-1	not sensitising	Guinea pig maximisation test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
n-butyl acetate 123-86-4	not sensitising	Guinea pig maximisation test	guinea pig	not specified

Germ cell mutagenicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
4-methylpentan-2-one 108-10-1	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		equivalent or similar to OECD Guideline 471 (Bacterial Reverse Mutation Assay)
4-methylpentan-2-one 108-10-1	negative	in vitro mammalian chromosome aberration test	without		equivalent or similar to OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
4-methylpentan-2-one 108-10-1	ambiguous without metabolic activation	mammalian cell gene mutation assay	with and without		equivalent or similar to OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
n-butyl acetate 123-86-4	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
n-butyl acetate 123-86-4	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)

Carcinogenicity

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Sex	Method
4-methylpentan-2-one 108-10-1		inhalation: vapour	2 y 6 h/d, 5 d/w	rat	male/female	OECD Guideline 451 (Carcinogenicity Studies)

Reproductive toxicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Test type	Route of application	Species	Method
4-methylpentan-2-one 108-10-1		screening	oral: gavage	rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
4-methylpentan-2-one 108-10-1		One generation study	oral: gavage	rat	OECD Guideline 415 (One-Generation Reproduction Toxicity Study)
4-methylpentan-2-one 108-10-1		Two generation study	oral: gavage	rat	OECD Guideline 416 (Two-Generation Reproduction Toxicity Study)

STOT-single exposure:

No data available.

STOT-repeated exposure:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Route of application	Exposure time / Frequency of treatment	Species	Method
4-methylpentan-2-one 108-10-1	NOAEL 250 mg/kg	oral: gavage	13 w daily	rat	equivalent or similar to OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
n-butyl acetate 123-86-4	NOAEL 125 mg/kg	oral: gavage	6 (interim sacrifice) or 13 w daily	rat	EPA OTS 798.2650 (90- Day Oral Toxicity in Rodents)

Aspiration hazard:

No data available.

11.2 Information on other hazards

not applicable

SECTION 12: Ecological information**General ecological information:**

Do not empty into drains / surface water / ground water.

12.1. Toxicity**Toxicity (Fish):**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
4-methylpentan-2-one 108-10-1	LC50	600 mg/l	96 h	Salmo gairdneri (new name: Oncorhynchus mykiss)	OECD Guideline 203 (Fish, Acute Toxicity Test)
n-butyl acetate 123-86-4	LC50	18 mg/l	96 h	Pimephales promelas	OECD Guideline 203 (Fish, Acute Toxicity Test)
cellulose nitrate 9004-70-0	LC50	> 1.000 mg/l	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute Toxicity Test)

Toxicity (aquatic invertebrates):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
4-methylpentan-2-one 108-10-1	EC50	170 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
n-butyl acetate 123-86-4	EC50	44 mg/l	48 h	Daphnia sp.	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
cellulose nitrate 9004-70-0	EC50	> 1.000 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)

Chronic toxicity (aquatic invertebrates):

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
n-butyl acetate 123-86-4	NOEC	23,2 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)

Toxicity (Algae):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
4-methylpentan-2-one 108-10-1	EC50	400 mg/l	96 h	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
n-butyl acetate 123-86-4	EC50	674,7 mg/l	72 h	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)	OECD Guideline 201 (Alga, Growth Inhibition Test)
n-butyl acetate 123-86-4	EC10	295,5 mg/l	72 h	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)	OECD Guideline 201 (Alga, Growth Inhibition Test)
cellulose nitrate 9004-70-0	EC50	> 90.000 mg/l	72 h	Scenedesmus sp.	OECD Guideline 201 (Alga, Growth Inhibition Test)

Toxicity (microorganisms):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
4-methylpentan-2-one 108-10-1	EC0	275 mg/l	16 h		not specified
n-butyl acetate 123-86-4	IC50	356 mg/l	40 h	Ciliate (Tetrahymena pyriformis)	other guideline:
cellulose nitrate 9004-70-0	EC0	1.000 mg/l	30 min	not specified	not specified

12.2. Persistence and degradability

The product is not biodegradable.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Test type	Degradability	Exposure time	Method
4-methylpentan-2-one 108-10-1	readily biodegradable	aerobic	99 %	7 day	OECD Guideline 301 E (Ready biodegradability: Modified OECD Screening Test)
n-butyl acetate 123-86-4	readily biodegradable	aerobic	83 %	28 d	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)
cellulose nitrate 9004-70-0	readily biodegradable	aerobic	> 60 %	28 d	OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test)
2-Naphthalenol, 1-[[4- (phenylazo)phenyl]azo]-, ar- heptyl ar',ar''-Me derivs. 92257-31-3	not readily biodegradable.	other:	> 0 - < 60 %	28 d	QSAR (Quantitative Structure Activity Relationship)

12.3. Bioaccumulative potential

No data available.

12.4. Mobility in soil

The product evaporates readily.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	LogPow	Temperature	Method
4-methylpentan-2-one 108-10-1	1,31	20 °C	not specified
n-butyl acetate 123-86-4	2,3	25 °C	OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC Method)
2-Naphthalenol, 1-[[4-(phenylazo)phenyl]azo]-, ar-heptyl ar',ar"-Me derivs. 92257-31-3	5,14		OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)

12.5. Results of PBT and vPvB assessment

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	PBT / vPvB
4-methylpentan-2-one 108-10-1	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
n-butyl acetate 123-86-4	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
cellulose nitrate 9004-70-0	Not fulfilling PBT (persistent/bioaccumulative/toxic) criteria
2-Naphthalenol, 1-[[4-(phenylazo)phenyl]azo]-, ar-heptyl ar',ar"-Me derivs. 92257-31-3	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

12.6. Endocrine disrupting properties

not applicable

12.7. Other adverse effects

No data available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product disposal:

Dispose of in accordance with local and national regulations.

Do not empty into drains / surface water / ground water.

Disposal of uncleaned packages:

Disposal must be made according to official regulations.

After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.

Waste code

14 06 03 - other solvents and solvent mixtures

The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We will be happy to advise you.

SECTION 14: Transport information

14.1. UN number or ID number

ADR	1263
RID	1263
ADN	1263
IMDG	1263
IATA	1263

14.2. UN proper shipping name

ADR	PAINT
RID	PAINT
ADN	PAINT
IMDG	PAINT
IATA	Paint

14.3. Transport hazard class(es)

ADR	3
RID	3
ADN	3
IMDG	3
IATA	3

14.4. Packing group

ADR	II
RID	II
ADN	II
IMDG	II
IATA	II

14.5. Environmental hazards

ADR	not applicable
RID	not applicable
ADN	not applicable
IMDG	not applicable
IATA	not applicable

14.6. Special precautions for user

ADR	Special provision 640D Tunnelcode: (D/E)
RID	Special provision 640D
ADN	Special provision 640D
IMDG	not applicable
IATA	not applicable

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Ozone Depleting Substance (ODS) (Regulation (EC) No 1005/2009):	Not applicable
Prior Informed Consent (PIC) (Regulation (EU) No 649/2012):	Not applicable
Persistent organic pollutants (Regulation (EU) 2019/1021):	Not applicable

VOC content 74,7 %
(2010/75/EC)

15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text of all abbreviations indicated by codes in this safety data sheet are as follows:

H201 Explosive; mass explosion hazard.
H225 Highly flammable liquid and vapour.
H226 Flammable liquid and vapour.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H336 May cause drowsiness or dizziness.
H351 Suspected of causing cancer.
H361 Suspected of damaging fertility or the unborn child.
H373 May cause damage to organs through prolonged or repeated exposure.
H413 May cause long lasting harmful effects to aquatic life.

ED:	Substance identified as having endocrine disrupting properties
EU OEL:	Substance with a Union workplace exposure limit
EU EXPLD 1:	Substance listed in Annex I, Reg (EC) No. 2019/1148
EU EXPLD 2	Substance listed in Annex II, Reg (EC) No. 2019/1148
SVHC:	Substance of very high concern (REACH Candidate List)
PBT:	Substance fulfilling persistent, bioaccumulative and toxic criteria
PBT/vPvB:	Substance fulfilling persistent, bioaccumulative and toxic plus very persistent and very bioaccumulative criteria
vPvB:	Substance fulfilling very persistent and very bioaccumulative criteria

Further information:

This Safety Data Sheet has been produced for sales from Henkel to parties purchasing from Henkel, is based on Regulation (EC) No 1907/2006 and provides information in accordance with applicable regulations of the European Union only. In that respect, no statement, warranty or representation of any kind is given as to compliance with any statutory laws or regulations of any other jurisdiction or territory other than the European Union. When exporting to territories other than the European Union, please consult with the respective Safety Data Sheet of the concerned territory to ensure compliance or liaise with Henkel's Product Safety and Regulatory Affairs Department (SDSinfo.Adhesive@henkel.com) prior to export to other territories than the European Union.

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Dear Customer,

Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your_company.com).

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.