

D-5440NS

Page: 1

Compilation date: 28 August 2013

Revision date: 05 July 2017

Revision No: 3

### Section 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product name: D-5440NS

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: PC24: Lubricants, greases, release products.

## 1.3. Details of the supplier of the safety data sheet

Company name: Zip-Chem Products

400 Jarvis Dr. Morgan Hill California 95037 USA

Tel: (408) 782-2335
Fax: (408) 782-6304
Email: 4info@zipchem.com

## 1.4. Emergency telephone number

**Emergency tel:** 1 (800) 424-9300 (Chemtrec)

#### Section 2: Hazards identification

### 2.1. Classification of the substance or mixture

Classification under CLP: Acute Tox. 4: H302; Flam. Aerosol 1: H222; STOT SE 2: H371; -: H229

Most important adverse effects: Extremely flammable aerosol. May cause damage to organs . Pressurised container:

May burst if heated. Harmful if swallowed.

## 2.2. Label elements

Label elements:

 $\textbf{Hazard statements:} \quad \text{H222: Extremely flammable aerosol.}$ 

H371: May cause damage to organs.

H229: Pressurised container: May burst if heated

H302: Harmful if swallowed.

Hazard pictograms: GHS02: Flame

GHS07: Exclamation mark GHS08: Health hazard







D-5440NS

Page: 2

Signal words: Danger

Precautionary statements: P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P301+312: IF SWALLOWED: Call a if you feel unwell.

P211: Do not spray on an open flame or other ignition source.

P251: Do not pierce or burn, even after use.

P260: Do not breathe dust/fumes/gas/mist/vapours/spray.

P410+412: Protect from sunlight. Do not expose to temperatures exceeding 50 °C.

### 2.3. Other hazards

Other hazards: Not applicable.

PBT: This product is not identified as a PBT/vPvB substance.

## Section 3: Composition/information on ingredients

# 3.2. Mixtures

## **Hazardous ingredients:**

#### DIMETHYL ETHER

<b>EINECS</b>	CAS	PBT / WEL	CLP Classification	Percent
204-065-8	115-10-6	Substance with a Community workplace exposure limit.	Flam. Gas 1: H220; Press. Gas: H280	30-50%
METHANOL				
200-659-6	67-56-1	-	Flam. Liq. 2: H225; Acute Tox. 3: H331; Acute Tox. 3: H311; Acute Tox. 3: H301; STOT SE 1: H370	1-10%
PROPAN-2-OI	L			
200-661-7	67-63-0	-	Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336	1-10%
ISOBUTYL ISO	OBUTYRATE			
-	97-85-8	-	Flam. Liq. 3: H226; STOT SE 3: H336	1-10%

### Section 4: First aid measures

## 4.1. Description of first aid measures

**Skin contact:** Wash immediately with plenty of soap and water.

**Eye contact:** Bathe the eye with running water for 15 minutes.

Ingestion: Wash out mouth with water. Do not induce vomiting. If conscious, give half a litre of water

to drink immediately. Transfer to hospital as soon as possible.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a

doctor.

D-5440NS

Page: 3

#### 4.2. Most important symptoms and effects, both acute and delayed

**Skin contact:** There may be mild irritation at the site of contact.

**Eye contact:** There may be irritation and redness.

Ingestion: There may be soreness and redness of the mouth and throat. There may be difficulty

swallowing. Nausea and stomach pain may occur. There may be vomiting.

Inhalation: Absorption through the lungs can occur causing symptoms similar to those of ingestion.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

## 4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Not applicable.

## Section 5: Fire-fighting measures

### 5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray

to cool containers.

#### 5.2. Special hazards arising from the substance or mixture

**Exposure hazards:** In combustion emits toxic fumes.

### 5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact

with skin and eyes.

### Section 6: Accidental release measures

## 6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. Mark out the contaminated area

with signs and prevent access to unauthorised personnel. Turn leaking containers

leak-side up to prevent the escape of liquid.

#### 6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

#### 6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for

disposal by an appropriate method.

#### 6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

### Section 7: Handling and storage

D-5440NS

Page: 4

### 7.1. Precautions for safe handling

Handling requirements: Avoid the formation or spread of mists in the air. Avoid direct contact with the substance.

## 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed.

Suitable packaging: Must only be kept in original packaging.

### 7.3. Specific end use(s)

Specific end use(s): No data available.

### Section 8: Exposure controls/personal protection

## 8.1. Control parameters

### Hazardous ingredients:

### DIMETHYL ETHER

### Workplace exposure limits:

#### Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
EU	1920 mg/m3	-	-	-

#### **METHANOL**

FR	260 mg/m3	1300 mg/m3	-	-

### PROPAN-2-OL

FR	_	980 ma/m3	_	_
1 11	_	300 1119/1113	_	

## **DNEL/PNEC Values**

**DNEL / PNEC** No data available.

## 8.2. Exposure controls

**Engineering measures:** Ensure there is sufficient ventilation of the area.

Respiratory protection: Respiratory protection not required.

Hand protection: Protective gloves.

**Eye protection:** Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.Environmental: No special requirement.

## Section 9: Physical and chemical properties

## 9.1. Information on basic physical and chemical properties

State: Aerosol
Colour: White
Odour: Alcoholic

Evaporation rate: Moderate

D-5440NS

Page: 5

Oxidising: Non-oxidising (by EC criteria)

Solubility in water: Slightly soluble

Also soluble in: Methanol.

Viscosity: Non-viscous

**Boiling point/range°C:** >35 **Melting point/range°C:** No data available.

Flammability limits %: lower: No data available. upper: No data available.

Flash point°C: No data available. Part.coeff. n-octanol/water: No data available.

Autoflammability°C: No data available. Vapour pressure: No data available.

Relative density: 0.79 pH: No data available.

**VOC g/I:** 449

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

**Hazardous ingredients:** 

**METHANOL** 

17/81	DAT	I DEO	2424	ma/ka
IVN	KAI	LD50	2131	mg/kg

D-5440NS

Page: 6

ORL	MUS	LD50	7300	mg/kg
ORL	RAT	LD50	5628	mg/kg

#### PROPAN-2-OL

IVN	RAT	LD50	1088	mg/kg
ORL	MUS	LD50	3600	mg/kg
ORL	RAT	LD50	5045	mg/kg
SCU	MUS	LDLO	6	gm/kg

## Relevant hazards for product:

Hazard	Route	Basis
Acute toxicity (ac. tox. 4)	ING	Hazardous: calculated
STOT-single exposure	-	Hazardous: calculated

## Symptoms / routes of exposure

**Skin contact:** There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be soreness and redness of the mouth and throat. There may be difficulty

swallowing. Nausea and stomach pain may occur. There may be vomiting.

Inhalation: Absorption through the lungs can occur causing symptoms similar to those of ingestion.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

## **Section 12: Ecological information**

## 12.1. Toxicity

Ecotoxicity values: No data available.

## 12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

## 12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

## 12.4. Mobility in soil

Mobility: Readily absorbed into soil.

## 12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

#### 12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

D-5440NS

Page: 7

### Section 13: Disposal considerations

#### 13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal

company.

**Recovery operations:** Use principally as a fuel or other means to generate energy.

Disposal of packaging: Dispose of as normal industrial waste.

NB: The user's attention is drawn to the possible existence of regional or national

regulations regarding disposal.

### **Section 14: Transport information**

### 14.1. UN number

UN number: UN1950

### 14.2. UN proper shipping name

Shipping name: AEROSOLS (IATA ONLY), FLAMMABLE

#### 14.3. Transport hazard class(es)

Transport class: 2.1

#### 14.4. Packing group

### 14.5. Environmental hazards

Environmentally hazardous: No Marine pollutant: No

## 14.6. Special precautions for user

Special precautions: No special precautions.

### **Section 15: Regulatory information**

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

### 15.2. Chemical Safety Assessment

# Section 16: Other information

#### Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No

2015/830.

\* indicates text in the SDS which has changed since the last revision.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally

Harmonized System of Classification and Labeling of Chemicals (GHS).

The components of this product are listed in the TSCA inventory.

#### D-5440NS

Phrases used in s.2 and s.3: H220: Extremely flammable gas.

H222: Extremely flammable aerosol.

H225: Highly flammable liquid and vapour.

H226: Flammable liquid and vapour.

H229: Pressurised container: May burst if heated

H301: Toxic if swallowed.

H302: Harmful if swallowed.

H311: Toxic in contact with skin.

H319: Causes serious eye irritation.

H331: Toxic if inhaled.

H336: May cause drowsiness or dizziness.

H370: Causes damage to organs <or state all organs affected, if known> <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>. H371: May cause damage to organs <or state all organs affected, if known> <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.

**Legal disclaimer:** The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.

Page: 8