

**DOW CORNING(R) 3-6548 SILICONE RTV  
FOAM KIT (PART B information is below)**

Version 3.1      Revision Date: 11/17/2016      SDS Number: 638443-00007      Date of last issue: 04/09/2016  
Date of first issue: 10/16/2014

---

**SECTION 1. IDENTIFICATION**

Product name : DOW CORNING(R) 3-6548 SILICONE RTV FOAM KIT  
(PART B information is below)

Product code : 000000000001494473

**Manufacturer or supplier's details**

Company name of supplier : Dow Corning Corporation

Address : South Saginaw Road  
Midland Michigan 48686

Telephone : (989) 496-6000

Emergency telephone : 24 Hour Emergency Telephone : (989) 496-5900  
CHEMTREC : (800) 424-9300

**Recommended use of the chemical and restrictions on use**

Recommended use : Flame retardants

---

**SECTION 2. HAZARDS IDENTIFICATION****GHS classification in accordance with 29 CFR 1910.1200**

Reproductive toxicity : Category 2

**GHS label elements**

Hazard pictograms :



Signal Word : Warning

Hazard Statements : H361f Suspected of damaging fertility.

Precautionary Statements :

**Prevention:**

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat/sparks/open flames/hot surfaces.  
No smoking.

P234 Keep only in original container.

P280 Wear protective gloves/ protective clothing/ eye protection/  
face protection.

**Response:**

P308 + P313 IF exposed or concerned: Get medical advice/

---

# DOW CORNING(R) 3-6548 SILICONE RTV FOAM KIT (PART B information is below)

Version 3.1      Revision Date: 11/17/2016      SDS Number: 638443-00007      Date of last issue: 04/09/2016  
Date of first issue: 10/16/2014

attention.

**Storage:**

P403 Store in a well-ventilated place.  
P405 Store locked up.

**Disposal:**

P501 Dispose of contents/ container to an approved waste disposal plant.

**Other hazards**

May generate flammable hydrogen gas. Avoid contact with water, alcohols, acidic, basic, or oxidizing materials.

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture  
Chemical nature : Silicone compound

**Hazardous ingredients**

Chemical name	CAS-No.	Concentration (% w/w)
Quartz	14808-60-7	>= 10 - < 20
Octamethylcyclotetrasiloxane	556-67-2	>= 0.1 - < 1

## SECTION 4. FIRST AID MEASURES

General advice : In the case of accident or if you feel unwell, seek medical advice immediately.  
When symptoms persist or in all cases of doubt seek medical advice.

If inhaled : If inhaled, remove to fresh air.  
Get medical attention.

In case of skin contact : In case of contact, immediately flush skin with soap and plenty of water.  
Remove contaminated clothing and shoes.  
Get medical attention.  
Wash clothing before reuse.  
Thoroughly clean shoes before reuse.

In case of eye contact : Flush eyes with water as a precaution.  
Get medical attention if irritation develops and persists.

If swallowed : If swallowed, DO NOT induce vomiting.  
Get medical attention.  
Rinse mouth thoroughly with water.

Most important symptoms and effects, both acute and delayed : Suspected of damaging fertility.

## DOW CORNING(R) 3-6548 SILICONE RTV FOAM KIT (PART B information is below)

Version	Revision Date:	SDS Number:	Date of last issue: 04/09/2016
3.1	11/17/2016	638443-00007	Date of first issue: 10/16/2014

Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists.

Notes to physician : Treat symptomatically and supportively.

### SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Water spray  
Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)

Unsuitable extinguishing media : Dry chemical

Specific hazards during fire fighting : Exposure to combustion products may be a hazard to health. Applying foam will release significant amounts of hydrogen gas that can be trapped under the foam blanket.

Hazardous combustion products : Carbon oxides  
Silicon oxides  
Formaldehyde

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Use water spray to cool unopened containers.  
Do not allow extinguishing medium to contact container contents. Most fire extinguishing media will cause hydrogen evolution, and once the fire is put out, may accumulate in poorly ventilated or confined areas and result in flash fire or explosion if ignited.  
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.  
Remove undamaged containers from fire area if it is safe to do so.  
Evacuate area.

Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.  
Use personal protective equipment.

### SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.  
Follow safe handling advice and personal protective equipment recommendations.

Environmental precautions : Discharge into the environment must be avoided.  
Prevent further leakage or spillage if safe to do so.  
Prevent spreading over a wide area (e.g. by containment or oil

## DOW CORNING(R) 3-6548 SILICONE RTV FOAM KIT (PART B information is below)

Version	Revision Date:	SDS Number:	Date of last issue: 04/09/2016
3.1	11/17/2016	638443-00007	Date of first issue: 10/16/2014

---

barriers).  
Retain and dispose of contaminated wash water.  
Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up : Soak up with inert absorbent material.  
For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container.  
Clean up remaining materials from spill with suitable absorbent.  
Materials in contact with water, moisture, acids or bases have the potential to generate hydrogen gas. Recovered material should be stored in a vented container.  
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.  
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

---

### SECTION 7. HANDLING AND STORAGE

Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : Use only with adequate ventilation.

Advice on safe handling : Avoid inhalation of vapor or mist.  
Do not swallow.  
Avoid contact with eyes.  
Avoid prolonged or repeated contact with skin.  
Handle in accordance with good industrial hygiene and safety practice.  
Keep away from water.  
Protect from moisture.  
Take care to prevent spills, waste and minimize release to the environment.

Conditions for safe storage : Keep in properly labeled containers.  
Store in original container.  
Store in a closed container.  
Store in accordance with the particular national regulations.  
Product may evolve minute quantities of flammable hydrogen gas which can accumulate. Adequately ventilate to maintain vapors well below flammability limits and exposure guidelines.  
Do not repackage. Clogged container vents may increase pressure build up.

Materials to avoid : Do not store with the following product types:  
Strong oxidizing agents

# DOW CORNING(R) 3-6548 SILICONE RTV FOAM KIT (PART B information is below)

Version 3.1      Revision Date: 11/17/2016      SDS Number: 638443-00007      Date of last issue: 04/09/2016  
Date of first issue: 10/16/2014

Packaging material : Unsuitable material: Do not store in or use containers except the original product package.

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Ingredients with workplace control parameters

Ingredients	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Quartz	14808-60-7	TWA (total dust)	30 mg/m <sup>3</sup> / %SiO <sub>2</sub> +2	OSHA Z-3
		TWA (respirable)	10 mg/m <sup>3</sup> / %SiO <sub>2</sub> +2	OSHA Z-3
		TWA (respirable)	250 mppcf / %SiO <sub>2</sub> +5	OSHA Z-3
		TWA (Respirable fraction)	0.025 mg/m <sup>3</sup> (Silica)	ACGIH
		TWA (Respirable dust)	0.05 mg/m <sup>3</sup> (Silica)	NIOSH REL
Octamethylcyclotetrasiloxane	556-67-2	TWA	10 ppm	US WEEL

**These substance(s) are inextricably bound in the product and therefore do not contribute to a dust inhalation hazard.**

Quartz

**Engineering measures** : Processing may form hazardous compounds (see section 10).  
Ensure adequate ventilation, especially in confined areas.  
Minimize workplace exposure concentrations.

### Personal protective equipment

Respiratory protection : General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection.

Hand protection  
Material : Chemical-resistant gloves

Remarks : Choose gloves to protect hands against chemicals depending

## DOW CORNING(R) 3-6548 SILICONE RTV FOAM KIT (PART B information is below)

Version	Revision Date:	SDS Number:	Date of last issue: 04/09/2016
3.1	11/17/2016	638443-00007	Date of first issue: 10/16/2014

---

on the concentration specific to place of work. Breakthrough time is not determined for the product. Change gloves often! For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

- Eye protection : Wear the following personal protective equipment:  
Safety glasses
- Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.  
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).
- Hygiene measures : Ensure that eye flushing systems and safety showers are located close to the working place.  
When using do not eat, drink or smoke.  
Wash contaminated clothing before re-use.  
These precautions are for room temperature handling. Use at elevated temperature or aerosol/spray applications may require added precautions.  
For further information regarding the use of silicones / organic oils in consumer aerosol applications, please refer to the guidance document regarding the use of these type of materials in consumer aerosol applications that has been developed by the silicone industry ([www.SEHSC.com](http://www.SEHSC.com)) or contact the Dow Corning customer service group.

---

### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : liquid
- Color : off-white
- Odor : No data available
- Odor Threshold : No data available
- pH : No data available
- Melting point/freezing point : No data available
- Initial boiling point and boiling range : 150 °C
- Flash point : 100 °C  
Method: closed cup
- Evaporation rate : No data available
- Flammability (solid, gas) : Not applicable

# SAFETY DATA SHEET

**DOW CORNING**

## DOW CORNING(R) 3-6548 SILICONE RTV FOAM KIT (PART B information is below)

Version 3.1      Revision Date: 11/17/2016      SDS Number: 638443-00007      Date of last issue: 04/09/2016  
Date of first issue: 10/16/2014

---

Self-ignition : The substance or mixture is not classified as pyrophoric. The substance or mixture is not classified as self heating.

Upper explosion limit : No data available

Lower explosion limit : No data available

Vapor pressure : No data available

Relative vapor density : No data available

Relative density : 1.08

Solubility(ies)  
Water solubility : No data available

Partition coefficient: n-octanol/water : No data available

Autoignition temperature : No data available

Decomposition temperature : No data available

Viscosity  
Viscosity, kinematic : 6250 cSt

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Molecular weight : No data available

---

### SECTION 10. STABILITY AND REACTIVITY

Reactivity : Contact with water liberates highly flammable gases.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reactions : Can react with strong oxidizing agents. Product may evolve flammable hydrogen gas on contact with water, alcohols, acidic or basic materials, many metals or metallic compounds and can form explosive mixtures in air. When heated to temperatures above 180 °C (356 °F) in the presence of air, trace quantities of formaldehyde may be released. Adequate ventilation is required. See OSHA formaldehyde standard, 29 CFR 1910.1048 Hazardous decomposition products will be formed at elevated temperatures.

**DOW CORNING(R) 3-6548 SILICONE RTV  
FOAM KIT (PART B information is below)**

Version	Revision Date:	SDS Number:	Date of last issue: 04/09/2016
3.1	11/17/2016	638443-00007	Date of first issue: 10/16/2014

Conditions to avoid : Exposure to moisture.

Incompatible materials : Oxidizing agents

**Hazardous decomposition products**

Thermal decomposition : Formaldehyde

**SECTION 11. TOXICOLOGICAL INFORMATION****Information on likely routes of exposure**

Inhalation  
Skin contact  
Ingestion  
Eye contact

**Acute toxicity**

Not classified based on available information.

**Ingredients:****Quartz:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

**Octamethylcyclotetrasiloxane:**

Acute oral toxicity : LD50 (Rat): > 4,800 mg/kg  
Assessment: The substance or mixture has no acute oral toxicity  
Remarks: On basis of test data.

Acute inhalation toxicity : LC50 (Rat): 2975 ppm  
Exposure time: 4 h  
Test atmosphere: vapor  
Assessment: The substance or mixture has no acute inhalation toxicity  
Remarks: On basis of test data.

Acute dermal toxicity : LD50 (Rabbit): > 2.5 ml/kg  
Assessment: The substance or mixture has no acute dermal toxicity  
Remarks: On basis of test data.

**Skin corrosion/irritation**

Not classified based on available information.

**Ingredients:****Octamethylcyclotetrasiloxane:**

Species: Rabbit  
Result: No skin irritation  
Remarks: On basis of test data.



**DOW CORNING(R) 3-6548 SILICONE RTV  
FOAM KIT (PART B information is below)**

Version 3.1      Revision Date: 11/17/2016      SDS Number: 638443-00007      Date of last issue: 04/09/2016  
Date of first issue: 10/16/2014

---

**Serious eye damage/eye irritation**

Not classified based on available information.

**Ingredients:****Octamethylcyclotetrasiloxane:**

Species: Rabbit  
Result: No eye irritation  
Remarks: On basis of test data.

**Respiratory or skin sensitization****Skin sensitization**

Not classified based on available information.

**Respiratory sensitization**

Not classified based on available information.

**Ingredients:****Octamethylcyclotetrasiloxane:**

Assessment: Does not cause skin sensitization.

Test Type: Maximization Test  
Species: Guinea pig  
Result: negative  
Remarks: On basis of test data.

**Germ cell mutagenicity**

Not classified based on available information.

**Ingredients:****Octamethylcyclotetrasiloxane:**

Genotoxicity in vitro      : Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative  
Remarks: On basis of test data.

   : Test Type: Mutagenicity (in vitro mammalian cytogenetic test)  
Result: negative  
Remarks: On basis of test data.

   : Test Type: Chromosome aberration test in vitro  
Result: negative  
Remarks: On basis of test data.

   : Test Type: In vitro sister chromatid exchange assay in mam-  
malian cells  
Result: negative  
Remarks: On basis of test data.

   : Test Type: DNA damage and repair, unscheduled DNA syn-

# DOW CORNING(R) 3-6548 SILICONE RTV FOAM KIT (PART B information is below)

Version	Revision Date:	SDS Number:	Date of last issue: 04/09/2016
3.1	11/17/2016	638443-00007	Date of first issue: 10/16/2014

thesis in mammalian cells (in vitro)  
Result: negative  
Remarks: On basis of test data.

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)  
Species: Rat  
Application Route: inhalation (vapor)  
Result: negative  
Remarks: On basis of test data.

Test Type: Rodent dominant lethal test (germ cell) (in vivo)  
Species: Rat  
Application Route: Ingestion  
Result: negative  
Remarks: On basis of test data.

Germ cell mutagenicity - Assessment : Animal testing did not show any mutagenic effects.

## Carcinogenicity

Not classified based on available information.

## Ingredients:

### Quartz:

Species: Humans  
Application Route: inhalation (dust/mist/fume)  
Result: positive  
Remarks: IARC: (International Agency for Research on Cancer)  
These substance(s) are inextricably bound in the product and therefore do not contribute to a dust inhalation hazard.

Carcinogenicity - Assessment : Positive evidence from human epidemiological studies (inhalation)

### IARC

Group 1: Carcinogenic to humans

Quartz 14808-60-7

### OSHA

No ingredient of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

### NTP

Known to be human carcinogen

Quartz 14808-60-7

## Reproductive toxicity

Suspected of damaging fertility.

**DOW CORNING(R) 3-6548 SILICONE RTV  
FOAM KIT (PART B information is below)**

Version 3.1      Revision Date: 11/17/2016      SDS Number: 638443-00007      Date of last issue: 04/09/2016  
Date of first issue: 10/16/2014

---

**Ingredients:****Octamethylcyclotetrasiloxane:**

- Effects on fertility : Test Type: Two-generation reproduction toxicity study  
Species: Rat, male and female  
Application Route: inhalation (vapor)  
Symptoms: Effects on fertility.  
Remarks: On basis of test data.
- Effects on fetal development : Test Type: Prenatal development toxicity study (teratogenicity)  
Species: Rabbit  
Application Route: inhalation (vapor)  
Symptoms: No effects on fetal development.  
Remarks: On basis of test data.
- Reproductive toxicity - Assessment : Some evidence of adverse effects on sexual function and fertility, based on animal experiments.

**STOT-single exposure**

Not classified based on available information.

**STOT-repeated exposure**

Not classified based on available information.

**Ingredients:****Quartz:**

Routes of exposure: inhalation (dust/mist/fume)  
Target Organs: Lungs  
Assessment: Shown to produce significant health effects in animals at concentrations of 0.02 mg/l/6h/d or less.

**Octamethylcyclotetrasiloxane:**

Routes of exposure: Ingestion  
Assessment: No significant health effects observed in animals at concentrations of 100 mg/kg bw or less.

Routes of exposure: inhalation (vapor)  
Assessment: No significant health effects observed in animals at concentrations of 1 mg/l/6h/d or less.

Routes of exposure: Skin contact  
Assessment: No significant health effects observed in animals at concentrations of 200 mg/kg bw or less.

**Repeated dose toxicity****Ingredients:****Quartz:**

Species: Humans  
LOAEL: 0.053 mg/m<sup>3</sup>

**DOW CORNING(R) 3-6548 SILICONE RTV  
FOAM KIT (PART B information is below)**

Version	Revision Date:	SDS Number:	Date of last issue: 04/09/2016
3.1	11/17/2016	638443-00007	Date of first issue: 10/16/2014

---

Application Route: Inhalation

Remarks: These substance(s) are inextricably bound in the product and therefore do not contribute to a dust inhalation hazard.

**Octamethylcyclotetrasiloxane:**

Species: Rat

Application Route: Ingestion

Remarks: On basis of test data.

Species: Rat

Application Route: inhalation (vapor)

Remarks: On basis of test data.

Species: Rabbit

Application Route: Skin contact

Remarks: On basis of test data.

**Aspiration toxicity**

Not classified based on available information.

**Further information****Ingredients:****Octamethylcyclotetrasiloxane:**

Remarks: Results from a 2 year repeated vapor inhalation exposure study to rats of octamethylcyclotetrasiloxane (D4) indicate effects (benign uterine adenomas) in the uterus of female animals. This finding occurred at the highest exposure dose (700 ppm) only. Studies to date have not demonstrated if these effects occur through pathways that are relevant to humans. Repeated exposure in rats to D4 resulted in protoporphyrin accumulation in the liver. Without knowledge of the specific mechanism leading to the protoporphyrin accumulation the relevance of this finding to humans is unknown.

---

**SECTION 12. ECOLOGICAL INFORMATION****Ecotoxicity****Ingredients:****Quartz:****Ecotoxicology Assessment**

Acute aquatic toxicity : No toxicity at the limit of solubility.

Chronic aquatic toxicity : No toxicity at the limit of solubility.

**Octamethylcyclotetrasiloxane:**

Toxicity to fish : LC50 (Cyprinodon variegatus (sheepshead minnow)): > 0.0063 mg/l  
Exposure time: 336 h  
Remarks: No toxicity at the limit of solubility.

**DOW CORNING(R) 3-6548 SILICONE RTV  
FOAM KIT (PART B information is below)**

Version	Revision Date:	SDS Number:	Date of last issue: 04/09/2016
3.1	11/17/2016	638443-00007	Date of first issue: 10/16/2014

Toxicity to daphnia and other aquatic invertebrates : EC50 (Mysidopsis bahia (opossum shrimp)): > 0.0091 mg/l  
Exposure time: 96 h  
Remarks: No toxicity at the limit of solubility.

Toxicity to algae : ErC50 (Pseudokirchneriella subcapitata (green algae)): > 0.022 mg/l  
Exposure time: 72 h  
Remarks: No toxicity at the limit of solubility.

Toxicity to fish (Chronic toxicity) : NOEC (Oncorhynchus mykiss (rainbow trout)): >= 0.0044 mg/l  
Remarks: On basis of test data.  
No toxicity at the limit of solubility.

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): >= 0.0079 mg/l  
Exposure time: 21 d  
Remarks: On basis of test data.  
No toxicity at the limit of solubility.

**Ecotoxicology Assessment**

Chronic aquatic toxicity : May cause long lasting harmful effects to aquatic life.

**Persistence and degradability****Ingredients:****Octamethylcyclotetrasiloxane:**

Biodegradability : Result: Not readily biodegradable.  
Biodegradation: 3.7 %  
Exposure time: 28 d  
Method: OECD Test Guideline 310

Stability in water : Degradation half life: 69.3 - 144 h (24.6 °C) pH: 7  
Method: OECD Test Guideline 111

**Bioaccumulative potential****Ingredients:****Octamethylcyclotetrasiloxane:**

Bioaccumulation : Species: Pimephales promelas (fathead minnow)  
Bioconcentration factor (BCF): 12,400

Partition coefficient: n-octanol/water : log Pow: 6.48 (25.1 °C)

**Mobility in soil**

No data available

**DOW CORNING(R) 3-6548 SILICONE RTV  
FOAM KIT (PART B information is below)**

Version	Revision Date:	SDS Number:	Date of last issue: 04/09/2016
3.1	11/17/2016	638443-00007	Date of first issue: 10/16/2014

---

**Other adverse effects****Ingredients:****Octamethylcyclotetrasiloxane:**

Results of PBT and vPvB assessment : Remarks: Octamethylcyclotetrasiloxane (D4) meets the current REACh Annex XIII criteria for PBT and vPvB. In Canada, D4 has been assessed and deemed to meet the PiT criteria. However, D4 does not behave similarly to known PBT/vPvB substances. The weight of scientific evidence from field studies shows that D4 is not biomagnifying in aquatic and terrestrial food webs. D4 in air will degrade by reaction with naturally occurring hydroxyl radicals in the atmosphere. Any D4 in air that does not degrade by reaction with hydroxyl radicals is not expected to deposit from the air to water, to land, or to living organisms.

---

**SECTION 13. DISPOSAL CONSIDERATIONS****Disposal methods**

Resource Conservation and Recovery Act (RCRA) : When a decision is made to discard this material as supplied, it is classified as a RCRA hazardous waste.

Waste Code : D003: Reactivity

Waste from residues : Dispose of in accordance with local regulations.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.  
If not otherwise specified: Dispose of as unused product.

---

**SECTION 14. TRANSPORT INFORMATION****International Regulations****UNRTDG**

Not regulated as a dangerous good

**IATA-DGR**

Not regulated as a dangerous good

Remarks : VENTED PACKAGES ARE FORBIDDEN FOR AIR TRANSPORT.

**IMDG-Code**

Not regulated as a dangerous good

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

Not applicable for product as supplied.

**Domestic regulation****49 CFR**

Not regulated as a dangerous good

# DOW CORNING(R) 3-6548 SILICONE RTV FOAM KIT (PART B information is below)

Version	Revision Date:	SDS Number:	Date of last issue: 04/09/2016
3.1	11/17/2016	638443-00007	Date of first issue: 10/16/2014

## SECTION 15. REGULATORY INFORMATION

### EPCRA - Emergency Planning and Community Right-to-Know

#### CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

#### SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

#### SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

**SARA 311/312 Hazards** : Chronic Health Hazard

**SARA 313** : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

### US State Regulations

#### Pennsylvania Right To Know

Dimethyl siloxane, hydroxy-terminated	70131-67-8
Quartz	14808-60-7
Methylhydrogen Siloxane, Trimethylsiloxy-terminated	63148-57-2
Aluminum oxide	1344-28-1

**California Prop. 65** : This product does not contain any chemicals known to the State of California to cause cancer, birth, or any other reproductive defects.

#### California Permissible Exposure Limits for Chemical Contaminants

Quartz	14808-60-7
--------	------------

#### The ingredients of this product are reported in the following inventories:

NZIoC	: All ingredients listed or exempt.
REACH	: All ingredients (pre-)registered or exempt.
TSCA	: All chemical substances in this product are either listed on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.
AICS	: All ingredients listed or exempt.
IECSC	: All ingredients listed or exempt.
ENCS/ISHL	: All components are listed on ENCS/ISHL or exempted from inventory listing.
KECI	: All ingredients listed, exempt or notified.
DSL	: All chemical substances in this product comply with the CEPA 1999 and NSNR and are on or exempt from listing on the

# SAFETY DATA SHEET

**DOW CORNING**

## DOW CORNING(R) 3-6548 SILICONE RTV FOAM KIT (PART B information is below)

Version 3.1      Revision Date: 11/17/2016      SDS Number: 638443-00007      Date of last issue: 04/09/2016  
Date of first issue: 10/16/2014

Canadian Domestic Substances List (DSL).


PICCS : All ingredients listed or exempt.

TCSI : All ingredients listed or exempt.

### SECTION 16. OTHER INFORMATION

#### Further information

##### NFPA:



##### HMIS® IV:

HEALTH	*	0
FLAMMABILITY		1
PHYSICAL HAZARD		1

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "\*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

#### Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)  
NIOSH REL : USA. NIOSH Recommended Exposure Limits  
OSHA Z-3 : USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts  
US WEEL : USA. Workplace Environmental Exposure Levels (WEEL)  
ACGIH / TWA : 8-hour, time-weighted average  
NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek  
OSHA Z-3 / TWA : 8-hour time weighted average  
US WEEL / TWA : Time weighted average

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - Interna-



**DOW CORNING(R) 3-6548 SILICONE RTV  
FOAM KIT (PART B information is below)**

Version	Revision Date:	SDS Number:	Date of last issue: 04/09/2016
3.1	11/17/2016	638443-00007	Date of first issue: 10/16/2014

---

tional Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 11/17/2016

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8