



Revision Number: 005.0

Issue date: 08/12/2016

1. PRODUCT AND COMPANY IDENTIFICATION

Product name: LOCTITE EA E-20NS A RESIN known as DB EPOXY ADH E-20NS 400 ML RESI
IDH number: 702005
Product type: Epoxy resin
Item number: 29336_209540
Restriction of Use: None identified
Region: United States
Company address:
 Henkel Corporation
 One Henkel Way
 Rocky Hill, Connecticut 06067
Contact information:
 Telephone: (860) 571-5100
 MEDICAL EMERGENCY Phone: Poison Control Center
 1-877-671-4608 (toll free) or 1-303-592-1711
 TRANSPORT EMERGENCY Phone: CHEMTREC
 1-800-424-9300 (toll free) or 1-703-527-3887
 Internet: www.henkelna.com

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

WARNING: CAUSES SKIN IRRITATION.
 MAY CAUSE AN ALLERGIC SKIN REACTION.
 CAUSES SERIOUS EYE IRRITATION.
 MAY CAUSE RESPIRATORY IRRITATION.

HAZARD CLASS	HAZARD CATEGORY
SKIN IRRITATION	2
EYE IRRITATION	2A
SKIN SENSITIZATION	1
SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE	3

PICTOGRAM(S)



Precautionary Statements

Prevention: Avoid breathing vapors, mist, or spray. Wash affected area thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves, eye protection, and face protection.

Response: IF ON SKIN: Wash with plenty of water. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or physician if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation or rash occurs: Get medical attention. If eye irritation persists: Get medical attention. Take off contaminated clothing.

Storage: Store in a well-ventilated place. Keep container tightly closed. Store locked up.

Disposal: Dispose of contents and/or container according to Federal, State/Provincial and local governmental regulations.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*
Epoxy resin	Proprietary	30 - 60
Talc	14807-96-6	30 - 60
Epoxy resin	Proprietary	10 - 30
Treated fumed silica	67762-90-7	1 - 5
Titanium dioxide	13463-67-7	0.1 - 1
Substituted silane	Proprietary	0.1 - 1
Epoxy resin	Proprietary	0.1 - 1

* Exact percentage is a trade secret. Concentration range is provided to assist users in providing appropriate protections.

4. FIRST AID MEASURES

Inhalation:	Move to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.
Skin contact:	Immediately flush skin with plenty of water (using soap, if available). Remove contaminated clothing and footwear. Get medical attention. Wash clothing before reuse. Thoroughly clean shoes before reuse.
Eye contact:	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.
Ingestion:	DO NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention.
Symptoms:	See Section 11.

5. FIRE FIGHTING MEASURES

Extinguishing media:	Water spray (fog), foam, dry chemical or carbon dioxide.
Special firefighting procedures:	Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.
Unusual fire or explosion hazards:	May decompose above 149°C (300°F). May polymerize above 260°C (500°F) in which case closed containers may rupture or explode. Fumes and vapors from thermal decompositions vary in composition and toxicity. In case of fire, keep containers cool with water spray.
Hazardous combustion products:	Oxides of carbon. Phenolics. Acids. Aldehydes. Formaldehyde. Irritating vapors.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions:	Do not allow product to enter sewer or waterways.
-----------------------------------	---

Clean-up methods:

Remove all sources of ignition. Evacuate and ventilate spill area; dike spill to prevent entry into water system; wear full protective equipment during clean-up. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Scrape up as much material as possible. Store in a partly filled, closed container until disposal. Refer to Section 8 "Exposure Controls / Personal Protection" prior to clean up.

7. HANDLING AND STORAGE

Handling:

Use only with adequate ventilation. Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist. Wash thoroughly after handling. Keep container closed. Refer to Section 8.

Storage:

Store in original container until ready to use. Keep container tightly closed and in a cool, well-ventilated place away from incompatible materials. Protect from direct sunlight. Store away from heat, sparks, flames, or other sources of ignition.

For information on product shelf life contact Henkel Customer Service at (800) 243-4874.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Epoxy resin	None	None	None	None
Talc	2 mg/m ³ TWA Respirable fraction.	20 MPPCF TWA 2.4 MPPCF TWA Respirable. 0.1 mg/m ³ TWA Respirable. 0.3 mg/m ³ TWA Total dust.	None	50 ppm
Epoxy resin	None	None	None	None
Treated fumed silica	10 mg/m ³ TWA Inhalable dust. 3 mg/m ³ TWA Respirable fraction.	15 mg/m ³ TWA Total dust. 5 mg/m ³ TWA Respirable fraction.	None	None
Titanium dioxide	10 mg/m ³ TWA	15 mg/m ³ PEL Total dust.	None	None
Substituted silane	None	None	None	None
Epoxy resin	None	None	None	None

Engineering controls:

Provide adequate local exhaust ventilation to maintain worker exposure below exposure limits.

Respiratory protection:

Use a NIOSH approved air-purifying respirator if the potential to exceed established exposure limits exists.

Eyeface protection:

Safety goggles or safety glasses with side shields. Full face protection should be used if the potential for splashing or spraying of product exists. Safety showers and eye wash stations should be available.

Skin protection:

Use chemical resistant, impermeable clothing including gloves and either an apron or body suit to prevent skin contact.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:

Viscous, Liquid

Color:

Off white

Odor:

mild

Odor threshold:

Not available.

pH:	Not available.
Vapor pressure:	Nil
Boiling point/range:	> 260 °C (> 500°F)
Melting point/ range:	Not available.
Vapor density:	Not available.
Flash point:	> 93 °C (> 199.4 °F) Setaflash Closed Cup
Flammable/Explosive limits - lower:	Not available.
Flammable/Explosive limits - upper:	Not available.
Autoignition temperature:	Not available.
Flammability:	Not applicable
Evaporation rate:	Not available.
Solubility in water:	Insoluble
Partition coefficient (n-octanol/water):	Not available.
VOC content:	< 1 %; < 10 g/l Estimated
Viscosity:	Not available.
Decomposition temperature:	Not available.

10. STABILITY AND REACTIVITY

Stability:	Stable under normal conditions of storage and use.
Hazardous reactions:	Reaction with some curing agents may produce an exothermic reaction which in large masses could cause runaway polymerization.
Hazardous decomposition products:	Oxides of carbon. Phenolics. Acids. Aldehydes. Formaldehyde. Irritating vapors.
Incompatible materials:	Acids. Bases. Oxidizing agents. Amines.
Reactivity:	Not available.
Conditions to avoid:	Keep away from heat, ignition sources and incompatible materials. Protect from direct sunlight. Note: Heating the epoxy resin in this product above 148.9 °C (300 °F) in the presence of air may cause slow oxidative decomposition. Above 260 °C (500 °F) polymerization of the epoxy resin may occur. Aliphatic polyamines can produce exothermic reactions with epoxy resins which in large masses can cause runaway polymerization and charring of the reactants. Fumes and vapors from these thermal and chemical decompositions vary widely in composition and toxicity. Do not breathe fumes.

11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure:	Skin, Inhalation, Eyes, Ingestion
-------------------------------------	-----------------------------------

Potential Health Effects/Symptoms

Inhalation: Inhalation of vapors or mists of the product may be irritating to the respiratory system. May cause irritation to nose and throat.
Skin contact: Causes skin irritation. May cause allergic skin reaction. Itching. Redness.
Eye contact: Causes serious eye irritation.
Ingestion: May cause gastrointestinal tract irritation if swallowed.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
Epoxy resin	None	Allergen, Irritant
Talc	None	Irritant, Lung, Some evidence of carcinogenicity
Epoxy resin	None	Allergen, Irritant
Treated fumed silica	None	Irritant
Titanium dioxide	None	Irritant, Respiratory, Some evidence of carcinogenicity
Substituted silane	None	Allergen, Irritant
Epoxy resin	None	No Data

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Epoxy resin	No	No	No
Talc	No	Group 2B	No
Epoxy resin	No	No	No
Treated fumed silica	No	No	No
Titanium dioxide	No	Group 2B	No
Substituted silane	No	No	No
Epoxy resin	No	No	No

12. ECOLOGICAL INFORMATION

Ecological information: Not available.

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Follow all local, state, federal and provincial regulations for disposal.

Hazardous waste number: Not a RCRA hazardous waste.

14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name: Not regulated
Hazard class or division: None
Identification number: None
Packing group: None

International Air Transportation (ICAO/IATA)

Proper shipping name: Environmentally hazardous substance, liquid, n.o.s. (Bisphenol-A Epichlorhydrin resin)
Hazard class or division: 9
Identification number: UN 3082
Packing group: III

Water Transportation (IMO/IMDG)

Proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Bisphenol-A Epichlorhydrin resin)
Hazard class or division: 9
Identification number: UN 3082
Packing group: III
Marine pollutant: Bisphenol-A Epichlorhydrin resin

15. REGULATORY INFORMATION**United States Regulatory Information**

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.
TSCA 12 (b) Export Notification: None above reporting de minimis
CERCLA/SARA Section 302 EHS: None above reporting de minimis.
CERCLA/SARA Section 311/312: Immediate Health, Delayed Health
CERCLA/SARA Section 313: None above reporting de minimis.
California Proposition 65: This product contains a chemical known in the State of California to cause cancer. This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

Canada Regulatory Information

CEPA DSL/NDL Status: All components are listed on or are exempt from listing on the Canadian Domestic Substances List.

16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: 3

Prepared by: Rebecca Coons, Regulatory Affairs Specialist

Issue date: 08/12/2016

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.



Revision Number: 005.1

Issue date: 12/02/2015

1. PRODUCT AND COMPANY IDENTIFICATION

Product name:	LOCTITE EA E-20NS B HARDENER known as DB EPOXY ADH E-20NS 400 ML HARD	IDH number:	702006
Product type:	Epoxy Hardener	Item number:	29336_209541
Restriction of Use:	None identified	Region:	United States
Company address:	Contact information:		
Henkel Corporation	Telephone: (860) 571-5100		
One Henkel Way	MEDICAL EMERGENCY Phone: Poison Control Center 1-877-671-4608 (toll free) or 1-303-592-1711		
Rocky Hill, Connecticut 06067	TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887		
	Internet: www.henkelna.com		

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

DANGER: CAUSES SEVERE SKIN BURNS AND EYE DAMAGE.
MAY CAUSE AN ALLERGIC SKIN REACTION.
MAY CAUSE ALLERGY OR ASTHMA SYMPTOMS OR BREATHING
DIFFICULTIES IF INHALED.

HAZARD CLASS	HAZARD CATEGORY
SKIN CORROSION	1B
SERIOUS EYE DAMAGE	1
RESPIRATORY SENSITIZATION	1
SKIN SENSITIZATION	1

PICTOGRAM(S)



Precautionary Statements

Prevention:	Do not breathe vapors, mist, or spray. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves, eye protection, and face protection. In case of inadequate ventilation wear respiratory protection.
Response:	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison control center or physician. If skin irritation or rash occurs: Get medical attention. If experiencing respiratory symptoms: Call a poison center or physician. Wash contaminated clothing before reuse.
Storage:	Store locked up.
Disposal:	Dispose of contents and/or container according to Federal, State/Provincial and local governmental regulations.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

IDH number: 702006

Product name: LOCTITE EA E-20NS B HARDENER known as DB EPOXY ADH E-20NS 400 ML HARD

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*
Talc	14807-96-6	30 - 60
Quartz (SiO ₂)	14808-60-7	10 - 30
Substituted Piperazine	Proprietary	5 - 10
Nonylphenol	25154-52-3	5 - 10
Diethylenetriamine	111-40-0	5 - 10
4,4'-Isopropylidenediphenol	80-05-7	1 - 5
Treated fumed silica	67762-90-7	1 - 5
Substituted silane	Proprietary	0.1 - 1

* Exact percentage is a trade secret. Concentration range is provided to assist users in providing appropriate protections.

4. FIRST AID MEASURES

Inhalation:	Move to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.
Skin contact:	Immediately flush skin with plenty of water (using soap, if available). Remove contaminated clothing and footwear. Get medical attention. Wash clothing before reuse. Thoroughly clean shoes before reuse.
Eye contact:	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.
Ingestion:	DO NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention.
Symptoms:	See Section 11.

5. FIRE FIGHTING MEASURES

Extinguishing media:	Water spray (fog), foam, dry chemical or carbon dioxide.
Special firefighting procedures:	Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear. In case of fire, keep containers cool with water spray.
Unusual fire or explosion hazards:	Personnel in vicinity and downwind should be evacuated. Burning produces obnoxious and toxic fumes. Use of water may result in the formation of very toxic aqueous solutions. Do not allow run-off from fire fighting to enter drains or water courses. Closed containers may rupture (due to build up of pressure) when exposed to extreme heat.
Hazardous combustion products:	Oxides of carbon. Oxides of nitrogen. Aldehydes. Ammonia. Formaldehyde. Nitric acid. Toxic fumes. Irritating vapors.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions:	Do not allow product to enter sewer or waterways.
-----------------------------------	---

Clean-up methods:

Remove all sources of ignition. Evacuate and ventilate spill area; dike spill to prevent entry into water system; wear full protective equipment during clean-up. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Scrape up as much material as possible. Store in a partly filled, closed container until disposal. Refer to Section 8 "Exposure Controls / Personal Protection" prior to clean up.

7. HANDLING AND STORAGE

Handling:

Use only with adequate ventilation. Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist. Wash thoroughly after handling. Keep container closed. Refer to Section 8.

Storage:

Store in original container until ready to use. Keep container tightly closed and in a cool, well-ventilated place away from incompatible materials. Store away from heat, sparks, flames, or other sources of ignition.

For information on product shelf life contact Henkel Customer Service at (800) 243-4874.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Talc	2 mg/m ³ TWA Respirable fraction.	20 MPPCF TWA 2.4 MPPCF TWA Respirable. 0.1 mg/m ³ TWA Respirable. 0.3 mg/m ³ TWA Total dust.	None	50 ppm
Quartz (SiO ₂)	0.025 mg/m ³ TWA Respirable fraction.	0.3 mg/m ³ TWA Total dust. 2.4 MPPCF TWA Respirable. 0.1 mg/m ³ TWA Respirable.	None	None
Substituted Piperazine	None	None	None	None
Nonylphenol	None	None	None	None
Diethylenetriamine	1 ppm TWA (SKIN)	None	None	None
4,4'-Isopropylidenediphenol	None	None	None	None
Treated fumed silica	10 mg/m ³ TWA Inhalable dust. 3 mg/m ³ TWA Respirable fraction.	15 mg/m ³ TWA Total dust. 5 mg/m ³ TWA Respirable fraction.	None	None
Substituted silane	None	None	None	None

Engineering controls:

Provide adequate local exhaust ventilation to maintain worker exposure below exposure limits.

Respiratory protection:

Use a NIOSH approved air-purifying respirator if the potential to exceed established exposure limits exists.

Eye/face protection:

Safety goggles or safety glasses with side shields. Full face protection should be used if the potential for splashing or spraying of product exists. Safety showers and eye wash stations should be available.

Skin protection:

Use chemical resistant, impermeable clothing including gloves and either an apron or body suit to prevent skin contact.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	Viscous, Liquid
Color:	Tan, Light, Green
Odor:	Strong, Ammoniacal
Odor threshold:	Not available.
pH:	Not available.
Vapor pressure:	Not available.
Boiling point/range:	Not available.
Melting point/ range:	Not available.
Specific gravity:	1.47
Vapor density:	Not available.
Flash point:	> 93 °C (> 199.4 °F) Setaflash Closed Cup
Flammable/Explosive limits - lower:	Not available.
Flammable/Explosive limits - upper:	Not available.
Autoignition temperature:	Not available.
Evaporation rate:	Not available.
Solubility in water:	Slight
Partition coefficient (n-octanol/water):	Not available.
VOC content:	< 1.0 %; < 10 g/l (estimated value for resin and hardener mixed together)
Viscosity:	Not available.
Decomposition temperature:	Not available.

10. STABILITY AND REACTIVITY

Stability:	Stable under normal conditions of storage and use.
Hazardous reactions:	None under normal processing.
Hazardous decomposition products:	Oxides of carbon. Oxides of nitrogen. Aldehydes. Ammonia. Formaldehyde. Nitric acid. Toxic fumes. Irritating vapors.
Incompatible materials:	Acids. Bases. Oxidizing agents. Peroxides. Reactive metals. Sodium hypochlorite. This product slowly corrodes copper, aluminum, zinc and galvanized surfaces.
Reactivity:	Not available.
Conditions to avoid:	Keep away from heat, ignition sources and incompatible materials. Avoid mixing resin (Part A) and curing agent (Part B) unless you plan to use immediately. Failure to observe these precautions may result in excessive heat build-up causing an exotherm.

11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure:	Skin, Inhalation, Eyes, Ingestion
-------------------------------------	-----------------------------------

Potential Health Effects/Symptoms

Inhalation: Inhalation of vapors or mists of the product may be irritating to the respiratory system. Can cause severe irritation and burns to the respiratory tract.

Skin contact: Corrosive to skin. Causes skin burns. May cause allergic skin reaction. Product may be absorbed through skin and cause nausea, headache and general discomfort.

Eye contact: Causes serious eye damage. Causes eye burns. Burns of the eye may cause blindness.

Ingestion: Irritation and corrosive action can occur in the mouth, stomach tissue and digestive tract if swallowed. If ingested, severe burns of the mouth and throat may occur, as well as perforation of the esophagus and the stomach.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
Talc	None	Irritant, Lung, Some evidence of carcinogenicity
Quartz (SiO2)	None	Immune system, Lung, Some evidence of carcinogenicity
Substituted Piperazine	None	Irritant, Corrosive, Allergen
Nonylphenol	Oral LD50 (RAT) = 1,600 mg/kg Dermal LD50 (RABBIT) = 2,140 mg/kg	Allergen, Corrosive, Irritant, Kidney
Diethylenetriamine	Oral LD50 (RAT) = 1,080 mg/kg Oral LD50 (RAT) = 2.33 g/kg Oral LD50 (RAT) Approximate 1,140 mg/kg	Allergen, Irritant, Eyes
4,4'-Isopropylidenediphenol	Oral LD50 (RAT) = 4,100 mg/kg Oral LD50 (RAT) = 3,300 mg/kg	Allergen, Blood, Irritant, Kidney, Reproductive, Spleen
Treated fumed silica	None	Irritant
Substituted silane	None	Irritant, Allergen

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Talc	No	Group 2B	No
Quartz (SiO2)	Known To Be Human Carcinogen.	Group 1	No
Substituted Piperazine	No	No	No
Nonylphenol	No	No	No
Diethylenetriamine	No	No	No
4,4'-Isopropylidenediphenol	No	No	No
Treated fumed silica	No	No	No
Substituted silane	No	No	No

12. ECOLOGICAL INFORMATION

Ecological information: Not available.

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal:	Follow all local, state, federal and provincial regulations for disposal.
Hazardous waste number:	It is the responsibility of the user to determine if an item is hazardous as defined in the Resource Conservation and Recovery Act (RCRA) at the time of disposal. Product uses, transformations, mixtures, processes, etc., may render the resulting material hazardous, under the criteria of ignitability, corrosivity, reactivity and toxicity characteristics of the Toxicity Characteristics Leaching Procedure (TCLP) 40 CFR 261.20-24.

14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name:	Corrosive liquids, n.o.s. (Diethylenetriamine, Nonylphenol)
Hazard class or division:	8
Identification number:	UN 1760
Packing group:	II

International Air Transportation (ICAO/IATA)

Proper shipping name:	Corrosive liquid, n.o.s. (Diethylenetriamine, Nonylphenol)
Hazard class or division:	8
Identification number:	UN 1760
Packing group:	II

Water Transportation (IMO/IMDG)

Proper shipping name:	CORROSIVE LIQUID, N.O.S. (Diethylenetriamine, Nonylphenol)
Hazard class or division:	8
Identification number:	UN 1760
Packing group:	II
Marine pollutant:	Nonylphenol

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status:	All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.
TSCA 12 (b) Export Notification:	Alkyl phenol (CAS# 25154-52-3).
CERCLA/SARA Section 302 EHS:	None above reporting de minimis.
CERCLA/SARA Section 311/312:	Immediate Health, Delayed Health
CERCLA/SARA Section 313:	This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR 372). Nonylphenol (CAS# 25154-52-3). 4,4'-Isopropylidenediphenol (CAS# 80-05-7).
California Proposition 65:	This product contains a chemical known in the State of California to cause cancer. This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

Canada Regulatory Information

CEPA DSL/NDL Status:	All components are listed on or are exempt from listing on the Canadian Domestic Substances List.
-----------------------------	---

16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: 15, 16

Prepared by: Rebecca Pasco, Regulatory Affairs Specialist

Issue date: 12/02/2015

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates (“Henkel”) does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user’s responsibility to determine the suitability of Henkel’s products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel’s products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel’s products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.