Safety Data Sheet



Revision Number: 003.1

Issue date: 10/03/2017

1. PRODUCT AND COMPANY IDENTIFICATION

Product name:

Product type: **Restriction of Use:** Company address: Henkel Corporation One Henkel Way Rocky Hill, Connecticut 06067

LOCTITE LB 8209 DUP OR LU PFPE HIGH PERF known as Dupont® Krytox® RFE PFPE Lubri Lubricant None identified

IDH number:

234339

Item number: 29710 Region: **United States** Contact information: Telephone: +1 (860) 571-5100 MEDICAL EMERGENCY Phone: Poison Control Center 1-877-671-4608 (toll free) or 1-303-592-1711 TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887 Internet: www.henkelna.com

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW NOT CLASSIFIED. READ ENTIRE SAFETY DATA SHEET.

HAZARD CLASS HAZARD CATEGORY None None

PICTOGRAM(S)

None

Precautionary Statements

Prevention:	Not prescribed
Response:	Not prescribed
Storage:	Not prescribed
Disposal:	Not prescribed

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*
None	None	None

* Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

4. FIRST AID MEASURES			
Inhalation:	Move to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.		
Skin contact:	Wash with soap and water. If symptoms develop and persist, get medical attention.		
Eye contact:	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If symptoms develop and persist, get medical attention.		
Ingestion:	Do not induce vomiting. Never give anything by mouth to an unconscious person. Get medical attention.		
Symptoms:	See Section 11.		
Notes to physician:	Treat symptomatically.		
5. FIRE FIGHTING MEASURES			
Extinguishing media:	Will not burn. Use media appropriate for surrounding material.		
Special firefighting procedures:	Wear self contained breathing apparatus.		
Unusual fire or explosion hazards:	None		
Hazardous combustion products:	Toxic fluorine compounds. Oxides of carbon. Irritating vapors.		

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions:	Do not flush with water. Do not allow product to enter sewer or waterways.
Clean-up methods:	Ensure adequate ventilation. Remove all sources of ignition. Scrape up as much material as possible. Remove the absorbed material, and place in an appropriate chemical waste container for disposal.

7. HANDLING AND STORAGE

Handling:

Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist. Wash thoroughly after handling. Do not store or consume food, drink, or tobacco products in areas where they may become contaminated with this material. Refer to Section 8.

Storage:

Keep container closed. Keep away from heat and flames to avoid decomposition products.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
None	None	None	None	None

Engineering controls:

Provide adequate local exhaust ventilation to maintain worker exposure below exposure limits.

Product name: LOCTITE LB 8209 DUP OR LU PFPE HIGH PERF known as Dupont® Krytox® RFE PFPE Lubri

Respiratory protection:

Eye/face protection:

Skin protection:

Where the potential exists for exposure to decomposition products due to heating or elevated temperatures, wear NIOSH approved respiratory protection as appropriate.

Safety goggles or safety glasses with side shields. Full face protection should be used if the potential for splashing or spraying of product exists. Safety showers and eye wash stations should be available.

Use chemical resistant, impermeable clothing including gloves and either an apron or body suit to prevent skin contact.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Color: Odor: Odor threshold: pH: Vapor pressure: Boiling point/range: Melting point/ range: Specific gravity: Vapor density: Flash point: Flammable/Explosive limits - lower: Flammable/Explosive limits - upper: Autoignition temperature: Flammability: **Evaporation rate:** Solubility in water: Partition coefficient (n-octanol/water): **VOC content:** Viscosity: **Decomposition temperature:**

Solid, Waxy, Grease White Odorless Not available. Neutral 0.0000001 mm hg (20 °C (68°F)) Not available. 320 °C (608°F) 1.89 - 1.93 Not available. Does not ignite. Not available. Not available. Not available. Not applicable Not available. Insoluble Not available. Essentially Zero (Exempt Compounds) Not available. Not available.

10. STABILITY AND REACTIVITY

Stability:	Stable under normal conditions of storage and use.
Hazardous reactions:	None under normal processing.
Hazardous decomposition products:	Heating above 260-290°C (500-554°F) may form potentially toxic fluorine compounds. Oxides of carbon. Irritating vapors.
Incompatible materials:	Oxidizing agents. Acids and bases.
Reactivity:	Not available.
Conditions to avoid:	Avoid heating above temperatures of 260-290°C (500-554°F). Decomposition occurs at increasing rates as temperature is raised above 355°C (670°F).

11. TOXICOLOGICAL INFORMATION

Product toxicity data: A single inhalation exposure to PTFE caused irritation of the lungs. A repeated ingestion exposure caused no significant toxicological effects. Long term ingestion exposure altered white blood cell counts.

Relevant routes of exposure: Skin, Inhalation, Eyes, Ingestion

Potential Health Effects/Symptoms

Inhalation:	Inhalation of Fluorine containing compounds released as decomposition products above 290°C, (554°F) may cause lung irritation and pulmonary edema which require medical attention. Inhalation of fumes or smoke from overheating or burning may cause polymer fume fever, a temporary flu-like illness accompanied by fever, chills, and sometimes coughing. These symptoms generally last approximately 24 hours. Repeated episodes of polymer fume fever may cause lung damage.
Skin contact:	May cause skin irritation with discomfort or rash.
Eye contact:	May cause eye irritation.
Ingestion:	Not expected under normal conditions of use. May cause gastrointestinal tract irritation if swallowed.

Hazardous Component(s)	LD50s and LC50s		Immediate and Delayed Health Effects	
None	None			None
Hazardous Component(s)	NTP Carcinogen	IARC Ca	rcinogen	OSHA Carcinogen (Specifically Regulated)
None	None	No	ne	None

12. ECOLOGICAL INFORMATION

Ecological information:

Not available.

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal:

Hazardous waste number:

Follow all local, state, federal and provincial regulations for disposal.

14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

Not a RCRA hazardous waste.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name:	Not regulated
Hazard class or division:	None
Identification number:	None
Packing group:	None
International Air Transportation (ICAO/IATA)	
Proper shipping name:	Not regulated
Hazard class or division:	None
Identification number:	None

Water Transportation (IMO/IMDG) Proper shipping name: Hazard class or division: Identification number: Packing group:

Not regulated None None None

None

15. REGULATORY INFORMATION

United States Regulatory Information

Packing group:

TSCA 8 (b) Inventory Status:

All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.

IDH number: 234339

Product name: LOCTITE LB 8209 DUP OR LU PFPE HIGH PERF known as Dupont® Krytox® RFE PFPE Lubri

TSCA 12 (b) Export Notification:	Ethene, tetrafluoro-, homopolymer (CAS# 9002-84-0).
CERCLA/SARA Section 302 EHS: CERCLA/SARA Section 311/312: CERCLA/SARA Section 313:	None above reporting de minimis. Immediate Health None above reporting de minimis.
California Proposition 65:	No California Proposition 65 listed chemicals are known to be present.
Canada Regulatory Information	
CEPA DSL/NDSL Status:	All components are listed on or are exempt from listing on the Canadian Domestic

16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: 4, 5, 10, 11

Substances List.

Prepared by: Product Safety and Regulatory Affairs

Issue date: 10/03/2017

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.