



Revision Number: 004.0

Issue date: 03/01/2018

## 1. PRODUCT AND COMPANY IDENTIFICATION

<b>Product name:</b>	<b>TEROSON SI 9160 ALM known as SILATECH® SILICONE SEALANT IND</b>	<b>IDH number:</b>	475375
<b>Product type:</b>	Silicone	<b>Item number:</b>	32392
<b>Restriction of Use:</b>	None identified	<b>Region:</b>	United States
<b>Company address:</b>	<b>Contact information:</b>		
Henkel Corporation	Telephone: +1 (860) 571-5100		
One Henkel Way	MEDICAL EMERGENCY Phone: Poison Control Center		
Rocky Hill, Connecticut 06067	1-877-671-4608 (toll free) or 1-303-592-1711		
	TRANSPORT EMERGENCY Phone: CHEMTREC		
	1-800-424-9300 (toll free) or 1-703-527-3887		
	Internet: www.henkeln.com		

## 2. HAZARDS IDENTIFICATION

### EMERGENCY OVERVIEW

**DANGER:** CAUSES SKIN IRRITATION.  
CAUSES SERIOUS EYE DAMAGE.

HAZARD CLASS	HAZARD CATEGORY
SKIN IRRITATION	2
SERIOUS EYE DAMAGE	1

### PICTOGRAM(S)



### Precautionary Statements

<b>Prevention:</b>	Wash affected area thoroughly after handling. Wear protective gloves, eye protection, and face protection.
<b>Response:</b>	IF ON SKIN: Wash with plenty of water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation occurs: Get medical attention. Take off contaminated clothing.
<b>Storage:</b>	Not prescribed
<b>Disposal:</b>	Not prescribed

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

## 3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*
Distillates (petroleum), hydrotreated middle	64742-46-7	5 - 10
Silicon dioxide	7631-86-9	5 - 10
Methylsilanetriyl triacetate	4253-34-3	1 - 5

IDH number: 475375

Product name: TEROSON SI 9160 ALM known as SILATECH® SILICONE SEALANT IND

Page 1 of 5

Triacetoxyethylsilane	17689-77-9	1 - 5
Acetic acid	64-19-7	0.1 - 1

\* Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

## 4. FIRST AID MEASURES

<b>Inhalation:</b>	Move to fresh air. If symptoms persist, seek medical advice.
<b>Skin contact:</b>	Wipe off paste with paper towel or cloth. Wash with soap and water.
<b>Eye contact:</b>	Rinse thoroughly with plenty of water, also under the eyelids. If eye irritation persists, consult a specialist.
<b>Ingestion:</b>	Do not induce vomiting. If a person feels unwell or symptoms of skin irritation appear, consult a physician.
<b>Symptoms:</b>	See Section 11.
<b>Notes to physician:</b>	Treat symptomatically.

## 5. FIRE FIGHTING MEASURES

<b>Extinguishing media:</b>	Foam, dry chemical or carbon dioxide.
<b>Special firefighting procedures:</b>	Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.
<b>Unusual fire or explosion hazards:</b>	None
<b>Hazardous combustion products:</b>	Formaldehyde. Silica mist. Acrid smoke and fumes.

## 6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

<b>Environmental precautions:</b>	Do not allow product to enter sewer or waterways.
<b>Clean-up methods:</b>	Scrape up as much material as possible. Spilled material will solidify. Store in a partly filled, closed container until disposal. Maintain good ventilation for large spills.

## 7. HANDLING AND STORAGE

<b>Handling:</b>	Do not handle contact lenses until all sealant has been removed from hands. Residual sealant may transfer to lenses and cause eye irritation. Avoid contact with eyes, skin and clothing.
<b>Storage:</b>	Keep container closed. Store in a dry area below 90° F.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Distillates (petroleum), hydrotreated middle	5 mg/m <sup>3</sup> TWA Inhalable fraction.	5 mg/m <sup>3</sup> PEL Mist.	None	None
Silicon dioxide	6 mg/m <sup>3</sup> TWA	20 MPPCF TWA 0.8 mg/m <sup>3</sup> TWA	None	3 mg/m <sup>3</sup> TWA Respirable fraction.
Methylsilanetriyl triacetate	None	None	None	None
Triacetoxylethylsilane	None	None	None	None
Acetic acid	15 ppm STEL 10 ppm TWA	10 ppm (25 mg/m <sup>3</sup> ) PEL	None	None

<b>Engineering controls:</b>	Use only with adequate ventilation.
<b>Respiratory protection:</b>	Use NIOSH approved respirator if there is potential to exceed exposure limit(s). No personal respiratory protective equipment normally required.
<b>Eye/face protection:</b>	Safety goggles or safety glasses with side shields.
<b>Skin protection:</b>	Chemical resistant, impermeable gloves.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Physical state:</b>	Paste
<b>Color:</b>	Aluminum
<b>Odor:</b>	Acetic acid
<b>Odor threshold:</b>	Not available.
<b>pH:</b>	Not available.
<b>Vapor pressure:</b>	< 10 mm hg (68 °F (20°C))
<b>Boiling point/range:</b>	Not available.
<b>Melting point/ range:</b>	Not available.
<b>Specific gravity:</b>	1.01 at 20 °C (68°F)
<b>Vapor density:</b>	Heavier than air.
<b>Flash point:</b>	> 93 °C (> 199.4 °F)
<b>Flammable/Explosive limits - lower:</b>	4 % (acetic acid)
<b>Flammable/Explosive limits - upper:</b>	19.9 % (acetic acid)
<b>Autoignition temperature:</b>	Not available.
<b>Flammability:</b>	Not applicable
<b>Evaporation rate:</b>	Not available.
<b>Solubility in water:</b>	Not soluble. Polymerizes in presence of water.
<b>Partition coefficient (n-octanol/water):</b>	Not available.
<b>VOC content:</b>	3.08 %; 32 g/l
<b>Viscosity:</b>	Not available.
<b>Decomposition temperature:</b>	Not available.

## 10. STABILITY AND REACTIVITY

<b>Stability:</b>	Stable
<b>Hazardous reactions:</b>	Will not occur.
<b>Hazardous decomposition products:</b>	Acetic acid is liberated slowly upon contact with moisture. Formaldehyde.
<b>Incompatible materials:</b>	Acids. Water Oxidizing agents. Bases.
<b>Reactivity:</b>	Not available.
<b>Conditions to avoid:</b>	Prolonged heating at temperatures above 150 °C. Exposure to moisture.

## 11. TOXICOLOGICAL INFORMATION

**Relevant routes of exposure:** Skin, Inhalation, Eyes

### Potential Health Effects/Symptoms

**Inhalation:** May cause respiratory tract irritation.  
**Skin contact:** Causes skin irritation.  
**Eye contact:** Causes serious eye irritation.  
**Ingestion:** Not a relevant route of exposure. May cause gastrointestinal tract irritation if swallowed.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
Distillates (petroleum), hydrotreated middle	None	Irritant
Silicon dioxide	Oral LD50 (Rat) = > 22,500 mg/kg Oral LD50 (Mouse) = > 15,000 mg/kg	Nuisance dust
Methylsilanetriyl triacetate	None	Irritant, Allergen
Triacetoxethylsilane	None	No Target Organs
Acetic acid	Oral LD50 (Rabbit) = 1,200 mg/kg Oral LD50 (Mouse) = 4,960 mg/kg Oral LD50 (Rat) = 3.53 g/kg Oral LD50 (Rat) = 3.31 g/kg Dermal LD50 (Rabbit) = 1,060 mg/kg Inhalation LC50 (Rat, 4 h) = 11.4 mg/l	Allergen, Corrosive, Eyes, Gastrointestinal, Immune system, Irritant, Kidney

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Distillates (petroleum), hydrotreated middle	No	No	No
Silicon dioxide	No	No	No
Methylsilanetriyl triacetate	No	No	No
Triacetoxethylsilane	No	No	No
Acetic acid	No	No	No

## 12. ECOLOGICAL INFORMATION

**Ecological information:** Not available.

## 13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

**Recommended method of disposal:** Cured rubber can be incinerated or landfilled following EPA and local regulations. Follow all local, state, federal and provincial regulations for disposal.

**Hazardous waste number:** Not a RCRA hazardous waste.

## 14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

### U.S. Department of Transportation Ground (49 CFR)

**Proper shipping name:** Not regulated  
**Hazard class or division:** None  
**Identification number:** None  
**Packing group:** None

**International Air Transportation (ICAO/IATA)**

**Proper shipping name:** Not regulated  
**Hazard class or division:** None  
**Identification number:** None  
**Packing group:** None

**Water Transportation (IMO/IMDG)**

**Proper shipping name:** Not regulated  
**Hazard class or division:** None  
**Identification number:** None  
**Packing group:** None

**15. REGULATORY INFORMATION****United States Regulatory Information**

**TSCA 8 (b) Inventory Status:** All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.  
**TSCA 12 (b) Export Notification:** None above reporting de minimis  
**CERCLA/SARA Section 302 EHS:** None above reporting de minimis.  
**CERCLA/SARA Section 311/312:** Immediate Health  
**CERCLA/SARA Section 313:** None above reporting de minimis.  
**California Proposition 65:** No California Proposition 65 listed chemicals are known to be present.

**Canada Regulatory Information**

**CEPA DSL/NDSL Status:** All components are listed on or are exempt from listing on the Canadian Domestic Substances List.

**16. OTHER INFORMATION**

**This safety data sheet contains changes from the previous version in sections:** New Safety Data Sheet format.

**Prepared by:** Product Safety and Regulatory Affairs

**Issue date:** 03/01/2018

**DISCLAIMER:** The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.