



Printing Date 11/08/2013 Revision Number 1 Revision Date 11/08/2013

### 1 Identification

· Product identifier

· Trade name: 42223 (Kalex 42223 Part A)

· Article number: 42223

· Relevant identified uses of the substance or mixture. Adhesive

· Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

Royal Adhesives And Sealants, LLC

2001 W. Washington Street South Bend IN 46628-2023

Information Phone Number: 574-246-5000

· Information department: Environment protection department.

· Emergency telephone number: ChemTrec: UNITED STATES 1(800)424-9300 INTERNATIONAL 703-527-3887

## 2 Hazard(s) identification

· Classification of the substance or mixture



GHS08 Health hazard

Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335 May cause respiratory irritation.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms





GHS07

GHS08

- · Signal word Danger
- · Hazard statements

Causes skin irritation.

Causes serious eve irritation.

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause an allergic skin reaction.

May cause respiratory irritation.

(Contd. on page 2)

Printing Date 11/08/2013 Revision Number 1 Revision Date 11/08/2013

Trade name: 42223 (Kalex 42223 Part A)

(Contd. of page 1)

#### · Precautionary statements

If medical advice is needed, have product container or label at hand.

Keep out of reach of children.

Read label before use.

*In case of inadequate ventilation wear respiratory protection.* 

Avoid breathing dust/fume/gas/mist/vapours/spray.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

Specific treatment (see on this label).

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 2Fire = 1Reactivity = 1

· HMIS-ratings (scale 0 - 4)



2 Health = 2

1 Fire = 1

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

### 3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: polymer
- · Dangerous components:

and Non-Dangerous Components:

	polyether polyol	50-100%
5124-30-1	Dicyclohexylmethane-4,4'-Diisocyanate	25-50%

### 4 First-aid measures

- · Description of first aid measures
- · After inhalation:

Supply fresh air or oxygen; call for doctor.

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact:

Wipe excess from skin.

*Immediately wash with water and soap and rinse thoroughly.* 

- · After eye contact: Rinse opened eye for 20 minutes under running water. Call a Doctor immediately.
- · After swallowing:

Rinse out mouth with water. Drink 1 - 2 glasses of water but DO NOT induce vomiting. Do not give liquids to a drowsy, convulsing or unconscious person. If vomiting occurs spontaneously, keep head below hips to prevent aspiration.

(Contd. on page 3)

Printing Date 11/08/2013 Revision Number 1 Revision Date 11/08/2013

Trade name: 42223 (Kalex 42223 Part A)

(Contd. of page 2)

Seek medical treatment.

- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

### 5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray.

*Use fire fighting measures that suit the environment.* 

- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: Protective clothing and respiratory protective device.

#### 6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

- Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Cover spilled material with neutralization solution (see below) and mix Wait 15 minutes. Collect material in openhead metal containers. Repeat neutralization and cleaning process until surface is decontaminated. Apply drum lid but DO NOT secure. Allow containers to vent for 72 hours to let carbon dioxide escape.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose of contaminated material as waste in accordance with federal state and local regulations.

· Reference to other sections

Neutralization solutions:

- 1. A mixture of 90% water. 3-8% ammonium hydroxide or concentrated ammonia, and 2% liquid detergent.
- 2. A mixture of 80% water, 20% non-ionic surfactant.

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

#### 7 Handling and storage

- · Handling:
- · Precautions for safe handling

Avoid prolonged or repeated contact with skin.

Avoid contact with eyes.

Wash thoroughly after handling.

Open containers in a well ventilated area and avoid breathing headspace vapors.

Store in tightly closed containers to prevent moisture contamination. Do not reseal container if contamination is suspected. Optimum storage temperature is 80F to 100F.

Prevent formation of aerosols.

· Information about protection against explosions and fires:

Product reacts with water. Reaction may produce heat and/or gases. Container may rupture from gas generation in a fire situation. This reaction may be violent.

(Contd. on page 4)

Printing Date 11/08/2013 Revision Number 1 Revision Date 11/08/2013

Trade name: 42223 (Kalex 42223 Part A)

(Contd. of page 3)

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Keep containers tightly closed when not in use. Protect from atmospheric moisture.

· Information about storage in one common storage facility:

Store away from oxidizing agents.

Keep away from open flames and high temperatures.

· Further information about storage conditions:

Store in tightly closed containers to prevent moisture contamination. Do not reseal if contamination is suspected. Optimun storage temperature is 80F to 100F.

· Specific end use(s) No further relevant information available.

### 8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment (see listings below)
- · General protective and hygienic measures: Wash hands before breaks and at the end of work.
- · Breathing equipment:

In the absence of adequate ventilation, use NIOSH-certified respiratory protection when chemical exposure is excessive or above an established exposure limit. Comply with OSHA 29 CFR 1910.134.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· Material of gloves

Nitrile rubber, NBR

Butyl rubber, BR

Chloroprene rubber, CR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

· Body protection:

Apron

(Contd. on page 5)

Printing Date 11/08/2013 Revision Number 1 Revision Date 11/08/2013

Trade name: 42223 (Kalex 42223 Part A)

Protective work clothing

(Contd. of page 4)

· Information on basic physical and c	hemical properties	
· General Information	nemicui properties	
· Appearance:		
Form:	Liquid	
Color:	Clear	
· Odor:	Musty	
· Odour threshold:	Not determined.	
· pH-value:	Not determined.	
· Change in condition		
Melting point:	Undetermined.	
Boiling point:	Undetermined.	
· Flash point:	> 125 °C (> 257 °F)	
· Flammability (solid, gaseous):	Not applicable.	
· Ignition temperature:		
Decomposition temperature:	Not determined.	
· Auto igniting:	Product is not selfigniting.	
· Danger of explosion:	Product does not present an explosion hazard.	
· Flammable limits:		
Lower:	Not determined.	
Upper:	Not determined.	
· Vapor pressure:	Not determined.	
· Specific gravity at 20 °C (68 °F):	1.03 g/cm³ (8.595 lbs/gal)	
· Relative density	Not determined.	
· Vapour density	Not determined.	
· Evaporation rate	Not determined.	
· Solubility in / Miscibility with		
Water:	Not miscible or difficult to mix.	
· Partition coefficient (n-octanol/wate	r): Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:	0.0 %	
VOC (Per EPA 24)	not available GMS/L	
· Other information	No further relevant information available.	

USA ·

Printing Date 11/08/2013 Revision Number 1 Revision Date 11/08/2013

Trade name: 42223 (Kalex 42223 Part A)

(Contd. of page 5)

## 10 Stability and reactivity

- · Reactivity
- · Chemical stability
- · Thermal decomposition / conditions to be avoided:

Contact with moisture, other materials that react with isocyanates, or temperatures above 350F (177C), may cause polymerization.

· Possibility of hazardous reactions

Contact with moisture, other materials that react with isocyanates, or temperatures above 350F, may cause polymerization.

- · Conditions to avoid Avoid high temperatures. Avoid freezing.
- · Incompatible materials:

Reacts with amines, caustic alkali solutions, alcohols, ammonia, oxidizers, acids, polyols.

Reacts with water forming carbon dioxide-may rupture sealed containers if contaminated with water.

· Hazardous decomposition products:

Carbon Dioxide, Carbon Monoxide, Nitrogen Oxides, Isocyanate vapor and mist, traces of Hydrogen Cyanide.

## 11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · Primary irritant effect:
- · on the skin:

Skin irritant.

Skin contact may cause an allergic skin reaction.

- · on the eye: May be severely irritating to the eyes.
- · Sensitization: Prolonged or repeated contact may cause sensitization to the skin and lungs.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Harmful

Irritant

- · Carcinogenic categories
- · IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

· NTP (National Toxicology Program)

None of the ingredients is listed.

#### 12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- Additional ecological information:
- General notes: At present there are no ecotoxicological assessments.
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

(Contd. on page 7)

Printing Date 11/08/2013 Revision Number 1 Revision Date 11/08/2013

Trade name: 42223 (Kalex 42223 Part A)

· Other adverse effects No further relevant information available.

(Contd. of page 6)

### 13 Disposal considerations

- · Waste treatment methods
- · Recommendation: Must be specially treated adhering to official regulations.
- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

	_		-		
14'	Pran	cno	rt in	form	ation
		עעות			45444 <b>5</b> 44

· UN-Number	
-------------	--

· DOT, ADR, ADN, IMDG, IATA Void

· UN proper shipping name

· DOT, ÂDR, ÂDN, IMDG, IATA Void

· Transport hazard class(es)

· DOT, ADR, ADN, IMDG, IATA

· Class Void

· Packing group

· DOT, ADR, IMDG, IATA Void

• Environmental hazards: Not applicable.

· Special precautions for user Not applicable.

Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code Not applicable.

· UN "Model Regulation":

## 15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara
- · Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

5124-30-1 Dicyclohexylmethane-4,4'-Diisocyanate

· TSCA (Toxic Substances Control Act):

All components of this product are on the TSCA Inventory or are exempt from TSCA Inventory requirements.

- · Proposition 65
- · Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity:

None of the ingredients is listed.

(Contd. on page 8)

Printing Date 11/08/2013 Revision Number 1 Revision Date 11/08/2013

Trade name: 42223 (Kalex 42223 Part A)

(Contd. of page 7)

· (DSL) Canada Dosmestic Substance List

All components of this product are on the DSL(Canada Domestic Substance list) or are exempt from DSL requirements.

- · Cancerogenity categories
- · EPA (Environmental Protection Agency)

None of the ingredients is listed.

· TLV (Threshold Limit Value established by ACGIH)

None of the ingredients listed.

· MAK (German Maximum Workplace Concentration)

None of the ingredients is listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

- · National regulations:
- · Water hazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.
- · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

## **16 Other information**

Although the information and recommendations set forth in this MSDS are presented in good faith and are believed to be correct as of the date of this MSDS, Royal Adhesives & Sealants makes no representations as to the completeness or accuracy thereof. Information is supplied on the condition that the persons receiving and using it will make their own determination as to the suitability for their purpose prior to use. In no event will Royal Adhesives & Sealants or any affiliate thereof be responsible for damages of any nature whatsoever resulting from the use or reliance on the information set forth in the MSDS.

- · Department issuing MSDS: Environment protection department.
- · Creation Date: 11/08/2013
- · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International

Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA)

USA ·





Printing Date 11/12/2013 Revision Number 1 Revision Date 11/08/2013

### 1 Identification

· Product identifier

· Trade name: 52223 (Kalex 52223 Part B)

· Article number: 52223

· Relevant identified uses of the substance or mixture. Adhesive

· Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

Royal Adhesives And Sealants, LLC

2001 W. Washington Street

South Bend IN 46628-2023

Information Phone Number: 574-246-5000

· Information department: Environment protection department.

· Emergency telephone number: ChemTrec: UNITED STATES 1(800)424-9300 INTERNATIONAL 703-527-3887

### 2 Hazard(s) identification

· Classification of the substance or mixture



GHS05 Corrosion

Skin Corr. 1C H314 Causes severe skin burns and eye damage.



STOT SE 3 H335 May cause respiratory irritation.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms





GHS05

GHS07

- · Signal word Danger
- · Hazard statements

Causes severe skin burns and eye damage.

May cause respiratory irritation.

· Precautionary statements

If medical advice is needed, have product container or label at hand.

Keep out of reach of children.

Read label before use.

Do not breathe dust/fume/gas/mist/vapours/spray.

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

(Contd. on page 2)

Printing Date 11/12/2013 Revision Number 1 Revision Date 11/08/2013

Trade name: 52223 (Kalex 52223 Part B)

(Contd. of page 1)

Immediately call a POISON CENTER or doctor/physician.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 2Fire = 1Reactivity = 0

· HMIS-ratings (scale 0 - 4)



2 Health = 2 Fire = 1

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable. · vPvB: Not applicable.

## 3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture

· Dangerous components:			
dicarboxylic acid esters	25-50%		
Polymeric Aliphatic Amine	25-50%		

### 4 First-aid measures

- · Description of first aid measures
- · After inhalation:

Supply fresh air or oxygen; call for doctor.

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact:

Wipe excess from skin.

*Immediately wash with water and soap and rinse thoroughly.* 

- · After eye contact: Rinse opened eye for 20 minutes under running water. Call a Doctor immediately.
- · After swallowing:

Rinse out mouth with water. Drink 1 - 2 glasses of water but DO NOT induce vomiting. Do not give liquids to a drowsy, convulsing or unconscious person. If vomiting occurs spontaneously, keep head below hips to prevent aspiration.

Seek medical treatment.

- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

Printing Date 11/12/2013 Revision Number 1 Revision Date 11/08/2013

Trade name: 52223 (Kalex 52223 Part B)

(Contd. of page 2)

### 5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray.

Use fire fighting measures that suit the environment.

- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: Protective clothing and respiratory protective device.

#### 6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose of contaminated material as waste in accordance with federal state and local regulations.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

#### 7 Handling and storage

- · Handling:
- · Precautions for safe handling

Avoid prolonged or repeated contact with skin.

Avoid contact with eyes.

Wash thoroughly after handling.

Store in cool, dry place in tightly closed receptacles.

Prevent formation of aerosols.

- · Information about protection against explosions and fires: No special measures required.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- Information about storage in one common storage facility: Store away from oxidizing agents.
- · Further information about storage conditions:

Protect from contamination.

Keep receptacle tightly sealed.

· Specific end use(s) No further relevant information available.

## 8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

The Polymeric Aliphatic Amine used in this product has an established New Chemical Exposure Limit (NCEL) of 0.14 mg/m3 as an eight hour time weighted averge. Avoid skin contact. avoid breathing substance. avoid

(Contd. on page 4)

Printing Date 11/12/2013 Revision Number 1 Revision Date 11/08/2013

Trade name: 52223 (Kalex 52223 Part B)

(Contd. of page 3)

ingestion, use respiratory protection, or maintain workplace airborne concentrations at or below the timeweighted average of 0.14 mg/m3. Use skin protection.

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment (see listings below)
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

#### · Breathing equipment:

Not necessary if room is well-ventilated.

Use approved respiratory protection equipment when airborne exposure is excessive. Consult the respirator manufacturer to determine the appropriate type of equipment for a given application. Observe respirator use limitations specified by the manufacturer.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· Material of gloves

Chloroprene rubber, CR

Ansell - NEOX Style 9-912 gloves.

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

Safety glasses with side shields.

· Body protection: Protective work clothing

#### 9 Physical and chemical properties

- · Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Liquid
Color: Black

Odor: Characteristic
 Odour threshold: Not determined.

· pH-value: Not determined.

· Change in condition

Melting point:Undetermined.Boiling point:Undetermined.

(Contd. on page 5)

Printing Date 11/12/2013 Revision Number 1 Revision Date 11/08/2013

Trade name: 52223 (Kalex 52223 Part B)

		(Contd. of page
Flash point:	> 125 °C (> 257 °F)	
Flammability (solid, gaseous):	Not applicable.	
· Ignition temperature:		
Decomposition temperature:	Not determined.	
· Auto igniting:	Product is not selfigniting.	
Danger of explosion:	Product does not present an explosion hazard.	
Flammable limits:		
Lower:	Not determined.	
Upper:	Not determined.	
· Vapor pressure:	Not determined.	
Specific gravity at 20 °C (68 °F):	0.99 g/cm <sup>3</sup> (8.262 lbs/gal)	
Relative density	Not determined.	
Vapour density	Not determined.	
Evaporation rate	Not determined.	
Solubility in / Miscibility with		
Water:	Not miscible or difficult to mix.	
Partition coefficient (n-octanol/water	e <b>r</b> ): Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
Solvent content:		<u> </u>
Organic solvents:	0.0 %	
VOC (Per EPA 24)	not available GMS/L	
Other information	No further relevant information available.	

## 10 Stability and reactivity

- · Reactivity
- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid Moisture
- · Incompatible materials: Reacts with strong oxidizing agents.
- · Hazardous decomposition products: Oxides of carbon and nitrogen.

## 11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · Primary irritant effect:
- · on the skin: Skin irritant.
- · on the eye: May be severely irritating to the eyes.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

Inhalation - May cause irritation of respiratory tract.

(Contd. on page 6)

Printing Date 11/12/2013 Revision Number 1 Revision Date 11/08/2013

Trade name: 52223 (Kalex 52223 Part B)

(Contd. of page 5)

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

· NTP (National Toxicology Program)

None of the ingredients is listed.

## 12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes: At present there are no ecotoxicological assessments.
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

## 13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Incineration is the preferred method.

Must be specially treated adhering to official regulations.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

## 14 Transport information

· UN-Number	
-------------	--

· DOT, ADR, IMDG, IATA UN1760

· UN proper shipping name

DOT
 ADR
 Corrosive liquids, n.o.s. (Polymeric Aliphatic Amine)
 1760 Corrosive liquids, n.o.s. (Polymeric Aliphatic Amine)

· IMDG, IATA CORROSIVE LIQUID, N.O.S. (Polymeric Aliphatic Amine)

(Contd. on page 7)

USA

Printing Date 11/12/2013 Revision Number 1 Revision Date 11/08/2013

Trade name: 52223 (Kalex 52223 Part B)

(Contd. of page 6)

· Transport hazard class(es)

 $\cdot DOT$ 



· Class 8 Corrosive substances.

· Label

· ADR, IMDG, IATA



· Class 8 Corrosive substances

· Label

· Packing group

· DOT, ADR, IMDG, IATA III

· Environmental hazards: Not applicable.

· Special precautions for user Warning: Corrosive substances

Danger code (Kemler): 80EMS Number: F-A,S-B

· Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code Not applicable.

· UN ''Model Regulation'': UN1760, Corrosive liquids, n.o.s. (Polymeric Aliphatic Amine), 8,

III

### 15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara
- · Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

· TSCA (Toxic Substances Control Act):

All components of this product are on the TSCA Inventory or are exempt from TSCA Inventory requirements.

- · Proposition 65
- · Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity:

None of the ingredients is listed.

· (DSL) Canada Dosmestic Substance List

All components of this product are on the DSL(Canada Domestic Substance list) or are exempt from DSL requirements.

(Contd. on page 8)

Printing Date 11/12/2013 Revision Number 1 Revision Date 11/08/2013

Trade name: 52223 (Kalex 52223 Part B)

(Contd. of page 7)

· Cancerogenity categories

· EPA (Environmental Protection Agency)

None of the ingredients is listed.

· TLV (Threshold Limit Value established by ACGIH)

None of the ingredients listed.

· MAK (German Maximum Workplace Concentration)

None of the ingredients is listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

- · National regulations:
- · Water hazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.
- · Other regulations, limitations and prohibitive regulations

The Polymeric Aliphatic Amine used in this product is subject to a TSCA 5(e) consent order and significant new use rule (SNUR) codified at 40 CFR 721.10199.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

## 16 Other information

Although the information and recommendations set forth in this MSDS are presented in good faith and are believed to be correct as of the date of this MSDS, Royal Adhesives & Sealants makes no representations as to the completeness or accuracy thereof. Information is supplied on the condition that the persons receiving and using it will make their own determination as to the suitability for their purpose prior to use. In no event will Royal Adhesives & Sealants or any affiliate thereof be responsible for damages of any nature whatsoever resulting from the use or reliance on the information set forth in the MSDS.

- · Department issuing MSDS: Environment protection department.
- · Creation Date: 11/08/2013
- · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organization

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA)

USA