



Revision Number: 004.1

Issue date: 03/15/2013

## 1. PRODUCT AND COMPANY IDENTIFICATION

<b>Product name:</b>	<b>3924 Light Cure Medical Device</b>	<b>IDH number:</b>	434105
	<b>Adhesive Visible/UV Cure Fluorescent</b>		
<b>Product type:</b>	Ultraviolet adhesive	<b>Item number:</b>	36488
		<b>Region:</b>	United States
<b>Company address:</b>	<b>Contact information:</b>		
Henkel Corporation	Telephone: 860.571.5100		
One Henkel Way	MEDICAL EMERGENCY Phone: Poison Control Center		
Rocky Hill, Connecticut 06067	1-877-671-4608 (toll free) or 1-303-592-1711		
	TRANSPORT EMERGENCY Phone: CHEMTREC		
	1-800-424-9300 (toll free) or 1-703-527-3887		
	Internet: www.henkelna.com		

## 2. HAZARDS IDENTIFICATION

### EMERGENCY OVERVIEW

<b>Physical state:</b>	Liquid	<b>HEALTH:</b>	*2
<b>Color:</b>	Transparent, Hazy	<b>FLAMMABILITY:</b>	2
<b>Odor:</b>	Mild	<b>PHYSICAL HAZARD:</b>	1
		<b>Personal Protection:</b>	See MSDS Section 8

**WARNING:** COMBUSTIBLE LIQUID AND VAPOR.  
HARMFUL IF SWALLOWED, ABSORBED THROUGH SKIN OR INHALED.  
DO NOT SPRAY. DO NOT HEAT.  
MAY CAUSE ALLERGIC SKIN REACTION.  
CAUSES EYE, SKIN AND RESPIRATORY TRACT IRRITATION.

**Relevant routes of exposure:** Skin, Inhalation, Eyes

### Potential Health Effects

<b>Inhalation:</b>	Modified acrylamide is harmful if inhaled. Vapors and mists will irritate nose and throat and possibly eyes. Headache. Nausea. Causes respiratory tract irritation. DO NOT heat or spray as this increases the inhalation hazard.
<b>Skin contact:</b>	Modified acrylamide may be absorbed through skin in harmful amounts. Toxic. May cause allergic skin reaction. Causes skin irritation.
<b>Eye contact:</b>	Contact with eyes will cause irritation.
<b>Ingestion:</b>	Modified acrylamide is harmful if swallowed. Toxic.

**Existing conditions aggravated by exposure:** Eye, skin, and respiratory disorders.

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

See Section 11 for additional toxicological information.

### 3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous components	CAS NUMBER	%
Urethane Polymer	Proprietary	30 - 60
Acrylate monomer	Proprietary	30 - 60
N,N-Dimethylacrylamide	2680-03-7	10 - 30
Photoinitiator	947-19-3	1 - 5
Substituted silane	Proprietary	1 - 5
2-Hydroxyethyl acrylate	818-61-1	0.1 - 1

### 4. FIRST AID MEASURES

<b>Inhalation:</b>	Move to fresh air. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. If symptoms develop and persist, get medical attention.
<b>Skin contact:</b>	Immediately flush skin with plenty of water (using soap, if available). Remove contaminated clothing and footwear. Wash clothing before reuse. If symptoms develop and persist, get medical attention.
<b>Eye contact:</b>	Flush with copious amounts of water, preferably, lukewarm water for at least 15 minutes, holding eyelids open all the time. Get immediate medical attention.
<b>Ingestion:</b>	Do not induce vomiting. Keep individual calm. Never give anything by mouth to an unconscious person. Get immediate medical attention.

### 5. FIRE FIGHTING MEASURES

<b>Flash point:</b>	78 °C (172.4 °F) Pensky Martens closed cup
<b>Autoignition temperature:</b>	Not available.
<b>Flammable/Explosive limits - lower:</b>	Not available.
<b>Flammable/Explosive limits - upper:</b>	Not available.
<b>Extinguishing media:</b>	Water spray (fog), foam, dry chemical or carbon dioxide. Do not use high volume water jet.
<b>Special firefighting procedures:</b>	Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear. Water may be unsuitable as an extinguishing media, but may be helpful in keeping adjacent containers cool.
<b>Unusual fire or explosion hazards:</b>	Uncontrolled polymerization may occur at high temperatures resulting in explosions or rupture of storage containers.
<b>Hazardous combustion products:</b>	Oxides of carbon. Oxides of silicon. Oxides of nitrogen. Oxides of phosphorus. Formaldehyde. Irritating organic vapours. Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

### 6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

<b>Environmental precautions:</b>	Do not allow product to enter sewer or waterways.
<b>Clean-up methods:</b>	Remove all sources of ignition. Ensure adequate ventilation. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Store in a partly filled, closed container until disposal. Refer to Section 8 "Exposure Controls / Personal Protection" prior to clean up.

## 7. HANDLING AND STORAGE

<b>Handling:</b>	Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist. Wash thoroughly after handling. Do not taste or swallow. DO NOT heat or spray. Use only in area provided with appropriate exhaust ventilation. Keep container closed. Refer to Section 8.
<b>Storage:</b>	For safe storage, store at or below 26 °C (78.8 °F) Keep in a cool, well ventilated area away from heat, sparks and open flame. Keep container tightly closed until ready for use.

For information on product shelf life contact Henkel Customer Service at (800) 243-4874.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous components	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Urethane Polymer	None	None	None	None
Acrylate monomer	None	None	None	None
N,N-Dimethylacrylamide	None	None	None	0.1 mg/m3 TWA (Skin) 0.025 ppm TWA (Skin)
Photoinitiator	None	None	None	None
Substituted silane	None	None	None	None
2-Hydroxyethyl acrylate	None	None	None	None

<b>Engineering controls:</b>	Local exhaust ventilation is recommended when general ventilation is not sufficient to control airborne contamination below occupational exposure limits.
<b>Respiratory protection:</b>	Use NIOSH approved respirator if there is potential to exceed exposure limit(s). If this material is handled at elevated temperatures or under mist forming conditions, without engineering controls, a NIOSH approved respirator must be used.
<b>Eye/face protection:</b>	Safety goggles or safety glasses with side shields. Full face protection should be used if the potential for splashing or spraying of product exists.
<b>Skin protection:</b>	Use impermeable gloves and protective clothing as necessary to prevent skin contact. Neoprene gloves.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Physical state:</b>	Liquid
<b>Color:</b>	Transparent, Hazy
<b>Odor:</b>	Mild
<b>Odor threshold:</b>	Not available.
<b>pH:</b>	Not applicable
<b>Vapor pressure:</b>	Not available.
<b>Boiling point/range:</b>	> 93.0 °C (> 199.4 °F)
<b>Melting point/ range:</b>	Not available.
<b>Specific gravity:</b>	1.1454
<b>Vapor density:</b>	Not available.
<b>Flash point:</b>	78 °C (172.4 °F) Pensky Martens closed cup
<b>Flammable/Explosive limits - lower:</b>	Not available.
<b>Flammable/Explosive limits - upper:</b>	Not available.
<b>Autoignition temperature:</b>	Not available.
<b>Evaporation rate:</b>	Not available.
<b>Solubility in water:</b>	Slight
<b>Partition coefficient (n-octanol/water):</b>	Not available.
<b>VOC content:</b>	0.52 %; 5.95 g/l (process)

0.74 %; 8.47 g/l (potential)  
1.25 %; 14.31 g/l (total)  
(ASTM D5403)

## 10. STABILITY AND REACTIVITY

<b>Stability:</b>	Stable under normal conditions of storage and use.
<b>Hazardous reactions:</b>	May occur.
<b>Hazardous decomposition products:</b>	Oxides of carbon. Oxides of nitrogen. Oxides of silicon. Oxides of phosphorus. Formaldehyde.
<b>Incompatible materials:</b>	Strong oxidizing agents. Strong acids. Reducing agents. Bases. Peroxides. Free radical initiators. Other polymerization initiators.
<b>Conditions to avoid:</b>	Heat, flames, sparks and other sources of ignition. Avoid temperatures above 26°C (80°F). Store away from incompatible materials. Direct sunlight. UV light. Moisture.

## 11. TOXICOLOGICAL INFORMATION

<b>Acute oral product toxicity:</b>	Modified acrylamide LD50 (rat) 316 mg/kg
<b>Acute dermal product toxicity:</b>	Modified acrylamide LD50 (rabbit) 518 mg/kg
<b>Acute inhalation product toxicity:</b>	Modified acrylamide LC50 (rat) 1.00 h > 776 ppm

Hazardous components	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Urethane Polymer	No	No	No
Acrylate monomer	No	No	No
N,N-Dimethylacrylamide	No	No	No
Photoinitiator	No	No	No
Substituted silane	No	No	No
2-Hydroxyethyl acrylate	No	No	No

Hazardous components	Health Effects/Target Organs
Urethane Polymer	No Records
Acrylate monomer	Irritant, Allergen
N,N-Dimethylacrylamide	Irritant, Eyes, Mutagen, Kidney, Less weight gain and food intake.
Photoinitiator	No Records
Substituted silane	Irritant, Allergen
2-Hydroxyethyl acrylate	Allergen, Central nervous system, Heart, Irritant, Kidney, Liver, Lung, Some evidence of carcinogenicity, Spleen

## 12. ECOLOGICAL INFORMATION

<b>Ecological information:</b>	Not available.
--------------------------------	----------------

### 13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

**Recommended method of disposal:** Dispose of according to Federal, State and local governmental regulations.

**Hazardous waste number:** Not a RCRA hazardous waste.

### 14. TRANSPORT INFORMATION

#### U.S. Department of Transportation Ground (49 CFR)

**Proper shipping name:** Combustible liquid, n.o.s. (Modified Acrylamide)  
**Hazard class or division:** Combustible Liquid  
**Identification number:** NA 1993  
**Packing group:** III

#### International Air Transportation (ICAO/IATA)

**Proper shipping name:** Environmentally hazardous substance, liquid, n.o.s. (Isobornyl acrylate)  
**Hazard class or division:** 9  
**Identification number:** UN 3082  
**Packing group:** III

#### Water Transportation (IMO/IMDG)

**Proper shipping name:** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Isobornyl acrylate)  
**Hazard class or division:** 9  
**Identification number:** UN 3082  
**Packing group:** III  
**Marine pollutant:** Isobornyl acrylate

### 15. REGULATORY INFORMATION

#### United States Regulatory Information

**TSCA 8 (b) Inventory Status:** All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.  
**TSCA 12(b) Export Notification:** None above reporting de minimus  
**CERCLA/SARA Section 302 EHS:** None above reporting de minimis  
**CERCLA/SARA Section 311/312:** Immediate Health, Delayed Health, Fire  
**CERCLA/SARA 313:** None above reporting de minimis  
**California Proposition 65:** No California Proposition 65 listed chemicals are known to be present.

#### Canada Regulatory Information

**CEPA DSL/NDSL Status:** Contains one or more components listed on the Non-Domestic Substances List. All other components are listed on or are exempt from listing on the Domestic Substances List. Components listed on the NDSL must be tracked by all Canadian Importers of Record as required by Environment Canada. They may be imported into Canada in limited quantities. Please contact Regulatory Affairs for additional details.  
**WHMIS hazard class:** B.3, D.1.B, D.2.B

### 16. OTHER INFORMATION

This material safety data sheet contains changes from the previous version in sections: 1 and 16

**Prepared by:** Diane Annis, Sr. Regulatory Affairs Specialist

**DISCLAIMER:** The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.