



Revision Date: 01 JAN 2019

Version: 4.0

SECTION I: CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Identifier: Aeriol Thixo #2 Aviation Grease

Product Use: Lubricant grease.

Restrictions on Use: Refer to Grease Compatibility Chart

Manufacturer / Supplier: Awsum Outcomes Inc.

Bay 5 409 38 Ave NE Calgary, Alberta

Canada T2E 6R9

CANUTEC – 24 hr Emergency No.

Emergency Phone Number: 1-613-996-6666 Business Hour Number

1-587-353-2000

(Monday through Friday 8:00am to 4:30pm MST)

Revision Date: 01 JAN 2019

Version: 4.0 Page **1** of **15**



GHS Classification:

Product: AERIOL THIXO #2 AVIATION GREASE

Revision Date: 01 JAN 2019

Version: 4.0

SECTION II: HAZARDS IDENTIFICATION

Causes no serious eye irritation: May not cause an allergic skin	Not a hazardous substance				
reaction:	Not a hazardous substance				
GHS Label Element:					
Signal word :	Not a hazardous substance				
Hazard symbol:	None				
Hazard statements:	None				
Other hazards:	None				
Precautionary statements:	Prevention: P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray. P264 Wash skin thoroughly after handling. P272 Contaminated work clothing should not be allowed out of the workplace. P280 Wear eye protection/ face protection. P280 Wear protective gloves. Response: P302 + P352 IF ON SKIN: Wash with plenty of soap and water. P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention. P337 + P313 If eye irritation persists: Get medical				

advice/attention.

Revision Date: 01 JAN 2019 Version: 4.0



Revision Date: 01 JAN 2019

Version: 4.0

P363 Wash contaminated clothing before reuse.

Disposal:

P501 Dispose of contents/container to an approved waste

disposal plant.

Storage:

P411+235: Store at temperatures not exceeding 190°C/374 °F.

Keep cool.

Carcinogenicity:

IARC

No component of this product present at levels greater than or

equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

OSHA

No component of this product present at levels greater than or

equal to 0.1% is identified as a carcinogen or potential

Carcinogen by OSHA.

NTP

No component of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated

carcinogen by NTP.

SECTION III: COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous Ingredients	Concentration %	C.A.S. #
Distillates (petroleum), solvent-refined heavy paraffinic	>= 50 - < 70 %	64741-88-4
Residual oils (petroleum), solvent-refined	>= 10 - < 20 %	64742-01-4
Calcium carbonate (dust)	>= 5 - < 10 %	471-34-1
Benzenesulfonic acid, C10-16 – alkly derivatives, calcium salts	>= 1 - < 5 %	68584-23-6
Calcium dodecylbenzenesulphonate	>= 1 - < 5 %	26264-06-2
Sulfonic acids, petroleum, calcium salts	>= 1 - < 5 %	61789-86-4
Benzenesulfonic acid, mono C16-24 – alkyl derivatives, calcium salts	>= 1 - < 5 %	70024-69-0

Revision Date: 01 JAN 2019

Version: 4.0 Page **3** of **15**



AWSUM OUTCOMES INC. SAFETY DATA SHEET

Product: AERIOL THIXO #2 AVIATION GREASE

Revision Date: 01 JAN 2019

Version: 4.0

SECTION IV: FIRST AID MEASURES

Ingestion: Obtain medical attention. Never give anything by mouth to an

unconscious person. Not expected to be toxic by ingestion.

Skin Contact: Wash off with warm water and soap. If hot material contacts

skin, immediately cool before attempting removal. If skin irritation persists, call a physician. If high pressure forces the product under the skin get immediate medical attention!

Inhalation: Remove to fresh air. Aspiration may cause pulmonary oedema

and pneumonitis. If breathing is difficult, oxygen may be given by qualified personnel. If symptoms persist, consult physician.

Eye Contact: Flush with clean tepid water for 15 minutes keeping eyelids

open. Get medical attention immediately.

 $\\ Most \ important \ symptoms \ and$

effects, both acute and delayed:

Irritating to respiratory tract and eyes. Breathing mist caused by high temperature or swallowing large quantities may be irritating to skin, respiratory system, mucous membranes and

eyes.

SECTION V: FIRE-FIGHTING MEASURES

Suitable extinguishing media: On small fires: carbon dioxide (CO₂), dry chemicals, dry sand -

vermiculite. On large fires: treat as an oil fire, water fog, foam,

Unsuitable extinguishing media: Avoid spreading with water flooding.

Hazardous combustion

products:

Oxides of carbon, Sulphur, calcium.

Special extinguishing methods: Keep containers cool with water spray. Prevent fire

extinguishing water from contaminating surface water or the

ground water system.

Special protective equipment

and precautions for firefighters:

When fighting fire, treat as petroleum product, wear full protective clothing, including NIOSH approved self-contained

breathing apparatus.

Fire and explosion hazards:

Revision Date: 01 JAN 2019

Version: 4.0 Page **4** of **15**





Revision Date: 01 JAN 2019

Version 4.0

Do not cut, weld, or pressurize empty container. Container may

explode in heat of fire.

SECTION VI: ACCIDENTAL RELEASE MEASURES

Personal protection: Wear suitable protective equipment. Eliminate sources and or

potential sources of ignition.

Environmental precautions: Product has very low solubility in water. Do not flush to sewers,

streams or other bodies of water. For disposal, see Section XIII.

Methods for cleaning up: Absorb on inert material such as sand, earth, vermiculite. Sweep

up and collect in a suitable container for disposal. Observe

government regulations

Large spills: Stop leak if without risk. Dike to contain spill. Pump excess

material into suitable container (metal drums, metal tanks, or

such).

SECTION VII: HANDLING AND STORAGE

Handling: Keep drums tightly closed to prevent contamination. Avoid

contact with eyes, skin and clothing. Wear recommended

personal protection equipment.

Storage: Store in a cool well-ventilated area. Normal precautions common

to goo safety practice should be followed in storage.

Revision Date: 01 JAN 2019

Version: 4.0 Page **5** of **15**



Revision Date: 01 JAN 2019

Version: 4.0

SECTION VIII: EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Limits: If used in a way that generates a mist, observe the limits for

mineral oil mist.

Engineering controls: For normal application, special ventilation is not necessary. If

the user's operation generates mist, use local ventilation to keep exposure to airborne contaminants below exposure limits.

Respiratory protection: None required under normal conditions of use. Use approved

respirator with dual organic vapor/mist and particulate cartridge

if vapor concentration exceeds permissible exposure limit.

Use safety goggles or face shield.

Eye protection:

Use rubber or plastic apron. Wear protective clothing to

Skin protection: minimize skin contact. Use heat protective equipment when

handling molten material.

Use oil resistant gloves.

Hand protection:

USA

Component	CAS#	Form of Exposure	Permissible Concentration	Basis
Distillates (petroleum), solvent-refined heavy	64741-88-4	TWA (mist)	5 mg/m^3	OSHA Z-1
paraffinic				
		TWA (inhalable	5 mg/m^3	ACGIH
		fraction)		
		TWA	5 mg/m^3	OSHA P0
		TWA (mist)	5 mg/m ³	NIOSH REL
		ST (mist)	10 mg/m ³	NIOSH REL
Residual oils (petroleum), solvent-refined	64742-01-4	TWA (mist)	5 mg/m ³	OSHA Z-1
		TWA (inhalable	5 mg/m^3	ACGIH
		fraction)		
		TWA	5 mg/m ³	OSHA P0
		TWA (mist)	5 mg/m ³	NIOSH REL
		ST (mist)	10 mg/m ³	NIOSH REL
Calcium carbonate (dust)	471-34-1	TWA (respirable)	5 mg/m ³	NIOSH REL
		TWA (total)	10 mg/m ³	NIOSH REL

Revision Date: 01 JAN 2019

Version: 4.0 Page **6** of **15**





Revision Date: 01 JAN 2019 Version: 4.0

Components with workplace control parameters :

Canada

Canada	CACA	X7.1	G . 1	D .
Components	CAS-No.	Value type	Control	Basis
		(Form of	parameters /	
		exposure)	Permissible	
Division ()	64741 00 4	TEXTA OF C	concentration	GA PG OFF
Distillates (petroleum),	64741-88-4	TWA (Mist)	0.2 mg/m3	CA BC OEL
solventrefined heavy paraffinic		TEXA A	0.2	GA DO OFF
		TWA	0.2 mg/m3	CA BC OEL
		TWA (Mist)	1 mg/m3	CA BC OEL
		TWA (Mist)	5 mg/m3	CA AB OEL
		STEL (Mist)	10 mg/m3	CA AB OEL
		TWAEV	5 mg/m3	CA QC OEL
		(Mist)		
		STEV (Mist)	10 mg/m3	CA QC OEL
		TWA (Mist)	1 mg/m3	CA BC OEL
Residual oils (petroleum),	64742-01-4	TWA (Mist)	0.2 mg/m3	CA BC OEL
solvent-refined				
		TWA (Mist)	1 mg/m3	CA BC OEL
		TWA (Mist)	5 mg/m3	CA AB OEL
		STEL (Mist)	10 mg/m3	CA AB OEL
		TWAEV	5 mg/m3	CA QC OEL
		(Mist)		
		STEV (Mist)	10 mg/m3	CA QC OEL
		TWA (Mist)	1 mg/m3	CA BC OEL
calcium carbonate	471-34-1	TWAEV	10 mg/m3	CA QC OEL
		(total dust)		
		TWA	10 mg/m3	CA AB OEL
			(Calcium)	
		TWA	10 mg/m3	CA AB OEL
			(Calcium	
			carbonate)	
Distillates (petroleum), solventrefined heavy paraffinic	64741-88-4	TWA (Mist)	0.2 mg/m3	CA BC OEL
		TWA	0.2 mg/m3	CA BC OEL
		TWA (Mist)	1 mg/m3	CA BC OEL
		TWA (Mist)	5 mg/m3	CA AB OEL
		STEL (Mist)	10 mg/m3	CA AB OEL
		TWAEV	5 mg/m3	CA QC OEL
		(Mist)		
		STEV (Mist)	10 mg/m3	CA QC OEL
		TWA (Mist)	1 mg/m3	CA BC OEL
Residual oils (petroleum),	64742-01-4	TWA (Mist)	0.2 mg/m3	CA BC OEL
solvent-refined		(2.222)	<i>G</i>	
		TWA (Mist)	1 mg/m3	CA BC OEL
		TWA (Mist)	5 mg/m3	CA AB OEL

Revision Date: 01 JAN 2019

Version: 4.0



Revision Date: 01 JAN 2019 Version: 4.0

		STEL (Mist)	10 mg/m3	CA AB OEL
		TWAEV	5 mg/m3	CA QC OEL
		(Mist)		
		STEV (Mist)	10 mg/m3	CA QC OEL
		TWA (Mist)	1 mg/m3	CA BC OEL
calcium carbonate	471-34-1	TWAEV	10 mg/m3	CA QC OEL
		(total dust)		
		TWA	10 mg/m3	CA AB OEL
			(Calcium)	
		TWA	10 mg/m3	CA AB OEL
			(Calcium	
			carbonate)	

SECTION IX: PHYSICAL AND CHEMICAL PROPERTIES

Physical State: Semi-solid **Appearance:** Brown

Odor: Mild petroleum odor

Odor Threshold: Not established at 20°C (68°F)

pH:

Drop Point:

Boiling Point:

Flash Point:

Evaporation Rate:

Upper Flammability Limit:

Lower Flammability Limit:

Not applicable

300°C (572°F)

Not available

215°C (420°F)

Not available

Not determined

Not determined

Density: $1.05 \text{g/cm}^3 \text{ at } 25^{\circ}\text{C } (77^{\circ}\text{F})$

Specific Gravity: 0.95 - 1.05

Vapor Pressure: <0.0008 hPa (0.00 mmHg) at 20°C (68°F)

Vapor Density:Not availableSolubility in Water:NegligibleAutoignition Temperature:Not availablePartitioning Coefficient:Not available

SECTION X: STABILITY AND REACTIVITY

Chemical Stability: Stable.

Incompatibility: Avoid contact with oxidizing agents.

Reactivity: No reactivity.

Revision Date: 01 JAN 2019

Version: 4.0 Page **8** of **15**





Revision Date: 01 JAN 2019

Version: 4.0

Polymerization: Will not occur.

Decomposition Products: Oxides of carbon, nitrogen, sulfur, calcium

SECTION XI: TOXICOLOGICAL INFORMATION

Effects of Acute and Chronic

Exposure:

Skin Contact: May cause irritation.

Skin Absorption: If high pressure forces the product under the skin get

immediate medical attention.

Acute dermal toxicity:

Calcium LD50: > 4,199 mg/kg

dodecylbenzenesulphonate Species: rabbit

(component): Remarks: information given is based on data obtained from

similar substances.

Sulfonic acids, petroleum, LD50: > 4,000 mg/kg

calcium salts (component): Species: rabbit

Method: OECD Test Guideline 402

Benzenesulfonic acid, mono-C16- LD50: > 2,000 mg/kg

24-alkly derivatives, calcium salts Species: rat

(component): Method: OECD Test Guideline 402

Skin irritation:

Calcium carbonate (dust) Species: rabbit

(component): Result: no skin irritation

Calcium Species: rabbit

dodecylbenzenesulphonate Result: skin irritation (component): Exposure time: 4h

Remarks: information given is based on data obtained from

similar substances

Eye Contact: May cause irritation.

Eve irritation:

Revision Date: 01 JAN 2019

Version: 4.0 Page 9 of **15**



Revision Date: 01 JAN 2019

Version: 4.0

Calcium carbonate (dust)

(component):

Species: rabbit

Result: no eye irritation

Calcium

dodecylbenzenesulphonate

(component):

Species: rabbit

Result: rise of serious damage to eyes.

Remarks: information given is based on data obtained from

similar substances.

Inhalation:

No information available. Mist or spray may cause delayed onset of pulmonary oedema.

Ingestion:

No significant hazard. No evidence of harmful effect from

available information. May cause diarrhea.

Acute oral toxicity (Product):

Acute toxicity estimate: > 5,000 mg/kg

Irritancy:

Irritation to eyes and respiratory tract. Frequent and prolonged

contact may irritate skin. If misted, inhalation of mist may cause

irritation.

Sensitization:

Repeated or prolonged contact may cause sensitization in some

individuals.

Benzenesulfonic acid. C10-16alkly derivatives, calcium salts

(component):

Result: the product is a skin sensitizer, sub-category 1B.

Sulfonic acids, petroleum,

calcium salts (component):

Benzenesulfonic acid, mono-C16-24-alkyl derivatives, calcium salts

(component):

Result: the product is a skin sensitizer, sub-category 1B.

Result: the product is a skin sensitizer, sub-category 1B.

Carcinogenicity:

This product container material that has not been listed as a carcinogen or potential carcinogen by the National Toxicology

Program. Internation Agency for Research on Cancer, or the

Occupational Safety and Health Administration.

Reproductive Toxicity: No adverse effects are anticipated.

Calcium carbonate (dust)

Species: rat

(component):

Application route: oral

Revision Date: 01 JAN 2019 Version: 4.0





Revision Date: 01 JAN 2019

Version: 4.0

CMR Effects:

Calcium carbonate (dust)

(component):

Teratogenicity: No effect on or via lactation.

Reproductive toxicity: no toxicity to reproduction.

Further Information: No evidence of harmful effects from available information.

SECTION XII: ECOLOGICAL INFORMATION

Toxicity to Fish:

Calcium LC50: 22 mg/L dodecylbenzenesulphonate Exposure time: 96h

(component): Species: Pimephales promelas (fathead minnow)

Static test analytical monitoring: no Method: OECD Test Guideline 203

Remarks: information given is based on data obtained from

similar substances.

Sulfonic acids, petroleum, LC50 > 10,000 mg/L calcium salts (component): Exposure time: 96h

Species: Cyprinodon variegatus (sheepshead minnow)

Static test method: OECD Test Guideline 203

Toxicity to Daphnia and Other Aquatic Invertebrates:

Calcium EC50: 2.5 mg/L dodecylbenzenesulphonate Exposure time: 48h

(component): Species: Daphnia magna (water flea)

Static test method: OECD Test Guideline 202

Remarks: information given is based on data obtained from

similar substances.

Sulfonic acids, petroleum, EC50: > 100mg/L calcium salts (component): Exposure time: 48h

Species: Daphnia magna (water flea)

Static test method: OECD Test Guideline 202

Toxicity to Algae:

Sulfonic acids, petroleum,

calcium salts (component): EbC50: > 100mg/L Exposure time: 72h

r

Revision Date: 01 JAN 2019 Version: 4.0





Revision Date: 01 JAN 2019

Version: 4.0

Species: green algae (Scenedesmus subspicatus)

Static test analytical monitoring: no Method OECD Test Guideline 201

ErC50: > 100 mg/L

Species: green algae (Scenedesmus subspicatus)

Static test analytical monitoring: no Method: OECD Test Guideline 201

Bioaccumulation:

Calcium

dodecylbenzenesulphonate Species: Lepomis macrochirus (bluegill sunfish)

(component): Exposure time: 21d

Bioconcentration factor (BCF): 104

Biodegradability:

Calcium

dodecylbenzenesulphonate Result: readily biodegradable.

(component): Testing period: 28d

Remarks: information given is based on data obtained from

similar substances.

Sulfonic acids, petroleum,

calcium salts (component): Aerobic.

Result: not readily biodegradable.

8.6%

Benzenesulfonic acid, mono-C16-

24-alkyl derivatives, calcium salts

Aerobic.

(component):

Result: according to the results of tests of biodegradability this

product is not readily biodegradable.

8%

Method: OECD Test Guideline 301

Further Information on

Ecology:

Additional ecological information

(product):

No data available.

This product is stable in water, and can be mechanically

separated from water. The water may be suitable for disposal in

a biological waste water treatment plant.

Revision Date: 01 JAN 2019

Version: 4.0 Page **12** of **15**





Revision Date: 01 JAN 2019

Version: 4.0

SECTION XIII: DISPOSAL CONSIDERATION

RCRA 40 CFR 261 Classification: Not Listed

US EPA Waste Number / Classification: Not Available

Waste Disposal: Dispose of waste material in compliance with all federal, state,

> provincial and local regulations. Incinerate in a furnace or bury in an approved landfill where permitted under appropriate

federal, provincial and local regulations.

SECTION XIV: Transport Information

Department of Transport: Not regulated under DOT TDG - Canada: Not regulated under TDG

DOT/TDG Proper Shipping None

Name:

DOT/TDG Hazard Class: None **Product Identification Number:** None **Packing Group:** None

DOT/TDG Labels: Primary: None required None required **Subsidiary: DOT/TDG Placards:** None required

Not dangerous goods ADR: Not dangerous goods RID: **MERCOSUR:** Not dangerous goods Not dangerous goods IATA: Not dangerous goods **IMDG:**

SECTION XV: REGULATORY INFORMATION

CPR Compliance: This product has been classified in accordance with the hazard

> criteria of the Controlled Products Regulations and the SDS contains all of the information required by those regulations.

OSHA Hazard Communication

This product is not known to contain any of the carcinogens Standards 29CFR 1910.1200: required to be listed under OSHA Hazards Communication

Standards 29 CFR 1910.1200.

WHMIS Classification: D₂B

Revision Date: 01 JAN 2019

Version: 4.0 Page 13 of 15





Revision Date: 01 JAN 2019

Version: 4.0

NPRI Components: Diphenylamine CAS# 122-39-4

CERCLA Reportable Quantity:

Calcium CAS# 26264-06-02

dodecylbenzenesulphonate Component RQ (lbs): 1000

(component): Calcium product RQ: calculated RQ exceeds reasonably

attainable upper limit.

SARA 304 Reportable

Quantity:

This material does not contain any components with section 304

EHS RQ.

SARA 311/312 Hazards: Acute Health Hazard

SARA 302: No chemical in this material are subject to the reporting

requirements of SARA Title III, Section 302

SARA 313: This material does not contain any chemical components with

known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

California Prop 65: This product does contain a chemical known to State of

California to cause cancer, birth defects, or any other

reproductive harm(Oxirane 75-21-8).

US, TSCA: On TSCA inventory.

DSL: All components are on the Canadian DSL.

AICS: On the inventory, or in compliance with inventory. NZIoC: On the inventory, or in compliance with inventory.

ENCS: Not in compliance with the inventory.

FICCS:On the inventory, or in compliance with inventory.
On the inventory, or in compliance with inventory. **IECSC:**On the inventory, or in compliance with inventory.

Revision Date: 01 JAN 2019

Version: 4.0 Page **14** of **15**



AWSUM OUTCOMES INC. SAFETY DATA SHEET

Product: AERIOL THIXO #2 AVIATION GREASE

Degree of Hazard


4= Severe
3= Serious
2= Moderate
1= Slight
0= Minimal
*=Chronic

Revision Date: 01 JAN 2019

Version: 4.0

SECTION XVI: Other Information

HMIS Information



Revision Information

Prepared by: Awsum Outcomes Inc.

Phone: 1 587 353 2000 **Effective Date**: 01 JAN 2019

Supersedes: 3.0

Revision: 01 JAN 2019

Awsum Outcomes Inc. (the "Company"), shall not be liable for any damages arising from the information contained on this data sheet howsoever—caused, if the product in question is not employed in a normal or foreseeable use or circumstances. The Company shall not be liable for any indirect—or consequential damages arising out of the use of the information contained on this data sheet howsoever caused.

Revision Date: 01 JAN 2019

Version: 4.0 Page **15** of **15**