

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date: 02/21/2019 Date of issue: 07/26/2013

SECTION 1: Identification

Identification

Product form : Mixture

Product name : COR-BAN 23 AEROSOL

Recommended use and restrictions on use

Use of the substance/mixture : Coating

Recommended use : Coatings and paints, thinners, paint removers

Supplier

Zip-Chem Products 400 Jarvis Drive

Morgan Hill, CA 95037 - United States T 408-782-2335 - F 408-782-6304

4info@zipchem.com

Emergency telephone number

Emergency number : 1-800-424-9300

SECTION 2: Hazard(s) identification

Classification of the substance or mixture

GHS US classification

Flammable aerosols, Category 2

On basis of test

data

Specific target organ toxicity — Repeated exposure,

Category 1

H372 Causes damage to organs through prolonged or repeated exposure.

Expert judgment

Full text of H statements: see section 16

GHS Label elements, including precautionary statements

GHS US labelling

Hazard pictograms (GHS US)





H223 Flammable aerosol.

Signal word (GHS US) : Danger

Hazard statements (GHS US) H223 - Flammable aerosol.

H372 - Causes damage to organs through prolonged or repeated exposure.

Precautionary statements (GHS US) : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P211 - Do not spray on an open flame or other ignition source.

P251 - Do not pierce or burn, even after use.

P260 - Do not breathe dust/fume/gas/mist/vapours/spray.

P264 - Wash hands, forearms and face thoroughly after handling.

P270 - Do not eat, drink or smoke when using this product.

P314 - Get medical advice/attention if you feel unwell.

P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. P501 - Dispose of contents/container to hazardous or special waste collection point, in

accordance with local, regional, national and/or international regulation.

Other hazards which do not result in classification

No additional information available

Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/information on ingredients

Substances 3.1.

Not applicable

3.2. **Mixtures**

Page 1 01/10/2020 EN (English)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Name	Product identifier	%	GHS US classification
hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics	(CAS-No.) 64742-47-8	10-20	Flam. Liq. 4, H227 Asp. Tox. 1, H304
STRAIGHT RUN KEROSINE - SOLVENT NAPHTHA (PETROLEUM), MEDIUM ALIPH.	(CAS-No.) 64742-88-7	5-10	STOT RE 1, H372 Asp. Tox. 1, H304
LOW BOILING POINT HYDROGEN TREATED NAPHTHA - NAPHTHA (PETROLEUM), HYDROTREATED HEAVY	(CAS-No.) 64742-48-9	2-6	Flam. Liq. 3, H226 Muta. Not classified Carc. Not classified Asp. Tox. 1, H304

Full text of hazard classes and H-statements: see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.

First-aid measures after skin contact : Wash skin with plenty of water.

First-aid measures after eye contact : Rinse eyes with water as a precaution.

First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after inhalation : Inhalation may cause irritation (cough, short breathing, difficulty in breathing).

Symptoms/effects after skin contact : irritation (itching, redness, blistering).

Symptoms/effects after eye contact : redness, itching, tears.

Symptoms/effects after ingestion : Burns or irritation of the linings of the mouth, throat, and gastrointestinal tract.

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

5.2. Specific hazards arising from the chemical

Fire hazard : Flammable aerosol.

Hazardous decomposition products in case of : Toxic fumes may be released.

fire

5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing

apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information

refer to section 8: "Exposure controls/personal protection".

Emergency procedures : Evacuate unnecessary personnel. Keep away from combustible material. Stop leak if safe to do

SO.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Mechanically recover the product.

Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

01/10/2020 EN (English) 2/8

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling

: Ensure good ventilation of the work station. Wear personal protective equipment. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use.

Hygiene measures

: Do not eat, drink or smoke when using this product. Always wash hands after handling the

product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions

: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store in a well-ventilated place. Keep cool.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

COR-BAN 23 AEROSOL

No additional information available

STRAIGHT RUN KEROSINE - SOLVENT NAPHTHA (PETROLEUM), MEDIUM ALIPH. (64742-88-7)

No additional information available

LOW BOILING POINT HYDROGEN TREATED NAPHTHA - NAPHTHA (PETROLEUM), HYDROTREATED HEAVY (64742-48-9)

No additional information available

hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics (64742-47-8)

No additional information available

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.

Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Gloves.

Hand protection:

Protective gloves

Eye protection:

Safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

Personal protective equipment symbol(s):





SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid
Appearance : Liquid.
Colour : Red-brown
Odour : aromatic

01/10/2020 EN (English) 3/8

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Odour threshold: No data availablepH: Not applicable.Melting point: No data available.Freezing point: No data available.

Boiling point : > 35 °C Flash point : < 21 °C

Relative evaporation rate (butylacetate=1) : No data available

Flammability (solid, gas) : Not applicable. Flammable aerosol.

Vapour pressure : No data available Relative vapour density at 20 °C : No data available.

Relative density : 0.8
Density : 0.87 g/ml

: Insoluble in water. Solubility Partition coefficient n-octanol/water (Log Pow) : No data available : No data available. Auto-ignition temperature : No data available Decomposition temperature Viscosity, kinematic : 19 - 24 mm²/s : 30 - 46 cP Viscosity, dynamic Explosive limits : No data available Explosive properties : No data available Oxidising properties : No data available

9.2. Other information

VOC content : 528 g/l

SECTION 10: Stability and reactivity

10.1. Reactivity

Flammable aerosol.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

STRAIGHT RUN KEROSINE - SOLVENT NAPHTHA (PETROLEUM), MEDIUM ALIPH. (64742-88-7)		
LD50 oral rat	> 5000 mg/kg bodyweight (Equivalent or similar to OECD 420, Rat, Male / female, Experimental value, Oral)	
LD50 dermal rabbit	> 2000 mg/kg bodyweight (Equivalent or similar to OECD 402, 24 h, Rabbit, Male / female, Experimental value, Dermal)	
LC50 inhalation rat (mg/l)	> 5.28 mg/l air (Equivalent or similar to OECD 403, 4 h, Rat, Male / female, Experimental value, Inhalation (vapours))	

LOW BOILING POINT HYDROGEN TREATED NAPHTHA - NAPHTHA (PETROLEUM), HYDROTREATED HEAVY (64742-48-9)	
LD50 oral rat	> 15000 mg/kg (Rat, Oral)

01/10/2020 EN (English) 4/8

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

bedraing to rederal register / vol. //, rvc. 50/	Monday, March 20, 2012 / Nules and Negulations		
LOW BOILING POINT HYDROGEN TI	LOW BOILING POINT HYDROGEN TREATED NAPHTHA - NAPHTHA (PETROLEUM), HYDROTREATED HEAVY (64742-48-9)		
LD50 dermal rabbit	> 3160 mg/kg (Rabbit, Dermal)		
hydrocarbons, C11-C14, n-alkanes, i	soalkanes, cyclics, < 2% aromatics (64742-47-8)		
LD50 dermal rabbit	> 5000 mg/kg bodyweight (Rabbit, Literature, Dermal)		
Skin corrosion/irritation	: Not classified		
	pH: Not applicable.		
Serious eye damage/irritation	: Not classified		
	pH: Not applicable.		
Respiratory or skin sensitisation	: Not classified		
Germ cell mutagenicity	: Not classified		
Carcinogenicity	: Not classified		
Reproductive toxicity	: Not classified		
STOT-single exposure	: Not classified		

STOT-repeated exposure : Causes damage to organs through prolonged or repeated exposure.

STRAIGHT RUN KEROSINE - SOLVENT NAPHTHA (PETROLEUM), MEDIUM ALIPH. (64742-88-7)		
STOT-repeated exposure	Causes damage to organs through prolonged or repeated exposure.	
4	: Not classified : 19 – 24 mm²/s	
, ,	Inhalation may cause irritation (cough, short breathing, difficulty in breathing).irritation (itching, redness, blistering).redness, itching, tears.	

Symptoms/effects after ingestion : Burns or irritation of the linings of the mouth, throat, and gastrointestinal tract.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms nor to cause long-term adverse

effects in the environment.

LOW BOILING POINT HYDROGEN TREATED NAPHTHA - NAPHTHA (PETROLEUM), HYDROTREATED HEAVY (64742-48-9)		
LC50 fish 1	2200 mg/l (96 h, Pimephales promelas, Fresh water)	
hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics (64742-47-8)		
LC50 fish 1	> 100 mg/l (Pisces)	
EC50 Daphnia 1	> 100 mg/l (Invertebrata)	

12.2. Persistence and degradability

STRAIGHT RUN KEROSINE - SOLVENT NAPHTHA (PETROLEUM), MEDIUM ALIPH. (64742-88-7)		
Persistence and degradability	Readily biodegradable in water.	
LOW BOILING POINT HYDROGEN TREATED NAPHTHA - NAPHTHA (PETROLEUM), HYDROTREATED HEAVY (64742-48-9)		
Persistence and degradability	Not readily biodegradable in water.	
hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics (64742-47-8)		
Persistence and degradability	Readily biodegradable in water.	

12.3. Bioaccumulative potential

STRAIGHT RUN KEROSINE - SOLVENT NAPHTHA (PETROLEUM), MEDIUM ALIPH. (64742-88-7)		
Bioaccumulative potential	No bioaccumulation data available.	
LOW BOILING POINT HYDROGEN TREATED NAPHTHA - NAPHTHA (PETROLEUM), HYDROTREATED HEAVY (64742-48-9)		
Partition coefficient n-octanol/water (Log Pow)	2.1 – 6.5 (Calculated)	
hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics (64742-47-8)		
Partition coefficient n-octanol/water (Log Pow)	6 – 8.2	
Bioaccumulative potential	High potential for bioaccumulation (Log Kow > 5).	

01/10/2020 EN (English) 5/8

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

12.4. Mobility in soil

STRAIGHT RUN KEROSINE - SOLVENT NAPHTHA (PETROLEUM), MEDIUM ALIPH. (64742-88-7)		
Ecology - soil	Adsorbs into the soil.	
hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics (64742-47-8)		
Surface tension	0.026 N/m (20 °C)	
Ecology - soil	Adsorbs into the soil.	

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Transport document description : UN1950 Aerosols, 2.1

UN-No.(DOT) : UN1950
Proper Shipping Name (DOT) : Aerosols

Class (DOT) : 2.1 - Class 2.1 - Flammable gas 49 CFR 173.115

Hazard labels (DOT) : 2.1 - Flammable gas



DOT Packaging Non Bulk (49 CFR 173.xxx) : None DOT Packaging Bulk (49 CFR 173.xxx) : None

DOT Special Provisions (49 CFR 172.102) : N82 - See 173.306 of this subchapter for classification criteria for flammable aerosols.

DOT Packaging Exceptions (49 CFR 173.xxx) : 306 DOT Quantity Limitations Passenger aircraft/rail : 75 kg

(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 150 kg

CFR 175.75)

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a

passenger vessel.

DOT Vessel Stowage Other : 25 - Protected from sources of heat,87 - Stow "separated from" Class 1 (explosives) except

Division 14,126 - Segregation same as for Class 9, miscellaneous hazardous materials

Emergency Response Guide (ERG) Number : 12

Other information : No supplementary information available.

Transportation of Dangerous Goods

Transport document description : UN 1950, 2.1 UN-No. (TDG) : UN 1950

TDG Primary Hazard Classes : 2.1 - Class 2.1 - Flammable Gas.

Transport by sea

Transport document description (IMDG) : UN 1950 AEROSOLS, 2.1

UN-No. (IMDG) : 1950
Proper Shipping Name (IMDG) : AEROSOLS
Class (IMDG) : 2 - Gases

01/10/2020 EN (English) 6/8

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Air transport

Transport document description (IATA) : UN 1950 Aerosols, flammable, 2.1

UN-No. (IATA) : 1950

Proper Shipping Name (IATA) : Aerosols, flammable

Class (IATA) : 2

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

15.2. International regulations

CANADA

STRAIGHT RUN KEROSINE - SOLVENT NAPHTHA (PETROLEUM), MEDIUM ALIPH. (64742-88-7)

Listed on the Canadian DSL (Domestic Substances List)

LOW BOILING POINT HYDROGEN TREATED NAPHTHA - NAPHTHA (PETROLEUM), HYDROTREATED HEAVY (64742-48-9)

Listed on the Canadian DSL (Domestic Substances List)

hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics (64742-47-8)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

National regulations

COR-BAN 23 AEROSOL

One or all of the ingredients in this product are listed on the (AICS) Inventory list

15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date : 02/21/2019

Full text of H-statements:

H223	Flammable aerosol.
H226	Flammable liquid and vapour.
H227	Combustible liquid
H304	May be fatal if swallowed and enters airways.
H372	Causes damage to organs through prolonged or repeated exposure.

01/10/2020 EN (English) 7/8

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Hazard Rating

Health : 2 Moderate Hazard - Temporary or minor injury may occur

Flammability : 2 Moderate Hazard - Materials which must be moderately heated or exposed to high ambient

temperatures before ignition will occur. Includes liquids having a flash point at or above 100 F

but below 200 F. (Classes II & IIIA)

Physical : 1 Slight Hazard - Materials that are normally stable but can become unstable (self-react) at high

temperatures and pressures. Materials may react non-violently with water or undergo

hazardous polymerization in the absence of inhibitors.

Personal protection : G

G - Safety glasses, Gloves, Vapor respirator

SDS US (GHS HazCom 2012)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

01/10/2020 EN (English) 8/8