Section: 1 CHEMICAL PRODUCT AND COMPANY INFORMATION

Product Name: Sur Prep 3160 **For Additional Product** 1 (800) 648-2661

Information:

Chemical Family: Solvent Cleaner

Manufacturer: **Zip-Chem Products** In Emergency: 1 (800) 424-9300

400 Jarvis Drive Morgan Hill, CA 95037

Section: 2 COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

FOR EXPOSURE LIMITS SEE SECTION 8 FOR OTHER TOXICOLOGICAL INFORMATION SEE SECTION 11

HAZARDOUS INGREDIENTS

Descriptive Name	CAS Number	Percentage Range	Hazard Type per CFR 1910.1200	Exposure Limits	LD ₅₀	LC ₅₀	NTP, IARC, Or OSHA Carcinogen
Stoddard Solvent	8052-41-3	100	Combustible	OSHA: 500 ppm	Not Determined	Not Determined	No
Light Hydrotreated Distillate (Petroleum)	64742-47-8	100	Combustible	OSHA: 500 ppm	Not Determined	Not Determined	No
C10 Alkanes and Isoparaffins	Mixture	40-60%	Combustible	OSHA: 500 ppm	Not Determined	Not Determined	No
C11 Alkanes and Isoparaffins	Mixture	10-30%	Combustible	OSHA: 500 ppm	Not Determined	Not Determined	No
C9 Naphthenes	Mixture	10-15%	Combustible	None Given	Not Determined	Not Determined	No
Nonane, all isomers	Mixture	1-10%	Combustible	ACGIH: 200 ppm	Not Determined	Not Determined	No
C12 Alkanes and Isoparaffins	Mixture	0-5%	Combustible	None Given	Not Determined	Not Determined	No

Section: 3 HAZARDS IDENTIFICATION

PHYSICAL HAZARDS:

ACUTE HEALTH EFFECTS: Breathing high concentrations may be harmful. Mist or vapor can irritate the throat and lungs. Breathing this material may cause central nervous

> system depression with symptoms including nausea, headache, dizziness, fatigue, drowsiness, or unconsciousness. Breathing high concentrations of this material, for example, in an enclosed space or by intentional abuse, can cause irregular heartbeats which can cause death.

CHRONIC HEALTH EFFECTS: Chronic effects of ingestion and subsequent aspiration into the lungs may cause pneumatocele (lung cavity) formation and chronic lung dysfunction.

> Reports have associated repeated and prolonged occupational overexposure to solvents with irreversible brain and nervous system damage (sometimes referred to as "Solvent or Painter's Syndrome"). Intentional misuse by deliberately concentrating and inhaling this product

may be harmful or fatal.

Zip-Chem Products Sur Prep 3160

Material Safety Data Sheet

HMIS RATINGS:

Health: 1
Flammability: 2
Reactivity: 0
Protective Equipment: E

Section: 4 FIRST AID MEASURES

EYES: May be an eye irritant. Flush immediately with water for 15 minutes and take to physician.

SKIN: Wash affected area and consult a physician if irritation persists.

INGESTION: Call a physician and/or transport to emergency facility immediately. Do not induce vomiting

so as to avoid aspiration of material into the lungs.

INHALATION: Remove from exposure and restore breathing. Seek medical attention.

Section: 5 FIRE AND EXPLOSION HAZARDS

FLAMMABILITY DATA:

FLAMMABLE/COMBUSTIBLE/PYROPHORIC: Combustible

FLASH POINT AND METHOD: 145°F PMCC

AUTOIGNITION TEMPERATURE: Not established

FLAMMABLE LIMITS AT NORMAL TEMPERATURE AND PRESSURE (PERCENT VOLUME IN AIR):

LEL: 0.8% UEL: 6%

EXPLOSION DATA:

SENSITIVITY TO MECHANICAL IMPACT: Not Sensitive SENSITIVITY TO STATIC DISCHARGE: Not Sensitive

EXTINGUISHING MEDIA: Foam, Alcohol Foam, CO2, Dry Chemical, Water Fog

FIRE FIGHTING TECHNIQUES AND COMMENTS: Use standard firefighting techniques to fight fires

involving this material

HAZARDOUS COMBUSTION PRODUCTS: Carbon dioxide, carbon monoxide, smoke, fumes, and/or

unburned hydrocarbons.

Section: 6 ACCIDENTAL SPILL/RELEASE INFORMATION

FOR ALL TRANSPORTATION ACCIDENTS CALL CHEMTREC AT 1-800-424-9300.

REPORTABLE QUANTITY: Not Applicable

SPILL MITIGATION PROCEDURES:

Stop source of spill as soon as possible and notify appropriate personnel. Burm around spill area to prevent spill from spreading. Ventilate area. Do not flush into sewers.

AIR RELEASE:

Vapors may be suppressed by use of water fog or spray. Contain all liquid for treatment or neutralization.

WATER RELEASE:

Contain liquid for treatment.

LAND SPILL:

Create a trench to contain materials. Spilled materials may be contained using sand, clay, earth or a commercial absorbent. Do not place materials back in their original container.

SPILL RESIDUES:

Dispose of per guidelines under section 13, DISPOSAL CONSIDERATIONS.

PERSONNEL PROTECTION FOR EMERGENCY SPILL AND FIRE FIGHTING SITUATIONS:

Additional protective clothing must be worn to prevent personal contact with this material. Those items include but are not limited to gloves, apron, and safety glasses.

Section: 7 HANDLING AND STORAGE

DO NOT TAKE INTERNALLY. AVOID CONTACT WITH EYES AND CLOTHING. UPON CONTACT WITH SKIN OR EYES WASH OFF WITH WATER.

STORAGE CONDITIONS:

Store in a cool, dry, well-ventilated place.

STORE AT TEMPERATURES BELOW 120°F. DO NOT STORE OR USE NEAR HEAT, SPARKS, OR FLAMES. AVOID BREATHING VAPORS. VAPORS ARE HEAVIER THAN AIR AND WILL COLLECT IN LOW AREAS AND OTHER CONFINED AREAS.

PRODUCT STABILITY AND COMPATIBILITY:

SHELF LIFE LIMITATIONS: 36 months from date of shipment

INCOMPATIBLE MATERIALS FOR STORAGE OR TRANSPORT: None known.

INCOMPATIBLE MATERIALS FOR PACKAGING: N/A

Section: 8 PREVENTIVE MEASURES

PERSONAL PROTECTION FOR ROUTINE USE OF THIS PRODUCT:

RESPIRATORY PROTECTION: Breathing apparatus recommended only if necessary area used for application deems it necessary. Refer to NIOSH publication No. 89-105 and NIOSH No. 87-116. See OSHA requirement under 29 CFR 1910.1025 and 29 CFR 1910.134.

SKIN AND EYE PROTECTIVE EQUIPMENT: Impervious gloves are recommended to prevent skin contact. Safety glasses to prevent eye contact are recommended.

ENGINEERING CONTROLS

VENTILATION: Local or mechanical to keep Section II ingredients below their exposure limits.

EQUIPMENT SPECIFICATIONS (WHEN APPLICABLE):

RESPIRATOR TYPE: None required

PROTECTIVE CLOTHING TYPE: (This includes: gloves, boots, apron, protective suit):

Impervious gloves, safety glasses

WASTE DISPOSAL:

Spilled material collected in absorbent material should be transferred to steel disposal or recovery drums. If this product becomes a waste, it DOES NOT meet the criteria of a hazardous waste as defined under 40 CFR 261, in that it does not exhibit the characteristics of hazardous waste under Subpart D. If this product becomes a waste, it should be disposed of in accordance with local, state and federal regulations by incineration.

Zip-Chem Products

Sur Prep 3160 Material Safety Data Sheet

Section: 9 PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE(gas, liquid, solid): Liquid

APPEARANCE: Clear and colorless

ODOR: Solvent odor

FREEZING POINT: Not Determined

BOILING RANGE: 192° C- 205° C (378° F- 401° F)
DECOMPOSITION TEMPERATURE: Not Determined

SPECIFIC GRAVITY (H20=1): 0.8 BULK DENSITY: 6.7 lbs/gal @ 70 Deg F

pH @ 25 Deg C: Not Applicable

VAPOR PRESSURE @ 20 Deg C: 0.5 mm Hg SOLUBILITY IN WATER: Slightly solube (<0.1%) VOLATILES, PERCENT BY WEIGHT: 100%

EVAPORATION RATE: <0.1 (n-Butyl acetate = 1.0)

VAPOR DENSITY: Heavier than air

VOLATILE ORGANIC COMPOUND (VOC) G/L: 794 g/l

Section: 10 STABILITY AND REACTIVITY DATA

CONDITIONS UNDER WHICH THIS PRODUCT MAY BE UNSTABLE:

MECHANICAL SHOCK OR IMPACT: No ELECTRICAL (STATIC) DISCHARGE: No

HAZARDOUS POLYMÉRIZATION: Will Not Occur

INCOMPATIBLE MATERIALS: Strong acids, alkalies, and oxidizers (liquid chlorine and oxygen).

CONDITIONS OF REACTIVITY: None known

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon dioxide, carbon monoxide, smoke,

fumes, and/or unburned hydrocarbons.

Section: 11 TOXICOLOGICAL PROPERTIES

ROUTES OF ABSORPTION

Skin contact. Inhalation.

WARNING STATEMENTS AND WARNING PROPERTIES:

DO NOT TAKE INTERNALLY.

SIGNS, SYMPTOMS AND EFFECTS OF EXPOSURE

INHALATION

ACUTE: Breathing high concentrations may be harmful. Mist or vapor can irritate the throat and lungs.

Breathing this material may cause central nervous system depression with symptoms including nausea, headache, dizziness, fatique, drowsiness, or unconsciousness.

CHRONIC: Breathing high concentrations of this material, for example, in an enclosed space or by intentional abuse, can cause irregular heartbeats which can cause death...

SKIN

ACUTE: This product can cause mild, transient skin irritation with short-term exposure.

CHRONIC: Repeated or prolonged skin contact can produce moderate irritation (dermatitis).

EYE

This product can cause transient mild eye irritation with short-term contact with liquid sprays or mists. Symptoms include stinging, watering, redness, and swelling.

INGESTION

If swallowed, this material may irritate the mucous membranes of the mouth, throat, and esophagus. It can be readily absorbed by the stomach and intestinal tract. Symptoms include a burning sensation of the mouth and esophagus, nausea, vomiting, dizziness, staggering gait, drowsiness, loss of consciousness, and delirium, as well as additional central nervous system (CNS) effects. Due to its light viscosity, there is a danger of aspiration into the lungs during vomiting. Aspiration can result in severe lung damage or death.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: Disorders of the following organs or organ systems that may be aggravated by significant exposure to this material or its components include: Skin, Respiratory System, Liver, Kidneys, Central Nervous System (CNS)

INTERACTIONS WITH OTHER CHEMICALS THAT ENHANCE TOXICITY: None known TARGET ORGAN TOXICITY: May cause damage to the following organs: kidneys, lungs, liver, mucous membranes, upper respiratory tract, skin, central nervous system (CNS), eye, lens or cornea. REPRODUCTIVE AND DEVELOPMENTAL TOXICITY: There are no known or reported effects on

reproductive function or fetal development.

CARCINOGENICITY: NTP? NO IARC MONOGRAPHS? NO OSHA REGULATED? NO

MUTAGENICITY: This product is not known to be mutagenic.

EXPOSURE LIMITS: Not Determined

Section: 12 ECOLOGICAL INFORMATION

AQUATIC TOXICITY:

This mixture will normally float on water with its lighter components evaporating rapidly. In stagnant or slow-flowing waterways, a hydrocarbon layer can cover a large surface area. As a result, this covering layer might limit or eliminate natural atmospheric oxygen transport into the water. With time, if not removed, oxygen depletion in the waterway might be enough to cause a fish kill or create an anaerobic environment. This coating action can also be harmful or fatal to plankton, algae, aquatic life, and water birds.

Section: 13 DISPOSAL CONSIDERATIONS

Spilled material collected in absorbent material should be transferred to steel disposal or recovery drums.

If this product becomes a waste, it DOES NOT meet the criteria of a hazardous waste as defined under 40 CFR 261, in that it does not exhibit the characteristics of hazardous waste under Subpart D. If this product becomes a waste, it should be disposed of in accordance with local, state and federal regulations by incineration.

Section: 14 TRANSPORT INFORMATION

DOT SHIPPING NAME: D.O.T. Non-Regulated (Solvent Cleaner)

UN Number: None DOT HAZARD CLASS: None DOT PACKING GROUP: None

DOT REPORTABLE QUANTITY: None found in 49 CFR 172.101

Section: 15 REGULATORY INFORMATION

All components of this product are listed on the following inventories: MITI (Japan) EINECS (EEC) DSL (Canada).

FEDERAL

TOXIC SUBSTANCES CONTROL ACT (TSCA):

The components of this product are listed on the TSCA inventory.

SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT TITLE III (SARA):

Section 302/304

Requires emergency planning based on 'Threshold Planning Quantities' (TPQs), and release reporting based on Reportable Quantities (RQs) of 'Extremely Hazardous Substances' (EHS) listed in Appendix A of 40 CFR 355. There are no components of this material with known CAS numbers that are on the EHS list.

Section 311 & 312

The Superfund Amendments and Reauthorization Act of 1986 (SARA) Title III requires facilities subject to this subpart to submit aggregate information on chemicals by "Hazard Category" as defined in 40 CFR 370.2. This material would be classified under the following hazard categories:

Fire, Acute (Immediate) Health Hazard, Chronic (Delayed) Health Hazard

Section 313

This material does not contain chemicals with known CAS numbers subject to the reporting requirements of SARA Title III, Section 313 and 40 CFR 372.

Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA)

This material does not contain chemical(s) with known CAS numbers classified as hazardous substances subject to the reporting requirements of CERCLA (40 CFR 302) and to the release reporting requirements of SARA (Section 302) based on reportable quantities (RQs):

OSHA Regulations

'Chemical-specific' U. S. Occupational Safety and Health Administration (OSHA) regulations (1910.1002 to 1910.1050) presented under 29 CFR 1910 do not apply to this material or its components.

Other EPA Regulations

No additional information available.

State

California Safe Drinking Water and Toxic Enforcement Act of 1988- Proposition 65

This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins under California Proposition 65 at levels that would be subject to the proposition

California South Coast Air Quality Management District (SCAQMD) Rule 443.1 (VOC's)

A Volatile Organic Compound (VOC) is any volatile compound of carbon excluding methane, carbon monoxide, carbonic acid, metallic carbides or carbonates, ammonium carbonate, 1,1,1-trichloroethane, methylene chloride, FC-23, CFC-113, CFC-12, CFC-11, CFC-22, CFC-114, and CFC-115. By this definition, this is a VOC material.

Section: 16 PREPARATION INFORMATION

REVISION INFORMATION: Added additional CAS references for product

PREPARED BY: J Smith APPROVAL DATE: 4/9/07 SUPERSEDES: 2/5/07

This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of Zip-Chem Products Company. The data in this sheet is related only to the specific material designated herein. Zip-Chem Products Company assumes no legal responsibility for use or reliance upon these data.